Subjective Evaluation of Text-to-Speech Models: Comparing Absolute Category Rating and Ranking by Elimination Tests

Abstract

Modern text-to-speech (TTS) models are typically subjectively evaluated using an Absolute Category Rating (ACR) method. This method uses the mean opinion score to rate each model under test. However, if the models are perceptually too similar, a single stimulus test may not provide a valid differentiation. Pairwise comparison tests offer a more precise comparison but take more time as the number of tests increases exponentially with the number of models. Alternatively, a ranking-by-elimination (RBE) test can be used to assess multiple models. In a controlled experiment, we compared the ACR and RBE tests and found that the obtained results were similar even in the presence of perceptually close TTS models.

1. Introduction

Many modern text-to-speech (TTS) synthesis models [1, 2, 3] achieve nearly natural quality speech. This naturalness in quality is typically measured through subjective Absolute Category Rating (ACR) tests, which provides a Mean Opinion Score (MOS) per model. Cooper et al. [4] reported that the best five neural TTS models all had comparable quality in a newly conducted ACR test. This implies that there is a need to conduct subjective tests which can differentiate between the quality of such TTS models.

In a ACR test, the conditions to be evaluated are presented one after the other. This has the disadvantage that the listener cannot go back and forth between the conditions to evaluate them. The multiple stimuli with hidden reference and anchor (MUSHRA) test [5] avoids this issue by presenting multiple conditions at the same time to the listener, e.g., [6]. Such a test is difficult to conduct in a TTS scenario since the 3.5 kHz or 7 kHz anchor signals used typically in such tests may not qualify as good anchor signals, e.g., [7]. The duration of the utterances and their prosody varies across synthesis models, and hence not suited for a MUSHRA test. Also, it might not be possible to use ground truth signal references. Further, [8] found that MUSHRA and MOS scores were comparable, but the difference between the conditions was clearer in MUSHRA.

Wester et al. [9] reported that at least 30 listeners and 150 total judgments per MOS value are required for reliable results with the ACR test. It would be interesting to know if there is an objective test that can show reliable results with less number of listeners.

Pairwise comparison tests have also been used for subjective evaluation with TTS. The number of pairwise comparisons increases exponentially with the number of conditions to be tested, thereby increasing the time and costs required for such an evaluation. In the audio coding community, ranking-by-elimination (RBE) has been used with success for evaluation across multiple conditions in place of pairwise comparison. Wickelmaier et al. [10] compared the pairwise comparison test to the RBE test for audio codec evaluation. They showed that the results of pairwise comparison and the RBE test were comparable, but the RBE test was a lot faster. As an example, the RBE test took 50 seconds in their evaluation of a castanets file, whereas the pairwise comparison took 300 seconds.

In the current work, we compare the RBE test to the ACR test for speech synthesis evaluation. We simulate synthesis models with outputs at different perceptual qualities using the intermediate training checkpoints of a ForwardTacotron [3] model. Typically the quality of the model output improves progressively with training, which means that the expected quality changes are known. e.g., we know that the model trained for five epochs is worse than the model trained for 30 epochs. Since we are comparing evaluation methods, this prior knowledge is beneficial. In this approach, it would be easy to identify training checkpoints such that the quality of synthesis is similar, yet different. We further show that the ACR test and the RBE test can both be employed reliably to evaluate TTS models even when the model outputs are perceptually very hard to distinguish. Both tests require a similar number of ratings for reliability. There are multiple open-source software tools available for subjective testing of audio like WebMUSHRA [11] and Hulti-Gen-v2 [12], but they do not support RBE test. Hence we also implemented code to perform the RBE test as an extension to the WebMUSHRA software.

2. Evaluation Methods Under Test

2.1. Absolute category rating test

Typically subjective listening tests for evaluation of TTS models are done through absolute category rating tests. The mean of the rated categories across the obtained ratings is then reported as the MOS following the ITU-P.808 recommendation [13]. A five-point category-judgment scale is used for this purpose. Each of the test sentences should be synthesized using all models under test and presented one after the other in a randomized order. The sentences used in the test should also be presented at random to the listener. The listener is expected to rate the presented sample using the ACR scale. The test can, for example, be conducted using the WebMUSHRA [11] software with a Likert-single-stimulus scale.

The ACR test consists of training and test parts, which are expected to be performed consecutively. Both parts are to be conducted in the same way, but the training ratings are not included in the overall score. During the training, the listeners are expected to familiarize themselves with the test setup and are introduced to the typical artifacts present in the conditions. Further, the listeners are asked to use good-quality headphones

Figure 1: *The ranking-by-elimination test screen for one sentence. The eliminated conditions are hidden, with the order of their elimination visible as their ranks. Lower rank indicates eliminated earlier, with lower quality.*

and not change the volume once the test part begins.

The resultant ratings across all the listeners and conditions are averaged, and the confidence intervals are calculated. Further, the Wilcoxon-signed-rank tests are used to evaluate the statistical significance.

2.2. Ranking-by-elimination test

The RBE test is a multi-stimulus test, wherein the test sentence synthesized through each of the models under test is presented at the same time to the listener [10]. The conditions are hidden and randomized. The listener can listen to each of the test conditions as many times as desired. The listener is asked to sequentially eliminate the worst of the available conditions. Only the sample being heard can be eliminated. Once a sample is eliminated, its rank is displayed on the screen. The elimination of the conditions can be stopped if the remaining conditions are perceptually similar. This results in such remaining conditions having the same rank. A screenshot of the RBE test implemented by us is shown in Fig. 1. Our modification to the WebMUSHRA implementing this RBE test will be made public at *link* [1].

Statistical analysis on the generated rankings can be done through the Plackett-Luce model [14]. This model produces a worth value for the conditions on a logarithmic scale, which can then be compared. Further, the Plackett-Luce model also provides the p-values indicating the statistical significance of the difference between the conditions.

3. Controlled Test Conditions

3.1. Text-to-Speech Model

We used ForwardTacotron [3] with the StyleMelGAN vocoder [15] as the TTS model under test. This low-complexity TTS model can achieve state-of-the-art performance at faster than real-time inference speeds [16].

---

[1]Hidden for double-blind review.

ForwardTacotron is a single-pass non-autoregressive model built with a combination of feedforward networks, gated recurrent units, and long short-term memory networks [16]. This model predicts mel-spectrogram frames from the corresponding input phoneme sequence. Further, a duration predictor predicts the duration of individual phonemes to which the length regulator resamples the predicted mel-spectrogram frames. Finally, the mel-spectrogram frames are transformed into audio frames using StyleMelGAN, which is a generative adversarial network-based neural vocoder built using temporal adaptive denormalization blocks.

3.2. Test Sentences and Preliminary Objective Evaluation

It is commonly assumed that single stimulus tests, such as the ACR test, do not work well when the conditions under test are perceptually very close. To investigate this, we performed both subjective evaluations with the following two test sets:

1. Perceptually Distinguishable Set (PDS): Here, all the conditions being evaluated are clearly perceptually distinct from each other.

2. Perceptually Indistinguishable Set (PIS): There is at least one condition that is perceptually very close to the best condition in informal listening.

To simulate the TTS models with varying degrees of perceptual quality, we used a single-speaker training of the ForwardTacotron model at various stages of training. We used the LJ Speech [17] as the dataset for training the ForwardTacotron model. Here, Chapter 50 was reserved for testing, with the remaining 49 chapters used for training. Out of the training chapters, 10 samples at random were left for validation. Due to the small validation subset, the training loss was used as an indicator to select the checkpoints for the subjective analysis.

The output was intelligible at low quality, starting at 5K iterations of training with a batch size of 32. The model after 5K iterations was consequently used as our starting point. The last checkpoint of training at 500K iterations was chosen as the best model. We further chose checkpoints where the synthe-

Table 1: *Training losses at each of the selected checkpoints with MCD-DTW, MSD-DTW, and f0RMSE-DTW in relation to the 500K step trained model. Only the mean of the objective metrics over 40 Harvard sentences is shown.*

Training checkpoint (K iterations)	Training Loss ($\downarrow$)	MCD-DTW ($\downarrow$)	MSD-DTW ($\downarrow$)	f0RMSE-DTW ($\downarrow$)
5	1.382	17.84	32.20	238.87
25	1.088	15.60	27.96	209.68
50	0.960	14.40	26.16	198.01
140	0.930	11.79	21.42	167.49
500	0.725	–	–	–

sis outputs were perceptually different from one another. We verified that chosen iterations produced perceptually different quality speech using the objective metrics of mel-cepstral distortion (MCD), mel-spectrogram distortion (MSD), and f0 root mean square error (f0RMSE). The objective metrics indicated to us that these could be different from one another. Further, we verified that there are easily perceptible differences between the outputs at the chosen training iterations through informal listening.

As multiple definitions for the objective metrics exist in the literature, we present those used in our study here for completeness. The MCD was computed using [18]

$$\text{MCD}_{XY} = \frac{1}{N} \sum_{n=1}^{N} \sqrt{\sum_{k=1}^{K} (\text{MC}_X(k,n) - \text{MC}_Y(k,n))^2}, \quad (1)$$

where $\text{MC}_X(k,n)$ and $\text{MC}_Y(k,n)$ represent the k-th cepstral coefficient in n-th time frame for the file X and Y, respectively. The mel-cepstral values were in decibels (dB). The MSD was computed using

$$\text{MSD}_{XY} = \frac{1}{N} \sum_{n=1}^{N} \sqrt{\sum_{k=1}^{K} (\text{MS}_X(k,n) - \text{MS}_Y(k,n))^2}, \quad (2)$$

where $\text{MS}_X(k,n)$ and $\text{MS}_Y(k,n)$ represent the k-th spectral coefficient in n-th frame for the files X and Y respectively. We converted the spectral coefficients to the decibel (dB) scale before using them in this formula to get the MSD values in dB. Finally, the f0RMSE was computed using [19]

$$\text{f0RMSE}_{XY}$$
$$= 1200 \sqrt{\frac{1}{N} \sum_{n=1}^{N} (\log_2(F_X(n)) - \log_2(F_Y(n)))^2}, \quad (3)$$

where F_X and F_Y represent the f0 values for the file X and Y, respectively . The resulting f0RMSE is given in cents.

We used our best model, the model trained up to 500K iterations, as our reference model for the calculation of the objective metrics. Since the durations of the synthesized samples vary across checkpoints, we used dynamic time warping (DTW) to align the samples. The DTW cost for the MCD-DTW and MSD-DTW was the mel-cepstral and mel-spectral distance, respectively. To calculate the f0RMSE-DTW, we aligned time frames across files by finding the minimum MCD cost path between them. This allowed us to calculate the squared f0 error across all the frames even though meaningful f0 values existed only for the frames consisting of voiced phonemes. The f0 values for f0RMSE were measured using the SWIPE algorithm

Table 2: *Age and gender distribution across the different tests.*

Test	Average age (y)	Males	Females
PDS-ACR	31.8	9	7
PDS-RBE	31.4	11	5
PIS-ACR	29.3	11	5
PIS-RBE	31.5	13	3

from libf0 [20]. These values were used in f0RMSE calculation only if the prediction confidence for each of the corresponding frames was greater than 0.4.

We used the training checkpoints starting from barely intelligible (after 5K training iterations at a batch size of 32) to close to the best possible quality (after 140K training iterations). The selected checkpoints, their training losses, and the objective metrics are shown in Table 1. Here the objective metrics are averaged over the first 4 lists of Harvard sentences consisting of 40 sentences [21].

4. Results and Discussion

We conducted the subjective tests using 40 sentences from the first 4 Harvard sets with 16 listeners each. We limited each listener to listen to 20 sentences per condition. In total, we had 320 ratings per condition. We used the WebMUSHRA software for this purpose and used listeners from the lab not connected to the project. The age and gender distribution of the listeners varied across tests, which are shown in Table 2. From the ACR test results, we calculated the average and 95% confidence interval, and checked if the conditions were statistically significantly different using the Wilcoxon-signed-rank test. From the RBE test results, we calculated the worth values using the Plackett-Luce library from R, which also provided the p-values for the determination of the statistical significance of the differences.

The results of the ACR test and the RBE test for both of our two test sets, PDS and PIS, are shown in Figs. 2 and 3, respectively. The order of the conditions as determined by both the tests were identical, as we can see from the results. Both tests across the two scenarios also showed that each pair of successive iterations (from the chosen ones) was statistically significantly different, the p-values are shown in Table 3.

If we look at the two tests done using ACR, the resultant intervals between the scores of consecutively selected checkpoints remain approximately the same for PDS and PIS. A similar conclusion can be drawn for the RBE results. Further, from the RBE test results, we note that the calculated worth values for the lower-quality iterations, i.e., 50K and lower, are always lower for the PDS than for the PIS. This indicates that it was

Figure 2: *MOS values with their confidence intervals across iterations for the perceptually distinguishable set (PDS) and perceptually indistinguishable set (PIS).*

Figure 3: *Worth values with their confidence intervals across iterations for the perceptually distinguishable set (PDS) and perceptually indistinguishable sets (PIS) measured with the RBE test. The Worth values for the 5K iterations are -10.6 ± 2.66 dB and -6.3 ± 0.96 dB, respectively, and hence outside the plot range.*

Figure 4: *Box plot showing the time taken for each of the tests across different subjective test sessions.*

Table 3: *p-values for statistical significance, with a value less than 0.05 indicating statistically significant differences.*

Checkpoints	ACR Test PDS	ACR Test PIS	RBE Test PDS	RBE Test PIS
500K vs 140K	-	1.7e-5	-	0.04
500K vs 50K	1.3e-9	-	2e-16	-
140K vs 50K	-	1.9e-8	-	1.6e-10
50K vs 25K	1.7e-18	1.3e-10	2e-16	1.5e-10
25K vs 5K	3.2e-54	1.3e-51	8.9e-6	2e-16

easier to eliminate the conditions for the PDS. Hence, more correct decisions in terms of quality were made when there was a clear perceptible difference between conditions.

All four tests showed that the used conditions were all statistically significantly distinct, as shown in Table 3. We also did a significance analysis using smaller subsets of the listeners for both tests. For the most difficult case of 140K vs 500K comparison, more than 12 listeners were required to get the significance values to be distinct for both tests. Hence, the RBE test also requires a similar number of participants as the ACR test for reliable results.

We also recorded the time taken by the listeners to perform the ratings, which are shown in Fig. 4. We can conclude that the RBE tests take more time than the ACR test, almost double in the median sense. Even so, the overall median time taken to rank the 5 conditions is 40s, which may be acceptable for usage. For the ACR test, the time taken does not depend on the test set, meaning the time required to rate each condition remains almost the same across both PDS and PIS scenarios. This is

expected since each of the samples are rated independently. But for the RBE test, the rating for the PIS takes more time than the PDS. This intuitively makes sense since the listener has to listen more carefully to the conditions when some of the conditions are perceptually very close.

We conducted additional tests where we used different checkpoints (150K and 200K) instead of the 140K checkpoint. Both the ACR and RBE tests showed that there were no significant differences between the best two checkpoints (i.e., 500K vs. 200K or 500K vs. 150K). While these results do not provide any new information, they support our finding that the RBE and ACR tests yield similar results.

5. Conclusion

We conducted a study to determine how well the ACR test can evaluate perceptually similar outputs from various TTS models. To do this, we used a multi-stimulus RBE test where progressively worse quality conditions are eliminated. The rankings were then analyzed using a Plackett-Luce model, which assigns a worth value to each condition and calculates the statistical significance. We also extended the WebMUSHRA framework to support the RBE test.

To simulate TTS models with different perceptual qualities, we used models from various iterations during the training of a single-speaker non-autoregressive ForwardTacotron model. We conducted subjective evaluations using ACR and RBE tests under distinct and indistinguishable conditions. Our results showed that ACR test results are comparable to RBE test results and that it was possible to differentiate between perceptually close models using both tests.

6. References

[1] J. Shen, R. Pang, R. J. Weiss, M. Schuster, N. Jaitly, Z. Yang, Z. Chen, Y. Zhang, Y. Wang, R. Ryan, R. A. Saurous, Y. Agiomyrgiannakis, and Y. Wu, "Natural TTS synthesis by conditioning WaveNet on mel spectrogram predictions," in *Proc. IEEE Intl. Conf. on Acoustics, Speech and Signal Processing (ICASSP)*, Calgary, Canada, 2018, pp. 4779–4783.

[2] Y. Ren, Y. Ruan, X. Tan, T. Qin, S. Zhao, Z. Zhao, and T. Liu, "FastSpeech: Fast, robust and controllable text to speech," in *Advances in Neural Information Processing Systems*, Vancouver, Canada, 2019, pp. 3165–3174.

[3] C. Schäfer, O. McCarthy, and contributors, "ForwardTacotron," https://github.com/as-ideas/ForwardTacotron, 2020.

[4] E. Cooper and J. Yamagishi, "How do Voices from Past Speech Synthesis Challenges Compare Today?" in *Proc. ISCA Speech Synthesis Workshp*, Budapest, Hungary, 2021, pp. 183–188.

[5] I. Rec, "Bs1534-3, method for the subjective assessment of intermediate quality level of audio systems," *ITU-T, Geneva*, 2015.

[6] J. Latorre, J. Lachowicz, J. Lorenzo-Trueba, T. Merritt, T. Drugman, S. Ronanki, and V. Klimkov, "Effect of data reduction on sequence-to-sequence neural tts," in *Proc. IEEE Intl. Conf. on Acoustics, Speech and Signal Processing (ICASSP)*, 2019, pp. 7075–7079.

[7] T. Merritt, B. Putrycz, A. Nadolski, T. Ye, D. Korzekwa, W. Dolecki, T. Drugman, V. Klimkov, A. Moinet, A. Breen, R. Kuklinski, N. Strom, and R. Barra-Chicote, "Comprehensive evaluation of statistical speech waveform synthesis," in *Proc. IEEE Spoken Language Technology Workshop*, 2018, pp. 325–331.

[8] M. S. Ribeiro, J. Yamagishi, and R. A. J. Clark, "A perceptual investigation of wavelet-based decomposition of f0 for text-to-speech synthesis," in *Proc. Interspeech*, Dresden, Germany, 2015, pp. 1586–1590.

[9] M. Wester, C. Valentini-Botinhao, and G. E. Henter, "Are we using enough listeners? no! — an empirically-supported critique of interspeech 2014 TTS evaluations," in *Proc. Interspeech*, Dresden, Germany, 2015, pp. 3476–3480.

[10] F. Wickelmaier, N. Umbach, K. Sering, and S. Choisel, "Comparing three methods for sound quality evaluation with respect to speed and accuracy." in *Proc. AES Audio Engineering Society Convention*, May 2009.

[11] M. Schoeffler, F.-R. Stöter, B. Edler, and J. Herre, "Towards the next generation of web-based experiments: A case study assessing basic audio quality following the ITU-R recommendation BS.1534 (MUSHRA)," in *Proceedings of the Web Audio Conference*, Paris, France, January 2015.

[12] D. Johnson and contributors, "HultiGen-v2," https://github.com/APL-Huddersfield/HULTI-GENv2/, 2020.

[13] I. Rec, "P. 808, subjective evaluation of speech quality with a crowdsourcing approach," *ITU-T, Geneva*, 2018.

[14] R. Plackett, "The analysis of permutations," *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, vol. 24, no. 2, pp. 193–202, 1975.

[15] A. Mustafa, N. Pia, and G. Fuchs, "StyleMelGAN: An efficient high-fidelity adversarial vocoder with temporal adaptive normalization," in *Proc. IEEE Intl. Conf. on Acoustics, Speech and Signal Processing (ICASSP)*, Toronto, Canada, 2021, pp. 6034–6038.

[16] P. Govalkar, A. Mustafa, N. Pia, J. Bauer, M. Yurt, Y. Özer, and C. Dittmar, "A Lightweight Neural TTS System for High-quality German Speech Synthesis," in *Proc. ITG Conf. on Speech Communication*, 2021.

[17] K. Ito and L. Johnson, "The LJ speech dataset," https://keithito.com/LJ-Speech-Dataset/, 2017.

[18] R. Kubichek, "Mel-cepstral distance measure for objective speech quality assessment," in *Proc. IEEE Pacific Rim Conference on Communications Computers and Signal Processing*, 1993, pp. 125–128 vol.1.

[19] T. Hayashi, A. Tamamori, K. Kobayashi, K. Takeda, and T. Toda, "An investigation of multi-speaker training for wavenet vocoder," in *Proc. IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, 2017, pp. 712–718.

[20] S. Rosenzweig, S. Schwär, and M. Müller, "libf0: A python library for fundamental frequency estimation," in *Late Breaking Demos of the International Society for Music Information Retrieval Conference (ISMIR)*, 2022.

[21] E. Rothauser, W. Chapman *et al.*, "IEEE recommended practice for speech quality measurements," *IEEE Transactions on Audio and Electroacoustics*, vol. 17, 1969.