Familiarity-Based Open-Set Recognition Under Adversarial Attacks

Philip Enevoldsen,* Christian Gundersen,* Nico Lang, Serge Belongie, and Christian Igel†

Department of Computer Science, University of Copenhagen

Abstract

Open-set recognition (OSR), the identification of novel categories, can be a critical component when deploying classification models in real-world applications. Recent work has shown that familiarity-based scoring rules such as the Maximum Softmax Probability (MSP) or the Maximum Logit Score (MLS) are strong baselines when the closed-set accuracy is high. However, one of the potential weaknesses of familiarity-based OSR are adversarial attacks. Here, we present gradient-based adversarial attacks on familiarity scores for both types of attacks, False Familiarity and False Novelty attacks, and evaluate their effectiveness in informed and uninformed settings on TinyImageNet. Furthermore, we explore how novel and familiar samples react to adversarial attacks and formulate the adversarial reaction score as an alternative OSR scoring rule, which shows a high correlation with the MLS familiarity score.

1 Introduction

In many real-world applications of machine learning models, it is crucial to understand the models' limitations and the trustworthiness of their predictions in novel situations. Thus, we investigate open-set recognition (OSR) [1], which can be seen as a special case of out-of-distribution (OOD) detection [2], where the task is to identify novel categories at test time, which were not included in the training dataset. Recently, Vaze et al. [3] have demonstrated that the progress in OSR performance over the past years is not necessarily due to advancement in OSR approaches, but is correlated with improved performance on the closed-set categories, i.e. the classification of categories included in the training dataset. With this observation, simple baseline scoring rules such as the Maximum Softmax Probability (MSP) [4] and the Maximum Logit Score (MLS) [3, 5] are competitive and perform on par with— or even outperform—more dedicated approaches such as ARPL and ARPL+CS [6], OSRCI [7], and OpenHybrid [8]. At the same time, Dietterich & Guyer [9] have proposed the Familiarity Hypothesis, stating that such familiarity-based scoring rules

False Novelty Attack

False Familiarity Attack

Figure 1. Adversarial attacks on OSR familiarity scores. Considering novel categories as positives, the top box depicts a *false positive (FP)* attack that lowers the familiarity of the known category leading to a *false novelty*. In contrast, the bottom box indicates a *false negative (FN)* attack that increases the familiarity of a known category leading to a *missed novelty* or *false familiarity*.

identify novel categories by measuring the absence of familiar features instead of actively recognizing the presence of novel features. They investigated occlusions as one of the weaknesses of familiarity-based OSR, which can cause false novelty detections. Adversarial attacks pose another potential weakness to familiarity-based OSR, which we study in this work. Dietterich & Guyer [9] mention the risks of adversarial vulnerability in their outlook discussion:

> "By applying existing attack algorithms (e.g., the FGSM [10]), we predict that it will be very easy to raise the logit score of at least one class and thereby hide a novel class image from novelty detection. It may also be possible to depress the logit scores of enough classes to create false anomaly alarms."

In other words, this prediction states that it might be trivial to compute adversarial perturbations that

---

*Equal contribution.
†Corresponding author.

Proceedings of the 6th Northern Lights Deep Learning Conference (NLDL), PMLR 265, 2025.

amplify familiar features to cause a *false familiarity*, but it might be harder to hide (all) familiar features to yield a *false novelty* (See Fig. 1). While it has been shown that the OSR approach Open-Max [11] is vulnerable to adversarial attacks [12, 13], we study the vulnerability of familiarity-based OSR approaches to gradient-based adversarial white-box attacks (i.e., the model parameters are given).

A crucial difference to prior work studying adversarial robustness of OOD detection is that familiarity-based OSR approaches neither train on auxiliary OOD data (like e.g. [14, 15]), nor introduce an explicit category for the "openness" of the test data (e.g. [11]). Consequently, this requires different designs of adversarial objectives. Ultimately, using such perturbations for adversarial training may yield better robustness, but prior work relies on training with both perturbed closed-set and auxiliary OOD data [16].

Although we do not use the presented objectives for adversarial training in this work, we explore whether these adversarial attacks can be used to design an alternative OSR score. Liang et al. [17] found that OOD detection was enhanced by pre-processing inputs with an adversarial perturbation. We explore if this generalizes to the OSR setting and whether it can be used to develop new OSR methods. In summary, this paper aims to answer four main questions:

1. **False Familiarity vs. False Novelty:** What type of attack is more effective?

2. **Uninformed vs. informed attacks:** How can adversarial attacks profit from knowing the input type (i.e., closed-set or open-set sample)?

3. **FGSM vs. iterative attacks:** Is it worth exploring more flexible iterative attacks to improve upon the fast gradient sign method?

4. **OSR scores using adversarial attacks:** Can we use the reaction of adversarial perturbations as an OSR score to separate familiar and novel samples?

2 Methodology

2.1 Familiarity-based open-set recognition (OSR)

We consider an input space $\mathcal{X}$ and a set $\mathcal{F}$ of *familiar* categories, i.e. the closed-set. In closed-set recognition (CSR), the objective is to model the probability $p(y \mid \boldsymbol{x}, y \in \mathcal{F})$, where y is a label that is associated with the input $\boldsymbol{x} \in \mathcal{X}$. The model is trained on a training dataset $\mathcal{D}_{\text{train}} = \{(\boldsymbol{x}_i, \boldsymbol{y}_i)\}_{i=1}^N \subset \mathcal{X} \times \mathcal{F}$ and evaluated on a non-overlapping closed-set test set, $\mathcal{D}_{\text{test-csr}} = \{(\boldsymbol{x}_i, \boldsymbol{y}_i)\}_{i=1}^M \subset \mathcal{X} \times \mathcal{F}$ that contains the categories given at train time. We consider a deep neural network $f_{\boldsymbol{\theta}} : \mathcal{X} \to \mathbb{R}^{|\mathcal{F}|}$ parameterized by $\boldsymbol{\theta}$ for modelling $p(y \mid \boldsymbol{x}, y \in \mathcal{F})$. Here, $f_{\boldsymbol{\theta}}$ maps an input to a vector of logits that are normalized using the softmax function $\sigma : \mathbb{R}^{|\mathcal{F}|} \to (0, 1)^{|\mathcal{F}|}$ to obtain pseudo-probabilities for the familiar categories.

In open-set recognition (OSR) a set $\mathcal{N}$ of *novel* categories is additionally considered and a test set containing inputs from both novel and familiar classes is used to evaluate the OSR performance: $\mathcal{D}_{\text{test-osr}} = \{(\boldsymbol{x}_i, \boldsymbol{y}_i)\}_{i=1}^M \subset \mathcal{X} \times (\mathcal{F} \cup \mathcal{N})$. A balanced test set containing an equal number of familiar and novel samples is typically used to evaluate the OSR performance. To decide whether $y \in \mathcal{F}$, a familiarity score, $\mathcal{S}(y \in \mathcal{F} \mid \boldsymbol{x})$, is calculated and used to rank the test samples in $\mathcal{D}_{\text{test-osr}}$. Familiarity-based scoring rules include the *Maximum Softmax Probability (MSP)* score [4]

$$\mathcal{S}_{\text{MSP}}(y \in \mathcal{F} \mid \boldsymbol{x}) = \max_y \sigma(f_{\boldsymbol{\theta}}(\boldsymbol{x}))_y \qquad (1)$$

and the *Maximum Logit Score (MLS)* [3, 9]

$$\mathcal{S}_{\text{MLS}}(y \in \mathcal{F} \mid \boldsymbol{x}) = \max_y f_{\boldsymbol{\theta}}(\boldsymbol{x})_y, \qquad (2)$$

which has outperformed the MSP score in prior work [3]. For both scoring rules, high scores indicate familiar and low scores indicate novel categories.

2.2 Fast gradient sign method

A simple and effective method for generating adversarial inputs is the *Fast Gradient Sign Method* (FGSM) which was first described by [10]. The FGSM generates an adversarial input, $\boldsymbol{x}^{\text{adv}}$, using the following equation:

$$\boldsymbol{x}^{\text{adv}} = \boldsymbol{x} + \varepsilon \, \text{sign}[\nabla_{\boldsymbol{x}} \mathcal{L}(\boldsymbol{\theta}, \boldsymbol{x}, y)] \qquad (3)$$

Here $\boldsymbol{x}$ represents the unmodified input and the second term is known as the *adversarial perturbation*, where ε controls the magnitude of the perturbation (as visualized in Fig. 2). Initially, $\mathcal{L}$ is set to the training objective [10], but can be any objective function that an adversary aims to optimize. The adversarial perturbation is constrained such that $\|\boldsymbol{x}^{\text{adv}} - \boldsymbol{x}\|_\infty \le \varepsilon$.

Figure 2. Qualitative example. Perturbed images (top) and adversarial perturbations (bottom).

2.3 Iterative attacks

Iterative approaches can generate more diverse perturbations compared to the FGSM by optimizing the objective function in a more flexible manner but at higher computational costs. An iterative adversarial attack takes the general form

$$x_{n+1}^{\text{adv}} = \text{Clip}_{\boldsymbol{x},\varepsilon}\{x_n^{\text{adv}} + \text{Step}(\mathcal{L}, \boldsymbol{\theta}, x_n^{\text{adv}}, y)\} \ , \quad (4)$$

starting from $x_0^{\text{adv}} = \boldsymbol{x}$, where $\text{Clip}_{\boldsymbol{x},\varepsilon}(\boldsymbol{z})_i = \min(\max(z_i, x_i - \varepsilon), x_i + \varepsilon)$. The *Basic Iterative Method (BIM)* [18] applies the FGSM update iteratively by setting $\text{Step}(\mathcal{L}, \boldsymbol{\theta}, x_n^{\text{adv}}, y) = \alpha \, \text{sign}(\nabla_{\boldsymbol{x}} \mathcal{L}(\boldsymbol{\theta}, x_n^{\text{adv}}, y))$. In this method, the step size α and the number of iterations can be adjusted to get the desired trade-off between run-time and performance. Alternative approaches are inspired by gradient-based optimizers using momentum to improve performance [19]. We investigate an iterative approach using RPROP [20–22] that relaxes the fixed step size α of BIM with an adaptive step size, where $\text{Step}(\mathcal{L}, \boldsymbol{\theta}, x_n^{\text{adv}}, y)$ denotes the update step computed by some iterative optimization method. RPROP adjusts the step size separately for every optimizable parameter while iterating—in the case of adversarial attacks on images for every pixel per channel. Hence, adversarial perturbations created with RPROP can be sparse and may therefore be less noticeable. For a fair comparison with FGSM, the perturbations are clipped s.t. $\|x^{\text{adv}} - \boldsymbol{x}\|_\infty \le \varepsilon$.

2.4 Adversarial attacks on familiarity-based OSR

The goal of adversarial attacks on OSR is to destroy the ranking of novel and familiar samples given by the OSR score, e.g. MLS or MSP. We discuss two types of attacks as illustrated in Fig. 1.

False Familiarity (False Negative, FN). False Familiarity attacks aim to *increase* the logit (or softmax probability) of an arbitrary familiar category, which is similar to targeted attacks in closed-set recognition [23]. We investigate three objective functions to achieve this attack:

$$\mathcal{L}_{\max}(\boldsymbol{\theta}, \boldsymbol{x}, y) = \max_{y'} f_{\boldsymbol{\theta}}(\boldsymbol{x})_{y'} \quad (5)$$

$$\mathcal{L}_{2\text{-norm}}(\boldsymbol{\theta}, \boldsymbol{x}, y) = \|f_{\boldsymbol{\theta}}(\boldsymbol{x})\|_2 \quad (6)$$

$$\mathcal{L}_{\text{log-MSP}}(\boldsymbol{\theta}, \boldsymbol{x}, y) = \log \max_{y'} \sigma(f_{\boldsymbol{\theta}}(\boldsymbol{x}))_{y'} \quad (7)$$

The log-MSP loss has been proposed in the ODIN approach [17] (which was refined in the generalized ODIN [24]) to preprocess images with adversarial perturbations to improve OOD detection using the MSP score.[1]

---

[1]While this is not further investigated in this work, our OSR experiments did not confirm an improvement of the MSP score as also mentioned in other independent work [9].

False Novelty (False Positive, FP). In this likely more challenging setting, we may have to decrease the logits of multiple categories either with a single FGSM step or multiple iterative steps. Objective functions rewarding only the decrease of the largest logit might fail, thus, besides the $\mathcal{L}_{\max}$, we investigate a the $\mathcal{L}_{2\text{-norm}}$ and the sum-exp loss:

$$\mathcal{L}_{\text{sum-exp}}(\boldsymbol{\theta}, \boldsymbol{x}, y) = \sum_{y' \in |\mathcal{F}|} e^{f_{\boldsymbol{\theta}}(\boldsymbol{x})_{y'}} \quad (8)$$

The 2-norm encourages reducing non-maximum logits while still prioritizing the max logit. However, one limitation of the 2-norm is that it is non-negative. Since logits are unnormalized and can be negative, it would be preferable if the objective function also rewarded making the logits negative. This led us to propose the sum-exp loss, which continues to decrease if a logit becomes negative. Importantly, while False Familiarity attacks *maximize* these objectives, False Novelty attacks *minimize* them.

2.5 Uninformed vs. informed attacks

We call an attack *informed* if the adversary has access to the binary set-labels of the input, i.e. closed-set vs. open-set, and *uninformed* if that information is not available [25]. In the uninformed setting, either an FP or FN attack is applied to all images, disregarding whether an image is novel or familiar. For informed adversaries, FN attacks are only performed on novel images to make the classifier falsely predict that the inputs are familiar, leaving all familiar images unchanged. In contrast, FP attacks are only performed on familiar images to make the classifier wrongly assume novel inputs, leaving all novel images unchanged.

2.6 Adversarial reaction score (ARS)

The idea that novel and familiar inputs could react differently to adversarial attacks is motivated by the findings in [17] as discussed in the introduction and by our own analyses of the behaviour of scores before and after adversarial perturbation (See Fig. 5). Here, we present the concept of an Adversarial Reaction Score (ARS) as an alternative OSR score. The ARS measures the reaction to an adversarial attack applied to a given input. We define the ARS as the signed difference between the MLS (or MSP) before and after the adversarial attack:

$$\mathcal{S}_{\text{adv}}(y \in \mathcal{F} \mid \boldsymbol{x}) = \max_y f_{\boldsymbol{\theta}}(\boldsymbol{x}^{\text{adv}})_y - \max_y f_{\boldsymbol{\theta}}(\boldsymbol{x})_y \quad (9)$$

Note that this can lead to the comparison of scores coming from different categories for the original and adversarial version.

Figure 3. Uninformed FGSM attacks. Fast gradient sign method (FGSM) attacks on TinyImageNet. Left: False Familiarity (false negative, FN) attacks. Right: False Novelty (false positive, FP) attacks. (a,b) The OSR ranking measured by AUROC. (c,d) Median Maximum Logit Score (MLS) of all samples (familiar and novel).

3 Experimental results

We experiment with the TinyImageNet dataset [26], described as one of the more challenging benchmarks used in the OSR literature [3]. Here we use the open-set split presented in Vaze et al. [3] and follow their experimental setup. TinyImageNet consists of a subset of 200 ImageNet categories [27], whereas 20 classes are used as the closed-set training dataset and 180 classes as the open-set. The CNN architecture used is a VGG32[2], a lightweight version of the VGG architecture [28]. This results in a reproduced closed-set accuracy of 84.2% averaged over five class splits.

We report the OSR performance of the MLS for the first of the five splits with the area under the Receiver-Operator curve (AUROC). The AUROC is a threshold-less metric that evaluates the ranking from open-set to closed-set samples. As a higher AUROC means better OSR performance, adversarial attacks aim to lower the AUROC.

What type of attack is more effective? It depends. In the *uninformed* FGSM experiments, False Novelty (False Positive, FP) attacks are more effective in destroying the ranking, i.e. decreasing the AUROC, than False Familiarity (False Negative, FN) attacks at the same magnitude ε of adversarial perturbation (Fig. 3(a), 3(b)). However, we observe the opposite in the *informed* FGSM setting (Fig. 4(a), 4(b)), which also holds for the informed iterative attack (Fig. 6), where the AUROC of FN

attacks is lower than FP attacks. To understand this behaviour, we look at the distribution of scores before and after the attacks.

It is too easy to raise the logit score. Or in other words, to amplify familiar features. While FN attacks aim to amplify familiar features of the open-set to cause a missed novelty, in contrast, FP attacks aim to hide familiar features to reduce the familiarity of closed-set categories. We recall that uninformed attacks are performed on both novel and familiar images. Even though FN attacks can increase the median MLS above the 99th percentile of the original test data scores (Fig. 3(c)), the AU-ROC is rather preserved (Fig. 3(a)). Hence, the FN attacks not only increase the familiarity (i.e.; MLS) of the novel but also of the familiar samples, which preserves the ranking (See also Fig. 5(a)). In contrast, FP attacks cannot decrease the median MLS below the 1st percentile of the original test scores (Fig. 3(d)), but the ranking (AUROC) is effectively destroyed (Fig. 3(b)). This suggests that FP attacks tend to decrease the scores of the closed-set more than the scores of the open-set. Our experiments confirm the prediction of Dietterich & Guyer [9] that it is very easy to raise the logit score, which only leads to effective FN attacks in the informed setting. However, our results reveal that for uninformed attacks the ability to easily raise the logit score is not the key to attack the ranking of familiarity-based OSR approaches.

Which objective function performs best? While some objectives are able to perform both

---

[2]We use the model weights published on: `https://github.com/sgvaze/osr_closed_set_all_you_need` (accessed 2023-05-23).

(a) **(b)**

(c) **(d)**

Figure 4. Informed FGSM attacks. Fast gradient sign method (FGSM) attacks on TinyImageNet. Left: False Familiarity (false negative, FN) attacks. Right: False Novelty (false positive, FP) attacks. (a,b) The OSR ranking measured by AUROC. (c,d) Median Maximum Logit Score (MLS) of novel samples (c) and familiar samples (d).

(a) **(b)**

Figure 5. MLS for familiar and novel samples after adversarial perturbation. FGSM attacks on TinyImageNet. Median Maximum Logit Score (MLS) w.r.t. original scores separately for the familiar and novel samples. The filled region shows the 25th and 75th quantile. (a) False Familiarity (false negative, FN) attacks with the max loss. (b) False Novelty (false positive, FP) attacks with the 2-norm loss. I.e., the objectives that can push the scores most up or down w.r.t. the original scores, for FN and FP respectively (see Fig. 3(c), 3(d)).

types of attacks by swapping the sign, no objective is clearly best for both FN and FP attacks (Fig. 3, 4). In the uninformed setting (Fig. 3), FN attacks achieve the lowest AUROC using the Log-MSP loss and second lowest with the Max loss. For FP attacks, the Max loss achieves the lowest AUROC with $\epsilon < 0.1$. Whereas at $\epsilon \approx 0.3$ all objective functions achieve an AUROC of ≈ 0.5, for $\epsilon > 0.3$ the 2-norm achieves even lower AUROC.

Informed attacks reverse the ranking almost perfectly. As expected, informed FGSM attacks (Fig. 4) can improve substantially over uninformed attacks (Fig. 3). While the FN attacks can increase the median MLS of the adversarial novel samples beyond the 99th percentile of the test dataset (Fig. 4(c)), the FP attacks cannot decrease the median MLS of the adversarial familiar samples below

the 1st percentile (Fig. 4(d)). To study the combination of informed attack types in Fig. 6, we use the objectives yielding the lowest AUROC, i.e. the 2-norm for FP and the max loss for FN attacks. Ultimately, when using both FP attacks on familiar and FN attacks on novel samples together, informed attacks (both FGSM and iterative) are able to reverse the ranking of novel and familiar images almost perfectly (Fig. 6).

FGSM vs. iterative attacks. Informed iterative attacks are able to decrease the AUROC by an order of magnitude compared to informed FGSM attacks using the same or even smaller ε (Fig. 6). The AUROC for FP attacks is decreased from 0.34 (FGSM) to 0.06 (iterative) and for FN attack from 0.12 (FGSM) to 0.01 (iterative).

(a) FGSM   **(b)** Iterative attack

Figure 6. Informed FGSM vs. iterative attacks.
False Positive (FP) attacks are performed on familiar
samples (2-norm loss) and False Negative (FN) attacks
on novel samples (max loss). (a) Fast gradient sign
method (FGSM) using $\varepsilon = 0.07$ for FN and $\varepsilon = 0.04$ for
FP. (b) Our iterative method with $\varepsilon = 0.07$ for both the
FN and FP attacks.

**Can adversarial reaction scores be used for
OSR?** We calculated the ARS as in Eq. 9 by obtain-
ing $\boldsymbol{x}^{\mathrm{adv}}$ with the FGSM using all combinations of
loss-functions (5)-(8), attack types (i.e. FN and FP)
and ε-values. While all combinations exhibit similar
behaviour, we focus only on the combination that
achieved the best result. We found this to be the
MLS based ARS using FP FGSM with the 2-norm
loss and $\varepsilon = 0.051$. This resulted in an AUROC
of 0.81 compared to the 0.83 obtained by the MLS
scoring rule. Statistics from the evaluation of our
best ARS are shown in Fig. 7. Figure 7(a) shows
that the ARS indeed allows to distinguish novel and
familiar images. However, Fig. 7(b) reveals that the
ARS is strongly correlated with the MLS of the orig-
inal unattacked images. Given the same MLS value,
the overlapping trend lines show that the ARS for
a fixed MLS is very similar for novel and familiar
images. Hence, the effectiveness of the ARS as an
OSR score could be explained by the effectiveness
of the MLS, but further analyses are needed to gain
a better understanding of how the MLS and ARS
are related.

4   Limitations

While our study presents adversarial attacks on
familiarity-based OSR scores and steps towards un-
derstanding their adversarial robustness, some lim-
itations exist. Our empirical evaluation is limited
to the TinyImageNet dataset and the VGG32 archi-
tecture. It remains to be evaluated, if the observed
behavior generalizes to other domains and model
architectures. Furthermore, we focused on the MLS
and it needs to be tested if the observations hold for
alternative familiarity scores, like the MSP.

Although the studied objective functions can be
applied to both the MLS and MSP, the 2-norm can
be affected by negative scores. For the FN attack,
where we aim to increase the max logit, the at-

(a)   **(b)**

Figure 7. Adversarial reaction score (ARS). This
ARS uses the FP FGSM with the 2-norm loss and $\varepsilon =
0.051$. (a) ARS of familiar and novel samples. (b) ARS
compared with MLS. The trend lines show a sliding
average of the ARS of samples with similar MLS.

tack would fail if the logit with the largest absolute
value is negative. In this case, the 2-norm would
encourage making the negative logit even more neg-
ative. Empirically, this seems to be a rare case in
our experiments. Lastly, with very large epsilon
the adversarial perturbations are clearly visible in
the input images (see Fig. 2). These noisy images
lead to random OSR scores that in turn lead to a
random ranking of the test samples as measured by
the AUROC. However, large epsilons do not lead to
meaningful subtle adversarial attacks.

5   Conclusion

We have studied the vulnerability of familiarity-
based OSR approaches to adversarial attacks. Our
MLS experiments confirm Dietterich & Guyer's [9]
prediction that the logit score can be easily raised
with an adversarial perturbation. However, their
prediction did not specify what information is avail-
able to the attack. Here, we show that this ability –
to easily raise the logit score of one class – *only* leads
to effective false familiarity attacks in the informed
setting. In the uninformed setting, such attacks are
less effective than false novelty attacks that, in con-
trary, are able to successfully destroy the ranking
by lowering the logit scores of closed-set categories.
Furthermore, we explored using adversarial attacks
for defining new OSR scores. However, our ARS
scoring rules, contrary to the findings in [17], did
not seem to improve upon the MLS. Nonetheless,
we think that our study can contribute to the design
of better scoring rules in the future and to making
familiarity scores robust against adversarial attacks.

Acknowledgement P.E. and C.G. acknowledge support
by the Danish Data Science Academy (DDSA) travel grant.
This work was supported in part by the Pioneer Centre for
AI, DNRF grant number P1, and the European Union project
ELIAS (grant agreement number 101120237).

References

[1] W. J. Scheirer, A. de Rezende Rocha, A. Sapkota, and T. E. Boult. "Toward Open Set Recognition". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 35.7 (2013), pp. 1757–1772. DOI: 10.1109/TPAMI.2012.256.

[2] J. Yang, K. Zhou, Y. Li, and Z. Liu. "Generalized Out-of-Distribution Detection: A Survey". In: *International Journal of Computer Visionb* (2024). DOI: 10.1007/s11263-024-02117-4.

[3] S. Vaze, K. Han, A. Vedaldi, and A. Zisserman. "Open-Set Recognition: A Good Closed-Set Classifier is All You Need". In: *International Conference on Learning Representations (ICLR)*. 2022.

[4] D. Hendrycks and K. Gimpel. "A Baseline for Detecting Misclassified and Out-of-Distribution Examples in Neural Networks". In: *International Conference on Learning Representations (ICLR)*. 2017.

[5] D. Hendrycks, S. Basart, M. Mazeika, A. Zou, J. Kwon, M. Mostajabi, J. Steinhardt, and D. Song. "Scaling Out-of-Distribution Detection for Real-World Settings". In: *International Conference on Machine Learning (ICML)*. Vol. 162. PMLR. 2022, pp. 8759–8773.

[6] G. Chen, P. Peng, X. Wang, and Y. Tian. "Adversarial Reciprocal Points Learning for Open Set Recognition". In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 44.11 (2021), pp. 8065–8081. DOI: 10.1109/TPAMI.2021.3106743.

[7] L. Neal, M. L. Olson, X. Z. Fern, W. Wong, and F. Li. "Open Set Learning with Counterfactual Images". In: *European Conference on Computer Vision (ECCV)*. Vol. 11210. LNCS. 2018, pp. 620–635. DOI: 10.1007/978-3-030-01231-1_38.

[8] H. Zhang, A. Li, J. Guo, and Y. Guo. "Hybrid Models for Open Set Recognition". In: *European Conference on Computer Vision (ECCV)*. Ed. by A. Vedaldi, H. Bischof, T. Brox, and J. Frahm. Vol. 12348. LNCS. 2020, pp. 102–117. DOI: 10.1007/978-3-030-58580-8_7.

[9] T. G. Dietterich and A. Guyer. "The familiarity hypothesis: Explaining the behavior of deep open set methods". In: *Pattern Recognition* 132 (2022), p. 108931. DOI: doi.org/10.1016/j.patcog.2022.108931.

[10] I. J. Goodfellow, J. Shlens, and C. Szegedy. "Explaining and Harnessing Adversarial Examples". In: *International Conference on Learning Representations (ICLR)*. 2015.

[11] A. Bendale and T. E. Boult. "Towards open set deep networks". In: *Computer Vision and Pattern Recognition (CVPR)*. 2016, pp. 1563–1572. DOI: 10.1109/CVPR.2016.173.

[12] R. Shao, P. Perera, P. C. Yuen, and V. M. Patel. "Open-set adversarial defense". In: *European Conference on Computer Vision (ECCV)*. LNCS 12362. Springer, 2020, pp. 682–698. DOI: 10.1007/978-3-030-58520-4_40.

[13] R. Shao, P. Perera, P. C. Yuen, and V. M. Patel. "Open-set adversarial defense with clean-adversarial mutual learning". In: *International Journal of Computer Vision* 130.4 (2022), pp. 1070–1087. DOI: 10.1007/s11263-022-01581-0.

[14] J. Chen, Y. Li, X. Wu, Y. Liang, and S. Jha. "Robust out-of-distribution detection for neural networks". In: *arXiv preprint arXiv:2003.09711* (2020).

[15] J. Chen, Y. Li, X. Wu, Y. Liang, and S. Jha. "Atom: Robustifying out-of-distribution detection using outlier mining". In: *Machine Learning and Knowledge Discovery in Databases. Research Track: European Conference, ECML PKDD 2021, Bilbao, Spain, September 13–17, 2021, Proceedings, Part III 21*. Springer. 2021, pp. 430–445.

[16] M. Azizmalayeri, A. Soltani Moakhar, A. Zarei, R. Zohrabi, M. Manzuri, and M. H. Rohban. "Your out-of-distribution detection method is not robust!" In: *Advances in Neural Information Processing Systems* 35 (2022), pp. 4887–4901.

[17] S. Liang, Y. Li, and R. Srikant. "Enhancing The Reliability of Out-of-distribution Image Detection in Neural Networks". In: *International Conference on Learning Representations (ICLR)*. 2018.

[18] A. Kurakin, I. J. Goodfellow, and S. Bengio. "Adversarial examples in the physical world". In: *Artificial Intelligence Safety and Security*. Chapman and Hall/CRC, 2018, pp. 99–112. DOI: 10.1201/9781351251389.

[19] Y. Dong, F. Liao, T. Pang, H. Su, J. Zhu, X. Hu, and J. Li. "Boosting Adversarial Attacks with Momentum". In: *Computer Vision and Pattern Recognition (CVPR)*. IEEE, 2018, pp. 9185–9193. DOI: 10.1109/CVPR.2018.00957.

[20]   M. Riedmiller and H. Braun. "A direct adaptive method for faster backpropagation learning: The RPROP algorithm". In: *IEEE International Conference on Neural Networks (ICNN)*. IEEE. 1993, pp. 586–591. DOI: 10.1109/ICNN.1993.298623.

[21]   C. Igel and M. Hüsken. "Empirical Evaluation of the Improved Rprop Learning Algorithm". In: *Neurocomputing* 50.C (2003), pp. 105–123. DOI: https://doi.org/10.1016/S0925-2312(01)00700-7.

[22]   C. Florescu and C. Igel. "Resilient Backpropagation (Rprop) for Batch-learning in Tensor-Flow". In: *International Conference on Learning Representations (ICLR) Workshop*. 2018.

[23]   A. Kurakin, I. J. Goodfellow, and S. Bengio. "Adversarial Machine Learning at Scale". In: *International Conference on Learning Representations (ICLR)*. 2017.

[24]   Y.-C. Hsu, Y. Shen, H. Jin, and Z. Kira. "Generalized ODIN: Detecting out-of-distribution image without learning from out-of-distribution data". In: *Computer Vision and Pattern Recognition (CVPR)*. IEEE, 2020, pp. 10951–10960. DOI: 10.1109/CVPR42600.2020.01096.

[25]   L. Huang, A. D. Joseph, B. Nelson, B. I. Rubinstein, and J. D. Tygar. "Adversarial machine learning". In: *ACM Workshop on Security and Artificial Intelligence*. 2011, pp. 43–58. DOI: 10.1145/2046684.2046692.

[26]   Y. Le and X. S. Yang. "Tiny ImageNet Visual Recognition Challenge". In: In CS231N, 2015. 2015.

[27]   O. Russakovsky, J. Deng, H. Su, J. Krause, S. Satheesh, S. Ma, Z. Huang, A. Karpathy, A. Khosla, M. Bernstein, A. C. Berg, and L. Fei-Fei. "ImageNet large scale visual recognition challenge". In: *International Journal of Computer Vision* 115 (2015), pp. 211–252. DOI: 10.1007/s11263-015-0816-y.

[28]   K. Simonyan and A. Zisserman. "Very Deep Convolutional Networks for Large-Scale Image Recognition". In: *International Conference on Learning Representations (ICLR)*. Ed. by Y. Bengio and Y. LeCun. 2015.