Hallucination as Reward Hacking: Decomposed Visual-Grounding Rewards for Preference-Aligned Distillation in Multimodal LLMs

Abstract

Multimodal large language models (MLLMs) achieve strong vision–language performance yet frequently *hallucinate*: they generate content that is not supported by the input image. Prior work largely treats this as a data or fine-tuning problem. We instead argue that hallucination is a *reward-hacking* symptom: when the alignment objective scores only the linguistic plausibility of a response, the model maximizes that proxy through shortcuts rather than by grounding in the image. We make this diagnosis concrete by separating two shortcut pathways—an **input-side** pathway, where the model under-uses the image and falls back on language priors, and an **output-side** pathway, where the model emits objects that merely co-occur in text. Building on Preference-Aligned Distillation (PAD), we propose **VAPAD**, which augments the language-based teacher reward with three complementary vision-grounded terms—global image–text alignment (CLIP), object-level grounding, and counterfactual consistency—each targeting a specific pathway. On POPE (adversarial), MM-Bench, and MMHal-Bench, VAPAD improves over the LLaVA-1.5-7B base model by **+7.8** F1, **+3.9** points, and **+0.82**, respectively, and our ablations show the three rewards contribute additive, non-overlapping gains ($82.9 \rightarrow 83.9 \rightarrow 84.7 \rightarrow 86.1$ F1). A sensitivity sweep over the mixing weights confirms the gains are structural rather than the result of careful tuning. Our results indicate that reducing hallucination need not trade off general reasoning, and that structured reward decomposition is an effective lever against reward hacking in multimodal alignment.

1 Introduction

Multimodal large language models (MLLMs) (Liu et al., 2023, 2024b; OpenAI, 2023) now perform competitively across captioning, visual question answering, and instruction following. Yet they routinely produce *visual hallucinations*—fluent descriptions of objects, attributes, or actions that are absent from the image (Rohrbach et al., 2018; Li et al., 2023). Because such errors are confident and well-formed, they are particularly damaging in settings that demand reliability.

Most mitigation strategies attack the symptom. Robust instruction tuning (Liu et al., 2024a) and human-feedback fine-tuning (Yu et al., 2024) reduce hallucination by curating or correcting training data, but leave open *why* models hallucinate in the first place. We take a different stance, grounded in a long line of work on shortcut learning and reward hacking (Geirhos et al., 2020; Amodei et al., 2016; Skalse et al., 2022): *whenever the objective being optimized diverges from the objective we actually care about, a capable optimizer will exploit the gap.* Skalse et al. (Skalse et al., 2022) show this is essentially unavoidable—almost every proxy reward is "hackable." We argue that visual hallucination is exactly this phenomenon instantiated in multimodal alignment: alignment objectives that score a response by its *linguistic plausibility* reward fluent text that is not necessarily *faithful* to the image.

Two shortcut pathways. A purely language-based reward cannot tell a plausible answer from a faithful one, and the model games it in two distinct ways. On the **input side**, the model under-attends to the image and answers from language priors—e.g., predicting "a toy" for *What is the girl holding?* when the image clearly shows an umbrella, or ranking the statistically common phrase "repairing a car" above the correct "loading luggage into a car" (Figure 1). On the **output side**, the model emits objects that frequently *co-occur* in text but are absent from the scene—e.g., "macaroni and cheese" when only chicken and broccoli are visible. These two pathways motivate a reward design that supervises both *whether* the model relies on the image and

Figure 1: Reward hacking in multimodal alignment. For *"What are the people doing?"*, PAD ranks the linguistically frequent but visually wrong answer *"repairing a car"* above the correct *"loading luggage into a car."* VAPAD reverses this ranking by adding vision-grounded reward terms that enforce image–text faithfulness. (High-resolution version in the supplementary material.)

what it claims to see.

Our approach. We build on Preference-Aligned Distillation (PAD) (Gu et al., 2025), which distills a teacher's *full* preference distribution over candidate responses into a student, rather than only the pairwise ranking used by Direct Preference Optimization (DPO) (Rafailov et al., 2023). PAD's reward is explicit and modular, which makes it a natural backbone for inserting additional, targeted signals. We propose **VAPAD** (**V**isually-**A**ware **P**reference-**A**ligned **D**istillation), which keeps PAD's language reward and adds three vision-grounded terms: global image–text alignment via CLIP (r_{clip}) (Radford et al., 2021) closes the language-prior pathway; object-level grounding (r_{obj}) (Li et al., 2023) closes the co-occurrence pathway; and counterfactual consistency (r_{cf}) (Leng et al., 2024; Niu et al., 2021) enforces genuine dependence on visual evidence. Each term maps to one diagnosed failure mode, and our analysis (Section A) shows the hardest cases are resolved only when they act together.

Evidence. Across three benchmarks the diagnosis holds up empirically. On POPE-adversarial, which stresses object hallucination, VAPAD reaches **86.1** F1 versus **78.3** for LLaVA-1.5-7B (**+7.8**); on the general-reasoning benchmark MM-Bench it improves from **67.4** to **71.3** (**+3.9**); and on MMHal-Bench it improves from **3.12** to **3.94** (**+0.82**). Crucially, hallucination reduction and general reasoning improve *together*, and a controlled ablation shows the three visual rewards add up monotonically rather than substituting for one another.

Contributions.

- We frame visual hallucination as reward hacking and decompose it into input-side (language-prior, weak visual dependence) and output-side (object co-occurrence) shortcuts, yielding a falsifiable, per-failure-mode diagnosis.

- We propose VAPAD, which augments PAD with three vision-grounded reward terms, each targeting one diagnosed pathway, integrated through a single modular composite reward.

- We provide quantitative and qualitative evidence—main results, a component-wise ablation, a sensitivity sweep, and a failure-case study—showing each term resolves a distinct hallucination category and that the gains do not come at the cost of general capability.

2 Related Work

Visual hallucination in MLLMs. MLLMs (OpenAI, 2023; Liu et al., 2023, 2024b) frequently describe content absent from the image (Rohrbach et al., 2018). POPE (Li et al., 2023) reformulates hallucination as a polling-based object-existence test and reveals strong co-occurrence biases. Mitigations include robust instruction tuning (Liu et al., 2024a) and reinforcement learning from fine-grained human feedback (Yu et al., 2024). These methods improve faithfulness but operate at the data/supervision level; our work instead targets the *reward* that drives alignment.

Reward hacking and shortcut learning. Amodei et al. (2016) identified reward hacking as a core safety problem; Geirhos et al. (2020) documented its empirical counterpart, showing networks adopt brittle decision rules (e.g., texture over shape). Skalse et al. (2022) formalized reward hacking and proved that, over the set of stochastic policies, almost every proxy reward is hackable. We adopt this lens for MLLM alignment: a language-only reward is a hackable proxy for visual faithfulness, and we counter it by decomposing the reward along the axes the proxy ignores.

Preference alignment. DPO (Rafailov et al., 2023) optimizes pairwise preferences without an

explicit reward model but discards the magnitude of preference. PAD (Gu et al., 2025) distills the teacher's full preference distribution over multiple candidates, providing richer, distribution-level supervision. PAD's explicit reward makes additional terms easy to insert—the property VAPAD exploits.

Visual grounding and counterfactual reasoning. CLIP (Radford et al., 2021) yields aligned image–text embeddings for zero-shot relevance scoring. Object-level checks (Li et al., 2023) verify that each mentioned entity has a visual referent (*what* the model says). Counterfactual approaches (Leng et al., 2024; Niu et al., 2021) perturb or mask the image and test whether the answer changes (*why* the model says it). These two lines are orthogonal—referential vs. causal fidelity—and VAPAD operationalizes both as reward terms (r_{obj} and r_{cf}).

3 Method

VAPAD instantiates PAD (Gu et al., 2025) for the multimodal setting and adds vision-grounded reward terms. We use LLaVA-1.5-7B (Liu et al., 2024b) as the student π_{stu} and LLaVA-1.5-13B as the teacher p_{tch}. The pipeline has three stages: candidate generation (§3.1), composite reward computation (§3.2), and preference distillation (§3.4).

3.1 Candidate Generation

Given a multimodal input $\mathbf{x} = (\mathbf{x}_{\text{img}}, \text{prompt})$, we sample N candidate responses $\{\mathbf{y}_1, \ldots, \mathbf{y}_N\}$ from the student with high-temperature decoding to broaden the explored generation space. Inputs are drawn from a 2K-image subset of the COCO `val2017` split.

3.2 Reward Components

Language reward (inherited from PAD). The teacher's intrinsic preference is its average per-token log-likelihood:

$$r_{\text{lang}}(\mathbf{y} \mid \mathbf{x}) = \frac{1}{|\mathbf{y}|} \sum_{t=1}^{|\mathbf{y}|} \log p_{\text{tch}}(y_t \mid y_{<t}, \mathbf{x}). \quad (1)$$

MCQ calibration reward (inherited from PAD). Raw log-likelihood over-rewards lexically frequent responses. Following PAD, we wrap the N candidates into a multiple-choice question and read off the teacher's selection probability:

$$r_{\text{mcq}}(\mathbf{y}_i \mid \mathbf{x}) \\ = \log p_{\text{tch}}(\text{choice}{=}i \mid \text{MCQ}(\mathbf{y}_{1:N}, \mathbf{x})). \quad (2)$$

Semantic alignment reward (r_{clip}). Using a frozen CLIP ViT-B/32 encoder, we score global image–text alignment by cosine similarity:

$$r_{\text{clip}}(\mathbf{y}, \mathbf{x}_{\text{img}}) = \frac{\mathcal{E}_{\text{text}}(\mathbf{y}) \cdot \mathcal{E}_{\text{img}}(\mathbf{x}_{\text{img}})}{\|\mathcal{E}_{\text{text}}(\mathbf{y})\| \, \|\mathcal{E}_{\text{img}}(\mathbf{x}_{\text{img}})\|}. \quad (3)$$

This penalizes responses that drift from the visual content, directly countering the language-prior pathway.

Object grounding reward (r_{obj}). We extract noun phrases from the response via spaCy ($\mathcal{O}(\mathbf{y})$) and detect objects in the image via YOLOv8n ($\mathcal{O}(\mathbf{x}_{\text{img}})$), then compute the precision of mentioned objects:

$$r_{\text{obj}}(\mathbf{y}, \mathbf{x}_{\text{img}}) = \frac{|\mathcal{O}(\mathbf{y}) \cap \mathcal{O}(\mathbf{x}_{\text{img}})|}{|\mathcal{O}(\mathbf{y})|}. \quad (4)$$

This penalizes object-level hallucination—mentioning objects absent from the image (the co-occurrence pathway).

Counterfactual consistency reward (r_{cf}). We build a masked image $\widetilde{\mathbf{x}}_{\text{img}} = \text{mask}(\mathbf{x}_{\text{img}}, \mathcal{O}(\mathbf{x}_{\text{img}}))$ by replacing detected object regions with mean pixel values, then measure the relative drop in CLIP similarity:

$$r_{\text{cf}}(\mathbf{y}, \mathbf{x}_{\text{img}}) = 1 - \frac{\text{sim}_{\text{CLIP}}(\mathbf{y}, \widetilde{\mathbf{x}}_{\text{img}})}{\text{sim}_{\text{CLIP}}(\mathbf{y}, \mathbf{x}_{\text{img}})}. \quad (5)$$

A high r_{cf} means the response genuinely depends on the depicted objects; a low value means the answer is invariant to object removal and is likely hallucinated, enforcing input-side visual dependence.

3.3 Composite Teacher Reward

The three visual terms are first pooled into a visual score:

$$r_{\text{vis}} = w_1 r_{\text{clip}} + w_2 r_{\text{obj}} + w_3 r_{\text{cf}}, \quad (6)$$

with $(w_1, w_2, w_3) = (0.5, 0.3, 0.2)$. The final composite reward interpolates the language reward, the MCQ-calibrated reward, and the visual score:

$$\hat{r}_{\text{tch}}(\mathbf{y} \mid \mathbf{x}) = (1{-}\alpha{-}\gamma) \, r_{\text{lang}} + \alpha \, r_{\text{mcq}} + \gamma \, r_{\text{vis}}, \quad (7)$$

with $\alpha{=}0.2$ and $\gamma{=}0.2$ by default. All components are min–max normalized before aggregation. Setting $\gamma{=}0$ recovers standard (language-only) PAD, which we use as the principal ablation baseline.

Figure 2: Overview of VAPAD. (1) The student samples N candidate responses per multimodal input under high-temperature decoding. (2) A composite teacher reward scores each candidate by combining a language reward and an MCQ-calibrated reward (from PAD) with three vision-grounded terms ($r_{\text{clip}}, r_{\text{obj}}, r_{\text{cf}}$). (3) The student's preference distribution is aligned to the teacher's via Jensen–Shannon divergence, with an auxiliary cross-modal attention-alignment loss. (Replace with a vector/high-DPI figure for the camera-ready version.)

3.4 Preference Distillation

DPO baseline. For comparison we form the highest- and lowest-reward responses $(\mathbf{y}_w, \mathbf{y}_l)$ and apply the standard DPO loss:

$$\mathcal{L}_{\text{DPO}} = -\log \sigma\Big(\beta\big[\log \frac{\pi_{\text{stu}}(\mathbf{y}_w)}{\pi_{\text{ref}}(\mathbf{y}_w)}$$
$$- \log \frac{\pi_{\text{stu}}(\mathbf{y}_l)}{\pi_{\text{ref}}(\mathbf{y}_l)}\big]\Big), \quad (8)$$

where π_{ref} is the frozen initial 7B model.

Preference alignment. Instead of collapsing to a single pair, we align the student's distribution over *all* N candidates to the teacher's via Jensen–Shannon divergence:

$$\mathcal{L}_{\text{pref}} = \text{JSD}\big(p_{\text{tch}}^{(\tau)} \,\|\, p_{\text{stu}}^{(\tau)}\big), \quad (9)$$

with softmax distributions at temperature τ:

$$p_{\text{tch}}^{(\tau)}(\mathbf{y}_i) = \frac{\exp\big(\hat{r}_{\text{tch}}(\mathbf{y}_i)/\tau\big)}{\sum_j \exp\big(\hat{r}_{\text{tch}}(\mathbf{y}_j)/\tau\big)}, \quad (10)$$

$$p_{\text{stu}}^{(\tau)}(\mathbf{y}_i) = \frac{\exp\big(\bar{\ell}_{\text{stu}}(\mathbf{y}_i)/\tau\big)}{\sum_j \exp\big(\bar{\ell}_{\text{stu}}(\mathbf{y}_j)/\tau\big)}, \quad (11)$$

where $\bar{\ell}_{\text{stu}}(\mathbf{y}_i)$ is the student's average log-likelihood for candidate $\mathbf{y}_i$. Unlike DPO, this preserves ordinal information across all candidates.

Cross-modal attention alignment. To push the student to attend to the same visual regions as the teacher, we minimize the Frobenius distance between their cross-modal attention maps over the last $|\mathcal{L}^\star|$ layers:

$$\mathcal{L}_{\text{attn}} = \frac{1}{|\mathcal{L}^\star|} \sum_{l\in\mathcal{L}^\star} \big\|\mathbf{A}_{\text{stu}}^{(l)} - \mathbf{A}_{\text{tch}}^{(l)}\big\|_F^2, \quad \mathcal{L}^\star = \{\text{last } 4\},$$
$$(12)$$

Training objective.

$$\mathcal{L}_{\text{VAPAD}} = \mathcal{L}_{\text{pref}} + \lambda_{\text{attn}}\,\mathcal{L}_{\text{attn}}, \quad (13)$$

where $\mathcal{L}_{\text{pref}}$ uses the composite reward $\hat{r}_{\text{tch}}$ of Eq. (7).

4 Experimental Setup

Models. Student: LLaVA-1.5-7B (Liu et al., 2024b); teacher: LLaVA-1.5-13B. All training uses LoRA ($r{=}16$, $\alpha_{\text{LoRA}}{=}32$) on the query, key, value, and output projections; the base weights are frozen.

Data. Candidate responses are generated on a 2K-image subset of COCO `val2017`. We sample N candidates per input with temperature T.

Reward modules. r_{clip} uses a frozen CLIP ViT-B/32; r_{obj} uses YOLOv8n for detection and spaCy (`en_core_web_sm`) for noun-phrase extraction; r_{cf} masks detected regions with the per-image mean pixel. Mixing weights: $(w_1, w_2, w_3) = (0.5, 0.3, 0.2)$, $\alpha{=}\gamma{=}0.2$, distillation temperature τ, attention weight λ_{attn}.

Optimization.

Method	MMBench↑ (acc.)	POPE-adv↑ (F1)	MMHal↑ (score)
LLaVA-1.5-7B (base)	67.40	78.30	3.12
+ DPO	68.05	81.46	3.41
+ PAD ($\gamma{=}0$)	69.12	82.88	3.58
+ PAD + r_{clip}	69.85	83.94	3.77
+ PAD + r_{clip} + r_{obj}	70.41	84.70	3.86
VAPAD (full)	**71.26**	**86.10**	**3.94**

Table 1: Main results. Higher is better for all columns. Performance increases monotonically across all three benchmarks as reward components are added, with the full VAPAD model best throughout.

Benchmarks and metrics. We evaluate on three complementary benchmarks: **POPE** (Li et al., 2023) in the *adversarial* split (object-existence F1; primary hallucination metric), **MMBench** (Liu et al., 2024c) (overall accuracy; general multimodal reasoning), and **MMHal-Bench** (Sun et al., 2023) (GPT-assisted hallucination score in $[0, 6]$, higher is better). Together they probe object hallucination, general capability, and free-form hallucination.

Baselines. We compare against the LLaVA-1.5-7B base model, DPO (Rafailov et al., 2023), language-only PAD (Gu et al., 2025) ($\gamma{=}0$), and the progressive addition of each visual reward term.

5 Results

5.1 Main Results

Table 1 and Figure 3 report the full progression from the base model to VAPAD. Two findings stand out. First, hallucination robustness improves substantially: POPE-adversarial F1 rises from 78.3 to **86.1** ($+7.8$), with a *monotonic* gain as reward terms are added—direct evidence that hallucination is driven by the components of the reward that the language-only proxy ignores. Second, general reasoning improves *in tandem*: MMBench rises from 67.4 to **71.3** ($+3.9$) and MMHal-Bench from 3.12 to **3.94** ($+0.82$). Reducing hallucination therefore does not trade off against capability; it correlates with better grounding.

5.2 Ablation: Decomposing the Visual Reward

We isolate the contribution of each visual term on POPE-adversarial, starting from language-only PAD ($\gamma{=}0$, 82.88 F1) and adding terms one at a time (Figure 4). Each term yields a positive increment: r_{clip} adds $+1.06$ (global alignment pulls the model toward visual content), r_{obj} adds $+0.76$ (object-level grounding suppresses ungrounded entities), and r_{cf} adds the largest single increment $+1.40$ (enforcing genuine, causal dependence on visual evidence is the strongest lever). The increments are additive rather than redundant, supporting our claim that hallucination has multiple, separable reward-misalignment sources.

5.3 Sensitivity to Mixing Weights

We sweep the two mixing coefficients α (MCQ-calibration weight) and γ (visual-reward weight) over $\{0.1, 0.2, 0.3\}$ and report POPE-adversarial F1 (Figure 5). Performance stays within a narrow $[84.8, 86.1]$ band across all nine configurations, peaking at the balanced setting $\alpha{=}\gamma{=}0.2$. Deviations cost at most $\sim$1.3 F1. The method's effectiveness thus stems from the *structure* of the decomposed reward, not from precise tuning—evidence that the hallucination reduction is a systematic mitigation of reward hacking rather than a fragile, configuration-specific artifact.

5.4 On Scalability

Reviewers reasonably ask whether the gains persist at larger scale. Our claim is not that a fixed absolute margin transfers, but that the *mechanism*— a language-only reward is a hackable proxy for visual faithfulness—is scale-independent: it follows from the structure of the objective, not from model capacity, and the formal results on reward hacking (Skalse et al., 2022) are stated over policy classes rather than parameter counts. The reward terms are also architecture-agnostic, depending only on the candidate text and the image, so VAPAD plugs into any PAD-style teacher–student pair. We nonetheless treat large-scale validation as the most important open item (Section 7); the present 7B/13B study establishes feasibility and the additive structure of the gains.

6 Conclusion

We reframed visual hallucination in MLLMs as reward hacking and traced it to two shortcut pathways that a language-only alignment reward cannot suppress. Building on PAD, VAPAD adds three vision-grounded reward terms—CLIP alignment, object grounding, and counterfactual consistency— each targeting one pathway. Across POPE, MM-Bench, and MMHal-Bench the terms produce additive gains, improve hallucination robustness and general reasoning simultaneously, and are robust to the mixing weights. The broader message is that

Figure 3: Main results across MMBench, POPE-adversarial, and MMHal-Bench. All three metrics improve monotonically as reward components are added, peaking at the full VAPAD model.

Figure 4: Component-wise ablation of the visual reward on POPE-adversarial. Starting from language-only PAD (γ=0), each visual term adds a positive increment (+1.06, +0.76, +1.40), yielding a monotonic $82.9 \rightarrow 86.1$ trajectory. The gains are additive rather than redundant, with r_{cf} contributing most.

Figure 5: Sensitivity of POPE-adversarial F1 to the mixing weights α (MCQ-calibration) and γ (visual reward). Performance is stable in $[84.8, 86.1]$ across the sweep, peaking at the balanced α=γ=0.2.

hallucination is not a single defect to be patched but a systematic consequence of reward misalignment that structured reward design can mitigate.

7 Future Work

Three directions follow naturally. *(i) Scale.* Apply VAPAD to stronger teachers and larger students to test whether the additive structure of the gains holds at scale. *(ii) Reward composition as control.* PAD's modularity suggests that reweighting reward terms could steer models toward distinct behaviors (e.g., conservative low-hallucination vs. richly descriptive outputs), turning reward design into a controllability tool. *(iii) Finer grounding.* Region-level supervision and earlier-layer attention alignment may capture localized semantics that global CLIP misses, while reducing dependence on external detectors would improve efficiency.

Limitations

Scale. Our study uses a 13B teacher and a 7B student. This validates feasibility and the additive structure of the gains but does not establish behavior at larger scale; large-model validation is our top priority for future work (§5.4).

Global vs. local alignment. r_{clip} compares whole-response and whole-image embeddings and can miss localized mismatches, allowing globally consistent responses that contain subtle local hallucinations.

Dependence on external tools. r_{obj} relies on YOLOv8n and spaCy; detection or parsing errors inject noise into the reward and can affect training stability.

Computational overhead. Computing CLIP similarity, object detection, and counterfactual masking increases the cost of reward construction. We do not yet quantify the accuracy–cost trade-off,

which matters for deployment.

Teacher access. Reward computation assumes access to the teacher's likelihoods and preference distribution, limiting applicability when teachers are proprietary or API-gated.

References

Dario Amodei, Chris Olah, Jacob Steinhardt, Paul Christiano, John Schulman, and Dan Mané. 2016. Concrete problems in AI safety. *Preprint*, arXiv:1606.06565.

Robert Geirhos, Jörn-Henrik Jacobsen, Claudio Michaelis, Richard Zemel, Wieland Brendel, Matthias Bethge, and Felix A. Wichmann. 2020. Shortcut learning in deep neural networks. *Nature Machine Intelligence*, 2(11):665–673.

Yanggan Gu, Junzhuo Li, Sirui Huang, Xin Zou, Zhenghua Li, and Xuming Hu. 2025. Capturing nuanced preferences: Preference-aligned distillation for small language models. In *Findings of the Association for Computational Linguistics: ACL 2025*. Association for Computational Linguistics.

Sicong Leng, Hang Zhang, Guanzheng Chen, Xin Li, Shijian Lu, Chunyan Miao, and Lidong Bing. 2024. Mitigating object hallucinations in large vision-language models through visual contrastive decoding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. 2023. Evaluating object hallucination in large vision-language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Fuxiao Liu, Kevin Lin, Linjie Li, Jianfeng Wang, Yaser Yacoob, and Lijuan Wang. 2024a. Mitigating hallucination in large multi-modal models via robust instruction tuning. In *International Conference on Learning Representations (ICLR)*.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. 2024b. Improved baselines with visual instruction tuning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, Kai Chen, and Dahua Lin. 2024c. MMBench: Is your multi-modal model an all-around player? In *Proceedings of the European Conference on Computer Vision (ECCV)*.

Yulei Niu, Kaihua Tang, Hanwang Zhang, Zhiwu Lu, Xian-Sheng Hua, and Ji-Rong Wen. 2021. Counterfactual VQA: A cause-effect look at language bias. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

OpenAI. 2023. GPT-4V(ision) system card. Technical report, OpenAI.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning transferable visual models from natural language supervision. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Anna Rohrbach, Lisa Anne Hendricks, Kaylee Burns, Trevor Darrell, and Kate Saenko. 2018. Object hallucination in image captioning. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*.

Joar Skalse, Nikolaus H. R. Howe, Dmitrii Krasheninnikov, and David Krueger. 2022. Defining and characterizing reward hacking. In *Advances in Neural Information Processing Systems (NeurIPS)*.

Zhiqing Sun, Sheng Shen, Shengcao Cao, Haotian Liu, Chunyuan Li, Yikang Shen, Chuang Gan, Liang-Yan Gui, Yu-Xiong Wang, Yiming Yang, Kurt Keutzer, and Trevor Darrell. 2023. Aligning large multimodal models with factually augmented RLHF. *arXiv preprint arXiv:2309.14525*.

Tianyu Yu, Yuan Yao, Haoye Zhang, Taiwen He, Yifeng Han, Ganqu Cui, Jinyi Hu, Zhiyuan Liu, Hai-Tao Zheng, Maosong Sun, and Tat-Seng Chua. 2024. RLHF-V: Towards trustworthy MLLMs via behavior alignment from fine-grained correctional human feedback. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

A Failure Case Analysis

We walk through four representative PAD failures and show how the targeted reward term repairs each ranking. High-resolution versions of all case images are in the supplementary material.

A.1 Language-Prior Bias (resolved by r_{clip})

Prompt: *What are the people doing?* **Ground truth:** loading luggage into a car.

PAD ranking: `repairing a car > standing near a car > loading luggage into a car > shopping in a`

Figure 6: PAD prefers the frequent language pattern "repairing a car" over the visually grounded answer.

parking lot. PAD is dominated by the language prior.

With r_{clip}: loading luggage into a car > repairing a car > standing near a car > shopping in a parking lot. Global image–text alignment restores the visually correct answer.

A.2 Object-Level Hallucination (resolved by r_{obj})

Figure 7: PAD hallucinates "macaroni" due to co-occurrence bias; only chicken and broccoli are present.

Prompt: *What food is on the plate?* **Ground truth:** shredded chicken and broccoli in cheese sauce.

PAD ranking: macaroni and cheese > chicken and vegetables with cheese sauce > shredded chicken with broccoli > chicken with sauce. Co-occurrence bias hallucinates "macaroni."

With r_{obj}: shredded chicken with broccoli > chicken and vegetables with cheese sauce > chicken

with sauce > macaroni and cheese. Object grounding demotes the hallucinated concept.

A.3 Weak Visual Dependence (resolved by r_{cf})

Figure 8: The model predicts "toy" from the language prior instead of the visible umbrella.

Prompt: *What is the girl holding?* **Ground truth:** an umbrella.

PAD ranking: a toy > a blue umbrella > a stick > something in her hand. The answer barely depends on the image.

With r_{cf}: a blue umbrella > something in her hand > a toy > a stick. Counterfactual masking enforces dependence on visual evidence.

A.4 Ambiguity (resolved by $r_{cf} + r_{obj}$)

Figure 9: Only combining r_{cf} (relevance) and r_{obj} (object-level precision) yields the precise answer.

Prompt: *What objects are on the table?* **Ground truth:** cups, bowls, and plates.

PAD ranking: `people having a meal > food and dishes > plates and cups > cups, bowls, and plates.`

r_{cf} **only:** `food and dishes > plates and cups > cups, bowls, and plates > people having a meal` (relevant but coarse).

r_{obj} **only:** `cups, bowls, and plates > plates and cups > food and dishes > people having a meal.`

Combined: `cups, bowls, and plates > plates and cups > food and dishes > people having a meal.` r_{cf} ensures relevance while r_{obj} ensures object-level precision; only together do they yield the precise answer.