Instructions for *ACL Proceedings

Abstract

We introduce **Contrastive Region Masking (CRM)**, a training-free diagnostic for uncovering how multimodal large language models (MLLMs) rely on specific visual regions during each step of chain-of-thought (CoT) reasoning. Unlike prior approaches that focus only on final answers or coarse attention maps, CRM provides causal, step-level attribution by systematically masking annotated regions and contrasting the resulting reasoning traces with unmasked baselines. Applied to datasets such as **VisArgs** (Zhang et al., 2024), CRM reveals distinct failure modes: some models preserve reasoning structure but hallucinate when evidence is removed, while others ground tightly to visual cues yet collapse under perturbations. By shifting evaluation from answer correctness to reasoning faithfulness, CRM reframes visual benchmarks as diagnostic tools, emphasizing the need for multimodal evaluation frameworks that assess not only performance but also robustness and fidelity of reasoning.

1 Introduction

Chain-of-thought reasoning (CoT) (Wei et al., 2022) has emerged as a powerful technique for improving reasoning in large language models (LLMs). It encourages models to generate step-by-step intermediate reasoning before producing final answers. Multimodal large language models (MLLMs) (Caffagni et al., 2024; Dang et al., 2024; Han et al., 2025; Jin et al., 2024; Yin et al., 2023) have advanced the integration of visual and textual information, enabling complex reasoning over images and language (Zhou et al., 2023). However, these models often lack fine-grained selectivity, leading to reasoning failures such as hallucinated logic, semantic drift, and brittle answers when irrelevant or distracting visual content is present (Kang et al., 2025). MLLMs often fail to reason selectively over the most relevant image regions, especially in complex tasks that involve multiple objects or scenes (Wu et al., 2023). Our analysis on VisArgs dataset (CC-BY-4.0) shows that state-of-the-art models like GPT-4o (OpenAI, 2024), Gemini-1.5-Flash (Gemini Team, 2024), Qwen-2.5-VL-7b-Instruct (Bai et al., 2023), Llama-3.2-90B-Vision-Instruct (AI, 2024) exhibit these weaknesses.

Prior methods have been fragmented: some inspect attention (e.g., FOCUS (Zhong et al., 2025)), some explore grounding or region replay (e.g., VGR (Wang et al., 2025), Argus (Man et al., 2025), and others fine-tune visual reasoning (e.g., ICoV (Huang et al., 2025)). Crucially, none systematically link step-wise reasoning failures to specific visual regions, leaving an important gap in understanding **how** visual content drives reasoning.

This raises a central question: **What happens to a model's reasoning process when key visual regions are removed?**

To address this, we introduce a novel and training-free framework called CRM (Contrastive Region Masking), as shown in Figure 1, that evaluates MLLMs' reliance on specific visual regions during reasoning, not only for final answers but for each step in the chain-of-thought (CoT). Our contributions are threefold:

1. **Behavioral Attribution of Visual Reasoning via Contrastive Region Masking (CRM):** We systematically remove ground-truth bounding boxes and track how each CoT step changes, enabling causal attribution between visual regions and reasoning steps. This approach goes beyond saliency maps or final-answer metrics to reveal step-level reasoning failures.

2. **Step-to-Region Causality Without Training:** Our framework is black-box and model-agnostic, requiring no retraining. By combining simple region perturbations with semantic similarity over CoT traces, we expose where

MLLMs rely on visual evidence and where reasoning fails or hallucinates when cues are absent.

3. **Repurposing Structured Benchmarks for Step-Level Diagnostics:** We reframe Vis-Args, a dataset with region-level and reasoning annotations, as a diagnostic tool. By selectively masking regions associated with each CoT step and measuring resulting reasoning disruptions, we provide insights into model robustness, interpretability, and visual faithfulness.

2 Related Work

Prior research on evaluating and improving visual reasoning in multimodal large language models (MLLMs) is centered around four thematic axes.

Grounding Approaches: Methods such as VGR (Wang et al., 2025), Visual Chain-of-Thought (Visual CoT) (Wu et al., 2023), and Argus (Man et al., 2025) focus on grounding visual evidence during reasoning. VGR predicts bounding-box tokens during CoT inference to localize relevant regions, but its reliance on explicit annotations and handcrafted data limits scalability. Visual CoT extends textual reasoning to multimodal settings by prompting models to verbalize intermediate steps that mix linguistic and perceptual information. These approaches emphasize the plausibility of reasoning traces, yet often overlook whether steps are causally supported by the underlying visual input. Argus integrates grounded CoT with visual region grounding to enhance multimodal inference, though its dependence on the limited-scale VisCoT dataset restricts generalization. In contrast, CRM probes causal dependencies directly by systematically masking visual evidence and observing how reasoning steps change.

Training-Free Probes: Methods like FOCUS (Zhong et al., 2025) select regions in a training-free manner using MLLMs to inspect attention. While it provides insight into where models attend, it lacks structured decision-making and does not link attention patterns to causal reasoning outcomes. Unlike FOCUS, CRM directly tests how removing evidence alters reasoning steps and quantifies step-level reasoning failures.

Structured Reasoning Augmentation: Methods such as ICoV (Huang et al., 2025) and RSVP (Xu et al., 2025) augment reasoning with structured pipelines. RSVP decomposes images into regions and applies multimodal CoT, but it depends heavily on segmentation accuracy. ICoV breaks questions into subquestion–answer pairs, ranks visual regions with CLIP (Alec Radford, 2021), and fine-tunes MLLMs to align attention with evidence. However, ICoV depends on external tools like GPT-4o and CLIP, making it partially reliant on upstream model quality. Unlike RSVP and ICoV, CRM is training-free and exposes reasoning weaknesses directly through causal intervention on visual inputs.

Localization-Enhanced Pretraining: Methods like CLOC (Chen et al., 2024) improve the localization capability of CLIP (Alec Radford, 2021) by complementing CLIP with region-text contrastive loss and modules. Unlike CLIP, CLOC scales to billions of annotated images and generates spatially-localized region embeddings. This can be a replacement for CLIP in MLLMs, especially for tasks that require grounding and fine-grained region reasoning. However, CRM probes the reasoning process by testing the difference masking an image makes, while CLOC improves CLIP's localization ability.

3 Methods and Results

3.1 Data and Annotation Statistics

Our tests are conducted on 1,611 VisArgs benchmarks. VisArgs consists of image–question pairs with relevant and irrelevant region annotations, aimed at selective evaluation of visual reasoning. We sampled a balanced subset of both datasets (relevant and irrelevant region annotations) across topics and difficulty levels to ensure the highest diversity in visual content and reasoning complexity. We run all the experiments on Google Colab.

3.2 Pre-Masking CoT Generation

For each LLM that we use, we first get baseline CoT generations where we run CoT prompting on full unmasked images to log complete reasoning traces and answers as baseline output. Each question is paired with a bounding box that indicates a specific visual region. For these generations, we use a temperature of 0.2 for the CoT reasoning stage and a temperature of 0.0 for the final answer stage. Each question outputs a CoT answer and a final answer for the unmasked region and bounding box. To determine how much the model reasoning and analysis change with masked images, we evaluate and compare the baseline CoT with the CoT traces in masked images with attribution scores. Figure 1 illustrates the overall pipeline of

Figure 1: **Architecture of Contrastive Region Masking (CRM).** The diagram shows how CRM compares the original and masked chains of thought (CoT) and final answers to evaluate the importance of visual evidence in reasoning. Different metrics were then evaluated from the comparison.

Table 1: Attribution steps for Fig. 1: Comparison of Original vs. Masked chain-of-thought (CoT).

Step	Status	Cue	Original	Masked
0	Unchanged	Scene	Young boy on sofa in lush forest.	Boy on couch in dense jungle.
1	Modified	Secondary obj.	Panda on sofa using a laptop.	Large black rectangle in front of couch; TV-like shape.
2	Modified	Gaze/posture	Boy looks at panda.	Posture suggests focus on something in front.
3	Modified	Background	Background is a dense forest	A logo for a company along with text "Internet + TV	Dive"
4	Modified	Text/logo	"Internet + TV	Dive into impressions" with logo.	Lush jungle evokes nature/escape/relaxation.
5	Modified	Setting	Forest implies natural/remote environment.	Couch implies relaxation/entertainment context.
6	Modified	Symbolism	Panda connotes nature/peace/tranquility.	Large black rectangle strongly suggests a TV screen.
7	Modified	Device	Laptop implies tech/info/entertainment access.	Logo/services indicate the image is an advertisement.
8	Modified	Attention	Direct looking $\Rightarrow$ attention on object/being.	People typically face the TV when watching.
9	Modified	Ad framing	Text frames an internet/TV services ad; "immersive."	Given posture + rectangle placement, likely looking at a TV.
10	Modified	Juxtaposition	Boy's gaze at panda with laptop $\Rightarrow$ observing activity.	Jungle vs. TV suggests nature–tech contrast / access from anywhere.
11	Modified	Message	Nature (forest, panda) + tech (laptop) $\Rightarrow$ access even in remote places.	Ad conveys entertainment/connectivity anywhere; conclusion: boy looks at a TV.
12	Disappeared	Mask effect	Ad message: "Dive into impressions"; boy attends to panda–laptop interaction; conclusion: boy looks at panda using laptop (tech immersion).	Not applicable—the masking fully disappeared.

the process, while Table 1 details the attribution steps of the baseline generation and the corresponding masking generation.

3.3 CoT Prompts

Baseline CoT Generation: We use the following Chain-of-Thought (CoT) prompt template to elicit explicit visual and commonsense reasoning, followed by a concise final conclusion.

```
Use your observations and commonsense
    knowledge.

1) Visual Premises (VP): Identify and
    describe all key visual elements
    relevant to the question.
2) Commonsense Premises (CP): For each VP,
    explain the typical meaning,
    function, or implication of the
    element based on commonsense
    knowledge.
3) Inference/Conclusion (IC): Combine VP
    and CP to reason explicitly about
    what the image is showing and what it
    implies in relation to the question.
4) Final Conclusion: Provide a final
    answer to the question based on the
    reasoning.

Example
Image: A cup is pouring tea into a brain.
    Below the brain, theres a loading bar
    with the words Loading CreaTEAvity.
Question: What is being poured into the
    brain?
Reasoning:
- VP1: A cup is pouring a brown liquid
    into a brain.
- VP2: The brain is partially filled with
    the liquid.
- VP3: There is a progress bar labeled "
    Loading CreaTEAvity."
- CP1: Brains symbolize intellect and
    creativity.
- CP2: Brown liquids like tea or coffee
    are associated with mental
    stimulation.
- CP3: A progress bar indicates an ongoing
    process or enhancement.
- IC1: The brown liquid represents tea
    being used to metaphorically enhance
    mental creativity.
- IC2: The progress bar reinforces the
    idea of creativity being gradually
    boosted.
Final Conclusion: Tea is being poured into
    the brain, suggesting it enhances
    creativity.

Question: {question}
```

Final Answer generation (No CoT). For final answer generation that requires only a succinct response without revealing intermediate reasoning, we use:

```
Answer Template

Provide a final short answer to the
    question, based only on the image and
    bounding box context.
Do not include step-by-step reasoning.
Question: {question}
```

Masking CoT Generation: We use the same general CoT prompt in the masking function compared to the baseline CoT prompt. For the answer generation that require a response, we use:

```
Answer Template

Provide the final short answer based only
    on the masked image and context. Do
    not include step-by-step reasoning.
Question: {question}
```

3.4 Region Masking on CoT

For bounding box evaluation, we apply a mask to regions that are explicitly identified as important in the given dataset. These important regions are defined according to the dataset's annotations. After masking these specified regions, we reintroduce the original question to ensure consistency between masked and unmasked runs. We use the same temperature values as in the pre-masking CoT generation phase to guarantee consistency in inference behavior. The model then processes the modified image to produce a masked chain-of-thought (CoT) trace and final answer, which are compared against the baseline outputs.

3.5 Attribution Scores

In this stage, we assess how masking affects the model's reasoning and final predictions. First, we identify which reasoning steps and final answers are disrupted by the masking. We then measure the degree to which the baseline CoT and final answer semantically differ from the masked CoT and final answer. All reasoning steps that differ are marked. Semantic steps are characterized by hallucinated reasoning steps, disappearance of reasoning steps, or changes in the final answer. We observe the following evaluation metrics:

The metric results are in Table 2. Table 3 presents the disruption analysis of visual reasoning steps under masked region perturbations. We evaluate three metrics, Answer Flip Rate, Step Disruption Rate, and Hallucination Rate, for Gemini-1.5-Flash, GPT-4o, Qwen-2.5-VL-7B-Instruct, and Llama-3.2-90B-Vision-Instruct. We selected models of varying sizes and types to understand how these factors influence their responses. The models exhibit contrasting behaviors under masked region perturbations. For the Answer Flip Rate, Gemini-1.5-Flash records a value of 58.78%, while

GPT-4o shows a much higher rate of 74.74%, and Llama-3.2-90B-Vision-Instruct at 75.72%, and Qwen-2.5-VL-7b-Instructs shows the highest flip rate at 85.72%, indicating that Qwen-2.5-VL-7B-Instruct is the most sensitive to regional masking, GPT-4o and Llama-3.2-90B-Vision-Instruct are moderately sensitive, and Gemini-1.5-Flash is the most stable. In terms of the Step Disruption Rate, Gemini-1.5-Flash shows 79.08% of reasoning steps disrupted compared to 92.86% for GPT-4o, 95.59% for Qwen-2.5-VL-7B-Instruct, and 93.73% for Llama-3.2-90B-Vision-Instruct, suggesting that while all the models are heavily affected by perturbations, while all models are heavily affected by perturbations, Gemini-1.5-Flash retains the most step-level coherence, Llama-3.2-90B-Vision-Instruct and GPT-4o are heavily disrupted, and Qwen-2.5-VL-7B-Instruct suffers the most. However, when considering the Hallucination Rate, Qwen-2.5-VL-7B-Instruct hallucinates the least (26.57%), Gemini-1.5-Flash slightly more (30.60%), Llama-3.2-90B-Vision-Instruct higher still (49.97%), and GPT-4o the most (35.51%). This shows that Qwen-2.5-VL-7B-Instruct gives the most grounded responses, Gemini-1.5-Flash is moderately grounded, GPT-4o hallucinates more often, and Llama-3.2-90B-Vision-Instruct is the least grounded overall.

- **Answer Flipped**: Measures overall task sensitivity to visual region removal.
- **Step Disrupted**: Captures which reasoning steps change significantly, counting the entire image as disrupted if any step is modified.
- **Similarity**: We use Sentence-BERT all-MiniLM-L6-v2 (Reimers and Gurevych, 2019) to calculate semantic similarity between the reasoning steps for original images and the masked image. For this, we set a threshold of 0.80 and use it to measure the step-disrupted metric to capture moderate changes while still reflecting consistency. We use a similar method with a threshold of 0.90 to measure the answer-flipped metric to focus on the correctness of the final outcome, where even a small deviation can change the final answer semantics.
- **Hallucination**: Surfaces when models continue referring to missing content, counting the entire image as hallucinated if any step introduces spurious information.

Figure 2: Brain_Loading_Tea: (a) Original Image, (b) Masked Image. Question: "What is being poured into the brain in the image?" A case where Gemini-1.5-Flash, GPT-4o, Qwen-2.5-VL-7b-Instruct, and Llama-3.2-90B-Vision-Instruct models diverge in Answer Flipped and Region Attribution, showcasing the different behavior of the models as a result of masking (Table 3).

Figure 3: Soda_Plug_CocaCola: (a) Original Image, (b) Masked Image. Question: "What brand of soda is depicted in the plug?" A case where the CoT steps were disrupted, but answers did not flip across all four models, as the answer came from other image regions (Table 3).

Figure 4: Fish_Container: (a) Original Image, (b) Masked Image. Question: "What type of container is shown hanging from the fishing hook?" A case where CoT steps were disrupted across all the models, but Gemini-1.5-Flash and Llama-3.2-90B-Vision-Instruct showcase hallucination as well after masking. (Table 3).

Table 2: Comparison of evaluation metrics across models. **Qwen-2.5-VL-7B-Instruct** shows the highest Answer Flip Rate and Step Disruption, indicating stronger sensitivity to masking. **Llama-3.2-90B-Vision-Instruct** has the highest hallucination rate.

Metric	Gemini-1.5-Flash	GPT-4o	Qwen-2.5-VL-7B-Instruct	Llama-3.2-90B-Vision-Instruct
Answer flip rate	$58.78 \pm 1.23\%$	$74.74 \pm 1.08\%$	$\mathbf{85.72 \pm 0.87}\%$	$75.72 \pm 1.07\%$
Step disruption	$79.08 \pm 1.01\%$	$92.86 \pm 0.65\%$	$\mathbf{95.59 \pm 0.51}\%$	$93.73 \pm 0.60\%$
Hallucination	$30.60 \pm 1.15\%$	$35.51 \pm 1.19\%$	$26.57 \pm 1.10\%$	$\mathbf{49.97 \pm 1.25}\%$

Table 3: Disruption analysis of visual reasoning under masked region perturbations. For each image–model pair, the table shows the ground-truth reasoning step (GT Step), the masked region, whether the step was disrupted, the answer flipped, or hallucination occurred, and region attribution (alignment between GT regions and actual reasoning dependencies, bucketed as incorrect, correct, and partial), as well as similarity.

Image	Model	GT Step / Masked Region	Details
Brain_Loading_Tea	Gemini-1.5-Flash	Step 1 (VP1 "glass pouring tea") / Box (glass→brain)	– Step disrupted: Yes
– Answer flipped: Yes (Tea → Creativity)
– Similarity: ≈0(0.0)
– Region attribution: Incorrect
– Hallucination: No
Brain_Loading_Tea	GPT-4o	Step 1 (VP1 "brown liquid being poured") / Box (glass→brain)	– Step disrupted: No
– Answer flipped: No
– Similarity: ≈100 (1.0)
– Region attribution: Correct
– Hallucination: No
Brain_Loading_Tea	Qwen-2.5-VL-7B-Instruct	Step 1 (VP1 "brown liquid poured from cup") / Box (glass→brain)	– Step disrupted: Yes
– Answer flipped: No
– Similarity: ≈0 (0.0)
– Region attribution: Partial
– Hallucination: Yes
Brain_Loading_Tea	Llama-3.2-90B-Vision-Instruct	Step 1 (VP1 "brown liquid poured into brain") / Box (glass→brain)	– Step disrupted: Yes
– Answer flipped: Yes (Tea → Coffee)
– Similarity: 0(0.0)
– Region attribution: Partial
– Hallucination: Yes
Soda_Plug_CocaCola	Gemini-1.5-Flash	Step 1(plug+bottles as prongs)/Box (plug)	– Step disrupted: Yes
– Answer flipped: No
– Similarity: ≈82 (0.182)
– Region attribution: Partial
– Hallucination: No
Soda_Plug_CocaCola	GPT-4o	Step 1(plug+labels) / Box (plug)	– Step disrupted: Yes
– Answer flipped: No
– Similarity: ≈0 (0.0)
– Region attribution: Incorrect
– Hallucination: No
Soda_Plug_CocaCola	Qwen-2.5-VL-7B-Instruct	Step 1 VP1 "black rectangular podium with Coca-Cola bottles") / Box (plug)	– Step disrupted: Yes
– Answer flipped: No
– Similarity: ≈0 (0.0)
– Region attribution: Incorrect
– Hallucination: Yes
Soda_Plug_CocaCola	Llama-3.2-90B-Vision-Instruct	Step 1 (VP1 "black object resembling fridge or plug") / Box (plug)	– Step disrupted: Yes
– Answer flipped: No
– Similarity: ≈0.45
– Region attribution: Partially incorrect
– Hallucination: No
Fish_Container	Gemini-1.5-Flash	Step 1 (VP2 "transparent bottle hanging") / Box (bottle)	– Step disrupted: Yes
– Answer flipped: Yes (Bottle → Plastic bag)
– Similarity: ≈0.62
– Region attribution: Partial
– Hallucination: Yes
Fish_Container	GPT-4o	Step 1 (VP1 "clear plastic bottle") / Box (bottle)	– Step disrupted: Yes
– Answer flipped: No
– Similarity: ≈0%
– Region attribution: Incorrect
– Hallucination: No
Fish_Container	Qwen-2.5-VL-7B-Instruct	Step 1 (VP1 "rectangular shaped object hanging from hook") / Box (bottle)	– Step disrupted: Yes
– Answer flipped: Yes
– Similarity: ≈0 (0.0)
– Region attribution: Partial
– Hallucination: No
Fish_Container	Llama-3.2-90B-Vision-Instruct	Step 1 (VP1 "black rectangular object hanging from string") / Box (bottle)	– Step disrupted: Yes
– Answer flipped: Yes
– Similarity: 0.0
– Region attribution: Partial
– Hallucination: Yes

3.6 Ablation Study

To systematically assess model robustness, we perform a dual-ablation study evaluating GPT-4o, Gemini-1.5-Flash, Qwen-2.5-VL-7B-Instruct, and Llama-3.2-90B-Vision-Instruct under both specific masking and random masking.

In the random masking, irrelevant regions were selected by randomly picking image regions that were at least five percent away from the original masked region to avoid overlap. In specific masking, we measure the model's robustness to masking important regions provided in the ((Zhang et al., 2024)) dataset. This lets us see how sensitive models are to missing information and how robust they are to noise.

We consider three core metrics for this study: **Hallucination Rate**, **Step Disruption Rate**, and **Answer Flip Rate**. We perform a detailed comparative analysis of specific masking and random masking in GPT-4o, Gemini-1.5-Flash, Qwen-2.5-VL-7B-Instruct, and Llama-3.2-90B-Vision-Instruct using the three metrics. The ablation study results for random and specific masking are in Table 4 and Table 5 respectively.

Hallucination Rate:

GPT-4o maintains a relatively low hallucination rate across both settings, rarely introducing unsupported reasoning or invented content, even when input is masked. Gemini-1.5-Flash, by contrast, exhibits a high hallucination rate (52.64%) under random masking and remains notably prone to hallucination under specific masking (30.60%), indicating increased risk of spurious outputs, especially under missing evidence. Qwen-2.5-VL-7B-Instruct remains the most grounded with lowest hallucination rate (26.65%), suggesting strong evidence-based reasoning even when perturbed. Llama-3.2-90B-Vision-Instruct shows higher hallucination (41.59% random, 49.97% specific), reflecting weaker resistance to masking.

Step Disruption Rate:

All models showed high sensitivity to masking at the reasoning-step level, but extent varied. GPT-4o is markedly affected with 95.59% disruption under both random and specific masking. Gemini-1.5-Flash is less affected with disruption rates of 79.02% under random masking and 79.08% under specific masking. Qwen-2.5-VL-7B-Instruct exhibits the highest disruption rates of 95.59% for both random and specific masking

and Llama-3.2-90B-Vision-Instruct shows similar disruption to GPT-4o for both specific and random masking.

Answer Flip Rate:

The final answer stability shows clear model divergences. GPT-4o displays high answer flip rates (58.03% random, 74.74% masked), indicating that its final predictions are highly variable with perturbed or incomplete input. Gemini-1.5-Flash is more stable under general conditions (26.65%) but its answer flip rate rises sharply to 58.78% with visual region masking, reflecting reduced answer stability in the absence of key information. Qwen-2.5-VL-7B-Instruct is the most unstable with both flip rates exceeding 75% (75.54% random, 85.72% specific), showing its severe fragility in its final answers. Llama-3.2.90B-Vision-Instruct also exhibits high instability (55.37% random, 75.72% specific), showing weakness when essential parts of image is removed.

Model Behaviors:

In environments with general linguistic noise or synthetic perturbation, GPT-4o maintains solid factual correctness however is easily destabilized. Gemini-1.5-Flash prioritizes reasoning stability shown from lower disruption rates and lower answer flip rates. Qwen-2.5-VL-7B-Instruct shows the least hallucination rate but is extremely instable in both reasoning steps and answers. Finally, Llama-3.2-90B-Vision-Instruct has moderate hallucination rates and a higher rate for the models present, it also has high step disruption and flip rates as well, a more similar behavior to GPT-4o but weaker factual grounding.

Robustness Profile:

The aggregate results across both ablations indicate a trade-off between factual grounding and reasoning/answer stability. GPT-4o consistently delivers fact-based output with relatively low hallucination rates, yet suffers significant instability in both intermediate reasoning and final answer when inputs are incomplete or noisy. Gemini-1.5-Flash, in contrast, prioritizes stability and consistency, yet this comes with a higher likelihood of generating unsupported or spurious content, particularly as input completeness degrades. Qwen-2.5-VL-7B-Instruct is the most grounded, yet also the highest step-disruption rates as well as answer-flip rates. Llama-3.2-90B-Vision-Instruct is more unstable

Table 4: Random Masking results for models. Key results include Qwen achieving lowest hallucination and high answer flip rate. Gemini minimizes answer flips and lower step disruption but has hallucination struggles. Bold percentages show some of the key results.

Model	Hallucination Rate (%)	Step Disruption Rate (%)	Answer Flip Rate (%)
GPT-4o	$33.27 \pm 1.17\%$	$92.79 \pm 0.64\%$	$58.03 \pm 1.23\%$
Gemini-1.5-Flash	$\mathbf{52.64 \pm 1.24\%}$	$\mathbf{79.02 \pm 1.01\%}$	$\mathbf{26.65 \pm 1.12\%}$
Qwen-2.5-VL-7B-Instruct	$29.74 \pm 1.14\%$	$95.59 \pm 0.51\%$	$\mathbf{75.54 \pm 1.07\%}$
Llama-3.2-90B-Vision-Instruct	$41.59 \pm 1.23\%$	$93.73 \pm 0.60\%$	$55.37 \pm 1.24\%$

Table 5: Specific Masking results for models. Key results include Qwen behaving similar to random masking having lowest hallucination and higher answer flip rates. Gemini has the lowest step disruption rate. Bold percentages show some of the key results.

Model	Hallucination Rate (%)	Step Disruption Rate (%)	Answer Flip Rate (%)
GPT-4o	$35.51 \pm 1.19\%$	$92.86 \pm 0.65\%$	$74.74 \pm 1.08\%$
Gemini-1.5-Flash	$30.60 \pm 1.15\%$	$\mathbf{79.08 \pm 1.01\%}$	$58.78 \pm 1.23\%$
Qwen-2.5-VL-7B-Instruct	$26.57 \pm 1.10\%$	$95.59 \pm 0.51\%$	$\mathbf{85.72 \pm 0.87\%}$
Llama-3.2-90B-Vision-Instruct	$49.97 \pm 1.25\%$	$93.73 \pm 0.60\%$	$75.72 \pm 1.07\%$

overall, reflecting a high vulnerability in both reasoning steps and final answers.

4 Conclusion and Future Work

In this work, we systematically mask individual regions of VisArgs images and compare the resulting reasoning traces with the original output. This analysis exposed subtle weaknesses in multimodal reasoning, including logical omissions, semantic drift, and answer disruptions, which are often overlooked by traditional final-answer metrics. By revealing step-level causal dependencies, CRM provides a pathway to a more interpretable, transparent, and trustworthy evaluation of MLLMs. By re-framing visual benchmarks as diagnostic probes, our framework highlights that future progress should be measured not only by the correctness of answers but also by the fidelity of reasoning traces to visual evidence, emphasizing the importance of models that reason as reliably as they perform.

5 Limitations

While our study advances step-level visual reasoning, it has four key limitations. The study relies on the clean, well-annotated **VisArgs** dataset ((Zhang et al., 2024)), which may not truly reflect noisy real-world images very well. CRM is a diagnostic, not a corrective study, so it identifies flaws but doesn't solve the reasoning problems. The scope of the study is also restricted to static images, with richer temporal dynamics in video left for future work. Lastly, random masking might not be a sufficient way to find unimportant regions, as they can still overlap with semantically relevant content, so further analysis is needed to find unimportant regions.

Ethics Statement

We use a publicly available image dataset in compliance with its license. We acknowledge the environmental impact associated with GPU usage. The system generates text from images, which may reflect biases or lead to misuse. We encourage responsible use and careful consideration in deployment.

References

Meta AI. 2024. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Chris Hallacy Aditya Ramesh Gabriel Goh Sandhini Agarwal Girish Sastry Amanda Askell Pamela Mishkin Jack Clark Gretchen Krueger Ilya Sutskever Alec Radford, Jong Wook Kim. 2021. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*.

Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, Binyuan Hui, Luo Ji, Mei Li, Junyang Lin, Runji Lin, Dayiheng Liu, Gao Liu, Chengqiang Lu, Keming Lu, and 29 others. 2023. Qwen technical report. *arXiv preprint arXiv:2309.16609*.

Davide Caffagni, Federico Cocchi, Luca Barsellotti, Nicholas Moratelli, Sara Sarto, Lorenzo Baraldi, Marcella Cornia, and Rita Cucchiara. 2024. The revolution of multimodal large language models: A survey. In *Findings of the Association for Computational Linguistics: ACL*, pages 13590–13618.

Hong-You Chen, Zhengfeng Lai, Haotian Zhang, Xinze Wang, Marcin Eichner, Keen You, Meng Cao, Bowen

Zhang, Yinfei Yang, and Zhe Gan. 2024. Contrastive localized language-image pre-training. *arXiv preprint arXiv:2410.02746*.

Yunkai Dang, Kaichen Huang, Jiahao Huo, and *et al.* 2024. Explainable and interpretable multimodal large language models: A comprehensive survey. *arXiv preprint*. ArXiv:2412.02104.

Google Gemini Team. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.

Longzhen Han, Awes Mubarak, Almas Baimagambetov, Nikolaos Polatidis, and Thar Baker. 2025. Multimodal large language models: A survey. *arXiv preprint*. ArXiv:2506.10016.

Lei Huang, Shuo Qian, and Zhe Zheng. 2025. Autonomous multimodal reasoning via implicit chain-of-vision. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW, MAR)*.

Yizhang Jin and 1 others. 2024. Efficient multimodal large language models: A survey. *arXiv preprint*. ArXiv:2405.10739.

Seil Kang, Jinyeong Kim, Junhyeok Kim, and Seong Jae Hwang. 2025. See what you are told: Visual attention sink in large multimodal models. *arXiv preprint*. ArXiv:2503.03321.

Xiang Man, Yuchen Zhou, Chen Wang, and Yan Liu. 2025. Argus: Vision-centric reasoning with grounded chain-of-thought. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

OpenAI. 2024. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*.

Nils Reimers and Iryna Gurevych. 2019. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*.

Jian Wang, Rui Zhang, Feng Li, and Lei Xiao. 2025. Vgr: Visual grounded reasoning. *arXiv preprint arXiv:2506.11991*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed H. Chi, Quoc V. Le, and Denny Zhou. 2022. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pages 24824–24837. Curran Associates, Inc.

Jialu Wu, Yue Zhang, Yilun Chen, and et al. 2023. Visual chain-of-thought: Bridging logical gaps with multimodal reasoning. *arXiv preprint arXiv:2309.17421*.

Ming Xu, Yuchen Zhou, Chen Wang, and Yan Liu. 2025. Rsvp: Reasoning segmentation via visual prompting and multimodal chain-of-thought. *arXiv preprint arXiv:2506.04277*.

Shukang Yin, Chaoyou Fu, Sirui Zhao, Ke Li, Xing Sun, Tong Xu, and Enhong Chen. 2023. A survey on multimodal large language models. *arXiv preprint*. ArXiv:2306.13549.

Tao Zhang, Kai Chen, and Bo Liu. 2024. Selective vision is the challenge for visual reasoning: A benchmark for visual argument understanding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*.

Lei Zhong, Florian Rosenthal, Jonas Sicking, Felix Hüger, Tobias Bagdonat, Hannes Gottschalk, and Leon Schwinn. 2025. Focus: Internal mllm representations for efficient fine-grained visual question answering. *arXiv preprint arXiv:2506.21710*.

Denny Zhou, Dale Schuurmans, Xuezhi Wang, and et al. 2023. Multimodal chain-of-thought reasoning in language models. *arXiv preprint arXiv:2302.00923*.