A Simple Approach for Visual Room Rearrangement: 3D Mapping and Semantic Search

Abstract

Physically rearranging objects is an important capability for embodied agents. Visual room rearrangement evaluates an agent's ability to rearrange objects in a room to a desired goal based solely on visual input. We propose a simple yet effective method for this problem: (1) search for and map which objects need to be rearranged, and (2) rearrange each object until the task is complete. Our approach consists of an off-the-shelf semantic segmentation model, voxel-based semantic map, and semantic search policy to efficiently find objects that need to be rearranged. On the AI2-THOR Rearrangement Challenge, our method improves on current state-of-the-art end-to-end reinforcement learning-based methods that learn visual rearrangement policies from 0.53% correct rearrangement to 16.56%, using only 2.7% as many samples from the environment.

1 Introduction

Physically rearranging objects is an everyday skill for humans, but remains a core challenge for embodied agents that assist humans in realistic environments. Natural environments for humans are complex and require generalization to a combinatorially large number of object configurations (Batra et al., 2020a). Generalization in complex realistic environments remains an immense practical challenge for embodied agents, and the rearrangement setting provides a rich test bed for embodied generalization in these environments. The rearrangement setting combines two challenging perception and control tasks: (1) understanding the state of a dynamic 3D environment, and (2) acting over a long horizon to reach a goal. These problems have traditionally been studied independently by the vision and reinforcement learning communities (Chaplot et al., 2021), but the advent of large models and challenging benchmarks is showing that both components are important for embodied agents.

Reinforcement learning (RL) can excel at embodied tasks, especially if a lot of experience can be leveraged (Weihs et al., 2021; Chaplot et al., 2020b; Ye et al., 2021) for training. In a simulated environment with unlimited retries, this experience is cheap to obtain, and agents can explore randomly until a good solution is discovered by the agent. This pipeline works well for tasks like point-goal navigation (Wijmans et al., 2020), but in some cases this strategy is not enough. As the difficulty of embodied learning tasks increases, the agent must generalize to an increasing number of environment configurations, and broadly scaled experience can become insufficient.

In the rearrangement setting, a perfect understanding of the environment simplifies the problem: an object is here, it should go there, and the rest can be solved with grasping and planning routines. Representing the information about the locations and states of objects in an accessible format is therefore an important contribution for the rearrangement setting. Our initial experiments suggest that accurate 3D semantic maps of the environment are one such accessible format for visual rearrangement. With accurate 3D semantic maps, our method rearranges 15.11% of objects correctly, and requires significantly less experience from the environment to do so. While end-to-end RL requires up to 75 million environment steps in Weihs et al. (2021), our method only requires 2 million samples and trains offline. Our results suggest end-to-end RL without an accurate representation of the scene may be missing out on a fundamental aspect of understanding of the environment.

We demonstrate how semantic maps help agents effectively understand dynamic 3D environments and perform visual rearrangement. These dynamic environments have elements that can move (like furniture), and objects with changing states (like the door of a cabinet). We present a method that builds accurate semantic maps in these dynamic environments, and reasons about what has changed.

Figure 1: Our method incrementally builds voxel-based *Semantic Maps* from visual observations and efficiently finds objects using a *Semantic Search Policy*. We visualize an example rearrangement on the right with the initial position of the pink object (laptop on the bed), followed by the agent holding the object (laptop), and finally the destination position of the object (laptop on the desk).

Deviating from prior work that leverages end-to-end RL, we propose a simple approach for visual rearrangement: (1) search for and map which objects need to be rearranged, and (2) procedurally rearrange objects until a desired goal configuration is reached. We evaluate our approach on the AI2-THOR Rearrangement Challenge (Weihs et al., 2021) and establish a new state-of-the-art.

We propose an architecture for visual rearrangement that builds voxel-based semantic maps of the environment and rapidly finds objects using a search-based policy. Our method shows an improvement of 14.72 absolute percentage points over current work in visual rearrangement, and is robust to the accuracy of the perception model, the budget for exploration, and the size of objects being rearranged. We conduct ablations to diagnose where the bottlenecks are for visual rearrangement, and find that accurate scene understanding is the most crucial. As an upper bound, when provided with a perfect semantic map, our method solves 38.33% of tasks, a potential for significant *out-of-the-box* gains as better perception models are developed. Our results show the importance of building effective scene representations for embodied agents in complex and dynamic visual environments.

2 RELATED WORK

Embodied 3D Scene Understanding.   Knowledge of the 3D environment is at the heart of various tasks for embodied agents, such as point navigation (Anderson et al., 2018a), image navigation (Batra et al., 2020b; Yang et al., 2019), vision language navigation (Anderson et al., 2018b; Shridhar et al., 2020), embodied question answering (Gordon et al., 2018; Das et al., 2018), and more. These tasks require an agent to reason about its 3D environment. For example, vision language navigation (Anderson et al., 2018b; Shridhar et al., 2020) requires grounding language in an environment goal, and reasoning about where to navigate and what to modify in the environment to reach that goal. Reasoning about the 3D environment is especially important for the rearrangement setting, and has a rich interdisciplinary history in the robotics, vision, and reinforcement learning communities.

Visual Room Rearrangement.   Rearrangement has long been one of the fundamental tasks in robotics research (Ben-Shahar & Rivlin, 1996; Stilman et al., 2007; King et al., 2016; Krontiris & Bekris, 2016; Yuan et al., 2018; Correll et al., 2018; Labbé et al., 2020). Typically, these methods address the challenge in the context of the state of the objects being fully observed (Cosgun et al., 2011; King et al., 2016), which allows for efficient and accurate planning-based solutions. In contrast, there has been recent interest in visual rearrangement (Batra et al., 2020a; Weihs et al., 2021; Qureshi et al., 2021; Goyal et al., 2022; Gadre et al., 2022) where the states of objects and the rearrangement goal are not directly observed. In these cases, the agent is provided a direct visual input, and the environment is relatively complex and realistic. This latest iteration of rearrangement shares similarity with various other challenging embodied AI tasks such as embodied navigation (Anderson et al., 2018a; Batra et al., 2020b; Chaplot et al., 2020a; Shridhar et al., 2020; Francis et al., 2021; Min et al., 2021; Pashevich et al., 2021; Singh et al., 2021) and embodied question answering (Gordon et al., 2018; Das et al., 2018), which require finding objects and reasoning about their state.

AI2-THOR Rearrangement Challenge. Our work builds on the latest rearrangement methods and demonstrates how building accurate voxel-based semantic maps can produce significant gains. We focus on the AI2-THOR Rearrangement Challenge (Weihs et al., 2021), which uses AI2-THOR, an open-source and high-fidelity simulator used in many prior works (Gadre et al., 2022; Weihs et al., 2021; Shridhar et al., 2020; Gordon et al., 2018). Prior works on this challenge have studied a variety of approaches, including end-to-end RL in Weihs et al. (2021), and a planning-based approach in Gadre et al. (2022). Our approach is the first to use voxel-based semantic maps to infer what to rearrange from an experience goal as described by Batra et al. (2020a). Though both Gadre et al. (2022) and our method use planning, Gadre et al. (2022) use a graph-based continuous scene representation, and we use voxel-based semantic maps instead, which we show is more effective.

3D Mapping & Search. Agents that interact with an embodied world through navigation and manipulation must keep track of the world (mapping) (Thrun, 2002) and themselves (localization) (Thrun et al., 2001)—both extensively studied in robotics by processing low-level information (Engel et al., 2014), building semantic maps (Kuipers & Byun, 1991) and more recently, via techniques specifically developed to handle dynamic and general aspects of the environment (Rünz & Agapito, 2017; Rosinol et al., 2021; Wong et al., 2021). When semantics are more important than precision, such as for embodied learning tasks, recent methods have looked at neural network-based maps (Gupta et al., 2017; Chen et al., 2019; Wu et al., 2019a; Chaplot et al., 2020b; Blukis et al., 2021; Chaplot et al., 2021). Our method builds on these and adopts the use of a voxel-based semantic map and pretrained semantic segmentation model—a similar methodological setup to Chaplot et al. (2021); Min et al. (2021); Blukis et al. (2021). However, our method diverges from these prior works by using multiple voxel-based semantic maps to infer what to rearrange from an experience goal as described by Batra et al. (2020a). These prior works have instead considered geometric goals in Chaplot et al. (2021) and language goals in Min et al. (2021); Blukis et al. (2021), and ours is the first to consider an experience goal (Batra et al., 2020a). Furthermore, while a search-based policy is used in Min et al. (2021), we are the first to use search with an unspecified destination (the target object is not known a priori).

3 METHODOLOGY

In this section, we present a simple approach for solving visual rearrangement problems. We begin the section by discussing the visual rearrangement problem statement and metrics we use for evaluation. We then discuss our methodological contributions. First, we propose to build multiple voxel-based semantic maps representing the environment in different configurations. Second, we propose a policy that efficiently finds objects that need to be rearranged. Third, we propose a method for inferring the rearrangement goal from two semantic maps to efficiently solve visual rearrangement tasks.

Visual rearrangement definition and evaluation metrics. Consider the rearrangement setting defined by Batra et al. (2020a), which is a special case of a Markov Decision Process (MDP) augmented with a goal specification $g = \phi(s_0, S^*)$. This goal specification encodes the set of states S^* for which the rearrangement task is considered solved from initial state s_0. The agent typically does not directly observe the set of goal states S^*, and this is reflected by the goal specification function $\phi : S \times 2^S \longrightarrow \mathcal{G}$. We consider a setting where the rearrangement goal g is specified visually and the agent initially observes the environment in its goal configuration. This setting is especially challenging because the agent must remember what the environment initially looked like to infer the set of goal states. Once the goal has been understood and rearrangement has been attempted, we evaluate agents using metrics introduced by Weihs et al. (2021). We consider a *Success* metric that measures the proportion of tasks for which the agent has correctly rearranged all objects and misplaced none during rearrangement. This metric is strict in the sense that an agent receives a success of 0.0 if at least one object is misplaced—even if all others are correctly rearranged. We consider an additional *%Fixed Strict* metric that measures the proportion of objects per task correctly rearranged, equal to 0.0 per task if any were misplaced. This second metric is more informative regarding how close the agent was to solving each task. Effective agents will correctly rearrange all objects in the scene to their goal configurations, maximizing their *Success* and *%Fixed Strict*.

Building two semantic maps. Our approach builds off recent work that uses voxel-based semantic maps in embodied settings (Min et al., 2021; Chaplot et al., 2021). Our work differs from these in that we use multiple voxel-based semantic maps to encode both the goal state and current state of the

Figure 2: Overview of our method for an example task. Our method incrementally builds voxel-based *Semantic Maps* from visual observations. Our *Semantic Search Policy* helps build accurate maps by selecting navigation goals to efficiently find objects that need to be rearranged. Once accurate maps are built, our method compares the *Semantic Maps* to identify disagreements between the maps, and rearranges objects to resolve those disagreements using a deterministic rearrangement policy.

environment. In particular, we build two semantic maps $m_0, m_1 \in \mathcal{R}^{H \times W \times D \times C}$ that represent 3D grids with $H \times W \times D$ voxels. Each voxel is represented with a categorical distribution on C classes encoding which class is likely to occupy each voxel. Empty voxels are assigned the zero vector. In an initial observation phase for each task, our agent navigates the scene and builds m_0, a semantic map encoding the goal configurations for objects in the scene. Likewise, in a second interaction phase, our agent navigates the scene and builds m_1, a semantic map encoding the current state of objects in the scene. At every timestep during each phase, pose, RGB, and depth images are observed, and either m_0 or m_1 is updated depending on which instance of the scene the agent is currently observing.

Incorporating semantic predictions in the maps. Each semantic map is initialized to all zeros and, at every timestep t, semantic predictions from Mask R-CNN (He et al., 2017) are added to the map. Given the RGB image observation I_t, we generate semantic predictions from Mask R-CNN consisting of the probability of each pixel belonging to a particular class. We filter these predictions to remove those with a detection confidence lower than 0.9 and conduct an ablation in Section 4.3. We follow Chaplot et al. (2021) and generate an egocentric point cloud c_t^{ego} using the depth observation D_t. Each point in this point cloud is associated with a pixel in the image I_t and a vector of class probabilities from Mask R-CNN. Given the current pose x_t, we then transform the egocentric point cloud c_t^{ego} from the agent's coordinate system to world coordinate system. This transformation results in a geocentric point cloud c_t^{geo} that is converted to a geocentric voxel representation $v_t^{geo} \in \mathcal{R}^{H \times W \times D \times C}$ of the same cardinality as the semantic maps. We additionally generate a voxelized mask $v_t^{mask} \in \mathcal{R}^{H \times W \times D \times 1}$ that equals one for every occupied voxel in v_t^{geo} and zero otherwise. New semantic predictions are added to the maps with a moving average.

$$m_i[t+1] = m_i[t] \odot (1 - v_t^{mask}(1 - \epsilon)) + v_t^{geo}(1 - \epsilon) \tag{1}$$

The update in Equation 1 allows voxels to be updated at different rates depending on how frequently they are observed. The hyperparameter $\epsilon \in (0, 1)$ controls how quickly the semantic maps are updated to account for new semantic predictions, and is set to 0.5 in our experiments. An overview of how our two semantic maps are built is shown in Figure 2. We've detailed how the semantic maps are constructed from observations, and we will next describe how navigation goals are selected.

Locating objects with a search-based policy. Building accurate maps requires locating and observing every object in the scene so they can be added to the maps. This requires intelligently selecting navigation goals based on where objects are likely to be. We learn a high-level policy $\pi_\theta(\mathbf{x}|m_i)$ that builds off recent work in Min et al. (2021); Chaplot et al. (2021) and parameterizes a distribution over 3D search locations in the environment. The input to the policy is a 3D semantic

---

Algorithm 1 3D Mapping and Semantic Search For Visual Rearrangement

---

Require: visual rearrangement environment e, initial voxel-based semantic maps $m_0, m_1 \in \mathcal{R}^{H \times W \times D \times C}$, search-based policy $\pi_\theta(\mathbf{x}|m)$, pre-trained semantic segmentation model g
  for each phase $i \in \{0, 1\}$ **do**
    for each I_t, D_t, x_t observed **do**
      $v_t^{geo}, v_t^{mask} \leftarrow$ project($g(I_t), D_t, x_t$)   ▷ project to voxels
      $m_i[t] \leftarrow m_i[t-1] \odot (1 - v_t^{mask}(1-\epsilon)) + v_t^{geo}(1-\epsilon)$ ▷ update map
      if goal is reached or goal does not exist **then**
        goal $\sim \pi_\theta(\mathbf{x}|m_i[t])$ ▷ emit a semantic search goal
      end if
      navigate to goal
    end for
  end for
  while a disagreement d between m_0 and m_1 is detected **do**
    navigate to d in m_1 and rearrange d to match m_0
  end while

---

map m_i from whichever phase is currently active. The policy is a 5-layer 2D convolutional neural network that processes a 3D semantic map m_i and outputs a categorical distribution over voxels in m_i, corresponding to 3D search locations. The policy is trained using maximum likelihood training with an expert distribution $p^*(\mathbf{x})$ that captures the locations of the K objects the agent should rearrange in the current scene. This expert distribution in Equation 2 is a Gaussian mixture model with a mode centered at the location μ_k of each object, and a variance hyperparameter σ^2 for each mode.

$$p^*(\mathbf{x}) \propto \frac{1}{K} \sum_{k=1}^{K} \mathcal{N}(\mathbf{x}; \mu_k, \sigma^2 I) \tag{2}$$

Once a policy $\pi_\theta(\mathbf{x}|m_i)$ is trained that captures a semantic prior for object locations, we use planning to reach goals sampled from the policy. We build a planar graph that represents traversable space derived from voxel occupancy in the semantic map, and use Dijkstra's algorithm (Dijkstra, 1959) to find the shortest path from the agent's current location to the goal. We filter navigation goals to ensure only feasible goals are sampled, and then allow sufficient time for each navigation goal to be reached. Once the current goal is reached, we sample another goal and call the planner again.

Inferring the rearrangement goal from the maps. Once two semantic maps are built, we compare them to extract differences in object locations, which we refer to as map disagreements. These disagreements represent objects that need to be rearranged by the agent. To locate disagreements, we first use OpenCV (Bradski, 2000) to label connected voxels of the same class as object instances. We consider voxels with nonzero probability of class c to contain an instance of that class. Object instances are then matched between phases by taking the assignment of object instances that minimizes the difference in appearance between instances of the same class. We leverage the Hungarian algorithm (Kuhn & Yaw, 1955), and represent appearance by the average color of an object instance in the map. Once objects are matched, we label pairs separated by > 0.05 meters as disagreements. Given a set of map disagreements $\{(x_1, x_1^*), (x_2, x_2^*), \ldots, (x_N, x_N^*)\}$ represented by the current pose x_i and goal pose x_i^* for each object, we leverage a planning-based rearrangement policy to solve the task. Our rearrangement policy navigates to each object in succession and transports them to their goal location. By accurately mapping with a search-based policy, inferring the rearrangement goal, and planning towards the goal, our method in Algorithm 1 efficiently solves visual rearrangement.

4 EXPERIMENTS

In this section we evaluate our approach and show its effectiveness. We first evaluate our approach on the AI2-THOR Rearrangement Challenge Weihs et al. (2021) and show our approach leads to an improvement of 14.72 absolute percentage points over current work, detailed in Subsection 4.1. This benchmark tests an agent's ability to rearrange rooms to a desired object goal configuration, and is a suitable choice for measuring visual rearrangement performance. Next, we show the importance

Table 1: Evaluation on the 2022 AI2-THOR 2-Phase Rearrangement Challenge. Our method attains state-of-the-art performance on this challenge, outperforming prior work by 875% *%Fixed Strict*. Results are averaged over 1000 rearrangement tasks in each of the 2022 validation set and 2022 test set. Higher is better. A *Success* of 100.0 indicates all objects are successfully rearranged if none are misplaced and 0.0 otherwise. The metric *%Fixed Strict* is more lenient, equal to the percent of objects that are successfully rearranged if none are newly misplaced, and 0.0 otherwise.

	Validation		Test	
Method	**%Fixed Strict**	**Success**	**%Fixed Strict**	**Success**
VRR + Map (Weihs et al., 2021)	1.18	0.40	0.53	0.00
CSR (Gadre et al., 2022)	3.30	1.20	1.90	0.40
Ours w/o Semantic Search	15.77	4.30	+795% 15.11	+900% 3.60
Ours	**17.47**	**6.30**	+871% **16.56**	+1175% **4.70**

of each proposed component, and demonstrate in Subsection 4.2 our voxel-based map and search-based policy exhibit large potential gains as more performant models for perception and search are developed in the future. Finally, we show in Subsection4.3 our approach is robust to the quality of object detections and budget for exploration.

Description of the benchmark. In this benchmark, the goal is to rearrange up to five objects to a desired state, defined in terms of object locations and openness. The challenge is based on the RoomR (Weihs et al., 2021) dataset that consists of a training set with 80 rooms and 4000 tasks, validation set with 20 rooms and 1000 tasks, and a test set with 20 rooms and 1000 tasks. We consider a two-phase setting where an agent observes the goal configuration of the scene during an initial *Walkthrough Phase*. The scene is then shuffled, and the agent is tasked with rearranging objects back to their goal configuration during a second *Unshuffle Phase*. This two-phase rearrangement setting is challenging because it requires the agent to remember the scene layout from the *Walkthrough Phase*, to identify the rearrangement goal. Goals are internally represented by a set of valid object poses $S^* \subset (\mathcal{R}^3 \times SO(3)) \times (\mathcal{R}^3 \times SO(3)) \cdots \times (\mathcal{R}^3 \times SO(3))$, but the agent does not observe S^* directly. At every time step t during either phase, the agent observes a geocentric pose x_t, an egocentric RGB image I_t, and an egocentric depth image D_t. The rearrangement goal is specified indirectly via observations of the scene layout during the *Walkthrough Phase*. During training, additional metadata is available such as ground-truth semantic labels, but during evaluation only the allowed observations x_t, I_t and D_t can be used. Once both the *Walkthrough Phase* and *Unshuffle Phase* are complete, we measure performance using the *%Fixed Strict* and *Success* metrics described in Section 3.

4.1 EFFECTIVENESS AT VISUAL REARRANGEMENT

We report performance in Table 1 and show an improvement in *%Fixed Strict* from 1.9 to 15.11 over the current state-of-the-art method, namely Continuous Scene Representations (CSR) (Gadre et al., 2022). These results show our method is more effective than prior work at visual rearrangement. Our success of 4.63% on the test set indicates our method solves 46 / 1000 tasks, whereas the best existing approach, CSR, solves 4 / 1000 tasks. Furthermore, our method correctly rearranges 499 / 3004 objects in the test set, while the best existing approach, CSR, rearranges only 57 / 3004 objects in the test set.

The results in Table 1 support two conclusions. First, 3D Mapping is a helpful inductive bias. Ours is currently the only method on the challenge to leverage 3D Mapping for identifying rearrangement goals. The next best approach, CSR Gadre et al. (2022), represents the scene with a graph, where nodes encode objects, and edges encode spatial relationships. We speculate determining which objects need to be rearranged benefits from knowing their fine-grain 3D position, which our method directly represents via semantic maps. Second, these results also suggest that our method more successfully rearranges small objects. This is important (see additional results in Subsection 4.5) because many common objects humans use are small—cutlery, plates, cups, etc.

Table 2: Ablation of the importance of each component of our method. Our method produces significant gains as perception and search models become more accurate. Results are averaged over 1000 rearrangement tasks in each of the 2022 validation set and 2022 test set. As in Table 1, higher is better, and a *Success* of 100.0 indicates all objects are successfully rearranged if none are misplaced and 0.0 otherwise. Our results show that as perception and search models continue to improve with future research, we have an *out-of-the-box* improvement of 34.73 *Success* on the test set.

	Validation		Test	
Method	**%Fixed Strict**	**Success**	**%Fixed Strict**	**Success**
CSR + GT T	3.80	1.30	2.10	0.70
CSR + GT BT	7.90	3.00	5.90	2.20
CSR + GT MBT	26.00	8.80	27.00	10.00
Ours + GT Semantic Search	21.24	7.60	+942% 19.79	+871% 6.10
Ours + GT Segmentation	66.66	45.60	+1004% 59.29	+1707% 37.55
Ours + GT Both	**68.46**	**48.60**	+1008% **59.50**	+1742% **38.33**

4.2 COMPONENT ABLATION

The goal of this experiment is to determine the importance of each component to our method. We consider a series of ablations in Table 2 that replace different components of our method with ground truth predictions. We first consider *Ours + GT Semantic Search*, where we substitute the predictions of our search-based policy π_θ with the ground truth locations of objects that need to be rearranged. We also consider *Ours + GT Segmentation*, where we substitute the predictions of Mask R-CNN (He et al., 2017) with ground truth semantic segmentation labels. The final ablation in the table *Ours + GT Both* includes both substitutions at once. In addition to reporting our performance, we reference the performance of CSR (Gadre et al., 2022) in a similar set of ablations. We consider *CSR + GT T* which uses expert trajectories that observe all objects needing to be rearranged, *CSR + GT BT* which also uses ground truth object detection labels, and *CSR + GT MBT* which additionally uses ground truth object instance pairs between the *Walkthrough Phase* and the *Unshuffle Phase*. Table 2 shows our method produces a better *out-of-the-box* improvement in all metrics as the perception and search components become more accurate, suggesting both components are important.

Table 2 demonstrates our method produces significant gains when paired with accurate semantic search and accurate semantic segmentation. When using ground-truth semantic segmentation labels and ground-truth search locations, our method attains an improvement of 35.35 absolute percentage points in *Success* compared to existing work given access to the same experts. *CSR + GT BT* makes the same assumptions as our method with both components replaced with ground-truth, and is used to compute this improvement margin. When prior work is given the *additional* accommodation of ground-truth object instance pairs between the two environment phases, *CSR + GT MBT*, our method maintains an improvement of 27.55 absolute *Success* points without the accommodation. These results show our method has greater room for improvement than prior work, with a %Fixed Strict 32.50 absolute percentage points higher than current work. Our method's room for improvement with more accurate perception and search models is appealing because accurate 3D vision models are an active area of research, and our method directly benefits from innovations in these models.

4.3 STABILITY VERSUS PERCEPTION QUALITY

In the previous sections, we evaluated our method's effectiveness at rearrangement, and room for growth as better perception and search models are developed. This direct benefit from improvements in perception quality resulting from better models is desireable, but an effective method should also be robust when perception quality is poor. In this section, we evaluate our method's performance stability as a function of the quality of object detections. We simulate changes in object detection quality by varying the detection confidence threshold of Mask R-CNN (He et al., 2017) described in Section 3. A low threshold permits accepting detections where Mask R-CNN makes high-variance predictions, reducing the quality of detections overall. In the following experiment, we vary the detection confidence threshold on the validation and test sets of the rearrangement challenge.

Figure 3: Rearrangement performance versus perception quality. Dark colored lines represent the average metric across 1000 tasks, and shaded regions correspond to a 68% confidence interval. Lower *Num Newly Misplaced* (left plot) is better, higher *%Fixed Strict* (center plot) and *Success* (right plot) are better. Our method improves smoothly as perception quality increases, simulated by varying the detection confidence threshold used to filter Mask R-CNN predictions detailed in Section 3.

Figure 3 shows our method is robust to small changes in perception quality. As the detection confidence increases, simulating an improvement in object detection fidelity, performance of our method smoothly increases. Peak performance with our method on the validation set is attained with a detection confidence threshold close to 0.9, which is the value we employ throughout the paper. Error bars in this experiment are computed using a 68% confidence interval with 1000 sample points, corresponding to 1000 tasks in each of the validation and test sets. The small width of error bars indicates the observed relationship between perception quality and performance most likely holds for tasks individually (not just on average), supporting the conclusion our method is robust to small changes in perception quality. We make a final observation that as perception quality increases, fewer objects are misplaced as our method more accurately infers the rearrangement goal. These results suggest our method produces consistent gains in rearrangement as perception models improve.

4.4 STABILITY VERSUS EXPLORATION BUDGET

We conduct an ablation in this section to evaluate how the exploration budget affects our method. This is important because the conditions an agent faces in the real world vary, and an effective agent must be robust when the budget for exploring the scene is small. We simulate a limited exploration budget by varying the amount of navigation goals used by the agent when building the semantic maps. A lower budget results in fewer time steps spent building the semantic maps, and fewer updates to voxels described in Section 3. With fewer updates, sampling goals intelligently is crucial to ensure the agent has the information necessary to infer the task rearrangement goal.

Figure 4 shows our method is robust when the exploration budget is small. Performance is stable when less than 5 navigation goals are proposed by our semantic search module, where no penalty in *%Fixed Strict* and *Success* can be observed. This result confirms the effectiveness of semantic search: sampled goals correspond to the locations of objects likely to need rearrangement, so even when the budget is small, these objects are already observed. The experiment also shows that as the budget decreases, fewer objects are misplaced. This is intuitive because when the budget is small, fewer objects in the environment are observed and added to the map, reducing the chance of incorrect map disagreements being proposed. Additionally, when the budget is large, the agent spends the majority of the episode in navigation, and may not have enough time left to correct map disagreements, resulting in slightly lower overall performance. These results suggest our method is effective for a variety of exploration budgets, and is robust when the budget is small.

4.5 FAILURE MODES

Our previous experiments showed instances where our method is effective, but an understanding of its limitations is equally important. The goal of this subsection is to identify how and why our method can fail. To accomplish this, we conduct an ablation to study how three indicators—object size, distance to the goal position, and amount of nearby clutter—affect our method. These capture different aspects of what makes rearrangement hard. For example, small objects can be ignored, objects distant to their goal can be easier to misplace, and objects too close to one another can be

Figure 4: Rearrangement performance versus navigation budget. Dark colored lines represent the average metric across 1000 tasks, and shaded regions correspond to a 68% confidence interval. Lower *Num Newly Misplaced* (left plot) is better, higher *%Fixed Strict* (center plot) and *Success* (right plot) is better. Our method performs well even when the number of navigation goals is small and maintains a performance gain over prior work for all sizes of the budget, from one navigation goal (x-axis left) to 15 navigation goals (x-axis right).

mis-detected. We measure the performance of our method with respect to these indicators in Figure 6 in Appendix B, and analyze the experimental conditions when our method is less effective.

Our results illuminate what kinds of tasks are difficult for our method. We find experimentally that objects further from the rearrangement goal are harder for our method to successfully rearrange. Objects within 0.326 meters of the goal are correctly rearranged $>30\%$ of the time, whereas objects further than 4.157 meters from the goal are only correctly rearranged $<20\%$ of the time. One explanation for this disparity in performance could be matching object instances between phases is more difficult when those instances are further apart. Better perception models can mitigate this explanation by providing more information about object appearance that may be used to accurately pair instances. While this first observation is intuitive, our second is more surprising. We find that our method rearranges small objects as effectively as large objects, suggesting our method is robust to the size of objects it rearranges. This quality is desireable because realistic environments contain objects in a variety of sizes. Effective agents should generalize to a variety of object sizes.

5 CONCLUSION

We presented a simple modular approach for rearranging objects to desired visual goals. Our approach leverages a voxel-based semantic map containing objects detected by a perception model, and a semantic-search policy for efficiently locating the objects to rearrange. Our approach generalizes to rearrangement goals of varying difficulties, including objects that are small in size, far from the goal, and in cluttered spaces. Furthermore, our approach is efficient, performing well even with a small exploration budget. Our experimental evaluation shows our approach improves over current work in rearrangement by 14.7 absolute percentage points, and continues to improve smoothly as better models are developed and the quality of object detections increases. Our results confirm the efficacy of active perceptual mapping for the rearrangement setting, and motivate several future directions that can expand the flexibility and generalization of the method.

One limitation of the rearrangement setting in this work is that objects only have simple states: position, orientation, and openness. Real objects are complex and have states that may change over time, potentially from interactions not involving the agent. Investigating tasks that require modelling these dynamic objects in the map is an emerging topic that can benefit from new benchmarks and methods. Another promising future direction is using an agent's experience to improve its perception. Feedback from the environment, including instructions, rewards, and transition dynamics, provides rich information about how to improve perception when true labels may be difficult to acquire. Investigating how to leverage all sources of feedback available to an agent is a useful research topic that may unlock better generalization for embodied agents in dynamic environments.

REFERENCES

Peter Anderson, Angel Chang, Devendra Singh Chaplot, Alexey Dosovitskiy, Saurabh Gupta, Vladlen Koltun, Jana Kosecka, Jitendra Malik, Roozbeh Mottaghi, Manolis Savva, and Amir R. Zamir. On

evaluation of embodied navigation agents. *arXiv:1807.06757*, 2018a.

Peter Anderson, Qi Wu, Damien Teney, Jake Bruce, Mark Johnson, Niko Sünderhauf, Ian D. Reid, Stephen Gould, and Anton van den Hengel. Vision-and-language navigation: Interpreting visually-grounded navigation instructions in real environments. In *CVPR*, 2018b.

Dhruv Batra, Angel X Chang, Sonia Chernova, Andrew J Davison, Jia Deng, Vladlen Koltun, Sergey Levine, Jitendra Malik, Igor Mordatch, Roozbeh Mottaghi, et al. Rearrangement: A challenge for embodied ai. *arXiv:2011.01975*, 2020a.

Dhruv Batra, Aaron Gokaslan, Aniruddha Kembhavi, Oleksandr Maksymets, Roozbeh Mottaghi, Manolis Savva, A. Toshev, and Erik Wijmans. Objectnav revisited: On evaluation of embodied agents navigating to objects. *arXiv:2006.13171*, 2020b.

Ohad Ben-Shahar and Ehud Rivlin. Practical pushing planning for rearrangement tasks. *ICRA*, 1996.

Valts Blukis, Chris Paxton, Dieter Fox, Animesh Garg, and Yoav Artzi. A persistent spatial semantic representation for high-level natural language instruction execution. In *CoRL*, 2021.

G. Bradski. The OpenCV Library. *Dr. Dobb's Journal of Software Tools*, 2000.

Devendra Singh Chaplot, Dhiraj Gandhi, Abhinav Gupta, and Ruslan Salakhutdinov. Object goal navigation using goal-oriented semantic exploration. In *NeurIPS*, 2020a.

Devendra Singh Chaplot, Ruslan Salakhutdinov, Abhinav Gupta, and Saurabh Gupta. Neural topological slam for visual navigation. In *CVPR*, 2020b.

Devendra Singh Chaplot, Murtaza Dalal, Saurabh Gupta, Jitendra Malik, and Ruslan Salakhutdinov. SEAL: self-supervised embodied active learning using exploration and 3d consistency. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *NeurIPS*, 2021.

Kevin Chen, Juan Pablo de Vicente, Gabriel Sepulveda, Fei Xia, Alvaro Soto, Marynel Vazquez, and Silvio Savarese. A behavioral approach to visual navigation with graph localization networks. In *RSS*, 2019.

Nikolaus Correll, Kostas E. Bekris, Dmitry Berenson, Oliver Brock, Albert Causo, Kris Hauser, Kei Okada, Alberto Rodriguez, Joseph M. Romano, and Peter R. Wurman. Analysis and observations from the first amazon picking challenge. *IEEE Transactions on Automation Science and Engineering*, 2018.

Akansel Cosgun, Tucker Hermans, Victor Emeli, and Mike Stilman. Push planning for object placement on cluttered table surfaces. In *IROS*, 2011.

Abhishek Das, Samyak Datta, Georgia Gkioxari, Stefan Lee, Devi Parikh, and Dhruv Batra. Embodied Question Answering. In *CVPR*, 2018.

Edsger W Dijkstra. A note on two problems in connexion with graphs. *Numerische mathematik*, 1959.

Jakob Engel, Thomas Schöps, and Daniel Cremers. Lsd-slam: Large-scale direct monocular slam. In *ECCV*, 2014.

Jonathan Francis, Nariaki Kitamura, Felix Labelle, Xiaopeng Lu, Ingrid Navarro, and Jean Oh. Core challenges in embodied vision-language planning. *arXiv:2106.13948*, 2021.

Samir Yitzhak Gadre, Kiana Ehsani, Shuran Song, and Roozbeh Mottaghi. Continuous scene representations for embodied AI. *arXiv:2203.17251*, 2022.

Daniel Gordon, Aniruddha Kembhavi, Mohammad Rastegari, Joseph Redmon, Dieter Fox, and Ali Farhadi. IQA: Visual question answering in interactive environments. In *CVPR*, 2018.

Ankit Goyal, Arsalan Mousavian, Chris Paxton, Yu-Wei Chao, Brian Okorn, Jia Deng, and Dieter Fox. IFOR: iterative flow minimization for robotic object rearrangement. *CoRR*, abs/2202.00732, 2022. URL https://arxiv.org/abs/2202.00732.

Saurabh Gupta, James Davidson, Sergey Levine, Rahul Sukthankar, and Jitendra Malik. Cognitive mapping and planning for visual navigation. In *CVPR*, 2017.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *2016 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2016, Las Vegas, NV, USA, June 27-30, 2016*, pp. 770–778. IEEE Computer Society, 2016. doi: 10.1109/CVPR.2016.90. URL `https://doi.org/10.1109/CVPR.2016.90`.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross B. Girshick. Mask R-CNN. In *ICCV*, 2017.

Jennifer E King, Marco Cognetti, and Siddhartha S Srinivasa. Rearrangement planning using object-centric and robot-centric action spaces. In *ICRA*, 2016.

A. Krontiris and K. E. Bekris. Efficiently solving general rearrangement tasks: A fast extension primitive for an incremental sampling-based planner. In *ICRA*, 2016.

H. W. Kuhn and Bryn Yaw. The hungarian method for the assignment problem. *Naval Res. Logist. Quart*, 1955.

Benjamin Kuipers and Yung-Tai Byun. A robot exploration and mapping strategy based on a semantic hierarchy of spatial representations. *Robotics and autonomous systems*, 1991.

Yann Labbé, Sergey Zagoruyko, Igor Kalevatykh, Ivan Laptev, Justin Carpentier, Mathieu Aubry, and Josef Sivic. Monte-carlo tree search for efficient visually guided rearrangement planning. *IEEE Robotics and Automation Letters*, 2020.

Tsung-Yi Lin, Piotr Dollár, Ross B. Girshick, Kaiming He, Bharath Hariharan, and Serge J. Belongie. Feature pyramid networks for object detection. In *2017 IEEE Conference on Computer Vision and Pattern Recognition, CVPR 2017, Honolulu, HI, USA, July 21-26, 2017*, pp. 936–944. IEEE Computer Society, 2017. doi: 10.1109/CVPR.2017.106. URL `https://doi.org/10.1109/CVPR.2017.106`.

So Yeon Min, Devendra Singh Chaplot, Pradeep Ravikumar, Yonatan Bisk, and Ruslan Salakhutdinov. FILM: following instructions in language with modular methods. *arXiv:2110.07342*, 2021.

Alexander Pashevich, Cordelia Schmid, and Chen Sun. Episodic transformer for vision-and-language navigation. In *ICCV*, 2021.

Ahmed Hussain Qureshi, Arsalan Mousavian, Chris Paxton, Michael C. Yip, and Dieter Fox. Nerp: Neural rearrangement planning for unknown objects. In Dylan A. Shell, Marc Toussaint, and M. Ani Hsieh (eds.), *Robotics: Science and Systems XVII, Virtual Event, July 12-16, 2021*, 2021. doi: 10.15607/RSS.2021.XVII.072. URL `https://doi.org/10.15607/RSS.2021.XVII.072`.

A. Rosinol, A. Violette, M. Abate, N. Hughes, Y. Chang, J. Shi, A. Gupta, and L. Carlone. Kimera: from SLAM to spatial perception with 3D dynamic scene graphs. *Intl. J. of Robotics Research*, 2021.

Martin Rünz and Lourdes Agapito. Co-fusion: Real-time segmentation, tracking and fusion of multiple objects. In *ICRA*, 2017.

Mohit Shridhar, Jesse Thomason, Daniel Gordon, Yonatan Bisk, Winson Han, Roozbeh Mottaghi, Luke Zettlemoyer, and Dieter Fox. ALFRED: A Benchmark for Interpreting Grounded Instructions for Everyday Tasks. In *CVPR*, 2020.

Kunal Pratap Singh, Suvaansh Bhambri, Byeonghwi Kim, Roozbeh Mottaghi, and Jonghyun Choi. Factorizing perception and policy for interactive instruction following. In *ICCV*. IEEE, 2021.

Mike Stilman, Jan-Ullrich Schamburek, James Kuffner, and Tamim Asfour. Manipulation planning among movable obstacles. In *ICRA*, 2007.

Sebastian Thrun. Robotic mapping: A survey. *Exploring artificial intelligence in the new millennium*, 2002.

Sebastian Thrun, Dieter Fox, Wolfram Burgard, and Frank Dellaert. Robust monte carlo localization for mobile robots. *Artificial Intelligence*, 2001.

Luca Weihs, Matt Deitke, Aniruddha Kembhavi, and Roozbeh Mottaghi. Visual room rearrangement. In *CVPR*, 2021.

Erik Wijmans, Abhishek Kadian, Ari S. Morcos, Stefan Lee, Irfan Essa, Devi Parikh, Manolis Savva, and Dhruv Batra. Dd-ppo: Learning near-perfect pointgoal navigators from 2.5 billion frames. In *ICLR*, 2020.

Yu-Shiang Wong, Changjian Li, Matthias Niessner, and Niloy J. Mitra. Rigidfusion: Rgb-d scene reconstruction with rigidly-moving objects. *Computer Graphics Forum*, 2021.

Yi Wu, Yuxin Wu, Aviv Tamar, Stuart Russell, Georgia Gkioxari, and Yuandong Tian. Bayesian relational memory for semantic visual navigation. In *ICCV*, 2019a.

Yuxin Wu, Alexander Kirillov, Francisco Massa, Wan-Yen Lo, and Ross Girshick. Detectron2. `https://github.com/facebookresearch/detectron2`, 2019b.

Wei Yang, Xiaolong Wang, Ali Farhadi, Abhinav Gupta, and Roozbeh Mottaghi. Visual semantic navigation using scene priors. In *ICLR*, 2019.

Joel Ye, Dhruv Batra, Abhishek Das, and Erik Wijmans. Auxiliary tasks and exploration enable objectnav. *arXiv:2104.04112*, 2021.

Weihao Yuan, Johannes A Stork, Danica Kragic, Michael Y Wang, and Kaiyu Hang. Rearrangement with nonprehensile manipulation using deep reinforcement learning. In *ICRA*, 2018.