ACTION GUIDANCE: GETTING THE BEST OF SPARSE REWARDS AND SHAPED REWARDS FOR REAL-TIME STRATEGY GAMES

ABSTRACT

Training agents using Reinforcement Learning in games with sparse rewards is a challenging problem, since large amounts of exploration are required to retrieve even the first reward. To tackle this problem, a common approach is to use reward shaping to help exploration. However, an important drawback of reward shaping is that agents sometimes learn to optimize the shaped reward instead of the true objective. In this paper, we present a novel technique that we call *action guidance* that successfully trains agents to eventually optimize the true objective in games with sparse rewards while maintaining most of the sample efficiency that comes with reward shaping. We evaluate our approach in a simplified real-time strategy (RTS) game simulator called μRTS.

Training agents using Reinforcement Learning with sparse rewards is often difficult (Pathak et al., 2017). First, due to the sparsity of the reward, the agent often spends the majority of the training time doing inefficient exploration and sometimes not even reaching the first sparse reward during the entirety of its training. Second, even if the agents have successfully retrieved some sparse rewards, performing proper credit assignment is challenging among complex sequences of actions that have led to theses sparse rewards. Reward shaping (Ng et al., 1999) is a widely-used technique designed to mitigate this problem. It works by providing intermediate rewards that lead the agent towards the sparse rewards, which are the true objective. For example, the sparse reward for a game of Chess is naturally +1 for winning, -1 for losing, and 0 for drawing, while a possible shaped reward might be +1 for every enemy piece the agent takes. One of the critical drawbacks for reward shaping is that the agent sometimes learns to optimize for the shaped reward instead of the real objective. Using the Chess example, the agent might learn to take as many enemy pieces as possible while still losing the game. A good shaped reward achieves a nice balance between letting the agent find the sparse reward and being too shaped (so the agent learns to just maximize the shaped reward), but this balance can be difficult to find.

In this paper, we present a novel technique called *action guidance* that successfully trains the agent to eventually optimize over sparse rewards while maintaining most of the sample efficiency that comes with reward shaping. It works by constructing a *main agent* that only learns from the sparse reward function $R_{\mathcal{M}}$ and some *auxiliary agents* that learn from the shaped reward function $R_{\mathcal{A}_1}, R_{\mathcal{A}_2}, \ldots, R_{\mathcal{A}_n}$. During training, we use the same rollouts to train the main and auxiliary agents and initially set a high-probability of the main agent to take *action guidance* from the auxiliary agents, that is, *the main agent will execute actions sampled from the auxiliary agents*. Then the main agent and auxiliary agents are updated via off-policy policy gradient. As the training goes on, the main agent will get more independent and execute more actions sampled from its own policy. Auxiliary agents learn from shaped rewards and therefore make the training sample-efficient, while the main agent learns from the original sparse reward and therefore makes sure that the agents will eventually optimize over the true objective. We can see action guidance as combining reward shaping to train auxiliary agents interleaved with a sort of imitation learning to guide the main agent from these auxiliary agents.

We examine action guidance in the context of a real-time strategy (RTS) game simulator called μRTS for three sparse rewards tasks of varying difficulty. For each task, we compare the performance of training agents with the sparse reward function $R_{\mathcal{M}}$, a shaped reward function $R_{\mathcal{A}_1}$, and action guidance with a singular auxiliary agent learning from $R_{\mathcal{A}_1}$. The main highlights are:

Action guidance is sample-efficient. Since the auxiliary agent learns from $R_{\mathcal{A}_1}$ and the main agent takes action guidance from the auxiliary agent during the initial stage of training, the main agent is more likely to discover the first sparse reward more quickly and learn more efficiently. Empirically, action guidance reaches almost the same level of sample efficiency as reward shaping in all of the three tasks tested.

The true objective is being optimized. During the course of training, the main agent has never seen the shaped rewards. This ensures that the main agent, which is the agent we are really interested in, is always optimizing against the true objective and is less biased by the shaped rewards. As an example, Figure 1 shows that the main agent trained with action guidance eventually learns to win the game as fast as possible, even though it has only learned from the match outcome reward (+1 for winning, -1 for losing, and 0 for drawing). In contrast, the agents trained with reward shaping learn more diverse sets of behaviors which result in high shaped reward.

To support further research in this field, we make our source code available at GitHub[1], as well as all the metrics, logs, and recorded videos[2].

1 RELATED WORK

In this section, we briefly summarize the popular techniques proposed to address the challenge of sparse rewards.

Reward Shaping. Reward shaping is a common technique where the human designer uses domain knowledge to define additional intermediate rewards for the agents. Ng et al. (1999) show that a slightly more restricted form of state-based reward shaping has better theoretical properties for preserving the optimal policy.

Transfer and Curriculum Learning. Sometimes learning the target tasks with sparse rewards is too challenging, and it is more preferable to learn some easier tasks first. *Transfer learning* leverages this idea and trains agents with some easier source tasks and then later transfer the knowledge through value function (Taylor et al., 2007) or reward shaping (Svetlik et al., 2017). *Curriculum learning* further extends transfer learning by automatically designing and choosing a full sequences of source tasks (i.e. a curriculum) (Narvekar & Stone, 2018).

Imitation Learning. Alternatively, it is possible to directly provide examples of human demonstration or expert replay for the agents to mimic via Behavior Cloning (BC) (Bain & Sammut, 1995), which uses supervised learning to learn a policy given the state-action pairs from expert replays. Alternatively, Inverse Reinforcement Learning (IRL) (Abbeel & Ng, 2004) recovers a reward function from expert demonstrations to be used to train agents.

Curiosity-driven Learning. Curiosity driven learning seeks to design *intrinsic* reward functions (Burda et al., 2019) using metrics such as prediction errors (Houthooft et al., 2016) and "visit counts" (Bellemare et al., 2016; Lopes et al., 2012). These intrinsic rewards encourage the agents to explore unseen states.

Goal-oriented Learning. In certain tasks, it is possible to describe a goal state and use it in conjunction with the current state as input (Schaul et al., 2015). Hindsight experience replay (HER) (Andrychowicz et al., 2017) develops better utilization of existing data in experience replay by replaying each episode with different goals. HER is shown to be an effective technique in sparse rewards tasks.

Hierarchical Reinforcement Learning (HRL). If the target task is difficult to learn directly, it is also possible to hierarchically structure the task using experts' knowledge and train hierarchical agents, which generally involves a main agent that learns abstract goals, time, and actions, as well as auxiliary agents that learn primitive actions and specific goals (Dieterich, 2000). HRL is especially popular in RTS games with combinatorial action spaces (Pang et al., 2019; Ye et al., 2020).

The most closely related work is perhaps Scheduled Auxiliary Control (SAC-X) (Riedmiller et al., 2018), which is an HRL algorithm that trains auxiliary agents to perform primitive actions with

---

[1] https://github.com/anonymous-research-code/action-guidance
[2] Blinded for peer review

(a) shaped reward
(https://streamable.com/o797ca)

(b) action guidance
(https://streamable.com/hh7abp)

Figure 1: The screenshot shows the typical learned behavior of agents in the task of DefeatRandomEnemy. (a) shows that an agent trained with some shaped reward function $R_{\mathcal{A}_1}$ learns many helpful behaviors such as building workers (grey circles), combat units (blue circles), and barracks (grey square) or using owned units (with red boarder) to attack enemy units (with blue border), but does not learn to win as fast as possible (i.e. it still does not win at internal time step $t = 6000$). In contrast, (b) shows an agent trained with action guidance optimizes over the match outcome and learns to win as fast as possible (i.e. about to win the game at $t = 440$), with its main agent learning from the match outcome reward function $R_{\mathcal{M}}$ and a singular auxiliary agent learning from the same shaped reward function $R_{\mathcal{A}_1}$. Click on the link below figures to see the full videos of trained agents.

shaped rewards and a main agent to schedule the use of auxiliary agents with sparse rewards. However, our approach differs in the treatment of the main agent. Instead of learning to *schedule* auxiliary agents, our main agent learns to act in the entire action space by *taking action guidance* from the auxiliary agents. There are two intuitive benefits to our approach since our main agent learns in the full action space. First, during policy evaluation our main agent does not have to commit to a particular auxiliary agent to perform actions for a fixed number of time steps like it is usually done in SAC-X. Second, learning in the full action space means the main agent will less likely suffer from the definition of hand-crafted sub-tasks, which could be incomplete or biased.

2   BACKGROUND

We consider the Reinforcement Learning problem in a Markov Decision Process (MDP) denoted as $(S, A, P, \rho_0, r, \gamma, T)$, where S is the state space, A is the discrete action space, $P : S \times A \times S \to [0, 1]$ is the state transition probability, $\rho_0 : S \to [0, 1]$ is the the initial state distribution, $r : S \times A \to \mathbb{R}$ is the reward function, γ is the discount factor, and T is the maximum episode length. A stochastic policy $\pi_\theta : S \times A \to [0, 1]$, parameterized by a parameter vector θ, assigns a probability value to an action given a state. The goal is to maximize the expected discounted return of the policy:

$$\mathbb{E}_\tau \left[\sum_{t=0}^{T-1} \gamma^t r_t \right], \quad \begin{array}{l} \text{where } \tau \text{ is the trajectory } (s_0, a_0, r_0, s_1, \ldots, s_{T-1}, a_{T-1}, r_{T-1}) \\ \text{and } s_0 \sim \rho_0, s_t \sim P(\cdot|s_{t-1}, a_{t-1}), a_t \sim \pi_\theta(\cdot|s_t), r_t = r(s_t, a_t) \end{array}$$

Policy Gradient Algorithms.   The core idea behind policy gradient algorithms is to obtain the *policy gradient* $\nabla_\theta J$ of the expected discounted return with respect to the policy parameter θ. Doing gradient ascent $\theta = \theta + \nabla_\theta J$ therefore maximizes the expected discounted reward. Earlier work proposes the following policy gradient estimate to the objective J (Sutton & Barto, 2018):

$$g_{\text{policy}, \theta} = \mathbb{E}_{\tau \sim \pi_\theta} \left[\sum_{t=0}^{T-1} \nabla_\theta \log \pi_\theta(a_t|s_t) G_t \right],$$

where $G_t = \sum_{k=0}^{\infty} \gamma^k r_{t+k}$ denotes the discounted return following time t. This gradient estimate, however, suffers from large variance (Sutton & Barto, 2018) and the following gradient estimate is suggested instead:

$$g_{\text{policy},\theta} = \mathbb{E}_{\tau}\left[\nabla_{\theta} \sum_{t=0}^{T-1} \log \pi_{\theta}(a_t|s_t) A(\tau, V, t)\right],$$

where $A(\tau, V, t)$ is the General Advantage Estimation (GAE) (Schulman et al., 2015), which measures "how good is a_t compared to the usual actions", and $V : S \to \mathbb{R}$ is the state-value function.

3 ACTION GUIDANCE

The key idea behind *action guidance* is to create a main agent that trains on the sparse rewards, and creating some auxiliary agents that are trained on shaped rewards. During the initial stages of training, the main agent has a high probability to take *action guidance* from the auxiliary agents, that is, the main agent can execute actions sampled from the auxiliary agents, rather than from its own policy. As the training goes on, this probability decreases, and the main agent executes more actions sampled from its own policy. During training, the main and auxiliary agents are updated via off-policy policy gradient. Our use of auxiliary agents makes the training sample-efficient, and our use of the main agent, who only sees its own sparse reward, makes sure that the agent will eventually optimize over the true objective of sparse rewards. In a way, *action guidance* can be seen as training agents using shaped rewards, while having the main agent learn by imitating from them.

Specifically, let us define $\mathcal{M}$ as the MDP that the main agent learns from and $\mathcal{A} = \{\mathcal{A}_1, \mathcal{A}_2, ..., \mathcal{A}_k\}$ be a set of auxiliary MDPs that the auxiliary agents learn from. In our constructions, $\mathcal{M}$ and $\mathcal{A}$ share the same state, observation, and action space. However, the reward function for $\mathcal{M}$ is $R_{\mathcal{M}}$, which is the sparse reward function, and reward functions for $\mathcal{A}$ are $R_{\mathcal{A}_1}, ..., R_{\mathcal{A}_k}$, which are the shaped reward functions. For each of these MDPs $\mathcal{E} \in \mathcal{S} = \{\mathcal{M}\} \cup \mathcal{A}$ above, let us initialize a policy $\pi_{\theta_{\mathcal{E}}}$ parameterized by parameters $\theta_{\mathcal{E}}$, respectively. Furthermore, let us use $\pi_{\mathcal{S}} = \{\pi_{\theta_{\mathcal{E}}} | \mathcal{E} \in \mathcal{S}\}$ to denote the set of these initialized policies.

At each timestep t, let us use some exploration strategy S that selects a policy $\pi_b \in \pi_{\mathcal{S}}$ to sample an action a_t given s_t. At the end of the episode, each policy $\pi_{\theta} \in \pi_{\mathcal{S}}$ can be updated via its off-policy policy gradient (Degris et al., 2012; Levine et al., 2020):

$$\mathbb{E}_{\tau \sim \pi_{\theta_b}}\left[\left(\prod_{t=0}^{T-1} \frac{\pi_{\theta}(a_t|s_t)}{\pi_{\theta_b}(a_t|s_t)}\right) \sum_{t=0}^{T-1} \nabla_{\theta} \log \pi_{\theta}(a_t|s_t) A(\tau, V, t)\right] \tag{1}$$

When $\pi_{\theta} = \pi_{\theta_b}$, the gradient in Equation 1 means on-policy policy gradient update for π_{θ}. Otherwise, the objective means off-policy policy gradient update for π_{θ}.

3.1 PRACTICAL ALGORITHM

The gradient in Equation 1 is unbiased, but its product of importance sampling ratio $\left(\prod_{t=0}^{T-1} \frac{\pi_{\theta}(a_t|s_t)}{\pi_{\theta_b}(a_t|s_t)}\right)$ is known to cause high variance (Wang et al., 2016). In practice, we clip the gradient the same way as Proximal Policy Gradient (PPO) (Schulman et al., 2017):

$$L^{CLIP}(\theta) = \mathbb{E}_{\tau \sim \pi_{\theta_b}}\left[\sum_{t=0}^{T-1}\left[\nabla_{\theta}\min\left(\rho_t(\theta)A(\tau, V, t), \text{clip}\left(\rho_t(\theta), \varepsilon\right)A(\tau, V, t)\right)\right]\right] \tag{2}$$

$$\rho_t(\theta) = \frac{\pi_{\theta}(a_t|s_t)}{\pi_{\theta_b}(a_t|s_t)}, \quad \text{clip}\left(\rho_t(\theta), \varepsilon\right) = \begin{cases} 1 - \varepsilon & \text{if } \rho_t(\theta) < 1 - \varepsilon \\ 1 + \varepsilon & \text{if } \rho_t(\theta) > 1 + \varepsilon \\ \rho_t(\theta) & \text{otherwise} \end{cases}$$

During the optimization phase, the agent also learns the value function and maximize the policy's entropy. We therefore optimize the following joint objective for each $\pi_{\theta} \in \pi_{\mathcal{S}}$:

$$L^{CLIP}(\theta) = L^{CLIP}(\theta) - c_1 L^{VF}(\theta) + c_2 S[\pi_{\theta_b}], \tag{3}$$

where c_1, c_2 are coefficients, S is an entropy bonus, and L^{VF} is the squared error loss for the value function associated with π_{θ} as done by Schulman et al. (2017). Although action guidance can be

configured to leverage multiple auxiliary agents that learn diversified reward functions, we only use one auxiliary agent for the simplicity of experiments. In addition, we use ϵ-greedy as the exploration strategy S for determining the behavior policy. That is, at each timestep t, the behavior policy is selected to be $\pi_{\theta_\mathcal{M}}$ with probability $1 - \epsilon$ and $\pi_{\theta_\mathcal{D}}$ for $\mathcal{D} \in \mathcal{A}$ with probability ϵ (note that is ϵ is different from the clipping coefficient ε of PPO). Additionally, ϵ is set to be a constant 0.95 at start for some period of time steps (e.g. 800,000), which we refer to as the *shift* period (the time it takes to start "shifting" focus away from the auxiliary agents), then it is set to linearly decay to ϵ_{end} for some period of time steps (e.g. 1,000,000), which we refer to as the *adaptation* period (the time it takes for the main agent to fully "adapt" and become more independent).

3.2 Positive Learning Optimization

During our initial experiments, we found the main agent sometimes did not learn useful policies. Our hypothesis is that this was because the main agent is updated with too many trajectories with zero reward. Doing a large quantities of updates of these zero-reward trajectories actually causes the policy to converge prematurely, which is manifested by having low entropy in the action probability distribution.

To mitigate this issue of having too many zero-reward trajectories, we use a preliminary code-level optimization called Positive Learning Optimization (PLO). After collecting the rollouts, PLO works by skipping the gradient update for $\pi_{\theta_\mathcal{E}} \in \pi_\mathcal{S}$ and its value function if the rollouts contains no reward according to $R_\mathcal{E}$. Intuitively, PLO makes sure that the main agent learns from meaningful experience that is associated with positive rewards. To confirm its effectiveness, we provide an ablation study of PLO in the experiment section.

4 Evaluation

We use μRTS[3] as our testbed, which is a minimalistic RTS game maintaining the core features that make RTS games challenging from an AI point of view: simultaneous and durative actions, large branching factors and real-time decision making. To interface with μRTS, we use gym-microrts[4] (Huang & Ontañón, 2020) to conduct our experiments. The details of gym-microrts as a RL interface can be found at Appendix A.1.

4.1 Tasks Description

We examine the three following sparse reward tasks with a range of difficulties. For each task, we compare the performance of training agents with the sparse reward function $R_\mathcal{M}$, a shaped reward function $R_{\mathcal{A}_1}$, and action guidance with a single auxiliary agent learning from $R_{\mathcal{A}_1}$. Here are the descriptions of these environments and their reward functions.

1. LearnToAttack: In this task, the agent's objective is to learn move to the other side of the map where the enemy units live and start attacking them. Its $R_\mathcal{M}$ gives a +1 reward for each valid attack action the agent issues. This is of sparse reward because the action space is so large: the agent could have build a barracks or produce a unit; it is unlikely that the agents will by chance issue lots of moving actions (out of 6 action types) with correct directions (out of 4 directions) and then start attacking. Its $R_{\mathcal{A}_1}$ gives the difference between previous and current Euclidean distance between the enemy base and its closet unit owned by the agent as the shaped reward in addition to $R_\mathcal{M}$.

2. ProduceCombatUnits: In this task, the agent's objective is to learn to build as many combat units as possible. Its $R_\mathcal{M}$ gives a +1 reward for each combat unit the agent produces. This is a more challenging task because the agent needs to learn 1) harvest resources, 2) produce barracks, 3) produce combat units once enough resources are gathered, 4) move produced combat units out of the way so as to not block the production of new combat units. Its $R_{\mathcal{A}_1}$ gives +1 for constructing every building (e.g. barracks), +1 for harvesting resources, +1 for returning resources, and +7 for each combat unit it produces.

---

[3] https://github.com/santiontanon/microrts
[4] https://github.com/vwxyzjn/gym-microrts

3. DefeatRandomEnemy: In this task, the agent's objective is to defeat a biased random bot of which the attack, harvest and return actions have 5 times the probability of other actions. Additionally, the bot subjects to the same gym-microrts' limitation (See Appendix A.2) as the agents used in our experiments. Its $R_{\mathcal{M}}$ gives the match outcome as the reward (-1 on a loss, 0 on a draw and +1 on a win). This is the most difficult task we examined because the agent is subject to the full complexity of the game, being required to make both macro-decisions (e.g. deciding the high-level strategies to win the game) and micro-decisions (e.g. deciding which enemy units to attack. In comparison, its $R_{\mathcal{A}_1}$ gives +5 for winning, +1 for harvesting one resource, +1 for returning resources, +1 for producing one worker, +0.2 for constructing every building, +1 for each valid attack action it issues, +7 for each combat unit it produces, and $+(0.2 * d)$ where d is difference between previous and current Euclidean distance between the enemy base and its closet unit owned by the agent.

4.2 Agent Setup

We use PPO (Schulman et al., 2017) as the base DRL algorithm to incorporate action guidance. The details of the implementation, neural network architecture, hyperparameters, proper handling of μRTS's action space and invalid action masking (Huang & Ontañón, 2020) can be found in Appendix B. We compared the following strategies:

1. **Sparse reward (first baseline).** This agent is trained with PPO on $R_{\mathcal{M}}$ for each task.

2. **Shaped reward (second baseline).** This agent is trained with PPO on $R_{\mathcal{A}_1}$ for each task.

3. **Action guidance - long adaptation.** The agent is trained with PPO + action guidance with $shift = 2,000,000$ time steps, $adaptation = 7,000,000$ time steps, and $\epsilon_{end} = 0.0$

4. **Action guidance - short adaptation.** The agent is trained with PPO + action guidance with $shift = 800,000$ time steps, $adaptation = 1,000,000$ time steps, and $\epsilon_{end} = 0.0$

5. **Action guidance - mixed policy.** The agent is trained with PPO + action guidance with $shift = 2,000,000$ time steps and $adaptation = 2,000,000$ time steps, and $\epsilon_{end} = 0.5$. We call this agent "mixed policy" because it will eventually have 50% chance to sample actions from the main agent and 50% chance to sample actions from the auxiliary agent. It is effectively having mixed agent making decisions jointly.

Although it is desirable to add SAC-X to the list of strategies compared, it was not designed to handle domains with large discrete action spaces. Lastly, we also toggle the PLO option for action guidance - long adaptation, action guidance - short adaptation, action guidance - mixed policy, and sparse reward training strategies for a preliminary ablation study.

4.3 Experimental Results

Each of the 6 strategies is evaluated in 3 tasks with 10 random seeds. We report the results in Table 1. All the learning curves can be found in Appendix C. Below are our observations.

Action guidance is almost as sample-efficient as reward shaping. Since the auxiliary agent learns from $R_{\mathcal{A}_1}$ and the main agent takes a lot of action guidance from the auxiliary agent during the shift period, the main agent is more likely to discover the first sparse reward more quickly and learn more efficiently. As an example, Figure 2 demonstrates such sample-efficiency in ProduceCombatUnits, where the agents trained with sparse reward struggle to obtain the very first reward. In comparison, most action guidance related agents are able to learn almost as fast as the agents trained with shaped reward.

Action guidance eventually optimizes the sparse reward. This is perhaps the most important contribution of our paper. Action guidance eventually optimizes the main agent over the true objective, rather than optimizing shaped rewards. Using the ProduceCombatUnits task as an example, the agent trained with shaped reward would only start producing combat units once all the resources have been harvested, probably because the +1 reward for harvesting and returning resources are easy to retrieve and therefore the agents exploit them first. Only after these resources are exhausted would the agents start searching for other sources of rewards then learn producing combat units.

Figure 2: The faint lines are the actual episode reward of each seed for selected strategies in ProduceCombatUnits; solid lines are their means. The left figure showcase the sample-efficiency of action guidance; the right figure is a motivating example for PLO.

Table 1: The average episode reward (according to $R_\mathcal{M}$) achieved by each training strategy in each task over 10 random seeds.

	LearnToAttack	ProduceCombatUnit	DefeatRandomEnemy
sparse reward (first baseline)	3.30 ± 5.04	0.00 ± 0.01	-0.07 ± 0.03
sparse reward w/ PLO	0.00 ± 0.00	0.00 ± 0.01	-0.05 ± 0.03
shaped reward (second baseline)	10.00 ± 0.00	$\mathbf{9.57 \pm 0.30}$	0.08 ± 0.17
action guidance - long adaptation	$\mathbf{11.00 \pm 0.00}$	8.31 ± 2.62	0.11 ± 0.35
action guidance - long adaptation w/ PLO	$\mathbf{11.00 \pm 0.01}$	6.96 ± 4.04	$\mathbf{0.52 \pm 0.35}$
action guidance - mixed policy	$\mathbf{11.00 \pm 0.00}$	9.67 ± 0.17	0.40 ± 0.37
action guidance - mixed policy w/ PLO	10.67 ± 0.12	9.36 ± 0.35	0.30 ± 0.42
action guidance - short adaptation	$\mathbf{11.00 \pm 0.01}$	2.95 ± 4.48	-0.06 ± 0.04
action guidance - short adaptation w/ PLO	$\mathbf{11.00 \pm 0.00}$	$\mathbf{9.48 \pm 0.51}$	-0.05 ± 0.03

In contrast, the main agent of action guidance - short adaptation w/ PLO are initially guided by the shaped reward agent during the shift period. During the adaptation period, we find the main agent starts to optimize against the real objective by producing the first combat unit as soon as possible. This disrupts the behavior learned from the auxiliary agent and thus cause a visible degrade in the main agent's performance during 1M and 2M timesteps as shown in Figure 2. As the adaption period comes to an end, the main agent becomes fully independent and learn to produce combat units and harvest resources concurrently. This behavior matches the common pattern observed in professional RTS game players and is obviously more desirable because should the enemy attack early, the agent will have enough combat units to defend.

In the DefeatRandomEnemy task, the agents trained with shaped rewards learn a variety of behaviors; some of them learn to do a worker rush while others learn to focus heavily on harvesting resources and producing units. This is likely because the agents could get similar level of shaped rewards despite having diverse set of behaviors. In comparison, the main agent of action guidance - long adaptation w/ PLO would start optimizing the sparse reward after the shift period ends; it almost always learns to do a worker rush, which an efficient way to win against a random enemy as shown in Figure 1.

The hyper-parameters adaptation and shift matter. Although the agents trained with action guidance - short adaptation w/ PLO learns the more desirable behavior, they perform considerably worse in the harder task of DefeatRandomEnemy. It suggests the harder that task is perhaps the longer adaptation should be set. However, in ProduceCombatUnits, agents trained with action guidance - long adaptation w/ PLO exhibits the same category of behavior as agents trained with shaped reward, where the agent would only start producing combat units once all the resources have been harvested. A reasonable explanation is that higher adaptation gives more guidance to the main agents to consistently find the sparse reward, but it also inflicts more bias on how the task should be accomplished; lower adaption gives less guidance but increase the likelihood for the main agents to find better ways to optimize the sparse rewards.

(a) shaped reward
(https://streamable.com/ytpt7u)

(b) action guidance
(https://streamable.com/mpzxef)

Figure 3: The screenshot shows the typical learned behavior of agents in the task of ProduceCombatUnits. (a) shows an agent trained with shaped reward function $R_{\mathcal{A}_1}$ learn to only produce combat units once the resources are exhausted (i.e. it produces three combat units at $t = 1410$). In contrary, (b) shows an agent trained with action guidance learn to produce units and harvest resources concurrently (i.e. it produces three combat units at $t = 890$). Click on the link below figures to see the full videos of trained agents.

Positive Learning Optimization results are inconclusive. We found PLO to be an interesting yet sometimes effective optimization in stabilizing the performance for agents trained with action guidance. As a motivating example, Figure 2 showcases the actual episode reward of 10 seeds in ProduceCombatUnits, where agents trained with action guidance - short adaptation and PLO seem to always converge while agents trained without PLO would only sometimes converge. However, PLO does not always help. For example, PLO actually hurt the performance of action guidance - long adaptation in ProduceCombatUnits by having a few degenerate runs as shown in Figure 2. It is also worth noting the PLO does not help the sparse reward agent at all, suggesting PLO is a an optimization somewhat unique to action guidance.

Action guidance - mixed policy is viable. According to Table 1, agents trained with action guidance - mixed policy with or without PLO seem to perform relatively well in all three tasks examined. This is a interesting discovery because it suggests action guidance could go both ways: the auxiliary agents could also benefit from the learned policies of the main agent. An alternative perspective is to consider the main agent and the auxiliary agents as a whole entity that mixes different reward functions, somehow making joint decision and collaborating to accomplish common goals.

5 CONCLUSIONS

In this paper, we present a novel technique called *action guidance* that successfully trains the agent to eventually optimize over sparse rewards yet does not lose the sample efficiency that comes with reward shaping, effectively getting the best of both worlds. Our experiments with DefeatRandomEnemy in particular show it is possible to train a main agent on the full game of μRTS using only the match outcome reward, which suggests action guidance could serve as a promising alternative to the training paradigm of AlphaStar (Vinyals et al., 2019) that uses supervised learning with human replay data to bootstrap an agent. As part of our future work, we would like to scale up the approach to defeat stronger opponents.

REFERENCES

Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, pp. 1, 2004.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in neural information processing systems*, pp. 5048–5058, 2017.

Michael Bain and Claude Sammut. A framework for behavioural cloning. In *Machine Intelligence 15*, pp. 103–129, 1995.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in neural information processing systems*, pp. 1471–1479, 2016.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemyslaw Debiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, Rafal Józefowicz, Scott Gray, Catherine Olsson, Jakub W. Pachocki, Michael Petrov, Henrique Pond'e de Oliveira Pinto, Jonathan Raiman, Tim Salimans, Jeremy Schlatter, Jonas Schneider, Szymon Sidor, Ilya Sutskever, Jie Tang, Filip Wolski, and Susan Zhang. Dota 2 with large scale deep reinforcement learning. *ArXiv*, abs/1912.06680, 2019.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A. Efros. Large-scale study of curiosity-driven learning. In *ICLR*, 2019.

Thomas Degris, Martha White, and Richard S Sutton. Off-policy actor-critic. *arXiv preprint arXiv:1205.4839*, 2012.

Prafulla Dhariwal, Christopher Hesse, Oleg Klimov, Alex Nichol, Matthias Plappert, Alec Radford, John Schulman, Szymon Sidor, Yuhuai Wu, and Peter Zhokhov. Openai baselines. `https://github.com/openai/baselines`, 2017.

Thomas G Dietterich. Hierarchical reinforcement learning with the maxq value function decomposition. *Journal of artificial intelligence research*, 13:227–303, 2000.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Firdaus Janoos, Larry Rudolph, and Aleksander Madry. Implementation matters in deep rl: A case study on ppo and trpo. In *International Conference on Learning Representations*, 2019.

Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Curiosity-driven exploration in deep reinforcement learning via bayesian neural networks. 2016.

Shengyi Huang and Santiago Ontañón. A closer look at invalid action masking in policy gradient algorithms. *arXiv preprint arXiv:2006.14171*, 2020.

Shengyi Huang and Santiago Ontañón. Comparing observation and action representations for deep reinforcement learning in μrts. 2019.

Anssi Kanervisto, Christian Scheller, and Ville Hautamäki. Action space shaping in deep reinforcement learning. *arXiv preprint arXiv:2004.00980*, 2020.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

Manuel Lopes, Tobias Lang, Marc Toussaint, and Pierre-Yves Oudeyer. Exploration in model-based reinforcement learning by empirically estimating learning progress. In *Advances in neural information processing systems*, pp. 206–214, 2012.

Vinod Nair and Geoffrey E Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th international conference on machine learning (ICML-10)*, pp. 807–814, 2010.

Sanmit Narvekar and Peter Stone. Learning curriculum policies for reinforcement learning. *arXiv preprint arXiv:1812.00285*, 2018.

Andrew Y Ng, Daishi Harada, and Stuart Russell. Policy invariance under reward transformations: Theory and application to reward shaping. 1999.

Zhen-Jia Pang, Ruo-Ze Liu, Zhou-Yu Meng, Yi Zhang, Yang Yu, and Tong Lu. On reinforcement learning for full-length game of starcraft. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 4691–4698, 2019.

Deepak Pathak, Pulkit Agrawal, Alexei A. Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *ICML*, 2017.

Martin Riedmiller, Roland Hafner, Thomas Lampe, Michael Neunert, Jonas Degrave, Tom Van de Wiele, Volodymyr Mnih, Nicolas Heess, and Jost Tobias Springenberg. Learning by playing-solving sparse reward tasks from scratch. *arXiv preprint arXiv:1802.10567*, 2018.

Tom Schaul, Daniel Horgan, Karol Gregor, and David Silver. Universal value function approximators. In *International conference on machine learning*, pp. 1312–1320, 2015.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Maxwell Svetlik, Matteo Leonetti, Jivko Sinapov, Rishi Shah, Nick Walker, and Peter Stone. Automatic curriculum graph generation for reinforcement learning agents. In *Thirty-First AAAI Conference on Artificial Intelligence*, 2017.

Matthew E. Taylor, Peter Stone, and Yaxin Liu. Transfer learning via inter-task mappings for temporal difference learning. *J. Mach. Learn. Res.*, 8:2125–2167, 2007.

Oriol Vinyals, Timo Ewalds, Sergey Bartunov, Petko Georgiev, Alexander Sasha Vezhnevets, Michelle Yeo, Alireza Makhzani, Heinrich Küttler, John Agapiou, Julian Schrittwieser, et al. Starcraft ii: A new challenge for reinforcement learning. *arXiv preprint arXiv:1708.04782*, 2017.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

Ziyu Wang, Victor Bapst, Nicolas Heess, Volodymyr Mnih, Remi Munos, Koray Kavukcuoglu, and Nando de Freitas. Sample efficient actor-critic with experience replay. *arXiv preprint arXiv:1611.01224*, 2016.

Deheng Ye, Zhao Liu, Mingfei Sun, Bei Shi, Peilin Zhao, Hao Wu, Hongsheng Yu, Shaojie Yang, Xipeng Wu, Qingwei Guo, et al. Mastering complex control in moba games with deep reinforcement learning. In *AAAI*, pp. 6672–6679, 2020.