Exploiting Data Sparsity in Secure Cross-Platform Social Recommendation

Abstract

Social recommendation has shown promising improvements over traditional systems since it leverages social correlation data as an additional input. Most existing work assumes that all data are available to the recommendation platform. However, in practice, user-item interaction (e.g.,rating) data and user-user social data are usually generated by different platforms, and both of which contain sensitive information. Therefore, *How to perform secure and efficient social recommendation across different platforms, where the data is highly-sparse in nature* remains an important challenge. In this work, we combine secure computation techniques and social recommendation, and propose S^3Rec, a sparse-aware secure cross-platform social recommendation framework. As a result, S^3Rec can not only improve the recommendation performance of the rating platform by incorporating the sparse social data on the social platform, but also protect data privacy of both platforms. Moreover, to further improve model training efficiency, we propose two secure sparse matrix multiplication protocols based on homomorphic encryption and private information retrieval. Our experiments on two benchmark datasets demonstrate the effectiveness of S^3Rec.

1 Introduction

The recent advances of social recommendation have achieved remarkable performances in recommendation tasks [10, 26]. Unlike traditional methods, social recommendation leverages user-item rating data (e.g. from Netflix) with user-user social data (e.g. from Facebook) to facilitate model training. The cross-platform nature, the high sparsity and sensitivity of recommendation/social data make social recommendation hard-to-deploy in the real world [5]. Therefore, the main problem is,

*How to perform **secure** and **efficient** social recommendation across different platforms, where the data is **highly-sparse** in nature?*

Specifically, we focus on the problem of collaborative social recommendation training in the two-party model, where one party (denoted as P_0) holds user-item rating data, and the other party (denoted as P_1) holds user-user social data. We also assume that the adversaries are semi-honest and non-colluding, which is commonly used in literature [8]. That is, the adversary will not deviate from the pre-defined protocol, but will try to learn as much information as possible from its received messages.

Choices of privacy enhancing techniques. On the one hand, many anonymization techniques have been used in publishing recommendation data, such as *k-anonymity* and *differential privacy* [9]. On the other hand, cryptographic methods like *secure multiparty computation* (MPC) [9] and *homomorphic encryption* (HE) have been proposed to enable calculation on protected data. Since k-anonymity has been demonstrated risky in practice (i.e. the re-identification attack on Netflix Prize dataset [20]), and differential privacy introduces random noises to the dataset which eventually

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

affects model accuracy, we consider they are not the ideal choice for our framework. Instead, we choose a combination of cryptographic tools (i.e. MPC and HE, but mainly MPC) which allows multiple parties to jointly compute a function depending on their private inputs while providing security guarantees.

Choice of social recommendation model. In literature, many social recommendation models have been proposed [7, 16, 25] using matrix factorization or neural networks. Existing MPC-based neural network protocols [19, 27] usually suffer from accuracy loss and inefficiency due to their approximation of non-linear operations. Especially for the case of social recommendation, training data could exceeds to millions, and this makes NN-based model a less ideal choice. Therefore, we choose the classic social recommendation model, Soreg [16], as a typical example, and present how to build a secure and efficient version of Soreg under cross-domain social recommendation scenario.

Dealing with sparse data in secure machine learning. One important property of social recommendation data is its high sparsity. Take LibraryThing dataset [29] for example, its social matrix density is less than 0.02%. Recently, Schoppmann et al. introduced the ROOM framework [24] for secure computation over sparse data. However, their solution only works on column-sparse or row-sparse data. In this work, we proposed a PIR-based matrix multiplication which does not require additional MPC matrix multiplication.

Our framework. In this paper, we propose S^3Rec, a sparse-aware secure cross-platform social recommendation framework. Starting with the classic Soreg model, we observe that the training process of Soreg involves two types of calculation terms, (1) the *rating term* which could be calculated by P_0 locally, and (2) the *social term* which needs to be calculated by P_0 and P_1 collaboratively. Therefore, the key to S^3Rec is designing secure and efficient protocols for calculating the social term.

To begin with, we first let both parties performs local calculation. Then both parties invoke a secure social term calculation protocol and let P_0 finally receives the plaintext social term, and updates the model accordingly. In this way, the security of our protocol replies significantly on the secure social term calculation protocol (for simplicity, we refer this protocol as the 'ST-MPC' protocol), and we propose a secure instantiation and prove its security. Similarly, the efficiency of S^3Rec relies heavily on the performance of ST-MPC, and at the core, it relies on the efficiency of a matrix multiplication protocol. The naïve secure matrix multiplication protocol is traditionally evaluated through Beaver's triples [3], and has $O(km^2)$ asymptotic communication complexity, where k is the dimension of latent factors and m is the number of users. To improve the communication efficiency, we propose two secure sparse matrix multiplication protocols for ST-MPC, based on two sparsity settings. (1) *insensitive sparsity*, which is a weaker variant of matrix multiplication where we assume both parties know the locations of non-zero values in the sparse matrix, and (2) *sensitive sparsity*, which is also a weaker variant of matrix multiplication, but stronger than (1), and we assume 'only' the number of zeros is public. Nevertheless, we present secure constructions for MatrixMul in both cases by leveraging two cryptography primitives called *Private Information Retrieval* (PIR) [1] and *Homomorphic Encryption* (HE) [22]. PIR can hide the locations of the non-zero values in the sparse matrix while HE enables additions and multiplications on ciphertexts. To this end, we drop the communication complexity of secure MatrixMul to $O(km)$ for the insensitive sparsity case and to $O(\alpha km)$ for the sensitive sparsity case, where α denotes the density of user social matrix.

Summary of our experimental results. We conduct experiments on two popularly used dataset, i.e., Epinions [17] and LibraryThing [29]. The results demonstrate that (1) S^3Rec achieves the same performance as existing social recommendation models, and (2) S^3Rec improves the computation time and communication size of the state-of-the-art (SeSoRec) by about $40\times$ and $423\times$ in average.

Contributions. We summarize our main contributions below: (1) We propose S^3Rec, a privacy-preserving cross-platform social recommendation framework, which relies on a general protocol for calculating the social term securely; (2) We propose two secure sparse matrix multiplication protocols based on different sparsity visibility, i.e. insensitive sparsity and sensitive sparsity. We prove that both protocols are secure under semi-honest adversaries; and (3) We empirically evaluate the performance of S^3Rec on benchmark datasets.

2 Preliminaries and Recommendation Model

We begins with the syntax., we use $[n]$ to denote the set $\{1, ..., n\}$, and $|x|$ to denote the length of x. In terms of MPC, we denote a secret shared value of x in $\mathbb{Z}_N$ as $[\![x]\!]$, where N is a positive integer. Also, we let $[\![x]\!]_0$ denote P_0's share, and $[\![x]\!]_1$ denote P_1's share, where $[\![x]\!] = [\![x]\!]_0 + [\![x]\!]_1 \in \mathbb{Z}_N$.

Multi-Party Computation (MPC). MPC is a cryptographic tool which enables multiple parties (say, n parties) to jointly compute a function $f(x_1, ..., x_n)$, where x_i is i-th party's private input. MPC protocols ensure that, at the end of the protocol, parties eventually learn nothing but their own input and the function output. MPC has been widely-used in secure machine learning systems such as PrivColl [28] and CrypT-Flow [13], most of which support a wide range of linear (e.g. addition, multiplication) and non-linear functions (e.g. equality test, comparison). Here, we present three popular MPC protocols, which we will use later in our protocol,

- $[\![z]\!] \leftarrow \mathsf{Add}([\![x]\!], [\![y]\!])$: P_0 lets $[\![z]\!]_0 = [\![x]\!]_0 + [\![y]\!]_0$, and P_1 lets $[\![z]\!]_1 = [\![x]\!]_1 + [\![y]\!]_1$;

- $[\![z]\!] \leftarrow \mathsf{Mul}([\![x]\!], [\![y]\!])$: Multiplication is evaluated via Beaver's Triples [3].

$$\boxed{\begin{array}{l} [\![\mathbf{Z}]\!] \leftarrow \mathsf{MatrixMul}(\mathbf{X}, \mathbf{Y}) \\ \hline 1: \quad P_0, P_1 \text{ jointly generate } km^2 \text{ Beaver's triples} \\ \cdots\cdots\cdots\cdots \text{ Offline Completed } \cdots\cdots\cdots\cdots \\ 2: \quad \forall x_{i,j} \in \mathbf{X}, P_0 \text{ invokes } [\![x_{i,j}]\!] \leftarrow \mathsf{Shr}(x_{i,j}) \\ 3: \quad \forall y_{i,j} \in \mathbf{Y}, P_1 \text{ invokes } [\![y_{i,j}]\!] \leftarrow \mathsf{Shr}(y_{i,j}) \\ 4: \quad \textbf{foreach } i \in [k], j \in [m], \text{ let } [\![z_{i,j}]\!] = 0, \\ 5: \quad\quad \textbf{foreach } a \in [m], b \in [m], \\ 6: \quad\quad\quad [\![\mathsf{tmp}]\!] \leftarrow \mathsf{Mul}([\![x_{i,a}]\!], [\![y_{b,j}]\!]) \\ 7: \quad\quad\quad [\![z_{i,j}]\!] \leftarrow \mathsf{Add}([\![\mathsf{tmp}]\!], [\![z_{i,j}]\!]) \\ 8: \quad\quad \textbf{endfor} \\ 9: \quad \textbf{endfor} \\ 10: \quad \textbf{return } [\![\mathbf{Z}]\!] \end{array}}$$

Figure 1: Matrix multiplication protocol.

Homomorphic Encryption (HE) scheme. HE is essentially a specific type of encryption scheme which allows manipulation on encrypted data. More specifically, HE involves a key pair $(\mathsf{pk}, \mathsf{sk})$, where the public key pk is used for encryption and the secret key sk is used for decryption. In this work, we use an additive HE scheme (i.e., Paillier [22]) which allows the following operations:

- $z \leftarrow \mathsf{Enc}_{\mathsf{pk}}(x) \oplus \mathsf{Enc}_{\mathsf{pk}}(y)$: addition between two ciphertexts, where $z = \mathsf{Enc}_{\mathsf{pk}}(x + y)$;

- $z \leftarrow \mathsf{Enc}_{\mathsf{pk}}(x) \otimes y$: multiplication between a ciphertext and a plaintext, where $z = \mathsf{Enc}_{\mathsf{pk}}(x \cdot y)$.

Private Information Retrieval (PIR). Now, we introduce single-server PIR [1]. In this setting, we assume there is a server and a client, where the server holds a database $\mathsf{DB} = \{d_1, ..., d_n\}$ with n elements, and the client wants to retrieve DB_i while hiding the query index i from the server. Roughly, a PIR protocol consists of a tuple of algorithm $(\mathsf{PIR.Query}, \mathsf{PIR.Response}, \mathsf{PIR.Extract})$. First, the client generates a query $q \leftarrow \mathsf{PIR.Query}(i)$ from an index i, and then sends query q to the server. The server then is able to generate a response $r \leftarrow \mathsf{PIR.Response}(\mathsf{DB}, q)$ based on the query and database DB, and returns r to the client. Finally, the client extracts the result from server's response $\mathsf{DB}_i \leftarrow \mathsf{PIR.Extract}(r)$.

$$\boxed{\begin{array}{lcl} \textbf{Client} & & \textbf{Server} \\ \\ q \leftarrow \mathsf{PIR.Query}(i) & \xrightarrow{\quad q \quad} & \\ \\ & \xleftarrow{\quad r \quad} & r \leftarrow \mathsf{PIR.Response}(\mathsf{DB}, q) \\ \\ \mathsf{DB}_i \leftarrow \mathsf{PIR.Extract}(r) & & \end{array}}$$

Figure 2: An overview of Private Information Retrieval

2.1 Recommendation model

Recall that we assume there are two platforms, a rating platform P_0, and a social platform P_1. We assume P_0 holds a private rating matrix $\mathbf{R} \in \mathbb{R}^{m \times n}$, and P_1 holds a private user social matrix $\mathbf{S} \in \mathbb{R}^{m \times m}$, where n and m denote the number of items and their common users, respectively. Also, we denote the user latent factor matrix as $\mathbf{U} \in \mathbb{R}^{k \times m}$ and item latent factor matrix as $\mathbf{V} \in \mathbb{R}^{k \times n}$,

Global Parameter: Regularization strength γ, and learning rate θ.

Input: Private rating matrix $\mathbf{R}$ from platform P_0, private user social matrix $\mathbf{S}$ from platform P_1.

Output: Platform P_0 receives the user latent matrix $\mathbf{U}$ and item latent matrix $\mathbf{V}$.

1 : Platform P_0 initializes $\mathbf{U}$ and $\mathbf{V}$,

2 : **while** not coverage,

3 : P_0 and P_1 securely calculate the social term $\leftarrow$

4 : P_0 locally computes the rating terms

5 : P_0 locally updates $\mathbf{U}$ by $\mathbf{U} \leftarrow \mathbf{U} - \theta \cdot \partial \mathcal{L} / \partial \mathbf{U}$

6 : P_0 locally updates $\mathbf{V}$ by $\mathbf{V} \leftarrow \mathbf{V} - \theta \cdot \partial \mathcal{L} / \partial \mathbf{V}$

7 : **endwhile**

8 : **return** $\mathbf{U}$ and $\mathbf{V}$ to platform P_0

ST-MPC$(\gamma, \mathbf{U}, \mathbf{D}, \mathbf{E}, \mathbf{S})$

1 : $[\![\mathbf{R}_0]\!] \leftarrow \mathsf{MatrixMul}(\gamma\mathbf{U}/2, \mathbf{D}^T + \mathbf{E}^T)$

2 : $[\![\mathbf{R}_1]\!] \leftarrow \mathsf{MatrixMul}(-\gamma\mathbf{U}, \mathbf{S}^T)$

3 : $[\![\mathbf{R}]\!] \leftarrow \mathsf{Add}([\![\mathbf{R}_0]\!], [\![\mathbf{R}_1]\!])$

4 : **return** $\mathsf{Rec}([\![\mathbf{R}]\!])$ to P_0

Figure 3: Our proposed S³RecFramework, where MatrixMul stands for secure matrix multiplication protocol, Add stands for secure add protocol, Rec stands for reconstruction protocol for secret sharing.

where k is the dimension of latent factors. We further define an indication matrix $\mathbf{I} \in \mathbb{R}^{m \times n}$, where $I_{i,j}$ denotes whether user i has rated item j.

Existing work [25] summarizes factorization based social recommendation models as the combination of a "basic factorization model" and a "social information model". To date, different kinds of social information models have been proposed [16, 12], and their common intuition is that users with social relations tend to have similar preferences. In this work, we focus on the classic social recommendation model, i.e., Soreg [16], which aims to learn $\mathbf{U}$ and $\mathbf{V}$ by minimizing the following objective function,

$$\sum_{i=1}^{m} \sum_{j=1}^{n} \frac{1}{2} I_{i,j} \left(r_{i,j} - \mathbf{u}_{*,i}^T \mathbf{v}_{*,j} \right)^2 + \frac{\lambda}{2} \sum_{i=1}^{m} \|\mathbf{u}_{*,i}\|_F^2 + \frac{\lambda}{2} \sum_{j=1}^{n} \|\mathbf{v}_{*,j}\|_F^2 + \frac{\gamma}{2} \sum_{i=1}^{m} \sum_{f=1}^{m} s_{i,f} \|\mathbf{u}_{*,i} - \mathbf{u}_{*,f}\|_F^2,$$
(1)

where the first term is the basic factorization model, the last term is the social information model, and the middle two terms are regularizers, $\| \cdot \|_F^2$ is the Frobenius norm, λ and γ are hyper-parameters. If we denote $\mathbf{D} \in \mathbb{R}^{m \times m}$ as a diagonal matrix with diagonal element $d_b = \sum_{c=1}^{m} s_{b,c}$ and $\mathbf{E} \in \mathbb{R}^{m \times m}$ as a diagonal matrix with diagonal element $e_i = \sum_{b=1}^{m} s_{b,i}$. The gradients of $\mathcal{L}$ in Eq. (1) with respect to $\mathbf{U}$ and $\mathbf{V}$ are,

$$\frac{\partial \mathcal{L}}{\partial \mathbf{U}} = \underbrace{-\mathbf{V}\left(\left(\mathbf{R} - \mathbf{U}^T \mathbf{V}\right)^T \circ \mathbf{I} \right) + \lambda \mathbf{U}}_{\text{Rating term: computed by } P_0 \text{ locally}} + \underbrace{\frac{\gamma}{2}\mathbf{U}(\mathbf{D}^T + \mathbf{E}^T) - \gamma \mathbf{U}\mathbf{S}^T}_{\text{Social term: computed by } P_0 \text{ and } P_1 \text{ collaboratively}} ,$$
(2)

$$\frac{\partial \mathcal{L}}{\partial \mathbf{V}} = \underbrace{-\mathbf{U}\left(\left(\mathbf{R} - \mathbf{U}^T \mathbf{V}\right)^T \circ \mathbf{I} \right) + \lambda \mathbf{V}}_{\text{Rating term: computed by } P_0 \text{ locally}} .$$
(3)

3 Framework

We summarize our proposed S³Recframework in Figure 3. To begin with, we assume that party P_0 holds the rating matrix $\mathbf{R}$ and P_1 holds the social matrix $\mathbf{S}$. At first, P_0 randomly initializes $\mathbf{U} \leftarrow_\$ \mathbb{R}^{k \times m}$ and $\mathbf{V} \leftarrow_\$ \mathbb{R}^{k \times n}$. Then, for each iteration (while the model dose not coverage), we let P_0 and P_1 jointly evaluate the social term defined in Eq 2. P_0 then locally calculate the rating term in Eq 2 and Eq 3, as well as $\partial \mathcal{L} / \partial \mathbf{U}$ and $\partial \mathcal{L} / \partial \mathbf{V}$. Party P_0 then locally updates $\mathbf{U}$ and $\mathbf{V}$ accordingly and ends the iteration.

Communication efficiency. In our framework, the only communication between two parties occurs in the ST-MPC protocol. Since we choose additive secret sharing, the Add protocol contains only local computation, we claim that the communication efficiency of S³Rec significantly rely on the efficiency of matrix multiplication protocol. We give a popular MatrixMul protocol in Figure 1 and analyze its efficiency in our framework. The protocol in Figure 1 require $km^2 \log_2 N$ bit online

---

Protocol: $\llbracket \mathbf{Z} \rrbracket \leftarrow \mathsf{MatrixMul}(\mathbf{X}, \mathbf{Y})$

---

1 : P_0, P_1 jointly generate km^2 Beaver's triples

. . . . Offline Completed . . . .

2 : $\forall (i,j) \in l_y, P_1$ pushes $y_{i,j}$ into $T_y(j)$

3 : **for** $j \in [k]$ **do**

4 : P_1 lets $T_y = \emptyset$

5 : $\forall a \in [m], b \in [m],$ if $(i, a) \in l_y, P_0$ pushes $x_{a,b}$ into $T_x(a)$

6 :   **for** $j \in [m]$ **do**

7 :   Both parties let $\llbracket z_{i,j} \rrbracket = 0,$ then, for all values $v \in T_x(i), u \in T_y(j)$

8 : P_0 invokes $\llbracket v \rrbracket \leftarrow \mathsf{Shr}(v), P_1$ invokes $\llbracket v \rrbracket \leftarrow \mathsf{Shr}(u)$

9 : $\llbracket z_{i,j} \rrbracket = \mathsf{Add}(\mathsf{Mul}(\llbracket v \rrbracket, \llbracket u \rrbracket), \llbracket z_{i,j} \rrbracket)$

10 :   **endfor**

11 : **endfor**

Figure 5: Dense-sparse $\mathsf{MatrixMul}(\mathbf{X}, \mathbf{Y})$ with insensitive sparsity, that is, $\mathbf{X} \in \mathbb{R}^{k \times m}, \mathbf{Y} \in \mathbb{R}^{m \times m}$, and $\mathbf{Y}$'s location vector l_y is public.

communication, where m is the number of users and k is the dimension of latent factors. As for the usual case where the number of users is $\approx 10^4$, $k = 10$, and $\log_N = 64$, one invocation of $\mathsf{MatrixMul}$ protocol would have a total communication of around 7.4GB. Considering 100 iterations of our framework, this leads to ≈ 1491GB communication, which is impractical. Fortunately, the social matrices ($\mathbf{D}$, $\mathbf{E}$, and $\mathbf{S}$) are highly sparse in social recommendation. In the following section, we propose a PIR-based sparse matrix multiplication protocol with better communication.

3.1 Secure sparse matrix multiplication

Essentially, any matrix could be represented by a value vector and a location vector, where the value vector contains all non-zero values and the location vector contains locations of those values. That is, a sparse matrix $\mathbf{Y} \in \mathbb{R}^{m \times m}$ can be represented by a pair of vectors $(l_y \in \mathbb{N}_{m^2}^t, v_y \in \mathbb{R}^t)$, where t is the number of non-zero values in $\mathbf{Y}$.

Dense-sparse matrix multiplication. Considering the case where $\mathbf{X} \in \mathbb{R}^{k \times m}$ is the dense matrix from P_0 and $\mathbf{Y} \in \mathbb{R}^{m \times m}$ is the sparse matrix from P_1. Now we consider the following two cases.

Case 1: insensitive sparsity, i.e., insensitive l_y and sensitive v_y. This refers to the case where the locations of zero values are public or contain no sensitive information. Take the social matrices ($\mathbf{D}$ and $\mathbf{E}$) for example, both of them are diagonal, and thus the location vector is insensitive while the value vector is still sensitive.

Our protocol mainly works as follows. First, P_0 and P_1 parse $\mathbf{X}$ and $\mathbf{Y}$ into two tables T_x and T_y separately, where the value set of each bin in T_x is a subset of one row in $\mathbf{X}$, that is, $T_x(i) \subseteq x_{i,*}$. Similarly, bin set in T_y is a subset of one column in $\mathbf{Y}$, $T_y(i) \subseteq y_{*,i}$. The intuition behind is to use bins to contain only

Figure 4: Matrix multiplication with insensitive sparsity.

the necessary values needed to calculate the output value (which means filter out the zero multiplies in each bin). Take the first bins for example (that is, $T_x(0)$ and $T_y(0)$), for $j \in [m]$, $T_x(0)$ contains all $x_{0,j}$ where $y_{j,0}$ is a non-zero value, and $T_y(0)$ contains all non-zero $y_{j,0}$. In order to get the final result, we perform the secure inner product protocol on $T_x(0)$ and $T_y(0)$, and denote the result as $\llbracket z_{0,0} \rrbracket$. We show the high level idea in Figure 4. By doing this, our protocol concretely consumes $k|l_y|$ Beaver's triples and therefore has $O(k|l_y|)$ online communication complexity. Figure 5 shows the technical details of our proposed protocol for case 1. For Line 1 in ST-MPC (Figure 3), clearly

Protocol: $[\![\mathbf{Z}]\!] \leftarrow \mathsf{MatrixMul}(\mathbf{X}, \mathbf{Y})$

1 : P_0 generates an additive HE key pair $(\mathsf{pk}, \mathsf{sk})$, then sends pk to P_1

.... Offline Completed ....

2 : $\forall i \in [k], j \in [m]$, P_0 lets $e_{i,j} = \mathsf{Enc}(\mathsf{pk}, x_{i,j})$, and lets $\mathbf{E}$ be the encrypted matrix

3 : $\forall (i,j) \in l_y$, P_1 pushes $y_{i,j}$ into $T_y(j)$, also, P_1 invokes $q_{i,j} \leftarrow \mathsf{PIR.Query}(i + jk)$

4 : P_1 sends the query set (denoted as $\mathbf{q}$) to P_0

5 : $\forall q_{i,j} \in \mathbf{q}$, P_0 invokes $r_{i,j} \leftarrow \mathsf{PIR.Response}(\mathbf{E}, q_{i,j})$.

6 : P_0 sends the response set (denoted as $\mathbf{r}$) to P_1

7 : $\forall r_{i,j} \in \mathbf{r}$, P_1 invokes $e_{i,j} \leftarrow \mathsf{PIR.Extract}(r_{i,j})$ and pushes $e_{i,j}$ to $T_e'(i)$

8 :   **for** $i \in [k], j \in [m]$ **do**

9 : P_0 lets $\beta_{i,j} = \mathsf{Enc}_{\mathsf{pk}}(0)$

10 : $\forall v \in T_e'(i), u \in T_y(j)$, P_0 invokes $\beta_{i,j} = v \otimes u \oplus \beta_{i,j}$

11 : P_0 samples random numbers $g_{i,j} \leftarrow\!\!\$\ \mathbb{Z}_\delta$, then lets $\beta_{i,j} = g_{i,j} \oplus \beta_{i,j}$

12 : P_0 sends $\beta_{i,j}$ to P_1, then lets $[\![z_{i,j}]\!]_0 = -g_{i,j}$

13 :   **endfor**

14 : P_0 decrypts all receiving messages and lets $[\![z_{i,j}]\!]_1 = \mathsf{Dec}_{\mathsf{sk}}(\beta_{i,j})$

15 :   **return** $[\![Z]\!]$

Figure 6: Dense-sparse MatrixMul with sensitive sparsity, that is, $\mathbf{X} \in \mathbb{R}^{k \times m}, \mathbf{Y} \in \mathbb{R}^{m \times m}$, and $\mathbf{Y}$'s location vector l_y is private.

both parties know that $\mathbf{D}$ and $\mathbf{E}$ are diagonal matrices, that is, $|l_y| = m$. Therefore, our proposed protocol in Figure 4 can drop the complexity from $O(km^2)$ to $O(km)$.

Lemma 1. *The protocol in Figure 5 is secure in the MPC-hybrid model.*

Proof. Please find the proof in the Technical Appendix. □

Case 2: sensitive sparsity, i.e., sensitive l_y and sensitive v_y. For a more general case, where both the location vector and the value vector contain sensitive information. Take the social matrix $\mathbf{S}$ for instance, its location vector indicates the existence of a social relation between two users, its value vector further shows the strength of their relation, and both of which are sensitive.

In this case, both the dense matrix $\mathbf{X}$ and the entire sparse matrix $\mathbf{Y}$ are sensitive. Following the idea in case 1, the matrix multiplication protocol should first generate T_x, T_y according to v_x, v_y and l_y, and then perform the inner product multiplication for each aligned bins in T_x, T_y. Still, P_1 can generate T_y according to its own inputs v_y, l_y. However, P_0 cannot generate T_x directly, since v_x is kept by itself while l_y is held by P_1. We make a communication and computation trade-off by leveraging PIR techniques, and as a result, our PIR-based approach has lower concrete communication, and overall faster than the baseline protocol.

Figure 7: Matrix multiplication with sensitive sparsity.

We show the high-level idea of our PIR-based protocol in Figure 7. The intuition behind is to let P_1 obliviously filters each bin in T_x since both value vector and location vector are sensitive. In summary, first P_0 encrypts all the values in T_x, the encrypted table is denoted as T_e. Then P_1 and P_0 invoke PIR protocol, where P_0 acts as server and sets T_e as PIR database, P_1 acts as client and parses l_y to many PIR queries. At the end of PIR protocol, P_1 receives the encrypted and filtered table T_e'. Afterwards P_1 performs secure inner product evaluation. By doing this, the communication complexity drops from $O(km^2)$ to $O(\alpha km)$, compared with the simple solution. The details of our

protone are shown in Figure 6. For Line 2 in ST-MPC (Figure 3), the social matrix ($\mathbf{S}$) is sparse in nature, and thus our proposed protocol in Figure 7 can significantly improve its efficiency. In summary, with our proposed two secure MatrixMul protocols, one can securely calculate the social term efficiently. For instance, again considering the social recommendation with $\approx 10^4$ users, our proposal only requires a total of ≈ 3.6GB communication for each iteration.

Lemma 2. *The protocol in Figure 6 is secure in the PIR-hybrid model with the leakage of $|l_y|$.*

Proof. Please find the proof in the Technical Appendix. □

3.2 Security discussions of the social term

In S^3Rec, P_0 and P_1 securely calculate the social term $\mathsf{ST} = \gamma\mathbf{U}(\mathbf{D}^T + \mathbf{E}^T)/2 - \gamma\mathbf{U}\mathbf{S}^T$ and reveal the result to P_0 (Eq.(2)). We denote the ideal functionality of secure calculating the social term as $\mathcal{F}_{\mathsf{st}}$. During each epoch in Algorithm 3, P_0 sends $\mathbf{U}$ to $\mathcal{F}_{\mathsf{st}}$, and P_1 sends $\mathbf{D}, \mathbf{E}, \mathbf{S}$ to $\mathcal{F}_{\mathsf{st}}$ accordingly. From the view of P_0, after each iteration, it additionally learns the output of $\mathcal{F}_{\mathsf{st}}$, that is, the social term ST. The security of S^3Rec relies on whether P_0 can resolve the social matrix $\mathbf{S}^T$ given its own inputs $\mathbf{U}$ and the social term ST. We claim that this is difficult because, the number of equations (#epoch, 100 in our experiments) is much smaller than that of the variables (#user, much more than 100 in practice), which indicates that there are infinite solutions for this. Moreover, the reveal of the social term to P_0 could be avoided by taking the whole model training procedure as an MPC functionality and designing a complicated protocol for it. Inevitably, such protocol introduces impractical communication costs, and we leave how to solve this efficiently as a future work.

4 Experiments

Our experiments intend to answer the following questions. **Q1:** How do the social recommendation models using both rating data on P_0 and social data on P_1 outperform the model that only uses rating data on P_0 (Section 4)? **Q2:** How does our model perform compared with SeSoRec (Section 4)? **Q3:** How does the social data sparsity affect the performance of SeSoRec and our model (Section 4)?

Implementation and setup. We run our experiments on a machine with 4-Core 2.4GHz Intel Core i5 with 16G memory, we compile our program using a modern C++ compiler (with support for C++ standard 17). In addition, our tests were run in a local network, with ≈ 3ms network latency. For additive HE scheme, we choose the implementation of libpaillier[1]. Also, we use Seal-PIR[2] with same parameter setting as the original paper [1]. For security, we choose 128-bit computational security and 40-bit statistical security as recommended by NIST[2]. Similarly we leverage the generic ABY library[3] to implement SeSoRec [5] and MPC building blocks such as addition, multiplication, and truncation. In particular, we choose 64-bit secret sharing in all our experiments.

Dataset. We choose two popular benchmark datasets to evaluate the performance of our proposed model, i.e., Epinions [17] and LibraryThing (Lthing) [29], both of which are popularly used for evaluating social recommendation tasks. Following existing work [5], we remove the users and items that have less than 15 interactions for both datasets. We summarize the statistics of both datasets after process in Table 1. Notice that we assume users' rating data are located at P_0, users' social data are located at P_1, and P_0 and P_1 share the same user set.

Table 1: Dataset statistics

Dataset	#user	#item	#rating	rating density	#social relation	social density
Epinions	11,500	7,596	283,319	0.32%	275,117	0.21%
Lthing	15,039	14,957	529,992	0.24%	44,710	0.02%

Comparison Methods. We compare S^3Rec with the following classic and state-of-the-art models:

---

[1]libpaillier: http://acsc.cs.utexas.edu/libpaillier/, GPL license

[2]Seal-PIR: https://github.com/microsoft/SealPIR, MIT license

[3]ABY: https://github.com/encryptogroup/ABY, LGPL license

Table 2: Comparison results of different models in terms of model accuracy (in RMSE), running time (in seconds), and communication size (in GB), on Epinions and Lthing datasets.

Models	Epinions dataset				Lthing dataset			
	MF	Soreg	SeSoRec	S^3Rec	MF	Soreg	SeSoRec	S^3Rec
RMSE	1.193	1.062	1.062	1.062	0.927	0.908	0.908	0.908
Offline Time	-	-	7,271	**10.86**	-	-	14,450	**8.912**
Total Time	3.846	40.50	7,799	**419.9**	9.596	57.76	16,084	**262.1**
Offline Comm.	-	-	788.3	**0**	-	-	1,348	**0**
Total Comm.	-	-	798.6	**3.552**	-	-	1,365	**2.201**

Table 3: Comparison results by varying social data sparsity on Epinions and Lthing datasets.

Metric	Models	Epinions			Lthing		
		0.4	0.6	0.8	0.4	0.6	0.8
Total time (Seconds)	SesoRec	7,799	7,799	7,799	16,084	16,084	16,084
	S^3Rec	366.3	381.2	401.8	194	217	238
	(Improvement)	(21.29x)	(20.46x)	(19.41x)	(82.91x)	(74.12x)	(67.58x)
Total communication (GB)	SesoRec	798	798	798	1,366	1,366	1,366
	S^3Rec	3.12	3.29	3.46	1.62	1.82	2.01
	(Improvement)	(255x)	(243x)	(231x)	(843x)	(751x)	(680x)

– *MF* [18] is a classic matrix factorization model that only uses rating data on P_0, i.e., when $\gamma = 0$ for S^3Rec.

– *Soreg* [16] is a classic social recommendation model, which does not consider data privacy and assumes both rating data and social data are available on P_0.

– *SeSoRec* [5] tries to solve the privacy-preserving cross-platform social recommendation problem, but suffers from security and efficiency problem.

Hyper-parameters. For all the model, during comparison, we set $k = 10$. We tune learning rate θ and regularizer parameter λ in $\{10^{-3}, 10^{-2}, ..., 10^1\}$ to achieve their best values. We also report the effect of K on model performance.

Metrics. We will evaluate both accuracy and efficiency of our proposed model. For accuracy, we choose Root Mean Square Error (RMSE) as the evaluation metric, since ratings range in [0, 5]. For efficiency, we report the computation time (in seconds) and the communication size between P_0 and P_1 (in gigabytes), if has, for all the models. We use five-fold cross-validation as the evaluation metric during experiments.

Performance Comparison. We first compare the model performances in terms of accuracy (RMSE) and efficiency (total time and communication). Table 2 show the time and communication for each epoch, where time is shown in seconds, and communication is shown in GB.

From those Tables, we find that, (1) the use of social information can indeed improve the recommendation performance of the rating platform, e.g., 1.193 vs. 1.062 and 0.927 vs. 0.098 in terms of RMSE on Epinions and Lthing, respectively. This result is consistent with existing work from [16, 5]; (2) Despite the same RMSE as SeSoRec and Soreg, S^3Rec significantly improves the efficiency of SeSoRec, especially on the more sparse Lthing dataset, reducing the total time for one epoch from around 4.5 hours to around 4.5 minutes, and reducing the total communication from nearly 1.3TB to around 2.2GB. This yields an improvement of $18.57\times$ faster, and $224.8\times$ less communication on Epinions and $61.37\times$ faster and $620.2\times$ less communication on Lthing, respectively.

Effect of Social Data Sparsity. Next, we try to study the effect of social data sparsity on training efficiency. In order to do this, we sample the social relation of both datasets with rate of 0.8, 0.6, and 0.4. As the result, the RMSEs of both SeSoRec and S^3Rec decrease to 1.0932, 1.1373, 1.1751 on Epinions dataset, and 0.9112, 0.9187, 0.9210 on Lthing dataset. The rational behind is that

Table 4: Effect of k on running time and communication size on Epinions dataset

Models	SeSoRec			S^{3}Rec		
	$k = 10$	$k = 15$	$k = 20$	$k = 10$	$k = 15$	$k = 20$
Offline Time	7,271	12,651	17,676	10.86	9.667	9.815
Total Time	7,799	13,565	19,585	419.9	449.6	527.4
Offline Comm.	788.3	1,182	1,577	0	0	0.
Total Comm.	798.6	1,198	1,597	3.552	3.552	3.552

recommendation performance decreases with the number of social relations. We also report the efficiency of both models on Epinions and Lthing datasets in Table 3. From it, we can find that the computation time and communication size of SeSoRec are constant no mater what the sample rate is. In contrast, the computation time and communication size of S^{3}Rec decrease linearly with sample rate. This result benefits from that S^{3}Rec can deal with sparse social data with our proposed sparse matrix multiplication protocols.

Effect of k. For efficiency, we report the running time and communication size of SeSoRec and PriorRec w.r.t k in Table 4, where we use the Epinions dataset. From it, we can get that in average, S^{3}Rec improves SeSoRec **18.6x** in terms of total running time and **225x** in terms of communication. More specifically, we observe that (1) the total running time of both SeSoRec and PriorRec increases with k, but the increase rate of S^{3}Rec is slower than that of SeSoRec; (2) the communication size of SeSoRec increases with k, in contrast, the communication size of S^{3}Rec is constant. This result demonstrates that our proposed S^{3}Rec has better scalability than SeSoRec in terms of both running time and communication size.

5   Related Work

Traditional recommender systems that only consider user-item rating information suffer from severe data sparsity problem [18]. On the one hand, researchers extensively incorporate other kinds of information, e.g., social [25], review [23], location [14], and time [6], to further improve recommendation performance. On the other hand, existing studies begin to explore information on multiple platforms or domains to address the data sparsity problem, i.e. cross-platform and cross-domain recommendation [15, 30]. However, most of them cannot solve the data isolation problem in practice.

So far, there has been several work that may be applied for privacy-preserving cross-domain recommendations. For example, [21] applied garbled circuits for secure matrix factorization, and it has high security but low efficiency. Chai et al. [4] adopted homomorphic encryption for federated matrix factorization, but it assumes the existence of a semi-honest server and is not provable secure. [11] uses differential privacy to protect user location privacy using transfer learning technique, which is not provable secure and does not suitable to our problem. The most similar work to our is SeSoRec [5], however, it suffers from two main shortcomings: (1) as admitted by SeSoRec, it improves efficiency by sacrificing security. That is, it reveals the sum of two rows or two columns of the input matrix. We emphasis that this raises serious security concern in the social recommendation since one may infer detailed social relations from the element-wise sum of two rows/columns of the user social matrix, especially when social relations are binary values; (2) SeSoRec treats the social data as a dense matrix and thus still has serious efficiency issue under the practical sparse social data setting.

6   Conclusion

This paper aims to solve the data isolation problem in cross-platform social recommendation. To do this, we proposed S^{3}Rec, a sparse-aware secure cross-platform social recommendation framework. S^{3}Rec conducts social recommendation task and preserves data privacy at the same time. We also proposed two secure sparse matrix multiplication protocols to improve the model training efficiency. Experiments conducted on two datasets demonstrate that S^{3}Rec improves the computation time and communication size by around $40\times$ and $423\times$ on average, compared with the state-of-art work.

References

[1] Sebastian Angel, Hongzhang Chen, K. Laine, and S. Setty. Pir with compressed queries and amortized query processing. *IEEE S&P*, pages 962–979, 2018.

[2] Elaine Barker. Nist special publication 800-57 part 1, revision 5. *NIST, Tech. Rep*, 16, 2020.

[3] Donald Beaver. Efficient multiparty protocols using circuit randomization. In *Cryptology*, pages 420–432. Springer, 1991.

[4] Di Chai, Leye Wang, Kai Chen, and Qiang Yang. Secure federated matrix factorization. *IEEE Intelligent Systems*, 2020.

[5] Chaochao Chen, Liang Li, Bingzhe Wu, Cheng Hong, Li Wang, and Jun Zhou. Secure social recommendation based on secret sharing. In *ECAI*, pages 506–512, 2020.

[6] Chen Chen, Hongzhi Yin, Junjie Yao, and Bin Cui. Terec: A temporal recommender system over tweet stream. *VLDB*, 6(12):1254–1257, 2013.

[7] Chong Chen, Min Zhang, Chenyang Wang, Weizhi Ma, Minming Li, Yiqun Liu, and Shaoping Ma. An efficient adaptive transfer neural network for social-aware recommendation. In *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 225–234, 2019.

[8] Ivan Damgård, Valerio Pastro, Nigel Smart, and Sarah Zakarias. Multiparty computation from somewhat homomorphic encryption. In *Annual Cryptology Conference*, pages 643–662. Springer, 2012.

[9] C. Dwork and Aaron Roth. The algorithmic foundations of differential privacy. *Found. Trends Theor. Comput. Sci.*, 9:211–407, 2014.

[10] Wenqi Fan, Y. Ma, Qing Li, Yuan He, Y. Zhao, Jiliang Tang, and D. Yin. Graph neural networks for social recommendation. *The World Wide Web Conference*, pages 417–426, 2019.

[11] Chen Gao, Chao Huang, Yue Yu, Huandong Wang, Yong Li, and Depeng Jin. Privacy-preserving cross-domain location recommendation. *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, 3(1):1–21, 2019.

[12] Mohsen Jamali and Martin Ester. Trustwalker: a random walk model for combining trust-based and item-based recommendation. In *SIGKDD*, pages 397–406, 2009.

[13] N. Kumar, Mayank Rathee, N. Chandran, D. Gupta, Aseem Rastogi, and R. Sharma. Cryptflow: Secure tensorflow inference. *2020 IEEE Symposium on Security and Privacy (SP)*, pages 336–353, 2020.

[14] Justin J Levandoski, Mohamed Sarwat, Ahmed Eldawy, and Mohamed F Mokbel. Lars: A location-aware recommender system. In *ICDE*, pages 450–461. IEEE, 2012.

[15] Tzu-Heng Lin, Chen Gao, and Yong Li. Cross: Cross-platform recommendation for social e-commerce. In *SIGIR*, pages 515–524, 2019.

[16] Hao Ma, Dengyong Zhou, Chao Liu, Michael R Lyu, and Irwin King. Recommender systems with social regularization. In *WSDM*, pages 287–296. ACM, 2011.

[17] Paolo Massa and Paolo Avesani. Trust-aware recommender systems. In *RecSys*, pages 17–24, 2007.

[18] Andriy Mnih and Russ R Salakhutdinov. Probabilistic matrix factorization. *NeurIPS*, 20:1257–1264, 2007.

[19] Payman Mohassel and Y. Zhang. Secureml: A system for scalable privacy-preserving machine learning. *IEEE S&P*, pages 19–38, 2017.

[20] A. Narayanan and Vitaly Shmatikov. How to break anonymity of the netflix prize dataset. *ArXiv*, abs/cs/0610105, 2006.

[21] Valeria Nikolaenko, Stratis Ioannidis, Udi Weinsberg, Marc Joye, Nina Taft, and Dan Boneh. Privacy-preserving matrix factorization. In *Proceedings of the 2013 ACM SIGSAC conference on Computer & communications security*, pages 801–812, 2013.

[22] Pascal Paillier. Public-key cryptosystems based on composite degree residuosity classes. In *International conference on the theory and applications of cryptographic techniques*, pages 223–238. Springer, 1999.

[23] Francisco J Peña, Diarmuid O'Reilly-Morgan, Elias Z Tragos, Neil Hurley, Erika Duriakova, Barry Smyth, and Aonghus Lawlor. Combining rating and review data by initializing latent factor models with topic models for top-n recommendation. In *RecSys*, pages 438–443, 2020.

[24] Phillipp Schoppmann, Adrià Gascón, Mariana Raykova, and Benny Pinkas. Make some room for the zeros: Data sparsity in secure distributed machine learning. In *CCS*, pages 1335–1350, 2019.

[25] Jiliang Tang, Xia Hu, and Huan Liu. Social recommendation: a review. *Social Network Analysis and Mining*, 3(4):1113–1133, 2013.

[26] Jiliang Tang, Suhang Wang, Xia Hu, D. Yin, Yingzhou Bi, Yi Chang, and Huan Liu. Recommendation with social dimensions. In *AAAI*, 2016.

[27] Sameer Wagh, Divya Gupta, and Nishanth Chandran. Securenn: 3-party secure computation for neural network training. *Proceedings on Privacy Enhancing Technologies*, 2019:26 – 49, 2019.

[28] Yanjun Zhang, Guangdong Bai, Xue Li, Caitlin Curtis, Chen Chen, and Ryan KL Ko. Privcoll: Practical privacy-preserving collaborative machine learning. In *European Symposium on Research in Computer Security*, pages 399–418. Springer, 2020.

[29] Tong Zhao, Julian McAuley, and Irwin King. Improving latent factor models via personalized feature projection for one class recommendation. In *CIKM*, pages 821–830, 2015.

[30] Feng Zhu, Yan Wang, Chaochao Chen, Guanfeng Liu, and Xiaolin Zheng. A graphical and attentional framework for dual-target cross-domain recommendation. In *IJCAI*, pages 3001–3008, 2020.