Fast and Optimal Weight Update for Pruned Large Language Models

Abstract

Pruning large language models (LLMs) is a challenging task due to their enormous size. The primary difficulty is fine-tuning the model after pruning, which is needed to recover the lost performance caused by dropping weights. Recent approaches have either ignored fine-tuning entirely, focusing on efficient pruning criteria, or attempted layer-wise weight updates, preserving the behavior of each layer. However, even layer-wise weight updates can be costly for LLMs, and previous works have resorted to various approximations.

In our paper, we propose a fast and optimal weight update algorithm for pruned layers based on the Alternating Direction Method of Multipliers (ADMM). Coupled with a simple gradual pruning mask selection, our algorithm achieves state-of-the-art pruning performance across a wide range of LLMs.

1 Introduction

Large language models (LLMs) (Brown et al., 2020; Zhang et al., 2022; Touvron et al., 2023a;b) have displayed impressive performance in different tasks, but deploying them can be challenging due to their large size and high memory demands. In this work, we introduce a one-shot pruning and weight update algorithm for LLMs that is both fast and accurate. Our algorithm produces state-of-the-art results for LLM pruning while imposing minimal computational overhead (Table 1).

Neural networks are usually compressed by either quantization or weight pruning. LLM quantization (Dettmers et al., 2022; Dettmers & Zettlemoyer, 2023; Ahmadian et al., 2023; Xiao et al., 2023) compresses LLMs by storing weights using a small number of bits. On the other hand, pruning compresses models by dropping irrelevant weights (LeCun et al., 1989; Han et al., 2015; Zhu & Gupta, 2018). Pruning can be helpful for LLMs since, during inference, the main bottleneck is memory bandwidth for loading weights to processing unit (Xia et al., 2023). However, the main challenge in deploying LLM pruning is that the network needs to be fine-tuned (Blalock et al., 2020; Liu et al., 2018), which is not feasible with LLMs due to extensive computational and memory footprint.

A feasible alternative is one-shot pruning, where one is given a trained model with a small amount of calibration data, and has to compress the model in a single forward pass using limited computational resources. This is typically done via layer-wise pruning, where the pruning problem is split into layer-wise subproblems. In each layer, one aims to select a pruning mask and update weights to minimize reconstruction error. Adaprune (Hubara et al., 2021) solves layer-wise reconstruction by updating weights directly via gradient descent (using Adam optimizer). However, it needs many iterations to achieve convergence. Optimal brain compression (OBC) (Frantar & Alistarh, 2022) removes weights one by one. In each step, it calculates the optimal weight to remove and also the optimal update. However, this approach is also very time-consuming for pruning LLMs. The first practical approach applicable to LLMs was SparseGPT (Frantar & Alistarh, 2023) using approximations on top of the OBC approach to make the problem feasible, albeit at the cost of decreased reconstruction quality.

Recently, Wanda (Sun et al., 2023) showed that LLMs can pruned by removing weights with the smallest product of weight magnitude and corresponding input activation norm. This selection approach without the weight update is competitive with SparseGPT on lower sparsities (up to 60%).

Table 1: WikiText perplexity of pruned LLaMA-7B. Our ADMM-based methods are superior to previous ones.

Method	Sparsity	Perplexity
Dense	0 %	5.68
Wanda	50 %	7.26
SparseGPT	50 %	7.22
ADMM1	50 %	7.20
ADMM-Gradual	50 %	**7.06**
Wanda	60 %	10.66
SparseGPT	60 %	10.51
ADMM1	60 %	9.96
ADMM-Gradual	60 %	**9.22**
Wanda	70 %	85.77
SparseGPT	70 %	26.30
ADMM1	70 %	26.31
ADMM-Gradual	70 %	**18.66**
Wanda	80 %	5e3
SparseGPT	80 %	154.75
ADMM1	80 %	202.04
ADMM-Gradual	80 %	**69.46**
Wanda	2:4	11.53
SparseGPT	2:4	11.00
ADMM1	2:4	10.38
ADMM-Gradual	2:4	**9.90**

Our results. In this paper, we introduce an efficient layer-wise weight update algorithm based on alternating direction method of multipliers (ADMM) (Boyd et al., 2011). Our algorithm sidesteps all of the problems of previous solutions. We only need a single inversion of a matrix similar in size to the weight matrix and very few simple iterations to achieve optimal weight updates for a given pruning mask. Furthermore, we extend our algorithm with gradual pruning (Zhu & Gupta, 2018), where in each step, we prune more and more weights. This simple extension allows us to obtain state-of-the-art pruning results at a very low additional cost.

2 Preliminaries

We consider a scenario of post-training pruning, where we prune an already trained model to a desired sparsity (we assume that the sparsity is the same in each pruned layer).

2.1 One-shot and layer-wise pruning

Since manipulating the whole LLM at once leads to huge computational and memory requirements, we follow the works of Hubara et al. (2021); Frantar & Alistarh (2022; 2023). We prune LLM during one forward pass (one-shot pruning) and split pruning into multiple layer-wise subproblems. During the forward pass, we capture the calibration inputs for each layer and then prune and update each layer accordingly.

We are given the original weights W_ℓ for each layer and calibration inputs X_ℓ. Our goal is to find a binary weight mask M_ℓ and updated weights $\widehat{W}_\ell$ such that the following reconstruction error is minimized:

$$||X_\ell W_\ell - X_\ell(M_\ell \odot \widehat{W}_\ell)||_2^2$$

For now, we assume that pruning mask M_ℓ was found via a separate method and focus only on finding updated weights $\widehat{W}_\ell$.

Assuming that our layer has n output neurons and m inputs, one can just solve n independent linear regressions to solve the problem optimally. Since the mask for each output is different, each one of n outputs requires a separate matrix inversion of the relevant submatrix of $X_\ell^T X_\ell$, which in total takes $O(m^3 n)$ time. This is infeasible even for small neural networks. It is possible to use various approximations to compute update faster, as shown in Frantar & Alistarh (2023). However, we demonstrate in our experiments that this compromises the quality of the solution.

Another possible solution is to update weights iteratively via gradient descent as in Adaprune (Hubara et al., 2021). Here, one update step is proportional to $X_\ell^T X_\ell (M_\ell \odot \widehat{W}_\ell - W_\ell)$. Assuming $X_\ell^T X_\ell$ is precomputed, one update step takes $O(m^2 n)$ time. While this looks much better than solving n linear regressions, Frantar & Alistarh (2023) as well as our own experiments show that one needs many iterations to achieve reasonable convergence.

2.2 Alternating Direction Method of Multipliers

Alternating direction method of multipliers (ADMM) (Boyd et al., 2011) is an optimization method for solving problems in the form :

$$\begin{aligned} \text{minimize} \quad & f(x) + g(z) \\ \text{subject to} \quad & Ax + Bz = c \end{aligned}$$

where $f(x)$ and $g(x)$ are convex functions. ADMM forms the augmented Lagrangian (u is scaled dual variable and ρ is a penalty factor):

$$L_\rho(x, z, u) = f(x) + g(z) + \frac{\rho}{2}(||Ax + Bz - c + u||_2^2 - ||u||_2^2)$$

The Lagrangian is then optimized via the following iterations:

$$\begin{aligned} x^{k+1} &= \arg\min_x f(x) + (\rho/2)||Ax + Bz^k - c + u^k||_2^2 \\ z^{k+1} &= \arg\min_z g(z) + (\rho/2)||Ax^{k+1} + Bz - c + u^k||_2^2 \\ u^{k+1} &= u^k + Ax^{k+1} + Bz^{k+1} - c \end{aligned}$$

One application of ADMM is solving constrained optimization over convex set C, i.e.:

$$\begin{aligned} \text{minimize} \quad & f(x) \\ \text{subject to} \quad & x \in C \end{aligned}$$

This problem can be rewritten into ADMM form using indicator function g, where $g(z) = 0$ if $z \in C$, and $g(z) = \infty$ otherwise:

$$\begin{aligned} \text{minimize} \quad & f(x) + g(z) \\ \text{subject to} \quad & x - z = 0 \end{aligned} \tag{1}$$

In this case, the ADMM update becomes:

$$\begin{aligned} x^{k+1} &= \arg\min_x f(x) + (\rho/2)||x - z^k + u^k||_2^2 \\ z^{k+1} &= \Pi_C(x^{k+1} + u^k) \\ u^{k+1} &= u^k + x^{k+1} - z^{k+1} \end{aligned} \tag{2}$$

Here, Π_C is an Euclidean projection operation onto set C. Also, note that the x update is just the original unconstrained problem with a simple quadratic penalty term.

3   Methods

Algorithm 1 Layerwise gradual pruning with ADMM. Given weight matrix W, calibration input X, desired sparsity s_f, number of iterations k, number of sparsification steps k_s, dampening factor λ (usually 0.1) and penalty factor ρ (usually 1), we prune matrix W to desired sparsity and optimally update weights for the given weight mask.

$norm \leftarrow ||X||_2 + \epsilon$
$W \leftarrow W * norm$
$X \leftarrow X/norm$
$XX \leftarrow X^T X + \lambda I$ // λ is usually 0.1
$XXW \leftarrow XX \cdot W$ // precomputation
$XX^{-1} = (XX + \rho I)^{-1}$
for $step = 1..k$ **do**
  if $step <= k_s$ **then**
    $s_i = s_f \left(\frac{i}{k_s}\right)^3$
    $M \leftarrow$ `mask lowest` s_i `indices`
        `from` $|W + U|$
  end if
  $Z \leftarrow (W + U) * M$
  $U \leftarrow U + (W - Z)$
  $W \leftarrow XX^{-1}(XXW + \rho(Z - U))$
end for
$W \leftarrow (W + U) * M/norm$

Here, we propose an alternative solution to finding updated weights in the layer-wise pruning problem. Our solution will have same iteration complexity as gradient descent, but will converge much faster. Recall, that we are looking for $\widehat{W}_\ell$, such that reconstruction error $||X_\ell W_\ell - X_\ell(M_\ell \odot \widehat{W}_\ell)||_2^2$ is minimized.

We observe that when a set of zeroed weights is fixed, valid weight matrices form a convex set C. In other words, we are solving the following constrained optimization problem (we omit ℓ subscript for clarity):

$$\min_{\widehat{W}} \quad ||XW - X\widehat{W}||_2^2$$
$$\text{subject to} \quad \widehat{W} \odot (1 - M) = 0$$

Note that our objective is also convex and thus we can use ADMM to solve our optimization problem. We denote our objective as $f(\widehat{W}) = ||XW - X\widehat{W}||_2^2$ and we will use indicator function $g(Z)$ which takes value 0 if $Z \odot (1 - M) = 0$ and ∞ otherwise. Using formulation (1) and updates (2), we get following iterations:

$$\widehat{W}^{k+1} = \arg\min_{\widehat{W}} f(\widehat{W}) + (\rho/2)||\widehat{W} - Z^k + U^k||_2^2$$
$$Z^{k+1} = \Pi_C(\widehat{W}^{k+1} + U^k)$$
$$U^{k+1} = U^k + \widehat{W}^{k+1} - Z^{k+1}$$

In our case, Z-update is just a projection onto the set of valid matrices, thus:

$$Z^{k+1} = (\widehat{W}^{k+1} + U^k) \odot M$$

Updating $\widehat{W}$ is very similar to ridge regression and can be computed as:

$$\widehat{W}^{k+1} = (X^T X + \rho I)^{-1}(X^T X W + \rho(Z^k - U^k))$$

We can precompute and cache $(X^T X + \rho I)^{-1}$ and $X^T X W$, and then this update has $O(m^2 n)$ complexity, which is the same as the complexity of gradient descent.

One can also view $\widehat{W}$ as a way of pulling pruned weights towards zero. Note that for unpruned weights, the penalty term $(\rho/2)||\widehat{W} - (Z^k - U^k)||_2^2$ only limits the step size, but for pruned weights, the value of $Z^k - U^k$ will have different sign than the value of W and thus they will be strongly pulled towards zero.

3.1 Mask selection and preconditioning

In the previous section, we described how to update weights when we are given the sparsity mask. Now, we will discuss how to select the mask for pruning.

Wanda (Sun et al., 2023) is a simple rule to select a high-quality mask for pruning LLMs. Instead of selecting weights with the largest value (magnitude pruning), they select weights with the highest product of weight absolute value and input neuron norm, i.e. $|W_{ij}| \cdot ||X_j||_2$. In our implementation, we follow this selection rule, but we use the norm of inputs as preconditioning. We multiply the weight matrix by feature norms and divide calibration inputs by their feature norms, run the ADMM algorithm, and then normalize the weight matrix back. Note that after the preconditioning, selecting the mask by weight magnitude is equivalent to the Wanda algorithm and that the diagonal of $X^T X$ contains only ones.

Wanda paper also suggests keeping a constant number of weights per output. We found that in our case with weight update, this constraint is actually slightly detrimental, and in our work, we select the top weights for the whole layer.

3.2 Gradual pruning

Until now, we considered a scenario where one selects the pruning mask first and then updates weights. Here, we propose a simple extension to our algorithm, which progressively prunes more and more weights and simultaneously computes the weight update. Note, that this still happens during one forward pass, we will just apply multiple iterations to one layer-wise problem.

We adopt cubic sparsity schedule from (Zhu & Gupta, 2018), where sparsity at step t is computed as $s_t = s_f \left(\frac{t}{k_s}\right)^3$, where s_f is final sparsity and k_s is the number of sparsification steps. In each step, we set s_t weights to zero and then proceed with the ADMM update. Note, that only overhead of gradual pruning is just a mask selection added into each step. While Z^k represents the current valid solution, we found that it is slightly better to use $W^{k+1} + U^k$ for selecting weights to prune. This is actually the optimal choice if our constraint (function g) was a specific sparsity, not a predefined mask. We summarize our pruning algorithm in Algorithm 1.

We also extend gradual pruning to structured 2:4 sparsity using the following straightforward idea. Our final sparsify will be $s_f = 0.5$. If in step t our target sparsity is s_t, then we always keep the two highest elements from each group of four and then prune $2s_t$ weights from the remaining ones.

3.3 Note on using ADMM with L_0 penalty

It is possible to use ADMM to optimize functions under L_0 constraint heuristically. This was previously done by Zhang et al. (2018); Ye et al. (2019); Gui et al. (2019). While some of the papers claim that this approach is "systematic", in reality, using ADMM with L_0 constraint is just a heuristic since the constraint is not convex. Moreover, in our preliminary experiments, we found that ADMM with L_0 is very sensitive to the choice of ρ, and for some choices, it will actually run in cycles and not converge.

Figure 1: Reconstruction error over time (in seconds) during optimization of weights in selected layers of LLaMA-7B. The mask was derived by Wanda using 50% sparsity. We compare our proposed ADMM algorithm to SGD with momentum and Adam using various learning rates. We also compare to the SparseGPT update. Our ADMM update converges much faster than other methods and is better than the SparseGPT update.

Figure 2: WikiText perplexity vs time overhead for ADMM, Adam, and SparseGPT weight update on LLaMA-7B. We run ADMM and Adam for 1, 10, 20, 50 and 100 update steps and test Adam with various learning rates. The top plot shows 60% sparsity. The bottom one uses 80% sparsity. SparseGPT full refers to normal SparseGPT, which also selects the pruning mask gradually. All other options just update weights over a fixed mask selected by Wanda. Our weight update is better than the one in SparseGPT and better than gradient-based methods.

4 Experiments

General setup. We implement our algorithms by extending the Wanda (Sun et al., 2023) codebase, which relies on Pytorch and the Huggingface library. Similarly to Wanda, we use 128 calibration samples from the C4 training dataset (Raffel et al., 2020). We run pruning on a machine with two Quadro RTX 5000 GPUs (each with 16GB of GPU memory). Since we prune layers sequentially in order, we need only to load one layer to GPU memory at one time. This allows us to prune 70B parameter LLaMA models using a relatively small GPU.

Models and evaluation. We test our methods on LLaMA (Touvron et al., 2023a) and LLaMA2 (Touvron et al., 2023b) models. Similarly to previous works (Frantar & Alistarh, 2023; Sun et al., 2023), we measure the performance of pruned models on language modeling and zero-shot tasks. Our main focus is perplexity on held-out WikiText (Merity et al., 2016), considered a goto metric for evaluating language model compression (Frantar & Alistarh, 2023). As an additional verification and testing, we use the same seven tasks as Wanda uses from EleutherAI LM Harness (Gao et al., 2021).

4.1 Reconstruction error convergence

As a first experiment, we study the quality of our update algorithm. We use a fixed sparsity mask derived using Wanda with 50% sparsity and observe reconstruction error convergence in one layer. We compare our algorithm to gradient-based approaches using Adam and SGD optimizers with varying learning rates. We also compare it to the SparseGPT update (without mask selection) used in the Wanda paper.

The results for selected layers of LLaMA-7b are presented in Figure 1. Our ADMM-based algorithm is superior to both gradient-based algorithms and SparseGPT as it converges almost instantly after computing the initial $X^T X$ matrix inverse. We also note that ADMM works well with the default setting of $\rho = 1$ and does not require learning rate tuning, which starkly contrasts with SGD and Adam, which have different optimal learning rates in different layers.

4.2 Weight update quality comparison

In this experiment, we first prune each layer of LLaMA-7B to 60% or 80% sparsity using Wanda mask selection and then update weights either using gradient-based (via Adam) or ADMM update. We select the pruning mask in a single step, i.e., we do not do any gradual mask selection. We test using 1, 10, 20, 50, and 100 update steps. We also test the performance of SparseGPT weight update and, for reference, include results of running SparseGPT with its own gradual mask selection.

We measure perplexity on Wikitext and time overhead (over forward pass) for each update option. Using just one update step, we can almost beat SparseGPT and all gradient-based algorithms (Figure 2). The ADMM update almost converges with ten update steps, while the gradient-based algorithms need more than 100 steps. ADMM is thus clearly a faster and superior weight update algorithm compared to the gradient-based update. Our algorithm also provides a better weight update than SparseGPT weight update, and at 60% sparsity, it is even better than SparseGPT with its own iterative mask selection.

Furthermore, we explicitly compare SparseGPT and ADMM weight updates over different weight masks. We select either Wanda or SparseGPT mask and apply SparseGPT or ADMM weight update (in the case of SparseGPT mask, SparseGPT update is no-op, and for ADMM update, we rewind weights and keep the selected mask). Results are summarized in Table 2. Our ADMM weight update is always better than SparseGPT update.

4.3 Pruning LLaMA-7B

Based on previous observations, we set the number of update iterations to 20, which should provide a pruning overhead similar to SparseGPT (Table 3) and also guarantee reasonable convergence of weight updates. We compare our weight update after mask selection without gradual pruning (ADMM1), our gradual pruning algorithm, which computes the mask over 15 iterations (ADMM-Gradual) with Wanda and SparseGPT

Table 2: Comparision of weight update quality between ADMM and SparseGPT on Llama-7B using 60% sparsity.

Mask selection	Weight update	Perplexity
Wanda	SparseGPT	10.86
Wanda	ADMM	9.96
SparseGPT	SparseGPT	10.51
SparseGPT	ADMM	9.92

Table 3: Total pruning time for Llama-7B

Method	Total seconds
Wanda	245
SparseGPT	850
ADMM1	832
ADMM-Gradual	869

pruning. We prune LLaMA-7b to various sparsities and also with 2:4 structured sparsity. First, we measure Wikitext perplexity (Table 1). We see that our weight update over a fixed Wanda mask (ADMM1) produces better results than any other algorithm at 50%, 60%, and 2:4 sparsities. Note that SparseGPT generates the pruning mask iteratively, which gives it a slight edge in higher sparsities. When selecting the mask gradually, we are superior to all previously developed algorithms, especially at higher sparsities.

Finally, we measure performance on seven zero-shot tasks (we use the same selection as the authors of Wanda): BoolQ (Clark et al., 2019), RTE (Wang et al., 2018), HellaSWAG (Zellers et al., 2019), WinoGrande (Sakaguchi et al., 2021), ARC easy and challenge (Clark et al., 2018), and OpenbookQA (Mihaylov et al., 2018).

Our results (Table 4) show that our algorithm is superior to the previous ones except for the RTE task. We note that results for the RTE task are slightly erratic (e.g. there is better performance at 60% sparsity than at 50%). We attribute this to the small RTE dataset size (277 samples). Notably, we recover 30-40% of the performance drop of SparseGPT on the BoolQ task at 50-70% sparsities and also on WinoGrande task using 50-60% sparsities. When using 2:4 sparsity, we recover 20-25% of the performance drop on WinoGrande and ARC-e tasks.

4.4 Pruning LLaMA-2 variants

Our algorithm generalizes and scales to bigger LLMs. We test it on variants of LLaMA-2 at various sparsity levels. Table 5 shows that our method is superior to previous ones, except at 2:4 sparsity on LLaMA2-70B. We note quite a substantial improvement of our algorithm over previous ones at 60% sparsity and also at 2:4 sparsity on 7B and 13B models.

5 Conclusions

In this work, we presented a simple, fast, and accurate post-pruning weight update algorithm based on the alternating direction method of multipliers. We showed that our algorithm converges much faster than any previously available option. Our weight update method is also theoretically sound and does not rely on any heuristical decisions or approximations.

We further improved the pruning performance by doing gradual mask selection and weight updates. This achieves state-of-the-art performance in layer-wise pruning setting, much better than previous solutions like Wanda or SparseGPT.

Our main limitation is that our update rule runs over dense matrices, and thus, during update computation, we have no time or space savings from potential sparsity. We hope to address this in future work.

Table 4: Zero shot accuracies on various tasks during pruning of LLaMA-7B

Sparsity	Method	BoolQ	RTE	HellaSwag	WinoGrande	ARC-e	ARC-c	OBQA	Mean
0 %	Dense	75.05	66.43	56.92	69.93	75.34	41.89	34.40	59.99
50%	Wanda	71.22	**55.60**	51.85	66.06	69.11	36.86	28.80	54.21
	SparseGPT	73.05	52.34	51.21	68.42	70.70	36.43	28.60	54.39
	ADMM-Gradual	**73.63**	52.34	**52.33**	**69.13**	**70.74**	**37.88**	**30.20**	**55.18**
60%	Wanda	69.26	59.56	43.76	62.35	62.58	30.29	25.20	50.43
	SparseGPT	70.7	**62.09**	44.84	65.58	64.14	30.97	25.20	51.93
	ADMM-Gradual	**72.41**	58.84	**46.61**	**66.77**	**64.52**	**31.65**	**26.20**	**52.43**
70%	Wanda	59.78	58.12	28.81	50.82	32.40	18.85	14.20	37.57
	SparseGPT	62.35	**55.95**	33.77	59.35	45.70	23.97	17.20	42.61
	ADMM-Gradual	**66.05**	53.79	**36.29**	**59.74**	**50.84**	**25.50**	**18.60**	**44.40**
80%	Wanda	37.82	48.37	26.29	48.77	27.23	**20.56**	13.00	31.72
	SparseGPT	41.89	**52.70**	27.83	48.38	30.30	18.77	**13.40**	33.32
	ADMM-Gradual	**56.14**	**52.70**	**28.75**	**50.74**	**31.56**	18.94	12.40	**35.89**
2:4	Wanda	69.3	51.99	42.06	62.75	60.94	28.07	24.60	48.53
	SparseGPT	**70.46**	**60.65**	42.99	64.88	61.49	30.12	23.60	50.60
	ADMM-Gradual	70.27	55.59	**44.88**	**66.14**	**64.18**	**30.97**	**25.20**	**51.03**

Table 5: Perplexity of pruned LLaMA-2 variants on WikiText

Method	Sparsity	7B	13 B	70B
Dense	0 %	5.12	4.57	3.12
Wanda	50 %	6.42	5.56	3.98
SparseGPT	50 %	6.51	5.63	3.98
ADMM-Gradual	50 %	**6.33**	**5.52**	**3.95**
Wanda	60 %	9.71	7.75	4.98
SparseGPT	60 %	9.58	7.80	4.98
ADMM-Gradual	60 %	**8.70**	**7.09**	**4.81**
Wanda	80 %	5e3	2e3	1e2
SparseGPT	80 %	108.87	94.23	25.86
ADMM-Gradual	80 %	**55.93**	**43.58**	**18.84**
Wanda	2:4	11.02	8.27	**5.16**
SparseGPT	2:4	10.17	8.32	5.40
ADMM-Gradual	2:4	**9.74**	**7.78**	5.19

The pruning results can certainly be improved by using nonuniform sparsity across layers (Yin et al., 2023); for now, we leave this as a future work. Another option for improvement is to use a more accurate mask selection rule, such as one in Optimal brain surgeon (Hassibi et al., 1993). Also, our algorithm provides an efficient update rule for sparse matrices and can be used in some advanced optimizers like FOOF (Benzing, 2022).

References

Arash Ahmadian, Saurabh Dash, Hongyu Chen, Bharat Venkitesh, Stephen Gou, Phil Blunsom, Ahmet Üstün, and Sara Hooker. Intriguing properties of quantization at scale. *arXiv preprint arXiv:2305.19268*, 2023.

Frederik Benzing. Gradient descent on neurons and its link to approximate second-order optimization. In *International Conference on Machine Learning*, pp. 1817–1853. PMLR, 2022.

Davis Blalock, Jose Javier Gonzalez Ortiz, Jonathan Frankle, and John Guttag. What is the state of neural network pruning? *Proceedings of machine learning and systems*, 2:129–146, 2020.

Stephen Boyd, Neal Parikh, Eric Chu, Borja Peleato, Jonathan Eckstein, et al. Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends® in Machine learning*, 3(1):1–122, 2011.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. Boolq: Exploring the surprising difficulty of natural yes/no questions. *arXiv preprint arXiv:1905.10044*, 2019.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Tim Dettmers and Luke Zettlemoyer. The case for 4-bit precision: k-bit inference scaling laws. In *International Conference on Machine Learning*, pp. 7750–7774. PMLR, 2023.

Tim Dettmers, Mike Lewis, Younes Belkada, and Luke Zettlemoyer. Llm. int8 (): 8-bit matrix multiplication for transformers at scale. *arXiv preprint arXiv:2208.07339*, 2022.

Elias Frantar and Dan Alistarh. Optimal brain compression: A framework for accurate post-training quantization and pruning. *Advances in Neural Information Processing Systems*, 35:4475–4488, 2022.

Elias Frantar and Dan Alistarh. Sparsegpt: Massive language models can be accurately pruned in one-shot. In *International Conference on Machine Learning*, pp. 10323–10337. PMLR, 2023.

Leo Gao, Jonathan Tow, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Kyle McDonell, Niklas Muennighoff, et al. A framework for few-shot language model evaluation. *Version v0. 0.1. Sept*, 2021.

Shupeng Gui, Haotao Wang, Haichuan Yang, Chen Yu, Zhangyang Wang, and Ji Liu. Model compression with adversarial robustness: A unified optimization framework. *Advances in Neural Information Processing Systems*, 32, 2019.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. *Advances in neural information processing systems*, 28, 2015.

Babak Hassibi, David G Stork, and Gregory J Wolff. Optimal brain surgeon and general network pruning. In *IEEE international conference on neural networks*, pp. 293–299. IEEE, 1993.

Itay Hubara, Brian Chmiel, Moshe Island, Ron Banner, Joseph Naor, and Daniel Soudry. Accelerated sparse neural training: A provable and efficient method to find n: m transposable masks. *Advances in neural information processing systems*, 34:21099–21111, 2021.

Yann LeCun, John Denker, and Sara Solla. Optimal brain damage. *Advances in neural information processing systems*, 2, 1989.

Zhuang Liu, Mingjie Sun, Tinghui Zhou, Gao Huang, and Trevor Darrell. Rethinking the value of network pruning. *arXiv preprint arXiv:1810.05270*, 2018.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering. *arXiv preprint arXiv:1809.02789*, 2018.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *The Journal of Machine Learning Research*, 21(1):5485–5551, 2020.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021.

Mingjie Sun, Zhuang Liu, Anna Bair, and J Zico Kolter. A simple and effective pruning approach for large language models. *arXiv preprint arXiv:2306.11695*, 2023.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023a.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajjwal Bhargava, Shruti Bhosale, et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023b.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

Haojun Xia, Zhen Zheng, Yuchao Li, Donglin Zhuang, Zhongzhu Zhou, Xiafei Qiu, Yong Li, Wei Lin, and Shuaiwen Leon Song. Flash-llm: Enabling cost-effective and highly-efficient large generative model inference with unstructured sparsity. *arXiv preprint arXiv:2309.10285*, 2023.

Guangxuan Xiao, Ji Lin, Mickael Seznec, Hao Wu, Julien Demouth, and Song Han. Smoothquant: Accurate and efficient post-training quantization for large language models. In *International Conference on Machine Learning*, pp. 38087–38099. PMLR, 2023.

Shaokai Ye, Kaidi Xu, Sijia Liu, Hao Cheng, Jan-Henrik Lambrechts, Huan Zhang, Aojun Zhou, Kaisheng Ma, Yanzhi Wang, and Xue Lin. Adversarial robustness vs. model compression, or both? In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 111–120, 2019.

Lu Yin, You Wu, Zhenyu Zhang, Cheng-Yu Hsieh, Yaqing Wang, Yiling Jia, Mykola Pechenizkiy, Yi Liang, Zhangyang Wang, and Shiwei Liu. Outlier weighed layerwise sparsity (owl): A missing secret sauce for pruning llms to high sparsity. *arXiv preprint arXiv:2310.05175*, 2023.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? *arXiv preprint arXiv:1905.07830*, 2019.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*, 2022.

Tianyun Zhang, Shaokai Ye, Kaiqi Zhang, Jian Tang, Wujie Wen, Makan Fardad, and Yanzhi Wang. A systematic dnn weight pruning framework using alternating direction method of multipliers. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 184–199, 2018.

Michael Zhu and Suyog Gupta. To prune, or not to prune: Exploring the efficacy of pruning for model compression. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Workshop Track Proceedings*. OpenReview.net, 2018. URL `https://openreview.net/forum?id=Sy1iIDkPM`.