Single-Pass Contrastive Learning Can Work for Both Homophilic and Heterophilic Graph

Abstract

Existing graph contrastive learning (GCL) techniques typically require two forward passes for a single instance to construct the contrastive loss, which is effective for capturing the low-frequency signals of node features. Such a dual-pass design has shown empirical success on homophilic graphs, but its effectiveness on heterophilic graphs, where directly connected nodes typically have different labels, is unknown. In addition, existing GCL approaches fail to provide strong performance guarantees. Coupled with the unpredictability of GCL approaches on heterophilic graphs, their applicability in real-world contexts is limited. Then, a natural question arises: *Can we design a GCL method that works for both homophilic and heterophilic graphs with a performance guarantee?* To answer this question, we theoretically study the concentration property of features obtained by neighborhood aggregation on homophilic and heterophilic graphs, introduce the single-pass graph contrastive learning loss based on the property, and provide performance guarantees for the minimizer of the loss on downstream tasks. As a direct consequence of our analysis, we implement the **S**ingle-**P**ass **G**raph **C**ontrastive **L**earning method (SP-GCL). Empirically, on 14 benchmark datasets with varying degrees of homophily, the features learned by the SP-GCL can match or outperform existing strong baselines with significantly less computational overhead, which demonstrates the usefulness of our findings in real-world cases. The anonymized code is available at `anonymous.4open.science/r/SPGCL-F723`.

1 Introduction

Graph Contrastive Learning (GCL) (Xie et al., 2021), as an approach for learning better representation without the demand of manual annotations, has attracted great attention in recent years. Existing works of GCL could be roughly divided into two categories according to whether or not a graph augmentation is employed. First, the *augmentation-based* GCL (You et al., 2020; Peng et al., 2020; Hassani & Khasahmadi, 2020; Zhu et al., 2021a;b; 2020d;c; Thakoor et al., 2021) follows the initial exploration of contrastive learning in the visual domain (Chen et al., 2020; He et al., 2020) and involves pre-specified graph augmentations (Zhu et al., 2021a); specifically, these methods encourage representations of the same node encoded from *two augmentation* views to contain as less information about the way the inputs are transformed as possible during training, *i.e.*, to be invariant to a set of manually specified transformations. Second, *augmentation-free* GCL (Lee et al., 2021; Xia et al., 2022) follows the recent bootstrapped framework (Grill et al., 2020) and constructs different views through *two encoders* of different updating strategies and pushes together the representations of the same node/class. For both categories, there has been notable success on homophilic graphs (where directly linked nodes tend to have similar features or same class labels).

However, real-world graphs do not necessarily adhere to the homophily assumption, but may instead exhibit heterophily, in which directly connected nodes have contrasting characteristics and different class labels. In addition, earlier research shows the importance of high-frequency information for heterophilic graphs (Bo et al., 2021), whereas the dual-pass GCL approaches tend to capture low-frequency information, which has been demonstrated in both theoretical analysis and empirical observations (Liu et al., 2022b; Wang et al., 2022a). Moreover, the homophily degree is specified by the node labels, which are difficult to obtain

in real-world situations; this makes it infeasible to determine if it is appropriate to apply a homophilic-customized GCL algorithm to a given graph. Coupled with the absence of a strong performance guarantee, the applicability of GCL methods in a variety of real-world scenarios is restricted. Therefore, in this paper, we ask the following question:

Can one design a simple graph contrastive learning method that is effective on both homophilic and heterophilic graphs with performance guarantee?

We provide an affirmative answer to this question both theoretically and empirically. First, we study the neighborhood aggregation mechanism on a homophilic/heterophilic graph and present the concentration property of the aggregated features that is independent of the graph type. By exploiting such a property, we introduce the single-pass graph contrastive loss, and show that its minimizer is equivalent to that of Matrix Factorization (MF) over the transformed graph where the edges are constructed based on the aggregated features. In turn, the transformed graph introduced conceptually is able to help us illustrate and derive the theoretical guarantee for the performance of the learned representations in the down-streaming node classification task.

To verify our theoretical findings, we present a direct implementation of our analysis, **S**ingle-**P**ass **G**raph **C**ontrastive **L**earning (SP-GCL). Experimental results show that SP-GCL achieves competitive performance on 8 homophilic graph benchmarks and outperforms state-of-the-art GCL algorithms on 6 heterophilic graph benchmarks with a substantial margin. Besides, we analyze the computational complexity of SP-GCL and empirically demonstrate a significant reduction of computational overhead brought by SP-GCL. Coupling with extensive ablation studies, we demonstrate that the techniques derived from our theoretical analysis are effective for real-world cases.

Our contribution could be summarized as:

- We demonstrate that the concentration attribute of representations derived by neighborhood feature aggregation is independent of graph type, which in turn drives our novel single-pass graph contrastive learning loss. A direct consequence is a graph contrastive learning method, SP-GCL, without relying on graph augmentations.

- We derive a theoretical guarantee for the node embedding obtained by optimizing the graph contrastive learning loss in the downstream node classification task.

- Experimental results show that without complex designs, compared with SOTA GCL methods, SP-GCL achieves competitive or better performance on 8 homophilic graph benchmarks and 6 heterophilic graph benchmarks, with significantly less computational overhead.

2 Related Work

Graph contrastive learning. Existing graph contrastive learning methods can be categorized into augmentation-based and augmentation-free methods, according to whether or not the graph augmentation techniques are employed during training. The augmentation-based methods (You et al., 2020; Peng et al., 2020; Hassani & Khasahmadi, 2020; Zhu et al., 2021a;b; 2020d; Thakoor et al., 2021; Zhu et al., 2020c) encourage the target graph encoder to be invariant to the manually specified graph transformations. Therefore, the design of graph augmentation is critical to the success of augmentation-based GCL. We summarized the augmentation methods commonly used by recent works in Table 8 of Appendix C. Other works (Lee et al., 2021; Xia et al., 2022) try to get rid of the manual design of augmentation strategies, following the bootstrapped framework (Grill et al., 2020). They construct different views through two graph encoders updated with different strategies and push together the representations of the same node/class from different views. In both categories, those existing GCL methods require two graph forward-pass. Specifically, two augmented views of the same graph will be encoded separately by the same or two graph encoders for augmentation-based GCLs and the same graph will be encoded with two different graph encoders for augmentation-free GCLs, which is prohibitively expensive for large graphs. Besides, the theoretical analysis for the performance of GCL in the downstream tasks is still lacking. Although several efforts have been

made in the visual domain (Arora et al., 2019; Lee et al., 2020; Tosh et al., 2021; HaoChen et al., 2021), the analysis for image classification cannot be trivially extended to graph setting, since the non-Euclidean graph structure is far more complex.

Heterophilic graph. Recently, the heterophily has been recognized as an important issue for graph neural networks, which is outlined by Pei et al. (2020) firstly. To make graph neural networks able to generalize well on the heterophilic graph, several efforts have been done from both the spatial and spectral perspectives (Pei et al., 2020; Abu-El-Haija et al., 2019; Zhu et al., 2020a; Chien et al., 2020; Li et al., 2021; Bo et al., 2021). Firstly, Chien et al. (2020) and Bo et al. (2021) analyze the necessary frequency component for GNNs to achieve good performance on heterophilic graphs and propose methods that are able to utilize high-frequency information. From the spatial perspective, several graph neural networks are designed to capture important dependencies between distant nodes (Pei et al., 2020; Abu-El-Haija et al., 2019; Bo et al., 2021; Zhu et al., 2020a; Liu et al., 2021; 2022a). Although those methods have shown their effectiveness on heterophilic graphs, human annotations are required to guide the learning of neural networks.

3 Preliminary

Notation. Let $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ denote an undirected graph, where $\mathcal{V} = \{v_i\}_{i \in [N]}$ and $\mathcal{E} \subseteq \mathcal{V} \times \mathcal{V}$ denote the node set and the edge set respectively. We denote the number of nodes and edges as N and E, and the label of nodes as $\mathbf{y} \in \mathbb{R}^N$, in which $y_i \in \{1, \ldots, c\}$ and $c \geq 2$ is the number of classes. The associated node feature matrix denotes as $\mathbf{X} \in \mathbb{R}^{N \times F}$, where $\mathbf{x}_i \in \mathbb{R}^F$ is the feature of node $v_i \in \mathcal{V}$ and F is the input feature dimension. We denote the adjacent matrix as $\mathbf{A} \in \{0, 1\}^{N \times N}$, where $\mathbf{A}_{ij} = 1$ if $(v_i, v_j) \in \mathcal{E}$; and the corresponding degree matrix as $\mathbf{D} = \text{diag}(d_1, \ldots, d_N)$, $d_i = \sum_j \mathbf{A}_{i,j}$. Our objective is to unsupervisedly learn a GNN encoder $f_\theta : \mathbf{X}, \mathbf{A} \to \mathbb{R}^{N \times K}$ receiving the node features and graph structure as input, that produces node representations in low dimensionality, i.e., $K \ll F$. The representations can benefit the downstream supervised or semi-supervised tasks, e.g., node classification.

Homophilic and heterophilic graph. Various metrics have been proposed to measure the homophily degree of a graph. Here we adopt two representative metrics, namely, node homophily and edge homophily. The edge homophily (Zhu et al., 2020b) is the proportion of edges that connect two nodes of the same class: $h_{edge} = \frac{|\{(v_i, v_j):(v_i, v_j) \in \mathcal{E} \wedge y_i = y_j\}|}{E}$, And the node homophily (Pei et al., 2020) is defined as, $h_{node} = \frac{1}{N} \sum_{v_i \in \mathcal{V}} \frac{|\{v_j:(v_i, v_j) \in \mathcal{E} \wedge y_i = y_j\}|}{|\{v_j:(v_i, v_j) \in \mathcal{E}\}|}$, which evaluates the average proportion of edge-label consistency of all nodes. They are all in the range of $[0, 1]$ and a value close to 1 corresponds to strong homophily while a value close to 0 indicates strong heterophily. As conventional, we refer the graph with high homophily degree as homophilic graph, and the graph with a low homophily degree as heterophilic graph. And we provided the homophily degree of graph considered in this work in Table 1 of Section 6.1.

4 Theoretical Analyses

In this section, we first show the property of node representations obtained through neighbor aggregation (Theorem 1). Then, based on the property, we introduce the single-pass graph contrastive loss (Equation (4)), where the contrastive pairs are made using the node representations instead of the augmented graph. With Lemma 1, we bridge the graph contrastive loss and the Matrix Factorization. Then, leveraging the analysis for matrix factorization, we obtain the performance guarantee for the embedding learned by SP-GCL in the downstream node classification task (Theorem 3).

4.1 Analysis of Aggregated Features

Assumptions on graph data. To obtain analytic and conceptual insights into the aggregated features, we first describe the graph data we considered. Consider the GNN model:

$$Z = \sigma(\mathbf{D}^{-1}\mathbf{A}\mathbf{X}\ \mathbf{W}) \in \mathbb{R}^{N \times K}$$

where σ represents the nonlinear activation function, and $\mathbf{W} \in \mathbb{R}^{F \times K}$ is the weight. Assume that $\|\mathbf{x}_i\|_2 \leq R$ for some $R \geq 0$, where $\mathbf{x}_i \in \mathbb{R}^F$ represents the node features of i-th input node (i.e., the transpose of the i-th row of $\mathbf{X}$). Define $\mathbf{w}_k \in \mathbb{R}^F$ to be the k-th column of $\mathbf{W}$. Given a label y, the node feature $\mathbf{x}$ is sampled from some distribution $P_{x|y}$. For node v_i, its neighbors' labels are independently sampled from neighbor distribution P_{y_i}.

Remark. The above assumption means that the label of a neighbor is only determined by the label of the central node. This is feasible for both homophily and heterophily.

We assume that the nonlinear activation function σ is homogeneous of degree τ for some $\tau \geq 1$ and $\sigma(q) \leq cq$ for some $c \geq 0$. For example, ReLU activation satisfies these assumptions with $\tau = c = 1$. Also, it covers the result of the linear model too since if σ is identity (i.e., linear model), then $\tau = c = 1$. With this assumption, we present the following Theorem 1, where we denote the learned embedding through the neighbor aggregation and a linear projection by $\mathbf{Z}$, and $\mathbf{Z}_i$ represents the learned embedding with respect to node v_i.

Theorem 1 (Concentration Property of Aggregated Features) *For any $\boldsymbol{W} \in \mathbb{R}^{F \times K}$, the following statements holds:*

- *For any pair (i, i') such that $y_i = y_{i'}$,*

$$\mathbb{E}[\boldsymbol{Z}_i] - \mathbb{E}[\boldsymbol{Z}_{i'}] = 0. \tag{1}$$

- *With probability at least $1 - \delta$,*

$$\|\mathbb{E}[\boldsymbol{Z}_i] - \boldsymbol{Z}_i\|_\infty \leq cR \left(\max_{k \in [K]} \|\boldsymbol{w}_k\|_2 \right) \sqrt{\frac{2 \ln(2K/\delta)}{D_{ii}^{2\tau-1}}}. \tag{2}$$

- *For any node pair (i, j), with probability at least $1 - \delta'$,*

$$|\mathbb{E}[\boldsymbol{Z}_i^\top \boldsymbol{Z}_j] - \boldsymbol{Z}_i^\top \boldsymbol{Z}_j| \leq c^2 R^2 \sum_{k=1}^{K} \|\boldsymbol{w}_k\|_2^2 \sqrt{\frac{2 \ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1}}}. \tag{3}$$

Remark. The above theorem indicates that, for any graph following the graph data assumption: *(i)* in expectation, nodes with the same label have the same representation, Equation (1); *(ii)* the representations of nodes with the same label tend to concentrate onto a certain area in the embedding space, which can be regarded as the inductive bias of the neighborhood aggregation mechanism, Equation (2); *(iii)* the inner product of hidden representations approximates to its expectation with a high probability, Equation (3). (Proof is in Appendix B.1.)

Note that, in contrast to the earlier concentration study Ma et al. (2021), we improve the theoretical analysis of the aggregated features in the non-linear situation, which is closer to the GNN models employed in the real-world application. In addition, we empirically validate the derived concentration property (Theorem 1) on the multi-class real-world graph data with the non-linear graph neural network. The results in Section 6.7 and Table 6 support our analysis. Also, we provide a discussion about the empirical observations of the concentration property in other recent works (Wang et al., 2022b; Trivedi et al., 2022) in Section 7.

4.2 Single-Pass Graph Contrastive Loss

In order to learn a more compact and linearly separable embedding space, we introduce the single-pass graph contrastive loss based on the property of aggregated features. Taking advantage of the concentration attribute explicitly, we consider nodes with a small distance in the embedding space to be positive pairs, and we characterize randomly chosen nodes as negative pairs by convention (Arora et al., 2019; Chen et al., 2020). Also, a theoretical discussion is provided for this intuitive design (Theorem 2). We formally define the positive and negative pairs to introduce the loss. For node $v_i \in \mathcal{V}$, we draw the positive node v_{i+}

uniformly from the set S_{pos}^i. The set S_{pos}^i is consisted by the K_{pos} nodes closest to node v_i. Concretely, $S_{pos}^i = \{v_i^1, v_i^2, \ldots, v_i^{K_{pos}}\} = \arg\max_{v_j \in \mathcal{V}} \left(\mathbf{Z}_i^\top \mathbf{Z}_j, K_{pos} \right)$, where $K_{pos} \in \mathbb{Z}^+$ and $\arg\max(\cdot, K_{pos})$ denotes the operator for the top-K_{pos} selection. Two nodes, (v_i, v_{i+}), form a positive pair. For nodes v_j and v_k, sampled independently from the node set $\mathcal{V}$, can be regarded as a negative pair (v_j, v_k). Following the insight of contrastive learning (Wang & Isola, 2020), similar sample pairs stay close to each other while dissimilar ones are far apart, then the Single-Pass Graph Contrastive Loss is defined as,

$$\mathcal{L}_{\text{SP-GCL}} = -2 \mathop{\mathbb{E}}_{\substack{v_i \sim Uni(\mathcal{V}) \\ v_{i+} \sim Uni(S_{pos}^i)}} \left[\mathbf{Z}_i^\top \mathbf{Z}_{i+} \right] + \mathop{\mathbb{E}}_{\substack{v_j \sim Uni(\mathcal{V}) \\ v_k \sim Uni(\mathcal{V})}} \left[\left(\mathbf{Z}_j^\top \mathbf{Z}_k \right)^2 \right]. \tag{4}$$

4.3 Performance Guarantee for Learning Linear Classifier

For the convenience of analysis, we first introduce the concept of *transformed graph* as follows, which is constructed based on the original graph and the selected positive pairs. *Note, the transformed graph is a concept only used to illustrate the theoretical derivation, instead of the actual computation.*

Definition 1 (Transformed Graph) *Given the original graph $\mathcal{G}$ and its node set $\mathcal{V}$, the transformed graph, $\widehat{\mathcal{G}}$, has the same node set $\mathcal{V}$ but with the selected positive pairs as the edge set, $\widehat{\mathcal{E}} = \bigcup_i \{ (v_i, v_i^k)|_{k=1}^{K_{pos}} \}$.*

Remark. The transformed graph is formed by positive pairs selected based on aggregated features. Coupling with the *Concentration Property of Aggregated Features* (Theorem 1), the transformed graph tends to have a larger homophily degree than the original graph. We provide more empirical verifications in Section 6.7.

Positive pairs   Transformed graph

Figure 1: Transformed Graph formed with Positive Pairs.

The transformed graph is illustrated in Figure 1. We denote the adjacency matrix of transformed graph as $\widehat{\mathbf{A}} \in \{0,1\}^{N \times N}$, the number of edges as $\widehat{E}$, and the symmetric normalized matrix as $\widehat{\mathbf{A}}_{sym} = \widehat{\mathbf{D}}^{-1/2} \widehat{\mathbf{A}} \widehat{\mathbf{D}}^{-1/2}$, where $\widehat{\mathbf{D}} = \text{diag}\left(\hat{d}_1, \ldots, \hat{d}_N \right), \hat{d}_i = \sum_j \widehat{\mathbf{A}}_{i,j}$. Correspondingly, we denote the symmetric normalized Laplacian as $\widehat{\mathbf{L}}_{sym} = \mathbf{I} - \widehat{\mathbf{A}}_{sym} = \mathbf{U}\mathbf{\Lambda}\mathbf{U}^\top$. Here $\mathbf{U} \in \mathbb{R}^{N \times N} = [\mathbf{u}_1, \ldots, \mathbf{u}_N]$, where $\mathbf{u}_i \in \mathbb{R}^N$ denotes the i-th eigenvector of $\widehat{\mathbf{L}}_{sym}$ and $\mathbf{\Lambda} = \text{diag}\left(\lambda_1, \ldots, \lambda_N \right)$ is the corresponding eigenvalue matrix. λ_1 and λ_N be the smallest and largest eigenvalue respectively.

Then we show that optimizing a model with the contrastive loss (Equation (4)) is equivalent to the matrix factorization over the transformed graph, as stated in the following Lemma:

Lemma 1 *Denote the learnable embedding for matrix factorization as $\mathbf{F} \in \mathbb{R}^{N \times K}$. Let $\mathbf{F}_i = F_\psi(v_i)$. Then, the matrix factorization loss function $\mathcal{L}_{\text{mf}}$ is equivalent to the contrastive loss, Equation (4), up to an additive constant:*

$$\mathcal{L}_{\text{mf}}(\mathbf{F}) = \left\| \widehat{\mathbf{A}}_{sym} - \mathbf{F}\mathbf{F}^\top \right\|_F^2 = \mathcal{L}_{\text{SP-GCL}} + const \tag{5}$$

The above lemma bridges the graph contrastive learning and the graph matrix factorization and therefore allows us to provide the performance guarantee of SP-GCL by leveraging the power of matrix factorization. We leave the derivation in Appendix B.2. With the Theorem 1 and Lemma 1, we arrive at a conclusion about the expected value of the inner product of embeddings (More details in Appendix B.3):

Theorem 2 *For a graph G following the graph data assumption, then when the optimal of the contrastive loss is achieved, i.e., $\mathcal{L}_{\text{mf}}(\mathbf{F}^*) = 0$, we have,*

$$\mathbb{E}[\mathbf{Z}_i^\top \mathbf{Z}_j|_{y_i=y_j}] - \mathbf{E}[\mathbf{Z}_i^\top \mathbf{Z}_j|_{y_i \neq y_j}] \geq 1 - \bar{\phi}, \tag{6}$$

Figure 2: Overview of SP-GCL. The graph data is encoded by a graph neural network f_θ and a following projection head g_ω. The contrastive pairs are constructed based on the representation $\mathbf{Z}$.

where $\bar{\phi} = \mathbb{E}_{v_i, v_j \sim Uni(\mathcal{V})} (\widehat{\mathbf{A}}_{i,j} \cdot \mathbb{1}[y_i \neq y_j])$.

Remark. The $1 - \bar{\phi}$ means the probability of an edge connecting two nodes from the same class, which can be regarded as the edge homophily of the transformed graph. Its value is always greater than 0. The theorem implies that a pair of nodes coming from the same class are likely have larger inner product similarity than a pair of nodes coming from different classes.

Finally, with the Theorem 1 and Theorem 2, we obtain a performance guarantee for node embeddings learned by SP-GCL with a linear classifier in the downstream task (More details in Appendix B.4):

Theorem 3 *Let $f^*_{\text{SP-GCL}} \in \arg\min_{f:\mathcal{X} \to \mathbb{R}^K}$ be a minimizer of the contrastive loss, $\mathcal{L}_{\text{SP-GCL}}$. Then there exists a linear classifier $\mathbf{B}^* \in \mathbb{R}^{c \times K}$ with norm $\|\mathbf{B}^*\|_F \leq 1/(1 - \lambda_K)$ such that, with a probability at least $1 - \delta$,*

$$\mathbb{E}_{v_i} \left[\left\| \vec{y}_i - \mathbf{B}^* f^*_{\text{gcl}}(v) \right\|_2^2 \right] \leq \frac{\bar{\phi}}{\hat{\lambda}_{K+1}} \quad + c^2 R^2 \sum_{k=1}^{K} \|\mathbf{w}_k\|_2^2 \sqrt{\frac{2 \ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1} \hat{\lambda}_{K+1}^2}}, \tag{7}$$

$\hat{\lambda}_i$ are the i smallest eigenvalues of the symmetrically normalized Laplacian matrix of the transformed graph.

5 Single-Pass Graph Contrastive Learning (SP-GCL)

As a direct consequence of our theory, we introduce the Single-Pass Graph Contrastive Learning (SP-GCL). Instead of relying on the graph augmentation function or the exponential moving average, our novel learning framework only forwards a single time and constructs contrastive pairs based on the aggregated features. As we shall see, this extremely simple, theoretically grounded strategy also achieves superior performance in practice than dual-pass graph contrastive learning methods on homophilic and heterophilic graph benchmarks.

According to the results of the analysis, for each class, the embedding generated through neighbor aggregation will converge on the expected class embedding. We build the self-supervision signal based on the discovered embedding and offer a novel single-pass graph contrastive learning framework, SP-GCL, that picks similar nodes as positive node pairings. As shown in Figure 2, in each iteration, the proposed framework firstly encodes the graph with a graph encoder f_θ denoted by $\mathbf{H} = f_\theta(\mathbf{X}, \mathbf{A})$. Then, a projection head with *L2*-normalization, g_ω, is employed to project the node embedding into the hidden representation $\mathbf{Z} = g_\omega(\mathbf{H})$. To scale up SP-GCL on large graphs, the node pool, P, are constructed by the T-hop neighborhood of b nodes (the seed node set S) uniformly sampled from $\mathcal{V}$. For each seed node $v_i \in S$, the top-K_{pos} nodes with highest similarity from the node pool are selected as positive set for it which denote as $S^i_{pos} = \arg\max_{v_j \in P} (\mathbf{Z}_i^\top \mathbf{Z}_j, K_{pos})$, and $S^i_{neg} = \{v_i^1, v_i^2, \ldots, v_i^{K_{neg}}\} \sim \mathcal{V}$, $S^i_{neg} \subseteq \mathcal{V}$. Concretely, the framework is optimized with the following objective:

$$\widehat{\mathcal{L}}_{\text{SP-GCL}} = -\frac{2}{N \cdot K_{pos}} \sum_{v_i \in \mathcal{V}} \sum_{v_{i+} \in S^i_{pos}} \left[\mathbf{Z}_i^\top \mathbf{Z}_{i+} \right] + \frac{1}{N \cdot K_{neg}} \sum_{v_j \in \mathcal{V}} \sum_{v_k \in S^i_{neg}} \left[(\mathbf{Z}_j^\top \mathbf{Z}_k)^2 \right]. \tag{8}$$

Notably, the empirical contrastive loss is an unbiased estimation of the Equation (4). Overall, the training algorithm SP-GCL is summarized in Algorithm 1.

Although our theoretical analysis indicates that SP-GCL can ensure performance for both homophilic and heterophilic graphs, it is yet unknown whether the proposed strategy is effective in real-world situations.

Algorithm 1 Single-Pass Graph Contrastive Learning (SP-GCL).

Input: Graph neural network f_θ, MLP projection head g_ω, input adjacency matrix $\mathbf{A}$, node features $\mathbf{X}$, batch size b, number of hops T, number of positive nodes K_{pos}.

for epoch $\leftarrow$ 1, 2, $\cdots$ **do**

    1. Obtain the node embedding, $\mathbf{H} = f_\theta(\mathbf{X}, \mathbf{A})$.

    2. Obtain the hidden representation, $\mathbf{Z} = g_\omega(\mathbf{H})$.

    3. Sample b nodes as seed node set S and construct the node pool P with the T-hop neighbors of each node in the set S.

    4. Select top-K_{pos} similar nodes for every $v_i \in S$ to form the positive node set S_{pos}^i.

    5. Compute the contrastive objective with Eq. (8) and update parameters by applying stochastic gradient.

end for

return Final model f_θ.

In the subsequent part, we empirically validate the effectiveness of the method and the applicability of our conclusions across a wide variety of graph datasets.

6 Experiments

We conduct experiments to evaluate the SP-GCL by answering the following questions:

- **RQ1**: How does the SP-GCL perform compared with other GCL methods on homophilic and heterophilic graphs?
- **RQ2**: What's the empirical memory consumption of SP-GCL compared with prior works?
- **RQ3**: Whether the learning procedure is stable? And whether node representation have expected behavior during training?
- **RQ4**: How do the specific hyper-parameters of SP-GCL, such as the selection of top-K and sampling hop-T, affect its performance?

To answer these questions, we apply supervised approaches, augmentation-based and augmentation-free GCL methods (a total of 13 baseline methods) in accordance with the linear evaluation scheme described in Velickovic et al. (2019). In addition, we utilize 14 benchmarking graph data to assess SP-GCL on diverse datasets with varying scales and features. We present the selected datasets, baselines, evaluation protocol and implementation details in the Section 6.1, 6.2, 6.3, and 6.4 respectively. Appendix A contains most details about infrastructures and hyperparameter configurations.

6.1 Dataset Information

We analyze the quality of representations learned by SP-GCL on transductive node classification benchmarks. Specifically, we evaluate the performance of using the pretraining representations on 8 benchmark homophilic graph datasets, namely, Cora, Citeseer, Pubmed (Kipf & Welling, 2016a) and Wiki-CS, Amazon-Computers, Amazon-Photo, Coauthor-CS, Coauthor-Physics (Shchur et al., 2018), as well as 6 heterophilic graph datasets, namely, Chameleon, Squirrel (Rozemberczki et al., 2021), Actor (Pei et al., 2020), Twitch-DE, Twitch-gamers (Rozemberczki & Sarkar, 2021), and Genius (Lim et al., 2021b). The datasets are collected from real-world networks from different domains; their detailed statistics are summarized in Table 1. For the 8 homophilic graph data, we use the processed version provided by PyTorch Geometric (Fey & Lenssen, 2019). Besides, for the 6 heterophilic graph data, 3 of them, e.g., Chameleon, Squirrel and Actor are provided by PyTorch Geometric library. The other three dataset, genius, twitch-DE and twitch-gamers can be obtained from the official github repository[1], in which the standard splits for all the 6 heterophilic graph datasets can also be obtained. Those graph datasets follow the MIT license, and the personal identifiers are not included. We do not foresee any form of privacy issues.

---

[1]https://github.com/CUAI/Non-Homophily-Large-Scale

Table 1: Statistics of datasets used in experiments.

Name	Nodes	Edges	Class.	Feat.	h_{node}	h_{edge}
Cora	2,708	5,429	7	1,433	.825	.810
CiteSeer	3,327	4,732	6	3,703	.717	.736
PubMed	19,717	44,338	3	500	.792	.802
Coauthor CS	18,333	327,576	15	6,805	.832	.808
Coauthor Phy.	34,493	991,848	5	8,451	.915	.931
Amazon Comp.	13,752	574,418	10	767	.785	.777
Amazon Photo	7,650	287,326	8	745	.836	.827
WikiCS	11,701	216,123	10	300	.658	.654
Chameleon	2,277	36,101	5	2,325	.103	.234
Squirrel	5,201	216,933	5	2,089	.088	.223
Actor	7,600	33,544	5	9,31	.154	.216
Twitch-DE	9,498	153,138	2	2,514	.529	.632
Twitch-gamers	168,114	**6,797,557**	2	7	.552	.545
Genius	**421,961**	984,979	2	12	.477	.618

6.2 Baselines

We consider representative baseline methods belonging to the following three categories (1) Traditional un-supervised graph embedding methods, including DeepWalk (Perozzi et al., 2014) and Node2Vec (Grover & Leskovec, 2016) , (2) Self-supervised learning algorithms with graph neural networks including Graph Autoencoders (GAE, VGAE) (Kipf & Welling, 2016b) , Deep Graph Infomax (DGI) (Velickovic et al., 2019) , Graphical Mutual Information Maximization (GMI) (Peng et al., 2020), and Multi-View Graph Representation Learning (MVGRL) (Hassani & Khasahmadi, 2020), graph contrastive representation learning (GRACE) (Zhu et al., 2020d) Graph Contrastive learning with Adaptive augmentation (GCA) (Zhu et al., 2021b), Bootstrapped Graph Latents (BGRL) (Thakoor et al., 2021), Augmentation-Free Graph Representation Learning (AFGRL) (Lee et al., 2021), (3) Supervised learning and Semi-supervised learning, e.g., Multilayer Perceptron (MLP) and Graph Convolutional Networks (GCN) (Kipf & Welling, 2016a), where they are trained in an end-to-end fashion.

6.3 Evaluation Protocol

We follow the evaluation protocol of previous state-of-the-art graph contrastive learning approaches. Specifically, for every experiment, we employ the linear evaluation scheme as introduced in Velickovic et al. (2019), where each model is firstly trained in an unsupervised manner; then, the pretrained representations are used to train and test via a simple linear classifier. For the datasets that came with standard train/valid/test splits, we evaluate the models on the public splits. For datasets without standard split, e.g., Amazon-Computers, Amazon-Photo, Coauthor-CS, Coauthor-Physics, we randomly split the datasets, where 10%/10%/80% of nodes are selected for the training, validation, and test set, respectively. For most datasets, we report the averaged test accuracy and standard deviation over 10 runs of classification. While, following the previous works (Lim et al., 2021b;a), we report the test ROC AUC on genius and Twitch-DE datasets.

6.4 Implementation Details

Model architecture and hyperparamters. We employ a two-layer GCN (Kipf & Welling, 2016a) as the encoder for all methods. The propagation for a single layer GCN is given by,

$$\text{GCN}_i(\mathbf{X}, \mathbf{A}) = \sigma \left(\bar{\mathbf{D}}^{-\frac{1}{2}} \bar{\mathbf{A}} \bar{\mathbf{D}}^{-\frac{1}{2}} \mathbf{X} \mathbf{W}_i \right),$$

where $\bar{\mathbf{A}} = \mathbf{A} + \mathbf{I}$ is the adjacency matrix with self-loops, $\bar{\mathbf{D}}$ is the degree matrix, σ is a non-linear activation function, such as ReLU, and $\mathbf{W}_i$ is the learnable weight matrix for the i'th layer. Besides, following the previous works (Lim et al., 2021a;b), we use batch normalization within the graph encoder for the heterophilic graphs. The hyperparameters configuration for all experiments are summarized in Appendix A.

Linear evaluation of embeddings. In the linear evaluation protocol, the final evaluation is over representations obtained from pretrained model. When fitting the linear classifier on top of the frozen learned embeddings, the gradient will not flow back to the encoder. We optimize the one layer linear classifier 1000 epochs using Adam with learning rate 0.0005.

6.5 Performance on Homophilic and Heterophilic graph

The homophilic graph benchmarks have been studied by several previous works (Velickovic et al., 2019; Peng et al., 2020; Hassani & Khasahmadi, 2020; Zhu et al., 2020d; Thakoor et al., 2021; Lee et al., 2021). We re-use their configuration and compare SP-GCL with those methods and leave the detailed description about the experiment setting in Appendix A. The result is summarized in Table 2, in which the best performance achieved by self-supervised methods is marked in boldface. Compared with augmentation-based and augmentation-free GCL methods, SP-GCL outperforms previous methods on 2 datasets and achieves competitive performance on the others, which shows the effectiveness of the single-pass contrastive loss on homophilic graphs. We further assess the model performance on heterophilic graph benchmarks that employed in Pei et al. (2020) and Lim et al. (2021a). As shown in Table 3, SP-GCL achieves the best performance on 6 of 6 heterophilic graphs by an evident margin. The above result indicates that, instead of relying on the augmentations which are sensitive to the graph type, **SP-GCL *is able to work well over a wide range of real-world graphs with different homophily degree*.**

Table 2: Graph Contrastive Learning on Homophilic Graphs. The highest performance of unsupervised models is highlighted in boldface. OOM indicates Out-Of-Memory on a 32GB GPU.

MODEL	CORA	CITESEER	PUBMED	WIKICS	AMZ-COMP.	AMZ-PHOTO	COAUTHOR-CS	COAUTHOR-PHY.
MLP	47.92 ± 0.41	49.31 ± 0.26	69.14 ± 0.34	71.98 ± 0.42	73.81 ± 0.21	78.53 ± 0.32	90.37 ± 0.19	93.58 ± 0.41
GCN	81.54 ± 0.68	70.73 ± 0.65	79.16 ± 0.25	93.02 ± 0.11	86.51 ± 0.54	92.42 ± 0.22	93.03 ± 0.31	95.65 ± 0.16
DEEPWALK	70.72 ± 0.63	51.39 ± 0.41	73.27 ± 0.86	74.42 ± 0.13	85.68 ± 0.07	89.40 ± 0.11	84.61 ± 0.22	91.77 ± 0.15
NODE2CEC	71.08 ± 0.91	47.34 ± 0.84	66.23 ± 0.95	71.76 ± 0.14	84.41 ± 0.14	89.68 ± 0.19	85.16 ± 0.04	91.23 ± 0.07
GAE	71.49 ± 0.41	65.83 ± 0.40	72.23 ± 0.71	73.97 ± 0.16	85.27 ± 0.19	91.62 ± 0.13	90.01 ± 0.71	94.92 ± 0.08
VGAE	77.31 ± 1.02	67.41 ± 0.24	75.85 ± 0.62	75.56 ± 0.28	86.40 ± 0.22	92.16 ± 0.12	92.13 ± 0.16	94.46 ± 0.13
DGI	82.34 ± 0.71	71.83 ± 0.54	76.78 ± 0.31	75.37 ± 0.13	84.01 ± 0.52	91.62 ± 0.42	92.16 ± 0.62	94.52 ± 0.47
GMI	82.39 ± 0.65	71.72 ± 0.15	79.34 ± 1.04	74.87 ± 0.13	82.18 ± 0.27	90.68 ± 0.18	OOM	OOM
MVGRL	$\mathbf{83.45 \pm 0.68}$	$\mathbf{73.28 \pm 0.48}$	80.09 ± 0.62	77.51 ± 0.06	87.53 ± 0.12	91.74 ± 0.08	92.11 ± 0.14	95.33 ± 0.05
GRACE	81.92 ± 0.89	71.21 ± 0.64	$\mathbf{80.54 \pm 0.36}$	78.19 ± 0.10	86.35 ± 0.44	92.15 ± 0.25	92.91 ± 0.20	95.26 ± 0.22
GCA	82.07 ± 0.10	71.33 ± 0.37	80.21 ± 0.39	78.40 ± 0.13	87.85 ± 0.31	92.49 ± 0.11	92.87 ± 0.14	95.68 ± 0.05
BGRL	81.44 ± 0.72	71.82 ± 0.48	80.18 ± 0.63	76.96 ± 0.61	89.62 ± 0.37	93.07 ± 0.34	92.67 ± 0.21	95.47 ± 0.28
AFGRL	81.60 ± 0.54	71.02 ± 0.37	80.02 ± 0.48	77.98 ± 0.49	89.66 ± 0.40	$\mathbf{93.14 \pm 0.36}$	$\mathbf{93.27 \pm 0.17}$	$\mathbf{95.69 \pm 0.10}$
SP-GCL	83.16 ± 0.13	71.96 ± 0.42	79.16 ± 0.73	$\mathbf{79.01 \pm 0.51}$	$\mathbf{89.68 \pm 0.19}$	92.49 ± 0.31	91.92 ± 0.10	95.12 ± 0.15

Table 3: Graph Contrastive Learning on Heterophilic Graphs. The highest performance of unsupervised models is highlighted in boldface. OOM indicates Out-Of-Memory on a 32GB GPU.

MODEL	CHAMELEON	SQUIRREL	ACTOR	TWITCH-DE	TWITCH-GAMERS	GENIUS
MLP	47.59 ± 0.73	31.67 ± 0.61	35.93 ± 0.61	69.44 ± 0.67	60.71 ± 0.18	86.62 ± 0.11
GCN	66.45 ± 0.48	53.03 ± 0.57	28.79 ± 0.23	73.43 ± 0.71	62.74 ± 0.03	87.72 ± 0.18
DEEPWALK	43.99 ± 0.67	30.90 ± 1.09	25.50 ± 0.28	70.39 ± 0.77	61.71 ± 0.41	68.98 ± 0.15
NODE2CEC	31.49 ± 1.17	27.64 ± 1.36	27.04 ± 0.56	70.70 ± 1.15	61.12 ± 0.29	67.96 ± 0.17
GAE	39.13 ± 1.34	34.65 ± 0.81	25.36 ± 0.23	67.43 ± 1.16	56.26 ± 0.50	83.36 ± 0.21
VGAE	42.65 ± 1.27	35.11 ± 0.92	28.43 ± 0.57	68.62 ± 1.82	60.70 ± 0.61	85.17 ± 0.52
DGI	60.27 ± 0.70	42.22 ± 0.63	28.30 ± 0.76	72.77 ± 1.30	61.47 ± 0.56	86.96 ± 0.44
GMI	52.81 ± 0.63	35.25 ± 1.21	27.28 ± 0.87	71.21 ± 1.27	OOM	OOM
MVGRL	53.81 ± 1.09	38.75 ± 1.32	32.09 ± 1.07	71.86 ± 1.21	OOM	OOM
GRACE	61.24 ± 0.53	41.09 ± 0.85	28.27 ± 0.43	72.49 ± 0.72	OOM	OOM
GCA	60.94 ± 0.81	41.53 ± 1.09	28.89 ± 0.50	73.21 ± 0.83	OOM	OOM
BGRL	64.86 ± 0.63	46.24 ± 0.70	28.80 ± 0.54	73.31 ± 1.11	60.93 ± 0.32	86.78 ± 0.71
AFGRL	59.03 ± 0.78	42.36 ± 0.40	27.43 ± 1.31	69.11 ± 0.72	OOM	OOM
SP-GCL	$\mathbf{65.28 \pm 0.53}$	$\mathbf{52.10 \pm 0.67}$	$\mathbf{28.94 \pm 0.69}$	$\mathbf{73.51 \pm 0.97}$	$\mathbf{62.04 \pm 0.17}$	$\mathbf{90.06 \pm 0.18}$

6.6 Computational Complexity Analysis

In order to illustrate the advantages of SP-GCL, we provide a brief comparison of the time and space complexities between SP-GCL, the previous strong contrastive method, GCA (Zhu et al., 2021b), and the memory-efficient contrastive method, BGRL (Thakoor et al., 2021). Consider a graph with N nodes

Table 4: Computational requirements on a set of standard benchmark graphs. OOM indicates running out of memory on a 32GB GPU.

DATASET	CS.	PHY.	GENIUS	GAMERS.
# NODES	18,333	34,493	421,961	168,114
# EDGES	327,576	991,848	984,979	6,797,557
GRACE	13.21 GB	30.11 GB	OOM	OOM
BGRL	3.10 GB	5.42 GB	8.18 GB	26.22 GB
SP-GCL	2.07 GB	3.21 GB	6.24 GB	22.15 GB

Table 5: True positive ratio of selected edges at the end of training. The minimal, maximal, average, standard deviation of 20 runs are presented.

Dataset	h_{edge} of $\widehat{\mathcal{G}}$
Cora	$0.812_\uparrow \pm 0.0022$ (0.810)
CiteSeer	$0.691_\downarrow \pm 0.0018$ (0.736)
PubMed	$0.819_\uparrow \pm 0.0011$ (0.802)
Coauthor CS	$0.883_\uparrow \pm 0.0018$ (0.808)
Coauthor Phy.	$0.952_\uparrow \pm 0.0021$ (0.931)
Amazon Comp.	$0.866_\uparrow \pm 0.0019$ (0.777)
Amazon Photo	$0.908_\uparrow \pm 0.0012$ (0.827)
WikiCS	$0.751_\uparrow \pm 0.0027$ (0.654)
Chameleon	$0.631_\uparrow \pm 0.0047$ (0.234)
Squirrel	$0.526_\uparrow \pm 0.0042$ (0.223)
Actor	$0.378_\uparrow \pm 0.0026$ (0.216)
Twitch-DE	$0.669_\uparrow \pm 0.0033$ (0.632)
Twitch-gamers	$0.617_\uparrow \pm 0.0021$ (0.545)
Genius	$0.785_\uparrow \pm 0.0028$ (0.618)

Table 6: Edge homophily of the transformed graph at the initial stage. Homophily value of original graphs is shown in parentheses.

Dataset	Min	Max	Avg	Std
Cora	0.817	0.836	0.826	0.0061
CiteSeer	0.708	0.719	0.713	0.0033
PubMed	0.820	0.832	0.825	0.0037
Coauthor CS	0.892	0.905	0.901	0.0025
Coauthor Phy.	0.952	0.963	0.959	0.0028
Amazon Comp.	0.874	0.896	0.878	0.0076
Amazon Photo	0.903	0.926	0.916	0.0054
WikiCS	0.757	0.771	0.761	0.0040
Chameleon	0.703	0.785	0.711	0.0183
Squirrel	0.529	0.541	0.530	0.0024
Actor	0.388	0.399	0.396	0.0016
Twitch-DE	0.693	0.726	0.703	0.0073
Twitch-gamers	0.620	0.633	0.627	0.0022
Genius	0.786	0.797	0.790	0.0029

and E edges, and a graph neural network (GNN), f, that compute node embeddings in time and space $O(N + E)$. BGRL performs four GNN computations per update step, in which twice for the target and online encoders, and twice for each augmentation, and a node-level projection; GCA performs two GNN computations (once for each augmentation), plus a node-level projection. Both methods backpropagate the learning signal twice (once for each augmentation), and we assume the backward pass to be approximately as costly as a forward pass. Both of them will compute the augmented graphs by feature masking and edge masking on the fly, the cost for augmentation computation is nearly the same. Thus the total time and space complexity per update step for BGRL is $6C_{encoder}(E + N) + 4C_{proj}N + C_{prod}N + C_{aug}$ and $4C_{encoder}(E + N) + 4C_{proj}N + C_{prod}N^2 + C_{aug}$ for GCA. The C_{prod} depends on the dimension of node embedding and we assume the node embeddings of all the methods with the same size. For our proposed method, only one GNN encoder is employed and we compute the inner product of b nodes to construct positive samples and K_{pos} and K_{neg} inner product for the loss computation. Then for SP-GCL, we have: $2C_{encoder}(E + N) + 2C_{proj}N + C_{prod}(K_{pos} + K_{neg})^2$, which is significantly lower than BGRL and GCA. We empirically measure the peak of GPU memory usage of SP-GCL, GCA and BGRL. As a fair comparison, we set the embedding size as 128 for all those methods on the four datasets and keep the other hyper-parameters of the three methods the same as the main experiments. As shown by Table 4, *the computational overhead of* **SP-GCL** *is much less than the previous methods*.

6.7 Empirical Verification for the Theoretical Analysis

Homophily of transformed graph (*Initial Stage*). The homophily of transformed graph largely depends on the hidden representations. We theoretically shows the concentration property of the representations (Theorem 1) with mild assumptions. It implies that the transformed graph formed by selected positive pairs will have large edge homophily degree. But it is still unclear whether the derived conclusion is still hold over real-world datasets. Thus, we empirically measure the edge homophily of the transformed graph at the beginning of the training stage with 20 runs. The mean and standard deviation are reported in Table 6. The edge homophily of all transformed graphs are larger than the original one with a small standard deviation,

except the CiteSeer in which a relatively high edge homophily (0.691) can still be achieved. The result indicates that the Theorem 1 is feasible over a wide-range real-world graph data.

Distance to class center and Node Coverage (*Learning Process*). We measure change of the average cosine distance ($1 - CosineSimilarity$) between the node embeddings and the class-center embeddings during training. Specifically, the class-center embedding is the average of the node embeddings of the same class. As shown in Figure 3, we found that the node embeddings will concentrate on their corresponding class centers during training, which implies that the learned embedding space becomes more compact and the learning process is stable. Intuitively, coupling with the "good" initialization as discussed above, the SP-GCL iteratively leverage the inductive bias to refine the embedding space. Furthermore, to study whether the representation of all nodes are benefited during the learning process, we measure the Node Cover Ratio and Overlapped Selection Ratio on four graph datasets. We denote the set of edges forming by the K_{pos} positive selection at epoch t as e^t and define the Overlapped Selection Ratio as $\frac{e^{t+1} \cap e^t}{|e^{t+1}|}$. Besides, we denote the set of positive nodes at at epoch t as v^t. Then the Node Cover Ratio at epoch t is defined as: $\frac{|v^0 \cap v^1 \cdots v^t|}{N}$. Following the hyperparameters described previously, we measure the node cover ratio and overlapped selection ratio during training. As shown in Figure 4, the overlapped selection ratio is low during the training and the node cover ratio coverage to 1 at the beginning of training. The result implies that all nodes can be benefited from the optimization procedure.

Figure 3: Average cosine distance between node embeddings and their corresponding class centers.

Figure 4: The Node Cover Ratio and Overlapped Selection Ratio.

Selected positive pairs (*End of Training*). To further study the effect of the proposed method, we provide the true positive ratio (TPR) of the selected pairs at the end of training with 20 runs. As shown in Table 5, the relatively large TPR and low variance suggests that the quality of the selected positive pairs is good and the learning process is stable.

6.8 Ablation Study for Hyper-parameter Selection

Effect of Top-K Positive Sampling. We study the effect of top-K positive sampling on the node classification performance by measuring the classification accuracy and the corresponding standard deviation with a wide range of K. The results over WikiCS, Chameleon, Squirrel, Cora, and Photo are summarized in Figure 5. We observe that the performance achieved by SP-GCL is insensitive to the selection of K from 2 to 18.

Effect of T-hop Neighbors. Factor T is the other factor involved in node sampling. We provide a study about the the effect of T-hop neighbors on the node classification performance by measuring the classification accuracy or ROCAUC score and the corresponding standard deviation with different T. Specifically, with the

same evaluation protocol described in Section 6.3, we measure the classification accuracy on Squirrel, Cora, Actor, and Chameleon dataset and ROCAUC score on twitch-DE. As shown in Figure 5, the performance achieved by SP-GCL is insensitive to the selection of T.

Figure 5: The effect of top-K positive sampling and T-hop neighborhood on the performance.

7 Connection with Existing Observations

In Theorem 1, we theoretically analyze the concentration property of aggregated features of graphs following the Graph Assumption (Section 4.1). The concentration property has also been empirically observed in some other recent works (Wang et al., 2022b; Trivedi et al., 2022). Specifically, in Figure 1 of Wang et al. (2022b), a t-SNE visualization of node representations of the Amazon-Photo dataset shows that the representations obtained by a randomly initialized untrained SGC (Wu et al., 2019) model will concentrate to a certain area if they are from the same class. This observation also provides an explanation for the salient performance achieved by SP-GCL on the Amazon-Photo, as shown in Table 2.

8 Conclusion

In this work, to build a practical GCL approach that can perform well on both homophilic and heterophilic graphs, we begin by analyzing the concentration property of aggregated features for homophilic and heterophilic graphs. We then introduce the single-pass graph contrastive loss by utilizing the concentration property. We establish a link between the contrastive objective and the matrix factorization. Then, by utilizing the analysis of matrix factorization, we establish a theoretical guarantee for the downstream classification task using node representations learnt by optimizing the contrastive loss. We implement Single-Pass Graph Contrastive Learning (SP-GCL). Empirically, we demonstrate that SP-GCL outperforms or is competitive with SOTA approaches on 8 homophilic and 6 heterophilic graph benchmarks, while incurring a much lower computational overhead. The empirical findings demonstrate the viability and efficacy of our method in real-world situations.

9 Limitation and Future Work

Our work is only the first step in understanding the possibility of single-pass graph contrastive learning and the corresponding performance guarantee on both the homophilic graph and heterophilic graph. There is still a lot of future work to be done. Below we indicate three questions that need to be addressed.

- Our theoretical framework is built upon the graph assumption (Section 4.1) in which we assume the neighbor pattern. The graph assumption includes the homophilic graph and the "benign" heterophilic graph. However, there could exist graphs in which the neighbor pattern is messy or arbitrarily distributed. It is still an open question to understand the graph contrastive learning on those graphs.
- Recently, several Graph neural networks (Zhu et al., 2020b; Chien et al., 2020; Luan et al., 2021; Li et al., 2022) have been proposed to work on heterophilic graphs. Whether further improvement can be achieved through combining with those GNNs is still an open question.
- To verify the effectiveness of our theoretical findings, we keep the implementation to be simple. Whether a better empirical result can be achieved by involving more complex techniques still need to be explored.

References

Sami Abu-El-Haija, Bryan Perozzi, Amol Kapoor, Nazanin Alipourfard, Kristina Lerman, Hrayr Harutyunyan, Greg Ver Steeg, and Aram Galstyan. Mixhop: Higher-order graph convolutional architectures via sparsified neighborhood mixing. In *international conference on machine learning*, pp. 21–29. PMLR, 2019.

Sanjeev Arora, Hrishikesh Khandeparkar, Mikhail Khodak, Orestis Plevrakis, and Nikunj Saunshi. A theoretical analysis of contrastive unsupervised representation learning. *arXiv preprint arXiv:1902.09229*, 2019.

Deyu Bo, Xiao Wang, Chuan Shi, and Huawei Shen. Beyond low-frequency information in graph convolutional networks. *arXiv preprint arXiv:2101.00797*, 2021.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Eli Chien, Jianhao Peng, Pan Li, and Olgica Milenkovic. Adaptive universal generalized pagerank graph neural network. *arXiv preprint arXiv:2006.07988*, 2020.

Fan RK Chung and Fan Chung Graham. *Spectral graph theory*. Number 92. American Mathematical Soc., 1997.

Carl Eckart and Gale Young. The approximation of one matrix by another of lower rank. *Psychometrika*, 1 (3):211–218, 1936.

Matthias Fey and Jan Eric Lenssen. Fast graph representation learning with pytorch geometric. *arXiv preprint arXiv:1903.02428*, 2019.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. *Advances in Neural Information Processing Systems*, 33:21271–21284, 2020.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 855–864, 2016.

Jeff Z HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable guarantees for self-supervised deep learning with spectral contrastive loss. *arXiv preprint arXiv:2106.04156*, 2021.

Kaveh Hassani and Amir Hosein Khasahmadi. Contrastive multi-view representation learning on graphs. In *International Conference on Machine Learning*, pp. 4116–4126. PMLR, 2020.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 9729–9738, 2020.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016a.

Thomas N Kipf and Max Welling. Variational graph auto-encoders. *arXiv preprint arXiv:1611.07308*, 2016b.

Jason D Lee, Qi Lei, Nikunj Saunshi, and Jiacheng Zhuo. Predicting what you already know helps: Provable self-supervised learning. *arXiv preprint arXiv:2008.01064*, 2020.

Namkyeong Lee, Junseok Lee, and Chanyoung Park. Augmentation-free self-supervised learning on graphs. *arXiv preprint arXiv:2112.02472*, 2021.

Shouheng Li, Dongwoo Kim, and Qing Wang. Beyond low-pass filters: Adaptive feature propagation on graphs. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 450–465. Springer, 2021.

Xiang Li, Renyu Zhu, Yao Cheng, Caihua Shan, Siqiang Luo, Dongsheng Li, and Weining Qian. Finding global homophily in graph neural networks when meeting heterophily. *arXiv preprint arXiv:2205.07308*, 2022.

Derek Lim, Felix Hohne, Xiuyu Li, Sijia Linda Huang, Vaishnavi Gupta, Omkar Bhalerao, and Ser Nam Lim. Large scale learning on non-homophilous graphs: New benchmarks and strong simple methods. *Advances in Neural Information Processing Systems*, 34, 2021a.

Derek Lim, Xiuyu Li, Felix Hohne, and Ser-Nam Lim. New benchmarks for learning on non-homophilous graphs. *arXiv preprint arXiv:2104.01404*, 2021b.

Juncheng Liu, Kenji Kawaguchi, Bryan Hooi, Yiwei Wang, and Xiaokui Xiao. Eignn: Efficient infinite-depth graph neural networks. *Advances in Neural Information Processing Systems*, 34:18762–18773, 2021.

Juncheng Liu, Bryan Hooi, Kenji Kawaguchi, and Xiaokui Xiao. MGNNI: Multiscale graph neural networks with implicit layers. In *Advances in Neural Information Processing Systems*, 2022a.

Nian Liu, Xiao Wang, Deyu Bo, Chuan Shi, and Jian Pei. Revisiting graph contrastive learning from the perspective of graph spectrum. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022b. URL https://openreview.net/forum?id=L0U7TUWRt_X.

Sitao Luan, Chenqing Hua, Qincheng Lu, Jiaqi Zhu, Mingde Zhao, Shuyuan Zhang, Xiao-Wen Chang, and Doina Precup. Is heterophily a real nightmare for graph neural networks to do node classification? *arXiv preprint arXiv:2109.05641*, 2021.

Yao Ma, Xiaorui Liu, Neil Shah, and Jiliang Tang. Is homophily a necessity for graph neural networks? *arXiv preprint arXiv:2106.06134*, 2021.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. 2017.

Hongbin Pei, Bingzhe Wei, Kevin Chen-Chuan Chang, Yu Lei, and Bo Yang. Geom-gcn: Geometric graph convolutional networks. *arXiv preprint arXiv:2002.05287*, 2020.

Zhen Peng, Wenbing Huang, Minnan Luo, Qinghua Zheng, Yu Rong, Tingyang Xu, and Junzhou Huang. Graph representation learning via graphical mutual information maximization. In *Proceedings of The Web Conference 2020*, pp. 259–270, 2020.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *Proceedings of the 20th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 701–710, 2014.

Jiezhong Qiu, Qibin Chen, Yuxiao Dong, Jing Zhang, Hongxia Yang, Ming Ding, Kuansan Wang, and Jie Tang. Gcc: Graph contrastive coding for graph neural network pre-training. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 1150–1160, 2020.

Benedek Rozemberczki and Rik Sarkar. Twitch gamers: a dataset for evaluating proximity preserving and structural role-based node embeddings. *arXiv preprint arXiv:2101.03091*, 2021.

Benedek Rozemberczki, Carl Allen, and Rik Sarkar. Multi-scale attributed node embedding. *Journal of Complex Networks*, 9(2):cnab014, 2021.

Oleksandr Shchur, Maximilian Mumme, Aleksandar Bojchevski, and Stephan Günnemann. Pitfalls of graph neural network evaluation. *arXiv preprint arXiv:1811.05868*, 2018.

Shantanu Thakoor, Corentin Tallec, Mohammad Gheshlaghi Azar, Rémi Munos, Petar Veličković, and Michal Valko. Bootstrapped representation learning on graphs. *arXiv preprint arXiv:2102.06514*, 2021.

Christopher Tosh, Akshay Krishnamurthy, and Daniel Hsu. Contrastive learning, multi-view redundancy, and linear models. In *Algorithmic Learning Theory*, pp. 1179–1206. PMLR, 2021.

Puja Trivedi, Ekdeep Singh Lubana, Yujun Yan, Yaoqing Yang, and Danai Koutra. Augmentations in graph contrastive learning: Current methodological flaws & towards better practices. In *Proceedings of the ACM Web Conference 2022*, pp. 1538–1549, 2022.

Petar Velickovic, William Fedus, William L Hamilton, Pietro Liò, Yoshua Bengio, and R Devon Hjelm. Deep graph infomax. *ICLR (Poster)*, 2(3):4, 2019.

Haonan Wang, Jieyu Zhang, Qi Zhu, and Wei Huang. Augmentation-free graph contrastive learning. *arXiv preprint arXiv:2204.04874*, 2022a.

Tongzhou Wang and Phillip Isola. Understanding contrastive representation learning through alignment and uniformity on the hypersphere. In *International Conference on Machine Learning*, pp. 9929–9939. PMLR, 2020.

Yuansheng Wang, Wangbin Sun, Kun Xu, Zulun Zhu, Liang Chen, and Zibin Zheng. Fastgcl: Fast self-supervised learning on graphs via contrastive neighborhood aggregation. *arXiv preprint arXiv:2205.00905*, 2022b.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *International conference on machine learning*, pp. 6861–6871. PMLR, 2019.

Jun Xia, Lirong Wu, Jintao Chen, Bozhen Hu, and Stan Z Li. Simgrace: A simple framework for graph contrastive learning without data augmentation. In *Proceedings of the ACM Web Conference 2022*, pp. 1070–1079, 2022.

Yaochen Xie, Zhao Xu, Jingtun Zhang, Zhengyang Wang, and Shuiwang Ji. Self-supervised learning of graph neural networks: A unified review. *arXiv preprint arXiv:2102.10757*, 2021.

Yuning You, Tianlong Chen, Yongduo Sui, Ting Chen, Zhangyang Wang, and Yang Shen. Graph contrastive learning with augmentations. *Advances in Neural Information Processing Systems*, 33:5812–5823, 2020.

Jiong Zhu, Ryan A Rossi, Anup Rao, Tung Mai, Nedim Lipka, Nesreen K Ahmed, and Danai Koutra. Graph neural networks with heterophily. *arXiv preprint arXiv:2009.13566*, pp. 11168–11176, 2020a.

Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. *arXiv preprint arXiv:2006.11468*, 2020b.

Qi Zhu, Yidan Xu, Haonan Wang, Chao Zhang, Jiawei Han, and Carl Yang. Transfer learning of graph neural networks with ego-graph information maximization. *arXiv preprint arXiv:2009.05204*, 2020c.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Deep graph contrastive representation learning. *arXiv preprint arXiv:2006.04131*, 2020d.

Yanqiao Zhu, Yichen Xu, Qiang Liu, and Shu Wu. An empirical study of graph contrastive learning. 2021a.

Yanqiao Zhu, Yichen Xu, Feng Yu, Qiang Liu, Shu Wu, and Liang Wang. Graph contrastive learning with adaptive augmentation. In *Proceedings of the Web Conference 2021*, pp. 2069–2080, 2021b.

A Appendix: Experiment Setting

Hardware and software infrastructures. Our model are implemented with PyTorch Geometric 2.0.3 (Fey & Lenssen, 2019), PyTorch 1.9.0 (Paszke et al., 2017). We conduct experiments on a computer server with four NVIDIA Tesla V100 SXM2 GPUs (with 32GB memory each) and twelve Intel Xeon Gold 6240R 2.40GHz CPUs.

Table 7: Hyperparameter settings for all experiments.

	$lr.$	K_{pos}	K_{neg}	b	T	K
Cora	.0010	5	100	512	2	1024
CiteSeer	.0020	10	200	256	2	1024
PubMed	.0010	5	100	256	2	1024
WikiCS	.0010	5	100	512	2	1024
Amz-Comp.	.0010	5	100	256	2	1024
Amz-Photo	.0010	5	100	512	2	1024
Coauthor-CS	.0010	5	100	512	2	1024
Coauthor-Phy.	.0010	5	100	256	2	1024
Chameleon	.0010	5	100	512	3	1024
Squirrel	.0010	5	100	512	3	1024
Actor	.0010	10	100	512	4	1024
Twitch-DE	.0010	5	100	512	4	1024
Twitch-gamers	.0010	5	100	256	4	128
Genius	.0010	5	100	256	3	512

B Appendix: Detailed proofs

B.1 Proof of Theorem 1

Assumptions on graph data. Consider the GNN model:

$$Z = \sigma(\mathbf{D}^{-1}\mathbf{A}\mathbf{X}\ \mathbf{W}) \in \mathbb{R}^{N \times K}$$

where σ represents the nonlinear activation function, the $\mathbf{X} \in \mathbb{R}^{N \times F}$ is the input layer, and $\mathbf{D} \in \mathbb{R}^{N \times N}$ is the degree matrix, $\mathbf{A} \in \mathbb{R}^{N \times N}$ is the adjacency matrix, and $\mathbf{W} \in \mathbb{R}^{F \times K}$ is the weight. Assume that $\|\mathbf{x}_i\|_2 \leq R$ for some $R \geq 0$, where $\mathbf{x}_i \in \mathbb{R}^F$ represents the node features of i-th input node (i.e., the transpose of the i-th row of $\mathbf{X}$). Define $\mathbf{w}_k \in \mathbb{R}^F$ to be the k-th column of $\mathbf{W}$. Given a label y, the node feature $\mathbf{x}$ is sampled from some distribution $P_{x|y}$. For node v_i, its neighbors labels are independently sampled from neighbor distribution P_{y_i}.

We assume that the nonlinear activation function σ is homogeneous of degree τ for some $\tau \geq 1$ and $\sigma(q) \leq cq$ for some $c \geq 0$. For example, ReLU activation satisfies these assumptions with $\tau = c = 1$. Also, it recoverse the result of the linear model too since if σ is identity (i.e., linear model), then $\tau = c = 1$.

Theorem 1 (Concentration Property of Aggregated Features) For any $\mathbf{W} \in \mathbb{R}^{F \times K}$, the following statements holds:

- For any pair (i, i') such that $y_i = y_{i'}$,

$$\mathbb{E}[\mathbf{Z}_i] - \mathbb{E}[\mathbf{Z}_{i'}] = 0. \tag{9}$$

- With probability at least $1 - \delta$,

$$\|\mathbb{E}[\mathbf{Z}_i] - \mathbf{Z}_i\|_\infty \leq cR \left(\max_{k \in [K]} \|\mathbf{w}_k\|_2\right) \sqrt{\frac{2\ln(2K/\delta)}{D_{ii}^{2\tau-1}}}. \tag{10}$$

- For any node pair (i, j), with probability at least $1 - \delta'$,

$$|\mathbb{E}[\mathbf{Z}_i^\top \mathbf{Z}_j] - \mathbf{Z}_i^\top \mathbf{Z}_j| \le c^2 R^2 \sum_{k=1}^K \|\mathbf{w}_k\|_2^2 \sqrt{\frac{2 \ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1}}}. \tag{11}$$

Proof. For any matrix $\mathbf{M}$, we use $\mathbf{M}_{i\cdot}$ and $\mathbf{M}_{\cdot j}$ to denote the i-th row vector and the j-th column vector of $\mathbf{M}$. We first calculate the expectation of aggregated embedding:

$$\mathbb{E}_X[\mathbf{Z}_i] = \mathbb{E}_X \left[\sigma \left(\sum_{j \in \mathcal{N}(i)} \frac{1}{D_{ii}} \mathbf{X}_{j\cdot} \mathbf{W} \right) \right] = \mathbb{E}_{(\mathbf{x}_j)_{j \in \mathcal{N}(i)}} \left[\sigma \left(\sum_{j \in \mathcal{N}(i)} \frac{1}{D_{ii}} \mathbf{x}_j^\top \mathbf{W} \right) \right]$$

$$= \mathbb{E}_{\bar{y}_k \sim P_{y_i}, \bar{\mathbf{x}}_k \sim P_{x|\bar{y}_k}, k=1,\dots,D_{ii}} \left[\sigma \left(\sum_{j \in \mathcal{N}(i)} \frac{1}{D_{ii}} \bar{\mathbf{x}}_k^\top \mathbf{W} \right) \right]$$

Therefore, for any pair (i, i') such that $y_i = y_{i'}$, we have

$$\mathbb{E}_X[\mathbf{Z}_i] - \mathbb{E}_X[\mathbf{Z}_{i'}] = 0.$$

Moreover,

$$\|\mathbb{E}_X[\mathbf{Z}_i] - \mathbf{Z}_i\|_\infty = \left\| \mathbb{E} \left[\sigma \left(\sum_{j \in \mathcal{N}(i)} \frac{1}{D_{ii}} \mathbf{X}_{j\cdot}^\top \mathbf{W} \right) \right] - \sigma \left(\sum_{j \in \mathcal{N}(i)} \frac{1}{D_{ii}} \mathbf{X}_{j\cdot}^\top \mathbf{W} \right) \right\|_\infty \tag{12}$$

$$= \left\| \frac{1}{D_{ii}^\tau} \left(\mathbb{E} \left[\sigma \left(\sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot}^\top \mathbf{W} \right) \right] - \sigma \left(\sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot}^\top \mathbf{W} \right) \right) \right\|_\infty$$

$$= \max_{k \in [K]} \left\| \frac{1}{D_{ii}^\tau} \left(\mathbb{E} \left[\sigma \left(\sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot}^\top \mathbf{W}_{\cdot k} \right) \right] - \sigma \left(\sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot}^\top \mathbf{W}_{\cdot k} \right) \right) \right\|_\infty$$

where the first line follows the definition and the last line holds because the nonlinear activation function σ is homogeneous of degree τ. Furthermore, since $\sigma(q) \le cq$,

$$\left| \sigma \left(\sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot} \mathbf{W}_{\cdot k} \right) \right| \le c \left| \sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot} \mathbf{W}_{\cdot k} \right| \le c \|\mathbf{W}_{\cdot k}\|_2 \left\| \sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot} \right\|_2$$

$$= c \|\mathbf{W}_{\cdot k}\|_2 \sqrt{\sum_{j \in \mathcal{N}(i)} \sum_{t=1}^F X_{jt}^2} \tag{13}$$

$$\le c \|\mathbf{W}_{\cdot k}\|_2 \sqrt{\sum_{j \in \mathcal{N}(i)} R^2}$$

$$= cR \|\mathbf{W}_{\cdot k}\|_2 \sqrt{D_{ii}}$$

Thus, the random variable $v_k = \frac{1}{D_{ii}^\tau} \sigma \left(\sum_{j \in \mathcal{N}(i)} \mathbf{X}_{j\cdot} \mathbf{W}_{\cdot k} \right)$ is bounded as $-\frac{1}{D_{ii}^\tau} r \le v_k \le \frac{1}{D_{ii}^\tau} r$ where $r = cR \|\mathbf{W}_{\cdot k}\|_2 \sqrt{D_{ii}}$. Thus, by applying Hoeffding's inequality to the RHS of equation (12),

$$P(|v_k - \mathbb{E}[v_k]| \ge t) \le 2 \exp \left(-\frac{t^2 D_{ii}^{2\tau}}{2r^2} \right)$$

Setting $\delta = 2 \exp \left(-\frac{t^2 D_{ii}^{2\tau}}{2r^2} \right)$ and solving for t, this means that with probability at least $1 - \delta$,

$$|v_k - \mathbb{E}[v_k]| \le \sqrt{\frac{2r^2 \ln(2/\delta)}{D_{ii}^{2\tau}}} = cR \|\mathbf{W}_{\cdot k}\|_2 \sqrt{\frac{2D_{ii} \ln(2/\delta)}{D_{ii}^{2\tau}}} = cR \|\mathbf{W}_{\cdot k}\|_2 \sqrt{\frac{2 \ln(2/\delta)}{D_{ii}^{2\tau-1}}}.$$

By taking union bound over $k \in [K]$, with probability at least $1 - \delta$,

$$\|\mathbb{E}_X[\mathbf{Z}_i] - \mathbf{Z}_i\|_\infty = \max_{k \in [K]} |v_k - \mathbb{E}[v_k]| \le cR \left(\max_{k \in [K]} \|\mathbf{W}_{\cdot k}\|_2 \right) \sqrt{\frac{2 \ln(2K/\delta)}{D_{ii}^{2\tau-1}}}.$$

Furthermore,

$$|\mathbf{Z}_i^\top \mathbf{Z}_j| = \left| \sigma \left(\sum_{i' \in \mathcal{N}(i)} \frac{1}{D_{ii}} \mathbf{X}_{i' \cdot} \mathbf{W} \right)^\top \sigma \left(\sum_{j' \in \mathcal{N}(j)} \frac{1}{D_{jj}} \mathbf{X}_{j' \cdot} \mathbf{W} \right) \right| \tag{14}$$

$$= \left| \sum_k \sigma \left(\sum_{i' \in \mathcal{N}(i)} \frac{1}{D_{ii}} \mathbf{X}_{i' \cdot} \mathbf{W}_{\cdot k} \right) \cdot \sigma \left(\sum_{j' \in \mathcal{N}(j)} \frac{1}{D_{jj}} \mathbf{X}_{j' \cdot} \mathbf{W}_{\cdot k} \right) \right| \tag{15}$$

$$= \left(\frac{1}{D_{ii}^\tau} \frac{1}{D_{jj}^\tau} \right) \left| \sum_k \sigma \left(\sum_{i' \in \mathcal{N}(i)} \mathbf{X}_{i' \cdot} \mathbf{W}_{\cdot k} \right) \cdot \sigma \left(\sum_{j' \in \mathcal{N}(j)} \mathbf{X}_{j' \cdot} \mathbf{W}_{\cdot k} \right) \right| \tag{16}$$

$$\le \left(\frac{1}{D_{ii}^\tau} \frac{1}{D_{jj}^\tau} \right) \sum_k \left| \sigma \left(\sum_{i' \in \mathcal{N}(i)} \mathbf{X}_{i' \cdot} \mathbf{W}_{\cdot k} \right) \right| \cdot \left| \sigma \left(\sum_{j' \in \mathcal{N}(j)} \mathbf{X}_{j' \cdot} \mathbf{W}_{\cdot k} \right) \right| \tag{17}$$

Coupling with the Equation (13),

$$|\mathbf{Z}_i^\top \mathbf{Z}_j| \le \left(\frac{1}{D_{ii}^\tau} \frac{1}{D_{jj}^\tau} \right) \sum_k c^2 R^2 \|\mathbf{W}_{\cdot k}\|_2^2 \sqrt{D_{ii} D_{jj}}.$$

Thus, the random variable $s_{ij} = \left(\frac{1}{D_{ii}^\tau} \frac{1}{D_{jj}^\tau} \right) \left[\sum_k \sigma(\sum_{i' \in \mathcal{N}(i)} \mathbf{X}_{i' \cdot} \mathbf{W}_{\cdot k}) \cdot \sigma(\sum_{j' \in \mathcal{N}(j)} \mathbf{X}_{j' \cdot} \mathbf{W}_{\cdot k}) \right]$ is bounded as $-\left(\frac{1}{D_{ii}^\tau} \frac{1}{D_{jj}^\tau} \right) r \le s_{ij} \le \left(\frac{1}{D_{ii}^\tau} \frac{1}{D_{jj}^\tau} \right) r$ where $r = \sum_k \sigma(\sum_{i' \in \mathcal{N}(i)} \mathbf{X}_{i' \cdot} \mathbf{W}_{\cdot k}) \cdot \sigma(\sum_{j' \in \mathcal{N}(j)} \mathbf{X}_{j' \cdot} \mathbf{W}_{\cdot k})$. Thus, by applying Hoeffding's inequality,

$$P\left(|s_{ij} - \mathbb{E}[s_{ij}]| \ge t \right) \le 2 \exp \left(-\frac{t^2 D_{ii}^{2\tau} D_{jj}^{2\tau}}{2r^2} \right).$$

Correspondingly, we set $\delta' = 2 \exp \left(-\frac{t^2 D_{ii}^{2\tau} D_{jj}^{2\tau}}{2r^2} \right)$ and solving for t, this means that with probability at least $1 - \delta'$,

$$|s_{ij} - \mathbb{E}[s_{ij}]| \le \sqrt{\frac{2r^2 \ln(2/\delta')}{D_{ii}^{2\tau} D_{jj}^{2\tau}}} = c^2 R^2 \sum_k \|\mathbf{W}_{\cdot k}\|_2^2 \sqrt{\frac{2 \ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1}}}.$$

With probability at least $1 - \delta'$,

$$\left| \mathbb{E}_X[Z_i^\top Z_j] - Z_i^\top Z_j \right| \le c^2 R^2 \sum_k \|\mathbf{W}_{\cdot k}\|_2^2 \sqrt{\frac{2 \ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1}}}.$$

B.2 Proof of Lemma 1

To prove this lemma, we first introduce the concept of the probability adjacency matrix. For the transformed graph $\widehat{\mathcal{G}}$, we denote its probability adjacency matrix as $\widehat{\mathbf{W}}$, in which $\hat{w}_{ij} = \frac{1}{E} \cdot \widehat{\mathbf{A}}_{ij}$. $\hat{w}_{ij}$ can be understood as the probability that two nodes have an edge and the weights sum to 1 because the total probability mass is 1: $\sum_{i,j} \hat{w}_{i,j'} = 1$, for $v_i, v_j \in \mathcal{V}$. The corresponding symmetric normalized matrix is $\widehat{\mathbf{W}}_{sym} = \widehat{\mathbf{D}}_{\mathbf{w}}^{-1/2} \widehat{\mathbf{W}} \widehat{\mathbf{D}}_{\mathbf{w}}^{-1/2}$, and the $\widehat{\mathbf{D}}_{\mathbf{w}} = diag([\hat{w}_1, \ldots, \hat{w}_N])$, where $\hat{w}_i = \sum_j \hat{w}_{ij}$. We then introduce the Matrix Factorization Loss which is defined as:

$$\min_{\mathbf{F} \in \mathbb{R}^{N \times k}} \mathcal{L}_{\mathrm{mf}}(\mathbf{F}) := \left\| \widehat{\mathbf{A}}_{sym} - \mathbf{F}\mathbf{F}^\top \right\|_F^2. \tag{18}$$

By the classical theory on low-rank approximation, Eckart-Young-Mirsky theorem (Eckart & Young, 1936), any minimizer $\widehat{\mathbf{F}}$ of $\mathcal{L}_{\mathrm{mf}}(\mathbf{F})$ contains scaling of the smallest eigenvectors of $\mathbf{L}_{sym}$ (also, the largest eigenvectors of $\widehat{\mathbf{A}}_{sym}$) up to a right transformation for some orthonormal matrix $\mathbf{R} \in \mathbb{R}^{K \times K}$. We have $\widehat{\mathbf{F}} = \mathbf{F}^*$. $\mathrm{diag}\left(\left[\sqrt{1-\lambda_1}, \ldots, \sqrt{1-\lambda_K}\right]\right)\mathbf{R}$, where $\mathbf{F}^* = [\mathbf{u}_1, \mathbf{u}_2, \cdots, \mathbf{u}_K] \in \mathbb{R}^{N \times K}$. To proof the Lemma 1, we first present the Lemma 2.

Lemma 2 *For transformed graph, its probability adjacency matrix* $\widehat{\mathbf{W}}$, *and adjacency matrix* $\widehat{\mathbf{A}}$ *are equal after the symmetric normalization,* $\widehat{\mathbf{W}}_{sym} = \widehat{\mathbf{A}}_{sym}$.
Proof. For any two nodes $v_i, v_j \in \mathcal{V}$ and $i \neq j$, we denote the the element in i-th row and j-th column of matrix $\widehat{\mathbf{W}}_{sym}$ as $\widehat{\mathbf{W}}_{sym}^{ij}$.

$$
\begin{aligned}
\widehat{\mathbf{W}}_{sym}^{ij} &= \frac{1}{\sqrt{\sum_k \hat{w}_{ik}}\sqrt{\sum_k \hat{w}_{kj}}} \frac{1}{E} \widehat{\mathbf{A}}^{ij} \\
&= \frac{1}{\sqrt{\sum_k \widehat{\mathbf{A}}_{ik}}\sqrt{\sum_k \widehat{\mathbf{A}}_{kj}}} \widehat{\mathbf{A}}^{ij} = \widehat{\mathbf{A}}_{sym}^{ij}
\end{aligned}
\tag{19}
$$

Leveraging the Lemma 2, we present the proof of Lemma 1.

Proof of Lemma 1 We start from the matrix factorization loss over $\widehat{\mathbf{A}}_{sym}$ to show the equivalence.

$$
\begin{aligned}
\|\widehat{\mathbf{A}}_{sym} &- \mathbf{F}\mathbf{F}^\top\|_F^2 = \|\widehat{\mathbf{W}}_{sym} - \mathbf{F}\mathbf{F}^\top\|_F^2 \\
&= \sum_{ij} \left(\frac{\hat{w}_{ij}}{\sqrt{\hat{w}_i}\sqrt{\hat{w}_j}} - f_{\mathrm{mf}}(v_i)^\top f_{\mathrm{mf}}(v_j)\right)^2 \\
&= \sum_{ij} (f_{\mathrm{mf}}(v_i)^\top f_{\mathrm{mf}}(v_j))^2 \\
&\quad - 2\sum_{ij} \frac{\hat{w}_{ij}}{\sqrt{\hat{w}_i}\sqrt{\hat{w}_j}} f_{\mathrm{mf}}(v_i)^\top f_{\mathrm{mf}}(v_j) + \|\hat{\mathbf{W}}_{sym}\|_F^2 \\
&= \sum_{ij} \hat{w}_i \hat{w}_j \left[\left(\frac{1}{\sqrt{\hat{w}_i}} \cdot f_{\mathrm{mf}}(v_i)\right)^\top \left(\frac{1}{\sqrt{\hat{w}_j}} \cdot f_{\mathrm{mf}}(v_j)\right)\right]^2 \\
&\quad - 2\sum_{ij} \hat{w}_{ij}\left(\frac{1}{\sqrt{\hat{w}_i}} \cdot f_{\mathrm{mf}}(v_i)\right)^\top \left(\frac{1}{\sqrt{\hat{w}_j}} \cdot f_{\mathrm{mf}}(v_j)\right) + C
\end{aligned}
\tag{20}
$$

where $f_{\mathrm{mf}}(v_i)$ is the i-th row of the embedding matrix $\mathbf{F}$. The $\hat{w}_i$ which can be understood as the node selection probability which is proportional to the node degree. Then, we can define the corresponding sampling distribution as P_{deg}. If and only if $\sqrt{w_i} \cdot F_\psi(v_i) = f_{\mathrm{mf}}(v_i) = \mathbf{F}_i$, the we have:

$$
\begin{aligned}
&\mathbb{E}_{\substack{v_i \sim P_{deg} \\ v_j \sim P_{deg}}} \left(F_\psi(v_i)^\top F_\psi(v_j)\right)^2 \\
&- 2\,\mathbb{E}_{\substack{v_i \sim Uni(\mathcal{V}) \\ v_{i+} \sim Uni(\mathcal{N}(v_i))}} \left(F_\psi(v_i)^\top F_\psi(v_{i+})\right) + C
\end{aligned}
\tag{21}
$$

where $\mathcal{N}(v_i)$ denotes the neighbor set of node v_i and $Uni(\cdot)$ is the uniform distribution over the given set. Because we constructed the transformed graph by selecting the top-K_{pos} nodes for each node, then all nodes have the same degree. We can further simplify the objective as:

$$
\mathbb{E}_{\substack{v_i \sim Uni(\mathcal{V}) \\ v_j \sim Uni(\mathcal{V})}} \left(\mathbf{Z}_i^\top \mathbf{Z}_j\right)^2 - 2\,\mathbb{E}_{\substack{v_i \sim Uni(\mathcal{V}) \\ v_{i+} \sim Uni(S_{pos}^i)}} \left(\mathbf{Z}_i^\top \mathbf{Z}_{i+}\right) + C.
\tag{22}
$$

Due to the node selection procedure, the factor $\sqrt{w_i}$ is a constant and can be absorbed by the neural network, F_ψ. Then, because $\mathbf{Z}_i = F_\psi(v_i)$, we can have the Equation 22. Therefore, the minimizer of matrix factorization loss is equivalent with the minimizer of the contrastive loss.

B.3 Proof of Theorem 2

Proof. Now we provide the proof for the inner product of embedding. In particular, when we can achieve near-zero contrastive learning loss, *i.e.*, $\mathcal{L}_{\mathrm{mf}}(\mathbf{F}) = 0$, the minimizer $\mathbf{F}^*$ of $\mathcal{L}_{\mathrm{mf}}(\mathbf{F})$ contains scaling of the

smallest eigenvectors of $\widehat{\mathbf{L}}_{sym}$ (also, the largest eigenvectors of $\widehat{\mathbf{A}}_{sym}$), $\mathbf{F}^* = [\mathbf{u}_1, \mathbf{u}_2, \cdots, \mathbf{u}_K] \in \mathbb{R}^{N \times K}$, according to the Eckart-Young-Mirsky theorem (Eckart & Young, 1936). Recall that $\mathbf{y} = \{1, -1\}^N \in \mathbb{R}^{N \times 1}$ is label of all nodes. Then we show there is a constraint on the quadratic form with respect to the optimal classifier. According to graph spectral theory (Chung & Graham, 1997), the quadratic form

$$\mathbf{y}^\top \widehat{\mathbf{L}}_{sym} \mathbf{y} = \frac{1}{2} \sum_{i,i'} (\widehat{\mathbf{A}}_{sym})_{i,i'} (y_i - y_{i'})^2$$

which captures the amount of edges connecting different labels. Furthermore, suppose that the expected homophily over distribution of graph feature and label, i.e., $y \sim P(y_i), \mathbf{x} \sim P_y(\mathbf{x})$, through similarity selection satisfies $\mathbb{E}[h_{edge}(\hat{\mathcal{G}})] = 1 - \bar{\phi}$. Here $\bar{\phi} = \mathbb{E}_{v_i, v_j \sim Uni(\mathcal{V})}(\widehat{\mathbf{A}}_{i,j} \cdot \mathbb{1}[y_i \neq y_j])$. Since we have defined that $\bar{\phi}$ as the density of edges that connects different labels, we can directly show that $\mathbf{y}^\top \widehat{\mathbf{L}}_{sym} \mathbf{y} \leq \bar{\phi} N$. Then we expand the above expression accoding to $\widehat{\mathbf{L}}_{sym} = \mathbf{I} - \widehat{\mathbf{A}}_{sym}$,

$$\mathbf{y}^\top \widehat{\mathbf{L}}_{sym} \mathbf{y} = \mathbf{y}^\top (\mathbf{I} - \widehat{\mathbf{A}}_{sym}) \mathbf{y} = N - \mathbf{y}^\top \widehat{\mathbf{A}}_{sym} \mathbf{y}$$

Next we consider the situation that we achieve the optimal solution of the contrastive loss, $\mathbf{Z} = \arg\min \mathcal{L}_{\text{SP-GCL}}$. Then, we have $\mathcal{L}_{mf}(\mathbf{F}^*) = 0$, which implies that $\widehat{\mathbf{A}}_{sym} = (\mathbf{F}^*)^\top \mathbf{F}^*$. As we analyzed in Section B.2, we have $\mathbf{Z} = \mathbf{F}^*$ in this case. Furthermore, we have,

$$\begin{aligned}
\mathbf{y}^\top \widehat{\mathbf{L}}_{sym} \mathbf{y} &= \mathbf{y}^\top (\mathbf{I} - \widehat{\mathbf{A}}_{sym}) \mathbf{y} = N - \mathbf{y}^\top \mathbf{Z}^\top \mathbf{Z} \mathbf{y} \\
&= N - \mathbf{y}^\top (\mathbf{Z}_i^\top \mathbf{Z}_j)_{(i,j \in n \times n)} \mathbf{y} \\
&= N - \left(\sum_{i,j} \mathbf{Z}_i^\top \mathbf{Z}_j |_{y_i = y_j} - \sum_{i,j} \mathbf{Z}_i^\top \mathbf{Z}_j |_{y_i \neq y_j} \right)
\end{aligned} \tag{23}$$

This leads to,

$$\begin{aligned}
\frac{1}{N} &\left[\sum_{i,j} \mathbf{Z}_i^\top \mathbf{Z}_j |_{y_i = y_j} - \sum_{i,j} \mathbf{Z}_i^\top \mathbf{Z}_j |_{y_i \neq y_j} \right] \\
&= \mathbb{E}[\mathbf{Z}_i^\top \mathbf{Z}_j |_{y_i = y_j}] - \mathbf{E}[\mathbf{Z}_i^\top \mathbf{Z}_j |_{y_i \neq y_j}] \geq 1 - \bar{\phi}
\end{aligned} \tag{24}$$

B.4 Proof of Theorem 3

Recently, HaoChen et al. (2021) presented the following theoretical guarantee for the model learned with the matrix factorization loss.

Lemma 3 *For a graph $\mathcal{G}$, let $f_{\text{mf}}^* \in \arg\min_{f_{\text{mf}}: \mathcal{V} \to \mathbb{R}^K}$ be a minimizer of the matrix factorization loss, $\mathcal{L}_{\text{mf}}(\mathbf{F})$, where $\mathbf{F}_i = f_{\text{mf}}(v_i)$. Then, for any label $\mathbf{y}$, there exists a linear classifier $\mathbf{B}^* \in \mathbb{R}^{c \times K}$ with norm $\|\mathbf{B}^*\|_F \leq 1/(1 - \lambda_K)$ such that*

$$\mathbb{E}_{v_i} \left[\|\vec{y}_i - \mathbf{B}^* f_{\text{mf}}^*(v_i)\|_2^2 \right] \leq \frac{\phi^{\mathbf{y}}}{\lambda_{K+1}}, \tag{25}$$

where $\vec{y}_i$ is the one-hot embedding of the label of node v_i. The difference between labels of connected data points is measured by $\phi^{\mathbf{y}}$, $\phi^{\mathbf{y}} := \frac{1}{E} \sum_{v_i, v_j \in \mathcal{V}} \mathbf{A}_{ij} \cdot \mathbb{1}[y_i \neq y_j]$.

Proof of Theorem 3. This proof is a direct summary on the established lemmas in previous section. By Lemma 1 and Lemma 3, we have,

$$\mathbb{E}_{v_i} \left[\|\vec{y}_i - \mathbf{B}^* f_{\text{gcl}}^*(v_i)\|_2^2 \right] \leq \frac{\phi^y}{\hat{\lambda}_{K+1}} \tag{26}$$

where $\hat{\lambda}_i$ is the i-th smallest eigenvalue of the Laplacian matrix $\widehat{\mathbf{L}}_{sym} = \mathbf{I} - \widehat{\mathbf{A}}_{sym}$. Note that ϕ^y in Lemma 3 equals $1 - h_{edge}$.

Then we apply Theorem 1 and Theorem 2 for h_{edge} to conclude the proof:

$$\mathbb{E}_{v_i}\left[\left\|\vec{y}_i - \mathbf{B}^* f_{\text{gcl}}^*(v)\right\|_2^2\right]$$

$$\leq \frac{1 - h_{edge}}{\hat{\lambda}_{K+1}} \leq \frac{\bar{\phi} + c^2 R^2 \sum_{k=1}^{K} \|\mathbf{w}_k\|_2^2 \sqrt{\frac{2\ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1}}}}{\hat{\lambda}_{K+1}} \qquad (27)$$

$$= \frac{\bar{\phi}}{\hat{\lambda}_{K+1}} + c^2 R^2 \sum_{k=1}^{K} \|\mathbf{w}_k\|_2^2 \sqrt{\frac{2\ln(2/\delta')}{D_{ii}^{2\tau-1} D_{jj}^{2\tau-1} \hat{\lambda}_{K+1}^2}}$$

C Augmentations in Existing Works

We summarized the graph augmentation techniques used in previous works into the Table 8.

Table 8: Summary of graph augmentations used by representative GCL models. Multiple[*] denotes multiple augmentation methods including edge removing, edge adding, node dropping and subgraph induced by random walks.

Method	Topology Aug.	Feature Aug.
DGI (Velickovic et al., 2019)	Node Shuffling	-
GMI (Peng et al., 2020)	Node Shuffling	-
MVGRL (Hassani & Khasahmadi, 2020)	Diffusion	-
GCC (Qiu et al., 2020)	Subgraph	-
GraphCL (You et al., 2020)	Multiple[*]	Feature Dropout
GRACE (Zhu et al., 2020d)	Edge Removing	Feature Masking
GCA (Zhu et al., 2021b)	Edge Removing	Feature Masking
BGRL (Grill et al., 2020)	Edge Removing	Feature Masking