Marginal Likelihood Gradient for Bayesian Neural Networks

Abstract

Bayesian learning of neural networks is attractive as it can protecting against over-fitting and provide automatic methods for inferring important hyperparameters by maximizing the marginal probability of the data. However existing approaches in this vein, such as those based on variational inference, do not perform well. In this paper we take a different approach, directly deriving a practical estimator of the gradient of the marginal log likelihood for BNNs by combining local reparametrization of the network w.r.t. the prior distribution with the self-normalized importance sampling estimator. We show promising preliminary results on a toy example and on vectorized MNIST classification where the new method to adjust hyperparameters results in significantly improved performance of variational inference compared to relying on predefined hyperparameters.

1. Introduction

We consider a supervised learning task with data set $\mathcal{D} = \{(\boldsymbol{x}_i, \boldsymbol{y}_i)\}$, likelihood $p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta}, \boldsymbol{\beta})$ and prior distribution $p(\boldsymbol{\theta}|\boldsymbol{\alpha})$ where $\boldsymbol{\alpha}$ and $\boldsymbol{\beta}$ denote hyperparameters. We denote the observation model of data $\mathcal{D}$ as $p(\boldsymbol{y}|\boldsymbol{x}, \boldsymbol{\theta}, \boldsymbol{\beta})$ defining the likelihood $p(\mathcal{D}|\boldsymbol{\theta}, \boldsymbol{\beta}) = \prod_{i=1}^{N} p(\boldsymbol{y}_i|\boldsymbol{x}_i, \boldsymbol{\theta}, \boldsymbol{\beta})$ and marginal likelihood as $p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) = \prod_i p(\{\boldsymbol{y}_i\}|\{\boldsymbol{x}_i\}, \boldsymbol{\alpha}, \boldsymbol{\beta})$. Given a new data point $(\boldsymbol{x}^*, \boldsymbol{y}^*)$, a fully Bayesian approach to modeling makes a prediction by marginalizing out posterior distribution over parameters $\boldsymbol{\theta}$ and hyperparameters $\boldsymbol{\alpha}, \boldsymbol{\beta}$ (MacKay, 1992a):

$$p(\boldsymbol{y}^*|\boldsymbol{x}^*, \mathcal{D}) = \int \int \int p(\boldsymbol{y}^*|\boldsymbol{x}^*, \boldsymbol{\theta}, \boldsymbol{\beta}) p(\boldsymbol{\theta}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta}) p(\boldsymbol{\alpha}, \boldsymbol{\beta}|\mathcal{D}) d\boldsymbol{\theta} d\boldsymbol{\alpha} d\boldsymbol{\beta}. \tag{1}$$

The integrals in Equation (1) inevitably carry high computational burden for non-trivial models, requiring us to recourse to approximate inference. We subsequently discuss approximations to posterior distributions $p(\boldsymbol{\theta}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})$ and $p(\boldsymbol{\alpha}, \boldsymbol{\beta}|\mathcal{D})$.

Variational inference (VI). Variational inference (Barber and Bishop, 1998; Hinton and van Camp, 1993) reformulates finding an approximation to a posterior $p(\boldsymbol{\theta}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})$ into an optimization problem finding a a simpler distribution $q(\boldsymbol{\theta}|\boldsymbol{\lambda})$ approximating $p(\boldsymbol{\theta}|\mathcal{D})$. This is done by minimizing the divergence $D_{KL}\big(q(\boldsymbol{\theta}|\boldsymbol{\lambda})||p(\boldsymbol{\theta}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})\big)$, which is equivalent to maximizing the Evidence Lower BOund (ELBO), a lower bound to $\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$, defined as:

$$\mathcal{L}(\boldsymbol{\lambda}; \boldsymbol{\alpha}, \boldsymbol{\beta}) = \sum_{i=1}^{N} \mathbb{E}_{q(\boldsymbol{\theta}|\boldsymbol{\lambda})} \log p(\boldsymbol{y}_i|\boldsymbol{x}_i, \boldsymbol{\theta}, \boldsymbol{\beta}) - D_{KL}\big(q(\boldsymbol{\theta}|\boldsymbol{\lambda})||p(\boldsymbol{\theta}|\boldsymbol{\alpha})\big). \tag{2}$$

Evidence framework. The evidence framework (MacKay, 1992a,b) provides a systematic framework for adaptation of hyperparameters $\boldsymbol{\alpha}, \boldsymbol{\beta}$. Equation (1) indicates that $p(\boldsymbol{\alpha}, \boldsymbol{\beta}|\mathcal{D})$, (and the marginal likelihood $p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ if the prior over $\boldsymbol{\alpha}, \boldsymbol{\beta}$ is uniform) embodies the

influence of predictions arising from hyperparameters $\boldsymbol{\alpha}, \boldsymbol{\beta}$ on marginalized predictions $p(\boldsymbol{y}^*|\boldsymbol{x}^*, \mathcal{D})$. If the integral in Equation (1) has no closed form, it can be approximated as $p(\boldsymbol{y}^*|\boldsymbol{x}^*, \mathcal{D}) \approx \int p(\boldsymbol{y}^*|\boldsymbol{x}^*, \boldsymbol{\theta})p(\boldsymbol{\theta}|\mathcal{D}, \boldsymbol{\alpha}^*, \boldsymbol{\beta}^*)d\boldsymbol{\theta}$ where $\boldsymbol{\alpha}^*, \boldsymbol{\beta}^* = \operatorname{argmax}_{\boldsymbol{\alpha}, \boldsymbol{\beta}} p(\boldsymbol{\alpha}, \boldsymbol{\beta}|\mathcal{D})$. Relying only on mode $\boldsymbol{\alpha}^*, \boldsymbol{\beta}^*$ can lead to poor approximation of $p(\boldsymbol{y}^*|\boldsymbol{x}^*, \mathcal{D})$, depending on the concentration of density $p(\boldsymbol{\alpha}, \boldsymbol{\beta}|\mathcal{D})$. Estimating log marginal likelihood $\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ for non trivial models is a well-known problem (Barber and Bishop, 1998).

Bayesian Neural Networks. We consider a neural network $\mathcal{F}_{\boldsymbol{W}}$ represented as composition of L fully-connected layers interleaved with activation functions $\mathcal{F}_{\boldsymbol{W}} = \mathcal{F}_{\boldsymbol{W}_L} \circ \phi \circ \mathcal{F}_{\boldsymbol{W}_{L-1}} \ldots \phi \circ \mathcal{F}_{\boldsymbol{W}_1}$ where ϕ denotes an activation function. We denote a forward pass with input $\boldsymbol{x}_l$ through l-th layer as $\mathcal{F}_{\boldsymbol{W}_l}(\boldsymbol{x}_l) = \boldsymbol{W}_l \boldsymbol{x}_l$ where biases are handled by expanding the dimension of $\boldsymbol{x}_l$. We employ the notation $\mathcal{N}(\boldsymbol{W}_l|\boldsymbol{\mu}_l, \boldsymbol{\sigma}_l^2)$ to denote the mean-field Gaussian distribution over layer l meaning $w_{l,ij} \sim \mathcal{N}(\mu_{l,ij}, \sigma_{l,ij}^2)$. We adopt the notation $\boldsymbol{W} = (\boldsymbol{W}_1, \boldsymbol{W}_2, \ldots, \boldsymbol{W}_l)$ for weights, $\boldsymbol{\mu} = (\boldsymbol{\mu}_1, \boldsymbol{\mu}_2, \ldots, \boldsymbol{\mu}_l)$ and $\boldsymbol{\sigma} = (\boldsymbol{\sigma}_1^2, \boldsymbol{\sigma}_2^2, \ldots, \boldsymbol{\sigma}_L^2)$ for variational parameters and $\boldsymbol{\mu_\alpha} = (\boldsymbol{\mu}_{\boldsymbol{\alpha}_1}, \boldsymbol{\mu}_{\boldsymbol{\alpha}_2}, \ldots, \boldsymbol{\mu}_{\boldsymbol{\alpha}_L}), \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2 = (\boldsymbol{\sigma}_{\boldsymbol{\alpha}_1}^2, \boldsymbol{\sigma}_{\boldsymbol{\alpha}_1}^2, \ldots, \boldsymbol{\sigma}_{\boldsymbol{\alpha}_L}^2)$ for prior hyperparameters. We restrict the attention to mean-field priors $p(\boldsymbol{W}_l)$ and mean-field approximate posteriors $q(\boldsymbol{W}_l|\boldsymbol{\mu}_l, \boldsymbol{\sigma}_l^2)$ factorizing over layers. Hyperparameter $\boldsymbol{\beta}$ belongs to an observation model, e.g. scale of Gaussian observation noise $\mathcal{N}(\boldsymbol{y}|\boldsymbol{0}, \operatorname{diag}[\boldsymbol{\beta}^2])$.

Priors for BNNs. Hyperparameters $\boldsymbol{\alpha}^*, \boldsymbol{\beta}^*$ can be also learned by optimizing $\mathcal{L}(\boldsymbol{\lambda}; \boldsymbol{\alpha}, \boldsymbol{\beta})$ as proxy for log marginal likelihood since $\log p(\mathcal{D}; \boldsymbol{\alpha}, \boldsymbol{\beta}) \geq \mathcal{L}(\boldsymbol{\lambda}; \boldsymbol{\alpha}, \boldsymbol{\beta})$ (MacKay, 1999; Wu et al., 2019). The local optima of $\log p(\mathcal{D}; \boldsymbol{\alpha}, \boldsymbol{\beta})$ and $\mathcal{L}(\boldsymbol{\lambda}; \boldsymbol{\alpha}, \boldsymbol{\beta})$ can significantly vary. This is manifested by a flexible prior distribution $p(\boldsymbol{\theta}|\boldsymbol{\alpha})$ learned by optimizing $\mathcal{L}(\boldsymbol{\lambda}; \boldsymbol{\alpha}, \boldsymbol{\beta})$ collapsing to the approximate posterior $q(\boldsymbol{\theta}|\boldsymbol{\lambda})$, resulting in no regularization (Blundell et al., 2015). Laplace approximation assumes $\log p(\mathcal{D}, \boldsymbol{W}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ is a quadratic w.r.t. weights and enables approximating $\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ in closed form (MacKay, 1992c), hence compare different $\boldsymbol{\alpha}, \boldsymbol{\beta}$. Poorly chosen prior can result in ELBO not correlating with predictive performance of the learned posterior (Trippe and Turner, 2018; Turner and Sahani, 2011). Priors for BNNs are a lively area of research (Atanov et al., 2019; Nalisnick et al., 2019; Krishnan et al., 2019).

Local Reparametrization Trick (LRT). The forward pass $\mathcal{F}_{\boldsymbol{W}_l}(\boldsymbol{x}_l)$ through a fully-connected layer with mean-field Gaussian distribution over weights $\boldsymbol{W}_l \sim \mathcal{N}(\boldsymbol{\mu}_l, \boldsymbol{\sigma}_l^2)$, can be reparametrized as (Kingma et al., 2015):

$$\mathcal{F}_{\boldsymbol{W}_l}(\boldsymbol{x}_l) = \mathcal{F}_{\boldsymbol{\mu}_l}(\boldsymbol{x}_l) + \sqrt{\mathcal{F}_{\boldsymbol{\sigma}_l^2}(\boldsymbol{x}_l)} \odot \boldsymbol{\epsilon}_l, \quad \boldsymbol{\epsilon}_l \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{I}), \tag{3}$$

where $\sqrt{}$ is applied element-wise and the Equation (3) denotes the equality between two random variables (both LHS and RHS follow the same distribution). We will denote the reparametrization noise as $\boldsymbol{\epsilon} = (\boldsymbol{\epsilon}_1, \boldsymbol{\epsilon}_2, \ldots, \boldsymbol{\epsilon}_L)$ and reparametrization of the network $f_{\boldsymbol{W}}$ arising from Equation (3) applied to every layer l by $g_{\boldsymbol{\mu}, \boldsymbol{\sigma}^2, \boldsymbol{\epsilon}}$, which yields $\mathbb{E}_{q(\boldsymbol{W}|\boldsymbol{\mu}, \boldsymbol{\sigma}^2)} h(f_{\boldsymbol{W}}(\boldsymbol{x})) = \mathbb{E}_{\boldsymbol{\epsilon} \sim \mathcal{N}(\boldsymbol{0}, \boldsymbol{I})} h(g_{\boldsymbol{\mu}, \boldsymbol{\sigma}^2, \boldsymbol{\epsilon}}(\boldsymbol{x}))$ for a continuous function h.

2. Methods

In this section we demonstrate that self-normalized importance sampling (SNIS) can be applied to derive a practical estimator of the gradient of log marginal probability of data $\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ for BNN with a mean-field Gaussian prior. First we discuss the problems emerging when naively attempting to apply methods developed for learning generative

models to maximize $\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ and subsequently we demonstrate these issues can be mitigated by locally reparametrizing the network. The gradient $\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ can be derived as (Bornschein and Bengio, 2014; Tucker et al., 2019):

$$\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) = \mathbb{E}_{p(\boldsymbol{W}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{W}|\boldsymbol{\alpha}). \tag{4}$$

See Appendix A for similar expression for $\nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ and associated derivations. In practice, the expectation w.r.t. posterior $p(\boldsymbol{W}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})$ in RHS of Equation (4) cannot be directly approximated. A naive attempt to apply SNIS to Equation (4) results in:

$$\hat{I}\big(\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})\big) = \sum_{s=1}^{S} \frac{w(\boldsymbol{W}^{(s)})}{\sum_{j=1}^{S} w(\boldsymbol{W}^{(j)})} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{W}^{(s)}|\boldsymbol{\alpha}, \boldsymbol{\beta}), \tag{5}$$

where $w(\boldsymbol{W}^{(s)}) = p(\mathcal{D}|\boldsymbol{W}^{(s)}, \boldsymbol{\beta})p(\boldsymbol{W}^{(s)}|\boldsymbol{\alpha})/q(\boldsymbol{W}^{(s)})$ and weights are proposed from $\boldsymbol{W}^{(s)} \sim q(\boldsymbol{W})$. There are several challenges associated with applying the estimators given by Equation (5). First, sampling multiple weights $\boldsymbol{W}^{(s)}$ is excessively costly even for networks of moderate size as this corresponds to sampling separate copies of the network $f_{\boldsymbol{W}}$. Second, RHS of Equation (5) is equivalent to high variance score gradient estimator (Williams, 1992). Third, a separate objective needs to be optimized to derive proposal $q(\boldsymbol{W}|\boldsymbol{\alpha})$ e.g. by minimizing mismatch between $q(\boldsymbol{W})$ and $p(\boldsymbol{W}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})$. Lastly, calculating weights $w(\boldsymbol{W}^{(s)})$ requires iterating over whole data set $\mathcal{D}$.

We now demonstrate that reparametrizing the network using LRT leads to the estimator free of two first described issues. More precisely, rather than operating in space of random weights $\boldsymbol{W}_l$, we can reparametrize the network using LRT and operate in the space of pre-activation reparametrization noise $\boldsymbol{\epsilon}_l \sim N(\mathbf{0}, \boldsymbol{I})$. This reduces the cost of sampling, as noise $\boldsymbol{\epsilon}_l$ has significantly lower dimensionality than weight matrices $\boldsymbol{W}_l$. In addition, the derived estimator is an improvement over one given by Equation (5) in a similar way as reparametrizing (Kingma and Welling, 2014; Rezende et al., 2014; Kingma et al., 2015) improve upon score function estimator applied to the ELBO (Paisley et al., 2012; Ranganath et al., 2014; Wingate and Weber, 2013; Titsias and Lázaro-Gredilla, 2014), since path derivative usually exhibits lower variance than score function gradient (Roeder et al., 2017). We subsequently discuss schemes to derive better proposal distribution and reduce the cost of computing IS weights. We now state Lemma deriving the reparametrized gradient of $\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$.

Lemma 1 (Evidence gradient for BNN with mean-field Gaussian prior) *Given a neural network $f_{\boldsymbol{W}}$ with layer-wise mean-field Gaussian prior $\mathcal{N}(\boldsymbol{W}_l|\boldsymbol{\mu}_{\boldsymbol{\alpha}_l}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}_l}^2)$ where $\boldsymbol{\alpha}, \boldsymbol{\beta}$ are hyperparameters, the log marginal likelihood gradient can be computed as:*

$$\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) = \mathbb{E}_{p(\boldsymbol{\epsilon}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \boldsymbol{\epsilon}}, \boldsymbol{\beta}), \tag{6}$$

where $p(\boldsymbol{\epsilon}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})$ is a posterior distribution over layer's preactivations resulting from applying reparametrization in Equation (3). Substituting $\nabla_{\boldsymbol{\alpha}}$ with $\nabla_{\boldsymbol{\beta}}$ in Equation (6) yields the gradient for hyperparameters of observation model $\nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$.

Note that Equation (6) still requires sampling from posterior distribution $p(\boldsymbol{\epsilon}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})$, where $\boldsymbol{\epsilon} = (\boldsymbol{\epsilon}_1, \boldsymbol{\epsilon}_2, \ldots, \boldsymbol{\epsilon}_l)$ denotes the reparametrization noise for consecutive layers $\mathcal{F}_{\boldsymbol{W}_l}$. While

the concept of posterior distribution over reparametrization noise might be somewhat confusing, it is well-defined: for fixed $\boldsymbol{\alpha}, \boldsymbol{\beta}$ and for every $\boldsymbol{\epsilon}$ we can compute the likelihood of $\boldsymbol{\epsilon}$ explaining the data $\prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}},\boldsymbol{\beta})$ and hence we can calculate posterior distribution over reparametrization noise $p(\boldsymbol{\epsilon}|\mathcal{D},\boldsymbol{\alpha},\boldsymbol{\beta})$ given prior $p(\boldsymbol{\epsilon})$. Crucially, the noise $\boldsymbol{\epsilon}_l$ has the dimension of layer's output N_{out}^l as oppose to weight matrices $\boldsymbol{W}_l$ of shape $N_{in}^l \times N_{out}^l$, enabling the practical estimation of Equation (6). Applying self-weighted importance sampling estimator where we propose from prior distribution $\boldsymbol{\epsilon}^{(s)} \sim q(\boldsymbol{\epsilon})$ gives us the following estimator of the log marginal likelihood gradient $\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})$:

$$\hat{I}(\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})) = \sum_{s=1}^{S} \frac{w(\boldsymbol{\epsilon}^{(s)})}{\sum_{j=1}^{S} w(\boldsymbol{\epsilon}^{(j)})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}^{(s)}}(\boldsymbol{x}_i)), \ \boldsymbol{\epsilon}^{(s)} \sim q(\boldsymbol{\epsilon}), \quad (7)$$

where $w(\boldsymbol{\epsilon}^{(s)}) = \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}},\boldsymbol{\beta})p(\boldsymbol{\epsilon})/q(\boldsymbol{\epsilon})$. The gradient in RHS of Equation (7) bears similarity to gradients derived for generative models (Bornschein and Bengio, 2014; Burda et al., 2015; Tucker et al., 2019). However, it is important to note not all derivations applicable to generative models transfer to BNNs if local reparametrization is desired, as LRT requires the expression under the expectation to be expressed only as a function of layer's outputs $\{\mathcal{F}(\boldsymbol{x}_l)\}_l$. For instance, $\mathbb{E}_{q(\boldsymbol{W})} p(\boldsymbol{y}|\boldsymbol{x}, f_{\boldsymbol{W}})p(\boldsymbol{W})/q(\boldsymbol{W})$ cannot be locally reparametrized due to the dependency on $p(\boldsymbol{W})/q(\boldsymbol{W})$.

Better proposal distributions. We now focus on deriving better proposal distributions $q(\boldsymbol{\epsilon})$ for estimator in Equation (7). This requires finding a distribution over noise $\boldsymbol{\epsilon}$ closer to posterior distribution $p(\boldsymbol{\epsilon}|\mathcal{D},\boldsymbol{\alpha},\boldsymbol{\beta})$. We define means and variances for Gaussian distributions over layer preactivations as $\boldsymbol{\mu_\epsilon} = (\boldsymbol{\mu}_{1,\boldsymbol{\epsilon}},\boldsymbol{\mu}_{2,\boldsymbol{\epsilon}},\ldots,\boldsymbol{\mu}_{L,\boldsymbol{\epsilon}})$ and $\boldsymbol{\sigma_\epsilon^2} = (\boldsymbol{\sigma}_{1,\boldsymbol{\epsilon}}^2,\boldsymbol{\sigma}_{2,\boldsymbol{\epsilon}}^2,\ldots,\boldsymbol{\sigma}_{L,\boldsymbol{\epsilon}}^2)$. We assume factors $q(\boldsymbol{\epsilon}_l|\boldsymbol{\mu}_{l,\boldsymbol{\epsilon}},\boldsymbol{\sigma}_{l,\boldsymbol{\epsilon}}^2)$ to follow mean-field Gaussian distribution. Further, we construct $q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2})$ by assuming independence between layers $q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}) = \prod_l^L q(\boldsymbol{\epsilon}_l|\boldsymbol{\mu}_{\boldsymbol{\epsilon}_l},\boldsymbol{\sigma}_{\boldsymbol{\epsilon}_l}^2)$. We learn an approximate posterior distribution $q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2})$ to $p(\boldsymbol{\epsilon}|\mathcal{D},\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})$ by minimizing $D_{KL}(q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2})||p(\boldsymbol{\epsilon}|\mathcal{D},\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2}))$ leading to ELBO-like expression:

$$\mathcal{L}(\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}) = \sum_{i=1}^{N} \mathbb{E}_{q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2})} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i)) - \sum_{l=1}^{L} D_{KL}(q(\boldsymbol{\epsilon}_l|\boldsymbol{\mu}_{\boldsymbol{\epsilon}_l},\boldsymbol{\sigma}_{\boldsymbol{\epsilon}_l}^2)||\mathcal{N}(\boldsymbol{\epsilon}_l|\boldsymbol{0},\boldsymbol{I})). \quad (8)$$

Importantly, the approximate posterior distribution $q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2})$ depends on the prior hyperparameters $\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2}$, so in practice we will optimize the above equation by performing one (or possibly a few) updates while we simultaneously learning $p(\boldsymbol{W}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})$. This setup of learning jointly learning model parameters $\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2}$ and auxiliary parameters $\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}$ resembles algorithms developed for generative models (Kingma and Welling, 2014; Bornschein and Bengio, 2014; Burda et al., 2015; Rezende et al., 2014), which simultaneously learn model parameters and variational parameters.

Computing weights $w(\boldsymbol{\epsilon})$. The cost of calculating weights $w(\boldsymbol{\epsilon})$ grows linearly with the size of data set $\mathcal{D}$. To ease the computational cost of iterating over whole data set $\mathcal{D}$ to calculate $w(\boldsymbol{\epsilon})$, we propose to employ the "average" likelihood calculated based on subsample set of data points, similarly as Li and Turner (2016). While the theoretical properties of this approximation are not very well studied, it appears to be a sensible heuristic.

Defining hyperpriors. Adjusting hyperparameters to data via evidence framework (type II MLE) can be prone to over-fitting. The standard approach to mitigate over-fitting

hyperparameters is to introduce hyperprior over $p(\boldsymbol{\alpha}, \boldsymbol{\beta})$. In addition, the variances of units $\boldsymbol{\sigma}_l^2$ can be shared across the layer l, so that $\boldsymbol{\sigma}_l^2 = \sigma_l^2 \mathbf{1}$. The gradients of log hyperprior $\nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{\alpha})$ and $\nabla_{\boldsymbol{\beta}} \log p(\boldsymbol{\beta})$ are simply added to the Equation (7).

3. Experimental demonstration

We will now empirically investigate the differences between learning hyperparameters $\boldsymbol{\alpha}, \boldsymbol{\beta}$ via optimizing $\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ and $\mathcal{L}(\boldsymbol{\mu}, \boldsymbol{\sigma}^2; \boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)$. In our experiments we assume layer-wise Gaussian hyperprior over shared (within every layer) prior log variances $p(\log \sigma_{\alpha_l}^2) = \mathcal{N}(\log \sigma_{\alpha_l}^2 | \log[40/(N_{in}+1)], \gamma_l^2)$, where N_{in} is the size of the layer's input and we set $\gamma_l^2 = 5$.

(a) Fixed hyperparameters $\quad$ (b) Optimizing ELBO $\quad$ (c) Log marginal gradient

Figure 1: Comparison of different approaches to infer prior means, variances and observation noise for regression with one hidden layer BNN. Prior distribution over function (top) and posterior learned with VI (bottom).

One dimensional regression. We first consider one dimensional regression where we try to learn function $f(x) = (x+1)\sin(2x+2) + 0.3\epsilon$, $\epsilon \sim \mathcal{N}(0,1)$ after observing only 3 data points. We learn a two hidden layer network with 128 hidden units, tanh activations and assume Gaussian observation model $\log p(y|f_{\boldsymbol{W}}(x), \beta) \propto -(y - f_{\boldsymbol{W}}(x))^2/2\beta^2 - \log \beta$. We use ADAM optimizer (Kingma and Ba, 2014) to optimize $\mathcal{L}(\boldsymbol{\mu}, \boldsymbol{\sigma}^2; \boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)$. We consider three approaches: (a) use fixed value of observation noise $\beta = 1$, zero prior unit means $\boldsymbol{\mu}$ and fixed variances $\sigma_{\alpha}^2 = 1/N_{in}$, (b) optimize $\mathcal{L}(\boldsymbol{\mu}, \boldsymbol{\sigma}^2; \boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \beta)$ w.r.t. both variational parameters $\boldsymbol{\mu}, \boldsymbol{\sigma}^2$, and prior hyperparameters $\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \beta$, and (c) learn $\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \beta$ using evidence gradient given by Equation (7) and then learn variational posterior $q(\boldsymbol{\mu}, \boldsymbol{\sigma}^2)$ by optimizing $\mathcal{L}(\boldsymbol{\mu}, \boldsymbol{\sigma}^2; \boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \beta)$. We report prior and posterior predictive distribution in Figure 1. First, in Figure 1(a) we observe that MF-VI with predefined variances of units can severely underfit data if prior variances of the units are not tuned. This happens when the optimization of $\mathcal{L}(\boldsymbol{\mu}, \boldsymbol{\sigma}^2; \boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \beta)$ focuses on reducing complexity penalty and explains data $\mathcal{D}$ by noise. Next, in Figure 1(b) we see that learning prior hyperparameters by optimizing $\mathcal{L}(\boldsymbol{\mu}, \boldsymbol{\sigma}^2; \boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \beta)$ leads to an improved performance, but results in overconfident predictive distribution. This happens as optimizing prior $p(\boldsymbol{W}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)$ using Equation (2) can

set it very close to posterior $q(\boldsymbol{W}|\boldsymbol{\mu},\boldsymbol{\sigma}^2)$, yielding almost no regularization. Lastly, we see from Figure 1(c) that using the derived log marginal likelihood gradient results in a prior explaining the data $\mathcal{D}$ with subsequent application of VI yielding reasonable performance.

Vectorized MNIST classification. Next we investigate if adjusting hyperparameters leads to MF-VI yielding improved results on a vectorized MNIST classification task, a standard benchmark for Bayesian deep learning (Blundell et al., 2015). We learn a two hidden layer network with 400 hidden units and ReLU activations (Nair and Hinton, 2010) and report learning curves as optimization proceeds in Figure 2. We use the same hyperpriors for all approaches and compare using predefined setting of hyperparameters with learning them via optimizing ELBO and using the derived marginal likelihood gradient.

Overall, we observe similar patterns as in 1D regression experiment. Using predefined set of hyperparameters yields underfitting with test NLL 0.095 and test error rate 2.49%, as optimizing ELBO constrains $q(\boldsymbol{W}|\boldsymbol{\mu},\boldsymbol{\sigma}^2)$ to prior distribution incapable of modeling data. Tuning prior by optimizing ELBO leads to over-fitting (test NLL 0.177 and test error rate 1.57%), as prior distribution $p(\boldsymbol{W}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)$ collapse to posterior $q(\boldsymbol{W}|\boldsymbol{\mu},\boldsymbol{\sigma}^2)$ leading to insufficient regularization. Using log marginal likelihood gradient given by Equation (6) optimizes prior $p(\boldsymbol{W}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)$ directly to fit the data and hence introduces sufficient regularization when optimizing ELBO, leading to the best test log likelihood 0.042 and test error rate 1.15%. We also observe that the learning curve of ELBO correlates very strongly with complexity penalty curve as optimization proceeds, indicating the importance of the choice of regularizing prior distribution for BNNs.

Figure 2: Different approaches to infer prior means and shared variances across layers for MF-VI on vectorized MNIST classification. Using log marginal likelihood gradient given by Equation (7) leads to the best predictive performance.

4. Conclusions

We have derived a pragmatic algorithm capable of adjusting hyperparameters of Bayesian Neural Networks with mean-field Gaussian priors by applying local reparametrization of the network combined with self-normalized importance sampling. The optimized priors roughly explained the data and subsequent application of VI resulted in fitting posterior distribution resulting in good predictive performance. We hope our work will catalyze research on algorithms inferring hyperparameters for BNNs.

References

Andrei Atanov, Arsenii Ashukha, Kirill Struminsky, Dmitry Vetrov, and Max Welling. The deep weight prior, 2019.

D. Barber and Christopher Bishop. Ensemble learning in bayesian neural networks. In *Generalization in Neural Networks and Machine Learning*, pages 215–237. Springer Verlag, January 1998. URL https://www.microsoft.com/en-us/research/publication/ensemble-learning-in-bayesian-neural-networks/.

Charles Blundell, Julien Cornebise, Koray Kavukcuoglu, and Daan Wierstra. Weight uncertainty in neural networks. In *Proceedings of the 32nd International Conference on International Conference on Machine Learning - Volume 37*, ICML'15, page 1613–1622. JMLR.org, 2015.

Jörg Bornschein and Yoshua Bengio. Reweighted wake-sleep, 2014.

Yuri Burda, Roger Grosse, and Ruslan Salakhutdinov. Importance weighted autoencoders, 2015.

Geoffrey E. Hinton and Drew van Camp. Keeping the neural networks simple by minimizing the description length of the weights. In *Proceedings of the Sixth Annual Conference on Computational Learning Theory*, COLT '93, page 5–13, New York, NY, USA, 1993. Association for Computing Machinery. ISBN 0897916115. doi: 10.1145/168304.168306. URL https://doi.org/10.1145/168304.168306.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 12 2014.

Diederik P. Kingma and Max Welling. Auto-encoding variational bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014. URL http://arxiv.org/abs/1312.6114.

Diederik P. Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. In *Proceedings of the 28th International Conference on Neural Information Processing Systems - Volume 2*, NIPS'15, page 2575–2583, Cambridge, MA, USA, 2015. MIT Press.

Ranganath Krishnan, Mahesh Subedar, and Omesh Tickoo. Specifying weight priors in bayesian deep neural networks with empirical bayes, 2019.

Yingzhen Li and Richard E Turner. Rényi divergence variational inference. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems 29*, pages 1073–1081. Curran Associates, Inc., 2016. URL http://papers.nips.cc/paper/6208-renyi-divergence-variational-inference.pdf.

David J. C. MacKay. Bayesian interpolation. *Neural Comput.*, 4(3):415–447, May 1992a. ISSN 0899-7667. doi: 10.1162/neco.1992.4.3.415. URL https://doi.org/10.1162/neco.1992.4.3.415.

David J. C. MacKay. The evidence framework applied to classification networks. 4(5): 720–736, September 1992b. ISSN 0899-7667. doi: 10.1162/neco.1992.4.5.720. URL https://doi.org/10.1162/neco.1992.4.5.720.

David J. C. MacKay. A practical bayesian framework for backpropagation networks. *Neural Comput.*, 4(3):448–472, May 1992c. ISSN 0899-7667. doi: 10.1162/neco.1992.4.3.448. URL https://doi.org/10.1162/neco.1992.4.3.448.

David J. C. MacKay. Comparison of approximate methods for handling hyperparameters. *Neural Comput.*, 11(5):1035–1068, July 1999. ISSN 0899-7667. doi: 10.1162/089976699300016331. URL https://doi.org/10.1162/089976699300016331.

Vinod Nair and Geoffrey E. Hinton. Rectified linear units improve restricted boltzmann machines. ICML'10, page 807–814, Madison, WI, USA, 2010. Omnipress. ISBN 9781605589077.

Eric Nalisnick, José Miguel Hernández-Lobato, and Padhraic Smyth. Dropout as a structured shrinkage prior, 2019.

John Paisley, David M. Blei, and Michael I. Jordan. Variational bayesian inference with stochastic search. In *Proceedings of the 29th International Coference on International Conference on Machine Learning*, ICML'12, page 1363–1370, Madison, WI, USA, 2012. Omnipress. ISBN 9781450312851.

Rajesh Ranganath, Sean Gerrish, and David Blei. Black Box Variational Inference. In Samuel Kaski and Jukka Corander, editors, *Proceedings of the Seventeenth International Conference on Artificial Intelligence and Statistics*, volume 33 of *Proceedings of Machine Learning Research*, pages 814–822, Reykjavik, Iceland, 22–25 Apr 2014. PMLR. URL http://proceedings.mlr.press/v33/ranganath14.html.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In Eric P. Xing and Tony Jebara, editors, *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pages 1278–1286, Bejing, China, 22–24 Jun 2014. PMLR. URL http://proceedings.mlr.press/v32/rezende14.html.

Geoffrey Roeder, Yuhuai Wu, and David K Duvenaud. Sticking the landing: Simple, lower-variance gradient estimators for variational inference. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems 30*, pages 6925–6934. Curran Associates, Inc., 2017.

Michalis Titsias and Miguel Lázaro-Gredilla. Doubly stochastic variational bayes for non-conjugate inference. In Eric P. Xing and Tony Jebara, editors, *Proceedings of the 31st International Conference on Machine Learning*, volume 32 of *Proceedings of Machine Learning Research*, pages 1971–1979, Bejing, China, 22–24 Jun 2014. PMLR. URL http://proceedings.mlr.press/v32/titsias14.html.

Brian Trippe and Richard Turner. Overpruning in variational bayesian neural networks, 2018.

George Tucker, Dieterich Lawson, Shixiang Gu, and Chris J. Maddison. Doubly reparameterized gradient estimators for monte carlo objectives. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=HkG3e205K7.

R. E. Turner and M. Sahani. Two problems with variational expectation maximisation for time-series models. In D. Barber, T. Cemgil, and S. Chiappa, editors, *Bayesian Time series models*, chapter 5, pages 109–130. Cambridge University Press, 2011.

Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Mach. Learn.*, 8(3–4):229–256, May 1992. ISSN 0885-6125. doi: 10.1007/BF00992696. URL https://doi.org/10.1007/BF00992696.

David Wingate and Theophane Weber. Automated variational inference in probabilistic programming. *ArXiv*, abs/1301.1299, 2013.

Anqi Wu, Sebastian Nowozin, Edward Meeds, Richard E. Turner, Jose Miguel Hernandez-Lobato, and Alexander L. Gaunt. Deterministic variational inference for robust bayesian neural networks. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=B1l08oAct7.

Appendix A.

We provide derivations of $\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ and $\nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})$ in Equation (6).

$$\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) = \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\alpha}} p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) \tag{9}$$

$$= \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\alpha}} \int p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) p(\boldsymbol{W}|\boldsymbol{\alpha}) d\boldsymbol{W} \tag{10}$$

$$= \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \int \nabla_{\boldsymbol{\alpha}} p(\boldsymbol{W}|\boldsymbol{\alpha}) p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) d\boldsymbol{W} \tag{11}$$

$$= \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \int p(\boldsymbol{W}|\boldsymbol{\alpha}) \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{W}|\boldsymbol{\alpha}) p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) d\boldsymbol{W} \tag{12}$$

$$= \int \frac{p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) p(\boldsymbol{W}|\boldsymbol{\alpha})}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{W}|\boldsymbol{\alpha}) d\boldsymbol{W} \tag{13}$$

$$= \mathbb{E}_{p(\boldsymbol{W}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{W}|\boldsymbol{\alpha}). \tag{14}$$

$$\nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) = \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\beta}} p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta}) \tag{15}$$

$$= \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\beta}} \int p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) p(\boldsymbol{W}|\boldsymbol{\alpha}) d\boldsymbol{W} \tag{16}$$

$$= \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \int p(\boldsymbol{W}|\boldsymbol{\alpha}) \nabla_{\boldsymbol{\beta}} p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) d\boldsymbol{W} \tag{17}$$

$$= \frac{1}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \int p(\boldsymbol{W}|\boldsymbol{\alpha}) p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) \nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) d\boldsymbol{W} \tag{18}$$

$$= \int \frac{p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) p(\boldsymbol{W}|\boldsymbol{\alpha})}{\log p(\mathcal{D}|\boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) \tag{19}$$

$$= \mathbb{E}_{p(\boldsymbol{W}|\mathcal{D}, \boldsymbol{\alpha}, \boldsymbol{\beta})} \nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}). \tag{20}$$

We now provide proof of Lemma 1. The derivation is based on applying reparametrization of the network $f_{\boldsymbol{W}}$ into $g_{\boldsymbol{\mu}, \boldsymbol{\sigma}^2, \boldsymbol{\epsilon}}$ together with applying log trick $\nabla f(x) = f(x) \nabla \log f(x)$.

Proof Derivation of Lemma 1.

$$\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2) = \tag{21}$$

$$= \frac{1}{p(\mathcal{D}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)} \nabla_{\boldsymbol{\alpha}} \int p(\mathcal{D}|\boldsymbol{W}, \boldsymbol{\beta}) p(\boldsymbol{W}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2) d\boldsymbol{W} \tag{22}$$

$$= \frac{1}{p(\mathcal{D}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)} \nabla_{\boldsymbol{\alpha}} \int \prod_{i=1}^{N} p(\boldsymbol{y}_i|f_{\boldsymbol{W}}(\boldsymbol{x}_i), \boldsymbol{\beta}) p(\boldsymbol{W}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2) d\boldsymbol{W} \tag{23}$$

$$= \frac{1}{p(\mathcal{D}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)} \nabla_{\boldsymbol{\alpha}} \int \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \boldsymbol{\epsilon}}(\boldsymbol{x}_i), \boldsymbol{\beta}) p(\boldsymbol{\epsilon}) d\boldsymbol{\epsilon} \tag{24}$$

$$= \frac{1}{p(\mathcal{D}|\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2)} \int p(\boldsymbol{\epsilon}) \nabla_{\boldsymbol{\alpha}} \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu}_{\boldsymbol{\alpha}}, \boldsymbol{\sigma}_{\boldsymbol{\alpha}}^2, \boldsymbol{\epsilon}}(\boldsymbol{x}_i), \boldsymbol{\beta}) d\boldsymbol{\epsilon} \tag{25}$$

$$= \frac{1}{p(\mathcal{D}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})} \int p(\boldsymbol{\epsilon}) \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) \nabla_{\boldsymbol{\alpha}} \log \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) d\boldsymbol{\epsilon} \qquad (26)$$

$$= \frac{1}{p(\mathcal{D}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})} \int p(\boldsymbol{\epsilon}) \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) \nabla_{\boldsymbol{\alpha}} \sum_{i=1}^{N} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) d\boldsymbol{\epsilon} \qquad (27)$$

$$= \int \frac{p(\boldsymbol{\epsilon}) \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i))}{p(\mathcal{D}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) d\boldsymbol{\epsilon} \qquad (28)$$

$$= \mathbb{E}_{p(\boldsymbol{\epsilon}|\mathcal{D},\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) \qquad (29)$$

Following the same derivations for $\nabla_{\boldsymbol{\beta}}$ yields

$$\nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2}) = \mathbb{E}_{p(\boldsymbol{\epsilon}|\mathcal{D},\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\beta}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta}) \qquad (30)$$

as $p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}}(\boldsymbol{x}_i),\boldsymbol{\beta})$ depends on both $\boldsymbol{\alpha}$ and $\boldsymbol{\beta}$. ∎

Details of the algorithm. The gradients used to estimate prior parameters $\boldsymbol{\alpha}, \boldsymbol{\beta}$ (excluding subsampling data set $\mathcal{D}$ and hyperprior gradient $\nabla \log p(\boldsymbol{\alpha},\boldsymbol{\beta})$):

$$\nabla_{\boldsymbol{\alpha}} \log p(\mathcal{D}|\boldsymbol{\alpha},\boldsymbol{\beta}) \approx \frac{w(\boldsymbol{\epsilon}^{(s)})}{\sum_{j=1}^{S} w(\boldsymbol{\epsilon}^{(j)})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\alpha}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}^{(s)}}(\boldsymbol{x}_i)), \ \boldsymbol{\epsilon}^{(s)} \sim q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}), \quad (31)$$

$$\nabla_{\boldsymbol{\beta}} \log p(\mathcal{D}|\boldsymbol{\alpha},\boldsymbol{\beta}) \approx \frac{w(\boldsymbol{\epsilon}^{(s)})}{\sum_{j=1}^{S} w(\boldsymbol{\epsilon}^{(j)})} \sum_{i=1}^{N} \nabla_{\boldsymbol{\beta}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}^{(s)}}(\boldsymbol{x}_i)), \ \boldsymbol{\epsilon}^{(s)} \sim q(\boldsymbol{\epsilon}|\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}), \quad (32)$$

$$(33)$$

$w(\boldsymbol{\epsilon}^{(s)}) = \prod_{i=1}^{N} p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\epsilon}},\boldsymbol{\beta})p(\boldsymbol{\epsilon})/q(\boldsymbol{\epsilon})$. The updates for auxiliary parameters $\boldsymbol{\mu_\epsilon}$ and $\boldsymbol{\sigma_\epsilon^2}$:

$$\nabla_{\boldsymbol{\mu_\epsilon}} \mathcal{L}(\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}) \approx \sum_{i=1}^{N} \mathbb{E}_{\boldsymbol{\epsilon}'} \nabla_{\boldsymbol{\mu_\epsilon}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\mu_\epsilon}+\boldsymbol{\sigma_\epsilon}\boldsymbol{\epsilon}'}(\boldsymbol{x}_i)) - \nabla_{\boldsymbol{\mu_\epsilon}} \sum_{l=1}^{L} D_{KL}\big(q(\boldsymbol{\epsilon}_l|\boldsymbol{\mu}_{\boldsymbol{\epsilon}_l},\boldsymbol{\sigma}_{\boldsymbol{\epsilon}_l}^2)||\mathcal{N}(\boldsymbol{\epsilon}_l|\boldsymbol{0},\boldsymbol{I})\big),$$
$$(34)$$

$$\nabla_{\boldsymbol{\sigma_\epsilon^2}} \mathcal{L}(\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}) \approx \sum_{i=1}^{N} \mathbb{E}_{\boldsymbol{\epsilon}'} \nabla_{\boldsymbol{\sigma_\epsilon^2}} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\mu_\epsilon}+\boldsymbol{\sigma_\epsilon}\boldsymbol{\epsilon}'}(\boldsymbol{x}_i)) - \nabla_{\boldsymbol{\sigma_\epsilon^2}} \sum_{l=1}^{L} D_{KL}\big(q(\boldsymbol{\epsilon}_l|\boldsymbol{\mu}_{\boldsymbol{\epsilon}_l},\boldsymbol{\sigma}_{\boldsymbol{\epsilon}_l}^2)||\mathcal{N}(\boldsymbol{\epsilon}_l|\boldsymbol{0},\boldsymbol{I})\big).$$
$$(35)$$

Approximate scheme using one objective. Approximating weights with uniform distribution $w(\boldsymbol{\epsilon}^{(s)}) = \frac{1}{S}$ can be used to formulate the objective that can be used to learn both $\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2}$ and $\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2}$:

$$\tilde{\mathcal{L}}_1(\boldsymbol{\mu_\epsilon},\boldsymbol{\sigma_\epsilon^2},\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2}) \approx$$
$$\sum_{i=1}^{N} \mathbb{E}_{\boldsymbol{\epsilon}'} \log p(\boldsymbol{y}_i|g_{\boldsymbol{\mu_\alpha},\boldsymbol{\sigma_\alpha^2},\boldsymbol{\mu_\epsilon}+\boldsymbol{\sigma_\epsilon}\boldsymbol{\epsilon}'}(\boldsymbol{x}_i)) - \sum_{l=1}^{L} D_{KL}\big(q(\boldsymbol{\epsilon}_l|\boldsymbol{\mu}_{\boldsymbol{\epsilon}_l},\boldsymbol{\sigma}_{\boldsymbol{\epsilon}_l}^2)||\mathcal{N}(\boldsymbol{\epsilon}_l|\boldsymbol{0},\boldsymbol{I})\big) + \log p(\boldsymbol{\alpha},\boldsymbol{\beta}). \quad (36)$$

Alternatively, an approximation

$$\hat{I}(\tilde{\mathcal{L}}_2(\boldsymbol{\mu_\epsilon}, \boldsymbol{\sigma_\epsilon^2}, \boldsymbol{\mu_\alpha}, \boldsymbol{\sigma_\alpha^2})) =$$

$$\sum_{i=1}^{N} \frac{w(\boldsymbol{\epsilon}^{(s)})}{\sum_{j=1}^{S} w(\boldsymbol{\epsilon}^{(j)})} \log p(\boldsymbol{y}_i | g_{\boldsymbol{\mu_\alpha}, \boldsymbol{\sigma_\alpha^2}, \boldsymbol{\epsilon}^{(s)}}(\boldsymbol{x}_i)) - \sum_{l=1}^{L} D_{KL}\big(q(\boldsymbol{\epsilon}_l | \boldsymbol{\mu_{\epsilon_l}}, \boldsymbol{\sigma_{\epsilon_l}^2}) || \mathcal{N}(\boldsymbol{\epsilon}_l | \boldsymbol{0}, \boldsymbol{I})\big) + \log p(\boldsymbol{\alpha}, \boldsymbol{\beta}),$$

$$(37)$$

where $\boldsymbol{\epsilon}^{(s)} \sim q(\boldsymbol{\epsilon} | \boldsymbol{\mu_\epsilon}, \boldsymbol{\sigma_\epsilon^2})$ can be used, where $\hat{I}$ denotes estimator.