Evaluating the Adversarial Robustness of CNNs Layer by Layer

Abstract

In order to measure the adversarial robustness of a feature extractor, Bhagoji et al. introduced a distance on example spaces measuring the minimum perturbation of a pair of examples to achieve identical feature extractor outputs. They related these distances to the best possible robust accuracy of any classifier using the feature extractor. By viewing initial layers of a neural network as a feature extractor, this provides a method of attributing adversarial vulnerability of the classifier as a whole to individual layers. However, this framework views any injective feature extractor as perfectly robust: any bad choices of feature representation can be undone by later layers. Thus the framework attributes all adversarial vulnerabilities to the layers that perform dimensionality reduction. Feature spaces at intermediate layers of convolutional neural networks are generally much larger than input spaces, so this methodology provides no information about the contributions of individual layers to the overall robustness of the network. We extend the framework to evaluate feature extractors with high-dimensional output spaces by composing them with a random linear projection to a lower dimensional space. This results in non-trivial information about the quality of the feature space representations for building an adversarial robust classifier.

1 Introduction

Over the last several years, a line of work has characterized the optimal adversarial loss achievable for a particular data distribution and adversarial constraint specification Bhagoji et al. (2019; 2021); Pydi & Jog (2020); Trillos et al. (2023); Dai et al. (2023). These works characterize the problem of minimizing adversarial loss over all possible classifier functions to some kind of optimal transport problem on the class conditional distributions. In order to set up this problem, one needs the distance structure of the data distribution with regard to the distance appearing in the adversarial constraint. These characterizations of optimal loss provide a lower bound for loss achievable using a particular architecture and a benchmark performance level that a trained classifier can be compared to. At a higher level, they provide an objective method to determine whether a given adversarial constraint is reasonable to use with a particular dataset.

More recently, this method has been extended to analyze the robustness of a feature extractor, or equivalently the initial layers of a feed-forward network Bhagoji et al. (2023). Just as the minimum loss on a data distribution is a minimization over all possible classifiers, the robustness of a feature extractor is a minimization over all classifiers using that feature extractor. The robustness of a feature extractor can be computed via a characterization that uses the distance structure of the data distribution using a specially defined distance that takes into account the behavior of the feature extractor. This allows the adversarial loss of the model to be decomposed layer-by-layer: including a layer of the model in the feature extractor decreases the size of the class of models using that feature extractor and thus increases the minimum loss. This increase can be considered the contribution of that layer to the overall adversarial loss of the model.

Unfortunately, for wide models, the decomposition tends to be uninformative. Layers are assigned none of the adversarial loss until dimensionality reduction to below the input space dimension occurs. Since the development of CNNs, state of the art architectures have used huge feature spaces. Dimensionality reduction has to occur eventually, but this methodology often results in the attribution of all the loss to the final layer.

In this paper, we propose a variation on the feature extractor distance tailored to wide networks, or equivalently feature extractors with high dimension feature spaces. We explore basic properties of this feature extractor distance and propose and implement an algorithm to approximately compute it for ReLU CNNs feature extractors. We use the algorithm to perform some intial exploration in the into the effects of architectural and training method decisions on layaer-by-layer robustness.

As pre-trained models and the transfer learning paradigm are more widely used, analysis of these models as feature extractors rather than fully specified classifiers become more and more relevant. We illustrate the potential feasibility of the layer-by-layer approach to this task.

At this point, adversarial examples have been known to be a serious problem in neural network for over a decade Szegedy et al. (2013); Goodfellow et al. (2015). Adversarial training has succeeded at mitigating this vulnerability to an extent, but is computationally expensive and does not achieve information-theoretic limits on adversarial robustness Bhagoji et al. (2021). Certified methods give stronger guarantees, but are usually even more computationally expensive and limited in the scale of the adversarial budget.

We would like to provide new analysis tools to enable continued progress on training adversarially robust models. With these tools, we can better identify different behaviors in models as training method is varied. By localizing adversarial vulnerabilities within a model, we allow computational resources to be spent efficiently.

Contributions   We introduce a novel collision search algorithm applicable to any feature extractor. We provide a theoretical framework for understanding the robustness of feature extractors. We utilize random projections to transform feature extractors with high-dimensional feature spaces and only trivial input collisions to representative low-dimensional versions whose robustness can be efficiently analyzed. From our experiments, we find that different training methods produce significant variation in layer-by-layer robustness.

2   Framework

We consider the following adversarial classification scenario. There is an example space $\mathcal{X} = \mathbb{R}^{n_0}$ equipped with a a distance metric d and a label space $\mathcal{Y} = \{0, 1, \ldots, k-1\}$. A labeled example (x, y) is sampled from a distribution P over $\mathcal{X} \times \mathcal{Y}$. An adversary selects a point $\tilde{x} \in \mathcal{X}$ such that $d(x, \tilde{x}) \leq \varepsilon$. The classifier receives $\tilde{x}$, uses a classifer h to produces a probability vector $h(\tilde{x}) \in \mathbb{P}(\mathcal{Y})$, and incurs loss $\ell(h(\tilde{x}), y)$. The expected adversarial loss of h is $\widetilde{L}(\varepsilon, P, h) = E_{(x,y) \sim P}[\sup_{\tilde{x}:d(x,\tilde{x}) \leq \varepsilon} \ell(h(\tilde{x}), y)]$.

Lower Bounds on Adversarial Loss   We briefly summarize the characterization of optimal adversarial cross entropy loss for a two-class discrete data distribution Bhagoji et al. (2021).

The distance structure of the data can be summarized in a bipartite *conflict graph* $(\mathcal{V}, \mathcal{E}_\varepsilon)$ in which, the vertices $\mathcal{V}$ represent labeled examples, and the edges $\mathcal{E}_\varepsilon$ indicate the presence of intersections under a given attack budget ϵ. When such an intersection exists, it signifies a fundamental limitation: no classifier can correctly classify both points in the adversarial setting. In the graph the left vertices are examples from class zero, the right vertices are examples from class one, and an edge (x, x') is present when $d(x, x') \leq 2\varepsilon$. The polytope $\mathcal{P}_\epsilon \subset \mathbb{R}^V$ is defined by the following inequalities:

$$0 \leq q_v \leq 1, v \in \mathcal{V} \tag{1}$$

$$q_v + q_{v'} \leq 1, (v, v') \in \mathcal{E}_\varepsilon. \tag{2}$$

For a labeled example (x, y) and soft classifier $h : \mathcal{X} \to \mathbb{P}(\mathcal{Y})$, $h(x)_y$ is the probability that h assigns to the correct class. Bhagoji et al. show that there is an h such that $\inf_{\tilde{x}:d(x,\tilde{x}) \leq \varepsilon} h(x)_y \geq q_{(x,y)}$ for each labeled example (x, y) in the support of the data distribution if and only if $q \in \mathcal{P}_\varepsilon$. Thus $\mathcal{P}_\epsilon$ is the space of achievable correct-classification-probability vectors.

Using this characterization of the correct classification vectors, we obtain a convex optimization problem for the minimum adversarial loss:

$$\min_h \widetilde{L}(\varepsilon, P, h) = \min_{q \in \mathcal{P}_\varepsilon} \sum_{v \in \mathcal{V}} p_v \log \frac{1}{q_v}.$$

The optimal loss represents the lower bound on the loss that any possible classifier can achieve when attempting to correctly classify an adversarial example under the current perturbation.

2.1 A Previous Approach to Feature Extractor Robustness

This analysis has been extended to multi-layer classifiers. Consider a classifier $h : \mathbb{R}^{n_0} \to \mathbb{P}(\mathcal{Y})$ that is the composition of ℓ layers: $h = \text{softmax} \circ h_\ell \circ h_{\ell-1} \circ \ldots \circ h_1$, where $h_i : \mathbb{R}^{n_{i-1}} \to \mathbb{R}^{n_i}$ and $n_\ell = k = |\mathcal{Y}|$. We can consider its initial j layers $f_j : R^{n_0} \to \mathbb{R}^{n_j}$, $f_j = h_j \circ \ldots \circ h_1$ as a *feature extractor*. The key idea of Bhagoji et al. is to evaluate any feature extractor f via the set of all classifiers that use f as their initial layers: $\mathcal{H}_f = \{g \circ f \text{ such that } g : \mathbb{R}^{n_j} \to \mathbb{P}(\mathcal{Y})\}$ Bhagoji et al. (2023). To measure the adversarial robustness of f, they consider the best achievable adversarial loss over this family: $\widetilde{L}^*(\varepsilon, P, f) = \inf_{h \in \mathcal{H}_f} \widetilde{L}(\varepsilon, P, h)$.

This definition has some nice properties. As more layers are considered to be part of the feature extractor, the robustness can only decrease because $\mathcal{H}_{g \circ f} \subseteq \mathcal{H}_f$. The set of all classifiers is $\mathcal{H}_{\text{id}}$, so the identity feature extractor has perfect robustness, i.e. no reduction from input space loss lower bound.

However, there is a key weakness to the definition: *any* injective feature extractor achieves perfect adversarial robustness. A feature extractor $f : \mathbb{R}^{n_0} \to \mathbb{R}^{n_j}$ will typically be injective or close enough to only introduce a negligible amount of loss. By this definition, only feature extractors that perform significant dimensionality reduction typical cause loss of robustness.

Colliding adversarial examples   Let f be a feature extractor and let (x, y) and (x', y') be labeled example from different classes ($y \neq y'$). A pair of colliding adversarial examples are produced when the adversarial perturbations cause the examples to be mapped to the same point in the feature space, thereby guaranteeing a classification error for at least one example: $\tilde{x}$ and $\tilde{x}'$ satisfy $d(x, \tilde{x}) \leq \epsilon$, $d(x, \tilde{x}) \leq \epsilon$, and $f(\tilde{x}) = f(\tilde{x}')$.

Feature Layer Distances   When the data distribution is discrete, Bhagoji et al. show that $\widetilde{L}^*(\varepsilon, P, f)$ can be characterized similarly to if the appropriate notion of distance between examples is used. In particualar,

$$\widetilde{L}^*(\varepsilon, P, f) = \inf_{h \in \mathcal{H}_f} \widetilde{L}(\varepsilon, P, h) = \min_{q \in \mathcal{P}_{f,\varepsilon}} \sum_{v \in V} p_v \log \frac{1}{q_v}.$$

where $\mathcal{P}_{f,\varepsilon}$ is defined analogously to $\mathcal{P}_\varepsilon$ in equation 2, but using the distance

$$d_f(x, x') = \inf_{\tilde{x}, \tilde{x}' : f(\tilde{x}) = f(\tilde{x}')} \max(d(x, \tilde{x}), d(x', \tilde{x}')).$$

This is the minimum adversarial budget required to find inputs that collide in the feature space. This distance (which is not a metric in general) can be used in place of the input distance d to build a conflict graph and characterize optimal adversarial loss over $\mathcal{H}_f$. Then $\mathcal{E}_{f,\epsilon} = \{(x, x') : d_f(x, x') \leq \varepsilon\}$ is the edge set of the conflict graph for d_f.

2.2 Feature Layer Distances for High-dimensional Features

To evaluate a feature extractor $f : \mathbb{R}^{n_0} \to \mathbb{R}^{n_j}$, we consider $\widetilde{L}^*(\varepsilon, P, a \circ f)$, where $a : \mathbb{R}^{n_j} \to \mathbb{R}^m$ is a random linear function: $a(x) = Ax$, $A \in \mathbb{R}^{m \times n_j}$ is a matrix with i.i.d. standard Gaussian entries.

Note that because a is a random function, $d_{a \circ f}(x, x')$ and $\widetilde{L}^*(\varepsilon, P, a \circ f)$ are random variables.

Discussion   An injective feature extractor does not commit to any aspect of the behavior of the classifier using it: subsequent layers of the classifier could invert it. However, a feature extractor causes some classifiers extending it to have simpler representations than others. We would like to measure the robustness of a "typical" classifier extending f and we use the composition of a random dimension-reducing linear function with f as a proxy for this that is computationally tractable to analyze.

The random linear function is comparable to an randomly initialized but untrained classifier network using the features.

3 Properties of the Robustness Measure

In this section, we discuss key properties of the feature extractor distance $d_{a \circ f}$ and the robustness measure $\widetilde{L}^*(\varepsilon, P, a \circ f)$.

Invariance of d_f to scaling of f or a   For any $c \neq 0$, $\widetilde{L}^*(\varepsilon, P, cf) = \widetilde{L}^*(\varepsilon, P, f)$. A collision $Af(\tilde{x}) = Af(\tilde{x}')$ for random linear layer A is still a collision after scaling by a constant. This also means that the scale of the distribution of A does not affect our definitions.

Rotation invariance   The distribution of random linear maps is rotation invariant, so any rotation of the feature space leaves all distances unchanged. When $m \leq n_j$, the random matrix A has rank m with probability one. It has singular value decomposition $A = U\Sigma V^T$, where $V \in \mathbb{R}^{n_j \times m}$ and $U \in \mathbb{R}^{m \times m}$ are orthogonal and $\Sigma \in \mathbb{R}^{m \times m}$ is diagonal and invertible. Then $U\Sigma V^T f(\tilde{x}) = U\Sigma V^T f(\tilde{x}')$ if and only if $V^T f(\tilde{x}) = V^T f(\tilde{x}')$. Thus using i.i.d. Gaussian matrices results in the same distance as a uniform distribution over orthogonal projections to a dimension-d subspace.

Invertible function non-invariance   On the other hand, applying generic invertible linear transformation b to the feature space $\mathbb{R}^{n_j}$ *does* affect the distribution of the distance: it is not true that $\widetilde{L}^*(\varepsilon, P, b \circ f) = \widetilde{L}^*(\varepsilon, P, f)$. Applying the linear transformation to $f(x)$ is equivalent to applying the inverse to the random matrix A, which changes its distribution. All linear maps still appear, but with skewed densities.

3.1 Adding, removing, rescaling features

This means that while d_f does not depend on the absolute scaling of features, it does depend on the relative scaling. It is easier for the adversary to satisfy $Af(\tilde{x}) = Af(\tilde{x}')$ by modifying the examples in ways that change large magnitude features.

If we modify a feature extractor f to add an additional feature, giving f', this could increase the distance between x and x' or decrease it. Adding a constant feature leaves the distance unchanged.

Specializing to ℓ_2   In the remainder of this section and in our experiments, we use ℓ_2 distance as our input space distance.

3.2 Linear Feature Extractors

Suppose that f is affine linear, so $f(x) = Hx + k$. Suppose that $\text{rank}(H) = r$, the singular value decomposition of H is $H = U\Sigma V^T$ where $\Sigma \in \mathbb{R}^{r \times r}$. Then Bhagoji et al. observe that the optimal adversarial examples are $\tilde{x} = x + \delta$ and $\tilde{x}' = x' - \delta$ where $\delta = \frac{1}{2}VV^T(x - x')$. The perturbation is the projection of half the difference of examples onto the orthogonal complement of the nullspace of H: the adversary should not allocate any of their budget to moving within the level sets of f. Thus $d_f(x, x')$ is $\frac{1}{2}\|V^T(x - x')\|$. The left part of Figure 1 illustrates this.

Proposition 1 (Informal version). *Let $f(x) = ALx$, where $L \in \mathbb{R}^{n_1 \times n_0}$ is a fixed linear feature extractor and the entries of $A \in \mathbb{R}^{m \times n_1}$ are i.i.d. standard Gaussian. Let $r_4 = \frac{\|L\|_4^4}{\|L\|^4}$, where $\|L\|_4$ is a Schatten p-norm and $\|L\|$ is the ℓ_2 operator norm. Then r_4 is a variation of stable rank for L.*

If $1 \ll m \ll \sqrt{r_4}$, then $d_f(x, x')$ concentrates tightly around $\frac{\sqrt{m}\|L(x-x')\|}{2\|L\|_F}$.

Precise statement and proof are in Appendix C. Note that $\|L(x - x')\|$ is just the distance between the feature representations of x and x'. If we were only interested in linear layers, computing $d_{a \circ h}$ would not be justified: $\|L(x - x')\|$ and $\|L\|_F$ are much more straightforward to compute, and not random! However, these norms do not obviously generalize to a nonlinear h, which would have different linear approximations at different points in the input space, while $d_{a \circ h}$ does still make sense. When evaluating nonlinear h, we would still like to pick m so that $d_{a \circ h}$ concentrates so that we can efficiently and accurately estimate it by sampling.

Figure 1: Visualization of $d_f(x, x')$ for two feature extractors $f : \mathbb{R}^2 \to \mathbb{R}^1$, one linear and one piecewise-linear. Blue lines are level sets of f. Each of the balls has radius $d_f(x, x')$. The level set of the colliding adversarial examples is highlighted. These are not classifiers and the highlighted line is not a decision boundary. When the feature space is more than one dimension smaller than the input space, level sets do not disconnect the input space.

Input space calculation The special case of $d_a(x, x')$ for a random linear function a is more intuitive. This corresponds to $L = I \in \mathbb{R}^{n_0 \times n_0}$ and $\|L\|_F = n_0$. The orthogonal complement of the nullspace of $A \in \mathbb{R}^{m \times n_0}$ is a uniformly distributed dimension-m subspace. So $d_a(x, x')^2$ has mean $\frac{m}{4n_0}\|x - x'\|_2^2$ and $d_a(x, x')$ concentrates around $\frac{\sqrt{m}}{2\sqrt{n_0}}\|x - x'\|_2$ when m is large enough.

Figure 2: Random non-linear level sets for compositions of a random linear function with good and bad feature extractors. The lines represent the level sets of a random linear function composed with the feature extractor. The bad feature extractor contains all of the features in the good extractor plus many more. Most of these are low quality so a random linear combination has low robustness.

3.3 Relationship between distances at different layers

Now we compare $d_{a \circ f_j}(x, x')$ and $d_{a \circ f_{j+1}}(x, x')$. As we noted before, $d_{f_j}(x, x') \geq d_{f_{j+1}}(x, x')$: adding an additional layer can only decrease distances by introducing new collisions between inputs. In contrast, $d_{a \circ f_{j+1}}$ could be either larger or smaller than $d_{a \circ f_j}$. Including an additional layer h_{j+1} to the feature extractor introduces new possibilities for collisions, which reduces robustness, but it also reweights the existing feature

information in a way that may reduce the effect of weak features. Figure 4 presents paired adversarial examples identified for the 7-layer model. We observe that as the feature extractor becomes deeper, the average adversarial distance $d_{a \circ f_i}(x, x')$ increases as well.

3.4 Varying the output dimension of the random projection

As we vary the output dimension m of the random linear function, the distance $d_{a \circ f}$ reveal different information about the structure of the feature space representation. At one extreme, if $m \geq n_j$, then the linear map a is injective with probability one and $d_f(x, x') = d_{a \circ f}(x, x')$. If $m = 1$, we roughly learn how much of the feature representation is usable by a linear classifier. By using a single fixed m to analyze multiple layers with different feature space dimensions n_i, we eliminate some the effects of this dimension variation on measured robustness. For most of our experiments, we use $m = 10$ to facilitate comparison with the logits.

4 Algorithm for approximating feature-layer distances

When we use ℓ_2 distance to constrain our adversary, for $f : \mathbb{R}^{n_0} \to \mathbb{R}^d$, $d_f(x, x')$ becomes

$$\min_{\tilde{x}, \tilde{x}'} \|\tilde{x} - x\|_2^2 + \|\tilde{x}' - x'\|_2^2 \quad \text{subject to} \quad f(\tilde{x}) = f(\tilde{x}')$$

This is a slight relaxation: to get a smoother problem we have replaced the original objective $\max(\|\tilde{x} - x\|_2, \|\tilde{x}' - x'\|_2)$ with the sum of squares. Now we present the algorithm that we use to approximately solve this optimization problem.

Our algorithm is related to a method used to compute distance from an example to the decision boundary of a classifer. The linear approximated decision hyperplane is used in DeepFool Moosavi-Dezfooli et al. (2016), and the FAB attack paper Croce & Hein (2020) employs convex combinations to make the solution closer to the original point.

Algorithm 1 Collision Search Algorithm

Require: Original points x, x'; initial step $\alpha \in (0, 1)$; decay rate $\gamma \in (0, 1)$; maximum number of iteration $N_{\max}$; convergence threshold ϵ.

1: Initialize $\tilde{x}^{(0)} = (x + x')/2$, $\tilde{x}'^{(0)} = (x + x')/2$, $i = 0$.
2: **for** $i = 0 \ldots N_{\max} - 1$ **do**
3:     Compute Jacobians, build collision subspace:

$$\mathcal{H}_i = \{ (\tilde{x}, \tilde{x}') \in \mathbb{R}^{2n_0} : f(\tilde{x}'^{(i)}) - f(\tilde{x}^{(i)}) + Df(\tilde{x}'^{(i)})(\tilde{x}' - \tilde{x}'^{(i)}) - Df(\tilde{x}^{(i)})(\tilde{x} - \tilde{x}^{(i)}) = 0 \}$$

4:     Convex combination and projection:

$$(\tilde{x}^{(i+1)}, \tilde{x}'^{(i+1)}) = \text{proj}\left((1 - \alpha^{(i)})(\tilde{x}^{(i)}, \tilde{x}'^{(i)}) + \alpha^{(i)}(x, x'), \mathcal{H}_i\right)$$

5:     Break if converged:

$$\left\|f(\tilde{x}'^{(i+1)}) - f(\tilde{x}^{(i+1)})\right\| < \epsilon \quad \text{and} \quad (\|\tilde{x}^{(i)} - x\|_2^2 + \|\tilde{x}'^{(i)} - x'\|_2^2) - (\|\tilde{x}^{(i+1)} - x\|_2^2 + \|\tilde{x}'^{(i+1)} - x'\|_2^2) < \epsilon$$

6:     $\alpha^{(i+1)} = \alpha^{(i)} \times \gamma$.
7: **end for**
8: **Return** colliding adversarial examples $\tilde{x}^{(i+1)}$, $\tilde{x}'^{(i+1)}$.

The algorithm can be viewed as an approximate version of projected gradient descent. Because f is a nonconvex piecewise-linear function, it is intractable to project onto the true constraint set $f(\tilde{x}) = f(\tilde{x}')$. Instead, we locally approximate the constraint set as an affine subspace. The derivative of $(\tilde{x}, \tilde{x}') \mapsto f(\tilde{x}) - f(\tilde{x}')$ at $(\tilde{x}, \tilde{x}')$ is the matrix $\left(Df(\tilde{x}) \quad -Df(\tilde{x}')\right) \in \mathbb{R}^{m \times 2n_0}$, where D represents the Jacobian matrix of the gradient. The affine subspace on which the linear approximation is zero has dimension at least $2n_0 - m$. In contrast to

(a) First two steps. Initialize at (x_0, x'_0) and project orthogonally onto the first linearized collision subspace H_0 to obtain $(\tilde{x}^{(1)}, \tilde{x}'^{(1)})$. Relinearize to form H_1 and project again to get $(\tilde{x}^{(2)}, \tilde{x}'^{(2)})$. Red markers indicate the feet of the projections.

(b) Convergence of the linearize–project scheme. The true collision set $\mathcal{C}$ is curved. At iteration i, we linearize at $(\tilde{x}^{(i)}, \tilde{x}'^{(i)})$ to obtain the affine subspace H_i and convex combination with (x, x') project to $(\tilde{x}^{(i+1)}, \tilde{x}'^{(i+1)})$. The iterates approach the low point $(\tilde{x}^\star, \tilde{x}'^\star)$ on $\mathcal{C}$; $H^\star$ denotes the limiting linearization at the solution.

Figure 3: Geometry of our linearize–project algorithm on the collision manifold: (a) initialization and the first two projections; (b) iterative convergence toward the optimal point on the true collision set.

related algorithms to compute minimum distance to the classification boundary, the subspace usually has codimension greater than one. i.e. is not a hyperplane. Thus projection onto the subspace requires us to solve a linear system and it is preferable to choose m to be not too large. Details are shown in Appendix A.

We know that $\tilde{x} = \tilde{x}'$ implies $f(\tilde{x}) = f(\tilde{x}')$, so we initialize $\tilde{x}$ and $\tilde{x}'$ by minimizing the objective subject to this constraint. Thus we set $\tilde{x}^{(0)} = \tilde{x}'^{(0)} = (x + x')/2$, the midpoint of the original examples. We found that starting with points satisfying the collision condition worked much better than any algorithm initialized at the original examples ($\tilde{x}^{(0)} = x$ and $\tilde{x}'^{(0)} = x'$).

4.1 Convex Combination Projection

We address the NP-hard collision-search problem Katz et al. (2017) via a simple iterative method that alternates between convex combination and projection onto a locally linearized subspace. At iteration i, this subspace is $\mathcal{H}_i$. If the subspace were the true collision manifold, then the minimizer would be $\text{proj}((x, x'), \mathcal{H}_i)$. However, $\mathcal{H}_i$ is only an accurate approximation locally, so we improve the objective by mixing the projection of the current estimate $(\tilde{x}^{(i)}, \tilde{x}'^{(i)})$ with the projection of original point (x, x'):

$$(\tilde{x}^{(i+1)}, \tilde{x}'^{(i+1)}) = (1 - \alpha^{(i)}) \, \text{proj}\left((\tilde{x}^{(i)}, \tilde{x}'^{(i)}), \mathcal{H}_i\right) + \alpha^{(i)} \, \text{proj}\left((x, x'), \mathcal{H}_i\right)$$
$$= \text{proj}\left((1 - \alpha^{(i)})(\tilde{x}^{(i)}, \tilde{x}'^{(i)}) + \alpha^{(i)}(x, x'), \mathcal{H}_i\right)$$

The second expression for the iterate holds because the projection is affine. Using this saves computation by performing the convex combination first.

Since the midpoint $\frac{1}{2}(x + x')$ is itself a perfect collision in function space, we initialize our search there and compute its Jacobian to define the first affine subspace. In the very first projection step, we set $\alpha^{(0)} = 1$, so that $\tilde{x}^{(1)} = \text{proj}(x, \mathcal{H}_0)$, using both original points to project onto $\mathcal{H}_0$. Thereafter, we gradually reduce $\alpha^{(i)}$ to introduce bias toward the original point x. This diminishing bias keeps every iterate within a controlled neighborhood of a feasible input, preventing large jumps that might violate constraints or break the validity of the local linear approximation. Figure 3 shows the convex-combination and projection operation in first two step as well as the convergent case in which the initial point x exactly projects to the current iteration point $\tilde{x}^{(i)}$.

The algorithm proposed in Bhagoji et al. (2023) is tailored to ReLU networks: it greedily searches ReLU activation patterns to formulate a sequence of linear programs. However, as network depth increases or when non-ReLU activations are used, this combinatorial approach becomes intractable. In contrast, our Jacobian-subspace method sidesteps these limitations by relying solely on gradient information. By constructing an affine subspace from the model's local Jacobians, we can handle arbitrary activation functions and deep architectures efficiently and keep the result accuracy the same time.

Figure 4: Colliding adversarial examples and their ℓ_2 perturbation distance for one pair across different layers.

5 Experiments

In this section, we test several theories and evaluate the robustness of convolutional models layer by layer on the MNISTLeCun et al. (1998) and CIFAR-10Krizhevsky & Hinton (2009) datasets. Since MNIST is a relatively simple dataset, it allows us to easily explore robustness properties. And the MNIST dataset highlights a larger robustness gap between layers and provides a range of ϵ values for testing. For our baseline, we use an adversarially trained model on MNIST with projected gradient descent (PGD)Madry et al. (2017) and set perturbation budget $\epsilon = 2$. To design the experiment, we selected 100 examples from two class in the training dataset for evaluation.

Algorithm 2 Optimal Loss Calculation via Conflict Graph

1: Choose feature extractor $f_j : \mathbb{R}^n \to \mathbb{R}^{n_j}$
2: Specify the number of random projections N, and projection dimension m
3: **for** $i = 1$ to N **do**
4:     Generate random projection matrix $A_i \in \mathbb{R}^{m \times n_j}$, with elements drawn i.i.d. from $\mathcal{N}(0, 1)$
5:     Build new feature extractor $(a_i \circ f_j)(x) = A_i f_j(x')$
6:     **for** example pairs (x, x') **do**
7:         Approximate $d_{a_i \circ f_j}(x, x')$ using Algorithm 1,
8:     **end for**
9:     **for** $\varepsilon = \varepsilon_{\min} \ldots \varepsilon_{\max}$ **do**
10:         Build conflict graph graph (V, E_ε), where:
11:         V is the set of data, $x, x' \in V$
12:         $E_\varepsilon = \{(x, x') : d_{a_i \circ f_j}(x, x') \le \varepsilon\}$
13:         Find $L_{\text{opt}}(\varepsilon)$ using Algorithm B
14:     **end for**
15: **end for**
16: **Return** List of averaged optimal losses L_{opt}

For the selection of CNN models, we trained three different architectures, following the work in Gowal et al. (2019), where all layers utilize ReLU activation functions. We employed two robust training methods: PGD adversarial training, and TRADES adversarial training Zhang et al. (2019). Each of these methods was

applied with robustness constraints based on the l_2 norm. For all models, we used a cosine learning rate schedule Loshchilov & Hutter (2016) with an initial learning rate set to 0.01 to ensure consistency across training approaches.

Optimal Loss We use optimal loss $\widetilde{L}^*(\varepsilon, P, a \circ f)$ defined in Section 2.1 to represent the robustness of the feature extractor. Recall that higher loss represent lower robustness performance. Algorithm 2 computes the optimal loss using a conflict graph–based procedure. The process begins by selecting a feature extractor and generating a sequence of random matrices with i.i.d. Gaussian entries. Each random matrix A_i is combined with the feature extractor f_j to create a lower-dimensional feature mapping $x \mapsto A_i f_j(x)$, making the representation suitable for robustness analysis. The algorithm then evaluates all example pairs to estimate pairwise distances and identifies collisions according to a perturbation-based threshold ε. These collisions define the edges of a conflict graph, where nodes represent examples and edges connect pairs within the specified perturbation distance. For each adversarial budget the algorithm invokes Algorithm B (corresponding to Algorithm 1 from Bhagoji et al. (2021)) to compute the optimal loss over the conflict graph. Finally, the results are averaged over multiple random matrices to produce the final optimal loss estimates.

5.1 Validating the robustness metric

To evaluate the true robustness loss on both the training and test datasets, we use FAB Attack as the benchmark for true adversarial performance, rather than relying on the standard training attack loss. When we calculate the distance based on all logits while FAB attack only consider the true label and attack target logit.

Figure 5: MNIST Medium CNN Model trained with PGD-2: FAB Attack Loss and Our Optimal Collision Loss.

Figure 6: CIFAR-10 Medium CNN Model trained with PGD-0.5: FAB Attack Loss and Our Optimal Collision Loss.

In our setup, the worst-case loss is $\log(2)$, indicating that even when collisions occur, we still have a 50% chance of classify them correctly. As shown in the figure 5 , when the value of ϵ increases, the true adversarial training loss rises, and our loss reaches its maximum value at $\log(2)$. While our loss provides more opportunities for the follower to correctly predict the adversarial examples, the true model plateaus at this point. Consequently, the loss from FAB attack remains consistently higher than ours. This gap represents an ideal model could do after the feature extractor based on our assumptions.

5.2 Varying the dimension of the projected features

Since the output dimension of the convolution is higher than the input, when no random projection is applied, the only collisions occur when the pairs are identical. Therefore, the distance between pairs reflects the exact input distance, as shown by the brown line in the figure 7. When projecting to a higher-dimensional space, we introduce less noise while preserving more useful feature information. As a result, the dimension increase, and the loss decreases.

The distances scale roughly with $\sqrt{m}$, but not exactly, which reflects the somewhat different information about feature structure accessed by different choices of m.

Figure 7: MNIST Medium CNN Model trained with PGD-2: First convolutional layer with different random projection dimensions. As $m \to 784$, the curves should approach the input optimal loss curve.

Figure 8: Medium CNN optimal loss using the method in Bhagoji et al. (2023).

5.3 Baseline layer-by-layer robustness results

When applying the method of Bhagoji et al. Bhagoji et al. (2023), the search algorithm cannot find any nontrivial collisions because none of the initial linear layers have an output dimension smaller than the example space dimension. The robustness measure for these initial layers remains essentially the same as at the input level. This is illustrated in 8. Layer dimensions for all models investigate are listed in Table 1 in Appendix B.

In Figures 9 and 10, we have baseline layer-by-layer results for MNIST and CIFAR10 respectively. As we more through the layers, robustness increases, suggesting that low-quality feature are being pruned. This effect is far outweighing any reductions in robustness due to the introduction of new opportunities for collisions as the feature dimension spaces decrease. Clearly, the dimensions of the feature spaces have a significant impact on the robustness measure, but they do not explain the curves by themselves. For both datasets, there is a relatively large improvement from layer one to layer two and from layer four to layer five. These layers perform dimensionality reduction by a factors of four and six, which are larger than reductions in adjacent layers. However, from layer six to the logits, we do not observe much robustness improvement despite dimensionality reduction from 512 to 10.

As we move through the layers, we observe that the optimal loss decreases, indicating that the model gradually learns more about the data's robustness, and the features become increasingly separable. Notably, there is a distinct gap between the convolutional layers and the fully connected layers. Additionally, the random projection appears to perform similarly to the learned matrix. The last few linear layers, however, seem to contribute little to the overall robustness.

5.4 Effects of architecture on layer-by-layer robustness

Figure 9: MNIST Medium CNN Model trained with PGD-2: All layers robustness.

Figure 10: CIFAR-10 Medium CNN Model trained with PGD-0.5: All layer robustness.

Figure 11: MNIST Small CNN Model trained with PGD-2: All layer robustness.

Figure 12: MNIST Large CNN Model trained with PGD-2: All layer robustness.

Figure 13: CIFAR-10 Large CNN Model trained with PGD-0.5: All layer robustness.

When comparing the layer-wise robustness of the small CNN in figure 11 and the Large CNN in figure 12 on MNIST, we observe that robustness does not change uniformly throughout the models. The same observation shows in robustness on CIFAR in figure 13. Although the small CNN exhibits lower overall robustness, its first convolutional layer appears to perform better, and its second layer achieves a similar level of robustness to that of the medium CNN.

5.5 Effects of training method on layer-by-layer robustness

Figure 14: MNIST Medium CNN Model with benign training: All layer robustness.

Figure 15: MNIST Medium CNN Model trained with TRADES-2: All layer robustness.

Figure 16: CIFAR-10 Medium CNN Model trained with TRADES-0.5: All layer robustness.

In Figures 14,15,16, we examine the medium CNN models trained with methods other than plain PGD. These can be compared to Figure 9. TRADES have layer-one robustness cliffs at lower adversarial budgets than PGD. Besides, TRADES achieves more separation between fully-connected layer curves and more gradual growth of those curves.

Relationship between intermediate layer robustness and test robust accuracy In Figures 17a and 17b, we see the test robust accuracy of the models. As expected, benign training achieves very limited robustness, TRADES significantly outperforms plain PGD. It is unclear to us whether the layer-one behavior of TRADES should be viewed as an undesirable side-effect that suggests room for improvement, or an indication that layer-one robustness curves are no appropriate objectives.

5.6 Conclusion

An interesting finding is that, for models exhibiting greater robustness under the norm-based attack, the optimal loss at the logit layer remains relatively low, which indicates high overall robustness, yet the first convolutional layer does not consistently follow this trend. In fact, this layer often learns less robust features even when the model as a whole is quite robust. This suggests that prioritizing the robustness of the first convolutional layer early in the training process is a potential avenue for improving a model's robustness.

At the same time, our experiments show that robustness does not grow uniformly across layers or blocks or depend in on feature space dimension a simple manner. Some adjacent layers have similar robustness, and robustness levels often stabilize before the final linear layer. Of course, this behavior varies with different datasets, training methods, and architectures.

(a) Test AutoAttack loss for the MNIST model above.

(b) Test AutoAttack loss for the CIFAR-10 model above.

Figure 17: Comparison of AutoAttack test loss for MNIST and CIFAR-10 models.

6 Related work

Compare with Bhagoji et al. (2023), our work introduces a novel collision search algorithm that can evaluate robustness for any feature extractor, regardless of the type of activation function used. This is achieved by leveraging gradient information, enabling the method to be widely applicable. Additionally, our use of random projection allows us to test feature extractors with high-dimensional outputs, providing a broader framework for robustness evaluation.

The robustness of middle layers in neural networks has been a growing focus in adversarial robustness research. Song et al. (2021) proposed a method to improve robustness by optimizing layer-wise quantization while bounding the Lipschitz constant of each layer, emphasizing how individual layers contribute to overall model robustness. Craig et al. (2023)introduced a framework for analyzing the information flow through subnetworks, providing theoretical bounds to evaluate the robustness contributions of specific layers or groups of layers. Zhou et al. (2022) explored robustness in Vision Transformers, attributing their resilience to grouping-based mid-level representations driven by self-attention mechanisms.

Our work builds on this foundation by introducing a novel collision-based robustness analysis specifically focused on middle layers. Unlike prior approaches that aim to bound properties such as Lipschitz constants or information flow, our method identifies collision points in feature spaces, enabling direct evaluation of vulnerabilities at the layer level. Additionally, our approach generates adversarial examples that cause these collisions, functioning as both a robustness analysis tool and an attack mechanism—a capability not present in existing methods. This dual functionality allows us to explore middle-layer robustness in a more practical and nuanced way across different feature extractor.

Our Gaussian random projection is philosophically related to the Sliced Wasserstein (SW) distance. Optimal adversarially robust classification is closely connected with optimal transport distances between class distributions Bhagoji et al. (2019); Pydi & Jog (2020); Trillos et al. (2023). On the other hand, estimation of optimal transport distances from data suffers from a curse of dimensionality, which SW distance bypasses by moving to a lower dimensional space. The SW distance is a computationally efficient variant of the Wasserstein distance where high-dimensional probability measures are projected onto one-dimensional subspaces before the optimal transport cost is computed. SW has been used to align latent distributions in autoencoders Kolouri et al. (2018), stabilize GAN training through max-slicing strategies Deshpande et al. (2019), and serve as a metric for comparing feature distributions in classification and domain adaptation Bonneel et al. (2015); Nadjahi et al. (2021). Whereas these methods average 1-D Wasserstein distances over many slices to approximate the full high-dimensional transport cost, we instead apply a 10-D random projection to approximate the optimal adversarial classifier loss.

References

Arjun Nitin Bhagoji, Daniel Cullina, and Prateek Mittal. Lower bounds on adversarial robustness from optimal transport. In *Advances in Neural Information Processing Systems*, pp. 7496–7508, 2019.

Arjun Nitin Bhagoji, Daniel Cullina, Vikash Sehwag, and Prateek Mittal. Lower bounds on cross-entropy loss in the presence of test-time adversaries. In *International Conference on Machine Learning*, pp. 863–873. PMLR, July 2021.

Arjun Nitin Bhagoji, Daniel Cullina, and Ben Y Zhao. A theoretical perspective on the robustness of feature extractors. In *The Second Workshop on New Frontiers in Adversarial Machine Learning*, 2023.

Nicolas Bonneel, Julien Rabin, Gabriel Peyré, and Hanspeter Pfister. Sliced and radon wasserstein barycenters of measures. *Journal of Mathematical Imaging and Vision*, 51(1):22–45, 2015.

Jared Craig, Jayson Andle, Thomas S. Nowak, and Sahand Y. Sekeh. A theoretical perspective on subnetwork contributions to adversarial robustness. *arXiv preprint arXiv:2307.03803*, 2023.

Francesco Croce and Matthias Hein. Minimally distorted adversarial examples with a fast adaptive boundary attack. In *International Conference on Machine Learning*, pp. 2196–2205. PMLR, November 2020.

Sihui Dai, Wenxin Ding, Arjun Nitin Bhagoji, Daniel Cullina, Heather Zheng, Ben Zhao, and Prateek Mittal. Characterizing the optimal 0-1 loss for multi-class classification with a test-time attacker. In A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (eds.), *Advances in Neural Information Processing Systems*, volume 36, pp. 49467–49489. Curran Associates, Inc., 2023.

Ishan Deshpande, Ziyu Hu, Liyuan Sun, Nicholas Kolkin, Justin Solomon, Changil Kim, Sanja Fidler, Deva Ramanan, and Krishna Singh. Max-sliced wasserstein distance and its use for gans. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10648–10656, 2019.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015.

Sven Gowal, Krishnamurthy (Dj) Dvijotham, Robert Stanforth, Jonathan Uesato, Relja Arandjelovic, Brendan O'Donoghue, and Pushmeet Kohli. Scalable verified training for provably robust image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pp. 4842–4851, 2019.

Guy Katz, Clark Barrett, David L. Dill, Kyle Julian, and Mykel J. Kochenderfer. Reluplex: An efficient smt solver for verifying deep neural networks. In *Computer Aided Verification (CAV)*, volume 10426 of *Lecture Notes in Computer Science*, pp. 97–117. Springer, 2017. doi: 10.1007/978-3-319-63387-9_5.

Soheil Kolouri, Phillip E. Pope, Charles E. Martin, and Gustavo K. Rohde. Sliced wasserstein auto-encoders. In *International Conference on Learning Representations*, 2018.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *arXiv preprint arXiv:1706.06083*, 2017.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: a simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2574–2582, 2016.

Kimia Nadjahi, Ievgen Redko, Guillaume Bouchard, Marc Sebban, and Nicolas Courty. Fast approximation of sliced-wasserstein distances using concentration of measure. In *Advances in Neural Information Processing Systems*, volume 34, pp. 22238–22250, 2021.

Muni Sreenivas Pydi and Varun Jog. Adversarial risk via optimal transport and optimal couplings. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 7814–7823, 2020.

Chulin Song, Rajeev Ranjan, and Haoliang Li. A layer-wise adversarial-aware quantization optimization for improving robustness. *arXiv preprint arXiv:2110.12308*, 2021.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Nicolás Garcıa Trillos, Matt Jacobs, and Jakwang Kim. The multimarginal optimal transport formulation of adversarial multiclass classification. *Journal of Machine Learning Research*, 24(45):1–56, 2023.

Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric Xing, Laurent El Ghaoui, and Michael Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, pp. 7472–7482. PMLR, 2019.

Deyuan Zhou, Zhiding Yu, Enze Xie, Chaowei Xiao, Anima Anandkumar, Jiashi Feng, and Jose M. Alvarez. Understanding the robustness in vision transformers. In *International Conference on Machine Learning (ICML)*, pp. 27378–27394. PMLR, June 2022.

A Distance Calculation

A.1 Projection operation

The projection onto a collision affine subspace in the l_2 norm can be formulated as the following optimization problem:

$$\min_{\delta, \delta'} \left\| \begin{bmatrix} \delta \\ \delta' \end{bmatrix} \right\|_2$$

Subject to:

$$\begin{bmatrix} Df(x^i), & -Df(x'^i) \end{bmatrix} \begin{bmatrix} \delta \\ \delta' \end{bmatrix} = f(x^i) - f(x'^i)$$

In practice, we solve this optimization problem using PyTorch's least squares solver in code.

For the first linear layer, the problem of finding the distance can be framed as solving the following optimization problem:

$$\min_{\delta, \delta'} \left\| \begin{bmatrix} \delta \\ \delta' \end{bmatrix} \right\|_2$$

Subject to:

$$AL(x + \delta) = AL(x' + \delta')$$

where A is a random projection matrix, and L represents the weights of the first linear layer. The optimal δ is the projection of $(x - x')/2$ onto the orthogonal complement of the nullspace of AL. Assuming AL is invertible,

$$\|\delta\|_2^2 = \frac{1}{4}(x - x')^T A^T L^T (LAA^T L^T)^{-1} AL(x - x').$$

When $A \in \mathbb{R}^{1 \times n_1}$ (so it is a single row drawn from an i.i.d. Gaussian distribution), This simplifies

$$\|\delta\|_2^2 = \frac{\|AL(x - x')\|^2}{4\|AL\|^2} = \frac{\|B\Sigma w\|^2}{4\|B\Sigma\|^2} = \frac{\sum_{i=0}^{n_1-1}(b_i \sigma_i w_i)^2}{4\sum_{i=0}^{n_1-1}(b_i \sigma_i)^2}$$

where b_i are random Gaussians, σ_i are singular values of L, and w_i are the coefficients of $(x - x')$ is the basis of right singular vectors. Thus w_i measures the usefulness of a particular singular vector for distinguishing x from x'. Weak features contribute proportionally more to the denominator. By assigning these smaller singular values (or even zero), $\|\delta\|$ could be increased.

A.2 Concentrated

We measured the distance between one pair in the first and second layers with 100 different random gaussian projection matrix, and the distribution of these distances is presented in the histogram. The figure 18 shows that the distances are concentrated, clearly highlighting the differing distributions between the two layers.

B More experiments

B.1 Activation function and batchnorm

We evaluated the effect of including the ReLU activation functions as part of the feature extractor. As the ReLU is non-injective, it enables new types of input collisions and could potentially reduce robustness because of this. On the other hand, ReLUs can zero out weak features and improve robustness. The results in figure 19 indicate that the ReLU activation in the first and second layers effectively reduces the number of collisions,

Figure 18: One pair distance under different random projection matrix

Model	Layer	Mnist	Cifar
Med. CNN	Conv1 32 3× 3+1	25088	32768
	Conv2 32 4× 4+2	6272	8192
	Conv3 64 3× 3+1	12544	16384
	Conv4 64 4× 4+2	3136	4096
	FC 512	512	512
	FC 512	512	512
	FC 10	10	10
Small CNN	Conv1 16 4× 4+2	3136	4096
	Conv2 32 4× 4+1	5408	7200
	FC 100	100	100
	FC 10	10	10
Large CNN	Conv1 64 3× 3+1	50176	65536
	Conv2 64 3× 3+1	50176	65536
	Conv3 128 3× 3+2	25088	32768
	Conv4 128 3× 3+1	25088	32768
	Conv5 128 3× 3+1	25088	32768
	FC 512	512	512
	FC 10	10	10

Table 1: Model Architectures and Feature space dimensions of Each Layer for MNIST and CIFAR

Figure 19: The ReLU performance

Figure 20: The Batchnorm performance

suggesting a lower optimal loss in these layers. However, the situation changes with the third ReLU layer, where the activation function leads to an increase in collisions.

A similar pattern was observed with the batch normalization (BatchNorm) layers in figure 20. Adding BatchNorm after each layer showed that the first and second BatchNorm layers contributed to reduced collisions, whereas the third BatchNorm layer resulted in more collisions.

B.2 Different learning rate

Figure 21: Mnist Medium Cnn Model trained with PGD: All layer robustness, learning rate is 0.01 throughout training

Figure 22: Mnist Medium Cnn Model trained with PGD: All layer robustness, learning rate is 0.001 throughout training

To investigate how the learning rate affects layer-wise robustness, we retrained the model using a flat learning rate instead of a cosine schedule. At similar learning rate levels, the model trained with a flat learning rate exhibits no significant difference in layer-wise robustness compared to the one trained with a cosine schedule. However, when the learning rate is reduced to 0.001 in figure 22, the optimal loss curve narrows starting from the second layer. This indicates that the model achieves good robustness with just the first two layers, while the subsequent layers contribute only marginally to robustness.

B.3 Changing the width of a single layer

Figure 23: Mnist Medium Cnn Model trained with PGD: All layer robustness, and the first convolutional layer has more filters

Figure 24: Mnist Medium Cnn Model trained with PGD: All layer robustness, and the first convolutional layer has fewer filters

When we decrease the number of filters in the third layer, the overall robustness of the model slightly decreases, but the robustness of the first layer improves, which aligns with our conclusion in the main paper. Conversely, increasing the number of filters in the first layer leads to the opposite effect, with a slight decrease in first-layer robustness and a potential increase in overall robustness.

Figure 25: Mnist Medium Cnn Model trained with PGD-1: All layer robustness

Figure 26: Mnist Medium Cnn Model trained with PGD-3: All layer robustness,

B.4 Robust training with varying perturbation budgets

When training with different perturbation budgets, we observed that, compared to PGD-2, PGD-1 exhibits similar robustness in the first and second layers. However, in the remaining layers, more collisions are detected, indicating lower robustness as reflected by the higher optimal loss. In contrast, PGD-3 demonstrates greater robustness than PGD-2, with the third layer showing improved distance and lower optimal loss compared to the second layer—a pattern not observed in PGD-2. The robustness distance in the other layers follows the same properties previously identified.

B.5 More common architecture

WiderResNet-28 has three stages, each consisting of four blocks, for a total of twelve blocks. AlexNet, on the other hand, includes five convolutional layers with max pooling and three fully connected (linear) layers.

For MNIST, the performance of AlexNet aligns with the observations reported for other medium-sized CNN models in the paper. However, when evaluating CIFAR, it appears that the max pooling operation concentrates robustness in the layer following the third pool.

In the case of WideResNet-28 on MNIST, we observe that robustness information is gradually learned by each block. However, for CIFAR, the final linear layer retains the most robustness-related information. While the robustness of individual blocks remains similar, the final linear layer enhances overall robustness, bringing it to a level comparable with other models.

Figure 27: AlexNet Robustness on MNIST

Figure 28: The WideResNet PGD-2 robustness on Mnist

B.6 PCA

Here, we used PCA instead of training an actual model, and then performed random projection on the PCA down to 10 dimensions for comparison. This illustrates how removing low-quality features can improve robustness as we measure it. The PCA on CIFAR-10 retains much greater distance compared to a real model.

Figure 29: AlexNet Robustness on CIFAR

Figure 30: The WideResNet PGD-0.5 robustness on CIFAR

Model	Layer	Out Dim. Mnist	Out Dim. CIFAR
AlexNet	Conv1: 64, $5 \times 5 + 1$, M.P 3	12544	16384
	Conv2: 192, $5 \times 5 + 1$, M.P 3	9408	12288
	Conv3: 384, $3 \times 3 + 1$, M.P 3	18816	24576
	Conv4: 256, $3 \times 3 + 1$, M.P 3	12544	16384
	Conv5: 256, $3 \times 3 + 1$, M.P 3	2304	4096
	FC 4096	4096	4096
	FC 4096	4096	4096
	FC 10	10	10
Wide ResNet 28-10	Block 1: Residual Block, 3×3, 160 filters	125440	163840
	Block 2: Residual Block, 3×3, 160 filters	125440	163840
	Block 4: Residual Block, 3×3, 320 filters	125440	163840
	Block 6: Residual Block, 3×3, 320 filters	62720	81920
	Block 8: Residual Block, 3×3, 640 filters	62720	81920
	Block 10: Residual Block, 3×3, 640 filters	31360	40960
	Block 12: Residual Block, 3×3, 640 filters	31360	40960
	FC 10	10	10

Table 2: Model Architectures and Feature space dimensions of Each Layer of MNIST and CIFAR

Figure 31: Mnist PCA, then random projection to 10

Figure 32: Cifar10 PCA, then random projection to 10

B.7 Using feature extractor for training

To show that feature extractors really matter for robustness, we run a simple freeze-k test: freeze the first k layers ($k = 0 \dots 7$), re-initialize the rest, do one epoch of PGD-2 adversarial training on the unfrozen part, and record the adversarial training loss for $\epsilon \in [2.0, 3.0]$. Lower loss means the frozen extractor already makes robust learning easier for the new head.

Figure 33: Mnist benign model one epoch

Figure 34: Mnist adv trained on PGD-2 model one epoch

For the clean-trained ("benign") model, the one-epoch adversarial loss increases as k grows, showing that fixing more clean features hurts robust adaptation. For the adversarially pre-trained ("robust") model, the loss decreases with k, indicating that its features provide a stable, robustness-friendly backbone. This freeze-k test is an external sanity check that different feature extractors change downstream robust training. Our contribution is a fast, training-free test that scores extractor robustness. In experiments, our score aligns with the freeze-k behavior, so practitioners can pick good extractors without re-training many models.

C Analysis of the distance for linear layers

Throughout, let $r_4 = \frac{\|L\|_4^4}{\|L\|^4}$, where $\|L\|_4$ is a Schatten p-norm and $\|L\|$ is the ℓ_2 operator norm. Then r_4 is a variation of stable rank for L.

Proposition 2. *Let $f(x) = ALx$, where $L \in \mathbb{R}^{n_1 \times n_0}$ is a fixed linear feature extractor and the entries of $A \in \mathbb{R}^{m \times n_1}$ are i.i.d. standard Gaussian. For $\epsilon \geq 2 \max(e^{-m/4}, m^2 e^{-r_4})$,*

$$\frac{1 - \frac{2}{\sqrt{m}}\sqrt{\log(2/\epsilon)}}{1 + \frac{4m\|L\|_4^4}{\|L\|_F^2}\sqrt{\log(m^2/\epsilon)}} \leq \frac{d(x,x')^2}{\frac{m\|L(x-x')\|^2}{4\|L\|_F^2}} \leq \frac{1 + \frac{4}{\sqrt{m}}\sqrt{\log(2/\epsilon)}}{1 - \frac{4m\|L\|_4^4}{\|L\|_F^2}\sqrt{\log(m^2/\epsilon)}}$$

with probability $1 - \epsilon$.

This bound implies concentration of the distance when $m \gg 1$ and $m \ll \frac{\|\sigma\|_2^2}{\|\sigma\|_4^2} = \frac{\|\sigma\|_2^2}{\|\sigma\|_\infty^2} \frac{\|\sigma\|_\infty^2}{\|\sigma\|_4^2} = \frac{r_2}{\sqrt{r_4}}$. Because $r_4 = \sum_k \left(\frac{\sigma_k}{\sigma_1}\right)^4 \leq \sum_k \left(\frac{\sigma_k}{\sigma_1}\right)^2 = r_2$, $\sqrt{r_4} \leq \frac{r_2}{\sqrt{r_4}}$ and $m \ll \sqrt{r_4}$ is sufficient to get concentration.

Proof. For $f(x) = Hx$, $d_f(x', x'')^2$ is equal to

$$\min_{\delta \in \mathbb{R}^{n_1}} \|\delta\|^2 \text{ subject to } H(x + \delta) = \mathbf{0}$$

where $x = \frac{x' - x''}{2}$. Then the lagrangian is

$$L(\delta, \lambda) = \delta^T \delta + \lambda^T H(x + \delta)$$

and the dual problem is

$$\max_{\lambda \in \mathbb{R}^m} x^T H^T \lambda + \min_\delta (\delta^T \delta + \lambda^T H \delta)$$
$$= \max_\lambda x^T H^T \lambda - \tfrac{1}{4}\lambda^T H H^T \lambda$$

where the minimizing δ is $-\frac{1}{2}H^T\lambda$. This is unconstrained, so it is easier to work with than the primal problem. Let $\lambda = c\mu$. For fixed μ with $\|\mu\| = 1$, the maximizing c is $\frac{2x^T H^T \mu}{\mu^T HH^T \mu}$, so the dual can be reexpressed as

$$\max_{\mu:\|\mu\|=1} \frac{(x^T H^T \mu)^2}{\mu^T HH^T \mu}$$

We have shown the matrix HH^T appearing the denominator is close to $\|L\|_F^2 I$. This suggests that the optimizing the ratio is roughly the same as optimizing the numerator.

Pick $\mu^* = \frac{Hx}{\|Hx\|}$, $(x^T H^T \mu^*)^2 = \left(\frac{\|Hx\|^2}{\|Hx\|}\right)^2 = \|Hx\|^2 = \|ALx\|^2$.

$$\frac{\|Hx\|^2}{\max_{\mu:\|\mu\|=1} \mu^T HH^T \mu} = \frac{(x^T H^T \mu^*)^2}{\mu^{*T} HH^T \mu^*} \leq \max_{\mu:\|\mu\|=1} \frac{(x^T H^T \mu)^2}{\mu^T HH^T \mu} \leq \max_{\mu:\|\mu\|=1} \frac{\|Hx\|^2\|\mu\|^2}{\mu^T HH^T \mu} = \frac{\|Hx\|^2}{\min_{\mu:\|\mu\|=1} \mu^T HH^T \mu}$$

Thus we need upper and lower bounds on $\|Hx\|^2$. Then $(ALx)_i \sim N(0, \|Lx\|^2)$ so $\|ALx\|^2$ is $\|Lx\|^2$ times a χ^2 distribution with m degrees of freedom. By Proposition 4, with $\|\sigma\|_2^2 = m\|Lx\|^2$, $\|\sigma\|_4^4 = m\|Lx\|^4$, $\|\sigma\|_\infty^2 = \|Lx\|^2$, and $r_4 = m$.

$$\Pr[\|ALx\|^2 \leq t] \leq -\frac{(t - m\|Lx\|^2)^2}{4m\|Lx\|^4}.$$

To get a bound of $\epsilon/2$, we take $t = m\|Lx\|^2 - \sqrt{4m\|Lx\|^4 \log(2/\epsilon)}$.

$$\frac{\|Hx\|^2}{\max_{\mu:\|\mu\|=1} \mu^T HH^T \mu} \geq \frac{m\|Lx\|^2 - 2\|Lx\|^2\sqrt{m\log(2/\epsilon)}}{\|L\|_F^2 + 4m\|L\|_4^2\sqrt{\log(m^2/\epsilon)}} = \frac{m\|Lx\|^2}{\|L\|_F^2} \cdot \frac{1 - \frac{2}{\sqrt{m}}\sqrt{\log(2/\epsilon)}}{1 + \frac{4m\|L\|_4^2}{\|L\|_F^2}\sqrt{\log(m^2/\epsilon)}}$$

For $t \geq \|\sigma\|_2^2$, again using Proposition 4,

$$\log \Pr[\|ALx\|^2 \geq t] \leq \begin{cases} -\frac{(t - m\|Lx\|^2)^2}{16m\|Lx\|^4} & 0 \leq t - m\|Lx\|^2 \leq 2m\|Lx\|^2 \\ -\frac{t - 2m\|Lx\|^2}{4\|Lx\|^2} & 2m\|Lx\|^2 < t - m\|Lx\|^2 \end{cases}$$

To get a bound of $\epsilon/2$, we take

$$t = \begin{cases} m\|Lx\|^2 + 4\|Lx\|^2\sqrt{m\log(2/\epsilon)} & \epsilon/2 \geq e^{-m/4} \\ 2m\|Lx\|^2 + 4\|Lx\|^2\log(2/\epsilon) & \epsilon/2 > e^{-m/4} \end{cases}.$$

At the boundary between the cases, $t = 3m\|Lx\|^2$, which is three times the mean and too big of a threshold to interest us. Using only the first case, we get

$$\frac{\|Hx\|^2}{\min_{\mu:\|\mu\|=1} \mu^T HH^T \mu} \leq \frac{m\|Lx\|^2 + 4\|Lx\|^2\sqrt{m\log(2/\epsilon)}}{\|L\|_F^2 - 4m\|L\|_4^2\sqrt{\log(m^2/\epsilon)}} = \frac{m\|Lx\|^2}{\|L\|_F^2} \cdot \frac{1 + \frac{4}{\sqrt{m}}\sqrt{\log(2/\epsilon)}}{1 - \frac{4m\|L\|_4^2}{\|L\|_F^2}\sqrt{\log(m^2/\epsilon)}}$$

$\square$

Proposition 3. *Let $H = AL$, where $L \in \mathbb{R}^{n_2 \times n_1}$ is a fixed linear feature extractor and the entries of $A \in \mathbb{R}^{m \times n_2}$ are i.i.d. standard Gaussian. Then for $\epsilon \geq m^2 e^{-r_4/4}$, for all $i, j \in [m]$,*

$$|(HH^T - \|L\|_F^2 I)_{ij}| \leq 4\|L\|_4^2\sqrt{\log(2m^2/\epsilon)}.$$

with probability $1 - \epsilon$.

Furthermore, for all $\mu \in \mathbb{R}^m$ with $\|\mu\| = 1$, $|\mu^T HH^T \mu - \|L\|_F^2| \leq 4m\|L\|_4^2\sqrt{\log(2m^2/\epsilon)}$.

Proof. Consider the singular value decomposition of L: $L = U\Sigma V^T$, where $U \in \mathbb{R}^{n_1 \times n_1}$. so $LL^T = U\Sigma^2 U^T$. Then $B = AU \in \mathbb{R}^{m \times n_1}$ also has i.i.d. standard Gaussian entries. We have $HH^T = ALL^T A^T = AU\Sigma^2 U^T A^T = B\Sigma^2 B^T$, so $(HH^T)_{ii} = \sum_{k=1}^{n_1} \sigma_k^2 B_{i,k}^2$. For $i \neq j$, $(HH^T)_{ij} = \sum_{k=1}^{n_1} \sigma_k^2 B_{i,k} B_{j,k}$. The first claim follows by applying Proposition 4 to $(HH^T)_{ii}$ and Proposition 5 case one to $(HH^T)_{ij}$. To achieve error probabilities of $\frac{\epsilon}{2m^2}$, we take $|t - E[(HH^T)_{ij}]| = 4\|L\|_4^2 \sqrt{\log(2m^2/\epsilon)}$.

For all $\mu \in \mathbb{R}^m$ with $\|\mu\| = 1$, using the triangle inequality we obtain

$$|\mu^T(HH^T - \|L\|_F^2 I)\mu| \leq \sum_{i,j} |\mu_i||\mu_j||(HH^T - \|L\|_F^2 I)_{ij}| \leq \langle|\mu|, \mathbf{1}\rangle^2 \cdot 4\|L\|_4^2 \sqrt{\log(2m^2/\epsilon)}$$

and $\langle|\mu|, \mathbf{1}\rangle^2 \leq \|\mu\|_2^2 \|\mathbf{1}\|_2^2 = m$. $\qquad\square$

Proposition 4 (Chernoff bounds for linear combinations of χ^2 random variables)**.** *Let* $Z = \sum_{k=1}^n \sigma_k^2 B_k^2$, *where* (B_k) *are i.i.d. standard Gaussian. Then for* $t \leq \|\sigma\|_2^2$

$$\Pr[Z \leq t] \leq -\frac{(t - \|\sigma\|_2^2)^2}{4\|\sigma\|_4^4}$$

and for $t \geq \|\sigma\|_2^2$

$$\Pr[Z \geq t] \leq \begin{cases} -\frac{(t - \|\sigma\|_2^2)^2}{16\|\sigma\|_4^4} & 0 \leq t - \|\sigma\|_2^2 \leq 2r_4\|\sigma\|_\infty^2 \\ -\frac{(t - \|\sigma\|_2^2)}{4\|\sigma\|_\infty^2} + \frac{r_4}{4} & 2r_4\|\sigma\|_\infty^2 < t - \|\sigma\|_2^2 \end{cases}$$

where $r_4 = \frac{\|\sigma\|_4^4}{\|\sigma\|_\infty^4}$.

Proof. The cumulant generating function of Z is

$$\log M(\theta) = \sum_{k=1}^n -\tfrac{1}{2}\log(1 - 2\sigma_i^2 \theta).$$

Observe that

$$E\left[\sum_{i=1}^n \sigma_i^2 B_{i,k}^2\right] = \sum_{i=1}^n \sigma_i^2 E[B_{i,k}^2] = \sum_{i=1}^n \sigma_i^2 = \|\sigma\|_2^2 = \|L\|_F^2$$

$$\mathrm{Var}\left[\sum_{i=1}^n z_i^2 \sigma_i^2 B_{i,k}^2\right] = \sum_{i=1}^n \sigma_i^4 \mathrm{Var}[B_{i,k}^2] = \sum_{i=1}^n 2\sigma_i^4 = 2\|\sigma\|_4^4 = 2\|L\|_4^4$$

lower tail For $z \leq 0$, $\log\frac{1}{1-z} \leq z + \frac{z^2}{2}$ (by comparing derivatives). We take $\theta^* = \frac{t - \|\sigma\|_2^2}{2\|\sigma\|_4^4}$ and for $t \leq \|\sigma\|_2^2$,

$$\log\Pr[(HH^T)_{ii} \leq t] \leq -\theta^* t + \frac{1}{2}\sum_{k=1}^{n_2} \log\frac{1}{1 - 2\sigma_i^2 \theta^*}$$

$$\leq -\theta^* t + \frac{1}{2}\sum_{k=1}^{n_2}(2\sigma_i^2\theta^* + 2\sigma_i^4\theta^{*2})$$

$$= -(t - \|\sigma\|_2^2)\theta^* + \theta^{*2}\|\sigma\|_4^4$$

$$= -\frac{(t - \|\sigma\|_2^2)^2}{4\|\sigma\|_4^4}$$

upper tail For $z < 1$, $\log \frac{1}{1-z} \le \frac{z}{1-z}$ and for $z \le \frac{1}{2}$, $\frac{z}{1-z} \le z + 2z^2$. For all $\theta \ge 0$, $\Pr[(HH^T)_{ii} \ge t] \le e^{-\theta t} M(\theta)$. Let

$$\theta^* = \min\left(\frac{t - \sum_{k=1}^{n_1}\sigma_k^2}{8\sum_{k=1}^{n_1}\sigma_k^4}, \frac{1}{4\max_k \sigma_k^2}\right) = \min\left(\frac{t - \|\sigma\|_2^2}{8\|\sigma\|_4^4}, \frac{1}{4\|\sigma\|_\infty^2}\right) = \begin{cases} \frac{t - \|\sigma\|_2^2}{8\|\sigma\|_4^4} & 0 \le t - \|\sigma\|_2^2 \le 2r_4\|\sigma\|_\infty^2 \\ \frac{1}{4\|\sigma\|_\infty^2} & 2r_4\|\sigma\|_\infty^2 < t - \|\sigma\|_2^2 \end{cases}.$$

This choice satisfies $2\sigma_i^2\theta^* \le \frac{1}{2}$ for all i, so we can apply our upper bound on $\log \frac{1}{1-z}$. Then for $t \ge \|\sigma\|_2^2$,

$$\log \Pr[(HH^T)_{ii} \ge t] \le -\theta^* t + \frac{1}{2}\sum_{k=1}^{n_2}\log \frac{1}{1 - 2\sigma_i^2\theta^*}$$

$$\le -\theta^* t + \frac{1}{2}\sum_{k=1}^{n_2}(2\sigma_i^2\theta^* + 8\sigma_i^4\theta^{*2})$$

$$= -(t - \|\sigma\|_2^2)\theta^* + 4\theta^{*2}\|\sigma\|_4^4$$

$$= \begin{cases} -\frac{(t - \|\sigma\|_2^2)^2}{16\|\sigma\|_4^4} & 0 \le t - \|\sigma\|_2^2 \le 2r_4\|\sigma\|_\infty^2 \\ -\frac{(t - \|\sigma\|_2^2)}{4\|\sigma\|_\infty^2} + \frac{r_4}{4} & 2r_4\|\sigma\|_\infty^2 < t - \|\sigma\|_2^2 \end{cases}$$

$\square$

Proposition 5 (Chernoff bounds for linear combinations of χ^2 random variables). *Let* $Z = \sum_{k=1}^n \sigma_k^2 B_k B_k'$, *where* (B_k) *and* (B_k') *are i.i.d. standard Gaussian. Then*

$$\log \Pr[Z \ge t] \le \begin{cases} -\frac{t^2}{16\|\sigma\|_4^4} & 0 \le t \le \sqrt{2}r_4\|\sigma\|_\infty^2 \\ -\frac{t}{\sqrt{2}\|\sigma\|_\infty^2} + \frac{r_4}{2} & \sqrt{2}r_4\|\sigma\|_\infty^2 < t \end{cases}$$

Proof. The cumulant generating function of Z is

$$\log M(\theta) = \sum_{k=1}^n -\frac{1}{2}\log(1 - \sigma_i^4\theta^2).$$

The off-diagonal entries have a symmetric distribution, so the upper and lower tail bounds are the same. For $z < 1$, $\log \frac{1}{1-z^2} \le \frac{z^2}{1-z^2}$ and for $z^2 \le \frac{1}{2}$, $\frac{z^2}{1-z^2} \le 2z^2$. For $t \ge 0$, pick

$$\theta^* = \min\left(\frac{t}{2\|\sigma\|_4^4}, \frac{1}{\sqrt{2}\|\sigma\|_\infty^2}\right)$$

and

$$E\left[\sum_{i=1}^n \sigma_i^2 B_{i,k}B_{j,k}\right] = \sum_{i=1}^n \sigma_i^2 E[B_{i,k}]E[B_{j,k}] = 0$$

$$\text{Var}\left[\sum_{i=1}^n z_i^2\sigma_i^2 B_{i,k}B_{j,k}\right] = \sum_{i=1}^n \sigma_i^4 E[B_{i,k}^2]E[B_{j,k}^2] = \sum_{i=1}^n \sigma_i^4 = \|\sigma\|_4^4 = \|L\|_4^4.$$

Then

$$\log \Pr[(HH^T)_{ij} \ge t] \le -\theta^* t + \frac{1}{2}\sum_{k=1}^{n_2}\log \frac{1}{1 - \sigma_i^4\theta^{*2}}$$

$$\le -\theta^* t + \frac{1}{2}\sum_{k=1}^{n_2}2\sigma_i^4\theta^{*2}$$

$$= -\theta^* t + \theta^{*2}\|\sigma\|_4^4$$

$$= \begin{cases} -\frac{t^2}{16\|\sigma\|_4^4} & 0 \le t \le \sqrt{2}r_4\|\sigma\|_\infty^2 \\ -\frac{t}{\sqrt{2}\|\sigma\|_\infty^2} + \frac{r_4}{2} & \sqrt{2}r_4\|\sigma\|_\infty^2 < t \end{cases}$$

$\square$