More Structure, Not More Capacity: Object-Centric Representations for Visuomotor Imitation Learning

Yi Li[1], Alexandre Chapin[2], Liming Chen[2], Jan Peters[1], Alap Kshirsagar[3]

[1]TU Darmstadt [2]École Centrale de Lyon [3]IIT Delhi - Abu Dhabi

Abstract—Robotic manipulation policies rely on pre-trained vision models that give either a global scene embedding or a dense patch grid. Both mix task-relevant and task-irrelevant features. Object-centric slot representations are a structured alternative: they group features into a few per-object slots. We test what this structure buys on ManiSkill3 PickCube-v1, with a frozen encoder and a held-out-seed evaluation. Holding the policy, goal token, rendering, and calibration fixed and changing only the encoder, a frozen object-centric SPOT representation (DINO ViT-B/16 + Slot Attention) reaches $55.0\pm2.9\%$ success, 22.4% above a dense DINO global-feature baseline $(32.6\pm1.5\%)$, with the same trainable policy and no encoder fine-tuning. More tokens alone do not help: a dense patch grid with $16\times$ the tokens performs no better than the global feature. Adding an explicit 2D spatial goal and native-resolution rendering raises the full system to $68.7\pm4.2\%$, just below a privileged 3D-oracle upper bound $(71.7\pm4.1\%)$. An automated kinematic failure taxonomy then separates spatial-precision (Near-Miss) failures from object-tracking (No-Grasp) failures: spatial grounding reduces Near-Miss while leaving No-Grasp unchanged. The same taxonomy transfers to the harder StackCube-v1 and points to occlusion as the main bottleneck.

I. INTRODUCTION

A visuomotor policy never sees the raw scene. It only sees what its visual encoder keeps. The choice of representation therefore decides what information reaches the policy. In robotics this question is most developed for mapping and localization, where geometric, probabilistic, dense, and implicit map representations each shape behavior differently [1]. It applies just as much to manipulation: how does the structure of the visual representation affect behavior when the policy must act on object and goal positions it never saw during training? We answer this with a controlled, task-level study on a simulated pick-and-place task.

Self-supervised vision transformers such as DINO [2] transfer well to recognition. It is less clear how they behave when a policy must act on scene configurations not seen in training. Recent work across image classification [14], 3D perception [17], and gaze estimation [11] points to one shared pattern: a backbone trained under global or invariance-oriented supervision finds a low-cost cue that holds in-distribution and breaks under shift, and in each case the fix is structural rather than adding parameters.

This paper studies a similar pattern in visuomotor imitation. Under matched conditions, we compare dense DINO features (both the global `[CLS]` token and dense patch

grids) against an object-centric slot representation built on the same frozen backbone. We treat the slot representation as a small, competition-based bottleneck. Slot Attention [9], as implemented in SPOT [6], compresses the dense patches into a few slots and makes each slot bind to one coherent region. This is an architectural inductive bias toward object-level structure. Since the encoder stays frozen, this bias has to come from the module placed on top of its features, not from retraining the backbone. A strong pretrained backbone is not enough when the task needs signals that the pretraining objective suppressed.

In this work, we make the following contributions:

1) A systematic, matched-condition comparison of dense global, dense patch, and object-centric representations for visuomotor imitation, under a single policy and a held-out-seed protocol that measures generalization to novel object and goal placements (a task-level evaluation of representation choice).

2) The finding that representational *structure*, not capacity, drives generalization: object-centric slots beat dense features by 22.4% under matched conditions, while a 392-token dense grid collapses, and neither bidirectional cross-attention nor a longer temporal window improves held-out success over their simpler counterparts. We read this as a similar shortcut-learning pattern to that seen in recent foundation-model work, and support that reading with what we can measure directly: how the slots bind, and how the failures are distributed.

3) An automated, encoder-agnostic kinematic failure taxonomy that separates spatial-precision (Near Miss) from object-tracking (No-Grasp) failures, giving a task-level read of the trade-offs and failure modes of each representation and grounding choice. It transfers across tasks: applied unchanged to StackCube-v1, it points to occlusion as the main bottleneck.

II. RELATED WORK

a) Object-centric representations.: Slot Attention [9] routes image patches into discrete, permutation-equivariant slots through iterative competition. Subsequent work extended this to video [7], to feature-space reconstruction on frozen backbones (DINOSAUR [13]), and to diffusion decoders (SlotDiffusion [16]). We build on SPOT [6], which stabilizes

slot binding via autoregressive patch-order permutations and self-training through attention-mask distillation on a frozen DINO ViT-B/16 backbone. We choose it over these alternatives because it gives stable slot binding on real images within an 11 GB VRAM budget and runs as a feed-forward encoder with no decoder at inference, which suits our frozen-feature, single-GPU setting. We use SPOT as a fixed feature extractor and ask what its structure gives the policy. Most directly related to our setting, Chapin et al. [3] present a large-scale comparison of global, dense, and object-centric representations and show, with frozen encoders, that object-centric slots improve manipulation generalization under visual distribution shifts (lighting, texture, clutter). We build on this in a complementary direction. Instead of visual shifts, we test generalization to unseen object and goal placements on a single task under a held-out-seed protocol; we isolate representational structure from token count; we add an explicit spatial-grounding study; and we introduce a kinematic failure taxonomy that applies unchanged across tasks.

b) Shortcut learning in vision foundation models.: Shi et al. [14] identify lazy aggregation in ViTs: the `[CLS]` token relies on low-frequency background content and generalizes poorly when foreground–background correlation shifts. Zhang et al. [17] show that cross-domain 3D encoders exploit scan patterns and gravity bias as domain identifiers, removable only with targeted structural interventions. Work on gaze estimation [11] shows that invariance-oriented pretraining discards the fine-grained geometric signal gaze estimation requires, and that a domain-matched, detail-preserving objective recovers it. The same pattern appears in robotic manipulation: Chapin et al. [3] show that global and dense features entangle task-relevant and irrelevant cues and lose robustness under scene changes. These works span 2D recognition, 3D perception, fine-grained regression, and manipulation; we add a controlled visuomotor-imitation study and, as in those settings, find the effective remedy to be structural rather than parametric.

c) Visuomotor imitation with frozen features.: R3M [10] and MVP [12] show that frozen self-supervised features support manipulation without end-to-end fine-tuning. ACT [18] and Diffusion Policy [4] establish action chunking and sequence-based policy decoders as strong behavior-cloning baselines. We build on this paradigm and isolate the *encoder structure* as the critical variable, holding the policy and the frozen-feature setting fixed.

III. METHOD

Figure 1 shows the pipeline: a frozen visual encoder, a token construction stage, and a trainable autoregressive policy.

A. Frozen SPOT Encoder

Two RGB cameras (a base and a diagonal-side view, both 224×224) observe the scene from complementary viewpoints. Each image is processed independently by the frozen SPOT encoder, which chains a DINO ViT-B/16 backbone with a Slot Attention module to compress 196 patch tokens into $K = 7$ object slots $S \in \mathbb{R}^{7 \times 256}$. K=7 is fixed by the publicly released

SPOT checkpoint and is not tuned; we inherit it as-is. Slot Attention [9] normalizes attention over the *slot* dimension, so each patch activates at most one slot strongly:

$$M_{i,j} = \frac{k(X_i) \cdot q(S_j)}{\sqrt{D}}, \quad W_{i,j} = \frac{\exp(M_{i,j})}{\sum_{l=1}^{K} \exp(M_{i,l})}, \quad (1)$$

$$S^{(t)} = \text{GRU}\left(S^{(t-1)}, W^\top v(X)\right) \quad (2)$$

This competition forces object-level binding and keeps the representation from collapsing to scene-level statistics. Slots from both cameras are concatenated into $S_{\text{vis}} \in \mathbb{R}^{14 \times 256}$. We use the publicly released SPOT checkpoint, pretrained on COCO and kept frozen throughout all experiments; observed performance differences therefore reflect properties of the representation, not task-specific fine-tuning.

B. Token Construction and Spatial Grounding

At each timestep, four token types are projected to a shared 256-dimensional space and concatenated into a 17-token sequence: (i) 14 visual slot tokens; (ii) 1 proprioception token (7-DoF joint positions via MLP); (iii) 1 goal token (below); (iv) 1 learnable action token queried at readout. We study three goal-conditioning conditions to isolate the contribution of spatial information:

- **Pure Visual:** no goal token; the policy relies on visual slots only.
- **2D Spatial Projection:** the 3D goal is projected onto both camera planes via intrinsics/extrinsics, giving a 4D pixel vector $g = [u_b, v_b, u_s, v_s]$ normalized to $[0, 1]$ and encoded by a 3-layer MLP.
- **3D Oracle:** ground-truth 3D world coordinates from the simulator. This is a privileged upper bound and is not deployable.

Both the 2D projection and the 3D oracle use the simulator's ground-truth goal location; they differ only in how the goal is represented (pixel vs. world coordinates), not in the information they assume. The 2D projection is therefore not self-supervised; deriving the goal anchor from observation alone (e.g. from the slot masks) is future work.

C. Autoregressive Sequence Policy

Our policy is a causal Transformer decoder trained for behavior cloning. We reuse the GPT (minGPT-style) decoder from the VQ-BeT implementation in LeRobot [8]; unlike VQ-BeT, we predict continuous actions directly, with no vector quantization. An 8-layer, 8-head causal Transformer policy with hidden dimension 256 processes a temporal window of $T = 5$ frames (85 tokens total) under a lower-triangular causal mask. The hidden state of the action token at the current timestep passes through a 3-layer ReLU MLP to predict a 10-step action chunk ($H = 10$, action dimension 8). The 7 continuous joint dimensions are Z-score normalized; the gripper dimension bypasses normalization and is decoded by a hard step function.

Fig. 1. System overview. RGB images from two fixed cameras are encoded by the frozen SPOT encoder (DINO ViT-B/16 + Slot Attention) into 7 object slots each. The 14 visual slots, 1 proprioception token, 1 goal token, and 1 learnable action token form a 17-token sequence per timestep. A causal Transformer policy predicts a 10-step action chunk.

D. Representation Baselines

Under identical policy architecture and goal conditioning, we compare:

- **DINO Global [CLS]:** 1 token per camera (2 total).
- **DINO 4×4 patches:** 16 tokens per camera (32 total), spatially subsampled.
- **DINO 14×14 dense:** 196 tokens per camera (392 total); memory forces $T=1$, $H=1$.
- **Object-Centric (SPOT):** 7 slots per camera (14 total).

The dense 14×14 baseline is a deliberate stress test: it has the most tokens but, forced to a single frame and single-step prediction by GPU memory, it removes temporal context.

IV. EXPERIMENTAL SETUP

a) Task and simulator.: All experiments use ManiSkill3 [15] with the deterministic `physx_cpu` backend. The primary task, **PickCube-v1**, uses a Franka Panda arm to grasp a red cube and place it at a randomly initialized 3D target. We additionally train and evaluate the same architecture on **StackCube-v1** (stack a red cube on a green cube) to characterize failure modes under higher occlusion. Training uses 1,000 expert demonstrations from the simulator's motion planner, replayed at 100% success.

b) Evaluation on unseen initializations.: Object and goal positions are randomized at each episode. Training uses seeds 0–9,999 and evaluation uses seeds $\geq 10,000$, so the policy is evaluated only on placements it never saw during training (the seed ranges are disjoint). This protocol measures generalization to novel placements rather than memorization.

c) Evaluation protocol.: Checkpoints are saved every 50 epochs and swept against 200 held-out episodes. The best checkpoint undergoes three independent stability runs of 300 episodes each; we report mean $\pm$ std. Episodes terminating in fewer than 10 steps are discarded as trivial successes. Because the encoder is frozen and only a lightweight module is trained on top of its features, this setup is a *decoder probing* of frozen representations: it measures how much task-relevant signal a

TABLE I
SUCCESS RATES (SR) ON PICKCUBE-V1 (HELD-OUT SEEDS $\geq 10,000$, MEAN $\pm$ STD OVER 3×300 EPISODES). THE REPRESENTATION COMPARISON (*upper block*) HOLDS POLICY, GOAL TOKEN, RENDERING RESOLUTION (128^2), AND APPROXIMATE CALIBRATION CONSTANT, SO THAT ONLY THE VISUAL ENCODER CHANGES. THE SPATIAL-GROUNDING AND RESOLUTION ABLATION (*lower block*) USES SPOT THROUGHOUT. † FORCED TO $T=1$, $H=1$ BY GPU MEMORY. ‡ PRIVILEGED SIMULATOR STATE; ORACLE UPPER BOUND ONLY.

Configuration	Tokens	SR (%)
Representation comparison (128^2, approx. cal., 2D goal)		
DINO 14×14 dense †	392	1.0
DINO Global [CLS]	2	32.6 ± 1.5
DINO 4×4 patches	32	31.7 ± 3.0
Object-Centric (SPOT)	14	55.0 ± 2.9
Spatial grounding and resolution ablation (SPOT)		
Pure visual (no goal)	14	31.0 ± 2.8
+ 2D goal, approx. cal., 128^2	14	55.0 ± 2.9
+ 2D goal, exact cal., 128^2	14	58.7 ± 3.4
+ 2D goal, exact cal., 224^2 (full system)	**14**	**68.7 ± 4.2**
3D Oracle ‡	14	71.7 ± 4.1

moderate non-linear decoder can extract, which is closer to the deployment regime than either linear probing or full fine-tuning.

d) Failure taxonomy.: Failed episodes from a separate 200-episode run are classified by an automated kinematic script (inputs: action variance, the `is_grasped` flag, and tool center point (TCP)-to-goal distance) into five mutually exclusive categories applied in priority order: **Idle** (mean action variance below threshold), **No Grasp** (`is_grasped` never true), **Drop** (grasped but released before the end), **Near Miss** (minimum TCP-to-goal distance < 0.1 m but final placement failed), and **Unknown**. The script uses no visual data and is encoder-agnostic.

Fig. 2. Success rate across representation types under matched conditions; the object-centric bar (shown as SPOT-Approx-128) is the SPOT representation at 128^2 with approximate calibration, i.e. the Object-Centric (SPOT) row of Table I. Object-centric grouping matters; token count does not.

V. RESULTS AND ANALYSIS

A. Object-Centric vs. Dense Representations

The upper block of Table I shows the matched comparison. All four configurations use the same policy, the same 2D goal token, 128^2 rendering, and approximate calibration; only the encoder changes. The object-centric SPOT representation reaches $55.0 \pm 2.9\%$, against $32.6 \pm 1.5\%$ for DINO Global [CLS] and $31.7 \pm 3.0\%$ for DINO 4×4 patches. That is a 22.4% gap from a change in structure alone, with the same trainable policy and no encoder fine-tuning. Token count does not track success: the 4×4 grid carries $16\times$ the tokens of the global feature but performs the same (31.7 vs 32.6), and the object-centric representation beats it with fewer tokens. The dense 14×14 baseline does collapse to 1.0%, but only after GPU memory forces it to $T = 1$, $H = 1$ and strips temporal context, so we do not read that as a token-count effect. **The gain comes from object-level structure, not token count** (Fig. 2).

B. Why It Works: A Capacity-Limited Bottleneck

We read this result through what the architecture does. Slot Attention compresses 196 patches per view into seven slots. The softmax competition over the slot dimension makes each patch commit to a single slot, so no slot can take in the whole image at once. Scene-level statistics are therefore not available as a shortcut, and the limited capacity goes to coherent object regions instead. Figure 3 shows this: in clean episodes, some slots bind to the cube, the goal marker, and the arm, while the rest cover the background. The per-slot patch counts make the competition explicit: one dominant slot absorbs most of the 196 patches (the table background), while smaller slots bind precisely to the cube and goal. This is the manipulation version of the pattern in Section I. A dense global feature is free to mix information across the whole image. It keeps co-occurrence cues from the training set, such as object textures, goal positions, and background statistics that vary together during training, and it breaks when a new

Fig. 3. Per-episode slot masks from the base camera. A subset of slots binds to the cube, goal marker, and arm, while the rest cover the background. Numbers in parentheses give the patches (of 196) assigned to each slot; the largest slot (122) covers the table background, while smaller slots bind precisely to the cube and goal. This competition-based grouping is the structural bottleneck the dense baselines lack.

TABLE II
MULTI-VIEW FUSION WITHOUT EXPLICIT GOAL CONDITIONING, ON PICKCUBE-V1. TRAINING SUCCESS RATES ARE APPROXIMATE, READ OFF DURING TRAINING ON SEEN INITIALIZATIONS; HELD-OUT SUCCESS RATES ARE OVER 3×300 HELD-OUT-SEED EPISODES. CROSS-ATTENTION LOOKS FAR BETTER DURING TRAINING BUT MATCHES CONCATENATION ON HELD-OUT SEEDS, SO ITS EXTRA CAPACITY DOES NOT TRANSFER.

Fusion strategy	Train. SR (%)	Held-out SR (%)
Token concatenation	≈ 38.6	31.0
Bidirectional cross-attention	≈ 60.0	31.0

initialization breaks those cues. We read the gap as consistent with the lazy-aggregation account of Shi et al. [14]. We do not measure [CLS] attention directly. What we report instead is the slot binding above and the spatial-precision failure profile in Section V-D.

C. Fusion and Temporal Capacity Do Not Transfer

We next ask whether adding *parameters* can recover what structure gives for free. Without a goal token, token concatenation and bidirectional cross-attention reach the same held-out SR of 31.0% (Table II), measured over three runs of 300 episodes. Their training-time behavior differs sharply: cross-attention reaches about 60% on seen initializations against roughly 38.6% for concatenation. We treat these training-time numbers only as a qualitative signal, since they are read off during training on seen seeds rather than under the held-out protocol; the point is the direction, not the level. The extra parameters of cross-attention fit the seen placements but do not transfer to held-out ones. Concatenation has no such dedicated capacity; it leaves cross-view integration to the causal self-attention over the 17-token sequence. **We therefore prefer token concatenation to a parametric fusion module.** One caveat on scope: this comparison was run without a goal token, where success sits at its floor for both strategies and the real limit is the missing spatial anchor.

A second capacity axis points the same way. Here we keep an early, pure-visual configuration fixed and change only the temporal window. Success rate does not move with history

Fig. 4. Failure breakdown across goal-conditioning conditions. Near-Miss (spatial precision) drops sharply with grounding; No-Grasp (object tracking) does not. The two bottlenecks are invisible to binary success rate.

Fig. 5. StackCube-v1 sub-task funnel (single 200-episode run). The dominant loss is at the grasp stage (72% No-Grasp), caused by arm-induced occlusion. This is a different bottleneck than PickCube's, and the same kinematic taxonomy applies unchanged.

length (6.7% at $T \in \{5, 20, 40\}$), while a shorter window trains about $4.5\times$ more epochs in the same compute budget. The low absolute value here is from before the spatial-grounding and resolution fixes; the point is that success does not change with T, not its level. Taken together: without an explicit spatial anchor, neither more fusion parameters nor more history turns into better generalization.

D. Spatial Grounding and the Failure Profile

The lower block of Table I isolates spatial grounding and rendering resolution, with the SPOT encoder fixed. Pure-visual success rate is $31.0\pm2.8\%$. Adding a 2D goal projection (approximate calibration, 128^2) raises it to $55.0\pm2.9\%$ ($+24\%$). Replacing approximate with exact intrinsics and extrinsics adds $+3.7\%$, to $58.7\pm3.4\%$. So a consistent but slightly biased anchor already recovers most of the gain; pixel-perfect calibration helps but is not critical. Rendering natively at 224^2 removes an upscaling artifact that let the cube and goal share one pixel cell at close placement distances. This adds a further $+10.0\%$, to $68.7\pm4.2\%$, just below the 3D-oracle ceiling ($71.7\pm4.1\%$).

The failure taxonomy (Fig. 4) makes this concrete, and shows that binary success rate hides two separate bottlenecks. As goal conditioning improves from pure visual to 3D oracle, Near-Miss failures (the robot reaches the goal area but fails the final placement) fall from 31% to 21% to 2.5%. No-Grasp failures are *not* reduced by spatial grounding (15, 15, and 24 episodes per 200 across the three conditions). The two modes need different fixes. Near Miss is fixed by spatial grounding. No-Grasp needs better occlusion handling or temporal slot consistency (e.g. SAVi++ [5]). The taxonomy therefore separates spatial-precision failures from object-tracking failures, which makes it possible to fix the right one rather than tune blindly. Beyond aggregate success rate, this gives a task-level read of what a representation or grounding choice fixes and what it leaves untouched.

E. Cross-Task Transfer of the Taxonomy: StackCube-v1

To test whether the diagnostic carries over to another task, we train the same architecture on **StackCube-v1** and apply

the same kinematic classifier without any change. The policy reaches $5.3\pm2.2\%$ SR, well below the PickCube result. The taxonomy points straight at the bottleneck (Fig. 5): No-Grasp accounts for 72% (144 of 200) of episodes, against 7.5% (15 of 200) on PickCube under the pure-visual condition. The cause is occlusion. During the close approach the arm hides the red cube from the base camera, and our frozen SPOT has no temporal memory of slots, so it cannot recover the cube once hidden. This is the opposite of the PickCube profile, where Near Miss was the main failure and No-Grasp was stable. **The taxonomy shows that the two tasks need different fixes**: StackCube needs temporal slot consistency, not more spatial grounding. Binary success rate gives no such guidance. The taxonomy works as a diagnostic that transfers across tasks.

VI. DISCUSSION

a) Structure, not capacity.: The results point to one statement: a small structural bottleneck on top of frozen features generalizes where added parameters do not. Object-centric grouping beats dense features by 22.4% with the same trainable policy (Sec. V-A), while cross-attention and longer temporal windows do not improve transfer (Sec. V-C). Slot Attention acts as a capacity-limited, competition-based bottleneck: it caps how much the representation can carry and pushes that capacity onto object-level regions. Since the encoder is frozen, the only lever for an inductive bias is the structure placed after the foundation model, not its weights.

b) One pattern across settings.: This failure-and-fix shape is not unique to manipulation. In ViT classification [14], in cross-domain 3D perception [17], and in gaze regression [11], a foundation model under global or invariance-oriented supervision finds a low-cost cue that holds in-distribution and breaks under shift, and the reported fix is structural rather than added capacity. We show the pattern in one domain. We offer the parallel across settings as context, not as a claim that it always holds.

c) Boundary of frozen slots.: Three limitations bound the conclusions. First, SPOT has no temporal memory of slots, so it cannot recover an object that becomes occluded mid-trajectory. This is the direct cause of the StackCube collapse. Second, the fusion comparison was run only without a goal token; we do not know whether concatenation is still better once a reliable spatial anchor is present. Third, the representation comparison uses approximate calibration. We show in Sec. V-D that exact calibration adds $+3.7\%$, so the matched comparison is conservative but not calibration-free. Each limitation points to a next step: temporal slot consistency for occlusion, a fusion comparison with grounding present, and goal grounding derived from slot masks so that camera extrinsics are no longer needed.

VII. CONCLUSION

We presented a controlled, task-level study of visual representation types for visuomotor imitation, evaluated on object and goal placements not seen in training. Object-centric slot representations beat dense global and patch features by 22.4% under matched conditions, which shows that structure matters more than token count. With an explicit 2D spatial goal, which is itself derived from the ground-truth target, the full system reaches 68.7%, close to the privileged 3D oracle (71.7%). All of this uses a frozen encoder, a single $11\,\text{GB}$ GPU, and no end-to-end fine-tuning. A fusion ablation shows that simple concatenation generalizes as well as cross-attention while overfitting less. An automated kinematic failure taxonomy separates spatial-precision failures from object-tracking failures, and transfers to StackCube-v1, where it points to occlusion as the main bottleneck. For a practitioner on a small budget: prefer object-centric slots to global features, use token concatenation rather than a parametric fusion module, and give the policy an explicit spatial goal anchor. Future work includes goal grounding from slot masks, temporal slot consistency for occlusion, and sim-to-real transfer on a physical Franka Panda.

ACKNOWLEDGMENTS

This work builds on the first author's M.Sc. thesis carried out at the Intelligent Autonomous Systems group, TU Darmstadt, and the LIRIS Lab, École Centrale de Lyon.

REFERENCES

[1] Cesar Cadena, Luca Carlone, Henry Carrillo, Yasir Latif, Davide Scaramuzza, José Neira, Ian Reid, and John J. Leonard. Past, present, and future of simultaneous localization and mapping: Toward the robust-perception age. *IEEE Transactions on Robotics*, 32(6):1309–1332, 2016.

[2] Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.

[3] Alexandre Chapin, Bruno Machado, Emmanuel Dellandréa, and Liming Chen. Spotlighting task-relevant features: Object-centric representations for better generalization in robotic manipulation. arXiv:2601.21416, 2026.

[4] Cheng Chi, Siyuan Feng, Yilun Du, Zhenjia Xu, Eric Cousineau, Benjamin Burchfiel, and Shuran Song. Diffusion policy: Visuomotor policy learning via action diffusion. In *Robotics: Science and Systems (RSS)*, 2023.

[5] Gamaleldin F. Elsayed, Aravindh Mahendran, Sjoerd van Steenkiste, Klaus Greff, Georg Heigold, and Thomas Kipf. SAVi++: Towards end-to-end object-centric learning from real-world videos. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[6] Ioannis Kakogeorgiou, Spyros Gidaris, Konstantinos Karantzalos, and Nikos Komodakis. SPOT: Self-training with patch-order permutation for object-centric learning with autoregressive transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024.

[7] Thomas Kipf, Gamaleldin F. Elsayed, Aravindh Mahendran, Austin Stone, Sara Sabour, Georg Heigold, Rico Jonschkowski, Alexey Dosovitskiy, and Klaus Greff. Conditional object-centric learning from video. In *International Conference on Learning Representations (ICLR)*, 2022.

[8] Seungjae Lee, Yibin Wang, Haritheja Etukuru, H. Jin Kim, Nur Muhammad Mahi Shafiullah, and Lerrel Pinto. Behavior generation with latent actions. In *International Conference on Machine Learning (ICML)*, 2024.

[9] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 33, 2020.

[10] Suraj Nair, Aravind Rajeswaran, Vikash Kumar, Chelsea Finn, and Abhinav Gupta. R3M: A universal visual representation for robot manipulation. *arXiv preprint arXiv:2203.12601*, 2022.

[11] Jiawei Qin, Xucong Zhang, and Yusuke Sugano. UniGaze: Towards universal gaze estimation via large-scale pre-training. In *IEEE Winter Conference on Applications of Computer Vision (WACV)*, 2025.

[12] Ilija Radosavovic, Tete Xiao, Stephen James, Pieter Abbeel, Jitendra Malik, and Trevor Darrell. Real-world robot learning with masked visual pre-training. In *Conference on Robot Learning (CoRL)*, 2022.

[13] Maximilian Seitzer, Max Horn, Andrii Zadaianchuk, Dominik Zietlow, Tianjun Xiao, Carl-Johann Simon-Gabriel, Tong He, Zheng Zhang, Bernhard Schölkopf, Thomas Brox, and Martin Engelcke. Bridging the gap to real-world object-centric learning. In *International Conference on Learning Representations (ICLR)*, 2023.

[14] Cheng Shi, Yizhou Yu, and Sibei Yang. Vision transformers need more than registers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2026.

[15] Stone Tao, Fanbo Xiang, Arth Shukla, Yuzhe Qin, Xander Hinrichsen, Xiaodi Yuan, Chen Bao, Xinsong Lin, Yulin Liu, Tse kai Chan, Yuan Gao, Xuanlin Li, Tongzhou Mu, Nan Xiao, Arnav Gurha, Viswesh Nagaswamy Rajesh, Yong Woo Choi, Yen-Ru Chen, Zhiao Huang, Roberto Calandra, Rui Chen, Shan Luo, and Hao Su. ManiSkill3: GPU parallelized robotics simulation and rendering for generalizable embodied AI. *Robotics: Science and Systems*, 2025.

[16] Ziyi Wu, Jingyu Hu, Wuyue Lu, Igor Gilitschenski, and Animesh Garg. SlotDiffusion: Object-centric generative modeling with diffusion models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023.

[17] Yujia Zhang, Xiaoyang Wu, Yunhan Yang, Xianzhe Fan, Han Li, Yuechen Zhang, Zehao Huang, Naiyan Wang, and Hengshuang Zhao. Utonia: Toward one encoder for all point clouds. In *International Conference on Machine Learning (ICML)*, 2026.

[18] Tony Z. Zhao, Vikash Kumar, Sergey Levine, and Chelsea Finn. Learning fine-grained bimanual manipulation with low-cost hardware. In *Robotics: Science and Systems (RSS)*, 2023.