Individuality in the hive - Learning to embed lifetime social behavior of honey bees

Abstract

Honey bees are a popular model for complex social systems, in which global behavior emerges from the actions and interactions of thousands of individuals. While the average life of a bee is organized as a sequence of tasks roughly determined by age, there is substantial variation at the individual level. For example, young bees can become foragers early in life, depending on the colony's needs. Using a unique dataset containing lifetime trajectories of all individuals over multiple generations in two honey bee colonies, we propose a new temporal matrix factorization model that jointly learns the average developmental path and structured variations of individuals in the social network over their entire lives. Our method yields inherently interpretable embeddings that are biologically plausible and consistent over time, which allow one to compare individuals regardless of when, or in which colony, they lived. Our method provides a quantitative framework for understanding behavioral heterogeneity in complex social systems applicable in fields such as behavioral biology, social sciences, neuroscience, and information science.

1 Introduction

Animals living in large groups often coordinate their behaviors, resulting in emergent properties at the group level, from flocking birds to democratic elections. In most animal groups, the role an individual plays in this process is thought to be reflected in the way it interacts with group members. Technological advances have made it possible to track all individuals and their interactions in animal societies, ranging from social insects to primate groups (Mersch et al., 2013; Gernat et al., 2018; Mathis et al., 2018; Graving et al., 2019; Pereira et al., 2019). These datasets have unprecedented scale and complexity, but understanding these data has emerged as a new and challenging problem in itself (Pinter-Wollman et al., 2014; Krause et al., 2015; Brask et al., 2020).

A popular approach to understand high-dimensional data is to learn semantic embeddings (Frome et al., 2013; Asgari & Mofrad, 2015; Camacho-Collados & Pilehvar, 2018; Nelson et al., 2019). Such embeddings can be learned without supervision, are interpretable, and are useful for accomplishing downstream tasks. Individuals in animal societies can be described with semantic embeddings extracted from social interaction networks using matrix factorization methods. For example, in symmetric nonnegative matrix factorization (SymNMF), the dot products of any two animals' factor vectors reconstruct the interaction matrix (Wang et al. (2011); Shi et al. (2015), see Figure 1 a and b). If the embeddings allow us to predict relevant behavioral properties, they serve our understanding as *semantic* representations. However, in temporal settings, i.e. when the interaction matrices change over time, there is no straightforward extension of this algorithm. The interaction matrices at different time points can be factorized individually, but there is no guarantee that the embeddings stay semantically consistent over time, i.e. the accuracy or our prediction of relevant behavioral properties will deteriorate.

In living systems, interaction dynamics are highly variable; individuals differ in when they appear in the data, and how long they live. We may also have access to partial observations from non-overlapping groups, e.g., from different years with completely disjointed individuals. How do we learn embeddings that generalize to these observations and still provide insights into these individuals' functional roles? If animals take on roles determined by a common factor, such as age, how can we learn this dependency from independent observations?

Figure 1: For a daily snapshot of a temporal social network, symmetric NMF is able to extract meaningful factor representations of the individuals. Colors represent the interaction frequencies of all individuals (**a**). The age-based division of labor in a honey bee colony is clearly reflected in the two factors - same-aged individuals are likely to interact with each other (**b**). For long observation windows spanning several weeks, the social network changes drastically as individuals are born, die, and switch tasks (**c**). Here, we investigate how a representation of temporal networks can be extracted, such that the factors representing individuals can be meaningfully compared over time, and even across datasets.

Several approaches to extend NMF to temporal settings have been proposed in a variety of problem settings. Yu et al. (2016) and Mackevicius et al. (2019) propose a factorization method for time series analysis. Gauvin et al. (2014) focus on the analysis of communities that are determined by their temporal activity patterns. Jiao et al. (2017) consider the case of communities from graphs over time and enforce temporal consistency with an additional loss term. Yu et al. (2017) and Wang et al. (2017) represent networks as a function of time. However, to our knowledge, no method yet considers the case of entities following a shared temporal structure starting at the time they first appear in the dataset, or even in completely separate datasets.

We approach this question using honey bees, a popular model system for studying individual and collective behavior (Elekonich & Roberts, 2005). Bees allocate tasks across thousands of individuals without central control, using an age-based system: young bees care for brood, middle-aged bees perform within-nest labor, and old bees forage outside (Seeley, 1982; Johnson, 2010). Colonies are also organized spatially: brood is reared in the center, honey and pollen are stored at the periphery, and foragers offload nectar near the exit. Therefore, an individual's role can be inferred from its location, which we use to interpret the embeddings our method learns.

We propose jointly learning two meaningful representations of honey bee social behavior: a vector representation of the individuals' functional position in the social network on a given day, and a parametric representation of their lifetime trajectories through this functional embedding. We show that these representations can be learned in an unsupervised fashion, using only interaction matrices of the individuals over time. We analyze a dataset obtained by tracking thousands of individually marked honey bees in two colonies, at high temporal and spatial resolution over a total of 155 days, covering entire lifespans and multiple generations. We evaluate how well the embeddings capture the semantic differences of individual honey bee development by evaluating their predictiveness for different tasks and behaviorally relevant metrics.

Our method can be used to study dynamic groups in which individual units change their latent properties over time, and group composition is not fixed due to birth, death, or migration of individuals.

Figure 2: Overview of the method: We learn a parametric function describing the average life trajectory and a set of basis functions of individual variation (**a**). For each individual, a learned embedding captures to what extent the lifetime can be described by the basis functions (**b** and **c**). At each time point, factors can be extracted from the individual lifetime trajectories (**d**) to reconstruct the interaction affinity between individuals (**e**). Note that the lifetime trajectories are functions of the individuals' ages, while interactions can occur at any time point. An adversarial model restricts the embeddings $e_\phi(i, k)$ from encoding when, or where, the individuals emerged, such that the embeddings are semantically consistent for all individuals.

We provide a new perspective on how to extract fundamental factors that underlie behavioral and developmental plasticity in animal groups.

2 METHODS

2.1 TEMPORAL NMF ALGORITHM

SymNMF factorizes a matrix $\boldsymbol{A} \in \mathbb{R}_+^{N \times N}$ such that it can be approximated by the product $\boldsymbol{F}\boldsymbol{F}^T$, where $\boldsymbol{F} \in \mathbb{R}_+^{N \times M}$ and $M \ll N$:

$$\hat{\boldsymbol{F}} = \underset{\boldsymbol{F} \geq 0}{\operatorname{argmin}} \left\| \boldsymbol{A} - \boldsymbol{F}\boldsymbol{F}^T \right\|^2 \qquad \boldsymbol{A}_{i,j} \approx \boldsymbol{f}(i) \cdot \boldsymbol{f}(j)^T \qquad \boldsymbol{f}(i) = \boldsymbol{F}_{i,:} \quad \boldsymbol{f}(i) \in \mathbb{R}_+^M \quad (1)$$

Here we present a novel temporal NMF algorithm (*TNMF*) which extends SymNMF to temporal settings in which $\mathbf{A} \in \mathbb{R}_+^{T \times N \times N}$ changes over time t. We assume that the entities $i \in \{0, 1, \ldots, N\}$ follow to some extent a common trajectory depending on an observable property (for example the age of an individual). We represent an entity at a specific point in time t using a factor vector $\boldsymbol{f}^+(t, i) \in \mathbb{R}_+^M$ such that

$$\hat{\mathbf{A}}_{t,i,j} = \boldsymbol{f}^+(t, i) \cdot \boldsymbol{f}^+(t, j)^T \qquad \hat{\mathbf{A}} \in \mathbb{R}_+^{T \times N \times N} \quad \boldsymbol{f}^+(t, i) \in \mathbb{R}_+^M \quad (2)$$

In contrast to SymNMF, we do not directly factorize $\mathbf{A}_t$ to find the optimal factors that reconstruct the matrices. Instead, we decompose the problem into learning a common trajectory of factors $\boldsymbol{m}_\theta$ and structured variations from this trajectory $\boldsymbol{o}_{\phi,\omega}$:

$$\boldsymbol{f}(t, i) = \boldsymbol{m}_\theta(\boldsymbol{c}(t, i)) + \boldsymbol{o}_{\phi,\omega}(i, c(t, i)) \qquad \boldsymbol{f}^+(t, i) = \max(0, \boldsymbol{f}(t, i)) \quad (3)$$

$$c : \mathbb{N}^{T \times N} \to \mathbb{N} \quad m_\theta : \mathbb{N} \to \mathbb{R}_+^M \quad o_{\phi,\omega} : \mathbb{N}^{N \times T} \to \mathbb{R}^M$$

Note that in the simplest case $c(t, i) = t$, i.e. the trajectory of all entities is aligned with the temporal dimension t of $\mathbf{A}$. In social networks $c(t, i)$ could map to the age of individual i at time t.

We obtain $\boldsymbol{o}_{\phi,\omega}$ from a learned set of *individuality basis functions* b_{ω_k} (shared among all entities) that define a coordinate system of possible individual variations and *individuality embeddings* $\boldsymbol{e}_\phi$ which

capture to what extent each basis function applies to an entity:

$$\boldsymbol{o}_{\phi,\omega}(i, c(t,i)) = \sum_{k=0}^{N_k} \boldsymbol{e}_{\phi}(i,k) \cdot b_{\omega_k}(c(t,i)) \qquad e_{\phi} : \mathbb{N}^{N \times N_k} \to \mathbb{R}_+^M \quad b_{\omega_k} : \mathbb{N}^T \to \mathbb{R} \qquad (4)$$

where N_k is the number of learned basis functions.

We implement the functions $\boldsymbol{m}_{\theta}, b_{\omega_j}$ with small fully connected neural networks with non-linearities and several hidden layers. The parameters of these functions and the entities' embeddings e_{ϕ} are learned jointly using minibatch stochastic gradient descent:

$$\hat{\theta}, \hat{\omega}, \hat{\phi} = \operatorname*{argmin}_{\theta,\omega,\phi} \left\| \boldsymbol{A} - \hat{\boldsymbol{A}} \right\|^2 + R_{\boldsymbol{f}^-} \qquad R_{\boldsymbol{f}^-} = N^{-1}T^{-1} \sum_{i=0}^{N} \sum_{t=0}^{T} \max(0, -\boldsymbol{f}(t,i)) \qquad (5)$$

where the regularisation term $R_{\boldsymbol{f}^-}$ is added to encourage the model to learn positive values for all possible inputs because the gradient of the max operation in equation 3 is zero for negative values. Note that the non-negativity constraint is not strictly necessary, but we only consider the non-negative case in this work for consistency with prior work (Wang et al., 2011; Shi et al., 2015).

2.2 REGULARIZATION

We use several regularization terms to increase the interpretability and semantic consistency of the model. We encourage sparsity in both the number of used factors and individuality basis functions by adding L_1 penalties of the mean absolute magnitude of the factors $\boldsymbol{f}(t,i)$ and basis functions b_{ω_j} to the objective. We encourage individuals' lifetimes to be represented with a sparse embedding using an L_1 penalty of the learned *individuality embeddings* $\boldsymbol{e}_{\phi}$. We also introduce an adversarial loss term to encourage the model to learn embeddings that are semantically consistent over time, i.e. to only represent two entities that were present in the dataset at different times with different embeddings if this is strictly necessary to factorize the matrices **A**. We jointly train a discriminative network $d_{\psi}(e)$ that tries to classify the time of first occurrence of all entities based on their *individuality embeddings* $\boldsymbol{e}_{\phi}$. The cross-entropy loss of this model is added as a regularization term to equation 5 in a training regime similar to generative adversarial networks (Goodfellow et al., 2014). We found that the model performs well without these regularizations, but we are willing to accept a higher methodological complexity for the honey bee data if this allows us to achieve a better interpretability of the results. See appendix A.2.1 for more details and A.4 for an ablation study of the effect the individual regularization terms have on the results of the model.

2.3 DATA

2.3.1 HONEY BEE DATA

Two colonies of honey bees were continuously recorded over a total of 155 days. Each individual was manually tagged at emergence, so the date of birth is known for each bee. Locations and identities of all honey bees (N=9286) were extracted from the raw images and used to construct daily aggregated temporal interaction networks based on spatial proximity. We embed all individuals from these two datasets into a common space of *individuality embeddings* $\boldsymbol{e}_{\phi}$ and *factor vectors* $\boldsymbol{f}^+$. The dataset also contains labels that can be used in proxy tasks (see section 2.5) to quantify if the learned embeddings and factors are semantically meaningful and temporally consistent. See Table 1, and appendix A.1 for details. We publish the data together with this paper[1].

Table 1: Honey bee datasets

Dataset	Days	Individuals	Interaction pairs
BN16	56	2443	43 174 748
BN19	99	6843	167 366 381

2.3.2 SYNTHETIC DATA

Although some ground truth labels exist for the honey bee datasets (section 2.5), factorizing these data is still fundamentally an unsupervised learning problem. We generated synthetic datasets to evaluate whether the model can identify groups of individuals with common latent factors that determine their

---

[1]See Anonymous (2020) for dataset

interaction frequencies. We model a common lifetime trajectory and groups of individual variation using smoothed Gaussian random walks. We randomly assign individuals to a group with random times of emergence and disappearance from the data and compute interaction matrices by calculating the dot product of the factors of 1024 individuals for 100 simulated days. We then measure how well the *individuality embeddings* e_ϕ of a fitted model correspond to the truth groups using the adjusted mutual information score (Vinh et al., 2009). We evaluate the model on 128 different random synthetic datasets with increasing Gaussian noise levels in the interaction tensor. See appendix A.1.2 for more details on the generation process.

In both datasets, we define $c(t, i)$ as the time since the date of emergence of an individual i at time t (i.e., for the honey bees $c(t, i)$ is an individuals' age). This inductive bias allows the model to learn semantically consistent embeddings for individuals, even if their interaction partners are entirely disjointed.

2.4 BASELINE MODELS

Symmetric NMF: We compute the factors that optimally reconstruct the original interaction matrices using the standard symmetric NMF algorithm (Shi et al., 2015; Kuang et al., 2015), for each day separately, using the same number of factors as in the TNMF model.

Aligned symmetric NMF: We consider a simple extension of the standard SymNMF algorithm that aligns the factors to be more consistent over time. For each pair of subsequent days, we consider all combinatorial reorderings of the factors computed for the second day. For each reordering, we compute the mean L_2 distance of all individuals that were alive on both days. We then select the reordering that minimizes those pairwise L_2 distances and greedily continue with the next pair of days until all factors are aligned. Furthermore, we align the factors across colonies (where individuals cannot overlap) as follows: we run this algorithm for both datasets separately and align the resulting factors by first computing the mean embedding for all individuals grouped by their ages. As before, we now select from all combinatorial possibilities the reordering that minimizes the L_2 distance between the embeddings obtained from both datasets. See section A.5.1 for pseudo code.

Temporal NMF models: We evaluate variants of the temporal symmetric matrix factorization algorithms proposed by Jiao et al. (2017) and Yu et al. (2017). Because they did not consider non-overlapping datasets, we follow the procedure given above for the *Aligned symmetric NMF* to find the optimal reordering to align the factors obtained by applying models to the two datasets separately.

2.5 EVALUATION METRICS

Reconstruction: We measure how well the original interaction matrices **A** can be reconstructed from the factors. We do not require the model to reconstruct the interaction matrices as well as possible because we only use the reconstruction as a proxy objective to learn a meaningful representation. Still, a high reconstruction loss could indicate problems with the model, such as excessive regularization.

Consistency: We measure to what extent the adversarial model can constrain the information in the lifetime embeddings $e_\phi(i, k)$. For each model, we train a multinomial logistic regression model to predict the source cohort (date of birth) and calculate the area under the ROC curve ($\text{AUC}_{\text{cohort}}$) using a stratified 100-fold cross-validation with scikit-learn (Pedregosa et al., 2011). Because the baseline models do not learn a lifetime embedding, we instead compute how well the model can predict the cohort using the mean factor representation of the individuals over their lives. We define consistency as $1 - \text{AUC}_{\text{cohort}}$ of this linear model.

Mortality and Rhythmicity: We evaluate how well a linear regression model can predict the mortality (number of days until death) and circadian rhythmicity of the movement (R^2 score of a sine with a period of 24 h fitted to the velocity over a three day window). These metrics are strongly correlated with an individual's behavior (e.g. foragers exhibit strong circadian rhythms because they can only forage during the daytime; foragers also have a high risk of mortality). We follow the procedure given in Wild et al. (2020) and report the 100-fold cross-validated R^2 scores for these regression tasks.

For this data, we expect the factors f^+ and lifetime embeddings $e_\phi(i, k)$ to be semantically meaningful and temporally consistent if they reflect an individual's behavioral metrics (mortality and rhythmicity) and if they do not change strongly over time (measured in the consistency metric).

3 RESULTS

We implemented the model using PyTorch (Paszke et al., 2019) and trained it in minibatches of 128 individuals for 100 000 iterations with the Adam optimizer (Kingma & Ba, 2015). See appendix A.2.3 for the architecture of the learned functions, a precise description of the regularization losses and further hyperparameters. The code is publicly available [2].

3.1 SYNTHETIC DATA

We factorize the interaction matrices of the 128 synthetic datasets with varying levels of Gaussian noise using the TNMF model. We confirmed that our model converges in all datasets and evaluate whether we can distinguish the ground truth group assignments of the individuals. To that end, we extract the *individuality embeddings* e_ϕ from the models and measure how well they correspond to ground truth data using the adjusted mutual information (AMI) score. We find that for low levels of noise, our model can identify the truth group assignments with high accuracy, and are still significantly better than random assignments even at very high levels of noise (see figure 3). See appendix A.1.2 for more details on the synthetic datasets.

Figure 3: AMI score for increasing noise levels.

3.2 HONEY BEES

Factor trajectories and relationship to allocated tasks

Figure 4: **Left:** Mean lifetime trajectories according to m_θ. The model learns a sparse representation of the functional position of the individuals in the social network. f_1 mostly corresponds to young bees, and f_3 predominantly describes middle aged and older bees. Only factors with a mean magnitude of at least 0.01 are shown. Even though the model uses only these two factors, it is still expressive due to individual variability, as can be seen in randomly sampled individuals' lifetime trajectories. **Right:** The individual factors f^+ and the proportion of time the individuals spent on different nest substrates. This mapping can be used to interpret the biological meaning of the factors. For example f_1, which is associated with young bees (see Figure 4), correlates with time spent in the brood area. This is biologically consistent, because young bees tend to care for brood. Note that the factors have been divided by their standard deviation here for ease of comparability.

Average lifetime model: The model learns a sparse representation of the developmental trajectory of a honey bee in the space of social interactions. Only two factors are effectively used (they exceed the threshold value of 0.01). These factors show a clear trend over the life of a bee, indicating that the model captures the temporal aspects of the honey bee division of labor (See Figure 4).

Interpretability of factors: To understand the relationship between the factors and division of labor, we calculate how the factors map to the fraction of time an individual spent on the brood area, honey storage, or dance floor (where foragers aggregate). Time spent on these different substrates is a strong indicator of an individual's task. The factor f_1, which peaks at young age (Figure 4), correlates with

---

[2]anonymous.4open.science/r/b2b7e2fc-aa04-4cf8-85c7-646d8dc46400

the proportion of time spent in the brood area, while a high f_3 indicates increased time spent on the dance floor. Therefore, the model learned to map biologically relevant processes.

Individuality basis functions and lifetime embeddings: Due to the regularization of the embeddings, the model learns a sparse set of individuality basis functions. As encouraged by the model, most individuals can predominantly be described by a single basis function. That means that while each honey bee can collect a unique set of experiences, most can be described with a few *individuality blueprints* which are consistent across cohorts and colonies. In the context of honey bee division of labor, the basis functions are interpretable because the factors correspond to different task groups. For example, ω_{11} (accounting for $\approx 24.5\%$ of the individuals) describes workers that occupy nursing tasks over their lives, whereas ω_6 (accounting for $\approx 9.9\%$ of the individuals) describes workers that associate with in-hive duties such as honey storage later, but also stronger than average. As the lifetime embeddings e_ϕ only scale the magnitude of the basis functions, they can be interpreted in the same way. Individual lifetime trajectories in the factor space can be computed based on the mean lifetime trajectories (m_θ), individuality basis functions (b_ω) and lifetime embeddings (e_ϕ). See Figure 5 for examples of individual lifetime trajectories from workers that most strongly corresponded to the common individuality basis functions.

Figure 5: **a)** Magnitude of factor offsets for the five most common individuality basis functions over age (b_{ω_k}). The percentage of individuals that most strongly correspond to the individual basis functions are shown in the column titles. More than 59% of the individuals strongly correspond to one of the five basis functions shown here. **b)** Because the basis functions describe *individuality offsets* from the mean lifetime trajectory, it may be easier to interpret them by visualizing individual examples. For each of the basis functions (top row), we show a lifetime trajectory of an individual that corresponds to that basis function (bottom row). Note that individuals can die or disappear at any time (solid lines). The mean lifetime trajectories are shown as dotted lines in the background.

Evaluation: We verify that the learned representations of the individuals are meaningful (i.e., they relate to other properties of the individuals, not just their interaction matrices) and semantically consistent over time and across datasets using the metrics described in the section *Evaluation metrics*. We compare variants of our model with different adversarial loss scaling factors and factor L_1 regularizations, the baseline models, as well as the individuals' ages. We expect a good model to be temporally consistent and semantically meaningful. All variants of our model outperform the baselines in terms of the semantic metrics *Mortality* and *Rhythmicity*, and the adversarial loss term further increases the *Consistency* metric without negatively affecting the other metrics. A very strong adversarial regularization (see row with $\lambda_{\mathrm{adv}} = 1$ in Table 2) prevents the model from learning a good representation of the data. See Table 2 for an overview of the results. We also evaluate the tradeoff between the different metrics using a grid search over the hyperparameters (see appendix A.3).

Scalability: The functions m_θ and b_{ω_j} are learned neural networks with non-linearities. The objective is non-convex and we learn the model parameters using stochastic gradient descent. Optimization is therefore slower than the standard NMF algorithms that can be fitted using algorithms such as Alternating Least Squares (Kim et al., 2014). We found that the model converges faster if the reconstruction loss of the age based model m_θ is additionally minimized with the main objective in equation 5. Due to the minibatch training regime, our method should scale well in larger datasets. For datasets with longer time spans, minibatch sampling could also be extended over the temporal dimension. Small neural networks are sufficient to learn the functions m_θ and b_{ω_j}. Most of the runtime during training is spent on the matrix multiplication $f^+(t, i) \cdot f^+(t, j)^T$ and the corresponding backwards pass.

Table 2: Evaluation metrics

	Model				
Method	Variant	$\left\|\left\| \boldsymbol{A} - \hat{\boldsymbol{A}} \right\|\right\|^2 \downarrow$	Consistency ↑	Mortality ↑	Rhythmicity ↑
Age	-	-	-	0.02	0.20
SymNMF	Vanilla	**0.9**	0.18	0.01	0.02
SymNMF	Aligned	**0.9**	0.12	0.09	0.35
Jiao et al. (2017)	$\gamma = 0.1$	**0.9**	0.19	0.02	0.05
Jiao et al. (2017)	$\gamma = 1$	1.15	0.15	0.01	0.04
Yu et al. (2017)	$\beta = 0.01, d = 5$	1.59	0.03	0.17	0.06
TNMF	$\lambda_{\mathrm{adv}} = 0, \lambda_{\mathrm{f}} = 0.01$	1.26	0.18	0.10	0.40
TNMF	$\lambda_{\mathrm{adv}} = 0.1, \lambda_{\mathrm{f}} = 0.01$	1.28	0.35	**0.20**	**0.42**
TNMF	$\lambda_{\mathrm{adv}} = 1, \lambda_{\mathrm{f}} = 0.01$	1.88	**0.5**	0.03	0.25
TNMF	$\lambda_{\mathrm{adv}} = 0, \lambda_{\mathrm{f}} = 0.1$	1.31	0.19	0.09	0.38
TNMF	$\lambda_{\mathrm{adv}} = 0.1, \lambda_{\mathrm{f}} = 0.1$	1.33	**0.37**	0.10	**0.42**

Table 3: The evaluation metrics for TNMF and the baseline models described in section 2.5. See appendix A.2.3 and A.5 for descriptions of the hyperparameters used. The underlined model is used in all plots in the results section.

Clustering of lifetime embeddings

Figure 6: Clustering of lifetime embeddings: Most individuals strongly correspond to a single individuality basis function, making it easy to cluster their lifetime social behavior (i.e. each individual has a high value in a single dimension for their lifetime embedding). Because each cluster is strongly associated with a specific individuality basis function, and because each basis function is interpretable (Figure 4), these blueprints of lifetime development can also be intuitively understood and compared.

4 CONCLUSION

Temporal NMF factorizes temporal matrices with overlapping and even disjointed communities by learning a common embedding of the lifetime development of the individual entities. In the context of honey bees, this embedding is biologically meaningful, consistent over time, and shows that interaction patterns follow a common lifetime trajectory. Differences from the mean are described in a coordinate system of individual variability. Honey bee colonies are known to exhibit suites of correlated traits (Wray et al., 2011), but this method provides a perspective at the individual-level, and opens the possibility for understanding how colony-level traits respond to biotic and abiotic pressures. The basis functions are interpretable with respect to the division of labor within colonies, and offer a valuable tool to understand and quantify the influence of experimental manipulations (e.g. pesticides or increased predatory pressure) on an individual, even between experimental trials on completely different sets of individuals. While we applied our method to honey bees as an exemplary system with many individuals that exhibit an entangled, non-overlapping social structure, our method can be applied to any setting in which some interaction structure follows a general pattern over an observable (such as time) to detect structured deviations at the individual level.

REFERENCES

Anonymous. Individuality in the hive - Learning to embed lifetime social behavior of honey bees - Data, June 2020. URL https://zenodo.org/record/3862966. No Citation Data type: dataset.

Ehsaneddin Asgari and Mohammad R. K. Mofrad. Continuous Distributed Representation of Biological Sequences for Deep Proteomics and Genomics. *PLOS ONE*, 10(11):e0141287, November 2015. ISSN 1932-6203. doi: 10.1371/journal.pone.0141287. 00294 Publisher: Public Library of Science.

Josefine Bohr Brask, Samuel Ellis, and Darren P. Croft. Animal social networks – an introduction for complex systems scientists. *arXiv:2005.09598 [physics, q-bio]*, May 2020. arXiv: 2005.09598.

Jose Camacho-Collados and Mohammad Taher Pilehvar. From word to sense embeddings: a survey on vector representations of meaning. *Journal of Artificial Intelligence Research*, 63(1):743–788, September 2018. ISSN 1076-9757. doi: 10.1613/jair.1.11259. 00086.

Michelle M. Elekonich and Stephen P. Roberts. Honey bees as a model for understanding mechanisms of life history transitions. *Comparative Biochemistry and Physiology. Part A, Molecular & Integrative Physiology*, 141(4):362–371, August 2005. ISSN 1095-6433. doi: 10.1016/j.cbpb. 2005.04.014. 00050.

Andrea Frome, Greg S Corrado, Jon Shlens, Samy Bengio, Jeff Dean, Marc\textquotesingle Aurelio Ranzato, and Tomas Mikolov. DeViSE: A Deep Visual-Semantic Embedding Model. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26*, pp. 2121–2129. Curran Associates, Inc., 2013. 01437.

Laetitia Gauvin, André Panisson, and Ciro Cattuto. Detecting the Community Structure and Activity Patterns of Temporal Networks: A Non-Negative Tensor Factorization Approach. *PLoS ONE*, 9 (1), January 2014. ISSN 1932-6203. doi: 10.1371/journal.pone.0086028.

Tim Gernat, Vikyath D. Rao, Martin Middendorf, Harry Dankowicz, Nigel Goldenfeld, and Gene E. Robinson. Automated monitoring of behavior reveals bursty interaction patterns and rapid spreading dynamics in honeybee social networks. *Proceedings of the National Academy of Sciences*, 115 (7):1433–1438, February 2018. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.1713568115. 00000.

Ian J. Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative Adversarial Networks. *arXiv:1406.2661 [cs, stat]*, June 2014. arXiv: 1406.2661.

Jacob M Graving, Daniel Chae, Hemal Naik, Liang Li, Benjamin Koger, Blair R Costelloe, and Iain D Couzin. DeepPoseKit, a software toolkit for fast and robust animal pose estimation using deep learning. *eLife*, 8:e47994, October 2019. ISSN 2050-084X. doi: 10.7554/eLife.47994. Publisher: eLife Sciences Publications, Ltd.

Pengfei Jiao, Haodong Lyu, Xiaoming Li, Wei Yu, and Wenjun Wang. Temporal community detection based on symmetric nonnegative matrix factorization. *International Journal of Modern Physics B*, March 2017. doi: 10.1142/S0217979217501028. Publisher: World Scientific Publishing Company.

Brian R. Johnson. Division of labor in honeybees: form, function, and proximate mechanisms. *Behavioral Ecology and Sociobiology*, 64(3):305–316, January 2010. ISSN 0340-5443. doi: 10.1007/s00265-009-0874-7. 00077.

Jingu Kim, Yunlong He, and Haesun Park. Algorithms for nonnegative matrix and tensor factorizations: a unified view based on block coordinate descent framework. *Journal of Global Optimization*, 58(2):285–319, February 2014. ISSN 1573-2916. doi: 10.1007/s10898-013-0035-4.

Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. In Yoshua Bengio and Yann LeCun (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. 43006.

Jens Krause, Richard James, Daniel W. Franks, and Darren P. Croft. *Animal Social Networks*. Oxford University Press, 2015. ISBN 978-0-19-967904-1. Google-Books-ID: cuAUDAAAQBAJ.

Da Kuang, Sangwoon Yun, and Haesun Park. SymNMF: nonnegative low-rank approximation of a similarity matrix for graph clustering. *Journal of Global Optimization*, 62(3):545–574, July 2015. ISSN 1573-2916. doi: 10.1007/s10898-014-0247-2.

Emily L Mackevicius, Andrew H Bahle, Alex H Williams, Shijie Gu, Natalia I Denisenko, Mark S Goldman, and Michale S Fee. Unsupervised discovery of temporal sequences in high-dimensional datasets, with applications to neuroscience. *eLife*, 8:e38471, February 2019. ISSN 2050-084X. doi: 10.7554/eLife.38471. Publisher: eLife Sciences Publications, Ltd.

Alexander Mathis, Pranav Mamidanna, Kevin M. Cury, Taiga Abe, Venkatesh N. Murthy, Mackenzie Weygandt Mathis, and Matthias Bethge. DeepLabCut: markerless pose estimation of user-defined body parts with deep learning. *Nature Neuroscience*, 21(9):1281–1289, September 2018. ISSN 1097-6256, 1546-1726. doi: 10.1038/s41593-018-0209-y. 00001.

Danielle P. Mersch, Alessandro Crespi, and Laurent Keller. Tracking individuals shows spatial fidelity is a key regulator of ant social organization. *Science*, 340(6136):1090–1093, 2013. tex.ids: mersch_tracking_2013-1 publisher: American Association for the Advancement of Science.

Walter Nelson, Marinka Zitnik, Bo Wang, Jure Leskovec, Anna Goldenberg, and Roded Sharan. To Embed or Not: Network Embedding as a Paradigm in Computational Biology. *Frontiers in Genetics*, 10, 2019. ISSN 1664-8021. doi: 10.3389/fgene.2019.00381. Publisher: Frontiers.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. PyTorch: An Imperative Style, High-Performance Deep Learning Library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d\textquotesingle Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8026–8037. Curran Associates, Inc., 2019. 00646.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake Vanderplas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Édouard Duchesnay. Scikit-learn: Machine Learning in Python. *Journal of Machine Learning Research*, 12(Oct): 2825–2830, 2011. tex.ids: pedregosa_scikit-learn:_2011-1.

Talmo D. Pereira, Diego E. Aldarondo, Lindsay Willmore, Mikhail Kislin, Samuel S.-H. Wang, Mala Murthy, and Joshua W. Shaevitz. Fast animal pose estimation using deep neural networks. *Nature Methods*, 16(1):117–125, January 2019. ISSN 1548-7105. doi: 10.1038/s41592-018-0234-5. Number: 1 Publisher: Nature Publishing Group.

Noa Pinter-Wollman, E. A. Hobson, J. E. Smith, A. J. Edelman, D. Shizuka, S. de Silva, J. S. Waters, S. D. Prager, T. Sasaki, G. Wittemyer, J. Fewell, and D. B. McDonald. The dynamics of animal social networks: analytical, conceptual, and theoretical advances. *Behavioral Ecology*, 25(2): 242–255, March 2014. ISSN 1045-2249, 1465-7279. doi: 10.1093/beheco/art047.

Thomas D. Seeley. Adaptive significance of the age polyethism schedule in honeybee colonies. *Behavioral Ecology and Sociobiology*, 11(4):287–293, December 1982. ISSN 1432-0762. doi: 10.1007/BF00299306. 00000.

Xiaohua Shi, Hongtao Lu, Yangchen He, and Shan He. Community detection in social network with pairwisely constrained symmetric non-negative matrix factorization. In *2015 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM)*, pp. 541–546, August 2015. doi: 10.1145/2808797.2809383. 00023.

Nguyen Xuan Vinh, Julien Epps, and James Bailey. Information theoretic measures for clusterings comparison: is a correction for chance necessary? In *Proceedings of the 26th Annual International Conference on Machine Learning*, ICML '09, pp. 1073–1080, New York, NY, USA, June 2009. Association for Computing Machinery. ISBN 978-1-60558-516-1. doi: 10.1145/1553374.1553511.

Fei Wang, Tao Li, Xin Wang, Shenghuo Zhu, and Chris Ding. Community discovery using nonnegative matrix factorization. *Data Mining and Knowledge Discovery*, 22(3):493–521, May 2011. ISSN 1573-756X. doi: 10.1007/s10618-010-0181-y. 00336.

Wei Wang, Wenchao Yu, Wei Cheng, Charu C. Aggarwal, and Haifeng Chen. Link Prediction with Spatial and Temporal Consistency in Dynamic Networks. *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence*, pp. 3343–3349, 2017. 00038.

Benjamin Wild, David M. Dormagen, Adrian Zachariae, Michael L. Smith, Kirsten S. Traynor, Dirk Brockmann, Iain D. Couzin, and Tim Landgraf. Social networks predict the life and death of honey bees. *bioRxiv*, pp. 2020.05.06.076943, May 2020. doi: 10.1101/2020.05.06.076943. Publisher: Cold Spring Harbor Laboratory Section: New Results.

Margaret K. Wray, Heather R. Mattila, and Thomas D. Seeley. Collective personalities in honeybee colonies are linked to colony fitness. *Animal Behaviour*, 81(3):559–568, March 2011. ISSN 0003-3472. doi: 10.1016/j.anbehav.2010.11.027. 00170.

Hsiang-Fu Yu, Nikhil Rao, and Inderjit S Dhillon. Temporal Regularized Matrix Factorization for High-dimensional Time Series Prediction. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 847–855. Curran Associates, Inc., 2016.

Wenchao Yu, Charu C. Aggarwal, and Wei Wang. Temporally Factorized Network Modeling for Evolutionary Network Analysis. In *Proceedings of the Tenth ACM International Conference on Web Search and Data Mining*, WSDM '17, pp. 455–464, New York, NY, USA, February 2017. Association for Computing Machinery. ISBN 978-1-4503-4675-7. doi: 10.1145/3018661.3018669. 00034.