Improving Computational Efficiency in Visual Reinforcement Learning via Stored Embeddings

Abstract

Recent advances in off-policy deep reinforcement learning (RL) have led to impressive success in complex tasks from visual observations. Experience replay improves sample-efficiency by reusing experiences from the past, and convolutional neural networks (CNNs) process high-dimensional inputs effectively. However, such techniques demand high memory and computational bandwidth. In this paper, we present Stored Embeddings for Efficient Reinforcement Learning (SEER), a simple modification of existing off-policy RL methods, to address these computational and memory requirements. To reduce the computational overhead of gradient updates in CNNs, we freeze the lower layers of CNN encoders early in training due to early convergence of their parameters. Additionally, we reduce memory requirements by storing the low-dimensional latent vectors for experience replay instead of high-dimensional images, enabling an adaptive increase in the replay buffer capacity, a useful technique in constrained-memory settings. In our experiments, we show that SEER does not degrade the performance of RL agents while significantly saving computation and memory across a diverse set of DeepMind Control environments and Atari games. Finally, we show that SEER is useful for computation-efficient transfer learning in RL because lower layers of CNNs extract generalizable features, which can be used for different tasks and domains.

1 Introduction

Success stories of deep reinforcement learning (RL) from high dimensional inputs such as pixels or large spatial layouts include achieving superhuman performance on Atari games [32, 39, 1], grandmaster level in Starcraft II [51] and grasping a diverse set of objects with impressive success rates and generalization with robots in the real world [23]. Modern off-policy RL algorithms [32, 15, 11, 12, 41, 24, 26] have improved the sample-efficiency of agents that process high-dimensional pixel inputs with convolutional neural networks (CNNs; LeCun et al. 27) using past experiential data that is typically stored as raw observations in a replay buffer [30]. However, these methods demand high memory and computational bandwidth, which makes deep RL inaccessible in several scenarios, such as learning with much lighter on-device computation (e.g. mobile phones or other light-weight edge devices).

For compute- and memory-efficient deep learning, several strategies, such as network pruning [13, 8], quantization [13, 18] and freezing [54, 38] have been proposed in supervised learning and unsupervised learning for various purposes (see Section 2 for more details). In computer vision, Raghu et al. [38] and Brock et al. [5] showed that the computational cost of updating CNNs can be reduced by freezing lower layers earlier in training, and Han et al. [13] introduced a deep compression, which reduces the memory requirement of neural networks by producing a sparse network. In natural language processing, several approaches [47, 43] have studied improving the computational efficiency

of Transformers [50]. In deep RL, however, developing compute- and memory-efficient techniques has received relatively little attention despite their serious impact on the practicality of RL algorithms.

In this paper, we propose **S**tored **E**mbeddings for **E**fficient **R**einforcement Learning (SEER), a simple technique to reduce computational overhead and memory requirements that is compatible with various off-policy RL algorithms [10, 15, 41]. Our main idea is to freeze the lower layers of CNN encoders of RL agents early in training, which enables two key capabilities: (a) compute-efficiency: reducing the computational overhead of gradient updates in CNNs; (b) memory-efficiency: saving memory by storing the low-dimensional latent vectors to experience replay instead of high-dimensional images. Additionally, we leverage the memory-efficiency of SEER to adaptively increase replay capacity, resulting in improved sample-efficiency of off-policy RL algorithms in constrained-memory settings. SEER achieves these improvements without sacrificing performance due to early convergence of CNN encoders.

The main contributions of this paper are as follows:

- We present SEER, a compute- and memory-efficient technique that can be used in conjunction with most modern off-policy RL algorithms [10, 15].

- We show that SEER significantly reduces computation while matching the original performance of existing RL algorithms on both continuous control tasks from DeepMind Control Suite [46] and discrete control tasks from Atari games [2].

- We show that SEER improves the sample-efficiency of RL agents in constrained-memory settings by enabling an increased replay buffer capacity.

- Finally, we show that SEER is useful for compute-efficient transfer learning, highlighting the generality and transferability of encoder features.

2 Related work

Off-policy deep reinforcement learning. The most sample-efficient RL agents often use off-policy RL algorithms, a recipe for improving the agent's policy from experiences that may have been recorded with a different policy [45]. Off-policy RL algorithms are typically based on Q-Learning [52] which estimates the optimal value functions for the task at hand, while actor-critic based off-policy methods [29, 40, 10] are also commonly used. In this paper we will consider Deep Q-Networks (DQN; Mnih et al. 32),which combine the function approximation capability of deep convolutional neural networks (CNNs; LeCun et al. 27) with Q-Learning along with the usage of the experience replay buffer [30] as well as off-policy actor-critic methods [29, 10], which have been proposed for continuous control tasks.

Taking into account the learning ability of humans and practical limitations of wall clock time for deploying RL algorithms in the real world, particularly those that learn from raw high dimensional inputs such as pixels [23], the sample-inefficiency of off-policy RL algorithms has been a research topic of wide interest and importance [25, 22]. To address this, several improvements in pixel-based off-policy RL have been proposed recently: algorithmic improvements such as Rainbow [15] and its data-efficient versions [49]; using ensemble approaches based on bootstrapping [36, 28]; combining RL algorithms with auxiliary predictive, reconstruction and contrastive losses [19, 16, 35, 53, 41, 42]; using world models for auxiliary losses and/or synthetic rollouts [44, 9, 22, 12]; using data-augmentations on images [26, 24].

Compute-efficient techniques in machine learning. Most recent progress in deep learning and RL has relied heavily on the increased access to more powerful computational resources. To address this, Mattson et al. [31] presented MLPerf, a fair and precise ML benchmark to evaluate model training time on standard datasets, driving scalability alongside performance, following a recent focus on mitigating the computational cost of training ML models. Several techniques, such as pruning and quantization [13, 8, 4, 18, 47] have been developed to address compute and memory requirements. Raghu et al. [38] and Brock et al. [5] proposed freezing earlier layers to remove computationally expensive backward passes in supervised learning tasks, motivated by the bottom-up convergence of neural networks. This intuition was further extended to recurrent neural networks [33] and continual learning [37], and Yosinski et al. [54] study the transferability of frozen and fine-tuned CNN parameters. Fang et al. [7] store low-dimensional embeddings of input observations in scene memory for long-horizon tasks. We focus on the feasibility of freezing neural network layers in deep

(a) SEER before freezing.   (b) SEER after freezing.

Figure 1: Illustration of our framework. (a) Before the encoder is frozen, all forward and backward passes are active through the network, and we store images in the replay buffer. (b) After freezing, we store latent vectors in the replay buffer, and remove all forward and backward passes through the encoder. We remark that more samples can be stored in the replay buffer due to the relatively low dimensionality of the latent vector.

RL and show that this idea can improve the compute- and memory-efficiency of many off-policy algorithms using standard RL benchmarks.

3 Background

We formulate visual control task as a partially observable Markov decision process (POMDP; Sutton & Barto [45], Kaelbling et al. [21]). Formally, at each timestep t, the agent receives a high-dimensional observation o_t, which is an indirect representation of the state s_t, and chooses an action a_t based on its policy π. The environment returns a reward r_t and the agent transitions to the next observation o_{t+1}. The return $R_t = \sum_{k=0}^{\infty} \gamma^k r_{t+k}$ is the total accumulated rewards from timestep t with a discount factor $\gamma \in [0, 1)$. The goal of RL is to learn a policy π that maximizes the expected return over trajectories. By following the common practice in DQN [32], we handle the partial observability of environment using stacked input observations, which are processed through the convolutional layers of an encoder f_ψ.

Soft Actor-Critic. SAC [10] is an off-policy actor-critic method based on the maximum entropy RL framework [56], which encourages robustness to noise and exploration by maximizing a weighted objective of the reward and the policy entropy. To update the parameters, SAC alternates between a soft policy evaluation and a soft policy improvement. At the soft policy evaluation step, a soft Q-function, which is modeled as a neural network with parameters θ, is updated by minimizing the following soft Bellman residual:

$$\mathcal{L}_Q^{\text{SAC}}(\theta, \psi) = \mathbb{E}_{\tau_t \sim \mathcal{B}}\left[\left(Q_\theta(f_\psi(o_t), a_t) - r_t\right.\right.$$
$$\left.\left. - \gamma\mathbb{E}_{a_{t+1} \sim \pi_\phi}\left[Q_{\bar{\theta}}(f_{\bar{\psi}}(o_{t+1}), a_{t+1}) - \alpha\log\pi_\phi(a_{t+1}|f_\psi(o_{t+1}))\right]\right)^2\right],$$

where $\tau_t = (o_t, a_t, r_t, o_{t+1})$ is a transition, $\mathcal{B}$ is a replay buffer, $\bar{\theta}, \bar{\psi}$ are the delayed parameters, and α is a temperature parameter. At the soft policy improvement step, the policy π with its parameter ϕ is updated by minimizing the following objective:

$$\mathcal{L}_\pi^{\text{SAC}}(\phi) = \mathbb{E}_{o_t \sim \mathcal{B}, a_t \sim \pi_\phi}\left[\alpha\log\pi_\phi(a_t|f_\psi(o_t)) - Q_\theta(f_\psi(o_t), a_t)\right].$$

Here, the policy is modeled as a Gaussian with mean and covariance given by neural networks.

Deep Q-learning. DQN algorithm [32] learns a Q-function, which is modeled as a neural network with parameters θ, by minimizing the following Bellman residual:

$$\mathcal{L}^{\text{DQN}}(\theta, \psi) = \mathbb{E}_{\tau_t \sim \mathcal{B}}\left[\left(Q_\theta(f_\psi(o_t), a_t) - r_t - \gamma\max_a Q_{\bar{\theta}}(f_{\bar{\psi}}(o_{t+1}), a)\right)^2\right],$$

where $\tau_t = (o_t, a_t, r_t, o_{t+1})$ is a transition, $\mathcal{B}$ is a replay buffer, and $\bar{\theta}, \bar{\psi}$ are the delayed parameters. Rainbow DQN integrates several techniques, such as double Q-learning [48] and distributional DQN [3]. For exposition, we refer the reader to Hessel et al. [15] for more detailed explanations of Rainbow DQN.

4 SEER: Stored Embeddings for Efficient Reinforcement Learning

In this section, we present SEER: **S**tored **E**mbeddings for **E**fficient **R**einforcement Learning, which can be used in conjunction with most modern off-policy RL algorithms, such as SAC [10] and Rainbow DQN [15]. Our main idea is to freeze lower layers during training and only update higher layers, which eliminates the computational overhead of computing gradients and updating in lower layers. We additionally improve the memory-efficiency of off-policy RL algorithms by storing low-dimensional latent vectors in the replay buffer instead of high-dimensional pixel observations. See Figure 1 and Appendix B for more details of our method.

4.1 Freezing encoder for saving computation and memory

We process high-dimensional image input with an encoder f_ψ to obtain $z_t = f_\psi(o_t)$, which is used as input for policy π_ϕ and Q-function Q_θ as described in Section 3. In off-policy RL, we store transitions (o_t, a_t, o_{t+1}, r_t) in the replay buffer $\mathcal{B}$ to improve sample-efficiency by reusing experience from the past. However, processing high-dimensional image input o_t is computationally expensive. To handle this issue, after T_f updates, we freeze the parameters of encoder ψ, and only update the policy and Q-function. We remark that this simple technique can save computation without performance degradation because the encoder is modeled as deep convolutional neural networks, while a shallow MLP is used for policy and Q-function. Freezing lower layers of neural networks also has been investigated in supervised learning based on the observation that neural networks converge to their final representations *from the bottom-up*, i.e., lower layers converge very early in training [38]. For the first time, we show the feasibility and effectiveness of this idea in pixel-based reinforcement learning (see Figure 7a for supporting experimental results) and present solutions to its RL-specific implementation challenges.

Moreover, in order to save memory, we consider storing (compressed) latent vectors instead of high-dimensional image inputs. Specifically, each experience in $\mathcal{B}$ is replaced by the latent transition (z_t, a_t, z_{t+1}, r_t), and the replay capacity is increased to $\widehat{C}$ (see Section 4.2 for more details). Thereafter, for each subsequent environment interaction, the latent vectors $z_t = f_\psi(o_t)$ and $z_{t+1} = f_\psi(o_{t+1})$ are computed prior to storing (z_t, a_t, z_{t+1}, r_t) in $\mathcal{B}$. During agent updates, the sampled latent vectors are directly passed into the policy π_ϕ and Q-function Q_θ, bypassing the encoder convolutional layers. Since the agent samples and trains with latent vectors after freezing, we only store the latent vectors and avoid the need to maintain large image observations in $\mathcal{B}$.

4.2 Additional techniques and details for SEER

Data augmentations. Recently, various data augmentations [41, 26, 24] have provided large gains in the sample-efficiency of RL from pixel observations. However, SEER precludes data augmentations because we store the latent vector instead of the raw pixel observation. We find that the absence of data augmentations could decrease sample-efficiency in some cases, e.g., when the capacity of $\mathcal{B}$ is small. To mitigate this issue, we perform K number of different data augmentations for each input observation o_t and store K distinct latent vectors $\{z_t^k = f_\psi(\text{AUG}_k(o_t))|k = 1 \cdots K\}$. We find empirically that $K = 4$ achieves competitive performance to standard RL algorithms in most cases.

Increasing replay capacity. By storing the latent vector in the replay buffer, we can adaptively increase the capacity (i.e., total number of transitions), which is determined by the size difference between the input pixel observations and the latent vectors output by the encoder, with a few additional considerations. The new capacity of the replay buffer is

$$\widehat{C} = \left\lfloor C * \left(\tfrac{P}{4NKL} \right) \right\rfloor,$$

where C is the capacity of the original replay buffer, P is the size of the raw observation, L is the size of the latent vector, and K is the number of data augmentations. The number of encoders N is algorithm-specific and determines the number of distinct latent vectors encountered for each observation during training. For Q-learning algorithms $N = 1$, whereas for actor-critic algorithms $N = 2$ if the actor and critic each compute their own latent vectors. Some algorithms employ a target network for updating the Q-function [32, 10], but we use the same latent vectors for the online and target networks after freezing to avoid storing target latent vectors separately and find that tying their

Figure 2: Learning curves for CURL with and without SEER, where the x-axis shows estimated cumulative FLOPs. The dotted gray line denotes the encoder freezing time $t = T_f$. The solid line and shaded regions represent the mean and standard deviation, respectively, across five runs.

Figure 3: Learning curves for Rainbow with and without SEER, where the x-axis shows estimated cumulative FLOPs. The dotted gray line denotes the encoder freezing time $t = T_f$. The solid line and shaded regions represent the mean and standard deviation, respectively, across five runs.

parameters does not degrade performance.[1] The factor of 4 arises from the cost of saving floats for latent vectors, while raw pixel observations are saved as integer pixel values. We assume the memory required for actions and rewards is small and only consider only the memory used for observations.

5 Experimental results

We designed our experiments to answer the following questions:

- Can SEER reduce the computational overhead of various off-policy RL algorithms for both continuous (see Figure 2) and discrete (see Figure 3) control tasks?
- Can SEER reduce the memory consumption and improve the sample-efficiency of off-policy RL algorithms by adaptively increasing the buffer size (see Figure 4 and Figure 5)?
- Can SEER be useful for compute-efficient transfer learning (see Figure 7a)?
- Do CNN encoders of RL agents converge early in training (see Figure 8a and Figure 8b)?

5.1 Setups

Compute-efficiency. We first demonstrate the compute-efficiency of SEER on the DeepMind Control Suite (DMControl; Tassa et al. 46) and Atari games [2] benchmarks. DMControl is commonly used for benchmarking sample-efficiency for image-based continuous control methods. For DMControl experiments, we consider a state-of-the-art model-free RL method, which applies contrastive learning (CURL; Srinivas et al. 41) to SAC [10], using the image encoder architecture from SAC-AE [53].

---

[1]We remark that the higher layers of the target network are not tied to the online network after freezing.

	Scores at 45T FLOPs		Scores at 500K environment steps (0.07GB)	
	Rainbow	Rainbow+SEER	Rainbow	Rainbow+SEER
Alien	992.0 ± 152.7	$\mathbf{1172.6} \pm 239.0$	1038.4 ± 101.1	$\mathbf{1134.6} \pm 452.9$
Amidar	144.0 ± 27.4	$\mathbf{250.5} \pm 47.4$	121.0 ± 31.2	$\mathbf{165.3} \pm 47.6$
BankHeist	145.8 ± 61.2	$\mathbf{276.6} \pm 98.1$	$\mathbf{161.6} \pm 57.7$	151.8 ± 65.8
CrazyClimber	21580.0 ± 3514.6	$\mathbf{28066.0} \pm 4108.5$	10498.0 ± 1387.8	$\mathbf{17620.0} \pm 4418.4$
Krull	2799.5 ± 468.1	$\mathbf{3277.5} \pm 440.5$	2215.7 ± 336.9	$\mathbf{3069.2} \pm 377.6$
Qbert	2325.5 ± 1152.7	$\mathbf{4123.5} \pm 1385.5$	2430.5 ± 658.8	$\mathbf{3231.0} \pm 1567.6$
RoadRunner	10376.0 ± 2886.0	$\mathbf{11794.0} \pm 1745.3$	10612.0 ± 2059.3	$\mathbf{13064.0} \pm 2489.2$
Seaquest	402.8 ± 48.4	$\mathbf{561.2} \pm 100.5$	262.8 ± 19.1	$\mathbf{336.8} \pm 45.9$

Table 1: Scores on Atari games at 45T FLOPs corresponding to Figure 3 and at 500K environment interactions in the constrained-memory setup (0.07GB) corresponding to Figure 4. The results show the mean and standard deviation averaged five runs, and the best results are indicated in bold.

Figure 4: Comparison of the sample-efficiency of Rainbow with and without SEER in constrained-memory (0.07 GB) settings. The dotted gray line denotes the encoder freezing time $t = T_f$. The solid line and shaded regions represent the mean and standard deviation, respectively, across five runs.

For evaluation, we compare the computational efficiency of CURL with and without SEER by measuring floating point operations (FLOPs).[2] For discrete control tasks from Atari games, we perform similar experiments comparing the FLOPs required by Rainbow [15] with and without SEER. For all experiments, we use the hyperparameters and architecture of data-efficient Rainbow [49].

Memory efficiency. We showcase the memory efficiency of SEER with a set of constrained-memory experiments in DMControl. For Cartpole and Finger, the memory allocated for storing observations is constrained to 0.03 GB, corresponding to an initial replay buffer capacity $C = 1000$. For Reacher and Walker, the memory is constrained to 0.06 GB for an initial capacity of $C = 2000$. In this constrained-memory setting, we compare the sample-efficiency of CURL with and without SEER. As an upper bound, we also report the performance of CURL without memory constraints, i.e., the replay capacity is set to the number of training steps. For Atari experiments, the baseline agent is data-efficient Rainbow and the memory allocation is 0.07 GB, corresponding to initial replay capacity $C = 10000$. The other hyperparameters are the same as those in the compute-efficiency experiments.

The encoder architecture used for our experiments with CURL is used in Yarats et al. [53]. It consists of four convolutional layers with 3 x 3 kernels and 32 channels, with the ReLU activation applied after each conv layer. The architecture used for our Rainbow experiments is from van Hasselt et al. [49], consisting of a convolutional layer with 32 channels followed by a convolutional layer with 64 channels, both with 5 x 5 kernels and followed by a ReLU activation. For SEER, we freeze the first fully-connected layer in CURL experiments and the last convolutional layer of the encoder in Rainbow experiments. We present the best results across various values of the encoder freezing time T_f. See Appendices H and I for more hyperparameters and Appendix A for source code.

---

[2]We explain our procedure for counting the number of FLOPs in Appendix C.

(a) Cartpole-swingup   (b) Finger-spin   (c) Reacher-easy

(d) Walker-walk   (e) Cheetah-run

Figure 5: Comparison of the sample-efficiency of CURL with and without SEER in constrained-memory settings. The dotted gray line denotes the encoder freezing time $t = T_f$. The solid line and shaded regions represent the mean and standard deviation, respectively, across five runs.

5.2 Improving compute- and memory-efficiency

Experimental results in DMControl and Atari showcasing the computational efficiency of SEER are provided in Figures 2 and Figure 3. CURL and Rainbow both achieve higher performance within significantly fewer FLOPs when combined with SEER in DMControl and Atari, respectively. Additionally, Table 1 compares the performance of Rainbow with and without SEER at 45T (4.5e13) FLOPs. In particular, the average returns are improved from 145.8 to 276.6 compared to baseline Rainbow in BankHeist and from 2325.5 to 4123.5 in Qbert. We remark that SEER achieves better computational efficiency while maintaining the agent's final performance and comparable sample-efficiency (see Appendix F for corresponding figures).

Experimental results in Atari and DMControl showcasing the sample-efficiency of SEER in the constrained-memory setup are provided in Figure 4 and Figure 5. CURL and Rainbow achieve higher final performance and better sample-efficiency when combined with SEER in DMControl and Atari, respectively. Additionally, Table 1 compares the performance of unbounded memory Rainbow and constrained-memory (0.07 GB) Rainbow with and without SEER at 500K interactions. In particular, the average returns are improved from 10498.0 to 17620.0 compared to baseline Rainbow in CrazyClimber and from 2430.5 to 3231.0 in Qbert. Although we disentangle the computational and memory benefits of SEER in these experiments, we also highlight the computational gain of SEER in constrained-memory settings (effectively combining the benefits) in Appendix E.

5.3 Freezing larger convolutional encoders

We also verify the benefits of SEER using deeper convolutional encoders, which are widely used in a range of applications such as visual navigation tasks and favored for their superior generalization ability. Specifically, we follow the setup described in Section 5.1 and replace the SAC-AE architecture (4 convolutional layers) with the IMPALA architecture [6] (15 convolutional layers containing residual blocks [14]). Figure 5.3 shows the computational efficiency of SEER in Cartpole-swingup and Walker-walk with the IMPALA architecture. CURL achieves higher performance within significantly fewer FLOPs when combined with SEER.

(a) Cartpole-swingup   (b) Walker-walk

Figure 6: Learning curves using IMPALA architecture, where the x-axis shows estimated cumulative FLOPs. The dotted gray line denotes the encoder freezing time $t = T_f$. The solid line and shaded regions represent the mean and standard deviation, respectively, across three runs.

237 We remark that the gains due to SEER are more significant because computing and updating gradients
238 for large convolutional encoders is very computationally expensive.

5.4 Improving compute-efficiency in transfer settings

240 We demonstrate, as another application of our
241 method, that SEER increases compute-efficiency
242 in the transfer setting: utilizing the parameters
243 from Task A on unseen Tasks B. Specifically, we
244 train a CURL agent for 60K environment interac-
245 tions on Walker-stand; then, we only fine-tune the
246 policy and Q-functions on unseen tasks using net-
247 work parameters from Walker-stand. To save com-
248 putation, during fine-tuning, we freeze the encoder
249 parameters. Figure 7a shows the computational
250 gain of SEER in task transfer (i.e., Walker-stand
251 to Walker-walk similar to Yarats et al. [53]), and
252 domain transfer (i.e., Walker-stand to Hopper-hop)
253 is shown in Figure 7b. Due to the generality of

(a) To Walker-walk   (b) To Hopper-hop

Figure 7: Comparison of the computational efficiency of agents trained from scratch with CURL and agents trained with CURL+SEER from Walker-stand pretraining. The solid line and shaded regions represent the mean and standard deviation, respectively, across three runs.

254 CNN features, we can achieve this computational gain using a pretrained encoder. For the task transfer
255 setup, we provide more analysis on the number of frozen layers and freezing time hyperparameter T_f
256 in Appendix D.

5.5 Encoder analysis

258 In this subsection we present visualizations to verify that the neural networks employed in deep
259 reinforcement learning indeed converge *from the bottom up*, similar to those used in supervised
260 learning [38]. Figure 8a shows the spatial attention map for two Atari games and one DMControl
261 environment at various points during training. Similar to Laskin et al. [26] and Zagoruyko &
262 Komodakis [55], we compute the spatial attention map by mean-pooling the absolute values of
263 the activations along the channel dimension and follow with a 2-dimensional spatial softmax. The
264 attention map shows significant change in the first 20% of training, and remains relatively unchanged
265 thereafter, suggesting that the encoder converges to its final representations early in training. Figure
266 8b shows the SVCCA [38] score, a measure of neural network layer similarity, between a layer and
267 itself at time t and $t + 10K$. The convolutional layers of the encoder achieve high similarity scores
268 with themselves between time t and $t + 10K$, while the higher layers of the policy and Q-network
269 continue to change throughout training. In our DMControl environments we freeze the convolutional
270 layers and the first fully-connected layer of the policy and Q-network (denoted fc1). Although the
271 policy fc1 continues to change, the convergence of the Q-network fc1 and the encoder layers allow us
272 to achieve our computational and memory savings with minimal performance degradation.

6 Discussion and Limitations

274 In this paper, we proposed a technique that reduces computation requirements for visual reinforcement
275 learning, which we hope serves to facilitate a shift toward more compute-efficient RL. Here, we
276 highlight other techniques for reducing training time. For experimentation in computationally
277 intensive environments, Obando-Ceron & Castro [34] propose to use small- and medium-scale
278 experiments, which could reproduce the conclusions of the Rainbow DQN paper in Atari games.
279 For faster training time in a particular experiment, one can also lower the resolution of the input
280 images. In Figures 9a and 9b we show that reducing the resolution by a factor of 2, from 100×100 to
281 50×50 (and scaling crops appropriately) produces significant compute-efficiency gain in DeepMind
282 Control Suite without sacrificing performance, and emphasize that this technique can be combined
283 with SEER for further improved efficiency. We remark that the additional gain from SEER is larger
284 in more complex environments (e.g., Walker) where learning requires more steps. However, we
285 find that naive resolution reduction may not generally be applicable across environments and may
286 require domain knowledge in order to prevent excessive information loss. In Figures 9c and 9d we
287 show that resolution reduction by a factor of 2, from 84×84 to 42×42, results in noticeably worse
288 performance in several Atari games. In contrast, SEER successfully improves compute-efficiency

(a) Spatial attention map   (b) SVCCA similarity scores

Figure 8: Visualizations of encoder features throughout training. (a) Spatial attention map from CNN encoders. (b) SVCCA [38] similarity scores between each layer and itself at time t and $t + 10K$ throughout training for Walker-walk task.

(a) Cartpole-swingup   (b) Walker-walk   (c) Alien   (d) Amidar

Figure 9: Evaluation of the compute-efficiency of CURL ((a) and (b)) and Rainbow ((c) and (d)) with original and reduced (by factor of 2) resolutions. The solid line and shaded regions represent the mean and standard deviation, respectively, across five runs.

without sacrificing performance in these games (see Figure 3). Overall, SEER is highly generalizable across visual domains, and can be easily combined with other modifications.

A limitation of our work is the introduction of a hyperparameter for the freezing time t. While domain knowledge can be used to decide a reasonable range for t and reduce the search space, an interesting future direction would be to adaptively determine the freezing time using a metric of convergence. We also do not show the application of SEER to tasks which are more computationally expensive or even infeasible. We evaluate our method in DM Control and Atari because they are common RL benchmarks used in many recent works on RL from pixels, but the full impact of SEER may be more easily seen in very visually complex and challenging tasks such as 3D navigation. We do not foresee any negative societal impacts of our work, as it simply reduces training time of already existing algorithms.

7 Conclusion

We presented SEER, a simple but powerful modification of off-policy RL algorithms that significantly reduces computation and memory requirements while maintaining state-of-the-art performance. We leveraged the intuition that CNN encoders in deep RL converge to their final representations early in training to freeze the encoder and subsequently store latent vectors to save computation and memory. In our experimental results, we demonstrated the compute- and memory-efficiency of SEER in various DMControl environments and Atari games, and proposed a technique for compute-efficient transfer learning. With SEER, we highlight the potential for improvements in compute- and memory-efficiency in deep RL that can be made without sacrificing performance, in hopes of making deep RL more practical and accessible in the real world.

References

[1] Badia, Adrià Puigdomènech, Piot, Bilal, Kapturowski, Steven, Sprechmann, Pablo, Vitvitskyi, Alex, Guo, Daniel, and Blundell, Charles. Agent57: Outperforming the atari human benchmark. In *International Conference on Machine Learning*, 2020.

[2] Bellemare, Marc G, Naddaf, Yavar, Veness, Joel, and Bowling, Michael. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

[3] Bellemare, Marc G, Dabney, Will, and Munos, Rémi. A distributional perspective on reinforcement learning. In *International Conference on Machine Learning*, 2017.

[4] Blalock, Davis, Ortiz, Jose Javier Gonzalez, Frankle, Jonathan, and Guttag, John. What is the state of neural network pruning? *arXiv preprint arXiv:2003.03033*, 2020.

[5] Brock, Andrew, Lim, Theodore, Ritchie, James M, and Weston, Nick. Freezeout: Accelerate training by progressively freezing layers. *arXiv preprint arXiv:1706.04983*, 2017.

[6] Espeholt, Lasse, Soyer, Hubert, Munos, Remi, Simonyan, Karen, Mnih, Volodymir, Ward, Tom, Doron, Yotam, Firoiu, Vlad, Harley, Tim, Dunning, Iain, Legg, Shane, and Kavukcuoglu, Koray. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures, 2018.

[7] Fang, Kuan, Toshev, Alexander, Fei-Fei, Li, and Savarese, Silvio. Scene memory transformer for embodied agents in long-horizon tasks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 538–547, 2019.

[8] Frankle, Jonathan and Carbin, Michael. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2019.

[9] Ha, David and Schmidhuber, Jürgen. World models. *arXiv preprint arXiv:1803.10122*, 2018.

[10] Haarnoja, Tuomas, Zhou, Aurick, Abbeel, Pieter, and Levine, Sergey. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *International Conference on Machine Learning*, 2018.

[11] Hafner, Danijar, Lillicrap, Timothy, Fischer, Ian, Villegas, Ruben, Ha, David, Lee, Honglak, and Davidson, James. Learning latent dynamics for planning from pixels. In *International Conference on Machine Learning*, 2019.

[12] Hafner, Danijar, Lillicrap, Timothy, Ba, Jimmy, and Norouzi, Mohammad. Dream to control: Learning behaviors by latent imagination. In *International Conference on Learning Representations*, 2020.

[13] Han, Song, Mao, Huizi, and Dally, William J. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015.

[14] He, Kaiming, Zhang, Xiangyu, Ren, Shaoqing, and Sun, Jian. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

[15] Hessel, Matteo, Modayil, Joseph, Van Hasselt, Hado, Schaul, Tom, Ostrovski, Georg, Dabney, Will, Horgan, Dan, Piot, Bilal, Azar, Mohammad, and Silver, David. Rainbow: Combining improvements in deep reinforcement learning. In *AAAI Conference on Artificial Intelligence*, 2018.

[16] Higgins, Irina, Pal, Arka, Rusu, Andrei A, Matthey, Loic, Burgess, Christopher P, Pritzel, Alexander, Botvinick, Matthew, Blundell, Charles, and Lerchner, Alexander. Darla: Improving zero-shot transfer in reinforcement learning. In *International Conference on Machine Learning*, 2017.

[17] Huang, Gao, Liu, Shichen, Van der Maaten, Laurens, and Weinberger, Kilian Q. Condensenet: An efficient densenet using learned group convolutions. In *IEEE conference on computer vision and pattern recognition*, 2018.

[18] Iandola, Forrest N, Han, Song, Moskewicz, Matthew W, Ashraf, Khalid, Dally, William J, and Keutzer, Kurt. Squeezenet: Alexnet-level accuracy with 50x fewer parameters and< 0.5 mb model size. *arXiv preprint arXiv:1602.07360*, 2016.

[19] Jaderberg, Max, Mnih, Volodymyr, Czarnecki, Wojciech Marian, Schaul, Tom, Leibo, Joel Z, Silver, David, and Kavukcuoglu, Koray. Reinforcement learning with unsupervised auxiliary tasks. In *International Conference on Learning Representations*, 2017.

[20] Jeong, Jongheon and Shin, Jinwoo. Training cnns with selective allocation of channels. In *International Conference on Machine Learning*, 2019.

[21] Kaelbling, Leslie Pack, Littman, Michael L, and Cassandra, Anthony R. Planning and acting in partially observable stochastic domains. *Artificial intelligence*, 101(1-2):99–134, 1998.

[22] Kaiser, Lukasz, Babaeizadeh, Mohammad, Milos, Piotr, Osinski, Blazej, Campbell, Roy H, Czechowski, Konrad, Erhan, Dumitru, Finn, Chelsea, Kozakowski, Piotr, Levine, Sergey, et al. Model-based reinforcement learning for atari. In *International Conference on Learning Representations*, 2020.

[23] Kalashnikov, Dmitry, Irpan, Alex, Pastor, Peter, Ibarz, Julian, Herzog, Alexander, Jang, Eric, Quillen, Deirdre, Holly, Ethan, Kalakrishnan, Mrinal, Vanhoucke, Vincent, et al. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. In *Conference on Robot Learning*, 2018.

[24] Kostrikov, Ilya, Yarats, Denis, and Fergus, Rob. Image augmentation is all you need: Regularizing deep reinforcement learning from pixels. *arXiv preprint arXiv:2004.13649*, 2020.

[25] Lake, Brenden M, Ullman, Tomer D, Tenenbaum, Joshua B, and Gershman, Samuel J. Building machines that learn and think like people. *Behavioral and brain sciences*, 40, 2017.

[26] Laskin, Michael, Lee, Kimin, Stooke, Adam, Pinto, Lerrel, Abbeel, Pieter, and Srinivas, Aravind. Reinforcement learning with augmented data. In *Advances in neural information processing systems*, 2020.

[27] LeCun, Yann, Bottou, Léon, Bengio, Yoshua, and Haffner, Patrick. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

[28] Lee, Kimin, Laskin, Michael, Srinivas, Aravind, and Abbeel, Pieter. Sunrise: A simple unified framework for ensemble learning in deep reinforcement learning. *arXiv preprint arXiv:2007.04938*, 2020.

[29] Lillicrap, Timothy P, Hunt, Jonathan J, Pritzel, Alexander, Heess, Nicolas, Erez, Tom, Tassa, Yuval, Silver, David, and Wierstra, Daan. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.

[30] Lin, Long-Ji. Self-improving reactive agents based on reinforcement learning, planning and teaching. *Machine learning*, 8(3-4):293–321, 1992.

[31] Mattson, Peter, Cheng, Christine, Coleman, Cody, Diamos, Greg, Micikevicius, Paulius, Patterson, David, Tang, Hanlin, Wei, Gu-Yeon, Bailis, Peter, Bittorf, Victor, et al. Mlperf training benchmark. In *Conference on Machine Learning and Systems*, 2020.

[32] Mnih, Volodymyr, Kavukcuoglu, Koray, Silver, David, Rusu, Andrei A, Veness, Joel, Bellemare, Marc G, Graves, Alex, Riedmiller, Martin, Fidjeland, Andreas K, Ostrovski, Georg, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529, 2015.

[33] Morcos, Ari, Raghu, Maithra, and Bengio, Samy. Insights on representational similarity in neural networks with canonical correlation. In *Advances in Neural Information Processing Systems*, 2018.

[34] Obando-Ceron, Johan S and Castro, Pablo Samuel. Revisiting rainbow: Promoting more insightful and inclusive deep reinforcement learning research. *arXiv preprint arXiv:2011.14826*, 2020.

[35] Oord, Aaron van den, Li, Yazhe, and Vinyals, Oriol. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[36] Osband, Ian, Blundell, Charles, Pritzel, Alexander, and Van Roy, Benjamin. Deep exploration via bootstrapped dqn. In *Advances in neural information processing systems*, 2016.

[37] Pellegrini, Lorenzo, Graffieti, Gabrile, Lomonaco, Vincenzo, and Maltoni, Davide. Latent replay for real-time continual learning. *arXiv preprint arXiv:1912.01100*, 2019.

[38] Raghu, Maithra, Gilmer, Justin, Yosinski, Jason, and Sohl-Dickstein, Jascha. Svcca: Singular vector canonical correlation analysis for deep understanding and improvement. In *Advances in neural information processing systems*, 2017.

[39] Schrittwieser, Julian, Antonoglou, Ioannis, Hubert, Thomas, Simonyan, Karen, Sifre, Laurent, Schmitt, Simon, Guez, Arthur, Lockhart, Edward, Hassabis, Demis, Graepel, Thore, et al. Mastering atari, go, chess and shogi by planning with a learned model. *arXiv preprint arXiv:1911.08265*, 2019.

[40] Schulman, John, Chen, Xi, and Abbeel, Pieter. Equivalence between policy gradients and soft q-learning. *arXiv preprint arXiv:1704.06440*, 2017.

[41] Srinivas, Aravind, Laskin, Michael, and Abbeel, Pieter. Curl: Contrastive unsupervised representations for reinforcement learning. In *International Conference on Machine Learning*, 2020.

[42] Stooke, Adam, Lee, Kimin, Abbeel, Pieter, and Laskin, Michael. Decoupling representation learning from reinforcement learning, 2020.

[43] Sun, Zhiqing, Yu, Hongkun, Song, Xiaodan, Liu, Renjie, Yang, Yiming, and Zhou, Denny. Mobilebert: a compact task-agnostic bert for resource-limited devices. In *Annual Meeting of the Association for Computational Linguistics*, 2020.

[44] Sutton, Richard S. Dyna, an integrated architecture for learning, planning, and reacting. *ACM Sigart Bulletin*, 2(4):160–163, 1991.

[45] Sutton, Richard S and Barto, Andrew G. *Reinforcement learning: An introduction*. MIT Press, 2018.

[46] Tassa, Yuval, Doron, Yotam, Muldal, Alistair, Erez, Tom, Li, Yazhe, Casas, Diego de Las, Budden, David, Abdolmaleki, Abbas, Merel, Josh, Lefrancq, Andrew, et al. Deepmind control suite. *arXiv preprint arXiv:1801.00690*, 2018.

[47] Tay, Yi, Zhang, Aston, Tuan, Luu Anh, Rao, Jinfeng, Zhang, Shuai, Wang, Shuohang, Fu, Jie, and Hui, Siu Cheung. Lightweight and efficient neural natural language processing with quaternion networks. In *Annual Meeting of the Association for Computational Linguistics*, 2019.

[48] Van Hasselt, Hado, Guez, Arthur, and Silver, David. Deep reinforcement learning with double q-learning. In *AAAI Conference on Artificial Intelligence*, 2016.

[49] van Hasselt, Hado P, Hessel, Matteo, and Aslanides, John. When to use parametric models in reinforcement learning? In *Advances in Neural Information Processing Systems*, pp. 14322–14333, 2019.

[50] Vaswani, Ashish, Shazeer, Noam, Parmar, Niki, Uszkoreit, Jakob, Jones, Llion, Gomez, Aidan N, Kaiser, Łukasz, and Polosukhin, Illia. Attention is all you need. In *Advances in neural information processing systems*, 2017.

[51] Vinyals, Oriol, Babuschkin, Igor, Czarnecki, Wojciech M, Mathieu, Michaël, Dudzik, Andrew, Chung, Junyoung, Choi, David H, Powell, Richard, Ewalds, Timo, Georgiev, Petko, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782): 350–354, 2019.

[52] Watkins, Christopher JCH and Dayan, Peter. Q-learning. *Machine learning*, 8(3-4):279–292, 1992.

[53] Yarats, Denis, Zhang, Amy, Kostrikov, Ilya, Amos, Brandon, Pineau, Joelle, and Fergus, Rob. Improving sample efficiency in model-free reinforcement learning from images. *arXiv preprint arXiv:1910.01741*, 2019.

[54] Yosinski, Jason, Clune, Jeff, Bengio, Yoshua, and Lipson, Hod. How transferable are features in deep neural networks? In *Advances in neural information processing systems*, 2014.

[55] Zagoruyko, Sergey and Komodakis, Nikos. Paying more attention to attention: Improving the performance of convolutional neural networks via attention transfer. In *International Conference on Learning Representations*, 2017.

[56] Ziebart, Brian D. Modeling purposeful adaptive behavior with the principle of maximum causal entropy. 2010.