MocoSFL: enabling cross-client collaborative self-supervised learning

Abstract

Existing collaborative self-supervised learning (SSL) schemes are not suitable for cross-client applications because of their expensive computation and large local data requirements. To address these issues, we propose MocoSFL, a collaborative SSL framework based on Split Federated Learning (SFL) and Momentum Contrast (MoCo). In MocoSFL, the large backbone model is split into a small client-side model and a large server-side model, and only the small client-side model is processed locally on the client's local devices. MocoSFL is equipped with three components: (i) vector concatenation which enables the use of small batch size and reduces computation and memory requirements by orders of magnitude; (ii) feature sharing that helps achieve high accuracy regardless of the quality and volume of local data; (iii) frequent synchronization that helps achieve better non-IID performance because of smaller local model divergence. For a 1,000-client case with non-IID data (each client has data from 2 random classes of CIFAR-10), MocoSFL can achieve over 84% accuracy with ResNet-18 model. We further present TAResSFL module that significantly improves the resistance to privacy threats and communication overhead with small sacrifice in accuracy for a MocoSFL system. On a Raspberry Pi 4B device, the final scheme requires less than 1MB of memory and less than 40MB of communication and consumes less than 5W power. Thus, compared to the SoTA FL-based approach, MocoSFL has significant advantages in accuracy and practicality for cross-client applications.

1 Introduction

Collaborative learning schemes have become increasingly popular, as clients can train their own local models without sharing their private local data. Current collaborative learning applications mostly focus on supervised learning applications where labels are available (Hard et al., 2018; Roth et al., 2020). However, availability of fully-labeled data may not be practical since labeling can be difficult and requires expertise.

Federated learning (FL) (McMahan et al., 2017) is the most popular collaborative learning framework. One representative algorithm is **"FedAvg"**, where clients send their local copies of the model to the server and the server performs a weighted average operation (weight depends on the amount of data) to get a new global model. FL has achieved great success in supervised learning, and has benefited a wide range of applications such as next word prediction McMahan et al. (2017), visual object detection for safety Liu et al. (2020), recommendation Wu et al. (2022a;b), graph-based analysis Chen et al. (2022); Wu et al. (2022c), etc.

For collaborative learning on unlabeled data, prior works (Zhang et al., 2020; Zhuang et al., 2021; 2022) combine FL scheme with classic self-supervised learning (SSL) methods such as BYOL (Grill et al., 2020) and Moco (He et al., 2020). These methods can all achieve good performance when clients' data is Independent and Identically Distributed (IID) but suffer from poor performance in non-IID cases. Recently, Zhuang et al. (2022) mitigated non-IID performance drop with divergence-aware aggregation technique and provided the state-of-the-art (SoTA) accuracy performance using a combination of FL and different SSL methods.

However, these SoTA FL-SSL schemes are not practical for cross-client applications. **First**, FL-SSL imposes a significant computation overhead and large memory requirement on clients. This is because SSL requires a large backbone architecture (Chen et al., 2020a) together with a large batch size to

Figure 1: Challenges in FL-SSL schemes. (a) A large batch size is necessary to achieve good performance (KNN validation accuracy (Wu et al., 2018)) (b) Accuracy reduces with an increasing number of clients as a result of insufficient local data. (c) Hard negative keys are essential for the success of contrastive learning.

ensure good performance. As shown in Fig. 1(a), accuracy drops dramatically when batch size is low for both FL-SSL methods. **Second**, FL-SSL schemes fail to maintain a good accuracy with a large number of clients (cross-client cases), as shown in Fig. 1(b). For a fixed sized dataset, data per client decreases when the number of clients increases, resulting in immediate accuracy degradation. The drop in accuracy is mainly because of the failure to meet data size requirement in performing contrastive learning. Zhang et al. (2020); Wu et al. (2021) attempt to address this issue in FL-SSL with feature sharing. However, its overhead is quite high due to the extra feature memory synchronization in every training step.

To solve the above two challenges, we propose MocoSFL, a scheme that adopts Split Federated Learning (SFL) Thapa et al. (2020) as its core and incorporates the feature memory bank and momentum model designs of MoCo (He et al., 2020). We adopt the SFL scheme for three reasons: (i) SFL utilizes a smaller client-side model and so reduces the computation overhead and has lower memory consumption and model parameters; (ii) SFL's latent vector concatenation enables a large equivalent batch size for the centralized server-side model, making the use of micro-batch in training possible for clients, and thus reducing local memory; (iii) SFL's shared server-side model enables effective feature sharing, which removes the requirement of large amount of local data and makes the scheme possible for cross-client applications. As a result, our proposed MocoSFL can achieve good accuracy with ultra-low memory requirements and computation overhead and can support a very large number of clients. MocoSFL shows better non-IID performance since local model divergence is smaller. However, the use of SFL in the proposed MocoSFL brings extra communication overhead as well as data privacy concern. Thus, we present target-aware ResSFL (TAResSFL) module as an effective solution to mitigate these issues with small accuracy drop.

Our main contributions are:

- We identify two major challenges in FL-SSL schemes for cross-client applications. We find that having a large amount of data and a large batch size are two critical factors in achieving a good accuracy performance. However, meeting these requirements is not practical for cross-client applications.

- We propose solutions based on SFL for self-supervised learning. The resulting MocoSFL scheme uses small client-side model, latent vector concatenation, and feature sharing, which effectively solves two challenges, making it amenable for cross-client cases. For cross-silo case, because of less model divergence, the proposed MocoSFL can achieve even better performance than SoTA FL-SSL schemes under non-IID setting.

- To address communication overhead and privacy issues that are inherent to SFL, we propose target-domain-aware ResSFL (TAResSFL) that effectively reduces the resource overhead and mitigates model inversion attacks.

2 BACKGROUND

2.1 SELF-SUPERVISED LEARNING

To learn from unlabeled data, SSL schemes based on contrastive learning such as SimCLR Chen et al. (2020a), BYOL Grill et al. (2020), Simsiam Chen and He (2021) and MoCo He et al. (2020) have achieved great performance on popular benchmarks. We choose MoCo since it adopts a key-storing mechanism. Unlike other scheme uses other samples in the current data-batch as negative keys, MoCo uses previously computed positive keys as negative keys, and store current positive keys in the feature memory for future iterations. The key-storing mechanism results in a relatively smaller batch size requirement that is beneficial for reducing device memory and also makes it easy for feature sharing implementations for our proposed scheme. For the loss function, MoCo relies on InfoNCE loss Oord et al. (2018) as the contrastive mechanism to update its model parameters:

$$\mathcal{L}_{Q,K,N} = -log \frac{exp(Q \cdot K^+/\tau)}{exp(Q \cdot K^+/\tau) + \sum_{N \in M} exp(Q \cdot N/\tau)} \tag{1}$$

where query key Q and positive key K^+ are the output vectors of feeding two augmented views of the image to the online model and the momentum model, respectively. N denotes all negative keys in the feature memory M. Importantly, the success of MoCo scheme highly depends on the "hardness" of its negative keys (Kalantidis et al., 2020; Robinson et al., 2020). The "hardness" for a negative key N in the feature memory bank, can be determined by the similarity (inner-product) between Q_t (at step t) and N; the smaller the similarity, the better the "hardness". We notice the "hardness" of negative key N reduces quickly because model updates are in the direction of minimizing the InfoNCE loss in Eq. (1). As a result, MoCo adopts a slow-changing momentum model to produce consistent negative keys to add to the feature memory at the end of every training step and thereby maintains their hardness.

2.2 SPLIT FEDERATED LEARNING

SFL Thapa et al. (2020) is a recent collaborative learning scheme that focuses on high computation efficiency at the client side. It splits the original model architecture into two parts, the client-side model that contains all layers upto the "cut-layer" and the server-side model contains the remaining layers. We distribute copies of client-side model C_i to client-i's local devices and instantiate the server-side model S in a cloud server. To complete each training step, clients need to send the latent vectors (the output of client-side model) to the server, and the server processes latent vectors, computes the loss, performs backward propagation and returns the corresponding gradients to clients. Thapa et al. (2020) presents two possible ways for server to process latent vectors sent by clients. In this paper, we use SFL-V1 where the server concatenates all clients' latent vectors and processes them altogether, which makes the batch size equivalently larger at the server and benefits the contrastive learning. In contrast, in SFL-V2, client's latent vectors are processed sequentially in a first-come-first-serve manner that does not bring the "large batch" benefit. We provide details of SFL-V1 in Appendix A.2.

3 MOTIVATION

As mentioned in Section 1, the two challenges in extending FL-SSL to cross-client applications are high computing resource requirement and large data requirement.

3.1 HIGH COMPUTING RESOURCE REQUIREMENT

The first challenge is the computing resource requirement of training an SSL model locally. Using a compact backbone model may be accurate for supervised learning, but is not suitable for SSL as it has a much higher requirement on the model capacity. (Shi et al., 2021; Fang et al., 2021) show that using compact architectures like Mobilenet-V3 (Howard et al., 2019), EfficientNet Tan and Le (2019) suffers from over 10% accuracy degradation compared to a larger ResNet-18 architecture, while an even larger ResNet-50 model is over 15% better over ResNet-18. This means memory requirement for training an SSL model is very high. Using a smaller batch size reduces accuracy dramatically,

as shown in Fig. 1(a) and is not an option. A typical FL-SSL scheme costs 590.6 MFLOPs per image and over 1100MB of memory per client for a ResNet-18 with a batch size of 128, which is not practical.

3.2 LARGE DATA REQUIREMENT

The other major difficulty for FL-SSL to generalize to the cross-client case is the large data requirement. Especially for cross-client applications, the amount of data available to each client can be very limited and biased. For example, in a cross-silo medical application, a client could be a hospital with tons of data. In comparison, in a cross-client application, a client could be a patient who has limited number of data.

The root of the problem lies in the difficulty to find hard negative samples when clients do not have enough local data. When the number of data is larger, the chance for hard negative samples to be present becomes much higher. As a result, existing FL-SSL can only be successful for cross-silo applications where clients have large amount of data and can perform effective contrastive learning locally. As demonstrated in Fig. 1(b), we observe high accuracy when clients have 10K samples of data, while the accuracy drops quickly to around 30% when clients have only 500 samples.

Unfortunately, feature sharing Zhang et al. (2020); Wu et al. (2021) in FL-SSL schemes cannot solve the large data requirement because they update the shared feature memory less frequently because of significant communication overhead with each update. Since clients must synchronize their local copies[1] of the shared feature memory each time a minor change happens, in Zhang et al. (2020), new negative keys are added to the feature memory only once per epoch and they cannot keep a good "hardness" through the entire epoch. As a result, this ineffective feature sharing mechanism not only bring very limited ($\sim 1\%$) improvement in accuracy, but also fail to support a large number of clients.

4 METHOD

4.1 PROPOSED MOCOSFL

Our proposed MocoSFL is an innovative combination of SFL-V1 and MoCo-V2 (Chen et al., 2020b) as shown in Fig. 2. There are three key components to its design. **First**, in each training step, the latent vectors sent by all clients are concatenated before being processed by the server-side model. This helps achieve a large equivalent batch size in order to support mini-batch training. **Second**, we use a shared feature memory which is updated by positive keys contributed by all clients in every training step. **Third**, we improve the non-IID performance by using a higher synchronization frequency. Next, we will elaborate on how these three components in the proposed MocoSFL address the aforementioned two challenges in Section 4.2 and Section 4.3. Section 4.4 describes how MocoSFL achieves better non-IID performance and Section 4.5 addresses the privacy and communication issues of the proposed scheme.

4.2 REDUCE HARDWARE RESOURCE REQUIREMENT

Choice of SFL helps reduce computational overhead and memory consumption of the client because of the much smaller client-side model. For example, on a CIFAR-10 ResNet-18 model with a batch size of 128, a client-side model with 3 layers only costs 13.7% of the FLOPs compared to the entire model, and its memory cost is 227MB, merely one fourth of the entire model. Furthermore, we reduce the batch size to 1 (also known as "micro-batch"), to further reduce the memory consumption. The use of micro-batch in local model training is only possible thanks to the latent vector concatenation mechanism which basically aggregates latent vectors sent by all clients into a big batch before sending it to the server. In addition, in a micro-batch setting, we replace the batch normalization layer by group normalization Wu and He (2018) and weight standardization (Qiao et al., 2019) to gain better accuracy performance. In Fig. 3(b), we compare the computation and memory consumption of the proposed MocoSFL with the FL-SSL scheme. MocoSFL with cut-layer of 3 achieves $\sim 288\times$

---

[1]Since clients must hold a local copy of the shared memory to calculate the loss locally.

Figure 2: MocoSFL scheme. Three highlighted components are (1) latent vector concatenation, (2) shared feature memory, and (3) frequent synchronization.

reduction in memory consumption than FL-SSL and has 2%-10% higher accuracy. Details of accuracy evaluation are included in Section 5.1.

4.3 MITIGATE LARGE DATA REQUIREMENT

As indicated by (Kalantidis et al., 2020; Robinson et al., 2020), the "hardness" of a negative key N heavily depends on its similarity with the current query key Q, given that N and Q have different ground-truth labels. To evaluate the hardness of negative key N_0 residing in the feature memory, we use the similarity measure (inner-product) between N_0 and Q_t, a freshly calculated query key at time t. In FL-SSL with feature sharing, the negative key is only updated after a long period of time to reduce communication overhead. As a result, the hardness diminishes quickly. In contrast, MocoSFL frequently updates its feature memory to maintain a good hardness. At every training step, a freshly calculated positive key K_+ is added to the tail of the queue, and the oldest one is popped out.

However, frequent updates of feature memory is not enough to ensure a high level of hardness. We also find it is necessary to use a large batch size and a large feature memory. This finding agrees with the study in Bulat et al. (2021) and also explains the accuracy drop for a small batch size in FL-MocoV2 in Fig. 1(a). To illustrate this, we consider the total similarity measure at time t and make following assumptions: For the newest batch of negative keys $N_t = K_{t-1}$ of size B in the feature memory at time t, we assume the similarity measure between N_t and Q_t is a constant η for all t. We also assume similarity of every negative key batch in feature memory gets reduced by a constant factor γ ($\gamma < 1$) after each model update to represent the degradation caused by model updates. Thus, for a freshly computed query Q_t, its total similarity measure with negative keys in the feature memory can be represented as:

$$hardness = B\eta\gamma + B\eta\gamma^2 + ... + B\eta\gamma^{\lfloor M/B \rfloor} \tag{2}$$

$$= B\eta\gamma \times (\frac{1 - \gamma^{\lfloor M/B \rfloor}}{1 - \gamma}) \tag{3}$$

where B is the batch size and M is the feature memory size. We see that using a large batch size B is beneficial as it helps bring more fresh negative keys and maintain better hardness. Also, using a large feature memory (increasing M) can keep enough negative keys and contribute to a better total hardness. These two requirements are hard to meet in cross-client case because of the memory limit for FL-SSL schemes. Nonetheless, they can be easily fulfilled by MocoSFL because (1) latent vector concatenation enables a large equivalent batch size, and (2) feature memory hosted by the cloud server can be much larger.

Figure 3: (a) Proposed MocoSFL reduces model divergence. (b) Computation overhead (online model, inference) comparison between FL-SSL scheme and MocoSFL schemes. MocoSFL-N: client-side model has N layers.

4.4 IMPROVING NON-IID PERFORMANCE

We found that use of SFL results in fewer model parameters at the client side and hence smaller model divergence. Furthermore, introducing frequent synchronization in MocoSFL provides additional reduction in model divergence and greatly improves the non-IID performance. According to Zhang et al. (2020); Zhuang et al. (2021; 2022), the model divergence between two models is calculated as the L2 norm of the weight difference. Following the same idea, the total divergence measure of a cross-client system can be measured as the average weight divergence of local models w.r.t. the global model during training:

$$divergence = \frac{1}{EN_C} \sum_{e=1}^{E} \sum_{i=1}^{N_C} \sum_{l=1}^{L} ||W_{e,l}^i - W_{e,l}^*||_2 \tag{4}$$

where L denotes the number of layers for the client-side model, E denotes the total number of synchronizations, N_C denotes the number of clients, and l, e, i are the respective indices for L, E, N_C. W^* is the average of all client models W^i. MocoSFL reduces the model divergence with two orthogonal mechanisms. The first mechanism is the reduction of client-side model size, which directly results in a lower model divergence. As shown in Fig. 3(a), compared to FL-SSL scheme, MocoSFL has a much lower model divergence when the client-side model has less than 5 layers. The other mechanism is frequent model synchronization which helps reduce the model divergence. This is only possible in SFL because the communication overhead is affordable as the client-side model parameter size is much smaller. Fig. 3(a) also illustrates how model divergence further reduces as we increase the synchronization frequency.

4.5 IMPROVING PRIVACY AND COMMUNICATION OVERHEAD OF MOCOSFL

The proposed MocoSFL scheme is based on SFL and suffers from two issues – high communication overhead due to transmitting, and receiving latent vectors and vulnerability to Model Inversion Attack (MIA) Fredrikson et al. (2015), in which the server can reconstruct clients' raw inputs from latent vectors, making clients' data privacy questionable. (We leave the details of its threat model and working mechanism in Appendix A.3) To address the privacy and communication issues in MocoSFL, we propose Target-Aware-ResSFL (TAResSFL). TAResSFL extends ResSFL Li et al. (2022) for self-supervised learning through: (1) target-data-aware self-supervised pre-training, and (2) freezing feature extractor during SFL training. TAResSFL also utilizes the bottleneck layer design from ResSFL to reduce the communication overhead.

In ResSFL Li et al. (2022), the server performs pretraining to build up the resistance to MIA using data from a different domain since it does not have access to clients' data. And the pretrained resistant client-side model is transferred and gets fine-tuned using SFL. TAResSFL improves the pretraining step by making an assumption that the server can get access to a small subset ($<1\%$) of training data, together with large amount of data from another domain, and performs the pre-training using self-supervised learning. Such a pretrained client-side model has better transferability, and can thus stay frozen during SFL process, thereby avoiding the expensive fine-tuning. As shown in Fig. 4, we blend the source dataset X_s with a tiny subset of target dataset X_t during the feature extractor training. The attacker-aware training has the min-max form:

$$\min_{\boldsymbol{W}_C, \boldsymbol{W}_S} \max_{\boldsymbol{W}_G} \underbrace{\mathcal{L}(S(\boldsymbol{W}_S; C(\boldsymbol{W}_C; [\boldsymbol{x}_q, \boldsymbol{x}_{k+}])))}_{\text{Contrastive Loss}} + \lambda \underbrace{\mathbb{R}(G(\boldsymbol{W}_G; C(\boldsymbol{W}_C; \boldsymbol{x}_q)), \boldsymbol{x}_q)}_{\text{Inversion Score}} \tag{5}$$

where $\mathbb{R}$ in the inner maximization denoting similarity measure, for which we use the structural similarity index (SSIM) score Zhao et al. (2016). The inner maximization is used to train the simulated attack model G, whose function is reconstructing the activation back to a raw input state that is similar with ground-truth X_q. The outer minimization step goes in the direction of lowering contrastive loss, where the regularization term makes the model accurate as well as resistant to attack. These two steps are done alternatively to make the feature extractor resistant, and also be able to achieve good accuracy on the target dataset.

Fig. 4 presents the Target-aware ResSFL scheme. We use the resistant feature extractor to initialize client-side models during transfer step. Unlike ResSFL, here we freeze its parameter completely to maintain the resistance (as shown by the pink arrow in Fig. 4), since any parameter change can cause resistance drop. However, freezing brings a noticeable accuracy drop (see Table 4) of larger than 3%, even with the use of CIFAR-100 as source dataset if we perform the pre-training by only using the source dataset. But we observe if we blend the source data with a small portion of target data during pre-training, the accuracy can be greatly improved.

The freezing also greatly benefits hardware resource requirement since: (1) clients only need to transmit the latent vectors to the server and do not need to perform backward propagation using gradients from the server; (2) client-side model synchronization is not needed. As a result, MocoSFL with TAResSFL component achieves a $\sim 128\times$ (=5001.4/39.1) overall communication reduction compared to the original MocoSFL, as shown in Table 1. Here MocoSFL methods undergo 200 model synchronizations for 200 epochs while FL-SSL methods need 100 synchronizations (using the same setting in Zhuang et al. (2022)).

Communication Overhead	Weights (MB)	Latent Vectors (MB)	Total (MB)
FL-SSL methods Zhuang et al. (2022)	8269.2	0.0	8269.2 (1.0x)
MocoSFL-1	1.4	5000	5001.4 (3.0x)
MocoSFL-3	57.9	5000	5057.9 (3.1x)
MocoSFL-1+TAResSFL	0.0	39.1	39.1 (0.02x)
MocoSFL-3+TAResSFL	0.0	39.1	39.1 (0.02x)

Figure 4: Target-aware ResSFL scheme. (1) target domain data is used in pretraining. (2) client-side model is frozen during training.

Table 1: Communication overhead per client. (FL-SSL: 100 times of synchronization; MocoSFL: 200 times of synchronization)

5 EXPERIMENTAL RESULT

Experimental Setting. We simulate the multi-client MocoSFL scheme on a Linux machine, where we use different CPU threads to simulate different clients and a single RTX-3090 GPU to simulate the cloud server. We use ResNet-18 (He et al., 2016) for the majority of the experiments to better compare with existing SoTA (Zhuang et al., 2022). We use CIFAR-10 as the main dataset and also present results on CIFAR-100 and ImageNet 12-class subset as in Li et al. (2021). For the IID case, we assume the entire dataset is divided randomly and equally among all clients. For non-IID experiments, we only consider the pathological (aka. class-wise) non-IID distribution as in McMahan et al. (2017); Zhuang et al. (2022) where we assign 2 classes of CIFAR-10/ImageNet-12 data or 20 classes of CIFAR-100 data randomly to each client. We perform MocoSFL training for a total of 200 epochs, using SGD as the optimizer with an initial learning rate of 0.06. For accuracy performance evaluation, we adopt similar linear probe methods as in Grill et al. (2020); Zhuang et al. (2022), where we train a new linear classifier on the representation outputs generated by the MocoSFL backbone model (stays frozen). We include details of hyper-parameter choices and evaluations in Appendix A.1.

5.1 ACCURACY PERFORMANCE

Improved non-IID performance. Fig. 5 shows how using an increased synchronization frequency can significantly improve the non-IID accuracy. We present results for the cut-layer choices of 1 and

3 convolutional layers in the client-side model, represented by "MocoSFL-1" and "MocoSFL-3", respectively. We attribute the improved accuracy to be due to reduction in model divergence.

Comparison with FL-SSL. When synchronization frequency of the MocoSFL is set to 10 (per epoch), in cross-silo cases, our proposed MocoSFL achieves significantly better non-IID accuracy performance than Zhuang et al. (2022), except on the CIFAR-100 dataset when $N_C = 5$, as shown in Table 2.

Method	CIFAR-10		CIFAR-100	
	$N_C = 5$	$N_C = 20$	$N_C = 5$	$N_C = 20$
FL-BYOL (Zhuang et al., 2022)	83.34	75.77	61.78	52.78
MocoSFL-1 (ours)	87.81	85.84	58.78	57.80
MocoSFL-3 (ours)	87.29	85.32	57.70	57.52

Figure 5: Effect of increasing synchronization

Table 2: Non-IID performance comparison (linear probe accuracy)

Cross-client Performance. Our proposed MocoSFL can generalize from a cross-silo application to a cross-client application with 100, 200, and 1000 clients. Note that none of the previous FL-SSL methods can scale to such a large number of clients. For the hyper-parameter choices, we follow two principles introduced in Appendix A.1 – we let each client use a batch size of 1 and use the synchronization frequency of $f_S = (1000/N_C)$/epoch, and we set the client sampling ratio to $100/N_C$ to keep the same equivalent batch size at the server. The results are shown in Table 3. Note that each client has only 50 data samples in the 1000-client case. MocoSFL's accuracy for IID case keeps high when N_C increases from 100 to 1,000, though its accuracy drop by 1% for non-IID case. This small drop is because model divergence scales with number of clients as described in Section 4.4.

Table 3: MocoSFL cross-client accuracy performance (linear probe accuracy) of ResNet-18 model on CIFAR-10, CIFAR-100 and Imagenet-12 datasets with different number of clients N_C.

Method	Dataset	IID			non-IID		
		$N_C = 100$	$N_C = 200$	$N_C = 1000$	$N_C = 100$	$N_C = 200$	$N_C = 1000$
MocoSFL-1	CIFAR-10	87.29	87.38	87.51	87.71	87.39	86.46
	CIFAR-100	58.91	59.15	58.85	59.22	58.90	56.75
	ImageNet-12	92.02	91.73	91.76	92.24	91.44	91.28
MocoSFL-3	CIFAR-10	87.29	87.15	87.25	87.10	85.22	84.09
	CIFAR-100	58.41	58.30	58.80	58.69	58.59	56.88
	ImageNet-12	92.08	92.24	92.02	92.60	91.83	91.28

5.2 PRIVACY EVALUATION

Method	Metric	Target Data		
		0.0%	0.5%	1.0%
MocoSFL-1	Accuracy (%)	81.68	80.92	77.86
	Attack MSE	0.044	0.043	0.040
MocoSFL-3	Accuracy (%)	81.72	81.56	**84.81**
	Attack MSE	0.044	0.037	**0.038**

Table 4: Accuracy and MIA Resistance performance (Attack MSE) of MocoSFL+TAResSFL.

Figure 6: Visualization of MIA reconstructed images of using TAResSFL.

We use G to perform the attack; the architecture information of G is given in Appendix A.3. We assume the real-time attacker also uses an attack model with the same architecture as G. For the pre-training step, we use a fixed hyper-parameter choice of $\lambda = 2.0$ and a target SSIM level of 0.6 to limit the strength of regularization. We assume 0.0%, 0.5% and 1.0% of the target dataset CIFAR-10 is accessible, and we use CIFAR-100 dataset as source dataset to assist the pre-training. For the bottleneck layers, we use a pair of convolutional layers of 4 channels with stride of 2 (C4S2). We set the cut-layer choices to 1 and 3 and set the #clients to 100 for the training process.

Successful mitigation of MIA. As shown in Table 4, applying TAResSFL can achieve good accuracy performance (>81%) as well as high enough MIA resistance (>0.020) for most cases. Fig. 6 shows the visualization of MocoSFL-3 when 1.0% target data is available.

Larger cut-layer allows a better resistance-accuracy tradeoff. Using a smaller cut-layer of 1 seems a better choice in terms of accuracy and hardware requirement. However, as shown in Table 4, the accuracy and resistance tradeoff seems much better by using a cut-layer of 3. We believe that the extra client-side model complexity helps in the optimization of both accuracy and resistance objectives. So, applying TAResSFL with a larger cut-layer is a more favorable option.

5.3 HARDWARE DEMONSTRATION

Finally, we compare the total hardware resource cost of the proposed MocoSFL and "MocoSFL+TAResSFL" with synchronization frequency of 1/epoch for 200 epochs, and FL-SSL (Zhuang et al., 2022) in its original setting (500 local epochs per client, with synchronization frequency set to 1 per 5 local epochs). For MocoSFL, we use 1,000 clients with batch size of 1, cut-layer of 3. For FL-SSL, to achieve similar accuracy, we use 5 clients with batch size of 128. And we assume the data follows the default 2-class non-IID setting. For the hardware, we use a Raspberry Pi 4B equipped with 1GB memory as one real client and simulate all other clients on the PC.

Figure 7: Hardware resource comparison between FL-SSL and MocoSFL schemes.

Figure 8: Raspberry Pi setup. The Raspberry connects to the output via a measurement tool, and it communicates wirelessly with the server using websocket (TCP).

As shown in Fig. 7, for FL-SSL (that is only suitable for cross-silo situation), Raspberry Pi 4B is not powerful enough as it requires 7,949 TFLOPs for the entire training session (as each client needs to perform 500 local epochs on 10K data) and a memory consumption of 921 MB[2]. The communication overhead due to synchronization also costs around 8,269 MB. For "MocoSFL+TAResSFL", hardware requirements are reasonable since computation is only 734 GFLOPs and communication is around 39 MB in total. The memory consumption is a tiny 0.8 MB mostly due to the weight parameters since TAResSFL does not require local training. As shown in Fig. 8, our measurement using a USB multimeter shows the proposed MocoSFL running on the Raspberry Pi only draws power of 2.26W, in average, and consumes around 9,100 mAh on a 5V battery.

6 CONCLUSION

We propose MocoSFL, a collaborative SSL framework based on SFL. The proposed framework addresses hardware resource requirement at client-side by enabling small batch size training and computation offloading. It also relieves the large data requirement of local contrastive learning by enabling effective feature sharing. The proposed scheme can support large number of clients. More importantly, we achieve even better IID/non-IID performance with much lower hardware requirement than the SoTA FL-based SSL methods.

Broader Impact. In this work, we address two practical issues of hardware resource and large data requirement in collaborative SSL by using SFL. Compared to conventional approaches, the resulting MocoSFL scheme has significant advantage in affordability and is much easier to deploy. Apart from being environmental-friendly, MocoSFL makes it possible to reach more clients, especially for those in poverty or under-represented minorities, and thus eliminate potential human-bias and unfairness issues of the ML service.

---

[2]theoretic memory consumption for holding model parameters and intermediate data, actual CPU/GPU memory consumption can be higher considering memory for CUDA library/OS kernel

REFERENCES

Adrian Bulat, Enrique Sánchez-Lozano, and Georgios Tzimiropoulos. Improving memory banks for unsupervised learning with large mini-batch, consistency and hard negative mining. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 1695–1699. IEEE, 2021.

Chaochao Chen, Jun Zhou, Longfei Zheng, Huiwen Wu, Lingjuan Lyu, Jia Wu, Bingzhe Wu, Ziqi Liu, Li Wang, and Xiaolin Zheng. Vertically federated graph neural network for privacy-preserving node classification. In *IJCAI*, 2022.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pages 1597–1607. PMLR, 2020a.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 15750–15758, 2021.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020b.

Xinlei Chen, Saining Xie, and Kaiming He. An empirical study of training self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 9640–9649, 2021.

Zhiyuan Fang, Jianfeng Wang, Lijuan Wang, Lei Zhang, Yezhou Yang, and Zicheng Liu. Seed: Self-supervised distillation for visual representation. *arXiv preprint arXiv:2101.04731*, 2021.

Matt Fredrikson, Somesh Jha, and Thomas Ristenpart. Model inversion attacks that exploit confidence information and basic countermeasures. In *Proceedings of the 22nd ACM SIGSAC Conference on Computer and Communications Security*, pages 1322–1333, 2015.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. *Advances in Neural Information Processing Systems*, 33: 21271–21284, 2020.

Andrew Hard, Kanishka Rao, Rajiv Mathews, Swaroop Ramaswamy, Françoise Beaufays, Sean Augenstein, Hubert Eichner, Chloé Kiddon, and Daniel Ramage. Federated learning for mobile keyboard prediction. *arXiv preprint arXiv:1811.03604*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 770–778, 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 9729–9738, 2020.

Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 1314–1324, 2019.

Yannis Kalantidis, Mert Bulent Sariyildiz, Noe Pion, Philippe Weinzaepfel, and Diane Larlus. Hard negative mixing for contrastive learning. *Advances in Neural Information Processing Systems*, 33:21798–21809, 2020.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big transfer (bit): General visual representation learning. In *European conference on computer vision*, pages 491–507. Springer, 2020.

Jingtao Li, Adnan Siraj Rakin, Xing Chen, Zhezhi He, Deliang Fan, and Chaitali Chakrabarti. Ressfl: A resistance transfer framework for defending model inversion attack in split federated learning, 2022.

Yige Li, Xixiang Lyu, Nodens Koren, Lingjuan Lyu, Bo Li, and Xingjun Ma. Anti-backdoor learning: Training clean models on poisoned data. *Advances in Neural Information Processing Systems*, 34:14900–14912, 2021.

Yang Liu, Anbu Huang, Yun Luo, He Huang, Youzhi Liu, Yuanyuan Chen, Lican Feng, Tianjian Chen, Han Yu, and Qiang Yang. Fedvision: An online visual object detection platform powered by federated learning. In *IAAI*, 2020.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pages 1273–1282. PMLR, 2017.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Siyuan Qiao, Huiyu Wang, Chenxi Liu, Wei Shen, and Alan Yuille. Micro-batch training with batch-channel normalization and weight standardization. *arXiv preprint arXiv:1903.10520*, 2019.

Joshua David Robinson, Ching-Yao Chuang, Suvrit Sra, and Stefanie Jegelka. Contrastive learning with hard negative samples. In *International Conference on Learning Representations*, 2020.

Holger R Roth, Ken Chang, Praveer Singh, Nir Neumark, Wenqi Li, Vikash Gupta, Sharut Gupta, Liangqiong Qu, Alvin Ihsani, Bernardo C Bizzo, et al. Federated learning for breast density classification: A real-world implementation. In *Domain adaptation and representation transfer, and distributed and collaborative learning*, pages 181–191. Springer, 2020.

Haizhou Shi, Youcai Zhang, Siliang Tang, Wenjie Zhu, Yaqian Li, Yandong Guo, and Yueting Zhuang. On the efficacy of small self-supervised contrastive models without distillation signals. *arXiv preprint arXiv:2107.14762*, 2021.

Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International conference on machine learning*, pages 6105–6114. PMLR, 2019.

Chandra Thapa, Mahawaga Arachchige Pathum Chamikara, Seyit Camtepe, and Lichao Sun. Splitfed: When federated learning meets split learning. *arXiv preprint arXiv:2004.12088*, 2020.

Praneeth Vepakomma, Abhishek Singh, Otkrist Gupta, and Ramesh Raskar. Nopeek: Information leakage reduction to share activations in distributed deep learning. In *2020 International Conference on Data Mining Workshops (ICDMW)*, pages 933–942. IEEE, 2020.

Chuhan Wu, Fangzhao Wu, Lingjuan Lyu, Yongfeng Huang, and Xing Xie. Communication-efficient federated learning via knowledge distillation. *Nature communications*, 13(1):1–8, 2022a.

Chuhan Wu, Fangzhao Wu, Lingjuan Lyu, Yongfeng Huang, and Xing Xie. Fedctr: Federated native ad ctr prediction with cross platform user behavior data. *ACM Transactions on Intelligent Systems and Technology (TIST)*, 2022b.

Chuhan Wu, Fangzhao Wu, Lingjuan Lyu, Tao Qi, Yongfeng Huang, and Xing Xie. A federated graph neural network framework for privacy-preserving personalization. *Nature Communications*, 13(1):1–10, 2022c.

Yawen Wu, Dewen Zeng, Zhepeng Wang, Yi Sheng, Lei Yang, Alaina J James, Yiyu Shi, and Jingtong Hu. Federated contrastive learning for dermatological disease diagnosis via on-device learning. In *2021 IEEE/ACM International Conference On Computer Aided Design (ICCAD)*, pages 1–7. IEEE, 2021.

Yuxin Wu and Kaiming He. Group normalization. In *Proceedings of the European conference on computer vision (ECCV)*, pages 3–19, 2018.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 3733–3742, 2018.

Fengda Zhang, Kun Kuang, Zhaoyang You, Tao Shen, Jun Xiao, Yin Zhang, Chao Wu, Yueting Zhuang, and Xiaolin Li. Federated unsupervised representation learning. *arXiv preprint arXiv:2010.08982*, 2020.

Hang Zhao, Orazio Gallo, Iuri Frosio, and Jan Kautz. Loss functions for image restoration with neural networks. *IEEE Transactions on computational imaging*, 3(1):47–57, 2016.

Weiming Zhuang, Xin Gan, Yonggang Wen, Shuai Zhang, and Shuai Yi. Collaborative unsupervised visual representation learning from decentralized data. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4912–4921, 2021.

Weiming Zhuang, Yonggang Wen, and Shuai Zhang. Divergence-aware federated self-supervised learning. *arXiv preprint arXiv:2204.04385*, 2022.