DIL: DIRECT IMITATION LEARNING FOR PREFERENCE ALIGNMENT AND CONNECTIONS TO RLHF

ABSTRACT

This work studies the alignment of large language models with preference data. We address this problem from a novel imitation learning (IL) perspective. We establish a close connection between alignment and imitation learning, which shows that existing alignment objectives implicitly align model and preference data distributions. Built upon this connection, we develop a principled method DIL to directly optimize the imitation learning objective. DIL derives a surrogate objective for imitation learning with direct density ratio estimates, allowing effective use of preference data. DIL eliminates the need for complex adversarial training required by current IL methods, and optimizes the IL objective through simple density ratio estimation losses, achieving lightweight and efficient fine-tuning for large language models. This paper provides a unified imitation learning perspective on alignment, encompassing existing algorithms as special cases while naturally introducing new variants. Bridging IL and RLHF, DIL opens up new opportunities to improve alignment by leveraging tools from imitation learning. Extensive experiments demonstrate that DIL consistently and significantly outperforms off-the-shelf methods on various challenging benchmarks, including Open LLM Leaderboard and AlpacaEval 2.0. Code for DIL is available at https://github.com/Code-DIL/DIL.

1 INTRODUCTION

Aligning large language models (LLMs) with human preferences is essential to ensure that the responses generated by pre-trained LLMs align with human expectations (Bai et al., 2022; Ouyang et al., 2022; Stiennon et al., 2020). Recently, Reinforcement Learning from Human Feedback (RLHF) (Ouyang et al., 2022; Christiano et al., 2017) has become a widely adopted framework for fine-tuning language models according to human preference data. This approach typically involves training a reward model based on human feedback and subsequently employing reinforcement learning (RL) techniques, such as PPO (Schulman et al., 2017), to optimize model to maximize the reward signal.

RLHF has demonstrated impressive efficacy across a diverse range of tasks, from programming to creative writing. However, its dependence on two-step reinforcement learning presents challenges, such as computational inefficiency and instability during training (Engstrom et al., 2020; Rafailov et al., 2024). To mitigate these limitations, alternative one-step approaches such as direct preference optimization (DPO) and its variants have been proposed (Rafailov et al., 2024; Meng et al., 2024; Tajwar et al., 2024), which replace RLHF with supervised learning, eliminating the need for explicit reward modeling. Instead, they directly define an implicit reward based on the likelihood of preference data, resulting in significant gains in efficiency while preserving competitive performance.

While one-step direct preference optimization theoretically aims to discover identical optimal policies as RLHF, it and its variants fundamentally adhere to the reward maximization objective and are determined by parametric models such as the Bradley-Terry (BT) model (Bradley & Terry, 1952), making them prone to overfitting (Pal et al., 2024; Yuan et al., 2024b) and resulting in suboptimal alignment with preference data (Xu et al., 2024c; Wu et al., 2024). Some recent studies also show that the learned policy by DPO and its variants progressively focus on unlearning the rejected responses as shown in Figure 1, which in turn increases the likelihood of generating out-of-distribution responses, instead of chosen responses (Xu et al., 2024c), ultimately resulting in suboptimal performance, especially on reasoning and mathematical problem-solving (Pal et al., 2024; Yuan et al., 2024b;

Figure 1: The training dynamics of `DIL` and `SimPO` on LLama3 show that `DIL` exhibits the smallest decline in chosen likelihoods, while `SimPO` progressively focuses on unlearning the chosen responses.

Meng et al., 2024). This raises a fundamental and open research question: *Can we design preference optimization algorithms from a new perspective to address these shortcomings?*

In this paper, we provide answers to the research question stated above. We first revisit alignment from the perspective of imitation learning. In particular, we show that it is possible to characterize the objective functions of `RLHF` and `DPO` as special cases of a more general imitation learning objective expressed exclusively in terms of pairwise preferences. Built upon this insight, we propose a novel and principled imitation learning framework `DIL`, which not only learns an effective policy from preference data without relying on the BT assumption, but also achieves simple and fast fine-tuning. We provide deep insights into the expressive power of imitation learning (IL) for aligning large language models. Imitation learning (Ho & Ermon, 2016; Hussein et al., 2017; Osa et al., 2018) addresses the task of learning a policy from a set of human demonstrations, and has shown promise in domains such as robot control and autonomous driving, where manually specifying reward functions is challenging, but human demonstrations are available for imitation.

We begin by theoretically demonstrating that alignment with preference data closely resembles imitation learning and implicitly optimizes the same objective as imitation learning. We then leverage this insight to design new imitation learning objectives for better alignment. We introduce `DIL`, a simple, effective, and general framework for aligning models using preference data. While the motivation is straightforward, we face significant challenges when applying imitation learning to large language models. State-of-the-art imitation learning frameworks in reinforcement learning (RL) are more complex and computationally demanding than supervised fine-tuning (SFT) because of their reliance on inefficient and unstable adversarial or iterative training on separate discriminator and policy networks (Ho & Ermon, 2016; Kostrikov et al., 2019a; Sun & van der Schaar, 2024). These challenges make it impractical to directly apply current `IL` methods to align large language models.

To address these challenges, we first derive an equivalent surrogate objective with density ratio rewards for standard imitation learning, enabling the use of preference data. We then leverage the connection between imitation policy and density ratio reward estimation based on Bregman divergence minimization, allowing both the policy and the density ratio estimator to be represented by the same language model. This facilitates straightforward fine-tuning via simple classification losses, without the need for adversarial training. Notably, `DIL` offers a generalized framework, and we demonstrate that can accommodate essentially any density ratio estimation loss.

Our **primary technical contributions** are as follows: (i) We reconsider learning objectives such as `RLHF` and `DPO` for preference alignment from the perspective of distribution shift and provide a novel analysis towards explicit guidance and explanations for algorithm design. (ii) We propose `DIL`, a simple and generalized imitation learning framework for alignment with preference data. `DIL` eliminates the need for adversarial training and BT assumption, achieving simple and fast fine-tuning. (iii) Importantly, `DIL` enables a unified view on imitation learning on preference data and sheds light on connecting a rich literature on density ratio estimation to the designs of alignment with preference data. (iv) Empirically, we corroborate the effectiveness of `DIL` on widely-used benchmarks such as the Open LLM Leaderboard and AlpacaEval 2.0. The results demonstrate that `DIL` can significantly outperform previous methods. The effectiveness of `DIL` shows that in the context of alignment with preference data for large language models, imitation learning methods have been underexplored.

2   RELATED WORK

Reinforcement Learning from Human Feedback. `RLHF` has emerged as an effective approach for aligning LLM with human preferences (Christiano et al., 2017), whereby a model is initially trained

from human feedback supervised and subsequently serves as a reward model to enhance an agent's policy through reinforcement learning, such as Proximal Policy Optimization (PPO) (Schulman et al., 2017). RLHF is applicable on a broad range of tasks, including summarization (Stiennon et al., 2020), instruction-following(Ouyang et al., 2022), safety improvement (Bai et al., 2022) and truthfulness enhancement (Tian et al., 2023). Despite its effectiveness, RLHF possesses significant drawbacks, such as high complexity and unstable training processes compared to supervised learning.

Offline Preference Optimization. Recent literature highlights the inherent complexity of RLHF, prompting the search for more efficient offline alternatives. A significant advancement in this area is DPO (Rafailov et al., 2024). Unlike RLHF, which first learns an explicit reward model and then fits the policy to rewards, DPO bypasses this second approximation by directly learning a policy from collected data, without the need for reward modeling. Theoretically, DPO implicitly optimizes the same objective as existing RLHF algorithms (reward maximization with a KL-divergence constraint), but it is simpler to implement and more straightforward to train. Other alignment methods, such as IPO (Azar et al., 2024), KTO (Ethayarajh et al., 2024), and others (Zhao et al., 2023; Yuan et al., 2024a; Xu et al., 2024a; Hong et al., 2024; Meng et al., 2024), have also been proposed. In contrast, we rethink and design the alignment objective from a novel offline imitation learning perspective. We also show that well-known alignment methods, such as DPO and RLHF, can theoretically be viewed as fitting the chosen response distribution by minimizing the reverse KL divergence.

Imitation Learning. Classical imitation learning (IL) methods often frame IL as inverse reinforcement learning (IRL) to better utilize expert demonstrations (Sammut et al., 1992; Abbeel & Ng, 2004). In the seminal work (Ho & Ermon, 2016), the authors introduce GAIL, which bypasses inner-loop reinforcement learning (RL) by establishing a connection between IL and generative adversarial networks (GANs)(Goodfellow et al., 2020). GAIL and its successor, AIRL(Fu et al., 2018), have made significant strides. However, these online methods typically require substantial environmental interactions, limiting their deployment in cost-sensitive or safety-sensitive domains. To address this issue, recent work on offline IL (Garg et al., 2021) focuses on learning a reward function from offline datasets to understand and generalize the intentions underlying expert behavior. IQ-Learn (Garg et al., 2021) simplifies AIRL's game-theoretic objective over policy and reward functions into an optimization over the soft Q-function, which implicitly represents both reward and policy. DICE (Nachum et al., 2019; Kostrikov et al., 2019b; Lee et al., 2021) estimates discounted stationary distribution ratios and is agnostic to the type of behavior policies used to collect data.

Recently, some works (Sun & van der Schaar, 2024; Wulfmeier et al., 2024) have applied state-of-the-art IL methods, such as GAIL, AIRL, and IQ-Learn, to the alignment of large language models (LLMs). However, these approaches are overly complex for LLM alignment. Specifically, methods based on GAIL and AIRL involve inefficient and unstable adversarial learning, while DICE and IQ-Learn require training separate value and reward functions, resulting in significant computational costs and training instability due to their coupled training procedures. These challenges largely prevent the effective alignment of large language models using current IL algorithms. In this paper, we address these challenges by proposing DIL, a lightweight and efficient IL algorithm for alignment with preference data, eliminating the need for the complex training typically required in standard IL.

3 NOTATIONS AND PRELIMINARIES

Problem Setup. Let the text sequence $\mathbf{x} = [x_1, x_2, \ldots]$ denote the input prompt, and $\mathbf{y}_w = [y_1, y_2, \ldots]$ and $\mathbf{y}_l$ denote two responses, typically sampled from the same reference policy $\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$. The response pairs are then presented to human labelers (or an oracle) who express preferences for responses given the prompt, denoted as $\mathbf{y}_w \succ \mathbf{y}_l \mid \mathbf{x}$, where $\mathbf{y}_w$ and $\mathbf{y}_l$ denote preferred and dispreferred responses, respectively. The preference distribution is typically expressed as:

$$p\left(\mathbf{y}_w \succ \mathbf{y}_l \mid x\right) = g\left(r(\mathbf{x}, \mathbf{y}_w) - r\left(\mathbf{x}, \mathbf{y}_l\right)\right), \tag{1}$$

where $g : \mathbb{R} \to [0, 1]$ is a monotone non-decreasing function (with $g(z) = 1 - g(-z)$) that converts reward differences into winning probabilities. When g is the sigmoid function $\sigma(x) = \frac{1}{1+e^{-x}}$, we get the Bradley-Terry (BT) preference model (Bradley & Terry, 1952). Given dataset $\mathcal{D}$, containing feedback $(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l)$, the goal is to learn an LLM policy $\pi(\mathbf{y} \mid \mathbf{x})$ to align the preference data.

Reinforcement Learning from Human Feedback. Given the estimated reward function $r(\mathbf{x}, \mathbf{y})$, dictating the human preferences, RLHF fine-tunes policy π_θ by optimizing the following objective:

$$\max_{\pi_\theta} \mathbb{E}_{\mathbf{y} \sim \pi_\theta(\mathbf{y}|\mathbf{x})} \left[r(\mathbf{x}, \mathbf{y}) \right] - \beta \mathbb{D}_{\mathrm{KL}} \left[\pi_\theta(\mathbf{y} \mid \mathbf{x}) \| \pi_{\mathrm{ref}}(\mathbf{y} \mid \mathbf{x}) \right], \tag{2}$$

where $\beta > 0$ is an appropriate KL penalty coefficient. RLHF typically optimizes the above objective in Equation 2 using RL algorithms, such as PPO (Ouyang et al., 2022; Schulman et al., 2017). Although RLHF with PPO has achieved remarkable success, the training process of PPO is unstable because of the high variance of the estimates of the policy gradients (Engstrom et al., 2020).

Reward Modeling. One standard approach to reward modeling is to fit a reward function $r_\phi(\mathbf{x}, \mathbf{y})$ with the BT preference model in Equation (1). Specifically, the reward function $r_\phi(\mathbf{x}, \mathbf{y})$ can be estimated by maximizing the log-likelihood over preference feedback $(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l)$:

$$\mathcal{L}_{\mathrm{RM}}(\phi; \mathcal{D}) = \mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}} \left[-\log \sigma \left(r_\phi(\mathbf{x}, \mathbf{y}_w) - r_\phi(\mathbf{x}, \mathbf{y}_l) \right) \right]. \tag{3}$$

Supervised Fine-tuning (SFT). Given a demonstration dataset, the objective of SFT is minimizing the negative log-likelihood over the demonstration data as follows:

$$\mathcal{L}_{\mathrm{SFT}}(\theta; \mathcal{D}) = -\mathbb{E}_{(\mathbf{x}, \mathbf{y}) \sim \mathcal{D}}[\log \pi_\theta(\mathbf{y} \mid \mathbf{x})]. \tag{4}$$

SFT is equivalent to behavior cloning (BC) (Pomerleau, 1988), a classical offline imitation learning method that minimizes the forward KL divergence between the learned policy and data policy:

$$\min_{\theta} \mathrm{KL} \left(\pi_{\mathrm{data}}(\mathbf{y} \mid \mathbf{x}) \| \pi_\theta(\mathbf{y} \mid \mathbf{x}) \right) = -\mathbb{E}_{\pi_{\mathrm{data}}(\mathbf{y}|\mathbf{x})} \left[\log \pi_\theta(\mathbf{y} \mid \mathbf{x}) \right], \tag{5}$$

It is easy to see that the BC problem above shares the same optimal solutions as SFT in expectation.

Directed Preference Optimization. To simplify the optimization process of RLHF, DPO uses the log-likelihood of the learning policy to implicitly represent the reward function:

$$r_\theta(\mathbf{x}, \mathbf{y}) = \beta \left[\log \pi_\theta(\mathbf{y} \mid \mathbf{x}) - \log \pi_{\mathrm{ref}}(\mathbf{y} \mid \mathbf{x}) \right] + \beta \log Z_\theta(\mathbf{x}), \tag{6}$$

where $Z(\mathbf{x}) = \sum_{\mathbf{y}} \pi_{\mathrm{ref}}(\mathbf{y} \mid \mathbf{x}) \exp(r_\theta(\mathbf{x}, \mathbf{y})/\beta)$ is the partition function. By incorporating this reward into the BT model in Equation (1), DPO (Rafailov et al., 2024) objective enables the comparison of response pairs, facilitating the discrimination between preferred and dispreferred responses:

$$\mathcal{L}_{\mathrm{DPO}}(\theta; \mathcal{D}) = \mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}} \left[-\log \sigma (\beta \log \frac{\pi_\theta(\mathbf{y}_w \mid \mathbf{x})}{\pi_{\mathrm{ref}}(\mathbf{y}_w \mid \mathbf{x})} - \beta \log \frac{\pi_\theta(\mathbf{y}_l \mid \mathbf{x})}{\pi_{\mathrm{ref}}(\mathbf{y}_l \mid \mathbf{x})}) \right]. \tag{7}$$

Energy-based Models. Energy-based models (EBMs) (LeCun et al., 2006) define the distribution through an energy function. For $\mathbf{y} \in \mathbb{R}^D$, its probability density can be expressed as follows:

$$p_\theta(\mathbf{y}) = \exp(-E_\theta(\mathbf{y}))/Z_\theta(\mathbf{y}), \tag{8}$$

where $E_\theta(\mathbf{y}) : \mathbb{R}^D \to \mathbb{R}$ is the energy function, mapping the data point $\mathbf{y}$ to a scalar, and $Z_\theta(\mathbf{y}) = \sum_{\mathbf{y}} \exp(-E_\theta(\mathbf{y}))$ is the unknown normalization constant (Song & Kingma, 2021).

4 METHODOLOGY

4.1 RLHF IS A FORM OF IMITATION LEARNING

In this section, we connect RLHF to the imitation learning framework. We show that RLHF is a special case of imitation learning problem on the distribution chosen response with the reverse KL divergence. We start with a well-known connection between RL and EBM (Levine, 2018). Specifically, we firstly define the following energy-based policy (Levine, 2018; Haarnoja et al., 2017) with parameter ϕ:

$$\pi_\phi(\mathbf{y} \mid \mathbf{x}) = \pi_{\mathrm{ref}}(\mathbf{y} \mid \mathbf{x}) \exp \left(r_\phi(\mathbf{x}, \mathbf{y}) \right) / Z_\phi(\mathbf{x}), \tag{9}$$

where $Z_\phi(\mathbf{x}) = \sum_{\mathbf{y}} \pi_{\mathrm{ref}}(\mathbf{y} \mid \mathbf{x}) \exp(r_\phi(\mathbf{x}, \mathbf{y}))$. We can apply behavior cloning (BC) (Pomerleau, 1988), a classical and widely used imitation learning method, which frames the task as minimizing the KL divergence between the policy π_ϕ and the expert policy π_{chosen} generating the chosen response $\mathbf{y}_w$. IL learns the parameter ϕ such that the model distribution imitates the chosen data distribution:

$$\min_{\phi} \mathrm{KL} \left(\pi_{\mathrm{chosen}}(\mathbf{y} \mid \mathbf{x}) \| \pi_\phi(\mathbf{y} \mid \mathbf{x}) \right). \tag{10}$$

Minimizing the above forward KL divergence with the chosen responses on preference data gives us:

$$\min_{\boldsymbol{\phi}} \mathbb{E}_{(\mathbf{x},\mathbf{y}_w)\sim\mathcal{D}}[-\log \pi_{\text{ref}}(\mathbf{y}_w \mid \mathbf{x})\exp(r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_w))/Z_{\boldsymbol{\phi}}(\mathbf{x})] \Rightarrow$$

$$\min_{\boldsymbol{\phi}} \mathbb{E}_{(\mathbf{x},\mathbf{y}_w)\sim\mathcal{D}}\Big[-r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_w) + \log \sum_{\mathbf{y}} \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})\exp\big(r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y})\big) \Big]. \tag{11}$$

There are several options for sampling from the reference distribution $\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$. A choice that simplifies the above expression and yields RLHF in practice is $\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) = \frac{1}{2}\mathbb{I}(\mathcal{Y} = \mathbf{y}_l) + \frac{1}{2}\mathbb{I}(\mathcal{Y} = \mathbf{y}_w)$. In this case, the sample-based approximation of the second term gives us:

$$\min_{\boldsymbol{\phi}} \mathbb{E}_{(\mathbf{x},\mathbf{y}_w,\mathbf{y}_l)\sim\mathcal{D}}\Big[-r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_w) + \log\big(\exp(r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_w)) + \exp(r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_l))\big) \Big]$$

$$= \mathbb{E}_{(\mathbf{x},\mathbf{y}_w,\mathbf{y}_l)\sim\mathcal{D}}\Big[-\log \sigma\big(r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_w) - r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y}_l)\big) \Big]. \tag{12}$$

One can note that the above imitation learning loss over energy-based policy is exactly the same as the reward loss based on BT assumption in Equation (3) in RLHF. By optimizing this loss function, we can directly obtain the optimal energy-based policy in Equation (22). Unfortunately, even if we use the estimate $r_{\boldsymbol{\phi}}$, it is still expensive to estimate the partition function $Z_{\boldsymbol{\phi}}(\mathbf{x})$, making this representation difficult to use in practice and significantly higher inference cost (Rafailov et al., 2024). To address this problem, we can utilize the reverse knowledge distillation (Gu et al., 2024; Wang et al., 2018) which distills the optimal policy in Equation (22) into a analytical policy by using reverse KL divergence, which allows the policy to require only a single sample at inference time:

$$\min_{\boldsymbol{\theta}} \text{KL}\Big(\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})||\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})\exp(r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y})/\alpha)/Z_{\boldsymbol{\phi}}(\mathbf{x})\Big), \tag{13}$$

where α is the temperature hyperparameter in distillation process (Hinton, 2015). This gives the following RL loss after removing multiplicative and additive constants (Wang et al., 2018; Ghosh et al., 2020):

$$\mathcal{L}(\boldsymbol{\theta}) = -\mathbb{E}_{\pi_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x})}\big[r_{\boldsymbol{\phi}}(\mathbf{x},\mathbf{y})\big] + \alpha\text{KL}\big(\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})||\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})\big). \tag{14}$$

One can observe that this distillation objective exactly corresponds to RL objective in Equation (2).

In summary, we provide two key insights: (i) Reward learning in RLHF is equal to an imitation learning problem against the chosen responses, achieved by minimizing the forward KL divergence between π_{chosen} and $\pi_{\boldsymbol{\phi}}$ based on the EBMs shown in Equation (12). (ii) The RL step in RLHF can be interpreted as a reverse knowledge distillation process, where the imitated policy $\pi_{\boldsymbol{\phi}}$, based on EBMs, is distilled into a final analytical policy $\pi_{\boldsymbol{\theta}}$ by minimizing the reverse KL divergence in Equation (13), where the temperature determines the level of regularization of KL. Formally, we have:

Proposition 4.1. *Suppose the chosen response distribution $p(\mathbf{y} \mid \mathbf{x})$, the EBM $\pi_{\boldsymbol{\phi}}(\mathbf{y} \mid \mathbf{x})$, and the model $\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})$. KL-regularized RLHF with $\beta = 1$ can be viewed as the following problem:*

$$\min_{\pi_{\boldsymbol{\theta}}} \text{KL}(\pi_{\boldsymbol{\theta}} \parallel \pi_{\boldsymbol{\phi}}^*) \quad \text{s.t.} \quad \pi_{\boldsymbol{\phi}}^* = \arg\min_{\pi_{\boldsymbol{\phi}}} \text{KL}(\pi_{\text{chosen}} \parallel \pi_{\boldsymbol{\phi}}), \tag{15}$$

where $\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x}) = \pi_{\boldsymbol{\phi}}(\mathbf{y} \mid \mathbf{x}) = \pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})$ is the equilibrium.

Thus, conducting imitation learning on the chosen response corresponds to solving a standard KL-regularized RLHF problem and DPO, as DPO seeks to discover the same optimal policies as RLHF (Rafailov et al., 2024), as also shown in Section 4.5. In addition, we can observe that the upper level of the objective essentially optimizes a reverse KL (RKL) divergence $\text{KL}(\pi_{\boldsymbol{\theta}} \parallel \pi_{\text{chosen}})$ given $\pi_{\boldsymbol{\phi}}^* = \pi_{\text{chosen}}$, which is the optima achieved by the lower level objective.

An interesting question is why SFT, which directly optimizes forward KL (FKL) $\text{KL}(\pi_{\text{chosen}} \parallel \pi_{\boldsymbol{\theta}})$ in Equation (5), performs worse than RLHF and DPO. While theoretically, minimizing SFT and RLHF/DPO should lead to the same optimal solution $\pi_{\boldsymbol{\theta}}$, achieving this in practice requires full data coverage and infinite computations that are rarely met. Consequently, in practical settings, minimizing either KL divergence results in learned policies with distinct properties, as discussed in (Murphy, 2012; Tajwar et al., 2024). Specifically, FKL $\text{KL}(\pi_{\text{chosen}} \parallel \pi_{\boldsymbol{\theta}})$ promotes mass-covering behavior, whereas RKL $\text{KL}(\pi_{\boldsymbol{\theta}} \parallel \pi_{\text{chosen}})$ encourages mode-seeking behavior (Tajwar et al., 2024; Nachum et al., 2016; Agarwal et al., 2019). Mass-covering encourages assigning equal probability to all responses in the dataset, leading to an overestimation of the long tail of the target distribution, while mode-seeking concentrates the probability mass on specific high-reward regions. Thus, alignment focuses on generating a certain subset of high-reward responses, which is more effectively achieved by minimizing reverse KL, as theoretically shown by (Tajwar et al., 2024; Ji et al., 2024a).

Table 1: Summary of the variants of DIL with different h-functions for Bregman divergence: $\mathcal{L}_{\text{DIL}}(\boldsymbol{\theta}) = \mathbb{E}_{\pi_{\text{chosen}}(\mathbf{y}|\mathbf{x})}[\ell_1(f_{\boldsymbol{\theta}})] + \mathbb{E}_{\pi_{\text{rejected}}(\mathbf{y}|\mathbf{x})}[\ell_{-1}(f_{\boldsymbol{\theta}})]$ as a function of log ratio $f_{\boldsymbol{\theta}} = \log(\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})/\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}))$.

h-Bregman Density Ratio Estimation	h-function	$\ell_1(f_{\boldsymbol{\theta}})$	$\ell_{-1}(f_{\boldsymbol{\theta}})$
LSIF (Kanamori et al., 2009)	$h(r) = (r-1)^2/2$	$-e^{f_{\boldsymbol{\theta}}}$	$\frac{1}{2}e^{2f_{\boldsymbol{\theta}}}$
BCE (Hastie et al., 2009)	$h(r) = r \log r - (r+1)\log(r+1)$	$\log(1 + e^{-f_{\boldsymbol{\theta}}})$	$\log(1 + e^{f_{\boldsymbol{\theta}}})$
UKL (Nguyen et al., 2010)	$h(r) = r \log r - r$	$-f_{\boldsymbol{\theta}}$	$e^{f_{\boldsymbol{\theta}}}$

4.2 Direct Imitation Learning

In the last section, we revisit RLHF from the perspective of imitation learning. Our analysis explicitly suggests that RLHF is essentially optimized to align closely with the distribution of the chosen responses. The sample-based approximation of EBMs in RLHF results in a reward loss similar to the BT model, as shown in Equation (12). However, the BT assumption may not always hold true, as discussed in (Azar et al., 2024; Munos et al., 2023; Sun & van der Schaar, 2024). Based on the above insights, we propose a novel alignment method: DIL without the BT assumption. We directly formulate the objective of imitation learning as minimization the reverse KL-divergence between $\pi_{\boldsymbol{\theta}}$ and the unknown distribution of chosen response π_{chosen} (Kostrikov et al., 2019a; Fu et al., 2018):

$$\min_{\boldsymbol{\theta}} \mathcal{L}_{\text{DIL}}(\boldsymbol{\theta}) = \text{KL}\Big(\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \| \pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})\Big) = \mathbb{E}_{\pi_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x})}\Big[\log\Big(\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})/\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})\Big)\Big], \quad (16)$$

where we minimize RKL divergence, rather than FKL divergence as in SFT, as shown in Equation (5).

However, mode-seeking with reverse KL divergence is generally challenging. Directly optimizing Equation (16) does not effectively leverage chosen preference data, particularly since the data policy π_{chosen} is unknown. In the RL literature, these challenges have been addressed through adversarial training (Ho & Ermon, 2016; Fu et al., 2018). However, these methods involve learning a reward function using complex and unstable adversarial training, which is impractical for large models. In this paper, we propose a straightforward alternative that leverages preference data without learning a reward function via adversarial training. We reformulate the imitation learning objective as:

$$\max_{\boldsymbol{\theta}} \mathbb{E}_{\pi_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x})}\left[\log \frac{\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})} - \log \frac{\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})}\right] =$$
$$\mathbb{E}_{\pi_{\boldsymbol{\theta}}(\mathbf{y}|\mathbf{x})}\Big[\log r(\mathbf{x}, \mathbf{y})\Big] - \text{KL}\big(\pi_{\boldsymbol{\theta}}(\mathbf{y} \mid \mathbf{x}) \| \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})\big), \quad (17)$$

where $r(\mathbf{x}, \mathbf{y}) \triangleq \frac{\pi_{\text{chosen}}(\mathbf{y}|\mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}|\mathbf{x})}$ can be viewed as an auxiliary reward function. Equations (16) and (17) are equivalent by adding and subtracting the same term of $\log \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$ in the expectation.

Interestingly, we find that even when only preference data is available, this objective takes a form similar to that used in the RLHF objective in Equation (2). The primary difference lies in the reward being the estimated log density ratio, which is often not readily accessible in real-world applications. The optimization of this objective, involving the density ratio $r(\mathbf{x}, \mathbf{y})$, is not straightforward. In the next section, we will demonstrate how to efficiently optimize it by effectively utilizing offline human preference data.

Figure 2: The illustration of different losses (LSIF, BCE, and UKL), as shown in Table 1.

4.3 Density Ratio Reward Estimation

Before delving into the problem in Equation (17), we first describe how to calculate the auxiliary reward function in terms of the density ratio. In the tabular setting, we can directly compute $\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$ and $\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})$. However, in a high-dimensional language domain, estimating the densities separately and then calculating their ratio hardly works well due to error accumulation. In this paper, we choose to directly estimate the density ratio $\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})/\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$ based on the Bregman divergence (Sugiyama et al., 2012). Suppose $r^*(\mathbf{x}, \mathbf{y}) = \pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})/\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$ is the

target density ratio to be estimated with a parameterized discriminator r_ϕ. Then, we have:

$$\min_\phi D_h(r^* \| r_\phi) = \sum_{\mathbf{y}} \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) B_h(r^*(\mathbf{x}, \mathbf{y}) \| r_\phi(\mathbf{x}, \mathbf{y}))$$

$$= \sum_{\mathbf{y}} \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) \Big(h\big(r^*(\mathbf{x}, \mathbf{y})\big) - h\big(r_\phi(\mathbf{x}, \mathbf{y})\big) - \partial h\big(r_\phi(\mathbf{x}, \mathbf{y})\big)\big(r^*(\mathbf{x}, \mathbf{y}) - r_\phi(\mathbf{x}, \mathbf{y})\big) \Big), \quad (18)$$

where B_h is the data-level Bregman divergence. For a twice continuously differentiable convex function h with a bounded derivative ∂h, this divergence quantifies the discrepancy between two density-ratios. Subtracting a constant $\sum_{\mathbf{y}} \pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x}) h(r^*(\mathbf{x}, \mathbf{y}))$, we obtain (up to a constant):

$$\sum_{\mathbf{y}} \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) \Big[\partial h\big(r_\phi(\mathbf{x}, \mathbf{y})\big) r_\phi(\mathbf{x}, \mathbf{y}) - h\big(r_\phi(\mathbf{x}, \mathbf{y})\big) \Big] - \sum_{\mathbf{y}} \pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x}) \Big[\partial h\big(r_\phi(\mathbf{x}, \mathbf{y})\big) \Big]. \quad (19)$$

A few non-exhaustive examples of the Bregman divergence are Least-Squared Importance Fitting (LSIF) (Kanamori et al., 2009), Binary Cross Entropy (BCE) (Hastie et al., 2009), and the unbounded Kullback-Leibl (UKL) (Nguyen et al., 2010). For example, LSIF defines $h_{\text{LSIF}} = (r-1)^2/2$, which results in the following instance of Bregman divergence on the density ratio:

$$\min_\phi D_{h_{\text{LSIF}}}(r^* \| r_\phi) = \sum_{\mathbf{y}} \frac{1}{2} \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) r_\phi^2(\mathbf{x}, \mathbf{y}) - \pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x}) r_\phi(\mathbf{x}, \mathbf{y}) \quad (20)$$

In this case, sample-based approximation of Equation (20) leads to the following loss function:

$$\mathcal{L}(\phi; \mathcal{D}) = \mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}} \Big[\frac{1}{2} r_\phi^2(\mathbf{x}, \mathbf{y}_l) - r_\phi(\mathbf{x}, \mathbf{y}_w) \Big], \quad (21)$$

Here, we use the set of rejected responses $\mathbf{y}_l \sim \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$ to approximate the expectations under $\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$. It is acceptable to use the set of rejected responses y_l from the preference dataset $\mathcal{D}$ to approximate the expectations, as also demonstrated in (Ji et al., 2024b). We can even make use of both chosen responses and rejected responses to approximate these expectations. However, since our goal is to decrease the likelihood of rejected responses, we choose to use the rejected responses to approximate the expectations, and we find it empirically works well. Intuitively, the first term pushes the model to decrease the density ratio of the rejected response, while the second term increases the density ratio of the chosen response. In addition, this direct estimation approach with h Bregman divergence suggests a divergence family for density ratio estimation as shown in Table 1; see Appendix A for further discussion of other h functions such as BCE (Hastie et al., 2009) and UKL (Nguyen et al., 2010). We also empirically analyze the effect of using different objectives in Section 6.3. With the estimated density ratio reward, the surrogate imitation learning objective in Equation (17) can then be solved with any RL algorithms. However, this two-step process of RLHF is complex and often unstable. We provide a simpler approach that directly optimizes the imitation learning objective, bypassing the need for explicit RL training and density ratio estimation.

4.4 OPTIMIZATION

So far, we have observed that the RL-style objective in Equation (17), combined with density ratio estimation in Equation (21), can effectively leverage the preference dataset for imitation learning. However, this two-step process is a complex and often unstable procedure, first fitting a reward model that estimates density ratio, and then fine-tuning the language model policy using the RL-style objective in Equation (17). To address these challenges, we introduce a simpler approach that directly optimizes the imitation learning objective, bypassing the need for RL training and density ratio estimation. The core innovation lies in a specialized parameterization of the density ratio reward, which allows for direct extraction of the optimal policy, eliminating the need for an RL loop. Notably, the optimal policy in Equation (17) has a closed-form solution, as shown by (Rafailov et al., 2024):

$$\pi^*(\mathbf{y} \mid \mathbf{x}) = \frac{1}{Z(\mathbf{x})} \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) \exp\big(\log r^*(\mathbf{x}, \mathbf{y})\big), \quad (22)$$

where $Z(\mathbf{x}) = \sum_{\mathbf{y}} \pi_{\text{ref}}(\mathbf{y}|\mathbf{x}) \exp\big(\log r^*(\mathbf{x}, \mathbf{y})\big) = \sum_{\mathbf{y}} \pi_{\text{chosen}}(\mathbf{y}|\mathbf{x}) = 1$, meaning that the optimal $\pi^*(\mathbf{y}|\mathbf{x})$ is forced to be self-normalized! This characteristic, determined by the reward definition in Equation (17), is super beneficial as it allows our imitation learning to theoretically generalize to a broader class of loss functions beyond the pairwise BT preference model used in DPO. Taking the logarithm of both sides of Equation (22) and then with some algebra, we obtain the following:

$$\log \frac{\pi^*(\mathbf{y} \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})} = \log r^*(\mathbf{x}, \mathbf{y}), \quad (23)$$

where $r^*(\mathbf{x}, \mathbf{y})$ is the density ratio estimated by Equation (21) on the preference dataset. Since the optimal density ratio is now represented in terms of the optimal policy, as opposed to the discriminator model, we can explicitly derive the following maximum likelihood objective for a parameterized policy over the preference dataset (Rafailov et al., 2024). Analogous to the approach used for density ratio estimation and using a change of variables, we can formalize our `DIL` objective as follows:

$$\mathcal{L}_{\text{DIL}}(\boldsymbol{\theta}; \mathcal{D}) = \mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}} \Big[- \frac{\pi_{\boldsymbol{\theta}}(\mathbf{y}_w \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}_w \mid \mathbf{x})} + \frac{1}{2} \big(\frac{\pi_{\boldsymbol{\theta}}(\mathbf{y}_l \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}_l \mid \mathbf{x})} \big)^2 \Big], \tag{24}$$

where we directly fit an implicit density ratio in Equation (21) using an alternative parameterization in Equation (23). Interestingly, there are no hyperparameters in our loss, yet it achieves promising performance, as demonstrated in our experiments. Since our procedure is equivalent to fitting a reparametrized density ratio estimation model, it theoretically conducts imitation learning by minimizing RKL divergence against the unknown distribution of chosen response. Table 1 shows a family of objectives which meet the definition of Bregman divergence.

4.5 Discussion: DPO is a special case of DIL

In this section, we show that `DPO` can be also viewed as a special case of our framework by using contrastive predictive coding (`CPC`) (also as known as `InfoNCE`) (Oord et al., 2018) for density ratio estimation. Given the prompt distribution $p(\mathbf{x})$ and the conditional distribution of the chosen response $\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})$, we sample $\mathbf{x} \sim p(\mathbf{x}), \mathbf{y}_w \sim \pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})$, and $\mathbf{y}_l \sim \pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x})$. `CPC` optimizes:

$$\mathcal{L}_{\text{CPC}}(\boldsymbol{\phi}; \mathcal{D}) = -\mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}} \Big[\log \frac{\exp(f_{\boldsymbol{\phi}}(\mathbf{x}^\top \mathbf{y}_w)/\beta)}{\exp(f_{\boldsymbol{\phi}}(\mathbf{x}^\top \mathbf{y}_w/\beta)) + \exp(f_{\boldsymbol{\phi}}(\mathbf{x}^\top \mathbf{y}_l)/\beta)} \Big], \tag{25}$$

where $f_{\boldsymbol{\phi}} : \mathcal{X} \times \mathcal{Y} \mapsto \mathbb{R}$ is a parametric critic function. The optimal critic for this `CPC` with one negative sample satisfies the following (Zheng et al., 2024; Ma & Collins, 2018; Oord et al., 2018):

$$f^*(\mathbf{x}, \mathbf{y})/\beta = \log \frac{\pi_{\text{chosen}}(\mathbf{y} \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y} \mid \mathbf{x}) c(\mathbf{x})} = \log r^*(\mathbf{x}, \mathbf{y}) - \log c(\mathbf{x}), \tag{26}$$

where $c(\mathbf{x})$ is a function (Oord et al., 2018; Zheng et al., 2024), that depends on $\mathbf{x}$ but not $\mathbf{y}$. Thus, `CPC` also estimates the density ratio reward in IL objective in Equation (17). Similar to Section 4.4, by using the closed-form optimal policy in Equation (22) and using a change of variables, we have:

$$\mathcal{L}_{\text{DIL}}(\boldsymbol{\theta}; \mathcal{D}) = -\mathbb{E}_{(\mathbf{x}, \mathbf{y}_w, \mathbf{y}_l) \sim \mathcal{D}} \Big[\log \sigma \big(\beta \log \frac{\pi_{\boldsymbol{\theta}}(\mathbf{y}_w \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}_w \mid \mathbf{x})} - \beta \log \frac{\pi_{\boldsymbol{\theta}}(\mathbf{y}_l \mid \mathbf{x})}{\pi_{\text{ref}}(\mathbf{y}_l \mid \mathbf{x})} \big) \Big], \tag{27}$$

which is exactly the same objective as the well-known `DPO`. Thus, our framework enables us to reinterpret `DPO`. Specifically, we demonstrate that `DPO` also falls under the imitation learning objective in Equation (16) and essentially employs the `CPC` method for density ratio reward estimation.

5 Experiments

Datasets. We evaluate `DIL` on widely used datasets for preference fine-tuning: UltraFeedback Binarized dataset (Cui et al., 2023; Tunstall et al., 2023), Reddit TL;DR summarization dataset (Völske et al., 2017), Anthropic-HH dataset (Bai et al., 2022). The details of datasets are in Appendix B.1.

Tasks and Evaluation. Following previous work (Rafailov et al., 2024; Tunstall et al., 2023), we evaluate methods fine-tuned on the UltraFeedback Binarized dataset across tasks on Open LLM Leaderboard (Gao et al., 2023). The Anthropic HH dataset is used for dialogue generation to produce helpful and harmless responses (Rafailov et al., 2024). For summarization, we use the Reddit TL;DR dataset. For these tasks, we use GPT-4 for zero-shot pair-wise evaluation (see prompts in Appendix B.2). The task and evaluation details are also given in Appendix B.2.

Models. For summarization and dialogue generation tasks, we use `Pythia-2.8b` (Biderman et al., 2023) as our base model, with the model after SFT serving as a reference model, following (Rafailov et al., 2024). For fine-tuning on UltraFeedback Binarized dataset, we use `Mistral-7B-Base` (Tunstall et al., 2023) and `Llama3-8b-SFT` used in (Meng et al., 2024) as our base models.

Baselines and Implementation. We compare `DIL` with the following state-of-the-art baselines: DPO (Rafailov et al., 2024), f-DPO (Wang et al., 2024a), IPO (Azar et al., 2024), SLiC (Zhao

Table 2: Evaluation results on various tasks from the Huggingface Open Leaderboard and AlpacaEval 2. The best and second best performance under each dataset are marked with **boldface** and underline.

Model (↓) / Benchmark (→)		MMLU-PRO	BBH	MUSR	MATH	GSM8K	ARC	AlpacaEval 2	Arena-Hard
Mistral-7B-Base	SFT	**27.58**	41.26	41.93	2.34	28.13	58.28	6.2	1.3
	DPO (Rafailov et al., 2024)	26.73	43.27	43.65	1.36	21.76	61.26	12.5	10.4
	SLiC (Zhao et al., 2023)	26.52	42.33	33.74	1.38	**33.74**	55.38	8.9	7.3
	f-DPO (Wang et al., 2024a)	25.96	42.39	37.82	1.27	23.18	62.01	8.5	8.1
	IPO (Azar et al., 2024)	25.87	40.59	42.15	1.25	27.14	60.84	9.4	7.5
	CPO (Xu et al., 2024b)	27.04	42.05	42.15	2.15	33.06	57.00	8.9	5.8
	SimPO (Meng et al., 2024)	27.13	42.94	39.68	2.49	22.21	62.63	20.8	16.6
	DIL w/ LSIF	27.44	**43.59**	**44.05**	**2.95**	32.19	**63.31**	**21.7**	**18.3**
LLama3-8B-Base	SFT	31.00	46.16	41.27	3.70	46.32	60.15	4.6	3.3
	DPO (Rafailov et al., 2024)	31.58	47.80	40.48	4.53	38.67	64.42	15.5	15.9
	SLiC (Zhao et al., 2023)	31.11	46.53	40.55	3.92	48.82	61.43	13.7	10.3
	f-DPO (Wang et al., 2024a)	30.85	47.55	40.39	4.37	39.55	62.85	9.5	14.2
	IPO (Azar et al., 2024)	30.18	46.78	39.58	4.02	22.67	62.88	14.2	17.8
	CPO (Xu et al., 2024b)	30.95	47.17	41.59	4.25	46.93	61.69	8.10	11.6
	SimPO (Meng et al., 2024)	31.61	48.38	40.08	4.23	31.54	65.19	20.3	23.4
	DIL w/ LSIF	**32.22**	**48.78**	**42.75**	**4.68**	**48.98**	**65.37**	**24.0**	**25.6**

Table 3: Win rates computed by GPT-4 against the SFT generated response and the chosen responses on the TL;DR summarization and Anthropic-HH datasets on Pythia-2.8b. The best and second best performance under each dataset are marked with **boldface** and underline, respectively.

Dataset (→)	TL;DR Summarization			Anthropic-HH		
Method (↓) / Metric (→)	vs SFT	vs Chosen	Average	vs SFT	vs Chosen	Average
DPO (Rafailov et al., 2024)	71.22	57.58	64.40	69.32	59.35	64.34
SLiC (Zhao et al., 2023)	68.61	55.72	62.17	65.52	57.71	61.62
f-DPO (Wang et al., 2024a)	66.19	51.37	58.78	60.21	52.38	56.30
IPO (Azar et al., 2024)	72.17	56.51	64.34	63.19	55.12	59.16
CPO (Xu et al., 2024b)	73.13	58.89	66.01	72.30	63.39	67.86
SimPO (Meng et al., 2024)	69.71	54.38	62.05	67.85	57.51	62.68
DIL w/ LSIF	**75.47**	**60.25**	**67.86**	**73.32**	**65.02**	**69.17**

et al., 2023), CPO (Xu et al., 2024b) and SimPO (Meng et al., 2024). We thoroughly tuned the hyperparameters for each baseline and reported the best performance. The details of baselines and the hyperparameter search space can be found in Appendix B.3. The density ratio in Section 4.3 is estimated through an optimization toward the Bregman divergence. A variety of functions meet the requirements of h, but in all experiments, we choose widely used LSIF as the default objective. The effect of using different density ratio estimation objectives is empirically analyzed in Section 6.3.

6 EXPERIMENTAL RESULTS

6.1 PERFORMANCE COMPARISON ON BENCHMARKS

In this section, as shown in Table 2, we compare the performance of DIL against other alignment methods on UltraFeedback. Our results show that DIL exhibits remarkable effectiveness in improving performance. Overall, DIL consistently outperforms state-of-the-art SimPO and DPO in various benchmarks. For instance, on LLama3, the improve-

Table 4: Ablation study on h-function of Bregman divergence: We observe that these variants of DIL can further bring improvements.

Model (↓) / Benchmark (→)		BBH	MUSR	MATH	GSM8K	AlpacaEval 2
Mistral-7B Base	DIL w/ LSIF	43.59	44.05	**2.95**	32.19	**21.7**
	DIL w/ UKL	43.92	**45.11**	2.04	30.71	21.6
	DIL w/ BCE	**45.13**	43.92	2.79	**33.13**	20.7
LLama3-8B Base	DIL w/ LSIF	48.78	42.75	4.68	48.98	24.0
	DIL w/ UKL	**49.71**	43.01	4.98	**50.95**	22.7
	DIL w/ BCE	48.96	**47.35**	**5.06**	49.36	**24.6**

ments are notable on the Math and AlpacaEval 2 benchmarks, with relative gains exceeding 7.5% and 18.2% over SimPO, respectively. Notably, we observe DPO and SimPO hurt the overall performance in most reasoning-heavy tasks such as GSM8K. This indicates that SimPO and DPO might not be suitable to improve reasoning abilities, which is consistent with findings in concurrent work (Pal

Figure 3: The training dynamics of `DIL` variants, `DPO` and `SimPO` on Mistral show that `DIL` exhibits the smallest decline in chosen likelihoods, while still increasing the likelihood margins between rejected and chosen responses, compared to `SimPO` and `DPO`. In contrast, `SimPO` and `DPO` progressively focuses on unlearning the chosen responses, leading to poor performance on reasoning tasks. et al., 2024; Meng et al., 2024). In contrast, `DIL` shows clear improvements in both the Mistral and LLama3 models. These findings underscore the effectiveness of `DIL`. These improvements can be attributed to avoiding the BT assumption and preventing the likelihood decrease of chosen responses.

6.2 PERFORMANCE COMPARISON WITH HUMAN PREFERENCES

We also explore learning from real human preferences, focusing on summarization and dialogue generation tasks. Specifically, we utilize the Reddit TL;DR dataset for summarization and the Anthropic-HH dataset for dialogue generation. We employ Pythia-2.8B (Biderman et al., 2023) as the base model and fine-tuned it on the chosen completions to train a reference model, ensuring that the completions remained within the model's distribution. Table 3 presents the GPT-4 evaluation results, indicating that `DIL` outperforms baselines when compared to both the SFT and the chosen responses. Notably, `DIL` aligns better with human preferences than baselines, achieving a win rate of at least 60% against the chosen responses. This highlights the strong potential of `DIL` for aligning with human preferences. Furthermore, GPT-4 consistently favored `DIL` over both baselines and chosen responses, demonstrating improvements of `DIL` over baselines in both helpfulness and harmlessness.

6.3 FURTHER ANALYSIS

Generalization to other objectives. As mentioned in Section 4.3, our approach to conducting imitation learning from preference data generalizes in a straightforward manner to other density ratio estimations, including UKL and BCE. Table 4 shows the comparison on UltraFeedback. We can observe that different variants of the h-function can lead to general improvements across various benchmarks. Specifically, UKL performs best on BBH, achieving the highest scores on both the Mistral and LLama3 models. BCE achieves a significant improvement on MUSR, with a notable 7.27% increase. These results indicate that appropriate variant can further enhance our performance.

Training Dynamics. We also investigate the likelihood patterns during the training process of `DIL`. Figure 3 presents the likelihood patterns of `SimPO`, and `DIL` on UltraFeedack. We observe that the likelihoods of the rejected responses continue to decrease, and the margins between the chosen and rejected responses steadily increase. However, in the case of `DPO` and `SimPO`, the likelihoods of the chosen responses fall below zero and continue to decrease. These results validate our motivation and demonstrate the effectiveness of `DIL` in preventing the likelihood of the chosen responses from decreasing. This also explains why `DIL` generally improves downstream task performance, particularly on reasoning-heavy tasks such as math, as shown in our Table 2.

7 CONCLUSION

We consider the problem of aligning large language models with preference data. We provide a novel perspective on imitation learning for the alignment problem, and demonstrate `RLHF/DPO` essentially conduct imitation learning on the distribution of chosen response. Built upon this connection, we propose `DIL`, which directly optimizes the imitation learning objective based on the Bregman divergence. Unlike existing methods, `DIL` does not rely on BT assumption, which is important since this assumption may not hold in the real world. Empirical result shows that `DIL` establishes superior performance on a comprehensive set of benchmarks and different families of language models. We hope that our work will inspire future research on preference alignment with imitation learning,

REFERENCES

Pieter Abbeel and Andrew Y Ng. Apprenticeship learning via inverse reinforcement learning. In *Proceedings of the twenty-first international conference on Machine learning*, pp. 1, 2004.

Rishabh Agarwal, Chen Liang, Dale Schuurmans, and Mohammad Norouzi. Learning to generalize from sparse and underspecified rewards. In *International conference on machine learning*, pp. 130–140. PMLR, 2019.

Mohammad Gheshlaghi Azar, Zhaohan Daniel Guo, Bilal Piot, Remi Munos, Mark Rowland, Michal Valko, and Daniele Calandriello. A general theoretical paradigm to understand learning from human preferences. In *International Conference on Artificial Intelligence and Statistics*, pp. 4447–4455. PMLR, 2024.

Yuntao Bai, Andy Jones, Kamal Ndousse, Amanda Askell, Anna Chen, Nova DasSarma, Dawn Drain, Stanislav Fort, Deep Ganguli, Tom Henighan, et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:2204.05862*, 2022.

Edward Beeching, Clémentine Fourrier, Nathan Habib, Sheon Han, Nathan Lambert, Nazneen Rajani, Omar Sanseviero, Lewis Tunstall, and Thomas Wolf. Open llm leaderboard (2023-2024). 2023.

Stella Biderman, Hailey Schoelkopf, Quentin Gregory Anthony, Herbie Bradley, Kyle O'Brien, Eric Hallahan, Mohammad Aflah Khan, Shivanshu Purohit, USVSN Sai Prashanth, Edward Raff, et al. Pythia: A suite for analyzing large language models across training and scaling. In *International Conference on Machine Learning*, pp. 2397–2430. PMLR, 2023.

Ralph Allan Bradley and Milton E Terry. Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, pp. 324–345, 1952.

Paul F Christiano, Jan Leike, Tom Brown, Miljan Martic, Shane Legg, and Dario Amodei. Deep reinforcement learning from human preferences. *Advances in neural information processing systems*, 30, 2017.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Ganqu Cui, Lifan Yuan, Ning Ding, Guanming Yao, Wei Zhu, Yuan Ni, Guotong Xie, Zhiyuan Liu, and Maosong Sun. Ultrafeedback: Boosting language models with high-quality feedback. *arXiv preprint arXiv:2310.01377*, 2023.

Logan Engstrom, Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Firdaus Janoos, Larry Rudolph, and Aleksander Madry. Implementation matters in deep policy gradients: A case study on ppo and trpo. In *International Conference on Learning Representations*, 2020.

Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. Kto: Model alignment as prospect theoretic optimization. *arXiv preprint arXiv:2402.01306*, 2024.

Clémentine Fourrier, Nathan Habib, Alina Lozovskaya, Konrad Szafer, and Thomas Wolf. Open llm leaderboard v2. 2024.

Justin Fu, Katie Luo, and Sergey Levine. Learning robust rewards with adverserial inverse reinforcement learning. In *International Conference on Learning Representations*, 2018.

Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac'h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, Eric Tang, Anish Thite, Ben Wang, Kevin Wang, and Andy Zou. A framework for few-shot language model evaluation, 12 2023.

Divyansh Garg, Shuvam Chakraborty, Chris Cundy, Jiaming Song, and Stefano Ermon. Iq-learn: Inverse soft-q learning for imitation. *Advances in Neural Information Processing Systems*, 34: 4028–4039, 2021.

Dibya Ghosh, Marlos C Machado, and Nicolas Le Roux. An operator view of policy gradient methods. *Advances in Neural Information Processing Systems*, 33:3397–3406, 2020.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *Communications of the ACM*, pp. 139–144, 2020.

Yuxian Gu, Li Dong, Furu Wei, and Minlie Huang. Minillm: Knowledge distillation of large language models. In *The Twelfth International Conference on Learning Representations*, 2024.

Tuomas Haarnoja, Haoran Tang, Pieter Abbeel, and Sergey Levine. Reinforcement learning with deep energy-based policies. In *International conference on machine learning*, pp. 1352–1361. PMLR, 2017.

Trevor Hastie, Robert Tibshirani, and Jerome H. Friedman. *The Elements of Statistical Learning: Data Mining, Inference, and Prediction, 2nd Edition*. Springer Series in Statistics. Springer, 2009.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the math dataset. *arXiv*, 2021.

Geoffrey Hinton. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. *Advances in neural information processing systems*, 29, 2016.

Jiwoo Hong, Noah Lee, and James Thorne. Reference-free monolithic preference optimization with odds ratio. *arXiv preprint arXiv:2403.07691*, 2024.

Ahmed Hussein, Mohamed Medhat Gaber, Eyad Elyan, and Chrisina Jayne. Imitation learning: A survey of learning methods. *ACM Computing Surveys (CSUR)*, pp. 1–35, 2017.

Haozhe Ji, Cheng Lu, Yilin Niu, Pei Ke, Hongning Wang, Jun Zhu, Jie Tang, and Minlie Huang. Towards efficient and exact optimization of language model alignment. *arXiv preprint arXiv:2402.00856*, 2024a.

Xiang Ji, Sanjeev Kulkarni, Mengdi Wang, and Tengyang Xie. Self-play with adversarial critic: Provable and scalable offline alignment for language models. *arXiv preprint arXiv:2406.04274*, 2024b.

Takafumi Kanamori, Shohei Hido, and Masashi Sugiyama. A least-squares approach to direct importance estimation. *J. Mach. Learn. Res.*, pp. 1391–1445, 2009.

Diederik P Kingma. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ilya Kostrikov, Ofir Nachum, and Jonathan Tompson. Imitation learning via off-policy distribution matching. In *International Conference on Learning Representations*, 2019a.

Ilya Kostrikov, Ofir Nachum, and Jonathan Tompson. Imitation learning via off-policy distribution matching. In *International Conference on Learning Representations*, 2019b.

Yann LeCun, Sumit Chopra, Raia Hadsell, M Ranzato, Fujie Huang, et al. A tutorial on energy-based learning. *Predicting structured data*, 2006.

Jongmin Lee, Wonseok Jeon, Byungjun Lee, Joelle Pineau, and Kee-Eung Kim. Optidice: Offline policy optimization via stationary distribution correction estimation. In *International Conference on Machine Learning*, pp. 6120–6130, 2021.

Sergey Levine. Reinforcement learning and control as probabilistic inference: Tutorial and review. *arXiv preprint arXiv:1805.00909*, 2018.

Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and Tatsunori B Hashimoto. Alpacaeval: An automatic evaluator of instruction-following models, 2023.

Zhuang Ma and Michael Collins. Noise contrastive estimation and negative sampling for conditional models: Consistency and statistical efficiency. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 3698–3707, 2018.

Yu Meng, Mengzhou Xia, and Danqi Chen. Simpo: Simple preference optimization with a reference-free reward. *arXiv preprint arXiv:2405.14734*, 2024.

Rémi Munos, Michal Valko, Daniele Calandriello, Mohammad Gheshlaghi Azar, Mark Rowland, Zhaohan Daniel Guo, Yunhao Tang, Matthieu Geist, Thomas Mesnard, Andrea Michi, et al. Nash learning from human feedback. *arXiv preprint arXiv:2312.00886*, 2023.

Kevin P Murphy. *Machine learning: a probabilistic perspective*. MIT press, 2012.

Ofir Nachum, Mohammad Norouzi, and Dale Schuurmans. Improving policy gradient by exploring under-appreciated rewards. *arXiv preprint arXiv:1611.09321*, 2016.

Ofir Nachum, Yinlam Chow, Bo Dai, and Lihong Li. Dualdice: Behavior-agnostic estimation of discounted stationary distribution corrections. *Advances in neural information processing systems*, 32, 2019.

XuanLong Nguyen, Martin J. Wainwright, and Michael I. Jordan. Estimating divergence functionals and the likelihood ratio by convex risk minimization. *IEEE Trans. Inf. Theory*, 56(11):5847–5861, 2010.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Takayuki Osa, Joni Pajarinen, Gerhard Neumann, J Andrew Bagnell, Pieter Abbeel, Jan Peters, et al. An algorithmic perspective on imitation learning. *Foundations and Trends® in Robotics*, pp. 1–179, 2018.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, pp. 27730–27744, 2022.

Arka Pal, Deep Karkhanis, Samuel Dooley, Manley Roberts, Siddartha Naidu, and Colin White. Smaug: Fixing failure modes of preference optimisation with dpo-positive. *arXiv preprint arXiv:2402.13228*, 2024.

Dean A Pomerleau. Alvinn: An autonomous land vehicle in a neural network. *Advances in neural information processing systems*, 1, 1988.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *Advances in Neural Information Processing Systems*, 36, 2024.

Claude Sammut, Scott Hurst, Dana Kedzier, and Donald Michie. Learning to fly. In *Machine Learning Proceedings 1992*, pp. 385–393, 1992.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Yang Song and Diederik P Kingma. How to train your energy-based models. *arXiv preprint arXiv:2101.03288*, 2021.

Zayne Sprague, Xi Ye, Kaj Bostrom, Swarat Chaudhuri, and Greg Durrett. Musr: Testing the limits of chain-of-thought with multistep soft reasoning. *arXiv preprint arXiv:2310.16049*, 2024.

Nisan Stiennon, Long Ouyang, Jeffrey Wu, Daniel Ziegler, Ryan Lowe, Chelsea Voss, Alec Radford, Dario Amodei, and Paul F Christiano. Learning to summarize with human feedback. *Advances in Neural Information Processing Systems*, 33:3008–3021, 2020.

Masashi Sugiyama, Taiji Suzuki, Shinichi Nakajima, Hisashi Kashima, Paul Von Bünau, and Motoaki Kawanabe. Direct importance estimation for covariate shift adaptation. *Annals of the Institute of Statistical Mathematics*, 60:699–746, 2008.

Masashi Sugiyama, Taiji Suzuki, and Takafumi Kanamori. Density-ratio matching under the bregman divergence: a unified framework of density-ratio estimation. *Annals of the Institute of Statistical Mathematics*, 64:1009–1044, 2012.

Hao Sun and Mihaela van der Schaar. Inverse-rlignment: Inverse reinforcement learning from demonstrations for llm alignment. *arXiv preprint arXiv:2405.15624*, 2024.

Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V. Le, Ed H. Chi, Denny Zhou, and Jason Wei. Challenging big-bench tasks and whether chain-of-thought can solve them. *arXiv*, 2022.

Fahim Tajwar, Anikait Singh, Archit Sharma, Rafael Rafailov, Jeff Schneider, Tengyang Xie, Stefano Ermon, Chelsea Finn, and Aviral Kumar. Preference fine-tuning of llms should leverage suboptimal, on-policy data. *arXiv preprint arXiv:2404.14367*, 2024.

Katherine Tian, Eric Mitchell, Huaxiu Yao, Christopher D Manning, and Chelsea Finn. Fine-tuning language models for factuality. *arXiv preprint arXiv:2311.08401*, 2023.

Lewis Tunstall, Edward Beeching, Nathan Lambert, Nazneen Rajani, Kashif Rasul, Younes Belkada, Shengyi Huang, Leandro von Werra, Clémentine Fourrier, Nathan Habib, et al. Zephyr: Direct distillation of lm alignment. *arXiv preprint arXiv:2310.16944*, 2023.

Michael Völske, Martin Potthast, Shahbaz Syed, and Benno Stein. Tl; dr: Mining reddit to learn automatic summarization. In *Proceedings of the Workshop on New Frontiers in Summarization*, pp. 59–63, 2017.

Chaoqi Wang, Yibo Jiang, Chenghao Yang, Han Liu, and Yuxin Chen. Beyond reverse KL: generalizing direct preference optimization with diverse divergence constraints. In *The Twelfth International Conference on Learning Representations*, 2024a.

Qing Wang, Jiechao Xiong, Lei Han, Han Liu, Tong Zhang, et al. Exponentially weighted imitation learning for batched historical data. *Advances in Neural Information Processing Systems*, 31, 2018.

Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, Tianle Li, Max Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue, and Wenhu Chen. Mmlu-pro: A more robust and challenging multi-task language understanding benchmark. *arXiv*, 2024b.

Yue Wu, Zhiqing Sun, Huizhuo Yuan, Kaixuan Ji, Yiming Yang, and Quanquan Gu. Self-play preference optimization for language model alignment. *arXiv preprint arXiv:2405.00675*, 2024.

Markus Wulfmeier, Michael Bloesch, Nino Vieillard, Arun Ahuja, Jorg Bornschein, Sandy Huang, Artem Sokolov, Matt Barnes, Guillaume Desjardins, Alex Bewley, et al. Imitating language via scalable inverse reinforcement learning. *arXiv preprint arXiv:2409.01369*, 2024.

Haoran Xu, Amr Sharaf, Yunmo Chen, Weiting Tan, Lingfeng Shen, Benjamin Van Durme, Kenton Murray, and Young Jin Kim. Contrastive preference optimization: Pushing the boundaries of llm performance in machine translation. *arXiv preprint arXiv:2401.08417*, 2024a.

Haoran Xu, Amr Sharaf, Yunmo Chen, Weiting Tan, Lingfeng Shen, Benjamin Van Durme, Kenton Murray, and Young Jin Kim. Contrastive preference optimization: Pushing the boundaries of llm performance in machine translation. In *Forty-first International Conference on Machine Learning*, 2024b.

Shusheng Xu, Wei Fu, Jiaxuan Gao, Wenjie Ye, Weilin Liu, Zhiyu Mei, Guangju Wang, Chao Yu, and Yi Wu. Is dpo superior to ppo for llm alignment? a comprehensive study. *arXiv preprint arXiv:2404.10719*, 2024c.

Hongyi Yuan, Zheng Yuan, Chuanqi Tan, Wei Wang, Songfang Huang, and Fei Huang. Rrhf: Rank responses to align language models with human feedback. *Advances in Neural Information Processing Systems*, 36, 2024a.

Lifan Yuan, Ganqu Cui, Hanbin Wang, Ning Ding, Xingyao Wang, Jia Deng, Boji Shan, Huimin Chen, Ruobing Xie, Yankai Lin, et al. Advancing llm reasoning generalists with preference trees. *arXiv preprint arXiv:2404.02078*, 2024b.

Yao Zhao, Rishabh Joshi, Tianqi Liu, Misha Khalman, Mohammad Saleh, and Peter J Liu. Slic-hf: Sequence likelihood calibration with human feedback. *arXiv preprint arXiv:2305.10425*, 2023.

Chongyi Zheng, Ruslan Salakhutdinov, and Benjamin Eysenbach. Contrastive difference predictive coding. In *The Twelfth International Conference on Learning Representations*, 2024.

A   DETAILS OF METHODS FOR DENSITY RATIO ESTIMATION

We overview examples of density ratio estimation methods under Bregman Divergence framework.

Least Squares Importance Fitting (LSIF). LSIF (Kanamori et al., 2009) minimizes the squared error between a density ratio model r and the true density ratio r^* defined as follows:

$$
\begin{aligned}
D_{h_{\mathrm{LSIF}}}(r^* \| r_\phi) &= \mathbb{E}_{\pi_{\mathrm{ref}}}[(r_\phi(\mathbf{x}, \mathbf{y}) - r^*(\mathbf{x}, \mathbf{y})^2] \\
&= \mathbb{E}_{\pi_{\mathrm{ref}}}[(r^*(\mathbf{x}, \mathbf{y}))^2] - 2\mathbb{E}_{\pi_{\mathrm{chosen}}}[r_\phi(\mathbf{x}, \mathbf{y})] + \mathbb{E}_{\pi_{\mathrm{ref}}}[(r_\phi(\mathbf{x}, \mathbf{y}))^2],
\end{aligned} \tag{28}
$$

where the first term in the above equation is constant w.r.t ϕ. This empirical risk minimization is equal to minimizing the empirical BD defined in Equation (18) with $h(r) = (r-1)^2/2$.

KL Importance Estimation Procedure (KLIEP). KLIEP is derived from the unnormalized Kullback–Leibler (UKL) divergence objective (Sugiyama et al., 2008; Nguyen et al., 2010), which uses $h(r) = r \log(r) - r$. Ignoring terms irrelevant to the optimization, we obtain (up to a constant):

$$
D_{h_{\mathrm{KLIEP}}}(r^* \| r_\phi) = \mathbb{E}_{\pi_{\mathrm{ref}}}\left[r(\mathbf{x}, \mathbf{y})\right] - \mathbb{E}_{\pi_{\mathrm{chosen}}}\left[\log\left(r(\mathbf{x}, \mathbf{y})\right)\right]. \tag{29}
$$

KLIEP is also known as solving a Lagrangian of the constrained problem with further imposing a constraint that the ratio model $r(\mathbf{x}, \mathbf{y})$ is non-negative and normalized as follows:

$$
\max_r \mathbb{E}_{\pi_{\mathrm{chosen}}}\left[\log\left(r(\mathbf{x}, \mathbf{y})\right)\right] \tag{30}
$$

$$
\text{s.t. } \mathbb{E}_{\pi_{\mathrm{ref}}}\left[r(\mathbf{x}, \mathbf{y})\right] = 1 \text{ and } r(\mathbf{x}, \mathbf{y}) \geq 0 \text{ for all } (\mathbf{x}, \mathbf{y}). \tag{31}
$$

Binary Cross Entropy.   By using $h(r) = \log(r) - (1+r)\log(1+r)$, we obtain the following Bregman Divergence called the Binary Cross Entropy (BCE) divergence:

$$
D_{h_{\mathrm{BCE}}}(r^* \| r_\phi) = -\mathbb{E}_{\pi_{\mathrm{ref}}}\left[\log\left(\frac{1}{1 + r(\mathbf{x}, \mathbf{y})}\right)\right] - \mathbb{E}_{\pi_{\mathrm{chosen}}}\left[\log\left(\frac{r(\mathbf{x}, \mathbf{y})}{1 + r(\mathbf{x}, \mathbf{y})}\right)\right].
$$

This Bregman divergence is derived from a formulation of logistic regression (Sugiyama et al., 2012).

B   EXPERIMENTAL DETAILS

B.1   THE DETAILS OF DATASETS

UltraFeedback Binarized (Cui et al., 2023; Tunstall et al., 2023): This dataset[1] contains 64k prompts, each paired with four completions generated by a variety of open-source and proprietary models. GPT-4 assigns scores to these completions based on helpfulness, honesty, and other metrics. Binary preferences are constructed by selecting the completion with the highest average score as the chosen response, while one of the other three completions is randomly selected as the rejected response.

Anthropic-HH (Bai et al., 2022): The Anthropic Helpful and Harmless dialogue dataset[2] includes 170k dialogues between humans and LLM assistants, used for evaluating single-turn dialogue tasks. Each dialogue includes a human query and two model responses rated on helpfulness and harmlessness. In line with DPO (Rafailov et al., 2024), the chosen responses from this dataset were employed during the supervised fine-tuning (SFT) phase.

Reddit TL;DR Summarization (Völske et al., 2017): This dataset[3] consists of forum posts from Reddit, specifically curated for summarization tasks with associated preference labels. Following prior work (Stiennon et al., 2020), we use a filtered version of this dataset to train the SFT policy, using its preference labels during the subsequent alignment phase.

---

[1] https://huggingface.co/datasets/HuggingFaceH4/ultrafeedback_binarized
[2] https://huggingface.co/datasets/Anthropic/hh-rlhf
[3] https://huggingface.co/datasets/openai/summarize_from_feedback

Table 5: The hyperparameter search space for the baselines.

Method		Method	
DPO	$\beta \in [0.01, 0.05, 0.1]$	IPO	$\tau \in [0.01, 0.1, 0.5, 1.0]$
CPO	$\lambda = 1.0$
$\beta \in [0.01, 0.05, 0.1]$	SLiC	$\lambda \in [0.1, 0.5, 1.0, 10.0]$
$\delta \in [0.1, 0.5, 1.0, 2.0]$
KTO	$\lambda_l = \lambda_w = 1.0$
$\beta \in [0.01, 0.05, 0.1]$	SimPO	$\beta \in [2.0, 2.5]$
$\gamma \in [0.3, 0.5, 1.0, 1.2, 1.4, 1.6]$

B.2   THE DETAILS OF TASKS AND EVALUATION

This section introduces the benchmark for model evaluation. The model fine-tuned on UltraFeedback Binarized dataset is evaluated following previous works (Rafailov et al., 2024; Tunstall et al., 2023): the HuggingFace Open LLM Leaderboard v1[4] and v2[5] (Beeching et al., 2023; Fourrier et al., 2024), including MMUL-PRO, BBH, MUSR, MATH, GSM8k, and ARC; instruction-following benchmark, AlpacaEval2. The models fine-tuned on Anthropic-HH dataset follow the evaluation protocol provided by (Rafailov et al., 2024), utilizing GPT-4 for zero-shot pair-wise evaluation.

MMUL-PRO (Wang et al., 2024b): Short hand for Massive Multitask Language Understanding Professional. This dataset builds on the MMLU by incorporating more complex multiple-choice questions and undergoing rigorous expert review to enhance quality, difficulty and reduce data biases.

BBH (Suzgun et al., 2022): Short hand for Big Bench Hard. This benchmark includes 23 tasks selected from BigBench testing capabilities in arithmetic, comprehension, and general knowledge.

MUSR (Sprague et al., 2024): Short hand for Multistep Soft Reasoning. This benchmark contains complex scenarios to assesses capacity to integrate information and reason across long contexts.

MATH (Hendrycks et al., 2021): This collection comprises math problems for high-school competitions, consistently presented using LaTeX and Asymptote to ensure clear and precise formatting.

GSM8k (5-shot) (Cobbe et al., 2021): This benchmark consists of grade school math problems to test the model's capability to navigate and solve complex, multi-step mathematical challenges.

ARC (25-shot) (Clark et al., 2018): Short hand for AI2 Reasoning Challenge. This science-focused benchmark includes questions from a grade-school curriculum to test factual and logical reasoning.

AlpacaEval 2.0 (Li et al., 2023): This benchmark uses LLM to automatically assess model performance on instruction-following tasks, validated against 20,000 human annotations for reliability.

GPT-4 Evaluation (Rafailov et al., 2024): The safety of models trained on Anthropic HH is assessed using the Anthropic HH test set, with preferred responses serving as benchmarks. GPT-4's evaluations are aligned with human judgments, ensuring reliable safety assessments. The model version used for these evaluations is `gpt-4-0314`, with specific prompts detailed in Table 6.

B.3   IMPLEMENTATION DETAILS

Training   For the general hyperparameters, we closely followed the configurations used in SimPO. Specifically, during the SFT stage, we applied a learning rate of 2×10^{-5}. For both the SFT and preference optimization stages, we used a batch size of 128, a maximum sequence length of 2048, and implemented a cosine learning rate schedule with 10% warmup steps for a single epoch, utilizing the Adam optimizer (Kingma, 2014). These settings were maintained consistently across all experiments to ensure uniformity and comparability. For method-specific hyperparameters, we also adhered to the search strategy outlined in SimPO. For each baseline method, which had its own unique set of hyperparameters, the search strategy is detailed in Table 5. Learning rates for each method were individually searched within the range of $[3e - 7, 5e - 7, 6e - 7, 1e - 6]$. For our methods, we also normalize the likelihood of the response, calculated as the average log probability of all tokens in a response using the policy model, to avoid the length bias as in SimPO. All training experiments

---

[4] https://huggingface.co/spaces/open-llm-leaderboard-old/open_llm_leaderboard
[5] https://huggingface.co/spaces/open-llm-leaderboard/open_llm_leaderboard

described in this paper were conducted using either four NVIDIA A100 80GB GPUs with 128 batchsize, utilizing the codebase from the alignment-handbook repository.[6]

Evaluation For the evaluation on the Open LLM Leaderboard V1, we use 5-shot setting for GSM8K, and 25-shot for ARC. For the evaluation on Open LLM Leaderboard V2, all tasks were performed by the default setting of the leaderboard. For the evaluation on AlpacaEval 2, we employ hyperparameters consistent with SimPO. Specifically, we set the temperature to 0.7 for the Mistral-Base configuration, 0.5 for the Mistral-Instruct configuration, and 0.9 for both Llama3 configurations.

```
For the following dialogue history to a chatbot, which response is more helpful and
harmless?

Dialogue history:
{dialogue history}

Response 1:
{Response 1}

Response 2:
{Response 2}

FIRST provide a one-sentence comparison of the two responses and explain which you
feel is more helpful and harmless.  SECOND, on a new line, state only "1" or "2" to
indicate which response is more helpful and harmless.  Your response should use the
format:
Comparison:  <one-sentence comparison and explanation>
More helpful:  <"1" or "2">
```

Table 6: GPT-4 prompt (Rafailov et al., 2024) for the safety evaluation on the Anthropic-HH dataset.

Table 7: Performance comparison on reasoning-heavy tasks.

Methods	HumanEval	LeetCode	GSM8K	MATH	TheoremQA	AlpacaEval 2
SFT	28.1	3.3	28.1	2.3	7.0	6.2
DPO	31.7	2.2	21.7	1.4	9.8	12.5
SimPO	26.5	1.9	22.2	2.5	8.5	20.8
DIL	**33.5**	**3.4**	**32.2**	**3.0**	**12.5**	**21.7**

Table 8: Performance comparison on Mixtral-8x22B-Instruct-v0.1.

Mixtral-8x22B	HumanEval	LeetCode	MATH	TheoremQA
DPO	75.1	24.5	48.5	34.7
SimPO	76.2	22.5	50.3	35.5
DIL	**77.3**	**28.7**	**52.8**	**36.9**

C FUTURE WORK

DIL presents many exciting directions for future work. First, we aim to gain a deeper theoretical understanding of which density-ratio estimation techniques are most effective for alignment. Our current analysis is limited to the offline setting and does not account for on-policy learning, where the policy can interact with the reward model during training. Exploring DIL in an on-policy learning scenario would be particularly interesting. The relationship between DIL and DPO bears a structural similarity to the connection between Bregman divergence and contrastive predictive coding, which suggests that further exploration of this connection could be fruitful. While this paper has primarily focused on three density ratio estimation loss functions, investigating DIL with other density ratio estimation loss functions would also be an intriguing direction for future research.

---

[6]https://github.com/huggingface/alignment-handbook