Unsupervised Learning of Energy Compositions

Abstract

Humans are able to rapidly understand scenes by utilizing concepts extracted from prior experience. Such concepts are diverse, and include global scene descriptors, such as the weather or lighting, as well as local scene descriptors, such as the color or size of a particular object. So far, unsupervised discovery of concepts has focused on either modeling the global scene-level or the local object-level factors of variation, but not both. In this work, we propose COMET, which discovers and represents concepts as separate energy functions, enabling us to represent both global concepts as well as objects under a unified framework. COMET discovers energy functions through recomposing the input image, which we find captures independent factors without additional supervision. Sample generation in COMET is formulated as an optimization process on underlying energy functions, enabling us to generate images with permuted and composed concepts. Finally, discovered visual concepts in COMET generalize well, enabling us to compose concepts between separate modalities of images as well as with other concepts discovered by a separate instance of COMET trained on a different dataset.

1 Introduction

Human intelligence is characterized by its ability to learn new concepts, such as the manipulation of a new tool from only a few demonstrations [1]. Essential to this capability is the composition and re-utilization of previously learned concepts to accomplish the task at hand [36]. This is especially apparent in natural language, which is often described as a tool for making 'infinite use of finite means' [8]. Previously acquired words can be infinitely nested using a set of grammatical rules to communicate an arbitrary thought, opinion, or state one is in. In this work, we are interested in constructing a system that can discover, in an unsupervised manner, a broad set of these compositional components, as well as subsequently combine them across distinct modalities and datasets.

For obtaining such decompositions, two separate lines of work exist. The first focuses on obtaining global, holistic, compositional factors by situating data points, such as human faces, in an underlying (fixed) factored vector space [24, 48]. Individual factors, such as emotion or hair color, are represented as independent dimensions of the vector space, with recombination between factors corresponding to the recombination of the underlying dimensions. Due to the fixed dimensionality of the vector space, multiple instances of a single factor, such as lighting, may not be combined, nor can individual factored vector spaces from separate datasets be combined, i.e. the facial expression in an image from one dataset, and the background lighting in an image from another.

To address this weakness, a separate line of work decomposes a scene into a set of underlying 'object' factors. Each object factor represents a separate set of pixels in an image, as defined by a disjoint segmentation mask [22, 47]. Such a representation allows for the composition of individual factors by compositing the segmentation masks. However, by explicitly constraining the decomposition to be in terms of disjoint segmentation masks, relationships between individual factors of variation become more difficult to represent and capture global factors describing a scene.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

| Input Image | Minimal Energy State (Per Inferred Energy Function) | Minimal Energy State (Across Energy Functions) | Input Image | Minimal Energy State (Per Inferred Energy Function) | Minimal Energy State (Across Energy Functions) |

Figure 1: COMET decomposes images into a set of energy functions. The minimal energy state across all energy functions reconstructs the input image. The minimal energy states of individual energy functions capture particular aspects of an image, in the form of local factors of variations such as individual objects, or global factors of variation such as hair color, background lighting, facial expression, or skin color, which we further illustrate. **Note that reconstructed face images in the remainder of the paper are synthetic and not existing human faces.**

In this work, we propose instead to decompose a scene into a set of factors represented as *energy functions*. An individual energy function represents a factor by assigning low energy to scenes with said factor and high energy to scenes where said factor is absent. A scene is then generated by optimizing the sum of energies for all factors. Multiple factors can be composed together, by summing the energies for each individual factor. Simultaneously, these individual factors are defined across the entire scene, allowing energy functions to represent global factors (lighting, camera viewpoint) and local factors (object existence).

Our work is inspired by recent work [12] which shows that energy based models may be utilized to represent flexible compositions of both global and local factors. However, while [12] required supervision, as labels were used to represent concepts, we aim to decompose and discover concepts in an unsupervised manner. In our approach, we discover energy functions from separate data points by enforcing compositions of these energy functions to recompose data.

Our work is further inspired by the ability of humans to effortlessly and reliably combine concepts gathered from disparate experiences. As a separate benefit of our approach, we show that we may take components inferred by one instance of COMET trained on one dataset, and compose it with other components inferred by other instances of COMET trained on separate datasets.

We provide analysis showing why our approach, COMET*, is favorable compared to existing unsupervised approaches for decomposing scenes. We contribute the following: First, we show COMET provides a unified framework enabling us to decompose images into both global factors of variation as well as local factors of variation. Second, we show that COMET enables us to scale to more realistic datasets than previous work. Finally, we show that components obtained by COMET generalize well, and are amenable to compositions across different modes of data, and with components discovered by other instances of COMET.

2   Related Work

Our work is related to research in the areas of global factor disentanglement [4, 7, 23, 34, 38, 43] and independent component analysis (ICA) [2, 9, 25–27, 31, 32, 42, 51]. Work in said areas focus on discovering an underlying global latent space which describes the input space. In contrast, we decompose data into a set of compositional vector spaces. This enables our approach to compose multiple instances of one factor together, as well as compose factors across distinct datasets.

Our work is also related to a large body of existing work on unsupervised object discovery [5, 10, 14–17, 21, 22, 35, 39, 45, 46, 49]. Such methods seek to decompose the scene into its underlying compositional objects by independently segmenting out each individual object in the scene. In contrast, our approach represents individual objects without the need of an explicit segmentation mask, enabling our approach to represent global relations between objects.

Our work draws on recent work in energy based models (EBMs) [11, 13, 18, 20, 33, 41, 44, 50]. Our underlying energy optimization procedure to generate samples is reminiscent of Langevin sampling, which is used to sample from EBMs [11, 41, 50]. Most similar to our work is that of [12], which

---

*short for COMposable Energy neTwork

Figure 2: Illustration of distinct approaches to composing components z_1, z_2, z_3 into an image x. (a) $\beta-$VAE utilizes a global decoder to map components to images. (b) MONET composits disjoint segmentation masks representing each image. (c) COMET defines an energy function per component, and optimizes the sum over the set of energy functions for each component.

proposes composing EBMs for compositional visual generation. Different from [12], we study how we may discover factors in an unsupervised manner from data.

3   Composable Energy Networks

Let $\mathcal{D} = \{X\}$ be a set of images $x \in \mathbb{R}^D$. Our goal is to obtain a set Z of components $\{z_0, z_1, \ldots, z_k\}$ for each image x representing the underlying factors of variation in the image, where each component $z \in \mathbb{R}^M$. We first discuss how we represent Z as a set of energy functions in Section 3.1. We then discuss how COMET learns to decompose data in an unsupervised manner into a set of components in Section 3.2.

3.1   Composing Factors of Variation as Energy Functions

In prior work for decomposing images into a set of components Z, approaches such as the β-VAE [23] utilize a parameterized, non-adaptive, feedforward decoder to map the set of components to an image. Due to this, the method is unable to compose multiple instances of the same component or a larger number of components then seen during training. On the other hand, approaches such as MONET [5] utilize a decoder with shared weights to process each individual component. Unfortunately, the components are decoded independently, preventing relationships between individual components from being captured.

To flexibly and generically compose a set of components Z, we require an approach that (1) utilizes a decoder that is shared across each component, such that variable-sized sets of components may be encoded, while also (2) decodes components jointly such that the relationships between individual components are covered. To construct an approach with the aforementioned desiderata, we propose to represent each component z as an energy function. We illustrate our approach and its differences from prior work in Figure 2.

Representing Components as Energy Functions.   Given a single component z, we encode the factor using an energy function $E_\theta(x, z) : \mathbb{R}^D \times \mathbb{R}^M \to \mathbb{R}$, which is learned to assign low energy to all images x which contain the component and high energy to all other images. To obtain an image x' with a component z, we solve for the expression $x' = \arg\min_x E_\theta(x; z_i)$.

Composing Energy Functions.   Given multiple components, we represent a set of components $\{z_i\}$ by performing a summation $\sum_i E_\theta(x, z_i)$ over each component's energy function. To obtain an image x' for the set of components Z, we solve for the expression $x' = \arg\min_x \sum_i E_\theta(x; z_i)$.

While both COMET and MONET rely on summation as a tool for composing components, MONET sums components in the image domain, while COMET sums the cost functions representing each component together. By summing cost functions, each component may combine with other components in a non-linear manner, enabling more complex relationships between components to be modeled.

As a result, our generation x' is the byproduct of jointly minimizing each individual energy function $E_\theta(x, z_i)$, and thus our generation contains each component. In addition, each individual component z_i is parameterized by the same energy function E_θ, enabling us to scale to a different number of components.

3.2 Unsupervised Decomposition of Composable Energy Functions

We next discuss how COMET discovers a set of composable energy functions from an input image $\boldsymbol{x}_i$. In Section 3.1, we discuss that a set of components $Z = \{\boldsymbol{z}_i\}$ may be encoded as a set of composable energy functions using the expression $\arg\min_{\boldsymbol{x}} \sum_i E_\theta(\boldsymbol{x}; \boldsymbol{z}_i)$. To discover the set of components Z in an unsupervised manner, we train by recomposing the input image $\boldsymbol{x}_i$

$$\mathcal{L}_{\text{MSE}}(\theta) = \| \arg\min_{\boldsymbol{x}}(\sum_k E_\theta(\boldsymbol{x}; \text{Enc}_\theta(\boldsymbol{x}_i)[k])) - \boldsymbol{x}_i \|^2. \tag{1}$$

We utilize a learned neural network encoder $\text{Enc}_\theta(\boldsymbol{x}_i)$ to infer a set of components $\boldsymbol{z}_k$. In practice, evaluating the expression $\arg\min_{\boldsymbol{x}} \sum_k E_\theta(\boldsymbol{x}; \text{Enc}_\theta(\boldsymbol{x}_i)[k])$, is computationally intractable. We thus approximate the $\arg\min$ operation with respect to $\boldsymbol{x}$ via N steps of gradient optimization, with an approximate optimum $\boldsymbol{x}_i^N$ obtained as

$$\boldsymbol{x}_i^N = \boldsymbol{x}_i^{N-1} - \lambda \nabla_{\boldsymbol{x}} \sum_k E_\theta(\boldsymbol{x}_i^{N-1}; \text{Enc}_\theta(\boldsymbol{x}_i)[k]). \tag{2}$$

In the above expression, we initialize optimization of $\boldsymbol{x}_i^0$ with uniform noise with λ representing the step size for each gradient step. We then train our energy function E_θ using the modified objective $\mathcal{L}_{\text{MSE}} = \|\boldsymbol{x}_i^N - \boldsymbol{x}_i\|^2$, which enforces that $\boldsymbol{x}_i^N$ matches the original data point $\boldsymbol{x}_i$, where to learn the parameters of E_θ we use automatic differentiation to compute gradients with respect to each optimization step depicted in Equation 2.

We provide pseudocode for training our model in Algorithm 1. While the approach is simple, we find that it performs favorably in both global disentanglement as well as object-level disentanglement, and requires no additional objectives or priors to shape underlying latents. We utilize the same energy architecture E_θ throughout all experiments, and present details in the appendix.

Algorithm 1 Training algorithm for COMET.

Input: data dist. $p_D(\boldsymbol{x})$, step size λ, number of gradient steps N, encoder Enc_θ, energy function E_θ, energy components K
while not converged **do**
    $\boldsymbol{x}_i \sim p_D$
    $\triangleright$ *Encode components $\boldsymbol{z}_i^k$ from $\boldsymbol{x}_i$*
    $\boldsymbol{z}_i^1, \dots, \boldsymbol{z}_i^K \leftarrow \text{Enc}_\theta(\boldsymbol{x}_i)$
    $\triangleright$ *Optimize sample $\boldsymbol{x}_i^0$ via gradient descent:*
    $\boldsymbol{x}_i^0 \sim \mathcal{U}(0, 1)$
    for gradient step $n = 1$ to N **do**
        $\boldsymbol{x}_i^n \leftarrow \boldsymbol{x}_i^{n-1} - \lambda \nabla_{\boldsymbol{x}} \sum_{k=1}^K E_\theta(\boldsymbol{x}_i^{n-1}; \boldsymbol{z}_i^k)$
    end for
    $\triangleright$ *Optimize objective $\mathcal{L}_{MSE}$ wrt θ:*
    $\Delta\theta \leftarrow \nabla_\theta \|\boldsymbol{x}_i^N - \boldsymbol{x}_i\|^2$
    Update θ based on $\Delta\theta$ using Adam optimizer
end while

Controlling Local and Global Decompositions. In many scenes, both global and local factor decompositions are valid. To control the decomposition obtained by COMET, we bias the system towards inferring local factor decompositions by utilizing i) low latent dimensionality and ii) positional embeddings [37], both of which have been used in previous object discovery works [5]. This bias serves to encourage and enable models to focus on local patches of an image. We provide analysis of the effect of each inductive bias on the decomposition in the appendix.

4 Complexity Analysis of Energy Function Compositions

In this section, we provide complexity-theoretic motivation for composing functions together using energy functions. Let Z denote a set of components, with individual components $\boldsymbol{z}_1, \dots, \boldsymbol{z}_K \in \mathbb{R}^M$. Let $\mathcal{F}$ be the space of functions $f: Z \to \mathbb{R}^D$ for mapping sets of components to an output vector $\boldsymbol{x}$. We consider two subspaces for $\mathcal{F}$.

Composition of Energy Functions. Let $\mathcal{F}_{\text{energy}} \subseteq \mathcal{F}$ be the subspace of functions of the form $\arg\min_{\boldsymbol{x}} \sum_{1 \leq k \leq K} E(\boldsymbol{x}, \boldsymbol{z}_k)$, where each $E(\boldsymbol{x}, \boldsymbol{z}_m)$ is a function from $\mathbb{R}^D \times \mathbb{R}^M \to \mathbb{R}$. This subspace corresponds to the set of compositions realized by COMET.

Composition of Segmentation Masks. We next consider the subspace of functions $\mathcal{F}_{\text{mask}} \subseteq \mathcal{F}$ consisting of functions f of the form $\sum_{1 \leq k \leq K} m_k(\boldsymbol{z}_k) f_k(\boldsymbol{z}_k)$ where $f(\boldsymbol{z}): \mathbb{R}^M \to \mathbb{R}^D$ and $m_k(\boldsymbol{z}_k): \mathbb{R}^M \to \{0, 1\}^D$. Here, $m_k(\boldsymbol{z}_k)$ represents a segmentation mask in $\mathbb{R}^D$. This composition is used in object decomposition methods, such as [5, 22].

159 We first show that compositions of energy functions are more expressive than compositions of
160 segmentation masks.

Remark 1. *The subspace $\mathcal{F}_{energy}$ is a strict superset of the subspace $\mathcal{F}_{mask}$.*

162 *Proof.* Any function of the form $\sum_{\boldsymbol{z} \in \boldsymbol{Z}} m_k(\boldsymbol{z}) f(\boldsymbol{z})$ is equivalent to $\arg\min_{\boldsymbol{x}} \sum_{\boldsymbol{z} \in \boldsymbol{Z}} E'(\boldsymbol{x}, \boldsymbol{z})$,
163 where $E'(\boldsymbol{x}, \boldsymbol{z}) = m_k(\boldsymbol{z})(\boldsymbol{x} - f(\boldsymbol{z}))^2$, so $\mathcal{F}_{mask} \subseteq \mathcal{F}_{energy}$. In the other direction, note that
164 according to the definition of $\mathcal{F}_{mask}$, the presence of a particular component $\boldsymbol{z}_i$ assigns a fixed
165 value to the output for the nonzero entries of $m_k(\boldsymbol{z}_k) f(\boldsymbol{z}_k)$, irrespective of the value of the other
166 components. In contrast, the optimal value of $\boldsymbol{x}$ in $\mathcal{F}_{energy}$ depends on the value of all compo-
167 nents. A constructive example of this is the set of energy functions over one-dimensional $\boldsymbol{x}$
168 where $E(x, \boldsymbol{z}_1) = (x - 2)^2$, $E(x, \boldsymbol{z}_2) = (x - 3)^2$, $E(x, \boldsymbol{z}_3) = (x - 4)^2$. Thus, we have that
169 $\arg\min_x E(x, \boldsymbol{z}_1) + E(x, \boldsymbol{z}_2) \neq \arg\min_x E(x, \boldsymbol{z}_1) + E(x, \boldsymbol{z}_3)$. Therefore, there are functions in
170 $\mathcal{F}_{energy}$ that are not in $\mathcal{F}_{mask}$. □

171 Next, we show that even in the setting in which we represent a single component $\boldsymbol{z}$, learning a
172 function to approximate $E(\boldsymbol{x}, \boldsymbol{z})$ is more computationally efficient than learning a function $f(\boldsymbol{z})$
173 that approximates $\arg\min_{\boldsymbol{x}} E(\boldsymbol{x}, \boldsymbol{z})$. Intuitively, an energy function $E(\boldsymbol{x}, \boldsymbol{z})$ can be seen as a
174 verifier of a set of constraints, with the value of $E(\boldsymbol{x}, \boldsymbol{z})$ being low when all constraints are satisfied.
175 Approximating the function $\arg\min_{\boldsymbol{x}} E(\boldsymbol{x}, \boldsymbol{z})$ corresponds to generating a solution given a set
176 of constraints, which is well-known in complexity theory to be much harder than verifying the
177 constraints. Thus, to enable formal analysis of $E(\boldsymbol{x}, \boldsymbol{z})$, we reduce the 3-SAT [28] problem to an
178 energy function $E(\boldsymbol{x}, \boldsymbol{z})$.

179 Given a 3-SAT formula ϕ with D variables and K clauses, we encode ϕ using an energy function
180 $E(\boldsymbol{x}, \boldsymbol{z}) := \sum_{1 \leq k \leq K} e_k(\boldsymbol{x}, \boldsymbol{z}[k])$, where, $\boldsymbol{x}$ encodes an assignment to all the variables, where $\boldsymbol{z}[k]$
181 represents the dimensions of $\boldsymbol{z}$ encoding the k^{th} clause, and each e_k is a function which has energy 0
182 if the assignment $\boldsymbol{x}$ satisfies the k^{th} clause, and has energy 1 otherwise. To encode a clause using
183 $\boldsymbol{z}[k]$, we utilize an ordinal representation (e.g. $\boldsymbol{z} = [1, 2, 3]$ to represent the clause $(x_1 \wedge x_2 \wedge x_3)$),
184 and round non-integer coordinates of $\boldsymbol{x}$ and $\boldsymbol{z}$ to the nearest integer. We assume the Exponential
185 Time Hypothesis (ETH)[28], which states that checking the satisfiability of a 3-SAT formula takes
186 time exponential in the sum of the number of variables and the number of clauses.

Remark 2. *There exists an energy function $E(\boldsymbol{x}, \boldsymbol{z}_1)$ which can be evaluated at any input in time*
188 *polynomial in the number of dimensions of $\boldsymbol{x}$ but for which the computational complexity of evaluating*
189 *$f(\boldsymbol{z}) := \arg\min_{\boldsymbol{x}} E(\boldsymbol{x}, \boldsymbol{z}_1)$ is (worst-case) exponential in the number of dimensions of $\boldsymbol{x}$.*

190 *Proof.* If we utilize the 3-SAT energy function $E(\boldsymbol{x}, \boldsymbol{z})$ defined above. ETH implies that solving the
191 3-SAT problem, corresponding to computing $f(\boldsymbol{z}) = \arg\min_{\boldsymbol{x}} E(\boldsymbol{x}, \boldsymbol{z}_1)$, is exponential in dimension
192 of $\boldsymbol{x}$. In contrast, evaluating each entry of our defined $E(\boldsymbol{x}, \boldsymbol{z}_1)$ is polynomial in dimension of $\boldsymbol{x}$. □

193 Our remark shows that it is computationally advantageous to learn an energy function $E(\boldsymbol{x}, \boldsymbol{z})$ as
194 opposed to a decoder $f(\boldsymbol{z})$. To realize the exponential number of computations needed to compute
195 $f(\boldsymbol{z})$, significantly more capacity is necessary to represent $f(\boldsymbol{z})$ in comparision to $E(\boldsymbol{x}, \boldsymbol{z})$. We
196 further show that as we compose multiple 3-SAT energy functions together, learning a decoder
197 $f(\boldsymbol{z}_1, \ldots, \boldsymbol{z}_k) := \arg\min_{\boldsymbol{x}} \sum_k E(\boldsymbol{x}, \boldsymbol{z}_k)$ that represents the optimization process scales exponen-
198 tially with the number of energy components.

Remark 3. *There exists a composition of energy functions $\sum_k E(\boldsymbol{x}, \boldsymbol{z}_k)$ which can be evaluated*
200 *in time polynomial in the number of components k, but for which the computational complexity for*
201 *evaluating $f(\boldsymbol{z}_1, \ldots, \boldsymbol{z}_k) := \arg\min_{\boldsymbol{x}} \sum_k E(\boldsymbol{x}, \boldsymbol{z}_k)$ is (worst-case) exponential in the components*
202 *of components k.*

203 *Proof.* Given k separate 3-SAT energy functions $E(\boldsymbol{x}, \boldsymbol{z}_k)$, minimizing the composed energy func-
204 tion, $f(\boldsymbol{z}_1, \ldots, \boldsymbol{z}_k) = \arg\min_{\boldsymbol{x}} \sum_k E(\boldsymbol{x}, \boldsymbol{z}_k)$ corresponds to solving all 3-SAT encoded clauses
205 across k energy functions. ETH implies the computational complexity of evaluating $f(\boldsymbol{z}_1, \ldots, \boldsymbol{z}_k)$ is
206 exponential in k while the evaluation of k energy functions is polynomial in k. □

207 Here as well, to represent the exponential number of computations, significantly more capacity is
208 necessary to realize the computation $f(\boldsymbol{z}_1, \ldots, \boldsymbol{z}_k)$, which scales with the number of components k,
209 in comparison to $\sum_k E(\boldsymbol{x}, \boldsymbol{z}_k)$. Thus, remark 2 and 3 show that it can be efficient, from a learning
210 perspective, to decode individual datapoints with energy functions.

Figure 3: **Global Decomposition.** Illustration of gradients with respect to input images and generations from each inferred energy function in the Falcor3D and CelebA-HQ datasets. Generations from energy functions are initialized from random noise, so areas of noise in a generation correspond to what the energy function deems to be less important. COMET infers a distinct set of energy functions.

Figure 4: **Global Factor Recombination.** Illustration of recombination of energy functions on Falcor3D and CelebA-HQ datasets. Energy functions recombine nicely between different datapoints. Generations for each individual energy function recombined here can be found in Figure 3 .

5 Evaluation

We quantitatively and qualitatively show that COMET can recover the global factors of variation in an image in Section 5.1, as well as the local factors in an image in Section 5.2. Furthermore, we show that the components captured by COMET can generalize well, across separate modalities in Section 5.3.

5.1 Global Factor Disentanglement

We assess the ability of COMET to decompose global factors of variation in scenes consisting of lighting and camera illumination from Falcor3D (NVIDIA high-resolution disentanglement dataset) [40], scene factors of variation in CLEVR [29], and face attributes in real images from CelebA-HQ [30]. For all experiments, we utilize the same convolutional encoder to extract sets of latents from each dataset, and utilize a latent dimension of 64 for each separately inferred latent. We provide additional training algorithm and model architecture details in the appendix.

Decomposition and Reconstructions. In Figure 3, on Falcor3D and CelebA-HQ, we illustrate the decomposition of images into component energy functions. To visualize an individual energy function, we generate an image by optimizing only with respect to that energy function. As a result, since generations from individual energy functions are initialized with random noise, noise in the generation corresponds to areas the energy function is insensitive to.

Given the individual gradients and resultant generations, we posit that the individual inferred energy functions for Falcor3D correspond to camera position, lighting direction, floor position and lighting intensity. Similarly, we hypothesize that the individual inferred energy functions for CelebA-HQ correspond to hair color, background lighting, facial expression and skin color. In both settings, we find that our reconstructions are significantly better than $\beta-$VAE.

	+Object	+Floor	+Lighting

Input | Generation (Per additive component)

Figure 5: **CLEVR Decomposition.** Generations on CLEVR when optimizing over increasing number of energy functions.

Table 1: **Disentanglement Evaluation.** Quantitative evaluation on the Falcor3D dataset. COMET enables better disentanglement across 3 common disentanglement metrics across different runs and seeds for training β-VAE.

Model	Dim (D)	β	Decoder Dist.	BetaVAE	MIG	MCC
COMET	64	–	–	99.24	21.48	77.27
β-VAE	64	4	Gaussian	79.28	15.15	68.06
β-VAE	32	4	Gaussian	92.20	13.39	64.03
β-VAE	256	4	Gaussian	76.96	11.60	64.98
β-VAE	64	16	Gaussian	76.50	12.94	59.72
β-VAE	64	1	Gaussian	88.92	10.40	66.02
β-VAE	64	4	Bernoulli	86.36	12.04	65.36

Input | Gradient (Per Component) | Generation (Per Component) | Final | Input | Generation | Final

Figure 6: **Object Decomposition.** COMET can decompose underlying object-level factors of variation in CLEVR (left) and Tetris (right). Individual energy functions exhibit sharp gradients with respect to each object in CLEVR.

In Figure 5, we show energy function decompositions of CLEVR, where we illustrate generations when composing an increasing number of inferred energy functions. By adding individual energy functions, we find that the generation transitions from consisting only of objects, to consisting of objects & floor to consisting of objects, floor, & lighting.

Recombination. To further verify that each individual energy function captures the expected decomposition of factors described earlier, we recombine individual energy functions representing each component in the Falcor3D and CelebA-HQ datasets in Figure 4. In the left side of Figure 4, we can recombine the underlying camera position, lighting direction, and lighting intensity of one image with that of another. In the right side of Figure 4, we can recombine the underlying facial expression, hair color, and background lighting of one image with that of another.

Quantitative Comparison. Finally, we evaluate the learned representations on disentanglement. In Falcor3D [40], each image corresponds to a combination of 7 factors of variation; lighting intensity, lighting x, y & z direction, and camera x, y & z position. We consider three commonly used metrics for evaluation, the BetaVAE metric [23], the Mutual Information Gap (MIG) [7], and the Mean Correlation Coefficient (MCC) [25]. See Appendix C of [34] for extended descriptions of metrics.

Standardized metrics in disentanglement assume flattened model latents, i.e. relate the 7 factors of variation to the D-dimensional encoding of the corresponding image. However, as discussed, our method extracts sets of latents from images. We thus extract D principal components from the set of latents, which we then compare with the β-VAE. In Table 1, we find that our approach performs better than that of the β-VAE across hyperparameter settings.

5.2 Object Level Decomposition

Next, we assess the ability of COMET to decompose object-level factors of variation in an image. We evaluate the ability of COMET to isolate individual tetris blocks in the Tetris dataset from [22], and individual object segmentations in the CLEVR dataset [29]. To bias energy functions to local object-level variations, we utilize small latent dimension (16), and add positional embeddings to images. To extract repeated object-level structure in an image, we utilize a recurrent network as our encoder, similar to prior unsupervised object discovery work [5]. We provide additional training algorithm and model architecture details for each experimental setup in the appendix.

Figure 7: **Compositional Generalization (Left).** Generalization of compositions of energy functions to 8 separate energy functions (combining 4 separate object energy functions from each image). **Global/Local Factor Recombination (Right).** Recombination of both global factors of variation (lighting) and local factors of variation (cube position).

Figure 8: **Multimodal Decomposition.** COMET obtains consistent factor decompositions of images from Danbooru / CelebA-HQ faces (left) and KITTI / Virtual KITTI (right) dataset.

Decomposition and Reconstructions.   We illustrate object-level decomposition of individual energy functions on CLEVR and Tetris in Figure 6. In both settings, we find that individual energy functions correspond to the underlying objects in the scene. On CLEVR, while in Figure 5 we obtain global factor decompositions, by biasing our energy function to object level decompositions we obtain individual cube decompositions in Figure 6.

Combinatorical Recombination.   We next consider recombining inferred object components. In Figure 7 (left), we combine energy functions for individual CLEVR objects across two separate scenes. We find that by combining 8 energy functions corresponding to 4 objects from separate images, we are able to successfully generate an image containing all 8 objects, and with some consistency with respect to occlusion. In contrast, objects composed together through MONET do not respect occlusion, as they are represented as disjoint segmentation masks.

Quantitative Comparisons.   For quantitative comparison with MONET, we create approximate segmentation masks per energy function in CLEVR by thresholding the gradients (illustrated in (Figure 6) of the energy function. We find that our approach obtains an ARI [22] of 0.889. In contrast, we find MONET obtains a similar ARI of 0.873.

Decompositions of Global and Object Level Factors.   COMET is distinct from previous approaches for unsupervised decomposition in that it is able to decompose both global and local factors of variation. We render a novel dataset, *CLEVR Lighting*, by increasing the lighting variation in CLEVR (illustrated in Figure 7 (right)), and train COMET to infer 5 separate energy functions. To encourage the first energy function to capture a global factor of variation, we remove positional embedding from the first inferred energy function in particular. In such a setting, we find COMET successfully infers lighting as the first energy function, and individual objects for the subsequent components, which we illustrate in the appendix. We present recombinations of these inferred components in Figure 7 (right). A limitation of our approach is that that lighting and object factors of variations are not completely disentangled. For example in the the top row, the permuted reconstruction of the image has incorrect lighting in the center.

5.3   Compositional Factor Generalization

Finally, we assess the ability of components inferred from COMET to generalize. We study two separate settings of generalization. We first evaluate the ability of components to generalize to

Figure 9: **Multimodal Recombination.** Recombination of factors discovered by COMET across Danbooru / CelebA-HQ faces (left) and KITTI / Virtual KITTI (right).

Figure 10: **Cross Dataset Composition.** Components from COMET discovered in one dataset may be combined with components from COMET discovered in a seperate datasets. In the left panel, we combine components of objects discovered in CLEVR with components for toys in CLEVR Toy. In the right panel, we recombine objects from CLEVR with lighting and objects from CLEVR Lighting.

multi-modal inputs by training COMET to decompose images drawn from both CelebA-HQ and Danbooru datasets [3], as well as KITTI [19] and Virtual KITTI [6] datasets. We next assess the ability of components from COMET to compose with a separate instance of COMET. We train separate COMET models on CLEVR, CLEVR Lighting and an additional novel dataset, *CLEVR Toy*, which is rendered by replacing sphere/cylinder/cube objects with pin/boot/toy/truck objects.

Cross Modality Decomposition and Recombination. We assess COMET decompositions on multi-modal datasets of Danbooru/CelebA-HQ and KITTI/Virtual KITTI in Figure 8. We find consistent decomposition of components between separate modes. Furthermore, we find that these components may be recombined between the separate modalities in Figure 9.

Cross Dataset Recombination. COMET may compose inferred components from one dataset with components discovered by a separate COMET trained on a separate dataset. We validate this in Figure 10 (left), where we recombine components specifying objects in CLEVR and CLEVR Toy. In Figure 10 (right), we further recombine components specifying objects in CLEVR with components specifying objects & lighting in CLEVR Lighting.

6   Conclusion

We have demonstrated an approach towards unsupervised learning of energy functions from images. We show how these functions encode both global and local factors of variations, and how they allow for further composition across separate modalities and datasets. A limitation of our current approach is that while it can compose factors across datasets that are substantially similar, compositions across datasets such as Falcor3D and CelebA-HQ are less interpretable. We posit that this is due to a lack of diversity in the underlying training data set. An interesting direction for future work would be to to train COMET on complex, higher diversity real world datasets, and observe subsequent recombinations of energy functions. We note that, as a consequence of using deep nets, our system is susceptible to dataset bias. Care must be put in ensuring a balanced and fair dataset if COMET is deployed in practice, as it should not serve to, even inadvertently, worsen societal prejudice.

References

[1] Kelsey R. Allen, Kevin A. Smith, and Joshua B. Tenenbaum. Rapid trial-and-error learning with simulation supports flexible tool use and physical reasoning. *Proceedings of the National Academy of Sciences*, 117 (47):29302–29310, 2020. ISSN 0027-8424. doi: 10.1073/pnas.1912341117. URL `https://www.pnas.org/content/117/47/29302`.

[2] Anthony J Bell and Terrence J Sejnowski. An information-maximization approach to blind separation and blind deconvolution. *Neural Computation*, 7(6):1129–1159, 1995.

[3] Gwern Branwen. Danbooru2019 portraits: A large-scale anime head illustration dataset, 2019.

[4] Christopher P Burgess, Irina Higgins, Arka Pal, Loic Matthey, Nick Watters, Guillaume Desjardins, and Alexander Lerchner. Understanding disentangling in beta-vae. *arXiv preprint arXiv:1804.03599*, 2018.

[5] Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. Monet: Unsupervised scene decomposition and representation. *arXiv:1901.11390*, 2019.

[6] Yohann Cabon, Naila Murray, and Martin Humenberger. Virtual kitti 2, 2020.

[7] Tian Qi Chen, Xuechen Li, Roger Grosse, and David Duvenaud. Isolating sources of disentanglement in variational autoencoders. *arXiv:1802.04942*, 2018.

[8] Noam Chomsky. *Aspects of the Theory of Syntax*. The MIT Press, Cambridge, 1965. URL `http://www.amazon.com/Aspects-Theory-Syntax-Noam-Chomsky/dp/0262530074`.

[9] Pierre Comon. Independent component analysis, a new concept? *Signal processing*, 36(3):287–314, 1994.

[10] Eric Crawford and Joelle Pineau. Spatiial invariant unsupervised object detection with convolutional neural networks. In *Thirty-Third AAAI Conference on Artificial Intelligence*, 2019.

[11] Yilun Du and Igor Mordatch. Implicit generation and generalization in energy-based models. *arXiv preprint arXiv:1903.08689*, 2019.

[12] Yilun Du, Shuang Li, and Igor Mordatch. Compositional visual generation with energy based models. In *Advances in Neural Information Processing Systems*, 2020.

[13] Yilun Du, Shuang Li, Joshua B Tenenbaum, and igor Mordatch. Improved contrastive divergence training of energy based models. In *Proceedings of the 38th international conference on Machine learning*. ACM, 2021.

[14] Yilun Du, Kevin A. Smith, Tomer Ullman, Joshua B. Tenenbaum, and Jiajun Wu. Unsupervised discovery of 3d physical objects. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=lf7st0bJIA5`.

[15] Martin Engelcke, Adam R. Kosiorek, Oiwi Parker Jones, and Ingmar Posner. Genesis: Generative scene inference and sampling with object-centric latent representations. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=BkxfaTVFwH`.

[16] SM Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, Koray Kavukcuoglu, and Geoffrey E Hinton. Attend, infer, repeat: Fast scene understanding with generative models. In *NeurIPS*, 2016.

[17] SM Ali Eslami, Danilo Jimenez Rezende, Frederic Besse, Fabio Viola, Ari S Morcos, Marta Garnelo, Avraham Ruderman, Andrei A Rusu, Ivo Danihelka, Karol Gregor, et al. Neural scene representation and rendering. *Science*, 360(6394):1204–1210, 2018.

[18] Ruiqi Gao, Erik Nijkamp, Diederik P Kingma, Zhen Xu, Andrew M Dai, and Ying Nian Wu. Flow contrastive estimation of energy-based models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7518–7528, 2020.

[19] Andreas Geiger, Philip Lenz, and Raquel Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *CVPR*, 2012.

[20] Will Grathwohl, Kuan-Chieh Wang, Jörn-Henrik Jacobsen, David Duvenaud, Mohammad Norouzi, and Kevin Swersky. Your classifier is secretly an energy based model and you should treat it like one. *arXiv preprint arXiv:1912.03263*, 2019.

[21] Klaus Greff, Sjoerd van Steenkiste, and Jürgen Schmidhuber. Neural expectation maximization. In *NeurIPS*, 2017.

[22] Klaus Greff, Raphaël Lopez Kaufmann, Rishab Kabra, Nick Watters, Chris Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-object representation learning with iterative variational inference. *arXiv preprint arXiv:1903.00450*, 2019.

[23] Irina Higgins, Loic Matthey, Arka Pal, Christopher P Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. Beta-vae: Learning basic visual concepts with a constrained variational framework. In *ICLR*, 2017.

[24] Irina Higgins, Nicolas Sonnerat, Loic Matthey, Arka Pal, Christopher P Burgess, Matko Bosnjak, Murray Shanahan, Matthew Botvinick, Demis Hassabis, and Alexander Lerchner. Scan: Learning hierarchical compositional visual concepts. *ICLR*, 2018.

[25] Aapo Hyvärinen and Hiroshi Morioka. Unsupervised feature extraction by time-contrastive learning and nonlinear ica. In *Advances in Neural Information Processing Systems*, pages 3765–3773, 2016.

[26] Aapo Hyvärinen and Hiroshi Morioka. Nonlinear ica of temporally dependent stationary sources. In *Proceedings of Machine Learning Research*, 2017.

[27] Aapo Hyvärinen, Hiroaki Sasaki, and Richard E Turner. Nonlinear ica using auxiliary variables and generalized contrastive learning. *arXiv preprint arXiv:1805.08651*, 2018.

[28] R. Impagliazzo and R. Paturi. Complexity of k-sat. *Proceedings. Fourteenth Annual IEEE Conference on Computational Complexity (Formerly: Structure in Complexity Theory Conference) (Cat.No.99CB36317)*, Jun 1999. doi: 10.1109/ccc.1999.766282.

[29] Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *CVPR*, 2017.

[30] Tero Karras, Timo Aila, Samuli Laine, and Jaakko Lehtinen. Progressive growing of gans for improved quality, stability, and variation. In *ICLR*, 2017.

[31] Ilyes Khemakhem, Diederik P Kingma, and Aapo Hyvärinen. Variational autoencoders and nonlinear ica: A unifying framework. *International Conference on Artificial Intelligence and Statistics (AISTATS)*, 2020.

[32] Ilyes Khemakhem, Ricardo Monti, Diederik Kingma, and Aapo Hyvarinen. Ice-beem: Identifiable conditional energy-based deep models based on nonlinear ica. *Advances in Neural Information Processing Systems*, 33, 2020.

[33] Taesup Kim and Yoshua Bengio. Deep directed generative models with energy-based probability estimation. *arXiv preprint arXiv:1606.03439*, 2016.

[34] David A. Klindt, Lukas Schott, Yash Sharma, Ivan Ustyuzhaninov, Wieland Brendel, Matthias Bethge, and Dylan Paiton. Towards nonlinear disentanglement in natural data with temporal sparse coding. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=EbIDjBynYJ8.

[35] Adam Kosiorek, Hyunjik Kim, Yee Whye Teh, and Ingmar Posner. Sequential attend, infer, repeat: Generative modelling of moving objects. In *NIPS*, 2018.

[36] Brenden M Lake, Tomer D Ullman, Joshua B Tenenbaum, and Samuel J Gershman. Building machines that learn and think like people. *Behav. Brain Sci.*, 40, 2017.

[37] Rosanne Liu, Joel Lehman, Piero Molino, Felipe Petroski Such, Eric Frank, Alex Sergeev, and Jason Yosinski. An intriguing failing of convolutional neural networks and the coordconv solution, 2018.

[38] Francesco Locatello, Ben Poole, Gunnar Rätsch, Bernhard Schölkopf, Olivier Bachem, and Michael Tschannen. Weakly-supervised disentanglement without compromises. *arXiv preprint arXiv:2002.02886*, 2020.

[39] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention, 2020.

[40] Weili Nie, Tero Karras, Animesh Garg, Shoubhik Debnath, Anjul Patney, Ankit Patel, and Animashree Anandkumar. Semi-supervised StyleGAN for disentanglement learning. In *Proceedings of the 37th International Conference on Machine Learning*, pages 7360–7369, 2020.

[41] Erik Nijkamp, Mitch Hill, Tian Han, Song-Chun Zhu, and Ying Nian Wu. On the anatomy of mcmc-based maximum likelihood learning of energy-based models. *arXiv preprint arXiv:1903.12370*, 2019.

[42] Geoffrey Roeder, Luke Metz, and Diedrik P. Kingma. On linear identifiability of learned representations. *arXiv preprint arXiv:2007.00810*, 2020.

[43] Michal Rolinek, Dominik Zietlow, and Georg Martius. Variational autoencoders pursue pca directions (by accident). In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 12406–12415, 2019.

[44] Yunfu Song and Zhijian Ou. Learning neural random fields with inclusive auxiliary generators. *arXiv preprint arXiv:1806.00271*, 2018.

[45] Aleksandar Stanić and Jürgen Schmidhuber. R-sqair: Relational sequential attend, infer, repeat. *arXiv:1910.05231*, 2019.

[46] Sjoerd van Steenkiste, Michael Chang, Klaus Greff, and Jürgen Schmidhuber. Relational neural expectation maximization: Unsupervised discovery of objects and their interactions. *arXiv preprint arXiv:1802.10353*, 2018.

[47] Sjoerd van Steenkiste, Karol Kurach, and Sylvain Gelly. A case for object compositionality in deep generative models of images. *arXiv preprint arXiv:1810.10340*, 2018.

[48] Ramakrishna Vedantam, Ian Fischer, Jonathan Huang, and Kevin Murphy. Generative models of visually grounded imagination. In *ICLR*, 2018.

[49] Rishi Veerapaneni, John D Co-Reyes, Michael Chang, Michael Janner, Chelsea Finn, Jiajun Wu, Joshua B Tenenbaum, and Sergey Levine. Entity abstraction in visual model-based reinforcement learning. In *CoRL*, 2019.

[50] Jianwen Xie, Yang Lu, Song-Chun Zhu, and Yingnian Wu. A theory of generative convnet. In *International Conference on Machine Learning*, pages 2635–2644, 2016.

[51] Roland S Zimmermann, Yash Sharma, Steffen Schneider, Matthias Bethge, and Wieland Brendel. Contrastive learning inverts the data generating process. *arXiv preprint arXiv:2102.08850*, 2021.