Fairness-Aware Data Valuation for Supervised Learning

February 15, 2023

ABSTRACT

Data valuation is an ML field that studies the value of training instances towards a given predictive task. Although data bias is one of the main sources of downstream model unfairness, previous work in data valuation does not consider how training instances may influence both performance and fairness of ML models. Thus, we propose **F**airness-**A**ware **D**ata ValuatiO**n (FADO), a framework that can be used to incorporate fairness concerns into a series of ML tasks (e.g., data pre-processing, exploratory data analysis, active learning). We propose an entropy-based data valuation metric suited to address our two-pronged goal of maximizing both performance and fairness, which is more computationally efficient than existing metrics. We then show how FADO can be applied as the basis for unfairness mitigation pre-processing techniques. Our methods achieve promising results — up to a 40 p.p. improvement in fairness at a less than 1 p.p. loss in performance compared to a baseline — and promote fairness in a data-centric way, where a deeper understanding of data quality takes center stage.

1 INTRODUCTION

A key ingredient in machine learning (ML) is the data used to train models (Hestness et al., 2017; Najafabadi et al., 2015). Even specific instances have been shown to play a crucial part in the performance of ML models (Toneva et al., 2019; Ngiam et al., 2018; Zhu et al., 2020): there can be more valuable and less valuable training data instances, with respect to a certain metric of interest. The field of data valuation has arisen in this context, with the goal of associating each training datum with its corresponding value. Several approaches for data valuation have been proposed (Ghorbani & Zou, 2019; Yoon et al., 2020; Ghorbani et al., 2020; Kwon & Zou, 2022; Sim et al., 2022) and have been applied in a series of applications, such as noisy labels detection, and active learning, with varying degrees of success (Ghorbani & Zou, 2019; Yoon et al., 2020; Kwon & Zou, 2022; Ghorbani et al., 2021).

However, along with their exceptional performance in some tasks, ML algorithms have been shown to have the potential to exacerbate and propagate biases embedded within data (Angwin et al., 2016; Howard & Borenstein, 2018; O'Neil, 2016). This is especially true if such models are trained with regards only to some performance metric, and if they are treated as unamenable black boxes. Such a stance is particularly problematic in high-stakes decision-making domains, where biased policies may result in certain social groups being systematically discriminated, and locked out of important goods and services (e.g., by race, sex). This phenomenon has sparked the creation of the field of fair ML, which has grown rapidly in recent years (Caton & Haas, 2020; Mehrabi et al., 2021; Pessach & Shmueli, 2022).

Just as data plays a part in the performance of models, so does it play a part in their potential for discrimination (Chakraborty et al., 2021; Chen et al., 2018; Verma et al., 2021; Wang et al., 2021). Indeed, data bias can shape the landscape of fairness and performance (Pombal et al., 2022a;b), but little work has been made to understand the sources of these biases. Thus, we propose fairness-aware data valuation (FADO), a data valuation framework that allows measuring which training

instances contribute the most to both performance and fairness of models. We also propose an entropy-based data valuation metric that is specifically tailored to relate to model performance and data bias concerns. We argue that the proposed framework embodies the ultimate goal of fair ML, which is to incorporate fairness concerns into ML systems, while keeping their performance high. FADO can be used in the same ways as data valuation, and, as such, can be a vehicle to introduce fairness concerns into a series of upstream and downstream tasks, such as data pre-processing, active learning, data generation, and exploratory data analysis (EDA).

In summary, we make the following contributions: **1)** we propose fairness-aware data valuation framework that is based on a notion of utility that incorporates the value of specific instances towards both performance and fairness (lack of data bias). It can be used with continuous and categorical targets and protected attributes, as well as to promote subgroup fairness (see Section 3.1). **2)** we introduce an entropy-based notion of data value, which can be used in any predictive task, and therefore used to calculate an instance's value towards accurate prediction of a target Y, and data bias with respect to one or more protected attributes (see Section 3.2). **3)** we conduct an evaluation of how the framework can be used for fairness-aware training data sampling and re-weighing for promising results on a real world use-case.

2 BACKGROUND & RELATED WORK

This work focuses on supervised learning, where data valuation is usually framed in the following way (Ghorbani & Zou, 2019; Ghorbani et al., 2021; 2020; Yoon et al., 2020; Karlaš et al., 2022): given a set of training data with *n* data instances, each characterized by a feature vector x_i (in which one, or more, protected attribute(s) z_i may be included), and a target variable y_i, the goal is to find the value v_i of each training instance, with respect to some value metric of interest V, obtained by a learning algorithm f trained to predict y_i, given x_i. How v_i is calculated varies from work to work. Ghorbani & Zou (2019) take a game-theoretical approach and calculate the Data Shapley value of each data instance. Although this method enjoys a series of desirable properties, it is intractable to compute, and approximations have been proposed by the original authors, and in other works (Kwon & Zou, 2022; Ghorbani et al., 2020; Karlaš et al., 2022). Conversely, Yoon et al. (2020) take a reinforcement learning approach (DVRL), where a data valuator model is jointly trained with the predictor of the task from which V is calculated.

As for the metric of interest, Ghorbani & Zou (2019) and Yoon et al. (2020) set V as the accuracy of a predictor f on unseen data (test set), with v_i being the importance of data instance i towards achieving the performance that predictor f obtains when trained on the whole dataset. However, V can be any metric of interest; Karlaš et al. (2022), for example, perform data valuation with equalized odds difference (Hardt et al., 2016) as V. That said, a glaring gap in the literature is that no work defines V as a combination of performance and fairness. These components, if fairness is mentioned, are always shown separately. However, the main goal of fair ML is to maximize both predictive performance and fairness. Furthermore, besides some applications in active learning and noisy instance detection, data valuation has never been used for fairness-promoting interventions.To bridge this gap, we lay out a framework that defines V as a function of both performance and data bias (fairness), and show how it can be used to promote observational fairness. Being an inherently data-centric task, we also believe that fairness-aware data valuation responds in some ways to the lack of exploratory data analysis tools in fair ML.

3 FAIRNESS-AWARE DATA VALUATION

3.1 FRAMEWORK

As mentioned before, the key component of our framework is the definition of V as a function of both performance and fairness, rather than having them be separate components. Our task is not only to accurately predict Y, but also to do it fairly. We shall refer to our metric of interest as utility (U) from here on in. This nomenclature is inspired by the economics literature, where the well-being (utility) of an individual is defined as a function of the utility derived from a weighted combination of factors (e.g., economic goods), rather than a single one. In our case, utility is a function of performance and fairness; how it is maximized depends on the definition of the function

and on the weights attributed to performance and fairness. Thus, the utility of a single data instance can be written as $U_i(v_{y_i}, v_{z_i})$, where v_{y_i} is the performance-related valuation of instance i, and v_{z_i} is the fairness-related one.

We propose two types of utility functions; a linear scalarization one:

$$U_i = \alpha v_{y_i} + (1 - \alpha) v_{z_i}, \tag{1}$$

where $\alpha \in [0, 1]$ governs the relative weight placed on performance and fairness, and a multiplicative scalarization one, inspired by the Cobb-Douglas formulation (Douglas, 1976) (widely used in Economics):

$$U_i = v_{y_i}^{\alpha} \cdot v_{z_i}^{1-\alpha}, \tag{2}$$

where α plays the same role as above. Each of these utilities abide by the principles of fair ML and, thus, the FADO framework, as they strike a balance between performance and fairness: both unfair, high-performing systems, and fair, low-performing systems, are inferior in terms of utility to systems that achieve acceptable values for both metrics. However, the two functions encode distinct preferences as far as this balance goes. For example, the multiplicative utility is zero if either valuation is zero, whereas the linear utility is not. Thus, if a practitioner is not interested in gains in performance if they do not lead to gains in fairness, they should opt for the multiplicative utility.

This general framework allows reasoning about and obtaining fairness-aware valuations for data instances, which can then be used for downstream tasks. Our framework can also be extended to applications concerned with subgroup fairness (fairness across a series of protected attributes and their combinations; one needs only to include several Z terms in the utility function. For example, in a case where there are k protected attributes Z_k, a linear utility function can be defined as:

$$U_i = \alpha v_{y_i} + \sum_{j=1}^{k} \beta_j v_{z_{j_i}}, \tag{3}$$

In the next Section, we propose an entropy-based metric for FADO, which is versatile for both performance- and fairness-related data valuation.

3.2 ENTROPY METRIC

The main challenge posed by the framework is to define and calculate a v_y for the predictive task at hand, and v_z for the fairness component of the utility. These could be, for example, the Data Shapley value with respect to a validation set accuracy in the predictive task (v_y) and the Shapley value with respect to, for instance, a validation set equality of opportunity difference among protected groups in the same predictive task (v_z). Such a choice would be appropriate within the framework, but entails two difficulties: first, it limits the user to a specific fairness metric, which as we have seen, often implies sacrificing others; second, data Shapley values are intractably hard to compute, thus they must be approximated. Instead, we propose a more metric-agnostic valuation, which is inspired by the literature on uncertainty estimation and active learning (for v_y), and on the data bias taxonomy proposed by Pombal et al. (2022a).

For some data instance i, we propose to define v_{y_i} as the corresponding prediction Shannon entropy, averaged over the output of one or more trained models[1]. In binary classification, the Shannon entropy (E) for uncertainty sampling for an instance i and prediction $\hat{y}_i$ is:

$$V_{y_i} = E_{y_i} = \hat{y}_i \cdot \log_2 \hat{y}_i + (1 - \hat{y}_i) \cdot \log_2(1 - \hat{y}_i) \tag{4}$$

The rationale behind choosing the entropy without the target label is inspired by active learning, where there is abundant data outside the training set, but a small budget to label it, and thus it is vital

---

[1]In the binary classification case; for multi-class, the metric could be cross-entropy; for regression, the metric would have to be the prediction's difference from the sample mean, for example.

to choose which instances to label. A popular method in active learning is *uncertainty sampling* (Lewis & Gale, 1994; Settles, 2009), where an ML model trained on data subsequently chooses to obtain labels for the observations on which it is most unsure (with the highest entropy). The idea is that the model will learn more from adding these observations to the training set, than by adding observations on which the model is sure, as the training data already contains that information. This metric is not perfect, since being confident does not necessarily mean being right, and high entropy observations may simply be noisy and not necessarily useful. However, it is a useful valuation heuristic, which has been shown to work well in many settings, including fraud detection (Lewis & Gale, 1994; Yang & Loog, 2018; Barata et al., 2021; Lorenz et al., 2020). We extend this rationale to data valuation and attribute the highest values to the instances with the highest entropy. In other words, we attribute less value to instances where the model is very sure, since there is reason to believe that these encode redundant information.

As for v_{z_i}, the metric is the same, but using a predictor of Z, rather than of Y. For an instance i, a binary protected attribute z_i, and predicted group $\hat{z}_i$, we have:

$$V_{z_i} = E_{z_i} = \hat{z}_i \cdot \log_2 \hat{z}_i + (1 - \hat{z})_i \cdot \log_2(1 - \hat{z}_i) \tag{5}$$

Notice that the metric is essentially the same for v_y and v_z, but for different reasons. In the first case, we want to prioritize observations on which the model had more difficulty during training, since these might contain less redundant information. In the second case, where the variable in question (Z) is not the target for the task at hand, and is seen by the model even at inference time, we prioritize observations where the model had more difficulty in establishing a relationship among X, Y, and Z, leveraging the fact the model has no explicit incentive to draw such relationships. This is directly related to mitigating the base bias condition of the taxonomy of Pombal et al. (2022a) ($\mathbb{P}[X, Y] \neq \mathbb{P}[X, Y|Z]$), and so related to promoting fairness. This metric can also be seen as a means to promote procedural fairness (Greenberg, 1987): we are "telling" the model to pay less attention during training to the protected attribute, and whatever variables may be related with it.

The resulting combination of v_y and v_z is a utility measure that balances both performance and fairness by assigning lower value to redundant information about Y and excessive information about Z in the data. Using a linear scalarization utility function, we would get:

$$U_i = \alpha E_{y_i} + (1 - \alpha) E_{z_i} \tag{6}$$

Recently, Xu et al. (2022) proposed using entropy as a measure of data value for online ML tasks (with respect only to performance). Other metrics, such as data shapley, are not suitable for these settings, as they require a fixed dataset. Our rationale for using entropy is similar to that of Xu et al., but we extend it seamlessly to the context of data bias and fairness, and to offline ML tasks. In terms of computation, our method requires only the additional training of a model for Z. This corresponds — in our case of binary classification and a binary protected attribute — to a roughly two-fold increase in training time, which is much faster than Data Shapley or DVRL alternatives.

4   Unfairness Mitigation Pre-processing with FADO

4.1   Dataset

Based on the proposed framework, we apply unfairness mitigation pre-processing interventions on AOF, a real-world large-scale bank account-opening fraud dataset. Fraud detection is an extremely pertinent field for fair ML, since holding a bank account is seen as a basic right in the European Union (European Parliament and Council, 2014). In this use case of fraud, fraudsters attempt to impersonate someone to open an account, and quickly exhaust its line of credit. Each row in the dataset corresponds to an application for opening a bank account, submitted via the online portal of a large retail bank. Data was collected over an 8-month period and contains over 500K rows. The first 6 months are used for training and the last 2 months are used for testing, mimicking the procedure of a real-world production environment.

4.2 EVALUATION FRAMEWORK

Fraud rate (positive label prevalence) is about 1% in both sets. This means that a naïve classifier that labels all observations as *not fraud* achieves a test set accuracy of almost (99%). Such large class imbalance entails certain additional challenges for learning (He & Garcia, 2009), and calls for a specific evaluation framework. In particular, bank account providers are not willing to go above a certain level of FPR, because each false positive may lead to customer attrition (unhappy clients who may wish to leave the bank). At an enterprise-wide level, this may represent losses that outweigh the gains of detecting fraud. The goal is then to maximize the detection of fraudulent applicants (high global true positive rate, TPR), while maintaining low customer attrition (low global false positive rate). As such, we evaluate the model's TPR at a fixed FPR, imposed as a business requirement in our case-study; we assess the FPR ceiling of 5%. As for fairness, we consider three popular metrics for classification settings: the ratio of group-wise FPRs, *predictive equality* (Corbett-Davies et al., 2017), the ratio of group-wise FNRs, a form of *equality of opportunity* (Hardt et al., 2016), and the ratio of group-wise predicted positive rate, *demographic parity* (Dwork et al., 2012). The protected attribute used will be the client's age (to counteract *ageism*).

4.3 EXPERIMENTAL SETUP

We wish to apply some pre-processing method on our training data in order to maximize performance and fairness on unseen data. To this end, our pre-processing method consists of three steps: first, computing each training instance's value with respect to Y and Z. Second, computing the utility of each instance, given a utility function and respective parameters. Third, sampling or reweighing the training set before training models. If sampling is done, the instances with lower utility are discarded first. In the case of reweighting, the instances with higher utility are assigned larger weights during training. We consider two strategies: utility-aware prevalence sampling (UASP), and utility-aware reweighting (UAR). UASP consists of undersampling the data, such that protected groups have the same prevalence (fraud rate); in our dataset, this means discarding label negatives of the group with the lowest fraud rate, starting with the instances with the least utility, until fraud rates are balanced. UAR implies assigning weights to each observation in the training set prior to training, where the weight corresponds to the instances utility — the full training set is used. We experiment with several hyperparameter configurations of the above approaches (see Appendix C).

After each preprocessing intervention, the resulting dataset (and instance weights, if it is the case) is used to train 25 LighGBM models (with hyperparameters sampled from a grid), which are then used to make predictions on a test set (the same 25 models are used throughout). LightGBM was chosen for being a state-of-the-art algorithm for tabular data, and for easily allowing weights to be assigned to instances during training. To highlight the models that achieve the best performance-fairness trade-offs, we also analyze the Pareto frontier (Pareto, 1919) of the landscape. We also outline the 80% rule (Meier et al., 1984) threshold as a guideline for how fair models should be: the best models are those the best performers above this threshold of fairness. We compare our fairness-aware data valuation approaches to the case of no intervention (the full training set), random prevalence sampling (RPS, same as UASP, but observations are randomly discarded, instead of using a utility-based order) and reweighing (RW) (Kamiran & Calders, 2012).

4.4 RESULTS & DISCUSSION

Figures 1 summarizes the performance-fairness trade-off landscape achieved by the models in the test set, trained on data that underwent the pre-processing techniques mentioned in the previous section. It plots performance on the x-axis, and fairness on the y-axis; circles represent the no intervention and literature baselines, while triangles and squares represent our prevalence sampling and reweighing methods, respectively. On our methods, the color varies between green and red. Greener points were trained on data that was pre-processed with a higher weight on fairness in the FADO utility function; redder points had a higher weight placed on performance. The underlying goal of this task is to maximize both performance and fairness, so the best points are the ones closest to the top right corner of the plots. In particular, we care about the points with the highest performance above the 0.8 line, since this represents the aforementioned 80% rule.

First, as expected, there seems to be relationship between alpha (the parameter that governs the weight placed on performance and data bias in the utility functions) and the fairness-accuracy land-

Figure 1: Each point corresponds to one of 25 LightGBM models trained on the corresponding pre-processesed training set (see legend). The axes represent performance and fairness on the test set in the task of predicting fraud (Y). Points that lie on the Pareto frontier of the two dimensions are represented by the larger, more opaque markers; small opaque markers are present to aid the visibility of baselines. The α colorbar represents the weight attributed to performance (α) and fairness (1 - α) in the utility function of our methods. The promising fairness-accuracy trade-off mentioned in the abstract can be found by comparing the rightmost dark blue circle on the leftmost plot, with the rightmost point above the 0.8 line.

scape — the top performing models tend to be related to a higher α, while the fairest models feature lower α. Furthermore, the best trade-offs on the Pareto frontier (high performance and high fairness) seem to be achieved by mid-range values (α around 0.5), which suggests that a balanced valuation of points allows models to be much fairer at little loss in performance. Notice, for example, on the leftmost plot of Figure 1, the opaque squares with TPR around 0.77 and fairness above 0.85. It also seems that steep increases in fairness can be achieved with only slight drops in performance, for all fairness metrics. The relative abundance of points coloured between blue and red can be explained by the fact that for each of our proposed methods (UAPS, and UAR) there are more hyperparameters to choose from, and with which we experimented.

Comparing our methods with those from the literature, ours present the best performance above the 0.8 fairness line for all three fairness metrics tested. Figure 1 shows that even outside the Pareto frontier, our methods seem to occupy spaces of higher fairness, for a given level of performance, than RPS and RW — especially our reweighing approach (UAR). This meets our expectations, since our methods attempt to tackle all sources of data bias, instead of just prevalence disparity which is the case with RPS and RW (though the latter achieves this in an indirect way, without discarding examples). Comparing among our own methods, reweighing approaches seem to obtain the best trade-offs. Not only do they feature several points on the Pareto frontier of all fairness metrics, but they also seem to perform better in general. This was in part to be expected, as these methods do not require examples to be discarded, thus, in principle, leaving more information in the data for models to learn from. Disregarding fairness for a moment, we can see that our approaches, for high values of α, are useful to increase the performance of ML models. They can reach up to about 1 extra TPR point, when compared to the best performing models trained on the training set without intervention.

5 Conclusions and Future Work

We introduced a framework and metric to relate performance and data bias to specific data instances. Our framework can be applied with any type of classification or regression task, as well with any number of categorical and continuous protected attributes. We also introduced an entropy-based notion of value and utility, which incorporates both performance and (procedural) fairness concerns. To validate the framework and the proposed metric, we showed how they could be applied in the context of an unfairness mitigation pre-processing intervention in binary classification setting (training set sampling and reweighing). A benchmark on our real-world fraud detection dataset showed that our methods often outperform existing ones in the literature, in terms of fairness-accuracy trade-offs. In the future, we would like to extend this benchmark to inlcude other datasets and baselines. We believe that tracing data bias to specific training instances is a promising practice to further the understanding of algorithmic unfairness and to add another layer of insight to data exploration and other tasks along the ML pipeline, like active learning — a priority for future work as well.

REFERENCES

Julia Angwin, Jeff Larson, Lauren Kirchner, and Surya Mattu. Machine Bias: There's software used across the country to predict future criminals. And it's biased against blacks, May 2016.

Ricardo Barata, Miguel Leite, Ricardo Pacheco, Marco O. P. Sampaio, João Tiago Ascensão, and Pedro Bizarro. Active learning for imbalanced data under cold start. In *Proceedings of the Second ACM International Conference on AI in Finance*, ICAIF '21, pp. 1–9, New York, NY, USA, November 2021. Association for Computing Machinery. ISBN 978-1-4503-9148-1. doi: 10.1145/3490354.3494423.

Simon Caton and Christian Haas. Fairness in Machine Learning: A Survey, October 2020.

Joymallya Chakraborty, Suvodeep Majumder, and Tim Menzies. Bias in Machine Learning Software: Why? How? What to Do? In *Proceedings of the 29th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*, ESEC/FSE 2021, pp. 429–440, New York, NY, USA, August 2021. Association for Computing Machinery. ISBN 978-1-4503-8562-6. doi: 10.1145/3468264.3468537.

Irene Chen, Fredrik D Johansson, and David Sontag. Why Is My Classifier Discriminatory? In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Sam Corbett-Davies, Emma Pierson, Avi Feller, Sharad Goel, and Aziz Huq. Algorithmic Decision Making and the Cost of Fairness. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '17, pp. 797–806, New York, NY, USA, August 2017. Association for Computing Machinery. ISBN 978-1-4503-4887-4. doi: 10.1145/3097983.3098095.

Paul H. Douglas. The Cobb-Douglas Production Function Once Again: Its History, Its Testing, and Some New Empirical Values. *Journal of Political Economy*, 84(5):903–915, October 1976. ISSN 0022-3808. doi: 10.1086/260489.

Cynthia Dwork, Moritz Hardt, Toniann Pitassi, Omer Reingold, and Richard Zemel. Fairness through awareness. In *Proceedings of the 3rd Innovations in Theoretical Computer Science Conference*, ITCS '12, pp. 214–226, New York, NY, USA, January 2012. Association for Computing Machinery. ISBN 978-1-4503-1115-1. doi: 10.1145/2090236.2090255.

European Parliament and Council. Directive 2014/92/EU of the European Parliament and of the Council of 23 July 2014 on the comparability of fees related to payment accounts, payment account switching and access to payment accounts with basic features. *Official Journal of the European Union (OJ)*, 57:214, 2014.

Amirata Ghorbani and James Zou. Data Shapley: Equitable Valuation of Data for Machine Learning. In *Proceedings of the 36th International Conference on Machine Learning*, pp. 2242–2251. PMLR, May 2019.

Amirata Ghorbani, Michael Kim, and James Zou. A Distributional Framework For Data Valuation. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 3535–3544. PMLR, November 2020.

Amirata Ghorbani, James Zou, and Andre Esteva. Data Shapley Valuation for Efficient Batch Active Learning, April 2021.

Jerald Greenberg. A Taxonomy of Organizational Justice Theories. *Academy of Management Review*, 12(1):9–22, January 1987. ISSN 0363-7425. doi: 10.5465/amr.1987.4306437.

Moritz Hardt, Eric Price, Eric Price, and Nati Srebro. Equality of Opportunity in Supervised Learning. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016.

Haibo He and Edwardo A. Garcia. Learning from Imbalanced Data. *IEEE Transactions on Knowledge and Data Engineering*, 21(9):1263–1284, September 2009. ISSN 1558-2191. doi: 10.1109/TKDE.2008.239.

Joel Hestness, Sharan Narang, Newsha Ardalani, Gregory Diamos, Heewoo Jun, Hassan Kianinejad, Md Mostofa Ali Patwary, Yang Yang, and Yanqi Zhou. Deep Learning Scaling is Predictable, Empirically, December 2017.

Stephen C. Hora. Aleatory and epistemic uncertainty in probability elicitation with an example from hazardous waste management. *Reliability Engineering & System Safety*, 54(2):217–223, November 1996. ISSN 0951-8320. doi: 10.1016/S0951-8320(96)00077-4.

Ayanna Howard and Jason Borenstein. The ugly truth about ourselves and our robot creations: The problem of bias and social inequity. *Science and engineering ethics*, 24(5):1521–1536, 2018.

Faisal Kamiran and Toon Calders. Data preprocessing techniques for classification without discrimination. *Knowledge and Information Systems*, 33(1):1–33, October 2012. ISSN 0219-3116. doi: 10.1007/s10115-011-0463-8.

Bojan Karlaš, David Dao, Matteo Interlandi, Bo Li, Sebastian Schelter, Wentao Wu, and Ce Zhang. Data Debugging with Shapley Importance over End-to-End Machine Learning Pipelines, April 2022.

Yongchan Kwon and James Zou. Beta Shapley: A Unified and Noise-reduced Data Valuation Framework for Machine Learning. In *Proceedings of The 25th International Conference on Artificial Intelligence and Statistics*, pp. 8780–8802. PMLR, May 2022.

DD Lewis and WA Gale. A sequential algorithmfor training text classifiers. In *Proc. ofSIGIR-94, 17th ACM International Conference on Research and Development in Information Retrieval*, pp. 3–12, 1994.

Joana Lorenz, Maria Inês Silva, David Aparício, João Tiago Ascensão, and Pedro Bizarro. Machine learning methods to detect money laundering in the bitcoin blockchain in the presence of label scarcity. In *Proceedings of the First ACM International Conference on AI in Finance*, ICAIF '20, pp. 1–8, New York, NY, USA, October 2020. Association for Computing Machinery. ISBN 978-1-4503-7584-9. doi: 10.1145/3383455.3422549.

Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A Survey on Bias and Fairness in Machine Learning. *ACM Computing Surveys*, 54(6):1–35, July 2021. ISSN 0360-0300, 1557-7341. doi: 10.1145/3457607.

Paul Meier, Jerome Sacks, and Sandy L. Zabell. What happened in hazelwood: Statistics, employment discrimination, and the 80% rule. *American Bar Foundation Research Journal*, 9(1): 139–186, 1984.

Maryam M. Najafabadi, Flavio Villanustre, Taghi M. Khoshgoftaar, Naeem Seliya, Randall Wald, and Edin Muharemagic. Deep learning applications and challenges in big data analytics. *Journal of Big Data*, 2(1):1, February 2015. ISSN 2196-1115. doi: 10.1186/s40537-014-0007-7.

Jiquan Ngiam, Daiyi Peng, Vijay Vasudevan, Simon Kornblith, Quoc V. Le, and Ruoming Pang. Domain Adaptive Transfer Learning with Specialist Models, December 2018.

Cathy O'Neil. *Weapons of Math Destruction: How Big Data Increases Inequality and Threatens Democracy*. Crown, 2016.

Vilfredo Pareto. *Manuale Di Economia Politica: Con Una Introduzione Alla Scienza Sociale*, volume 13. Società editrice libraria, 1919.

Dana Pessach and Erez Shmueli. A Review on Fairness in Machine Learning. *ACM Computing Surveys*, 55(3):51:1–51:44, February 2022. ISSN 0360-0300. doi: 10.1145/3494672.

José Pombal, André F. Cruz, João Bravo, Pedro Saleiro, Mário A. T. Figueiredo, and Pedro Bizarro. Understanding Unfairness in Fraud Detection through Model and Data Bias Interactions. In *KDD 2022 Workshop on Machine Learning in Finance*, July 2022a. doi: 10.48550/arXiv.2207.06273.

José Pombal, Pedro Saleiro, Mário A. T. Figueiredo, and Pedro Bizarro. Prisoners of Their Own Devices: How Models Induce Data Bias in Performative Prediction. In *ICML 2022 Workshop on Responsible Decision Making in Dynamic Environments*, August 2022b. doi: 10.48550/arXiv.2206.13183.

Burr Settles. Active Learning Literature Survey. Technical Report, University of Wisconsin-Madison Department of Computer Sciences, 2009.

Rachael Hwee Ling Sim, Xinyi Xu, and Bryan Kian Hsiang Low. Data Valuation in Machine Learning: "Ingredients", Strategies, and Open Challenges. In *Thirty-First International Joint Conference on Artificial Intelligence*, volume 6, pp. 5607–5614, July 2022. doi: 10.24963/ijcai.2022/782.

Mariya Toneva, Alessandro Sordoni, Remi Tachet des Combes, Adam Trischler, Yoshua Bengio, and Geoffrey J. Gordon. An Empirical Study of Example Forgetting during Deep Neural Network Learning. In *7th International Conference on Learning Representations, {ICLR} 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. doi: 10.48550/arXiv.1812.05159.

Sahil Verma, Michael Ernst, and Rene Just. Removing biased data to improve fairness and accuracy, February 2021.

Jialu Wang, Yang Liu, and Caleb Levy. Fair Classification with Group-Dependent Label Noise. In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '21, pp. 526–536, New York, NY, USA, March 2021. Association for Computing Machinery. ISBN 978-1-4503-8309-7. doi: 10.1145/3442188.3445915.

Anran Xu, Zhenzhe Zheng, Fan Wu, and Guihai Chen. Online Data Valuation and Pricing for Machine Learning Tasks in Mobile Health. In *IEEE INFOCOM 2022 - IEEE Conference on Computer Communications*, pp. 850–859, May 2022. doi: 10.1109/INFOCOM48880.2022.9796669.

Yazhou Yang and Marco Loog. A benchmark and comparison of active learning for logistic regression. *Pattern Recognition*, 83:401–415, November 2018. ISSN 0031-3203. doi: 10.1016/j.patcog.2018.06.004.

Jinsung Yoon, Sercan Arik, and Tomas Pfister. Data Valuation using Reinforcement Learning. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 10842–10851. PMLR, November 2020.

Linchao Zhu, Sercan Ö. Arık, Yi Yang, and Tomas Pfister. Learning to Transfer Learn: Reinforcement Learning-Based Selection for Adaptive Transfer Learning. In Andrea Vedaldi, Horst Bischof, Thomas Brox, and Jan-Michael Frahm (eds.), *Computer Vision – ECCV 2020*, Lecture Notes in Computer Science, pp. 342–358, Cham, 2020. Springer International Publishing. ISBN 978-3-030-58583-9.

A ALGORITHMS TO COMPUTE ENTROPY

Computing the required entropy-based metric for v is not as straightforward as in active learning, since our goal is to obtain valuations for a fully-labeled training set, and for two variables (Y and Z). With this in mind, we propose two algorithms. The first relies on creating bags from the training data of seen and unseen data, and training several models on each bag, from which entropy is obtained — akin to k-fold cross-validation. This is more closely related to active learning, since it involves a component of unseen data for which the model makes predictions. The second algorithm is arguably more straightforward as it does not involve sampling the training set, but is more a measure of epistemic uncertainty rather than a combination of epistemic and aleatoric uncertainty (Hora, 1996) (as is the case with the active learning case)[2].

Algorithm 1 FADO Out-of-bag Entropy Algorithm

Input: training set *D*; variable of interest *var*; number of bags *n_bags*; % of train in each unseen set in each bag *pct_unseen*; models to train (pre-defined by user) *M*
Output: valuation vector with respect to *var V*

1: *in_bag_sets*, *out_of_bag_sets* ← Split *D* into *n_bags*, each with *pct_unseen* of *D* into an out-of-bag set, and the rest into an in-bag set   ▷ Data is sampled without replacement within each bag, but with replacement across bags; each observation must appear in at least one set of out-of-bag data
2: *v_list* ← Empty list for intermediate target variable valuations
3: **for** in_bag, out_of_bag ∈ [in_bag_sets, out_of_bag_sets] **do**
4:      **for** m ∈ M **do**
5:          *fitted_m* ← Train *m* on *in_bag* to predict *var*
6:          *v* ← Vector of entropies of all predictions of *fitted_m* on *out_of_bag*
7:          *v_list* ← Append *v*
8:      **end for**
9: **end for**
10: *V* ← Average entropies of each observation over all intermediate valuations in *v_list*

Algorithm 2 FADO In-bag Entropy Algorithm

Input: training set *D*; variable of interest *var*; models to train (pre-defined by user) *M*
Output: valuation vector with respect to *var V*

1: **for** m ∈ M **do**
2:      *fitted_m* ← Train *m* on *D* to predict *var*
3:      *v* ← Vector of entropies of all predictions of *fitted_m* on *D*
4:      *v_list* ← Append *v*
5: **end for**
6: *V* ← Average entropies of each observation over all intermediate valuations in *v_list*

Figure 2: One iteration of the bagging-based algorithm, with one bag, one model for Y, and one model for Z. The final utility vector is obtained by averaging out all entropies obtained over each iteration, for each observation, and combining them into utilities.

---
[2]Loosely speaking, the latter pertains to uncertainty incorporated by the model, while the former pertains to uncertainty inherent to the data.

To obtain a measure of utility, one must run either algorithm with Y as the target (to calculate v_y) and with Z as the target (to obtain v_z), for the same training set, models, and bagging splits (if algorithm 1 is chosen). The final utility measure is then dependent on the chosen utility function, and its parameters. As we argued in the previous section, we believe this entropy-based valuation is best suited for a utility function to which both v_y and v_z contribute positively (e.g., the linear and multiplicative utilities shown in Section 3.1). In terms of the desiderata for data valuation strategies put forth recently by Sim et al. (2022), our entropy-based metric satisfies D1-D3, and D7 and D9 if the sum of the entropies of each observation is seen to be the value of the whole dataset.

B   ADDITIONAL RESULTS PLOT

Figure 3: Zoomed out version of Figure 1.

C   HYPERPARAMETERS

Hyperparameter	Distribution	Values	Description
boosting_type	-	"goss"	Boosting type
n_estimators	Log-uniform	{20, 10000}	Number of base tree learners
num_leaves	Log-uniform	{10, 1000}	Maximum leaves of a tree
min_child_samples	Log-uniform	{5, 300}	Min. num. samples needed to create a leaf node
max_depth	Log-uniform	{2, 20}	Maximum depth of a tree
learning_rate	Log-uniform	[0.02, 0.5]	Boosting learning rate

Table 1: Model hyperparameter grid for LightGBM.

To compute data valuations, all permutations of the hyperparameters below were tried (v_y is the entropy of the Y classifier, v_z is the entropy of the Z classifier):

Utility functions: $U = \alpha v_y + (1 - \alpha)v_z$, $U = \alpha v_y - (1 - \alpha)v_z$, $U = v_y^\alpha v_z^{1-\alpha}$;

alpha (α): [0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1];

Weights scaling: "min-max scaling", "no scaling" (only used for UAR);

Entropy algorithms: "bagging", "epistemic" (the ones proposed in Section A);