SimNet: Enabling Robust Unknown Object Manipulation from Pure Synthetic Data via Stereo

Abstract: Robot manipulation of unknown objects in unstructured environments is a challenging problem due to the variety of shapes, materials, arrangements and lighting conditions. Even with large-scale real-world data collection, robust perception and manipulation of transparent and reflective objects across various lighting conditions remains challenging. To address these challenges we propose an approach to performing sim-to-real transfer of robotic perception. The underlying model, SimNet, is trained as a single multi-headed neural network using simulated stereo data as input and simulated object segmentation masks, 3D oriented bounding boxes (OBBs), object keypoints and disparity as output. A key component of SimNet is the incorporation of a learned stereo sub-network that predicts disparity. SimNet is evaluated on 2D car detection, unknown object detection and deformable object keypoint detection and significantly outperforms a baseline that uses a structured light RGB-D sensor. By inferring grasp positions using the OBB and keypoint predictions, SimNet can be used to perform end-to-end manipulation of unknown objects in both "easy" and "hard" scenarios using our fleet of Toyota HSR robots in four home environments. In unknown object grasping experiments, the predictions from the baseline RGB-D network and SimNet enable successful grasps of most of the "easy" objects. However, the RGB-D baseline only grasps 35% of the "hard" (e.g., transparent) objects, while SimNet grasps 95%, suggesting that SimNet can enable robust manipulation of unknown objects, including transparent objects, in unknown environments. Additional visualizations and materials are located at https://tinyurl.com/simnet-corl.

Keywords: Sim-to-Real, Computer Vision, Manipulation

1 Introduction

To successfully deploy robots into diverse, unstructured environments, robots must have robust and general behaviors. Enabling general behaviors in complex environments, such as the home, requires robots to be able to perceive and manipulate previously unseen objects, such as new glass cups or t-shirts, even in the presence of significant variations in lighting, furniture, and objects.

A promising approach to learning robust, generalized behaviors is to use simulated data, which can be procedurally generated in large quantities with automatically labeled images, for perception tasks [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]. Perception models trained on simulated data can extract the necessary representations for a wide variety of manipulation tasks, where the manipulation policy itself is implemented via a classical planner [2, 8, 11, 12, 13].

However, perception models trained purely on simulated RGB data can overfit to simulation artifacts due to texture and lighting. In order to explicitly force models to focus on geometric features instead, models are often trained on active depth information [1, 2, 3, 4, 6]. Depth-trained models intuitively transfer well, because they do not overfit to simulated texture cues and instead focus on geometric features. However, depth sensors that use structured light struggle in environments where reflective and transparent objects are present, because they break Lambertian reflectance assumptions made by classical computer vision models [3]. These situations occur in commonly home environments, where the robot may need to perceive glassware in naturally lit rooms. This motivates designing a method that can leverage geometric features without using depth sensors.

Submitted to the 5th Conference on Robot Learning (CoRL 2021). Do not distribute.

Figure 1: **Simulation images:** Simulated data was generated for three domains: cars, small objects and t-shirts using a non-photorealistic simulator with domain-randomization. Dataset generation is parallelized across machines and can be generated in an hour for $60 (USD) cloud compute cost. By forcing the network to learn geometric features, sim-to-real transfer can be performed using only very low-quality scenes.

An alternative to active depth sensing is passive stereo matching, which captures images from two cameras and matches pixels in each image corresponding to the same point in 3D space. The disparity, or horizontal difference in the pixel coordinates of the point can be directly mapped to depth [14]. Recent work from the stereo vision community studies how to approximately perform stereo matching to predict depth images using a differentiable cost volume neural network to match features in a stereo image [15, 16]. While this literature typically focuses on accurate reconstruction of depth images, we show that approximate stereo matching, when combined with domain randomization [5, 17], can enable robust transfer of predicting "high-level" vision tasks. This paper presents a lightweight neural network for sim-to-real transfer, SimNet, which uses a cost volume and domain-randomized stereo images to predict task-relevant information for robot manipulation primitives, including segmentation masks, 3D oriented bounding boxes and keypoints. In contrast to previous work on manipulating novel objects in unstructured environments, this approach does not need large-scale real data collection [3, 18, 19, 20], active depth sensing [1, 3, 4], or photorealistic simulation [3].

SimNet is evaluated on three real-world domains: unknown object grasping, t-shirt folding, and 2D car detection. For unknown object grasping, SimNet shows accuracy gains over previous depth-based approaches and is able to grasp optically challenging transparent objects even where other depth-based approaches fail. The demonstration of t-shirt folding shows that sim-to-real transfer is possible with SimNet even in the presence of deformable objects and challenging optical conditions. Finally our sim-to-real technique is ablated over KITTI's [21] on 2D car detection tasks, which demonstrate significant demonstrate that sim-to-real transfer on significant benefits of using a cost-volume for sim-to-real transfer.

This work makes three contributions: *(i)* an efficient neural network for sim-to-real transfer, SimNet, that uses learned stereo matching to enable robust sim-to-real tranfer of "high-level" vision tasks, such as keypoints and oriented bounding boxes (OBBs), *(ii)* the first network to enable direct prediction of 3D oriented bounding boxes of unknown objects *(iii)* an indoor scenes dataset with 3D oriented bounding box labels of common household objects, corresponding stereo and RGB-D images, and training code for our model.

2   Related Work

Our related work is divided into perception for manipulation, sim-to-real and learned stereo.

2.1   Parameterized Representations for Manipulation

In contrast to end-to-end robot policy learning [19, 22, 23, 24], a popular approach for generating behaviors is to parameterize motions by the outputs of a perception network [1, 2, 8, 11, 25]. This decouples perception from planning and control, and enables perception systems to be trained in simulation without the need for accurate physical simulation. One representation commonly used for grasping of rigid objects are oriented bounding boxes (OBBs) [25]. These are useful for grasping common household objects, by aligning grasps along the principal components [25]. Our work contributes a method to directly predict OBBs from a neural network. A representation that is used for deformable manipulation are keypoints or learned correspondences, which have seen significant success in tasks such as deformable manipulation [2, 8, 10, 11, 12, 26] and grasping [27, 28]. Ganapathi et al. [8] and Sundaresan et al. [2] predict correspondences from domain-randomized depth or monocular RGB images and demonstrate impressive transfer to real fabrics and ropes in constrained lab environments. In contrast, we demonstrate robust transfer on diverse home scenes, and compare to the methods in these papers as baselines.

Figure 2: **SimNet:** In SimNet, each stereo RGB image is fed into a feature extractor before being fed into SCVN, which performs approximate stereo matching. The output of the SCVN is a low resolution disparity image fed in with features from the left image to a ResNet-FPN backbone and output prediction heads. The output heads predict room-level segmentation, OBBs, keypoints, and full-resolution disparity images.

2.2 Sim-to-Real Transfer

Transferring perception models trained on simulated data to reality is an active area of research. One technique to transfer from simulation to reality is to train directly on a geometric representation of the world such as a point cloud or depth image [1, 2]. Prior work has used depth-based transfer techniques in a variety of scenarios, such as grasping unknown objects [1], tying a rope [2], and segmenting object instances in cluttered scenes [4, 6]. Depth-based transfer is commonly performed with an active sensor using structured light. The applicability of these sensors is limited to regimes where their reflected infrared pattern is consistent enough that it can be pattern matched for 3-D reconstruction [29]. However, home settings contain non-Lambertian objects such as glassware and a large amount of natural light, which can create large sensing errors. Existing work studies combining depth sensors with RGB information to fill in missing depth information for clear objects [3] using photorealistic simulation and real data. In contrast to [3], we exclusively use inexpensive RGB sensors and low quality simulated data for training. Our approach is comparable to Xie et al. [4], which separately leverages depth and synthetic RGB inputs to compensate for the limitations of depth sensing alone. We compare to several variants of Xie et al. [4] as a baseline approach, and find that using stereo images outperforms using RGB and depth on optically challenging objects.

An alternative to depth-based transfer is domain randomization with RGB images (DR) [5, 17, 30, 31]. Typically, DR randomizes over the lighting and textures in the environment by utilizing a low-quality, non-photorealistic renderer and has produced successful results in car detection [30], 6-DOF pose estimation of known objects [32], and camera calibration [33]. By injecting large randomization into texture and lighting, the network is forced to use the geometry of the scene to solve the task [17]. A limitation of this approach is that geometric reasoning on a monocular image requires leveraging global shape priors, lighting effects, and scene understanding [34]. In this work, we propose a transfer technique that uses learned stereo matching with domain randomization to extract geometric features using only local non-semantic information and demonstrate robustness on the KITTI benchmark.

2.3 Learned Stereo Matching

The goal of stereo matching is to try to explicitly compute the pixel displacement offset between objects from the left and right images in a stereo pair [14]. By computing a per-pixel displacement offset, or disparity, a high-resolution point cloud can be generated of the world. Given that it is challenging to estimate similarity features of image patches, recent work has explored using deep learning techniques to advance stereo techniques [15, 16, 35, 36, 37, 38]. In contrast to the learned stereo community that targets achieving perfect depth-sensing when training with real data [15, 16], we are interested in enabling transfer from simulation for "high-level" vision tasks. We specifically propose a network for manipulation, SimNet, that regresses coarse depth with an efficient stereo matching network architecture based on [15, 16] to learn features that are robust enough to predict oriented bounding boxes, segmentation masks, and keypoints on real objects for manipulation.

3 SimNet: Enabling Predictions for Manipulation From Synthetic Stereo

In this section, we will discuss our network architecture that leverages approximate stereo matching techniques from [15, 16] and domain randomization [5, 17] to predict segmentation masks, OBBs, and keypoints on unseen objects for robot manipulation. Our key insight is that by training approximate

Figure 3: **Manipulation overview**: A stereo pair is fed as input to SimNet, which produces OBBs. Grasp positions are produced from OBBs and are used by a classical planner to grasp the object [25]. This grasping technique has been deployed on a fleet of home robots to perform manipulation in optically challenging scenarios.

stereo matching algorithms on pure synthetic data, robust "low-level" features like disparity can be learned, thereby enabling sim-to-real transfer on "high-level" vision tasks. First, we discuss how to learn robust low-level features, which are then fed into high-level perception algorithms. Finally, we discuss how our low-cost synthetic data is generated. For training details see supplemental Sec. B.2; the overall network architecture is in Fig. 2.

3.1 Stereo Cost Volume Networks (SCVN) For Robust Low-Level Features

We will now describe the stereo matching neural network module used in SimNet's backbone, which enables transfer from simulation. We refer to Sec. 4.4 for an ablation of our design decisions. In this section, we use $\odot$ to denote Hadamard products, and use $I_{[i,j:k,:]}$ to select all elements with index i in the first dimension of tensor I, index in $\{j, \ldots k-1\}$ in the second dimension of I, and any index in the third dimension onwards. Let I_l and I_r denote the left and right RGB images from the stereo pair. Each image has dimension $3 \times H_0 \times W_0$. The left and right images are fed into neural networks Φ_l and Φ_r that featurize each image respectively and output feature volumes ϕ_l and ϕ_r. Both ϕ_l and ϕ_r have dimension $C_\phi \times H_\phi \times W_\phi$, where C_ϕ is the number of channels in each feature volume, and H_ϕ and W_ϕ are their height and width, respectively. We used a lightweight Dilated ResNet-FPN [39] as our feature extractor, to enable large receptive fields with a minimal amount of convolutional layers.

The extracted features ϕ_l and ϕ_r are fed into a stereo cost volume network f_{cost} that consists of an approximate stereo matching module that searches horizontally in the feature volumes for correspondences within an allowed disparity range. In classical stereo vision literature, correspondences across left and right images can be found by searching along a horizontal line across the images for a match, and the disparity is the difference in the x coordinates in the match, which is high for closer points in 3D space and low for farther points. The architecture for f_{cost} is heavily inspired by the techniques in [15] and approximately performs this search. The first phase of the network $f_{\text{cost}}^{(0)}$ computes pixelwise dot products between horizontally shifted versions of the feature volumes. The output of this phase has dimension $C_c \times H_\phi \times W_\phi$. The value $2 * (C_c - 1)$ represents the maximum disparity considered by the network, and the minimum disparity considered is 0. The i-th $H_c \times W_c$ slice of the output is computed as:

$$f_{\text{cost}}^{(0)}(\phi_l, \phi_r)_{[i,:,i:]} = \sum_{j=0}^{C-1} \left(\phi_{l,[i,:,i:]} \odot \phi_{r,[i,:,:W-i]} \right)_{[j]}; \qquad f_{\text{cost}}^{(0)}(\phi_l, \phi_r)_{[i,:,:i]} = 0$$

The first case takes the rightmost $H_c - i$ columns of the left feature volume ϕ_l and computes a pixelwise dot product with the leftmost $H_c - i$ columns of ϕ_r. This operation horizontally searches for matches across the two feature volumes at a disparity of $2i$. The next phase of the network $f_{\text{cost}}^{(1)}$ feeds the resulting volume into a sequence of ResNet blocks, which outputs a volume of dimension $C_c \times H_\phi \times W_\phi$ before performing a soft argmin along the first axis of the volume. The soft argmin operation approximately finds the disparity for each pixel by locating its best match. The final volume is an estimate of a low-resolution disparity image $\hat{I}_{d,\text{low}}$ with shape $H_\phi \times W_\phi$. We denote $f_{\text{cost}} = f_{\text{cost}}^{(1)} \circ f_{\text{cost}}^{(0)}$.

Disparity Auxiliary Loss In addition to the losses for the high-level perception heads, we additionally train the weights of Φ_l, Φ_r, and f_{cost} by minimizing an auxiliary depth reconstruction loss function.

In particular, the loss function takes in a target disparity image $I_{\mathrm{targ,d}}$ of dimension $H_0 \times W_0$, downsamples it by a factor of H_0/H_ϕ and then computes the Huber loss [40] $\ell_{\mathrm{d,small}}$ of it with the low-resolution depth prediction $f_{\mathrm{cost}}(\phi_l, \phi_r)$. That is, the network weights are trained to minimize $\ell_{\mathrm{d,small}}(f_{\mathrm{cost}}(\phi_l, \phi_r), \texttt{downsample}(I_{\mathrm{targ,d}}, H_0/H_\phi))$.

3.2 Extracting High-Level Predictions for Manipulation Tasks

Given a SCVN to extract geometric features from stereo images, we need to learn on top of it high-level predictions relevant to manipulation. To design a backbone for robust simulation-trained manipulation, we feed the output of a SVCN, $\hat{I}_{\mathrm{d,low}}$, into a Resnet18-FPN [41] feature backbone f_{backbone}. Additionally, we leverage early stage features from the left RGB image, I_l, to enable high resolution texture information to be considered at inference time, similar to [4]. The features are extracted from the ResNet stem and concatenate with the output of the SCVN and fed into the backbone. The output of the backbone is fed into each of the prediction heads. In this section, we describe each of the prediction heads of SimNet (Fig. 2) and the losses used to train it. Each prediction head high uses the up-scaling branch defined in [41], which aggregates different resolutions across the feature extractor. Below we detailed the prediction heads used in our manipulation tasks, we describe the optional auxiliary prediction heads (i.e. segmentation and refined disparity) in Sec. 3.3.

Oriented Bounding Boxes: Detection of an OBB requires determining individual object instances as well as estimating translation, $t \in \mathbb{R}^3$, scale $S \in \mathbb{R}^{3\times3}$, and rotation, $R \in \mathbb{R}^{3\times3}$, of the encompassing OBB. These parameters can be recovered by using four different output heads. First to recover object instances, we regress a $W_0 \times H_0$ image, which is the resolution of the input left image, where for each object in the image a Gaussian heatmap is predicted. Instances can then be derived using peak detection as in [42, 43]. We use an L_1 loss on this output head and denote the loss as l_{inst}.

Given instances of object, we can now regress the remaining 9-DOF pose parameters. To recover scale and translation, we first regress a $W_0/8 \times H_0/8 \times 16$ output head where each element contains pixel-wise offset from detected peak to the 8 box vertices projected on to the image. We can then recover the scale and translation of the box up to a scale ambiguity using EPnP similar to [42]. In contrast to prior work in pose estimation, we aligned the predicted box based on principal axes sized in a fixed reference frame. To recover absolute scale and translation, we additionally regress the distance from the camera $z \in \mathbb{R}$ of the box centroid as a $W_0/8 \times H_0/8$ tensor. The two losses on these tensors are an L_1 loss and are denoted l_{vrtx} and l_{cent}.

Finally the rotation, R of the OBB can be recovered via directly predicting the covariance matrix, $\Sigma \in \mathbb{R}^{3\times3}$ of the ground truth 3D point cloud of the target object, which can be easily generated in simulation. The output tensor of $W_0/8 \times H_0/8 \times 6$ is directly regressed, where each pixel contains both the diagonal and symmetric off diagonal elements of the target covariance matrix. We can then recover rotation based on the SVD of Σ. L_1 loss on this output head is used and denoted as l_{rot}. Note for the 9-DOF pose loses, the loss is only enforced when the Gaussian heatmaps have score greater than 0.3 to prevent ambiguity in empty space.

Keypoints: Keypoints and learned correspondences are a common representation for robot manipulation, especially in deformable manipulation [2, 8, 11, 12, 27]. SimNet has an output head that predicts keypoints, such as t-shirt sleeves for t-shirt folding (Sec. 4). The output head predicts heatmaps for each keypoint class, and is trained to match target heatmaps with Gaussian distributions placed at each ground-truth keypoint location using a pixelwise cross-entropy loss l_{kp}. To extract keypoints from the predicted heatmaps, we use non-maximum suppression to perform peak detection as in Hou et al. [42].

3.3 High-level Predictions: Optional Auxiliary Prediction Heads

Two auxiliary prediction heads can enable better scene understanding of the world.

Room Level Segmentation: A room-level segmentation head can predict one of three categories: surfaces, objects and background. Cross-entropy loss l_{seg} is used for training, as in prior work [41]. This prediction head enables a mobile robot to detect surfaces and manipulable objects.

Full Resolution Disparity: Since SCVN produces a disparity image at quarter resolution, the feature extractor can combine the backbone and the left stereo image to produce a full resolution depth image. The same branch architecture as the previous heads is used to aggregate information across different scales. During training we use the same loss as the SCVN, but enforced at full resolution. This output

Figure 4: **Graspable Object Predictions:** SimNet is evaluated on an OBB regression task with objects of varying sizes and shapes on flat surfaces. Top: The left RGB image from different homes. Middle: Our model prediction trained with RGB-D sim-to-real transfer similar to [4]. The top right corner is the output of the Asus Xtion depth sensor. Bottom: SimNet. In the top right, we show the low-res disparity estimate predicted by the learned stereo net. SimNet consistently enables better sim2real transfer of the predictions for optically challenging scenarios.

is trained using a Huber loss function. A full resolution disparity image can be converted into a 3D point cloud for collision avoidance.

3.4 Efficient Synthetic Dataset Generation

Given the complexity of all the output predictions defined in the previous section, it would be impractical to label a sufficient amount of real-data to generalize across scenes. Thus, we are interested in using synthetic data to provide ground truth annotations on a wide variety of scenarios. To force the network to learn geometric features, we randomize over lighting and textures as recommended in Mayer et al. [37]. In contrast to [3, 44], we use OpenGL shaders with PyRender [45] instead of physically based rendering [46] approaches. Low-quality rendering greatly speeds up computation, and allows for data-set generation on the order of an hour. We generate three datasets: cars, graspable objects, and t-shirts (Fig. 1), and discuss specific dataset details in supplemental Sec. D. We intend to release our datasets as well as real-world validation data as part of this paper.

4 Experiments

SimNet is evaluated on a set of real-world computer vision and robotics tasks to see if training on synthetic stereo data will transfer robustly to diverse, real images in unstructured environments and enable manipulation of optically challenging objects. This includes evaluating learned perception models and manipulation policies on two optically challenging tasks: (1) grasping unknown objects on tabletops and (2) t-shirt folding. SimNet is compared against baseline approaches using monocular, naive stereo concatenation and active RGB-D sensing (supplemental Sec. B.1) and the SCVN component of SimNet is ablated on the KITTI car detection benchmark.

All physical experiments are conducted on tabletops found across four different, real homes. Manipulation is performed with the Toyota HSR robot, which has a four DOF arm, mobile base, and pair of parallel jaw grippers [47]. It has a mounted stereo pair from a Zed 2 camera and a Asus Xtion Pro RGB-D sensor. Each home has different background objects, furniture, graspable objects, and lighting conditions, which evaluates each network's ability to robustly generalize to diverse scenarios.

4.1 Ablation of Baselines on Validation Data

SimNet is compared to the following baselines: **mono**, which uses the left stereo image, **depth** [48], which only uses depth inputs, and **RGB-D**, which uses both RGB and depth inputs. To make the RGB-D baseline competitive, the best among four different approaches to fuse color and depth information was picked (See RGB-D baselines in Appendix, Section B.1) by evaluating on a held out

Figure 5: **T-shirt Keypoint Predictions:** SimNet is evaluated on keypoint regression for shirts in various stages of folding. Three classes of keypoints are predicted: sleeves, neck, and bottom corners. RGB-D performs poorly due to strong natural lighting and minimal depth variation. SimNet accurately predicts keypoints on the shirts despite these challenges.

set of 500 non-optically challenging scenes (i.e. matte objects with minimal natural light). SimNet is compared to a technique inspired by [4] **RGB-D Seq**, where inference is done in a two-stage manner on first depth and then RGB (see Section B.1). The performance of SimNet after turning off all auxiliary tasks (except auxilliary depth loss) is reported as **SimNet- w/o Aux.** Tasks. 3D mAP@0.25 of annotated bounding boxes of each object, a common metric in pose prediction [49], was used as an evaluation metric (see Appendix B.3). Results are shown in Table 1. Additional sensing ablations are in the Appendix, Sec. C.

Monocular sensing performs poorly on this task, likely due to the task being 3D in nature, while depth and RGB-D perform much better. Both versions of **SimNet** (with or without auxiliary tasks) perform better than all other sim-to-real techniques, including using RGB-D and the approach inspired by [4] (**RGB-D Seq**). The similar mAP score between **SimNet-w/o Aux.** tasks to **SimNet** shows that the additional output heads are optional and not needed for sim-to-real transfer. These results indicate that stereo matching can lead to more robust sim-to-real transfer.

Method	Mono [5]	Depth [48]	RGB-D	RGB-D Seq [4]	SimNet	SimNet- w/o Aux.
mAP	0.164	0.831	0.855	0.774	0.921	0.947

Table 1: **SimNet Perception Results:** An ablation of different sensing modalities on the 3D OBB prediction task evaluated using 3D mAP on a dataset of real, human-annotated images of optically **easy objects.**

4.2   Unknown Object Grasping

In this experiment, the robot's task is to grasp objects on a tabletop comprised of two classes of household objects in each home: **optically easy**, which consists of opaque, non-reflective objects, and **optically hard**, which contains optically challenging, transparent objects (Fig. 6). For each trial, an object is selected uniformly at random from the dataset and randomly placed on the tabletop with other distractor objects. The task is to grasp the foremost object in the scene using a heuristic grasp planner that takes OBBs as input. To grasp objects the robot aligns the gripper with the largest principal axis of the OBB. In the event of similar sized principal axes like a ball, the robot favors grasping the object on the side closest to the robot. A grasp is successful if the robot is able to raise the object off the table and remove it from the scene.

For each of the four homes we test five easy objects and five hard objects and compare SimNet against the best RGB-D baseline found in Sec. 4.1. Quantitative results are reported in Table 2 and qualitative results of the predictions are in Fig. 4. The results show that SimNet outperforms RGB-D, 92.5% vs. 62.5% in grasp success. On optically easy objects RGBD-D and SimNet perform similarly on average, while SimNet performs much better when grasping challenging objects such as glassware. These results demonstrate that SimNet is able to robustly grasp a variety of unknown challenging objects, even in optically challenging settings.

4.3   Grasp Point Prediction in T-shirt Folding

In this experiment, the robot is evaluated on a t-shirt folding task, where it must execute a sequence of four folds on unseen, real t-shirts. This task is challenging to perform using depth sensing, because the depth resolution of most commercial depth sensors cannot capture the subtle variations in depth due to the thickness of a t-shirt. Keypoints are a popular representation for manipulating deformable objects [11, 12]. A shirt folding policy is parameterized using keypoint predictions for the shirt's

Method (Object Class)	Home 1	Home 2	Home 3	Home 4	Overall
RGB-D (O. Easy)	4/5	**5/5**	4/5	**5/5**	**18/20**
SimNet (O. Easy)	**5/5**	4/5	**5/5**	4/5	**18/20**
RGB-D (O. Hard)	0/5	1/5	1/5	**5/5**	7/20
SimNet (O. Hard)	**5/5**	**5/5**	**5/5**	4/5	**19/20**

Table 2: **SimNet Grasping Results:** Grasp success scores comparing the best RGB-D method and SimNet.

neck, sleeves, and bottom corners (Sec. B.4.2). To compute quantitative results on sim2real transfer, a validation dataset of 32 real images is collected from 12 t-shirts in 3 homes (Fig. 5). Keypoint prediction mAP is reported (Table 3). Videos of t-shirt folding are presented on the project website.

The results show that SimNet significantly outperforms RGB-D and depth, and slightly outperforms mono. This is likely due to interference from natural lighting and low depth profile of the shirts. The monocular network transfers well to the real t-shirt images, and SimNet slightly outperforms it. Unlike the models that use active depth sensing, SimNet is robust to lighting variation and the low depth variation of the shirts. Also, these experiments indicate that SimNet can accurately predict object keypoints, thereby enabling manipulation of certain deformable objects.

Method	Mono	Depth	RGB-D	SimNet
mAP	0.893	0.282	0.631	**0.917**

Table 3: **T-Shirt Folding Results:** A comparison of t-shirt keypoint mAP across different sim-to-real approaches.

4.4 SCVN Ablation on KITTI 2D Car Detection

To motivate the use of SCVN for achieving sim-to-real transfer, evaluation on the standard 2-D car detection benchmark on KITTI was performed [21] since it has been used as a challenging sim-to-real domain in prior work [30]. The models compared include SimNet (with the SCVN) trained on simulated images and baseline networks including ones that are using monocular inputs (**Mono**), using stacked left and right image inputs (**Stacked**), not using the depth-auxiliary loss on the output of the SCVN (**SimNet-No Depth Loss**) and using real training data with a standard validation/training split used in [43] (**SimNet-real**). To predict 2D bounding boxes, SimNet is modified to use the single-shot box detection output head in CenterNet [43]. In the table below we report mAP@0.5 for the aggregate of moderate and easy car classes (see Appendix B.3 for discussion of evaluation metrics).

The results can be seen in Table 4. They show that SimNet can significantly outperform monocular images and naive stereo concatenation, which suggests explicit stereo matching leads to more robust transfer. However, if no auxiliary depth loss is enforced, there is a significant decrease in performance, indicating that the SCVN is very important for sim-to-real transfer. Furthermore, the gap between real and sim data is only 3.5%, which suggests relatively robust sim-to-real transfer. However, qualitatively SimNet fails to detect cars at distance, since the disparity for their pixels becomes very small as distance from the camera becomes large. For visualizations of the predictions see the Appendix, Fig. 13. Thus, SimNet is best used for applications with limited range from the camera, such as robot manipulation.

Method	Mono	Stacked	SimNet-No Depth Loss	SimNet	SimNet-real
mAP	0.565	0.710	0.612	**0.826**	0.861

Table 4: **KITTI Results:** Comparison of different sim-to-real techniques for 2D car detection on KITTI.

5 Conclusion

We present SimNet, an efficient, multi-headed prediction network that leverages approximate stereo matching to transfer from simulation to reality. The network is trained on entirely simulated data and robustly transfers to real images of unknown optically-challenging objects such as glassware, even in direct sunlight. We show that these predictions are sufficient for robot manipulation such as t-shirt folding and grasping. In future work, we plan to use SimNet to automate household chores.

References

[1] J. Mahler, M. Matl, V. Satish, M. Danielczuk, B. DeRose, S. McKinley, and K. Goldberg. Learning ambidextrous robot grasping policies. *Science Robotics*, 4(26), 2019.

[2] P. Sundaresan, J. Grannen, B. Thananjeyan, A. Balakrishna, M. Laskey, K. Stone, J. E. Gonzalez, and K. Goldberg. Learning rope manipulation policies using dense object descriptors trained on synthetic depth data. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 9411–9418. IEEE, 2020.

[3] S. Sajjan, M. Moore, M. Pan, G. Nagaraja, J. Lee, A. Zeng, and S. Song. Clear grasp: 3d shape estimation of transparent objects for manipulation. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 3634–3642. IEEE, 2020.

[4] C. Xie, Y. Xiang, A. Mousavian, and D. Fox. The best of both modes: Separately leveraging rgb and depth for unseen object instance segmentation. In *Conference on robot learning*, pages 1369–1378. PMLR, 2020.

[5] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pages 23–30. IEEE, 2017.

[6] M. Danielczuk, M. Matl, S. Gupta, A. Li, A. Lee, J. Mahler, and K. Goldberg. Segmenting unknown 3d objects from real depth images using mask r-cnn trained on synthetic data. In *2019 International Conference on Robotics and Automation (ICRA)*, pages 7283–7290. IEEE, 2019.

[7] I. Akkaya, M. Andrychowicz, M. Chociej, M. Litwin, B. McGrew, A. Petron, A. Paino, M. Plappert, G. Powell, R. Ribas, et al. Solving rubik's cube with a robot hand. *arXiv preprint arXiv:1910.07113*, 2019.

[8] A. Ganapathi, P. Sundaresan, B. Thananjeyan, A. Balakrishna, D. Seita, J. Grannen, M. Hwang, R. Hoque, J. E. Gonzalez, N. Jamali, et al. Learning dense visual correspondences in simulation to smooth and fold real fabrics. *arXiv preprint arXiv:2003.12698*, 2020.

[9] R. Hoque, D. Seita, A. Balakrishna, A. Ganapathi, A. K. Tanwani, N. Jamali, K. Yamane, S. Iba, and K. Goldberg. Visuospatial foresight for multi-step, multi-task fabric manipulation. *arXiv preprint arXiv:2003.09044*, 2020.

[10] D. Seita, A. Ganapathi, R. Hoque, M. Hwang, E. Cen, A. K. Tanwani, A. Balakrishna, B. Thananjeyan, J. Ichnowski, N. Jamali, et al. Deep imitation learning of sequential fabric smoothing from an algorithmic supervisor. *arXiv preprint arXiv:1910.04854*, 2019.

[11] J. Grannen, P. Sundaresan, B. Thananjeyan, J. Ichnowski, A. Balakrishna, M. Hwang, V. Viswanath, M. Laskey, J. E. Gonzalez, and K. Goldberg. Untangling dense knots by learning task-relevant keypoints. *arXiv preprint arXiv:2011.04999*, 2020.

[12] D. Seita, N. Jamali, M. Laskey, A. K. Tanwani, R. Berenstein, P. Baskaran, S. Iba, J. Canny, and K. Goldberg. Deep transfer learning of pick points on fabric for robot bed-making. *arXiv preprint arXiv:1809.09810*, 2018.

[13] P. Sundaresan, B. Thananjeyan, J. Chiu, D. Fer, and K. Goldberg. Automated extraction of surgical needles from tissue phantoms. In *2019 IEEE 15th International Conference on Automation Science and Engineering (CASE)*, pages 170–177. IEEE, 2019.

[14] D. A. Forsyth and J. Ponce. *Computer vision: a modern approach.* Pearson,, 2012.

[15] N. Mayer, E. Ilg, P. Hausser, P. Fischer, D. Cremers, A. Dosovitskiy, and T. Brox. A large dataset to train convolutional networks for disparity, optical flow, and scene flow estimation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 4040–4048, 2016.

[16] A. Kendall, H. Martirosyan, S. Dasgupta, P. Henry, R. Kennedy, A. Bachrach, and A. Bry. End-to-end learning of geometry and context for deep stereo regression. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 66–75, 2017.

[17] F. Sadeghi and S. Levine. Cad2rl: Real single-image flight without a single real image. *arXiv preprint arXiv:1611.04201*, 2016.

[18] A. Gupta, A. Murali, D. Gandhi, and L. Pinto. Robot learning in homes: Improving generalization and reducing dataset bias. *arXiv preprint arXiv:1807.07049*, 2018.

[19] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, et al. Qt-opt: Scalable deep reinforcement learning for vision-based robotic manipulation. *arXiv preprint arXiv:1806.10293*, 2018.

[20] X. Liu, R. Jonschkowski, A. Angelova, and K. Konolige. Keypose: Multi-view 3d labeling and keypoint estimation for transparent objects. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 11602–11610, 2020.

[21] A. Geiger, P. Lenz, and R. Urtasun. Are we ready for autonomous driving? the kitti vision benchmark suite. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2012.

[22] T. Haarnoja, A. Zhou, K. Hartikainen, G. Tucker, S. Ha, J. Tan, V. Kumar, H. Zhu, A. Gupta, P. Abbeel, et al. Soft actor-critic algorithms and applications. *arXiv preprint arXiv:1812.05905*, 2018.

[23] B. Thananjeyan, A. Balakrishna, S. Nair, M. Luo, K. Srinivasan, M. Hwang, J. E. Gonzalez, J. Ibarz, C. Finn, and K. Goldberg. Recovery rl: Safe reinforcement learning with learned recovery zones. *IEEE Robotics and Automation Letters*, 6(3):4915–4922, 2021.

[24] S. Levine, C. Finn, T. Darrell, and P. Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

[25] R. Balasubramanian, L. Xu, P. D. Brook, J. R. Smith, and Y. Matsuoka. Physical human interactive guidance: Identifying grasping principles from human-planned grasps. *IEEE Transactions on Robotics*, 28 (4):899–910, 2012.

[26] J. Maitin-Shepard, M. Cusumano-Towner, J. Lei, and P. Abbeel. Cloth grasp point detection based on multiple-view geometric cues with application to robotic towel folding. In *2010 IEEE International Conference on Robotics and Automation*, pages 2308–2315. IEEE, 2010.

[27] L. Manuelli, W. Gao, P. Florence, and R. Tedrake. kpam: Keypoint affordances for category-level robotic manipulation. *arXiv preprint arXiv:1903.06684*, 2019.

[28] P. R. Florence, L. Manuelli, and R. Tedrake. Dense object nets: Learning dense visual object descriptors by and for robotic manipulation. *arXiv preprint arXiv:1806.08756*, 2018.

[29] A. Grunnet-Jepsen, J. N. Sweetser, P. Winer, A. Takagi, and J. Woodfill. Projectors for intel® realsense™ depth cameras d4xx. *Intel Support, Interl Corporation: Santa Clara, CA, USA*, 2018.

[30] J. Tremblay, A. Prakash, D. Acuna, M. Brophy, V. Jampani, C. Anil, T. To, E. Cameracci, S. Boochoon, and S. Birchfield. Training deep networks with synthetic data: Bridging the reality gap by domain randomization. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 969–977, 2018.

[31] R. Alghonaim and E. Johns. Benchmarking domain randomisation for visual sim-to-real transfer. *arXiv preprint arXiv:2011.07112*, 2020.

[32] J. Tremblay, T. To, B. Sundaralingam, Y. Xiang, D. Fox, and S. Birchfield. Deep object pose estimation for semantic robotic grasping of household objects. *arXiv preprint arXiv:1809.10790*, 2018.

[33] T. E. Lee, J. Tremblay, T. To, J. Cheng, T. Mosier, O. Kroemer, D. Fox, and S. Birchfield. Camera-to-robot pose estimation from a single image. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 9426–9432. IEEE, 2020.

[34] I. P. Howard. *Perceiving in depth, volume 1: basic mechanisms*. Oxford University Press, 2012.

[35] W. Luo, A. G. Schwing, and R. Urtasun. Efficient deep learning for stereo matching. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 5695–5703, 2016.

[36] E. Ilg, N. Mayer, T. Saikia, M. Keuper, A. Dosovitskiy, and T. Brox. Flownet 2.0: Evolution of optical flow estimation with deep networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2462–2470, 2017.

[37] N. Mayer, E. Ilg, P. Fischer, C. Hazirbas, D. Cremers, A. Dosovitskiy, and T. Brox. What makes good synthetic training data for learning disparity and optical flow estimation? *International Journal of Computer Vision*, 126(9):942–960, 2018.

[38] J. Zbontar and Y. LeCun. Computing the stereo matching cost with a convolutional neural network. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1592–1599, 2015.

[39] F. Yu, V. Koltun, and T. Funkhouser. Dilated residual networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 472–480, 2017.

[40] P. J. Huber. Robust estimation of a location parameter. In *Breakthroughs in statistics*, pages 492–518. Springer, 1992.

[41] A. Kirillov, R. Girshick, K. He, and P. Dollár. Panoptic feature pyramid networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 6399–6408, 2019.

[42] T. Hou, A. Ahmadyan, L. Zhang, J. Wei, and M. Grundmann. Mobilepose: Real-time pose estimation for unseen objects with weak shape supervision. *arXiv preprint arXiv:2003.03522*, 2020.

[43] K. Duan, S. Bai, L. Xie, H. Qi, Q. Huang, and Q. Tian. Centernet: Keypoint triplets for object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6569–6578, 2019.

[44] M. Roberts and N. Paczan. Hypersim: A photorealistic synthetic dataset for holistic indoor scene understanding. *arXiv preprint arXiv:2011.02523*, 2020.

[45] M. Matl. Pyrender. https://github.com/mmatl/pyrender, 2013.

[46] M. Pharr, W. Jakob, and G. Humphreys. *Physically based rendering: From theory to implementation*. Morgan Kaufmann, 2016.

[47] T. Yamamoto, K. Terada, A. Ochiai, F. Saito, Y. Asahara, and K. Murase. Development of human support robot as the research platform of a domestic mobile manipulator. *ROBOMECH journal*, 6(1):1–15, 2019.

[48] J. Mahler, J. Liang, S. Niyaz, M. Laskey, R. Doan, X. Liu, J. A. Ojea, and K. Goldberg. Dex-net 2.0: Deep learning to plan robust grasps with synthetic point clouds and analytic grasp metrics. *arXiv preprint arXiv:1703.09312*, 2017.

[49] H. Wang, S. Sridhar, J. Huang, J. Valentin, S. Song, and L. J. Guibas. Normalized object coordinate space for category-level 6d object pose and size estimation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2642–2651, 2019.

[50] S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pages 448–456. PMLR, 2015.

[51] L. Li, K. Jamieson, G. DeSalvo, A. Rostamizadeh, and A. Talwalkar. Hyperband: A novel bandit-based approach to hyperparameter optimization. *The Journal of Machine Learning Research*, 18(1):6765–6816, 2017.

[52] A. Geiger, P. Lenz, C. Stiller, and R. Urtasun. Vision meets robotics: The kitti dataset. *International Journal of Robotics Research (IJRR)*, 2013.

[53] A. X. Chang, T. Funkhouser, L. Guibas, P. Hanrahan, Q. Huang, Z. Li, S. Savarese, M. Savva, S. Song, H. Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.