Zeroth-Order Hard-Thresholding: Gradient Error vs. Expansivity

Abstract

ℓ_0 constrained optimization is prevalent in machine learning, particularly for high-dimensional problems, because it is a fundamental approach to achieve sparse learning. Hard-thresholding gradient descent is a dominant technique to solve this problem. However, first-order gradients of the objective function may be either unavailable or expensive to calculate in a lot of real-world problems, where zeroth-order (ZO) gradients could be a good surrogate. Unfortunately, whether ZO gradients can work with the hard-thresholding operator is still an unsolved problem. To solve this puzzle, in this paper, we focus on the ℓ_0 constrained black-box stochastic optimization problems, and propose a new stochastic zeroth-order gradient hard-thresholding (SZOHT) algorithm with a general ZO gradient estimator powered by a novel random support sampling. We provide the convergence analysis of SZOHT under standard assumptions. Importantly, we reveal a conflict between the deviation of ZO estimators and the expansivity of the hard-thresholding operator, and provide a theoretical minimal value of the number of random directions in ZO gradients. In addition, we find that the query complexity of SZOHT is independent or weakly dependent on the dimensionality under different settings. Finally, we illustrate the utility of our method on a portfolio optimization problem as well as black-box adversarial attacks.

1 Introduction

ℓ_0 constrained optimization is prevalent in machine learning, particularly for high-dimensional problems, because it is a fundamental approach to achieve sparse learning. In addition to improving the memory, computational and environmental footprint of the models, these sparse constraints help reduce overfitting and obtain consistent statistical estimation [42, 4, 29, 26]. We formulate the problem as follows:

$$\min_{\boldsymbol{x} \in \mathbb{R}^d} \left\{ f(\boldsymbol{x}) := \mathbb{E}_{\boldsymbol{\xi}} f(\boldsymbol{x}, \boldsymbol{\xi}) \right\}, \quad \text{s.t.} \quad \|\boldsymbol{x}\|_0 \le k \tag{1}$$

where $f(\cdot, \boldsymbol{\xi}) : \mathbb{R}^d \to \mathbb{R}$ is a differentiable function and $\boldsymbol{\xi}$ is a noise term, for instance related to an underlying finite sum structure in f, of the form: $\mathbb{E}_{\boldsymbol{\xi}} f(\boldsymbol{x}, \boldsymbol{\xi}) = \frac{1}{n} \sum_{i=1}^{n} f_i(\boldsymbol{x})$. Hard-thresholding gradient algorithm [15, 28, 41] is a dominant technique to solve this problem. It generally consists in alternating between a gradient step, and a hard-thresholding operation which only keeps the k-largest components (in absolute value) of the current iterate. The advantage of hard-thresholding over its convex relaxations ([35, 37]) is that it can often attain similar precision, but is more computationally efficient, since it allows to directly ensure a desired sparsity instead of going through several values of an ℓ_1 penalty or constraint hyperparameter. The only expensive computation in hard-thresholding is the hard-thresholding step itself, which requires finding the top k elements of the current iterate. Hard-thresholding was originally developed in its full gradient form [15], but has been later on extended to the stochastic setting by Nguyen et al. [28], which developed a stochastic gradient

Table 1: Complexity of sparsity-enforcing algorithms. We give the query complexity for a precision ε, up to the system error (see section 4). For first-order algorithms, we give it in terms of number of first order oracle calls (#IFO), that is, calls to $\nabla f(x, \boldsymbol{\xi})$, and for ZO algorithms, in terms of calls of $f(\boldsymbol{\xi}, \cdot)$. Here κ denotes the condition number $\frac{L}{\nu}$, with L is the smoothness (or RSS) constant and ν is the strong-convexity (or RSC) constant.

Type	Name	Assumptions	#IZO/#IFO	#HT ops.
FO/ℓ_0	StoIHT [28]	RSS, RSC	$\mathcal{O}(\kappa \log(\frac{1}{\varepsilon}))$	$\mathcal{O}(\kappa \log(\frac{1}{\varepsilon}))$
ZO/ℓ_1	RSPGF [12]	smooth[3]	$\mathcal{O}(\frac{d}{\varepsilon^2})$	—
ZO/ℓ_1	ZSCG[2][2]	convex, smooth	$\mathcal{O}(\frac{d}{\varepsilon^2})$	—
ZO/ℓ_1	ZORO [5]	s-sparse gradient, weakly sparse hessian, smooth,[3] RSC$_{\text{bis}}$[1]	$\mathcal{O}(s \log(d) \log(\frac{1}{\varepsilon}))$	—
ZO/ℓ_0	**SZOHT**[4]	RSS, RSC	$\mathcal{O}((k + \frac{d}{s_2})\kappa^2 \log(\frac{1}{\varepsilon}))$	$\mathcal{O}(\kappa^2 \log(\frac{1}{\varepsilon}))$
ZO/ℓ_0	**SZOHT**	smooth, RSC	$\mathcal{O}(k\kappa^2 \log(\frac{1}{\varepsilon}))$	$\mathcal{O}(\kappa^2 \log(\frac{1}{\varepsilon}))$

[1] The definition of Restricted Strong Convexity from [5] is different from ours and that of [28], hence the bis subscript.

[2] We refer to the modified version of ZSCG (Algorithm 3 in [2]).

[3] RSPGF and ZORO minimize $f(x) + \lambda \|x\|_1$: only f needs to be smooth.

descent (SGD) version of hard thresholding (StoIHT), and further more with Zhou et al. [43], Shen and Li [32] and Li et al. [18], which used variance reduction technique to improve upon StoIHT.

However, the first-order gradients used in the above methods may be either unavailable or expensive to calculate in a lot of real-world problems. For example, in certain graphical modeling tasks [38], obtaining the gradient of the objective function is computationally hard. Even worse, in some settings, the gradient is inaccessible by nature, for instance in bandit problems [31], black-box adversarial attacks [36, 8, 9], or reinforcement learning [30, 24, 10]. To tackle those problems, ZO optimization methods have been developed [27]. Those methods usually replace the inaccessible gradient by its finite difference approximation which can be computed only from function evaluations, following the idea that for a differentiable function $f : \mathbb{R} \to \mathbb{R}$, we have: $f'(x) = \lim_{h \to 0} \frac{f(x+h)-f(x)}{h}$. Later on, ZO methods have been adapted to solve constrained problems. These could be used to solve problem (1), by solving its convex relaxation, that is, with an ℓ_1 penalty/constraint instead of the ℓ_0 one. To that end, Ghadimi et al. [12], and Cai et al. [5] introduce proximal ZO algorithms, Liu et al. [21] introduce a ZO projected gradient algorithm and Balasubramanian and Ghadimi [2] introduce a ZO conditional gradient [17] algorithm. We provide a review of those results in Table 1. As can be seen from the table, their query complexity is high (linear in d), except [5] that has a complexity of $\mathcal{O}(s \log(d) \log(\frac{1}{\varepsilon}))$, but assumes that gradients are sparse. In addition, those methods must introduce a hyperparameter λ (the strength of the ℓ_1 penalty) or R (the radius of the ℓ_1 ball), for which several values need to be tested to find the one ensuring an output of sparsity k. Therefore, it would be interesting to use the hard-thresholding techniques described in the previous paragraph, instead of those convex relaxations.

Unfortunately, ZO hard-thresholding gradient algorithms have not been exploited formally. Even more, whether ZO gradients can work with the hard-thresholding operator is still an unknown problem. Although there was one related algorithm proposed recently by Balasubramanian and Ghadimi [2], they did not target ℓ_0 constrained optimization problem and importantly have strong assumptions in their convergence analysis. Indeed, they assume that the gradients, as well as the solution of the unconstrained problem, are s-sparse: $\|\nabla f(\boldsymbol{x})\|_0 \leq s$ and $\|\boldsymbol{x}^*\|_0 \leq s^* \approx s$, where $\boldsymbol{x}^* = \arg\min_{\boldsymbol{x}} f(\boldsymbol{x})$. In addition, it was recently shown by Cai et al. [5] that they must in fact assume that the support of the gradient is fixed for all $\boldsymbol{x} \in \mathcal{X}$, for their convergence result to hold, which is a hard limitation, since that amounts to say that the function f depends on s fixed variables.

To fill this gap, in this paper, we focus on the ℓ_0 constrained black-box stochastic optimization problems, and propose a novel stochastic zeroth-order gradient hard-thresholding (SZOHT) algorithm. Specifically, we propose a dimension friendly ZO gradient estimator powered by a novel random support sampling technique, and then embed it into the standard hard-thresholding operator.

Combined with the classical convergence analysis from the hard-thresholding algorithm, this proposition allows us to provide the convergence and complexity analysis of SZOHT under the standard assumptions of sparse learning, which are restricted strong smoothness (RSS), and restricted strong convexity (RSC) [28, 32], to retain generality, therefore providing a positive answer to the question of whether ZO gradients can work with the hard-thresholding operator. Crucial to our analysis is to provide carefully tuned requirements on the parameters q and k. Finally, we illustrate the utility of our method on a portfolio optimization problem as well as black-box adversarial attacks, by showing that our method can achieve competitive performance in comparison to state of the art methods for sparsity-enforcing zeroth-order algorithm described in Table 1 such as [12, 2, 5].

Importantly, we also show that in the smooth case, the query complexity of SZOHT is independent of the dimensionality, which is significantly different to the dimensionality dependent result for most existing ZO algorithms. Indeed, it is known from Jamieson et al. [16] that the worst case query complexity of ZO optimization over the class $\mathcal{F}_{\nu,L}$ of ν-strongly convex and L-smooth functions defined over a convex set $\mathcal{X}$ is linear in d. Our work is thus in line with other works achieving dimension-insensitive query complexity in zeroth-order optimization such as [13, 33, 40, 5, 6, 2, 5, 20, 16], but contrary to those, instead of making further assumptions (i.e. restricting the class $\mathcal{F}_{\nu,L}$ to a smaller class), we bypass the impossibility result by replacing the convex feasible set $\mathcal{X}$ by a *non-convex* set (the ℓ_0 ball), which allows us to avoid making stringent assumptions on the class of functions f.

Contributions. We summarize the main contributions of our paper as follows:

1. We propose a new algorithm SZOHT that is, up to our knowledge, the first zeroth-order sparsity constrained algorithm that is dimension independent under the smoothness assumption, without assuming any gradient sparsity.
2. We reveal an interesting conflict between the error from zeroth-order estimates and the hard-thresholding operator, which results in a minimal value for q that is necessary to ensure.
3. We also provide the convergence analysis of our algorithm in the more general RSS setting, providing, up to our knowledge, the first zeroth-order algorithm that can work with the usual assumptions of RSS/RSC from the hard-thresholding literature.

2 Preliminaries

Throughout this paper, we denote by $\|\boldsymbol{x}\|$ the Euclidean norm for a vector $\boldsymbol{x} \in \mathbb{R}^d$, by $\|\boldsymbol{x}\|_\infty$ the maximum absolute component of that vector, and by $\|\boldsymbol{x}\|_0$ the ℓ_0 norm (which is not a proper norm). For simplicity, we denote $f_{\boldsymbol{\xi}}(\cdot) := f(\cdot, \boldsymbol{\xi})$. We call $\boldsymbol{u}_F$ (resp. $\nabla_F f(\boldsymbol{x})$) the vector which sets all coordinates $i \notin F$ of $\boldsymbol{u}$ (resp. $\nabla f(\boldsymbol{x})$) to 0. We also denote by $\boldsymbol{x}^*$ the solution of problem (1) defined in the introduction, for some target sparsity k^* which could be smaller than k. To derive our result, we will need the following assumptions on f.

Assumption 1 ((ν_s, s)-RSC, [15, 25, 23, 41, 18, 32, 28]). *f is said to be ν_s restricted strongly convex with sparsity parameter s if it is differentiable, and there exist a generic constant ν_s such that for all $(\boldsymbol{x}, \boldsymbol{y}) \in \mathbb{R}^d$ with $\|\boldsymbol{x} - \boldsymbol{y}\|_0 \le s$:*

$$f(\boldsymbol{y}) \ge f(\boldsymbol{x}) + \langle \nabla f(\boldsymbol{x}), \boldsymbol{y} - \boldsymbol{x} \rangle + \frac{\nu_s}{2} \|\boldsymbol{x} - \boldsymbol{y}\|^2$$

Assumption 2 ((L_s, s)-RSS, [32, 28]). *For almost any $\boldsymbol{\xi}$, $f_{\boldsymbol{\xi}}$ is said to be L_s restricted smooth with sparsity level s, if it is differentiable, and there exist a generic constant L_s such that for all $(\boldsymbol{x}, \boldsymbol{y}) \in \mathbb{R}^d$ with $\|\boldsymbol{x} - \boldsymbol{y}\|_0 \le s$:*

$$\|\nabla f_{\boldsymbol{\xi}}(\boldsymbol{x}) - \nabla f_{\boldsymbol{\xi}}(\boldsymbol{y})\| \le L_s \|\boldsymbol{x} - \boldsymbol{y}\|$$

Assumption 3 (σ^2-FGN [14], Assumption 2.3 (Finite Gradient Noise)). *f is said to have σ-finite gradient noise if for almost any $\boldsymbol{\xi}$, $f_{\boldsymbol{\xi}}$ is differentiable and the gradient noise $\sigma = \sigma(f, \boldsymbol{\xi})$ defined below is finite:*

$$\sigma^2 = \mathbb{E}_{\boldsymbol{\xi}}[\|\nabla f_{\boldsymbol{\xi}}(\boldsymbol{x}^*)\|_\infty^2]$$

Remark 1. *Even though the original version of [14] uses the ℓ_2 norm, we use the ℓ_∞ norm here, in order to give more insightful results in terms of k and d, as is done classically in ℓ_0 optimization, similarly to [43]. We also note that in [14], $\boldsymbol{x}^*$ denotes an unconstrained minimum when in our case it denotes the constrained minimum for some sparsity k^*.*

For Corollary 2, we will also need the more usual smoothness assumption:

Assumption 4 (*L*-smooth). *For almost any $\boldsymbol{\xi}$, $f_{\boldsymbol{\xi}}$ is said to be L smooth, if it is differentiable, and for all $(\boldsymbol{x}, \boldsymbol{y}) \in \mathbb{R}^d$:*

$$\|\nabla f_{\boldsymbol{\xi}}(\boldsymbol{x}) - \nabla f_{\boldsymbol{\xi}}(\boldsymbol{y})\| \leq L\|\boldsymbol{x} - \boldsymbol{y}\|$$

3 Algorithm

3.1 Random support Zeroth-Order estimate

In this section, we describe our zeroth-order gradient estimator. It is basically composed of a random support sampling step, followed by a random direction with uniform smoothing on the sphere supported by this support. We also use the technique of averaging our estimator over q dimensions, as described in [22].

More formally, our gradient estimator is described below:

$$\hat{\nabla} f_{\boldsymbol{\xi}}(\boldsymbol{x}) = \frac{d}{q\mu} \sum_{i=1}^{q} \left(f_{\boldsymbol{\xi}}(\boldsymbol{x} + \mu \boldsymbol{u}_i) - f_{\boldsymbol{\xi}}(\boldsymbol{x}) \right) \boldsymbol{u}_i \tag{2}$$

where each random direction $\boldsymbol{u}_i$ is a unit vector sampled uniformly from the set $\mathcal{S}_{s_2}^d := \{\boldsymbol{u} \in \mathbb{R}^d : \|\boldsymbol{u}\|_0 \leq s_2, \|\boldsymbol{u}\| = 1\}$. We can obtain such vectors $\boldsymbol{u}$ by sampling first a random support S (i.e. a set of coordinates) of size s_2 from $[d]$, (denoted as $S \sim \mathcal{U}(\binom{[d]}{s_2})$) in Algorithm 1) and then by sampling a random unit vector $\boldsymbol{u}$ supported on that support S, that is, uniformly sampled from the set $\mathcal{S}_S^d := \{\boldsymbol{u} \in \mathbb{R}^d : \boldsymbol{u}_{[d]-S} = \boldsymbol{0}, \|\boldsymbol{u}\| = 1\}$, (denoted as $\boldsymbol{u} \sim \mathcal{U}(\mathcal{S}_S^d)$ in algorithm 1). The original uniform smoothing technique on the sphere is described in more detail in [11]. However, in our case, the sphere along which we sample is restricted to a random support of size s_2. Our general estimator, through the setting of the variable s_2, can take several forms, which are similar to pre-existing gradient estimators from the literature described below:

- In the case $s_2 = d$, our estimator retrieves the *usual vanilla estimator with uniform smoothing on the sphere* [11].

- In the case where $1 \leq s_2 \leq d$, our estimator is similar to the Random Block-Coordinate gradient estimator from Lian et al. [19], except that the blocks are not fixed at initialization but chosen randomly, and that we use a uniform smoothing with forward difference on the given block instead of a coordinate-wise estimation with central difference. This random support technique allows us to give a convergence analysis under the classical assumptions of the hard-thresholding literature (see Remark 3), and to deal with huge scale optimization, when even sampling uniformly from a unit d-sphere is costly [5, 6].

Error Bounds of the Zeroth-Order Estimator. We now derive error bounds on the gradient estimator, that will be useful in the convergence rate proof, except that we consider *only the restriction to some support F* (that is, we consider a subset of components of the gradient/estimator). Indeed, proofs in the hard-thresholding literature (see for instance [41]), are usually written only on that support. That is the key idea which explains how the dimensionality dependence is reduced when doing SZOHT compared to vanilla ZO optimization. We give more insight on the shape of the original distribution of gradient estimators, and the distribution of their projection onto a hyperplane F in Figure 5 in Appendix E. We can observe that even if the original gradient estimator is poor, in the projected space, the estimation error is reduced. In this section, we will quantify how exactly better that projected estimate is.

Proposition 1. *(Proof in Appendix C.3) Let us consider any support $F \subset [d]$ of size s ($|F| = s$). For the Z0 gradient estimator in (2), with q random directions, and random supports of size s_2, and assuming that each $f_{\boldsymbol{\xi}}$ is (L_{s_2}, s_2)-RSS, we have, with $\hat{\nabla}_F f_{\boldsymbol{\xi}}(\boldsymbol{x})$ denoting the hard thresholding of the gradient $\nabla f_{\boldsymbol{\xi}}(\boldsymbol{x})$ on F (that is, we set all coordinates not in F to 0):*

(a) $\|\mathbb{E}\hat{\nabla}_F f_{\boldsymbol{\xi}}(\boldsymbol{x}) - \nabla_F f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 \leq \varepsilon_\mu \mu^2$

(b) $\mathbb{E}\|\hat{\nabla}_F f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 \leq \varepsilon_F \|\nabla_F f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 + \varepsilon_{F^c} \|\nabla_{F^c} f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 + \varepsilon_{abs} \mu^2$

(c) $\mathbb{E}\|\hat{\nabla}_F f_{\boldsymbol{\xi}}(\boldsymbol{x}) - \nabla_F f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 \leq 2(\varepsilon_F + 1)\|\nabla_F f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 + 2\varepsilon_{F^c} \|\nabla_{F^c} f_{\boldsymbol{\xi}}(\boldsymbol{x})\|^2 + 2\varepsilon_{abs} \mu^2$

152 *where* $\varepsilon_\mu = L_{s_2}^2 sd$, $\varepsilon_F = \frac{2d}{q(s_2+2)}\left(\frac{(s-1)(s_2-1)}{d-1}+3\right)+2$, $\varepsilon_{F^c} = \frac{2d}{q(s_2+2)}\left(\frac{s(s_2-1)}{d-1}\right)$ *and*

153 $\varepsilon_{abs} = \frac{2dL_{s_2}^2 ss_2}{q}\left(\frac{(s-1)(s_2-1)}{d-1}+1\right)+L_{s_2}^2 sd.$

3.2 SZOHT Algorithm

155 We now present our full algorithm to optimize problem 1, which we name SZOHT (Stochastic
156 Zeroth-Order Hard Thresholding). Each iteration of our algorithm is composed of two steps: (i) the
157 gradient estimation step, and (ii) the hard thresholding step, where the gradient estimation step is
158 the one described in the section above, and the hard-thresholding is described in more detail in the
159 following paragraph. We give the full formal description of our algorithm in Algorithm 1.

160 In the hard thresholding step, we only keep the k largest (in magnitude) components of the current
161 iterate x^t. This ensures that all our iterates (including the last one) are k-sparse. This hard-thresholding
162 operator has been studied for instance in [32], and possesses several interesting properties. Firstly, it
163 can be seen as a projection on the ℓ_0 ball. Second, importantly, it is not non-expansive, contrary to
164 other operators like the soft-thresholding operator [32]. That expansivity plays an important role in
165 the analysis of our algorithm, as we will see later.

166 Compared to previous works, our algorithm can be seen as a variant of Stochastic Hard Thresholding
167 (StoIHT from [28]), where we replaced the true gradient of f_ξ by the estimator $\hat{\nabla} f_\xi(x)$. It is also
168 very close to Algorithm 5 from Balasubramanian and Ghadimi [2] (Truncated-ZSGD), with just
169 a different zeroth-order gradient estimator: we use a uniform smoothing, random-block estimator,
170 instead of their gaussian smoothing, full support vanilla estimator. This allows us to deal with very
171 large dimensionalities, in the order of millions, similarly to Cai et al. [6]. Furthermore, as described
172 in the Introduction, contrary to Balasubramanian and Ghadimi [2], we provide the analysis of our
173 algorithm without any gradient sparsity assumption.

174 The key challenge arising in our analysis is described in Figure 1: the hard-thresholding operator is
175 known to not be non-expansive [32], which means that each approximate gradient step must approach
176 the solution enough to stay close to it even after hard-thresholding. Therefore, it is *a priori* unclear
177 whether the zeroth-order estimate can be accurate enough to guarantee the convergence of SZOHT.
178 Hopefully, as we will see in the next section, we can indeed ensure convergence, as long as we
carefully choose the value of q.

179 Figure 1: Conflict between the hard-thresholding operator and the zeroth-order estimate.

4 Convergence analysis

181 In this section, we provide the convergence analysis of SZOHT, using the assumptions from section
182 2, and discuss an interesting property of the combination of the zeroth-order gradient estimate and
183 the hard-thresholding operator, providing a positive answer to the question from the previous section.

Theorem 1. *(Proof in Appendix D.1) Assume that that each f_ξ is $(L_{s'}, s' := \max(s_2, s))$-RSS, and that f is (ν_s, s)-RSC and σ-FGN, with $s = 2k + k^* \le d$, with $k \ge \rho^2 k^*/(1-\rho^2)^2$, with ρ defined as below. Suppose that we run SZOHT with random supports of size s_2, with q random directions, a learning rate of $\eta = \frac{\nu_s}{(4\varepsilon_F+1)L_{s'}^2}$ (with ε_F defined above in Proposition 1), and with k coordinates kept at each iterations. Then, we have a geometric convergence rate, of the following form, with $x^{(t)}$ denoting the t-iterate of SZOHT:*

$$\mathbb{E}\|x^{(t)} - x^*\| \le (\gamma\rho)^t \|x^{(0)} - x^*\| + \left(\frac{\gamma a}{1-\gamma\rho}\right)\sigma + \left(\frac{\gamma b}{1-\gamma\rho}\right)\mu$$

Algorithm 1: Stochastic Zeroth-Order Hard-Thresholding (SZOHT)

Initialization: *Learning rate η, maximum number of iterations T, size of the random directions support s_2, number of random directions q, number of coordinates to keep at each iteration $k = \mathcal{O}(\kappa^4 k^*)$, initial point $\boldsymbol{x}^{(0)}$ with $\|\boldsymbol{x}^{(0)}\|_0 \leq k^*$ (typically $\boldsymbol{x}^{(0)} = 0$), .*

Output : $\boldsymbol{x}^T$.

for $t = 1, ..., T$ **do**

    Sample $\boldsymbol{\xi}$ (for instance sample a train sample i)

    for $i = 1, ..., q$ **do**

        Sample a random support $S \sim \mathcal{U}(\binom{[d]}{s_2})$

        Sample a random direction $\boldsymbol{u}_i$ from the unit sphere supported on S: $\boldsymbol{u}_i \sim \mathcal{U}\left(\mathcal{S}_S^d\right)$

        Compute $\hat{\nabla} f_{\boldsymbol{\xi}}(\boldsymbol{x}^{t-1}; \boldsymbol{u}_i) = \frac{d}{\mu}\left(f_{\boldsymbol{\xi}}(\boldsymbol{x} + \mu\boldsymbol{u}_i) - f_{\boldsymbol{\xi}}(\boldsymbol{x})\right)\boldsymbol{u}_i$;

    end

    Compute $\hat{\nabla} f_{\boldsymbol{\xi}}(\boldsymbol{x}^{t-1}) = \frac{1}{q} \sum_{i=1}^{q} \hat{\nabla} f_{\boldsymbol{\xi}}(\boldsymbol{x}^{t-1}; \boldsymbol{u}_j)$

    Compute $\tilde{\boldsymbol{x}}^t = \boldsymbol{x}^{t-1} - \eta \hat{\nabla} f_{\boldsymbol{\xi}}(\boldsymbol{x}^{t-1})$;

    Compute $\boldsymbol{x}^t = \tilde{\boldsymbol{x}}_k^t$ as the truncation of $\tilde{\boldsymbol{x}}^t$ with top k entries preserved;

end

---

with $a = \eta\left(\sqrt{(4\varepsilon_F s + 2) + \varepsilon_{F^c}(d-k)} + \sqrt{s}\right)$, $b = \left(\frac{\sqrt{\varepsilon_\mu}}{L_{s'}} + \eta\sqrt{2\varepsilon_{abs}}\right)$, $\rho^2 = 1 - \frac{\nu_s^2}{(4\varepsilon_F+1)L_{s'}^2}$,

$\gamma = \sqrt{1 + \left(k^*/k + \sqrt{(4 + k^*/k)\,k^*/k}\right)/2}$, and ε_F, ε_{abs} and ε_μ are defined in Proposition 1

above.

Remark 2 (System error)**.** *The format of our result is similar to the ones in [41] and [28], in that it contains a linear convergence term, and a system error which depends on the expected norm of the gradient at $\boldsymbol{x}^*$ (through the variable σ). But, due to the error from the ZO estimate, it also contains another system error term which depends on the smoothing radius μ.*

Remark 3 (Generality)**.** *If we take $s_2 \leq s$, the first assumption of Theorem 1 becomes the requirement that $f_{\boldsymbol{\xi}}$ is (L_s, s)-RSS. Therefore, SZOHT as well as the theorem above provides, up to our knowledge, the first algorithm that can work in the usual setting of hard-thresholding algorithms (that is, (L_s, s)-RSS and (ν_s, s)-RSC [28, 32]), as well as its convergence rate.*

Interplay between hard-thresholding and zeroth-order error Importantly, contrary to previous works in zeroth-order optimization, the number of random directions q must be chosen carefully here. Indeed, there is an interesting phenomenon arising in our specific setting which combines zeroth-order gradient estimates and the hard-thresholding operator. As described in [32], the hard-thresholding operator is not non-expansive, contrary to the soft-thresholding operator or the projection onto the ℓ_1 ball [32]. This means that projecting onto the ℓ_0 ball can drive the iterates away from the solution. Therefore, enough descent must be made by the (approximate) gradient step to ensure to that we get close enough to the solution. Since any error introduced in the gradient estimate may worsen the descent, it is crucial to limit those errors as much as possible. This problem arises with any kind of gradient errors: for instance with SGD errors [28, 43], it is generally dealt with either by ensuring some conditions on the function f [28], forming bigger batches of samples (to decrease the error in the gradient) [43], and/or considering a larger number of components k kept in hard-thresholding (to make the hard-thresholding less expansive). Since in our work we want to consider as much as possible assumptions-free settings, we don't consider ensuring additional conditions on f. Rather, similarly to Zhou et al. [43], we consider instead dealing with this problem by relaxing k and sampling more directions (that latter technique is the zeroth-order equivalent to taking bigger batch-size in SGD). However, there is an additional effect that happens in our case, specific to zeroth order estimation: indeed, as described in Proposition 1, the quality of our estimator *also depends on k*! Therefore, it may be hard to make the algorithm converge only by considering larger k: *higher k means less expansivity (which helps convergence), but worse gradient estimate (which harms convergence)*. Therefore, it is even more crucial to tune precisely our degree of freedom at hand which is q. We further illustrate this conflict between the non-expansiveness of hard-thresholding (quantified by the parameter γ [32]), and the error from the zeroth-order estimate in Figure 1

More precisely, we provide below the minimal value q, needed to ensure the descent of our algorithm, that is, to ensure $\rho\gamma < 1$ for some $k^* \geq 1$:

Lemma 1 (First condition on q, Proof in Appendix D.2). *Let $k^* \in \{1, ..., d\}$. In the case $s_2 > 1$, if $q \geq q_{min}$, with q_{min} defined below, then there exist $k \in \mathbb{N}$ such that $k \geq k^* \frac{\rho^2}{(1-\rho^2)^2}$. If $s_2 = 1$, no condition on q is needed to ensure such an existence. However, in the case $s_2 = 1$, $q = 1$ does not ensure the second necessary condition in the following Remark 4, as detailed in the proof of the present Lemma. Therefore, a minimal value of q is always necessary to ensure, for Theorem 1 to apply.*

$$q_{min} = \frac{16d(s_2 - 1)k^*\kappa^2}{(s_2 + 2)(d - 1)}\left[18\kappa - 1 + 2\sqrt{9\kappa(9\kappa - 1) + \frac{1}{2} - \frac{1}{2k^*} + \frac{3}{2}\frac{d-1}{s_2 - 1}}\right]$$

Remark 4 (Second condition on q). *As mentioned in the Lemma 1 above, there is also a second condition on q necessary to ensure for Theorem 1 to be valid, which is simply to ensure that the smallest valid k above (i.e. from the first condition), is smaller or equal to d (since we cannot keep more components than we have).*

4.1 Weak/non dependence on dimensionality of the query complexity.

In this section, we provide Corollaries 1 and 2, following from Theorem 1, which give an example of q that is valid for both these conditions above, allowing to converge (that is, to obtain $\gamma\rho < 1$ in Theorem 1), and that achieves weak dimensionality dependence in the case of RSS, and complete dimension independence in the case of smoothness.

Corollary 1 (RSS $f_{\boldsymbol{\xi}}$, proof in Appendix D.3). *Assume that that almost all $f_{\boldsymbol{\xi}}$ are $(L_{s'}, s' := \max(s_2, s))$-RSS, and that f is (ν_s, s)-RSC and σ-FGN, with $s = 2k + k^* \leq d$, with $k \geq (86\kappa^4 - 12\kappa^2)k^*$ (with $\kappa := \frac{L_{s'}}{\nu_s}$). Suppose that we run SZOHT with random support of size s_2, a learning rate of $\eta = \frac{\nu_s}{13L_{s'}^2}$, with k coordinates kept at each iterations by the hard-thresholding, and with $q \geq 2s + 6\frac{d}{s_2}$. Then, we have a geometric convergence rate, of the following form, with $\boldsymbol{x}^{(t)}$ denoting the t-iterate of SZOHT:*

$$\mathbb{E}\|\boldsymbol{x}^{(t)} - \boldsymbol{x}^*\| \leq (\gamma\rho)^t\|\boldsymbol{x}^{(0)} - \boldsymbol{x}^*\| + \left(\frac{\gamma a}{1 - \gamma\rho}\right)\sigma + \left(\frac{\gamma b}{1 - \gamma\rho}\right)\mu$$

with a, b and γ are defined above in Theorem 1, and $\rho = \sqrt{1 - \frac{2}{13\kappa^2}}$. Therefore, the query complexity to ensure that $\mathbb{E}\|\boldsymbol{x}^{(t)} - \boldsymbol{x}^*\| \leq \varepsilon + \left(\frac{\gamma a}{1-\gamma\rho}\right)\sigma + \left(\frac{\gamma b}{1-\gamma\rho}\right)\mu$ is $\mathcal{O}(\kappa^2(k + \frac{d}{s_2})\log(\frac{1}{\varepsilon}))$.

We now turn to the case where the functions $f_{\boldsymbol{\xi}}$ are smooth. The key result in that case is that we can have a query complexity independent of the dimension d, which is, up to our knowledge, the first result of such kind for sparse zeroth-order optimization without assuming any gradient sparsity.

Corollary 2 (Smooth $f_{\boldsymbol{\xi}}$, proof in Appendix D.4). *Assume that, in addition to the conditions from Corollary 1 above, almost all $f_{\boldsymbol{\xi}}$ are L-smooth, with $k \geq (86\kappa^4 - 12\kappa^2)k^*$ (with $\kappa := \frac{L}{\nu_s}$), and take $q \geq 2(s + 2)$, and $s_2 = d$ (that is, no random support sampling). Then, we have a geometric convergence rate, of the following form, with $\boldsymbol{x}^{(t)}$ denoting the t-iterate of SZOHT:*

$$\mathbb{E}\|\boldsymbol{x}^{(t)} - \boldsymbol{x}^*\| \leq (\gamma\rho)^t\|\boldsymbol{x}^{(0)} - \boldsymbol{x}^*\| + \left(\frac{\gamma a}{1 - \gamma\rho}\right)\sigma + \left(\frac{\gamma b}{1 - \gamma\rho}\right)\mu$$

Therefore, the query complexity to ensure that $\mathbb{E}\|\boldsymbol{x}^{(t)} - \boldsymbol{x}^*\| \leq \varepsilon + \left(\frac{\gamma a}{1-\gamma\rho}\right)\sigma + \left(\frac{\gamma b}{1-\gamma\rho}\right)\mu$ is $\mathcal{O}(\kappa^2 k \log(\frac{1}{\varepsilon}))$.

Additionally, our convergence rate highlights an interesting connection between the geometry of f (defined by the condition number $\kappa = L_{s'}/\nu_s$), and the number of random directions that we need to take at each iteration: if the problem is ill-conditioned, that is κ is high, then we need a bigger k. This result is standard in the ℓ_0 litterature (see for instance [41]). But specifically, in our ZO case, it also impacts the query complexity: since the projected gradient is harder to approximate when the

dimension k of the projection is larger, q needs to grow too, resulting in higher query complexity. We believe this is an interesting result for the sparse zeroth-order optimization community: it reveals that the query complexity may in fact depend on some notion of intrinsic dimension to the problem, related to both the sparsity of the iterates k, and the geometry of the function f for a given s_2 (through the restricted condition number κ), rather than the dimension of the original space d as in previous works like [12].

5 Experiments

5.1 Sensitivity analysis

We first conduct a sensitivity parameter analysis on a toy example, to highlight the importance of the choice of q, as discussed in Section 4. We fix a target sparsity $k^* = 5$, choose $k = 74k^*$, and consider a sparse quadric function $f : \mathbb{R}^{5000} \to \mathbb{R}$, with: $f(\boldsymbol{x}) = \frac{1}{2}\|\boldsymbol{a}^\top(\boldsymbol{x} - \boldsymbol{b})\|^2$, with $\boldsymbol{a}_i = 1$ if $i \geq d - s$ and 0 otherwise (to ensure f is s-RSC and smooth, with $\nu_s = L = 1$), and $\boldsymbol{b}_i = \frac{i}{100d}$ for all $i \in [d]$. We choose η as in Theorem 1: $\eta = \frac{1}{(4\varepsilon_F + 1)}$ with ε_F defined in Proposition 1 in terms of s and d (we take $s_2 = d$), and present our results in Figure 2, for six values of q. We can observe on Figure 2(b) that the smaller the q, the less $f(\boldsymbol{x})$ can descend. Interestingly, we can also see on Figure 2(a) that for $q = 1$ and 20, $\|\boldsymbol{x}^{(t)} - \boldsymbol{x}^*\|$ diverges: we can indeed compute that $\rho\gamma > 1$ for those q, which explains the divergence, from Theorem 1.

5.2 Baselines

We compare our SZOHT algorithms with state of the art zeroth-order algorithms that can deal with sparsity constraints, that appear in Table 1:

1. **ZSCG** [12] is a Frank-Wolfe ZO algorithm, for which we consider an ℓ_1 ball constraint.

2. **RSPGF** [2] is a proximal ZO algorithm, for which we consider an ℓ_1 penalty.

3. **ZORO** [5] is a proximal ZO algorithm, that makes use of sparsity of gradients assumptions, using a sparse reconstruction algorithm at each iteration to reconstruct the gradient from a few measurements. Similarly, as for ZSCG, we consider an ℓ_1 penalty.

In all the applications below, we will tune the sparsity k of SZOHT, the penalty of RSPGF and ZORO, and the radius of the constraint of ZSCG, such that all algorithms attain a similar converged objective value, for fair comparison.

5.3 Applications

We compare the algorithms above on two tasks: a sparse asset risk management task from [7], and an adversarial attack task [8] with a sparsity constraint.

Sparse asset risk management We consider the portfolio management task and dataset from [7], similarly to [5]. We have a given portfolio of d assets, with each asset i giving an expected return $\boldsymbol{m}_i$, and with a global covariance matrix of the return of assets denoted as $\boldsymbol{C}$. The cost function we minimize is the portfolio risk: $\frac{\boldsymbol{x}^T \boldsymbol{C} \boldsymbol{x}}{2(\sum_{i=1}^d \boldsymbol{x}_i)^2}$, where $\boldsymbol{x}$ is a vector where each component $\boldsymbol{x}_i$ denotes how much is invested in each asset, and we require to minimize it under a constraint of minimal return r: $\frac{\sum_{i=1}^d \boldsymbol{m}_i \boldsymbol{x}_i}{\sum_{i=1}^d \boldsymbol{x}_i}$. We enforce that constraint using the Lagrangian form below. Finally, we add a sparsity constraint, to restrict the investments to only k assets. Therefore, we obtain the cost function below:

$$\min_{x \in \mathbb{R}^d} \frac{\boldsymbol{x}^\top \boldsymbol{C} \boldsymbol{x}}{2\left(\sum_{i=1}^d \boldsymbol{x}_i\right)^2} + \lambda \left(\min\left\{\frac{\sum_{i=1}^d \boldsymbol{m}_i \boldsymbol{x}_i}{\sum_{i=1}^d \boldsymbol{x}_i} - r, 0\right\}\right)^2 \quad \text{s.t.} \quad \|\boldsymbol{x}\|_0 \leq k$$

We use three datasets: port3, port4 and port5 from the OR-library [3], of respective dimensions $d = 89; 98; 225$. We keep r and λ the same for the 4 algorithms: $r = 0.1$, $\lambda = 10$ (for port3 and port4); and $r = 1e - 3$, $\lambda = 1e - 3$ for port5. For SZOHT, we set $k = 10$, $s2 = 10$, $q = 10$, and

283 obtain the optimal μ and η by grid search, both over the interval $[10^{-3}, 10^3]$. For all other algorithms,
284 we got the optimal hyper-parameters through grid search. We present our results in Figure 3.

285 **Few pixels adversarial attacks** We consider the problem of adversarial attacks with a sparse
286 constraint. Our goal is to minimize $\min_\delta f(\boldsymbol{x} + \boldsymbol{\delta})$ such that $\|\boldsymbol{\delta}\|_0 \leq k$, where f is the Carlini-Wagner
287 cost function [8], that is computed from the outputs of a pre-trained model on the corresponding
288 dataset. We consider three different datasets for the attacks: MNIST, CIFAR, and Imagenet, of
289 dimension respectively $d = 784; 3072; 268203$. All algorithms are initialized with $\boldsymbol{\delta} = \boldsymbol{0}$. We set
290 the hyperparameters of SZOHT as follows: MNIST: $k = 20$, $s_2 = 100$, $q = 100$; CIFAR: $k = 60$,
291 $s_2 = 100$, $q = 1000$; ImageNet: $k = 100000$, $s_2 = 1000$, $q = 100$. We present our results in Figure
292 4. All experiments are conducted in the workstation with four NVIDIA RTX A6000 GPUs, and take
293 about one day to run.

5.4 Results and Discussion

295 We can observe from Figures 3 and 4 that the performance of SZOHT is comparable or better than
296 the other algorithms. This can be explained by the fact that SZOHT has a linear convergence, but the
297 query complexity of ZSCG and RSPGF is in $\mathcal{O}(1/T)$. We can also notice that RSPGF is faster than
298 ZSCG, which is natural since proximal algorithms are faster than Frank-Wolfe algorithms. Finally, it
299 appears that the convergence of ZORO is sometimes slower, particularly at the early stage of training,
300 which may come from the fact that ZORO assumes sparse gradients, which is not necessarily verified
301 in real-world use cases like the ones we consider; in those cases where the gradient is not sparse, it is
302 possible that the sparse gradient reconstruction step of ZORO does not work well. This motivates
303 even further the need to consider algorithms able to work without those assumptions, such as SZOHT.

(a) $f(\boldsymbol{x})$

(a) port3   (b) port4   (c) port5

Figure 3: $f(\boldsymbol{x})$ vs. # queries (asset management)

(b) $\|\boldsymbol{x} - \boldsymbol{x}^*\|$

(a) MNIST   (b) CIFAR   (c) Imagenet

Figure 2: Sensitivity analysis

Figure 4: $f(\boldsymbol{x})$ vs. # queries (adversarial attack)

304

6 Conclusion

306 In this paper, we proposed a new algorithm, SZOHT, for sparse zeroth-order optimization. We gave
307 its convergence analysis and showed that it is dimension independent in the smooth case, and weak
308 dimension-dependent in the RSS case. We further verified experimentally the efficiency of SZOHT
309 in several settings. Moreover, throughout the paper, we showed how the condition number of f as
310 well as the gradient error have an important impact on the convergence of SZOHT. As such, it would
311 be interesting to study whether we can improve the query complexity by regularizing f, by using
312 an adaptive learning rate or acceleration methods, or by using recent variance reduction techniques.
313 Finally, it would also be interesting to extend this work to a broader family of sparse structures, such
314 as low-rank approximations or graph sparsity. We leave this for future work.

References

[1] George B Arfken and Hans J Weber. Mathematical methods for physicists, 1999.

[2] Krishnakumar Balasubramanian and Saeed Ghadimi. Zeroth-order (non)-convex stochastic optimization via conditional gradient and gradient updates. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pages 3459–3468, 2018.

[3] John E Beasley. Or-library: distributing test problems by electronic mail. *Journal of the operational research society*, 41(11):1069–1072, 1990.

[4] Peter Bühlmann and Sara Van De Geer. *Statistics for high-dimensional data: methods, theory and applications*. Springer Science & Business Media, 2011.

[5] HanQin Cai, Daniel Mckenzie, Wotao Yin, and Zhenliang Zhang. Zeroth-order regularized optimization (zoro): Approximately sparse gradients and adaptive sampling. 2020.

[6] HanQin Cai, Yuchen Lou, Daniel McKenzie, and Wotao Yin. A zeroth-order block coordinate descent algorithm for huge-scale black-box optimization. In *International Conference on Machine Learning*, pages 1193–1203. PMLR, 2021.

[7] T-J Chang, Nigel Meade, John E Beasley, and Yazid M Sharaiha. Heuristics for cardinality constrained portfolio optimisation. *Computers & Operations Research*, 27(13):1271–1302, 2000.

[8] Pin-Yu Chen, Huan Zhang, Yash Sharma, Jinfeng Yi, and Cho-Jui Hsieh. Zoo: Zeroth order optimization based black-box attacks to deep neural networks without training substitute models. In *Proceedings of the 10th ACM workshop on artificial intelligence and security*, pages 15–26, 2017.

[9] Xiangyi Chen, Sijia Liu, Kaidi Xu, Xingguo Li, Xue Lin, Mingyi Hong, and David Cox. Zo-adamm: Zeroth-order adaptive momentum method for black-box optimization. *arXiv preprint arXiv:1910.06513*, 2019.

[10] Krzysztof Choromanski, Aldo Pacchiano, Jack Parker-Holder, Yunhao Tang, Deepali Jain, Yuxiang Yang, Atil Iscen, Jasmine Hsu, and Vikas Sindhwani. Provably robust blackbox optimization for reinforcement learning. In *Conference on Robot Learning*, pages 683–696. PMLR, 2020.

[11] Xiang Gao, Bo Jiang, and Shuzhong Zhang. On the information-adaptive variants of the admm: an iteration complexity perspective. *Journal of Scientific Computing*, 76(1):327–363, 2018.

[12] Saeed Ghadimi, Guanghui Lan, and Hongchao Zhang. Mini-batch stochastic approximation methods for nonconvex stochastic composite optimization. *Mathematical Programming*, 155 (1):267–305, 2016.

[13] Daniel Golovin, John Karro, Greg Kochanski, Chansoo Lee, Xingyou Song, and Qiuyi Zhang. Gradientless descent: High-dimensional zeroth-order optimization. In *International Conference on Learning Representations*, 2019.

[14] Robert Mansel Gower, Nicolas Loizou, Xun Qian, Alibek Sailanbayev, Egor Shulgin, and Peter Richtárik. SGD: general analysis and improved rates. *CoRR*, abs/1901.09401, 2019. URL http://arxiv.org/abs/1901.09401.

[15] Prateek Jain, Ambuj Tewari, and Purushottam Kar. On iterative hard thresholding methods for high-dimensional m-estimation. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014. URL https://proceedings.neurips.cc/paper/2014/file/218a0aefd1d1a4be65601cc6ddc1520e-Paper.pdf.

[16] Kevin G Jamieson, Robert D Nowak, and Benjamin Recht. Query complexity of derivative-free optimization. *arXiv preprint arXiv:1209.2434*, 2012.

[17] Evgeny S Levitin and Boris T Polyak. Constrained minimization methods. *USSR Computational mathematics and mathematical physics*, 6(5):1–50, 1966.

[18] Xingguo Li, Raman Arora, Han Liu, Jarvis Haupt, and Tuo Zhao. Nonconvex sparse learning via stochastic optimization with progressive variance reduction. *arXiv preprint arXiv:1605.02711*, 2016.

[19] Xiangru Lian, Huan Zhang, Cho-Jui Hsieh, Yijun Huang, and Ji Liu. A comprehensive linear speedup analysis for asynchronous stochastic parallel optimization from zeroth-order to first-order. *Advances in Neural Information Processing Systems*, 29, 2016.

[20] Hongcheng Liu and Yu Yang. A dimension-insensitive algorithm for stochastic zeroth-order optimization. *arXiv preprint arXiv:2104.11283*, 2021.

[21] Sijia Liu, Bhavya Kailkhura, Pin-Yu Chen, Paishun Ting, Shiyu Chang, and Lisa Amini. Zeroth-order stochastic variance reduction for nonconvex optimization. *arXiv preprint arXiv:1805.10367*, 2018.

[22] Sijia Liu, Pin-Yu Chen, Bhavya Kailkhura, Gaoyuan Zhang, Alfred O Hero III, and Pramod K Varshney. A primer on zeroth-order optimization in signal processing and machine learning: Principals, recent advances, and applications. *IEEE Signal Processing Magazine*, 37(5):43–54, 2020.

[23] Po-Ling Loh and Martin J Wainwright. Regularized m-estimators with nonconvexity: Statistical and algorithmic theory for local optima. *Advances in Neural Information Processing Systems*, 26, 2013.

[24] Horia Mania, Aurelia Guy, and Benjamin Recht. Simple random search provides a competitive approach to reinforcement learning. *arXiv preprint arXiv:1803.07055*, 2018.

[25] Sahand Negahban, Bin Yu, Martin J Wainwright, and Pradeep Ravikumar. A unified framework for high-dimensional analysis of m-estimators with decomposable regularizers. *Advances in neural information processing systems*, 22, 2009.

[26] Sahand N Negahban, Pradeep Ravikumar, Martin J Wainwright, and Bin Yu. A unified framework for high-dimensional analysis of m-estimators with decomposable regularizers. *Statistical science*, 27(4):538–557, 2012.

[27] Yurii Nesterov and Vladimir Spokoiny. Random gradient-free minimization of convex functions. *Foundations of Computational Mathematics*, 17(2):527–566, 2017.

[28] Nam Nguyen, Deanna Needell, and Tina Woolf. Linear convergence of stochastic iterative greedy algorithms with sparse constraints. *IEEE Transactions on Information Theory*, 63(11): 6869–6895, 2017.

[29] Garvesh Raskutti, Martin J Wainwright, and Bin Yu. Minimax rates of estimation for high-dimensional linear regression over ℓ_q-balls. *IEEE transactions on information theory*, 57(10): 6976–6994, 2011.

[30] Tim Salimans, Jonathan Ho, Xi Chen, Szymon Sidor, and Ilya Sutskever. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv preprint arXiv:1703.03864*, 2017.

[31] Ohad Shamir. An optimal algorithm for bandit and zero-order convex optimization with two-point feedback. *The Journal of Machine Learning Research*, 18(1):1703–1713, 2017.

[32] Jie Shen and Ping Li. A tight bound of hard thresholding. *The Journal of Machine Learning Research*, 18(1):7650–7691, 2017.

[33] Artem Sokolov, Julian Hitschler, Mayumi Ohta, and Stefan Riezler. Sparse stochastic zeroth-order optimization with an application to bandit structured prediction. *arXiv preprint arXiv:1806.04458*, 2018.

[34] Stanislav Sykora. Surface integrals over n-dimensional spheres. *Stan's Library*, (Volume I), May 2005. doi: 10.3247/sl1math05.002. URL https://doi.org/10.3247/sl1math05.002.

[35] Robert Tibshirani. Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society: Series B (Methodological)*, 58(1):267–288, 1996.

[36] Chun-Chen Tu, Paishun Ting, Pin-Yu Chen, Sijia Liu, Huan Zhang, Jinfeng Yi, Cho-Jui Hsieh, and Shin-Ming Cheng. Autozoom: Autoencoder-based zeroth order optimization method for attacking black-box neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 742–749, 2019.

[37] Sara A Van de Geer. High-dimensional generalized linear models and the lasso. *The Annals of Statistics*, 36(2):614–645, 2008.

[38] Martin J Wainwright, Michael I Jordan, et al. Graphical models, exponential families, and variational inference. *Foundations and Trends® in Machine Learning*, 1(1–2):1–305, 2008.

[39] Christian Walck et al. Hand-book on statistical distributions for experimentalists. *University of Stockholm*, 10:96–01, 2007.

[40] Yining Wang, Simon Du, Sivaraman Balakrishnan, and Aarti Singh. Stochastic zeroth-order optimization in high dimensions. In *International Conference on Artificial Intelligence and Statistics*, pages 1356–1365. PMLR, 2018.

[41] Xiao-Tong Yuan, Ping Li, and Tong Zhang. Gradient hard thresholding pursuit. *J. Mach. Learn. Res.*, 18(1):6027–6069, 2017.

[42] Xiaotong Yuan and Ping Li. Stability and risk bounds of iterative hard thresholding. In *International Conference on Artificial Intelligence and Statistics*, pages 1702–1710. PMLR, 2021.

[43] Pan Zhou, Xiaotong Yuan, and Jiashi Feng. Efficient stochastic gradient hard thresholding. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL https://proceedings.neurips.cc/paper/2018/file/ec5aa0b7846082a2415f0902f0da88f2-Paper.pdf.