MultiFacet: A Multi-Tasking Framework for Speech-to-Sign Language Generation

Submission Id: 9

ABSTRACT

Sign language is a rich form of communication, uniquely conveying meaning through a combination of gestures, facial expressions, and body movements. Existing research in sign language generation has predominantly focused on text-to-sign pose generation, while speech-to-sign pose generation remains relatively underexplored. Speech-to-sign language generation models can facilitate effective communication between the deaf and hearing communities. In this paper, we propose an architecture that utilises prosodic information from speech audio and semantic context from text to generate sign pose sequences. In our approach, we adopt a multi-tasking strategy that involves an additional task of predicting Facial Action Units (FAUs). FAUs capture the intricate facial muscle movements that play a crucial role in conveying specific facial expressions during sign language generation. We train our models on an existing Indian Sign language dataset that contains sign language videos with audio and text translations. To evaluate our models, we report Dynamic Time Warping (DTW) and Probability of Correct Keypoints (PCK) scores. We find that combining prosody and text as input, along with incorporating facial action unit prediction as an additional task, outperforms previous models in both DTW and PCK scores. We also discuss the challenges and limitations of speech-to-sign pose generation models to encourage future research in this domain. We commit to release all the models, results and code to foster reproducibility and encourage future research.

CCS CONCEPTS

• **Computing methodologies** → **Neural networks**; **Learning latent representations**; **Computer vision**; **Information extraction**.

KEYWORDS

speech to sign language, indian sign language, prosody, pose generation

ACM Reference Format:
Anonymous Author(s). 2023. MultiFacet: A Multi-Tasking Framework for Speech-to-Sign Language Generation. In *Proceedings of (GENEA-ICMI '23)*. ACM, New York, NY, USA, 7 pages. https://doi.org/10.1145/nnnnnnn.nnnnnnn

1 INTRODUCTION

Sign language is a rich form of communication that seamlessly blends together the fluidity of hand movements and gestures, the expressiveness of facial expressions and head movements, and the subtle nuances of body language. It is this harmony of hand movements and expression that makes it complete and effective. According to the World Health Organization (WHO), over 1.5 billion people, which accounts for approximately 20% of the global population, live with hearing loss, underscoring the importance of accessibility in communication [10]. While the field of Natural Language Processing (NLP) has made remarkable progress in developing language technologies that simplify daily tasks, the advancement in technology to support sign language has not been as substantial [24]. Bridging this gap, automatic sign language translation and generation systems provide an efficient and accessible means of communication between the deaf and the hearing community.

Recent years have seen a surge of interest in sign language technologies, with researchers exploring various computer vision and deep learning approaches to tackle this complex task [12]. While many of these works utilize text or gloss as input for generation tasks, the area of speech-to-sign language generation remains relatively underexplored [12]. Gloss, often used to represent sign language, has been found to lack accuracy in capturing the complete linguistic and expressive aspects of sign language [22, 27]. A study on the Phoenix dataset [2] showed that a significant portion of the data contained linguistic elements not present in the gloss representation [27]. While text input can help generate semantic signs, incorporating prosodic information extracted from audio can provide more comprehensive data for a richer sign language output[3].

Inspired by co-speech gesture generation literature[9], which shares similarities with sign language generation, we utilize audio along with text as input to generate sign pose sequences. In this paper, we introduce MultiFacet, an architecture that uses prosodic information derived from speech coupled with semantic information sourced from text. This integrated data serves as the input for the generation of keypoints pertaining to both facial and hand movements. Furthermore, our approach includes the prediction of Facial Action Units (AUs) within a multi-tasking setup. We evaluate our model using Dynamic Time Warping (DTW) and Probability of Correct Keypoints (PCK) metrics against the existing Indian Sign Language dataset[7] and demonstrate the critical importance of prosody and facial action unit prediction in better sign language generation. In summary, our main contributions are as follows:

- Leveraged prosody information from audio and semantic context from text to determine their significance in sign language generation.
- Exploring the importance of facial action unit prediction for generating hand and face keypoints in Indian sign language.

- We conducted ablation studies and extensively discussed the limitations of our work to inspire future research and advancements in this domain.

2 RELATED WORK

Sign Pose Generation Majority of the works in sign language generation are based on text or gloss as inputs[12]. [15] generated continuous hand pose sequences using text as input. While this is a great step in the field, it is only a partial representation of sign language, as facial expressions and body language also play a critical role in conveying meaning [5, 11]. Later works attempted to address this limitation by including both manual (hand movements) and non-manual (facial expressions) features in the generation process but still relied on text or gloss as input. [13] used adversarial training for multichannel sign production with text as input, and [16] represented sign sequences as skeletal graph structures with gloss as an intermediary. [21] generated keypoints for hand movements and face by concatenating embedding outputs from a text encoder and a gloss encoder. [22] first generated Hamnosys notation from text which was further converted to continuous sign pose sequences. These approaches made strides towards incorporating non-manual features but still lacked the use of prosodic information as input corresponding to the non-manual features in sign language. [14, 18] generated photo-realistic sign videos using text as input. They first generated skeleton poses from text and then generated sign videos conditioned on these poses.

To address this concern of loss of prosody in gloss representation, [27] presented gloss enhancement strategies for introducing intensity modifiers in gloss annotations using Phoenix dataset [2]. Intensity modifiers are the ones that quantify nouns, adjectives or adverbs in a sentence ((e.g., very happy or little happy). Recent works explored the use of speech melspectrogram inputs to generate hand movements in Indian Sign Language [7]. While this approach is a step in the right direction, generating hand movements alone is insufficient to capture the full extent of sign language.

Co-speech Gesture Generation Co-speech gesture generation studies have shown the significance of using both speech and text as input for generating semantically relevant and rythmic gestures [9]. [1, 8, 25] have proposed continuous gesture generation systems using audio and text as input, further underscoring the importance of multimodal information for generating meaningful gestures.

Non-Manual Recognition in Sign Language [19] presented 3D-CNN based multimodal framework for recognition of grammatical errors in continuous signing videos belonging to different sentence types. First, they used 3D-CNN networks to recognise the grammatical elements from manual gestures, facial expressions and head movements. Then they employed a sliding window approach to find the correspondences between these modalities to find the grammatical errors.

In this paper, by incorporating prosody and non-manual feature recognition, such as predicting Facial Action Units, we aim to improve the accuracy and naturalness of sign language generation.

3 SPEECH TO SIGN LANGUAGE GENERATION

Given audio and text inputs, our aim is to generate sequences of sign poses denoted as S, which include both upper body and face keypoints. To accomplish this, we adopt a multi-task learning approach, incorporating a speech encoder, a Facial Action Units (FACs) decoder, and a sign pose decoder. The overall architecture is illustrated in Figure 1.

3.1 Input Embeddings

To facilitate the generation process, we extract two types of embeddings from the input data: BERT embeddings for text and Tacotron 2 GST[23] encodings for audio. We use the GST model provided by NVIDIA[1] which was pre-trained on *train-clean-100* subset of LibriTTS dataset[26] to learn the expressive features in audio. The BERT embeddings, denoted as E_{text}, capture the semantic information embedded within the text, allowing our model to understand the linguistic context. We represent the input text as a sequence of tokens $\{x_1, x_2, ..., x_W\}$, and BERT provides the corresponding embeddings $\{e_{x_1}, e_{x_2}, ..., e_{x_W}\}$. Hence, the shape of the text embeddings is W × 768.

The Tacotron 2 GST encodings, denoted as E_{audio}, extract both linguistic content and prosody information from the audio input. The GST model was pretrained on LibriTTS dataset [26] with the objective of learning a large range of acoustic expressiveness. We represent the audio input as a sequence of mel-spectrograms $\{m_1, m_2, ..., m_T\}$, where each mel-spectrogram has T × 256 dimensions. Tacotron 2 GST[23] provides the corresponding embeddings $\{e_{m_1}, e_{m_2}, ..., e_{m_T}\}$.

3.2 FACS Preprocessing

Amongst various methods for denoting facial expressions, the Facial Action Coding System (FACS) stands as a comprehensive and standardized tool. It has been meticulously designed to describe and analyze these nonverbal cues by precisely identifying distinct facial muscle movements. Central to FACS are its action units, a set of codes representing individual facial muscle actions, which, when combined, proficiently portray a diverse array of emotions and expressions. As a result of its efficacy, FACS finds widespread application across various disciplines, including psychology, neuroscience, anthropology, and computer graphics, providing an objective and systematic means to categorize and comprehend facial expressions.

While FACS is an index of facial expressions with an anatomical basis, it generally does not provide the degree of muscle activation. While there are modifiers that extend this coding system to accommodate intensities as well, we don't consider them in our study due to limited resources and clear consensus on their use. For ease of understanding, we have provided examples of how the action units in FACS are mapped to corresponding facial expressions in **??**. For more details, we recommend our readers to refer to resources [2] and [3].

The use of FACS for sign language translation or generation is relatively understudied [4], [5], [6]. One of the primary reasons for

---

[1] https://github.com/NVIDIA/mellotron/tree/master

[2] https://en.wikipedia.org/wiki/Facial_Action_Coding_System

[3] https://imotions.com/blog/learning/research-fundamentals/facial-action-coding-system/

[4] https://ieeexplore.ieee.org/document/9320274

[5] https://www.semanticscholar.org/paper/Facial-action-unit-detection-methodology-with-in-Silva-Costa/25cab0f4cec903baf443dff301b39fcce171375c

[6] https://www.semanticscholar.org/paper/Analysis-of-Facial-Expressions-in-Brazilian-Sign-Silva-Kumada/d74bccb3b5271577569a008fe9e0b0c64fa3bd3e

Figure 1: The Architecture: We propose a novel architecture to generate sign pose sequences by utilising the prosodic information from speech and semantic context from text. We also incorporate additional decoders to facilitate rich sign pose generation: (i) Facial Action Unit decoder and (ii) Cross modal decoder.

its limited use is the costly annotation required for the existing sign language datasets. To overcome this issue, we propose using an existing state-of-the-art model, ME-GraphAU [7], to predict the action units for our chosen dataset and use it as weak-supervision during sign-language generation task. Details for chosen model such as its architecture, the dataset it is trained on and the action units it predicts, can be found in the appendix.

The output of the aforementioned model is noisy and lacks temporal consistency since the prediction occurs on a per-frame basis. Training with such an output would invariably lead to noisy supervision and poor learning on the model's part for the proposed task. As such, we propose a pre-processing pipeline for reducing the noise using the following steps:

- Threshold the output of the model using the probabilities as confidence for each action unit and remove any low confidence predictions.
- For these pruned predictions, we use linear interpolation for estimating their new values.
- Finally, to reduce the remaining noise, we use hanning smoothing over each action unit and get the final output.

We use a window length of 11, which corresponds to 0.5 seconds at 24FPS frame-rate of our source videos.

We show an example of the original prediction and output of each step in the above-mentioned pipeline in Figure 2. We provide both the raw as well as processed FACS for the chosen dataset to the users to evaluate and improve results with future experiments.

Figure 3 shows the ground truth facial action units extracted.

3.3 Model Components

The input embeddings $\mathbf{E}_{\text{text}}$ and $\mathbf{E}_{\text{audio}}$ are then passed to their respective encoders in our model:

1. **Prosody Encoder**: The transformer-based speech encoder, denoted as E_{speech}, processes the Tacotron 2 GST encodings $\mathbf{E}_{\text{audio}}$ to obtain intermediate representations $\mathbf{H}_{\text{speech}}$. This can be expressed as:

$$\mathbf{H}_{\text{speech}} = E_{\text{speech}}(\mathbf{E}_{\text{audio}})$$

2. **FACs Decoder**: We incorporate the FACs task as an additional objective to capture facial expressions. The FACs decoder, denoted as D_{FACs}, processes the Tacotron 2 GST encodings $\mathbf{E}_{\text{audio}}$ to predict the Facial Action Units, denoted as **FACs**. This can be expressed as:

$$\mathbf{FACs} = D_{\text{FACs}}(\mathbf{E}_{\text{audio}})$$

[7]https://arxiv.org/abs/2205.01782v2

Figure 2: FACs Preprocessing Pipeline

Figure 3: Ground Truth Facial Action Units

Facial AUs is a widely used facial expression coding system that consists of a set of action units that correspond to different facial muscle movements. We use a transformer-based decoder[20] for this task and train it using cross-entropy loss.

$$\mathcal{L}_{\text{FACs}} = -\frac{1}{N} \sum_{n=1}^{N} \sum_{i=1}^{M} y_{n,i} \log(p_{n,i}) \tag{1}$$

where N is the number of training examples, M is the number of Facial Action Units, $y_{n,i}$ is the ground-truth label for the i-th Facial Action Unit in the n-th example (either 0 or 1), and $p_{n,i}$ is the predicted probability for the i-th Facial Action Unit in the n-th example.

3. **Sign Pose Decoder**: Our sign pose decoder, denoted as D_{pose}, is a transformer-based decoder that takes the intermediate representations $\mathbf{H}_{\text{speech}}$ and the predicted Facial Action Units **FACs** as input to generate the sequence of sign poses $\mathbf{S}$. The keypoints for each frame in the sign pose sequence are represented as a 3D tensor, with dimensions num_frames $\times$ 85 $\times$ 3.

We use regression loss to train the sign pose decoder, given by:

$$\mathcal{L}_{\text{pose}} = \frac{1}{N} \sum_{n=1}^{N} \sum_{i=1}^{85} \|y_{n,i} - \hat{y}_{n,i}\|^2 \tag{2}$$

where N is the number of training examples, $y_{n,i}$ is the ground-truth value of the i-th keypoint for the n-th example, and $\hat{y}_{n,i}$ is the predicted value of the i-th keypoint for the n-th example.

4. **Cross-Modal Discriminator** We use the same discriminator used by [7] to match the speech segments with corresponding pose sequences. The softmax loss for the cross-modal discriminator can be defined as follows:

$$\mathcal{L}_{\text{discriminator}} = -\frac{1}{N} \sum_{n=1}^{N} \log(\text{softmax}(\mathbf{D}_{\text{cross-modal}}(\mathbf{H}_{\text{speech}_n}))_{y_n}) \tag{3}$$

where $\mathbf{D}_{\text{cross-modal}}$ is the cross-modal discriminator, $\mathbf{H}_{\text{speech}_n}$ is the intermediate representation for the n-th example obtained by the prosody encoder, y_n is the label indicating whether the corresponding pose sequence matches the speech segment or not, and $\text{softmax}(\mathbf{D}_{\text{cross-modal}}(\mathbf{H}_{\text{speech}_n}))_{y_n}$ is the predicted probability for the correct label.

3.4 Multi-Tasking Setup

We use a weighted sum of the losses from the individual decoders to compute the overall loss.

$$\mathcal{L}_{\text{total}} = \lambda_{\text{FACs}} \cdot \mathcal{L}_{\text{FACs}} + \lambda_{\text{pose}} \cdot \mathcal{L}_{\text{pose}} + \lambda_{\text{discriminator}} \cdot \mathcal{L}_{\text{discriminator}}$$

where λ_{FACs}, λ_{pose}, and $\lambda_{\text{discriminator}}$ are hyperparameters that control the relative importance of the FACs loss, pose loss, and discriminator loss, respectively.

The weights for each task are chosen to balance the contribution All the decoders are trained in a multitasking setup. The model is trained to minimize the multitasking loss $\mathcal{L}_{\text{total}}$ using gradient-based optimization techniques.

4 IMPLEMENTATION DETAILS

Our transformer comprises 2 layers for all the encoders and decoders with 8 attention heads each. The output dimensions are 512. We use adam optimizer with a learning rate of 0.001.

5 EXPERIMENTS

5.1 Dataset

The dataset used in our study is the continuous Indian Sign Language dataset, which was released by [7]. This dataset contains sign videos along with corresponding audio and text transcription, covering various topics, such as current affairs, sports, and world news. The dataset comprises 9137 videos and has a vocabulary size of 10k.

To represent the sign videos in our analysis, we extracted 3D joint position keypoints using mediapipe [4]. This process involved detecting 37 landmark points for the eyes, eyebrows, lips, and face outline, along with 6 landmark points for the shoulders, elbows, and hips. Additionally, each hand was represented with 21 landmark points, bringing the total to 85 keypoints for upper body, hands and face.

5.2 Baseline Models

Text2Sign We use the progressive transformers proposed by [15] as our baseline. We train them on the Indian Language Dataset with 3D keypoints for face and upper body.

Speech2Sign [7] utilized mel spectrograms as input to generate sign pose sequences of hand movements. They incorporate text decoder and a cross modal discriminator for learning the correlation between speech and sign pose sequences. We use this architecture to generate face and body keypoints and consider it as our baseline.

5.3 Evaluation Metrics

Dynamic Time Warping (DTW) Dynamic Time Warping (DTW) [6] is one of the evaluation metrics for speech-to-sign language generation models to assess the alignment between the predicted sign language sequences and the ground truth sign language sequences.

Let $P = (p_1, p_2, \ldots, p_M)$ denote the predicted sign language sequence, where p_i represents the i-th pose in the predicted sequence, and M is the length of the predicted sequence. Similarly, let the ground truth sign language sequence be denoted as $G = (g_1, g_2, \ldots, g_N)$, where g_i represents the i-th pose in the ground truth sequence, and N is the length of the ground truth sequence.

DTW aims to find an optimal alignment between the sequences P and G by introducing a warping path $W = \{w_1, w_2, \ldots, w_K\}$, where $w_k = (i, j)$ denotes the alignment of p_i in the predicted sequence with g_j in the ground truth sequence. The warping path satisfies the conditions: $w_1 = (1, 1)$, $w_K = (M, N)$, and $w_k - w_{k-1} \in \{(1, 0), (0, 1), (1, 1)\}$, allowing for insertions, deletions, and matches between the sequences.

The objective of DTW is to minimize the accumulated cost along the warping path W, which is defined by a distance or similarity measure between the individual poses in the sequences. Let $d(p_i, g_j)$ represent the distance between p_i and g_j in the pose space. The accumulated cost $C(W)$ along the warping path W is given by:

$$C(W) = \sum_{k=1}^{K} d(p_{w_k}, g_{w_k})$$

To compute the final DTW score, we aim to find the optimal warping path W^* that minimizes the accumulated cost $C(W)$:

$$DTW(P, G) = \min_{W} C(W)$$

The DTW score provides a measure of the alignment between the predicted and ground truth sign language sequences, considering the temporal differences and variations in the movement patterns. A lower DTW score indicates a better alignment and higher similarity between the sequences.

Probability of Correct Keypoints (PCK) PCK is a widely used evaluation metric to assess the accuracy of pose estimation models. It measures the percentage of correctly predicted keypoints within a certain threshold distance compared to the ground truth keypoints.

Let $G = \{g_1, g_2, \ldots, g_N\}$ be the set of ground truth keypoints, and $P = \{p_1, p_2, \ldots, p_N\}$ be the set of predicted keypoints. Each keypoint, g_i or p_i, consists of (x, y, z) coordinates representing the position of a particular body part, such as a hand or face.

To compute the PCK score, we need to define a threshold distance δ. For each ground truth keypoint g_i, we check if there exists a

Table 1: Comparison of Dynamic Time Warping (DTW) and Probabilty of Correct Keypoints (PCK) scores with baselines on dev and test sets. B+F indicates model that predicts body+face keypoints. PE - Prosody Encoder; TE: Text Encoder

Model	DTW Score ↓	PCK ↑
Dev set		
Text[15] ->Sign	19.55	0.61
Speech2sign [7]	15.94	0.72
PE + TE ->Sign	16.1	0.74
PE + TE ->Sign + FACS	**13.37**	**0.79**
Test set		
Text ->Sign	22.55	0.59
Speech2sign [7]	14.08	0.78
PE + TE ->Sign	17.3	0.72
PE + TE ->Sign + FACS	**13.37**	**0.79**

corresponding predicted keypoint p_j within the threshold distance δ. If such a predicted keypoint exists, and its distance to the ground truth keypoint is less than or equal to δ, we consider it as a correct prediction.

Mathematically, the PCK score can be computed as follows:

$$PCK = \frac{1}{N} \sum_{i} \delta(g_i, p_i)$$

where N is the total number of keypoints, and $\delta(g_i, p_i)$ is an indicator function defined as:

$$\delta(g_i, p_i) = \begin{cases} 1, & \text{if } ||g_i - p_i|| \leq \delta \\ 0, & \text{otherwise} \end{cases}$$

Here, $||g_i - p_i||$ represents the Euclidean distance between the ground truth keypoint g_i and the predicted keypoint p_i.

The PCK score is then calculated as the average of the indicator values over all keypoints. It represents the percentage of keypoints that have been correctly predicted within the specified threshold distance δ. A higher PCK score indicates better accuracy and alignment between the predicted and ground truth keypoints.

In the context of sign language generation models, PCK can be used to evaluate the quality of the generated sign language poses by comparing them to the ground truth poses. However, it's important to note that PCK only considers individual keypoints and does not capture the overall spatial or temporal coherence of the generated sign language sequences.

5.4 Results and insights

We report DTW[6] and Probability of Correct Keypoints scores on the Indian Sign Language dataset and compare it with the results of both Text2Sign[15] and Speech2Sign [7] methods. From table 1 we observe that our model performs significantly better than the existing Speech2Sign[7] method.

Table 2: Comparison of ablation studies. PE - Prosody Encoder; TE-Text Encoder

Model	DTW Score ↓	PCK ↑
TE ->Sign	13.82	0.81
TE ->Sign + FAUs	15.69	0.78
PE ->Sign	17.16	0.73
PE ->Sign + FAUs	14.52	0.75
PE + TE ->Sign + FAUs (Ours)	**13.23**	**0.81**

6 ABLATION ANALYSIS

To evaluate the contribution of each component in our proposed architecture, we conduct ablation studies on our model. Specifically, we perform experiments where we remove each compare from the multitasking setup one by one and compare the results with the full model.

Table 2 summarizes the results of our ablation studies. As can be seen, removing the FAUs decoder results in a drop in performance in both metrics. The results demonstrate the effectiveness of our multitasking approach in leveraging multiple modalities for sign language generation. However, we observe that the results are still close to the model that uses only the text encoder.

In summary, our ablation studies demonstrate the effectiveness of our multitasking approach in leveraging multiple modalities for sign language generation.

7 LIMITATIONS & CHALLENGES

Evaluation Methods: Although our model has achieved state-of-the-art results based on DTW scores, it is essential to conduct human evaluation with expert sign language interpreters to ensure the quality and relevance of the generated sign language. DTW scores only assess the alignment between ground truth poses and predicted poses but do not measure the correlation with the input speech. Correlating these scores with human evaluation ratings is crucial for understanding the model's performance in real-world communication scenarios. Metrics that measure the coherence and synchronization of other non-manual elements, such as body posture, head movements, and eye gaze are also necessary [19]. Therefore, when designing a sign language generation model, accounting for these linguistic elements and their dynamic interactions is essential to produce more accurate and culturally appropriate sign language outputs.

Fine Movements: The current model successfully learns coarse hand movements but lacks the ability to capture fine movements of fingers and facial parts. This limitation is attributed to the use of Mean Squared Error (MSE) loss, which penalizes larger movements more than fine movements. To address this issue, alternative loss functions, such as a keypoint loss proposed by [17], should be explored. This loss involves a hand keypoint discriminator pre-trained on 2D hand poses and may improve the model's capability to generate more accurate and intricate hand movements.

More Linguistic Information: One significant challenge lies in handling the sequential nature of input speech or text, as opposed to the non-linear and simultaneous nature of sign language. Speech unfolds in a linear manner, and sign language relies on the integration of multiple components in parallel. Thus, capturing and mapping these linguistic structures effectively requires specialized attention. Understanding how signers use space, directionality, and facial expressions to indicate different grammatical constructs is crucial for generating natural and contextually appropriate sign language. Currently, our model focuses primarily on generating hand and facial movements, neglecting other crucial components. Future work should explore incorporating non-manual markers, body language, and gaze direction into the generation process to enhance the naturalness and comprehensiveness of sign language communication.

Errors in Skeleton Pose Extraction: One of the significant challenges in sign language generation is accurately extracting the skeleton pose from the input video or speech. The skeleton pose serves as a crucial input to the model, representing the keypoint positions of the signer's hands, face, and body movements. Although advanced pose estimation techniques like Mediapipe provide robust keypoint predictions, there are inherent limitations and errors that can impact the overall performance of the sign language generation model. Sign language videos captured in real-world settings may contain various forms of noise, occlusions, and artifacts. These imperfections can lead to inaccuracies in the pose estimation process, resulting in incorrect keypoint positions. For instance, background clutter, complex hand gestures, or fast movements may obscure the hand keypoints, leading to incomplete or noisy pose representations. Additionally, sign language involves intricate hand and finger movements that can sometimes be challenging to discern accurately. The dynamic nature of sign language requires precise identification of hand shapes, finger positions, and gestures. However, the inherent ambiguity in certain signs or gestures can lead to misinterpretations and inaccuracies in the extracted skeleton pose.

Pose Representation: The representation of sign language as keypoint sequences in videos is abstract and results in the loss of some skeletal information. This may lead to some loss of fine-grained details in the generated sign language. Future research could explore alternative representations that preserve more intricate skeletal information for more accurate sign language generation.

Dataset Size and Variety: Our current dataset size and variety might be limited, which could impact the model's ability to capture the full complexity and richness of sign language. Expanding the dataset or exploring low-resource training techniques is essential to improve the model's generalization and performance on diverse signing styles and linguistic patterns.

Signer Style: Sign language relies on the signer's individual style and preferences, which can significantly affect the model's performance. Investigating the impact of varying signer styles on the model's output and devising methods to adapt the model to different signing styles are critical for real-world applicability.

In conclusion, while our model shows promising results in generating sign language from speech, there are several limitations and challenges that need to be addressed in future work.

8 CONCLUSION

In this paper, we introduced a multi-tasking approach, the MultiFacet model, for generating sign language poses from input speech and text. Our model goes beyond just hand movements, also capturing facial expressions, resulting in a more comprehensive representation of sign language.

To assess the effectiveness of our model, we conducted experiments on the Indian Sign Language dataset provided by [7]. By incorporating a pre-trained prosody encoder and utilizing Facial Action Units, we achieved even better results, surpassing previous methods. The potential applications of our approach extend beyond sign language communication.

To evaluate the effectiveness of our model, we conducted experiments on the Indian Sign Language dataset released by [7]. The addition of pre-trained speech encoder and the use of Facial Action Units have further improved the quality of generated poses. Although we achieved better results with the proposed approach, there is significant room for further advancements in several aspects, including the datasets, methodologies, understanding of the intricate relationship between speech and sign language, and evaluation methods. We hope that our work will inspire further research in this area and contribute to improving accessibility and inclusivity for the deaf and hard-of-hearing community.

REFERENCES

[1] Chaitanya Ahuja, Dong Won Lee, Ryo Ishii, and Louis-Philippe Morency. 2020. No Gestures Left Behind: Learning Relationships between Spoken Language and Freeform Gestures. In *Findings of the Association for Computational Linguistics: EMNLP 2020*. Association for Computational Linguistics, Online, 1884–1895. https://doi.org/10.18653/v1/2020.findings-emnlp.170

[2] Necati Camgoz, Simon Hadfield, Oscar Koller, Hermann Ney, and Richard Bowden. 2018. Neural Sign Language Translation. https://doi.org/10.1109/CVPR.2018.00812

[3] Svetlana Dachkovsky and Wendy Sandler. 2009. Visual Intonation in the Prosody of a Sign Language. *Language and Speech* 52, 2-3 (2009), 287–314. https://doi.org/10.1177/0023830909103175 arXiv:https://doi.org/10.1177/0023830909103175 PMID: 19624033.

[4] Ivan Grishchenko and Valentin Bazarevsky. 2020. *MediaPipe Holistic — Simultaneous Face, Hand and Pose Prediction, on Device.* https://ai.googleblog.com/2020/12/mediapipe-holistic-simultaneous-face.html

[5] Carlos Gussenhhoven and Aoju Chen. 2020. *The Oxford Handbook of Language Prosody.* Oxford University Press. https://doi.org/10.1093/oxfordhb/9780198832232.001.0001

[6] Peter J. Huber. 1964. Robust Estimation of a Location Parameter. *The Annals of Mathematical Statistics* 35, 1 (1964), 73 – 101. https://doi.org/10.1214/aoms/1177703732

[7] Parul Kapoor, Rudrabha Mukhopadhyay, Sindhu Hegde, Vinay Namboodiri, and C.V. Jawahar. 2021. Towards Automatic Speech to Sign Language Generation. 3700–3704. https://doi.org/10.21437/Interspeech.2021-1094

[8] Taras Kucherenko, Patrik Jonell, Sanne van Waveren, Gustav Eje Henter, Simon Alexandersson, Iolanda Leite, and Hedvig Kjellström. 2020. Gesticulator: A Framework for Semantically-Aware Speech-Driven Gesture Generation. In *Proceedings of the 2020 International Conference on Multimodal Interaction* (Virtual Event, Netherlands) *(ICMI '20)*. Association for Computing Machinery, New York, NY, USA, 242–250. https://doi.org/10.1145/3382507.3418815

[9] Simbarashe Nyatsanga, Taras Kucherenko, Chaitanya Ahuja, Gustav Eje Henter, and Michael Neff. 2023. A Comprehensive Review of Data-Driven Co-Speech Gesture Generation. *CoRR* abs/2301.05339 (2023). https://doi.org/10.48550/arXiv.2301.05339 arXiv:2301.05339

[10] World Health Organization. 2023. Hearing Loss. https://www.who.int/health-topics/hearing-loss#tab=tab_2 Accessed: 21-07-2023.

[11] Roland Pfau and Josep Quer. 2010. *Nonmanuals: their grammatical and prosodic roles.* Cambridge University Press, 381–402. https://doi.org/10.1017/

CBO9780511712203.018

[12] Razieh Rastgoo, Kourosh Kiani, Sergio Escalera, Vassilis Athitsos, and Mohammad Sabokrou. 2022. All You Need In Sign Language Production. http://arxiv.org/abs/2201.01609 arXiv:2201.01609 [cs.].

[13] Ben Saunders, Necati Cihan Camgoz, and Richard Bowden. 2020. Adversarial Training for Multi-Channel Sign Language Production. arXiv:2008.12405 [cs.CV]

[14] Ben Saunders, Necati Cihan Camgoz, and Richard Bowden. 2020. Everybody Sign Now: Translating Spoken Language to Photo Realistic Sign Language Video. arXiv:2011.09846 [cs.CV]

[15] Ben Saunders, Necati Cihan Camgoz, and Richard Bowden. 2020. Progressive Transformers for End-to-End Sign Language Production. http://arxiv.org/abs/2004.14874 arXiv:2004.14874 [cs.].

[16] Ben Saunders, Necati Cihan Camgoz, and Richard Bowden. 2021. Skeletal Graph Self-Attention: Embedding a Skeleton Inductive Bias into Sign Language Production. arXiv:2112.05277 [cs.CV]

[17] Ben Saunders, Necati Cihan Camgoz, and Richard Bowden. 2022. Signing at Scale: Learning to Co-Articulate Signs for Large-Scale Photo-Realistic Sign Language Production. arXiv:2203.15354 [cs.CV]

[18] Stephanie Stoll, Necati Cihan Camgoz, Simon Hadfield, and Richard Bowden. 2020. Text2Sign: Towards Sign Language Production Using Neural Machine Translation and Generative Adversarial Networks. *Int. J. Comput. Vision* 128, 4 (apr 2020), 891–908. https://doi.org/10.1007/s11263-019-01281-2

[19] Elahe Vahdani, Longlong Jing, Yingli Tian, and Matt Huenerfauth. 2020. Recognizing American Sign Language Nonmanual Signal Grammar Errors in Continuous Videos. http://arxiv.org/abs/2005.00253 arXiv:2005.00253 [cs.].

[20] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. Attention Is All You Need. http://arxiv.org/abs/1706.03762 arXiv:1706.03762 [cs.].

[21] Carla Viegas, Mert İnan, Lorna Quandt, and Malihe Alikhani. 2022. Including Facial Expressions in Contextual Embeddings for Sign Language Generation. http://arxiv.org/abs/2202.05383 arXiv:2202.05383 [cs.].

[22] Harry Walsh, Ben Saunders, and Richard Bowden. 2022. Changing the Representation: Examining Language Representation for Neural Sign Language Production. In *Proceedings of the 7th International Workshop on Sign Language Translation and Avatar Technology: The Junction of the Visual and the Textual: Challenges and Perspectives*. European Language Resources Association, Marseille, France, 117–124. https://aclanthology.org/2022.sltat-1.18

[23] Yuxuan Wang, Daisy Stanton, Yu Zhang, RJ Skerry-Ryan, Eric Battenberg, Joel Shor, Ying Xiao, Fei Ren, Ye Jia, and Rif A. Saurous. 2018. Style Tokens: Unsupervised Style Modeling, Control and Transfer in End-to-End Speech Synthesis. arXiv:1803.09017 [cs.CL]

[24] Kayo Yin, Amit Moryossef, Julie Hochgesang, Yoav Goldberg, and Malihe Alikhani. 2021. Including Signed Languages in Natural Language Processing. *arXiv:2105.05222 [cs]* (July 2021). http://arxiv.org/abs/2105.05222 arXiv:2105.05222.

[25] Youngwoo Yoon, Bok Cha, Joo-Haeng Lee, Minsu Jang, Jaeyeon Lee, Jaehong Kim, and Geehyuk Lee. 2020. Speech Gesture Generation from the Trimodal Context of Text, Audio, and Speaker Identity. *ACM Trans. Graph.* 39, 6, Article 222 (nov 2020), 16 pages. https://doi.org/10.1145/3414685.3417838

[26] Heiga Zen, Viet Dang, Rob Clark, Yu Zhang, Ron J. Weiss, Ye Jia, Zhifeng Chen, and Yonghui Wu. 2019. LibriTTS: A Corpus Derived from LibriSpeech for Text-to-Speech. arXiv:1904.02882 [cs.SD]

[27] Mert İnan, Yang Zhong, Sabit Hassan, Lorna Quandt, and Malihe Alikhani. 2022. Modeling Intensification for Sign Language Generation: A Computational Approach. (2022). https://doi.org/10.48550/ARXIV.2203.09679 Publisher: arXiv Version Number: 1.