SHOULD WE BE *Pre*-TRAINING?
AN ARGUMENT FOR END-TASK AWARE TRAINING AS AN ALTERNATIVE

ABSTRACT

Pre-training, where models are trained on an auxiliary objective with abundant data before being fine-tuned on data from the downstream task, is now the dominant paradigm in NLP. In general, the pre-training step relies on little to no direct knowledge of the task on which the model will be fine-tuned, even when the end-task is known in advance. Our work challenges this status-quo of end-task agnostic pre-training. First, on three different low-resource NLP tasks from two domains, we demonstrate that multi-tasking the end-task and auxiliary objectives results in significantly better downstream task performance than the widely-used task-agnostic continued pre-training paradigm of Gururangan et al. (2020). We next introduce an online meta-learning algorithm that learns a set of multi-task weights to better balance among our multiple auxiliary objectives, achieving further improvements on end task performance and data efficiency.

1 INTRODUCTION

The increasingly popular pre-training paradigm (Dai & Le, 2015; Devlin et al., 2018; Gururangan et al., 2020) involves first training a *generalist* model on copious amounts of easy-to-obtain data, e.g. raw text data in NLP, and then using this model to initialize training on a wide swath of downstream tasks. Generalist models like BERT (Devlin et al., 2018), RoBERTa (Liu et al., 2019), and GPT-3 (Brown et al., 2020) have a strong appeal; a few institutions with significant resources incur the cost of training these large models whilst the rest of the research community enjoys a significant performance improvement at minimal computational overhead. However, the advantages of initializing a downstream task from a generalist model are not guaranteed. Previous work has shown that the benefits of pre-training depend heavily on the degree of domain overlap between the end task data and the massive, heterogenous data on which the generalist model was trained (Beltagy et al., 2019; Gururangan et al., 2020; Lee et al., 2020).

Figure 1: Pre-training trains on auxiliary task T_{aux} before fine-tuning on primary task T^*. End-task aware training optimizes both T_{aux} and T^* simultaneously and can find better minima since optimization is informed by the end-task.

Notably, Gururangan et al. (2020) have demonstrated the benefits of continued pre-training of generalist models using data that is similar to that of the end task. Their approach is formalized into two classes: Domain Adaptive Pre-training (DAPT) and Task Adaptive Pretraining (TAPT) where further stages of pre-training of generalist models are conducted on domain- and task-specific data, respectively. DAPT and TAPT exploit the fact that *we often know the end task beforehand*, and so we can make specific choices about our pre-training regimen to improve end-task performance.

However, in both pre-training for generalist models and continued pre-training, the training procedure itself does not explicitly incorporate the *end task objective function*. Because of this, practitioners have to be careful with their choice of auxiliary tasks, the order in which they are trained on, and the early-stopping criteria for each pre-training stage so as to actually achieve good downstream

end-task performance (Gururangan et al., 2020; Dery et al., 2021). In the absence of principled criteria to make these difficult design choices, it is common to instead resort to the computationally demanding heuristic of pre-training on as much data as possible for as long as possible.

In this paper, we ask the following question: "*In settings where we have a particular end task in mind, should we be **pre**-training at all?*". In response, we advocate for an alternative approach in which we directly introduce the end task objective of interest into the learning process. This results in a suite of end-task aware methods called TARTAN (end-**T**ask **A**wa**R**e **TrA**ini**N**g). Our formulations incorporate both unsupervised auxiliary objectives traditionally used in NLP pre-training (such as masked language modeling as in Devlin et al. (2018)) *and* the end-task objective, followed by an optional fine-tuning step on the end task. We motivate TARTAN experimentally by focusing on the more computationally friendly and ubiquitous continued pre-training setting. Based on this, we make the following contributions to the literature on leveraging auxiliary tasks and data:

- In lieu of standard end-task agnostic continued pre-training, we suggest introducing the end task objective into the training process via multi-task learning (Caruana, 1997; Ruder, 2017). We call this procedure **M**ulti-**T**asking end-**T**ask **A**wa**R**e **TrA**ini**N**g (MT-TARTAN) (Section 3.1). MT-TARTAN is a simple yet surprisingly effective alternative to task-agnostic pre-training. In Section 5, we demonstrate that MT-TARTAN significantly improves performance, convergence time, and data efficiency over Gururangan et al. (2020)'s results. It also obviates the need for fickle hyper-parameter tuning through direct optimization of validation performance.
- To allow more fine-grained control of the end task over the auxiliary tasks, in Section 3.2, we present an online meta-learning algorithm that learns adaptive multi-task weights with the aim of improving final end task performance. Our **META**-learning end-**T**ask **A**wa**R**e **TrA**ini**N**g (META-TARTAN) allows us to robustly modulate between multiple objectives and further improves performance over MT-TARTAN .
- A naive implementation of META-TARTAN based on first-order meta-learning analysis results in a sub-optimal algorithm that ignores all tasks except the end-task. We trace this problem to the use of a single model training head for computing both the end-task training loss and meta-objective (end-task validation loss). To guard against this pathological solution, we introduce a separate model head for computing the meta-objective. In Section 3.3, we justify this simple-to-implement fix and validate its practical efficacy in Section 5.

Our results suggest that TARTAN may be an attractive alternative to the widely used pre-training paradigm, and further research in this direction is warranted.

2   FORMALIZING PRE-TRAINING AND CONTINUED PRE-TRAINING

Consider a dataset $D = \{(x_i, y_i)_{i \in [m]}\}$ consisting of m labelled examples. We define a task as an objective function and dataset pair: $T = \{\mathcal{L}(\cdot), D\}$. Consider M_θ, a model parameterized by θ. The objective function $\mathcal{L}(y_i, M_\theta(x_i))$ evaluates how well a model prediction $M_\theta(x_i)$ fits the true label y_i, such as cross-entropy loss in the case of classification. Note that the task dataset, D, is typically decomposed into the sets $(D^{\mathrm{train}}, D^{\mathrm{val}}, D^{\mathrm{test}})$. D^{train} is the set of examples used for model training whilst D^{test} is used for final task evaluation. The validation set, D^{val}, is typically used for model selection but it is also frequently used in meta-learning to define the meta-objective $- \mathcal{L}_{T^*}^{val}$.

Given a specific end-task T^*, our aim is to improve performance on T^* (as measured by the model loss on $D_{T^*}^{\mathrm{test}}$) by leveraging auxiliary tasks $\mathbb{T}_{\mathrm{aux}} = \{T_1, \ldots, T_n\}$. Note that we do not particularly care about the performance of any of the tasks in $\mathbb{T}_{\mathrm{aux}}$. We are willing to sacrifice performance on $\mathbb{T}_{\mathrm{aux}}$ if it improves performance on T^*.

From the perspective of model architecture, there are several ways to leverage $\mathbb{T}_{\mathrm{aux}}$. We focus on the simple but ubiquitous parameter sharing setting. Here, all tasks share a model body θ_{body} but each task T_i has its own head ϕ^i for prediction. We denote the head belonging to T^* as ϕ'. Thus $\theta = \left[\theta_{\mathrm{body}}; \left(\phi^1, \ldots, \phi^n, \phi'\right)\right]$ and θ_{body} is reusable across new tasks.

2.1   PRE-TRAINING

Pre-training is when a model is first trained on $\mathbb{T}_{\mathrm{aux}}$ before performing a final fine-tuning phase on T^*. The motivation behind pre-training is that learning $\mathbb{T}_{\mathrm{aux}}$ first hopefully captures relevant

information that can be utilized during training of T^*. This desire has led to the proliferation of generalist pre-trained models like BERT (Devlin et al., 2018), RoBERTa (Liu et al., 2019) and GPT-3 (Brown et al., 2020) that have been trained on copious amounts of data. Generalist models have been widely successful at improving downstream task performance when used as initilization.

We can formalize the pre-training procedure as follows:

$$\theta_0 = \text{argmin}_\theta \left(\sum_{T_i \in \mathbb{T}_{\text{aux}}} \mathcal{L}_{T_i}(\theta) \right) \tag{1}$$

In Equation 1, we seek a point θ_0 that achieves minimal loss on the tasks in $\mathbb{T}_{\text{aux}}$. We hope that θ_0 will be a good starting point for gradient descent on T^*. Let $g(\theta_0)$ represent the set of end-points of stochastic gradient descent on an initialization, θ_0. Stochastic gradient descent from the same initialization can produce different end-points due to differences in hyper-parameters like learning rate, batch size and order, as well as regularization strength. We can write the fine-tuning phase as:

$$\theta^* = \text{argmin}_{\{\theta \,\in\, g(\theta_0)\}} \mathcal{L}_{T^*}(\theta) \tag{2}$$

Note that pre-training is *end-task agnostic*: the pre-training Equation 1 occurs entirely before training on the end-task Equation 2, and does not explicitly incorporate the end-task objective, T^*. Since there is no awareness of the end-task during pre-training it is important to carefully choose $\mathbb{T}_{\text{aux}}$ so that pre-training actually results in improved performance on T^* (Wang et al., 2018a). For text data, past work has found left-to-right language modeling (Peters et al., 2017) and masked language modeling (MLM) (Devlin et al., 2018) to be good choices to include in $\mathbb{T}_{\text{aux}}$.

2.2 CONTINUED PRE-TRAINING

Recent work (Beltagy et al., 2019; Gururangan et al., 2020; Lee et al., 2020) showed that downstream performance on T^* can be improved by further adapting generalist models via continued pre-training on a more relevant set of auxiliary tasks. This is equivalent to sequentially performing multiple steps of Equation 1, with different $\mathbb{T}_{\text{aux}}$, before finally performing Equation 2 on T^*.

Domain and Task Adaptive Pre-training Gururangan et al. (2020) present Domain Adaptive Pre-Training (DAPT) and Task Adaptive Pre-Training (TAPT) as methods for continued pre-training. During DAPT, a generalist model is further pre-trained on an unsupervised objective with large amounts of data from the same domain as the end-task. TAPT also pre-trains with the same unsupervised objective as DAPT, but on the actual dataset of the end task. Gururangan et al. (2020) find that performance can be further improved by chaining objectives, DAPT first, followed by TAPT.

Though TAPT and DAPT do not directly incorporate the end-task objective during training, it still indirectly informs both the choice of pre-training data and the order in which the pre-training tasks are trained on. Below, we explore stronger versions of this influence.

3 END-TASK AWARE TRAINING (TARTAN)

In this section, we argue for the end-task to be added directly into the training process to create explicit interactions between T^* and $\mathbb{T}_{\text{aux}}$.

3.1 END-TASK AWARE TRAINING VIA MULTI-TASKING (MT-TARTAN)

We propose to directly incorporate knowledge of the end-task by multi-tasking T^* together with $\mathbb{T}_{\text{aux}}$, before optionally fine-tuning on T^* exclusively. To this end, we introduce a set of task weights $\mathbf{w} = (w^*, w_1, \cdots, w_{|\mathbb{T}_{\text{aux}}|})$ satisfying $w^* + \sum_i w_i = 1$, to modulate between the different losses. Our new formulation is:

$$\theta_0 = \text{argmin}_\theta \ \mathcal{L}_{\text{total}}(\theta, \mathbf{w}) = \text{argmin}_\theta \left(w^* \mathcal{L}_{T^*}(\theta) + \sum_i w_i \mathcal{L}_{T_i}(\theta) \right) \tag{3}$$

Here, Equation 3 replaces Equation 1 and can be followed by the optional fine-tuning stage of Equation 2. Note that this formulation fixes the tasks weights $\mathbf{w}$ throughout the training process. We call this formulation End-task Aware Training via Multi-tasking (MT-TARTAN) because we introduce the end-task **directly** into the training procedure, and do so by **multi-tasking** it with $\mathbb{T}_{\text{aux}}$.

MT-TARTAN allows us to prioritize performance on T^* in several ways. First, we can weight the end-task higher than all the other auxiliary tasks. Also, during training, we can monitor $\mathcal{L}_{T^*}$ on the end-task validation set and early stop when it plateaus; even if the auxiliary tasks have not yet converged. This is not possible during standard pre-training because we do not train T^* and so it performs at random before we actually start fine-tuning. **Early stopping on T^* represents significant computational savings over end-task agnostic pre-training.**

3.2 End-task Aware Training via Meta-learning (META-TARTAN)

MT-TARTAN, DAPT and TAPT, all share the same drawback: they implicitly assume that the auxiliary tasks have static importance to the end-task over the lifetime of its training, either by being end-task agnostic (DAPT and TAPT) or by having static task weights (MT-TARTAN). With MT-TARTAN, an additional drawback noted by Wang et al. (2019); Yu et al. (2020) is that multi-tasking can negatively impact task performance compared to isolated training. These shortcomings motivate the formulation of an adaptive algorithm that can mitigate the negative influence of some tasks whilst responding to the changing relevance of auxiliary tasks over the lifetime of end-task training.

As they stand, the pre-training equation pair (Equations 1, 2) and the MT-TARTAN pair (Equations 2, 3) are decoupled. The inner-level variables of the pre-training phase do not depend on the outer-level variables of the fine-tuning phase. Thus the equation pairs are typically solved sequentially. We propose to tightly couple Equations 2 and 3 by formulating jointly learning $\mathbf{w}$ and θ_0 as a bi-level optimization problem. A bi-level formulation allows us to leverage meta-learning (Schmidhuber, 1995) techniques to learn adaptive task weights which capture variable auxiliary task importance whilst mitigating the contribution of harmful tasks. We propose a meta-learning algorithm in the mold of Model Agnostic Meta-Learning (MAML) (Finn et al., 2017) to learn task weights. As a bi-level problem, this can be formulated as :

$$\theta^*, \mathbf{w}^* = \mathrm{argmin}_{\{\theta \,\in\, g(\theta_0),\, \mathbf{w}\}} \, \mathcal{L}_{T^*}(\theta) \tag{4}$$

where

$$\theta_0 = \mathrm{argmin}_\theta \; \mathcal{L}_{\mathrm{total}}(\theta, \mathbf{w}) = \mathrm{argmin}_\theta \; \left(w^* \mathcal{L}_{T^*}(\theta) \; + \sum_{T_i \in \mathbb{T}_{\mathrm{aux}}} w_i \mathcal{L}_{T_i}(\theta) \right) \tag{5}$$

We want to jointly learn $\mathbf{w}$, with θ_0, such that taking a gradient descent step modulated by $\mathbf{w}$ leads to improvement in end-task generalization. We use **performance on the end-task validation set ($D_{T^*}^{\mathrm{val}}$) as a meta-objective** to train $\mathbf{w}$. Performance on $D_{T^*}^{\mathrm{val}}$ serves as a stand-in for end-task generalization performance whilst also naturally capturing the asymmetrical importance of T^*.

Our joint descent algorithm proceeds as follows. At each timestep t, we hold the task weights fixed and update θ_t based on $\nabla_\theta \mathcal{L}_{\mathrm{total}}(\theta_t, \mathbf{w})$. We then proceed to update $\mathbf{w}$ via gradient descent on the end-task validation loss at θ_{t+1}. For this, we derive an approximation for $\nabla_w \mathcal{L}_{T^*}^{val}(\theta_{t+1}, \mathbf{w})$ below:

$$\mathcal{L}_{T^*}^{val}(\theta_{t+1}(\mathbf{w})) = \mathcal{L}_{T^*}^{val}\left(\theta_t - \beta\big(w^* \nabla \mathcal{L}_{T^*} + \sum_i w_i \nabla \mathcal{L}_{T_i} \big) \right)$$

$$\approx \mathcal{L}_{T^*}^{val}(\theta_t) - \beta \left(w^* \nabla \mathcal{L}_{T^*} + \sum_i w_i \nabla \mathcal{L}_{T_i} \right)^T \nabla \mathcal{L}_{T^*}^{val}(\theta_t)$$

We can take the gradient of the above first-order approximation w.r.t an individual weight w_i. This tells us how to update w_i to improve the meta-objective.

$$\frac{\partial \mathcal{L}_{T^*}^{val}(\theta_{t+1}(\mathbf{w}))}{\partial w_i} \approx -\beta \big(\nabla \mathcal{L}_{T_i} \big)^T \big(\nabla \mathcal{L}_{T^*}^{val}(\theta_t) \big) = -\beta \big(\nabla \mathcal{L}_{T_i} \big)^T \big(\nabla \mathcal{L}_{T^*}^{val}(\big[\theta_{\mathrm{body}}, \phi'\big]_t) \big) \tag{6}$$

In Equation 6, we explicitly specify $\big[\theta_{\mathrm{body}}, \phi'\big]_t$ because computing losses on T^* depend on only these parameters. $\mathcal{L}_{T_i}$ depends solely on $\big[\theta_{\mathrm{body}}, \phi^i\big]_t$ but we leave this out to avoid notation clutter.

Our analysis above is similar to that of Lin et al. (2019) with one key difference: we learn a weighting for the main task w^* too. This ability to directly modulate T^* allows us to capture the fact that at certain stages in training, auxiliary tasks may have greater impact on end-task generalization than the end-task's own training data. This choice also allows us to control for over-fitting and the influence of bad (mislabelled or noisy) training data.

3.3 INTRODUCING A SEPARATE CLASSIFICATION HEAD FOR META-LEARNING

Observe that from Equation 6, updates for $w \neq w^*$ involve gradients computed from different model heads ϕ^i and ϕ' whilst for w^*, we are taking the dot product of gradients from the same end-task head ϕ'. As we will show empirically in Section 5.4, computing weight updates this way creates a strong bias towards the primary task, causing w^* to rail towards 1 whilst the other weights dampen to 0, which may be sub-optimal in the long run.

Intuitively, this short-horizon (greedy) behavior makes sense: the quickest way to make short-term progress (improve $\mathcal{L}_{T^*}^{val}(\theta_{t+1})$) is to descend solely on T^*. More formally, the greedy approach arises because we derive $\nabla_{w_i} \mathcal{L}_{T^*}^{val}(\theta_{t+1})$ in Equation 6 as a proxy for the gradient at θ^*, the outer-loop end-point in Equation 4. Variations of this substitution are common in the meta-learning literature (Finn et al., 2017; Liu et al., 2018; Nichol et al., 2018) because it is computationally infeasible to train a model to convergence every time we wish to compute $\nabla_{w_i} \mathcal{L}_{T^*}^{val}(\theta^*)$.

To remedy the greedy solution, instead of estimating $\nabla_\theta \mathcal{L}_{T^*}$ and $\nabla_\theta \mathcal{L}_{T^*}^{val}$ from the same classification head (Equation 6), we introduce a special head ϕ^* for computing the meta-objective. Specifically, instead of trying to compute θ^*, we approximate it by fixing the body of the network θ_{body} and training the randomly initialized head ϕ^* to convergence on a subset of the end-task training data. We do this every time we wish to estimate $\nabla_{w_i} \mathcal{L}_{T^*}^{val}(\theta^*)$. Introducing ϕ^* eliminates the strong positive bias on w^* and enables us to compute a better proxy for the meta-gradient at θ^*:

$$\frac{\partial \mathcal{L}_{T^*}^{val}(\theta^*(\mathbf{w}))}{\partial w_i} \approx \left(\nabla_\theta \mathcal{L}_{T_i}\right)^T \left(\nabla_\theta \mathcal{L}_{T^*}^{val}([\theta_{\mathrm{body}}; \phi^*]_t)\right) \tag{7}$$

Equation 7 represents a simple-to-implement alternative to Equation 6. We provide a more detailed justification for Equation 7 in Appendix A.1. In Section 5.4, we empirically validate that the transition from Equation 6 to 7 improves performance whilst mitigating pathological solutions. Our approach of creating ϕ^* for approximating the meta-objective (down-stream validation performance) is inspired by Metz et al. (2018), who use a similar technique to construct a meta-objective for evaluating the quality of unsupervised representations.

See Algorithm 1 in Appendix A.3 for details about META-TARTAN.

4 EXPERIMENTAL SETUP

In keeping with previous work (Devlin et al., 2018; Gururangan et al., 2020; Lee et al., 2020), we focus on $\mathbb{T}_{\mathrm{aux}}$ as a set of MLM tasks on varied datasets. In the case of DAPT and our end-task aware variants of it, $\mathbb{T}_{\mathrm{aux}}$ is an MLM task with data from the domain of the end-task. For TAPT, $\mathbb{T}_{\mathrm{aux}}$ is an MLM task with data from the end-task itself. DAPT, TAPT and DAPT+TAPT (chained pre-training with DAPT followed by TAPT) will serve as our baseline pre-training approaches. We will compare these baselines to their end-task aware variants that use MT-TARTAN and META-TARTAN.

Our choice of baselines reflect our focus on the continued pre-training setting (Section 2.2) instead of pre-training from scratch as with *generalist* models (Section 2.1). The continued pre-training setting is more ubiquitous amongst everyday practitioners as it is less computationally demanding. It thus lends itself more easily to extensive exploration. We leave investigating end-task-aware training from scratch to future work.

Datasets Our experiments focus on two domains: computer science (CS) papers and biomedical (BIOMED) papers. We follow Gururangan et al. (2020) and build our CS and BIOMED domain data from the S2ORC dataset (Lo et al., 2019). We extract 1.49M full text articles to construct our CS corpus and 2.71M for our BIOMED corpus. Under both domains, our end-tasks are *low-resource* classification tasks. Using low-resource tasks allows us to explore a setting where pre-training can have a significant impact.

Under the CS domain, we consider two tasks: ACL-ARC (Jurgens et al., 2018) and SCIERC (Luan et al., 2018). ACL-ARC is a 6-way citation intent classification task with 1688 labelled training examples. For SCIERC, the task is to classify the relations between entities in scientific articles. This task has 3219 labelled examples as training data. We choose CHEMPROT (Kringelum et al., 2016) as the classification task from the BIOMED domain. This task has 4169 labelled training

examples and the goal is to classify chemical-protein interactions. More details of these datasets can be found in Table 2 of Gururangan et al. (2020). Gururangan et al. (2020) evaluate against all 3 tasks and their available code served as a basis on which we built MT-TARTAN and META-TARTAN.

Model Details We use a pre-trained RoBERTa$_{base}$ (Liu et al., 2019) as the shared model base and implement each task as a separate multi-layer perceptron (MLP) head on top of this pre-trained base. As in Devlin et al. (2018), we pass the `[CLS]` token embedding from RoBERTa$_{base}$ to the MLP for classification.

Training Details For DAPT and TAPT, we download the available pre-trained model bases provided by Gururangan et al. (2020). To train thier corresponding classification heads, we follow the experimental setup described in Appendix B of Gururangan et al. (2020).

Performing end-task aware training introduces a few extra hyper-parameters. We fix the other hyper-parameters to those used in Gururangan et al. (2020). MT-TARTAN and META-TARTAN introduce joint training of a classification head for the end-task T^*. We experiment with batch sizes of 128, 256 and 512 for training this head. We try out learning rates in the set $\{10^{-3}, 10^{-4}, 10^{-5}\}$ and drop out rates of $\{0.1, 0.3\}$. For META-TARTAN since we are now learning the task weights, $\mathbf{w}$, we test out task weight learning rates in $\{10^{-1}, 5 \times 10^{-2}, 3 \times 10^{-2}, 10^{-2}\}$. Note that for all MT-TARTAN experiments we use equalized task weights $\frac{1}{|\mathbb{T}_{aux}|+1}$. A small grid-search over a handful of weight configurations did not yield significant improvement over the uniform task weighting. We use the Adam optimizer (Kingma & Ba, 2014) for all experiments.

As mentioned in section 3.3, we train as separate meta-classification head, ϕ^*, to estimate the validation meta-gradients. To estimate ϕ^*, we use batch sizes of $\{16, 32\}$ samples from T^*'s train set. We regularize the meta-head with l_2 weight decay and set the decay constant to 0.1. We use a learning rate 10^{-3} to learn the meta-head. We stop training ϕ^* after 10 gradient descent steps.

5 RESULTS AND DISCUSSION

In this section, we will discuss the results of comparing our models against DAPT and TAPT baselines.[1] Broadly, we demonstrate the effectiveness of end-task awareness as improving both performance and data-efficiency.

Domain	Task	RoBERTa	TAPT	MT-TARTAN	META-TARTAN
CS	ACL-ARC	$66.03_{3.55}$	$67.74_{3.68}$	$\mathbf{70.48}_{4.42}$	$70.08_{4.70}$
	SCIERC	$77.96_{2.96}$	$79.53_{1.93}$	$\mathbf{80.81}_{0.74}$	$\mathbf{81.48}_{0.82}$
BIOMED	CHEMPROT	$82.10_{0.98}$	$82.17_{0.65}$	$\mathbf{84.29}_{0.63}$	$\mathbf{84.49}_{0.50}$

Table 1: Comparison of our end-task aware approaches to RoBERTa and TAPT. All end-task aware approaches use TAPT as the auxiliary task. Reported results are test macro-F1, except for CHEMPROT, for which we report micro-F1, following Beltagy et al. (2019). We average across 10 random seeds, with standard deviations as subscripts. Statistically significant performance (p-value from permutation test < 0.05), is boldfaced. See A.2,A.5 for more details about this table

5.1 END-TASK AWARENESS IMPROVES OVER TASK-AGNOSTIC PRE-TRAINING

Table 1 compares TAPT to its end-task aware variants. Just as in Gururangan et al. (2020), we observe that performing task adaptive pre-training improves upon just fine-tuning RoBERTa. However, note that introducing the end-task by way of multi-tasking with the TAPT MLM objective leads to a significant improvement in performance. This improvement is consistent across the 3 tasks we evaluate against. We find that both MT-TARTAN and META-TARTAN achieve similar results in this setting. In Appendix A.4, we show that the gains from end-task awareness are not restricted to only text data; we observe similar trends for image classification.

---

[1]Our results are slightly different from those presented in Table 5 of Gururangan et al. (2020) in terms of absolute values but the trends observed there still hold here. We attribute these differences to (1) minor implementation differences, and (2) averaging performance over ten seeds instead of five as used in the original paper in order to more strongly establish statistical significance. We observe slightly lower performance on ACL-ARC and SCIERC tasks due to these changes and higher performance on CHEMPROT.

5.2 END-TASK AWARENESS IMPROVES DATA-EFFICIENCY

Gururangan et al. (2020) train DAPT on large amounts of in-domain data in order to achieve results that are competitive with TAPT. They use 7.55 billion tokens in the case of the BIOMED domain and 8.10 billion tokens for the CS domain. This is on average over $10^4 \times$ the size of the training data of our end-tasks of interest. The large amount of data required to train a competitive DAPT model represents a significant computational burden to the every-day practitioner. This begets the question: *are such large amounts of auxiliary data necessary for achieving good downstream performance?* To answer this, we train DAPT and its TARTAN version on variable amounts of data for both SCIERC and ACL-ARC tasks.

Figure 2: Compared to DAPT, TARTAN makes more efficient use of data. Large standard deviations in this setting are attributable to the heterogeneity of the CS domain data used in the DAPT setting and the fact that our tasks are low-resource.

TARTAN is more data-efficient than DAPT In Figure 2, we focus on training on a small fraction of available domain data $n = \{10^0, 10^1\} \times |\text{Train}|$ for the DAPT auxiliary task. Full domain data is $n' \approx 10^4 \times |\text{Train}|$. This relatively low auxiliary data regime represents a realistic setting that is akin to those encountered by everyday practitioners who are likely to be computationally constrained. As can be seen in Figure 2, on the ACL-ARC task, META-TARTAN matches the performance of DAPT when the sizes of the domain data and end-task data are of the same order (10^0). At this data size, META-TARTAN supersedes DAPT on the SCIERC task. When trained on $10 \times$ more auxiliary data, META-TARTAN supersedes DAPT in performance on both tasks. META-TARTAN establishes a new state-of-the-art result ($82.08_{1.19}$) on the SCIERC task. On the ACL-ARC task, META-TARTAN achieves $71.19_{4.88}$, which is close to DAPT's performance of $72.49_{3.28}$ using more than $10^3 \times$ auxiliary data. These results indicate that end-task awareness can improve data-efficiency and in this case, improvements are on the order of $1000 \times$.

Domain	Task	DAPT	DAPT+TAPT	MT-TARTAN	META-TARTAN
CS	ACL-ARC	$68.60_{2.62}$	$69.12_{5.76}$	$71.58_{1.65}$	$71.05_{2.37}$
	SCIERC	$76.44_{1.19}$	$77.62_{1.38}$	$\mathbf{81.02_{1.24}}$	$\mathbf{81.41_{1.70}}$
BIOMED	CHEMPROT	$80.76_{0.54}$	$78.22_{0.74}$	$\mathbf{83.77_{0.60}}$	$83.38_{0.89}$

Table 2: We use $n = 10 \times |\text{Train}|$, a small fraction the full domain data which is $> 10^4 \times |\text{Train}|$. TARTAN methods are trained on both DAPT and TAPT. We average performance across 10 seeds. Statistically significant performance is boldfaced. See A.2, A.6 for more details about this table.

TARTAN is more data-efficient than DAPT+TAPT Table 2 compares DAPT and DAPT+TAPT (DAPT followed by TAPT) to *-TARTAN which multi-task DAPT, TAPT and the end-task. MT-TARTAN and META-TARTAN significantly outperform DAPT and DAPT+TAPT in 2 of the tasks whilst giving higher average performance in the ACL-ARC task. We thus conclude that **end-task awareness allows us to get a greater performance boost out of the same amount of data**.

We explore the data efficiency of TARTAN methods even further by comparing the relatively data-poor versions of MT-TARTAN and META-TARTAN above ($n = 10 \times |\text{Train}|$) to the DAPT and DAPT+TAPT variants trained on all the available domain data ($n' \approx 10^4 \times |\text{Train}|$). We can see from Table 3 that for the CS domain, our end-task aware variants come close to (ACL-ARC) and even supersede (SCIERC) the end-task agnostic variants though trained with $\approx 1000 \times$ less data. For BIOMED domain (CHEMPROT task), increasing the amount of data drastically improves the performance of end-task agnostic variants compared to MT-TARTAN and META-TARTAN trained on much less data.

Zhang et al. (2020) show that different tasks exhibit sigmoid-like curves in terms of how much pre-training data is required to achieve good results before performance levels off. We contextualize Tables 2 and 3 within said work and posit that the CHEMPROT task intrinsically requires much more data (compared to our other tasks) before performance begins to improve appreciably.

Task	$\mathbf{DAPT}_{full}$	$\mathbf{+TAPT}_{full}$
ACL-ARC	$72.49_{3.28}$	$73.79_{1.75}$
SCIERC	$79.97_{2.11}$	$80.00_{1.08}$
CHEMPROT	$86.54_{1.05}$	$87.24_{0.81}$

Table 3: DAPT and DAPT+TAPT runs on all domain data available.

5.3 META-TARTAN MORE EFFECTIVELY UTILIZES OUT-OF-DISTRIBUTION AUXILIARY DATA OVER MT-TARTAN

TARTAN	ACL-ARC	SCIERC	CHEMPROT
MT	$69.27_{0.96}$	$81.53_{0.99}$	$80.26_{3.79}$
META	$\mathbf{71.19}_{4.88}$	$\mathbf{82.08}_{1.19}$	$\mathbf{82.31}_{0.75}$

Table 4: All methods use only DAPT as auxiliary task. We use $n = 10 \times |\text{Train}|$. We report averages across 3 random seeds. Best average task performance is bolded.

So far we have seen that leveraging TAPT (Table 1 uses TAPT only, 2 uses TAPT+DAPT) leads MT-TARTAN and META-TARTAN to perform similarly. The advantage of learning adaptive weights becomes more pronounced in the DAPT only setting. Note that whilst TAPT uses the end-task's own training data for masked language modelling, DAPT uses heterogeneous domain data whose impact on the end-task performance is less clear. Notice from Table 4 that when required to rely solely on domain data for auxiliary tasking, META-TARTAN improves performance over MT-TARTAN. We attribute META-TARTAN's improvement over MT-TARTAN on its ability to more flexibly adapt to incoming data of variable utility to the end-task.

5.4 TASK WEIGHTING STRATEGIES DISCOVERED BY META-LEARNING

Figure 3: It is important to use a separate classification head for computing meta-gradients. Using the same head as used for training results in a bias that up-weights the end-task and fails to effectively utilize the auxiliary tasks.

To illustrate the importance of the separate classification head ϕ^* for computing the meta-signal for the task weights (described in Section 3.3), we run META-TARTAN experiments with ACL-ARC as the end-task and DAPT as the auxiliary task. We compare using either a separate (ϕ^*) or the same (ϕ') classification head for calculating the meta-gradient. Figure 3 plots the task weightings learned in each setting during training. We can clearly see that using a separate head counteracts the pathological solution of down-weighting all tasks that are not T^* and as a result, improves performance: **a delta of 1.7 F1 points in this case**. The strategy discovered by META-TARTAN presents an interesting contrast to classical pre-training: whilst the initial phase of classical pre-training involves solely the auxiliary task, early in training, META-TARTAN up-weights the auxiliary task but does not fully zero out the end-task. Later in training, we see leveling off of weights instead of railing the end-task to 1 as in classical pre-training.

Next, we plot a similar graph for using both DAPT and TAPT across our three tasks in Figure 4. From the figure, it is apparent that META-TARTAN discovers similar task-weighting strategies across different end-tasks. This suggests that the MLM objective and META-TARTAN's strategy for learning task weights are generic enough to induce similar behaviours across tasks. In general, DAPT is significantly up-weighted compared to the end-task and TAPT. Note that the TAPT + ACL-ARC task weights (Figure 4) has the same approximate trajectory as ACL-ARC task weight in

Figure 4: The meta-learned task weightings show similar trajectories across different end-tasks.

Figure 3. It seems important to assign high weight to the task data but not necessarily all of it needs to go to the actual task loss. We hypothesize that the diversity in the domain data counteracts overfitting to the end-task data (all our tasks are low-resource) and results in DAPT being up-weighted.

6 RELATED WORK

Multi-task learning can be traced back to seminal work by Caruana (1995), Caruana (1997), and has since been the subject of a flourishing literature, recent surveys of which can be found in Ruder (2017) or Zhang & Yang (2021). In NLP, while initial work from Collobert & Weston (2008) already showed the benefits of multi-task learning, it has only recently become a central topic in the field, with the advent of multi-task benchmarks (Wang et al., 2018b; McCann et al., 2018).

Pre-training is a variation on the multi-task learning paradigm where a machine learning model is first trained on a generic (generally more data-rich) task, before being fine-tuned on an end task. In NLP this practice dates back to the use of pre-trained word embeddings (Turian et al., 2010; Mikolov et al., 2013) and later pre-trained encoders (Kiros et al., 2015; Dai & Le, 2015). Peters et al. (2018) and Howard & Ruder (2018) heralded a renaissance of pre-training before BERT (Devlin et al., 2018) and its many offshoots (Liu et al., 2019; Yang et al., 2019; Lewis et al., 2019) cemented it as the de facto standard for modern NLP.

As an idea, meta-learning, or "learning to learn", dates back to early work from Schmidhuber (1995); Thrun (1998). More relevant to our work however is a modern strand of the literature concerned with gradient-based meta-learning for solving bi-level optimization problems, first popularized by Finn et al. (2017) and followup work (Nichol et al., 2018; Rajeswaran et al., 2019) for few-shot learning. This method has transferred to a variety of applications such as architecture search (Liu et al., 2018), multilingual data weighting (Wang et al., 2020) and model poisoning (Kurita et al., 2020).

7 CONCLUSION

In this work, we advocate for a paradigm shift in the way we approach pre-training. We have motivated making pre-training more end-task aware when the end task is known in advance. Our work introduced two novel end-task aware training algorithms: End-task Aware Training via Multi-tasking (MT-TARTAN) and End-task Aware Training via Meta-learning (META-TARTAN). In Section 5, through experiments on 3 different datasets, we demonstrated the ability of our proposed algorithms to improve performance and data-efficiency over their end-task agnostic counterparts.

This work suggests several promising directions for future work. First, it would be interesting to see if end-task aware training of generalist models like BERT and RoBERTa from scratch result in improved accuracy and efficiency; both in terms of data and computation. Also, instead of learning coarse task level weights, can further performance improvements be achieved via finer-grained example level weighting as in Wang et al. (2020)? Can meta-learning algorithms like META-TARTAN enable more effective utilization of previously discarded (Aroca-Ouellette & Rudzicz, 2020) pre-training auxiliary tasks like Next Sentence Prediction (NSP) (Devlin et al., 2018)? We hope this work spurs conversation around these questions and many more.

8 ETHICS STATEMENT

Our work introduces new algorithms but leverages pre-existing datasets and models. Overall, this work inherits some of the risk of original work upon which it is implemented. Algorithms for continued training such as TAPT and DAPT necessitate per-task training of unsupervised objectives which result in corresponding green-house emissions due to energy consumption (Strubell et al., 2019). However, as shown in Sections 3 and 5, our new compute-efficient algorithms greatly increase the data efficiency of these algorithms, reducing these harms as well as the various harms associated with labor for data-collection (Jo & Gebru, 2020). Also, since our work is set in the context of pre-existing datasets and models (Section 4), we recognize that any ethical issues that have been revealed in these (such as bias (Bender et al., 2021) or privacy leakage (Carlini et al., 2021)) may also propagate to models trained using our work, and mitigation strategies such as Schick et al. (2021); Liang et al. (2021) may be necessary. Finally, there is a potential risk in META-TARTAN that leveraging a validation set for defining the meta-objective could amplifying bias that exists in this data split, although this is done indirectly through task weighting and hence we believe that this risk is small.

9 REPRODUCIBILITY STATEMENT

We pledge to release the source-code for this project to improve the ease of reproducibility of our results by the NLP and machine learning communities. In Section 4, we have specified details about datasets, training regimes and models to allow anyone who wishes to reproduce our results without our original source code to do so. Our discussion of the algorithmic and evaluation details can be found in Appendices A.1, A.3 and A.2. As we noted in 4, we build off of Gururangan et al. (2020)'s implementations which can be found at https://github.com/allenai/dont-stop-pretraining.

REFERENCES

Stéphane Aroca-Ouellette and Frank Rudzicz. On Losses for Modern Language Models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 4970–4981, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.403. URL https://www.aclweb.org/anthology/2020.emnlp-main.403.

Iz Beltagy, Kyle Lo, and Arman Cohan. Scibert: A pretrained language model for scientific text. *arXiv preprint arXiv:1903.10676*, 2019.

Emily M Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, pp. 610–623, 2021.

Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

Nicholas Carlini, Florian Tramèr, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Úlfar Erlingsson, Alina Oprea, and Colin Raffel. Extracting training data from large language models. In *USENIX Security Symposium*, 2021.

Rich Caruana. Learning many related tasks at the same time with backpropagation. In *Advances in neural information processing systems*, pp. 657–664, 1995.

Rich Caruana. Multitask learning. *Machine learning*, 28(1):41–75, 1997.

Ronan Collobert and Jason Weston. A unified architecture for natural language processing: Deep neural networks with multitask learning. In *Proceedings of the 25th international conference on Machine learning*, pp. 160–167, 2008.

Andrew M Dai and Quoc V Le. Semi-supervised sequence learning. *arXiv preprint arXiv:1511.01432*, 2015.

Lucio M. Dery, Yann Dauphin, and David Grangier. Auxiliary task update decomposition : the good, the bad and the neutral. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=1GTma8HwlYp.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1383–1392, 2018.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, pp. 1126–1135. PMLR, 2017.

Phillip I Good. Permutation, parametric and bootstrap tests of hypotheses: a practical guide to resampling methods for testing hypotheses. 2005.

Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A Smith. Don't stop pretraining: Adapt language models to domains and tasks. *arXiv preprint arXiv:2004.10964*, 2020.

Jeremy Howard and Sebastian Ruder. Universal language model fine-tuning for text classification. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 328–339, 2018.

Eun Seo Jo and Timnit Gebru. Lessons from archives: Strategies for collecting sociocultural data in machine learning. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, pp. 306–316, 2020.

David Jurgens, Srijan Kumar, Raine Hoover, Dan McFarland, and Dan Jurafsky. Measuring the evolution of a scientific field through citation frames. *Transactions of the Association for Computational Linguistics*, 6:391–406, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ryan Kiros, Yukun Zhu, Russ R Salakhutdinov, Richard Zemel, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. Skip-thought vectors. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015. URL https://proceedings.neurips.cc/paper/2015/file/f442d33fa06832082290ad8544a8da27-Paper.pdf.

Jens Kringelum, Sonny Kim Kjaerulff, Søren Brunak, Ole Lund, Tudor I Oprea, and Olivier Taboureau. Chemprot-3.0: a global chemical biology diseases mapping. *Database*, 2016, 2016.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Keita Kurita, Paul Michel, and Graham Neubig. Weight poisoning attacks on pre-trained models. *arXiv preprint arXiv:2004.06660*, 2020.

Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. Biobert: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240, 2020.

Mike Lewis, Yinhan Liu, Naman Goyal, Marjan Ghazvininejad, Abdelrahman Mohamed, Omer Levy, Ves Stoyanov, and Luke Zettlemoyer. Bart: Denoising sequence-to-sequence pre-training for natural language generation, translation, and comprehension. *arXiv preprint arXiv:1910.13461*, 2019.

Paul Pu Liang, Chiyu Wu, Louis-Philippe Morency, and Ruslan Salakhutdinov. Towards understanding and mitigating social biases in language models. In *International Conference on Machine Learning*, pp. 6565–6576. PMLR, 2021.

Renjie Liao, Yuwen Xiong, Ethan Fetaya, Lisa Zhang, KiJung Yoon, Xaq Pitkow, Raquel Urtasun, and Richard Zemel. Reviving and improving recurrent back-propagation. In *International Conference on Machine Learning*, pp. 3082–3091. PMLR, 2018.

Xingyu Lin, Harjatin Singh Baweja, George Kantor, and David Held. Adaptive auxiliary task weighting for reinforcement learning. *Advances in neural information processing systems*, 32, 2019.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. Darts: Differentiable architecture search. *arXiv preprint arXiv:1806.09055*, 2018.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Kyle Lo, Lucy Lu Wang, Mark Neumann, Rodney Kinney, and Dan S Weld. S2orc: The semantic scholar open research corpus. *arXiv preprint arXiv:1911.02782*, 2019.

Jonathan Lorraine, Paul Vicol, and David Duvenaud. Optimizing millions of hyperparameters by implicit differentiation. In *International Conference on Artificial Intelligence and Statistics*, pp. 1540–1552. PMLR, 2020.

Yi Luan, Luheng He, Mari Ostendorf, and Hannaneh Hajishirzi. Multi-task identification of entities, relations, and coreference for scientific knowledge graph construction. *arXiv preprint arXiv:1808.09602*, 2018.

Bryan McCann, Nitish Shirish Keskar, Caiming Xiong, and Richard Socher. The natural language decathlon: Multitask learning as question answering. *arXiv preprint arXiv:1806.08730*, 2018.

Luke Metz, Niru Maheswaranathan, Brian Cheung, and Jascha Sohl-Dickstein. Meta-learning update rules for unsupervised representation learning. *arXiv preprint arXiv:1804.00222*, 2018.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL `https://proceedings.neurips.cc/paper/2013/file/9aa42b31882ec039965f3c4923ce901b-Paper.pdf`.

Aviv Navon, Idan Achituve, Haggai Maron, Gal Chechik, and Ethan Fetaya. Auxiliary learning by implicit differentiation. *arXiv preprint arXiv:2007.02693*, 2020.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. *arXiv preprint arXiv:1803.02999*, 2018.

Matthew Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 2227–2237, 2018.

Matthew E Peters, Waleed Ammar, Chandra Bhagavatula, and Russell Power. Semi-supervised sequence tagging with bidirectional language models. *arXiv preprint arXiv:1705.00108*, 2017.

Aravind Rajeswaran, Chelsea Finn, Sham Kakade, and Sergey Levine. Meta-learning with implicit gradients. *arXiv preprint arXiv:1909.04630*, 2019.

Sebastian Ruder. An overview of multi-task learning in deep neural networks. *arXiv preprint arXiv:1706.05098*, 2017.

Timo Schick, Sahana Udupa, and Hinrich Schütze. Self-diagnosis and self-debiasing: A proposal for reducing corpus-based bias in nlp. *arXiv preprint arXiv:2103.00453*, 2021.

Jürgen Schmidhuber. On learning how to learn learning strategies. 1995.

Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. *arXiv preprint arXiv:1906.02243*, 2019.

Sebastian Thrun. Lifelong learning algorithms. In *Learning to learn*, pp. 181–209. Springer, 1998.

Joseph Turian, Lev-Arie Ratinov, and Yoshua Bengio. Word representations: A simple and general method for semi-supervised learning. In *Proceedings of the 48th Annual Meeting of the Association for Computational Linguistics*, pp. 384–394, Uppsala, Sweden, July 2010. Association for Computational Linguistics. URL `https://aclanthology.org/P10-1040`.

Alex Wang, Jan Hula, Patrick Xia, Raghavendra Pappagari, R Thomas McCoy, Roma Patel, Najoung Kim, Ian Tenney, Yinghui Huang, Katherin Yu, et al. Can you tell me how to get past sesame street? sentence-level pretraining beyond language modeling. *arXiv preprint arXiv:1812.10860*, 2018a.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018b.

Xinyi Wang, Hieu Pham, Paul Michel, Antonios Anastasopoulos, Jaime Carbonell, and Graham Neubig. Optimizing data usage via differentiable rewards. In *International Conference on Machine Learning*, pp. 9983–9995. PMLR, 2020.

Zirui Wang, Zihang Dai, Barnabás Póczos, and Jaime Carbonell. Characterizing and avoiding negative transfer. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 11293–11302, 2019.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Ruslan Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *arXiv preprint arXiv:1906.08237*, 2019.

Tianhe Yu, Saurabh Kumar, Abhishek Gupta, Sergey Levine, Karol Hausman, and Chelsea Finn. Gradient surgery for multi-task learning. *arXiv preprint arXiv:2001.06782*, 2020.

Yian Zhang, Alex Warstadt, Haau-Sing Li, and Samuel R Bowman. When do you need billions of words of pretraining data? *arXiv preprint arXiv:2011.04946*, 2020.

Yu Zhang and Qiang Yang. A survey on multi-task learning. *IEEE Transactions on Knowledge and Data Engineering*, 2021.

A APPENDIX

A.1 JUSTIFYING THE INTRODUCTION OF A META-HEAD

Proof. To arrive at Equation 7 we start with the closed form solution for $\nabla_{w_i}\mathcal{L}_{T^*}^{val}(\theta^*)$ and then introduce approximations in order to produce Equation 7. First, note that :

$$\frac{\partial\mathcal{L}_{T^*}^{val}(\theta^*(\mathbf{w}))}{\partial w_i} = \left(\nabla_\theta\mathcal{L}_{T^*}^{val}(\theta^*(\mathbf{w}))\right)^T \left(\nabla_{w_i}\theta^*(\mathbf{w})\right) \quad \texttt{[Chain rule]} \qquad (8)$$

To get $\nabla_{w_i}\theta^*(\mathbf{w})$ we invoke the Cauchy Implicit Function Theorem (IFT) as with Lorraine et al. (2020); Navon et al. (2020); Liao et al. (2018):

$$\nabla_{w_i}\theta^*(\mathbf{w}) = \left[\nabla_\theta^2\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right]^{-1}\left[\nabla_{w_i}\nabla_\theta\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right] \quad \texttt{[IFT]}$$

$$= \left[\nabla_\theta^2\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right]^{-1}\left[\nabla_{w_i}\nabla_\theta\left(w^*\mathcal{L}_{T^*}(\theta^*(\mathbf{w})) + \sum_{T_i\in\mathbb{T}_{\text{aux}}} w_i\mathcal{L}_{T_i}(\theta^*(\mathbf{w}))\right)\right]$$

$$= \left[\nabla_\theta^2\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right]^{-1}\left[\nabla_\theta\mathcal{L}_{T_i}(\theta^*(\mathbf{w}))\right] \quad \texttt{[Only terms with } w_i \texttt{ survive]}$$

Bringing it all together, we get :

$$\frac{\partial\mathcal{L}_{T^*}^{val}(\theta^*(\mathbf{w}))}{\partial w_i} = \left(\nabla_\theta\mathcal{L}_{T^*}^{val}(\theta^*(\mathbf{w}))\right)^T\left(\left[\nabla_\theta^2\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right]^{-1}\left[\nabla_\theta\mathcal{L}_{T_i}(\theta^*(\mathbf{w}))\right]\right) \qquad (9)$$

$\square$

Computing $\nabla_{w_i}\mathcal{L}_{T^*}^{val}(\theta^*)$ from Equation 9 is computationally unwieldy since we would not only have to optimize θ to convergence for every step of w_i but we would also have to invert the Hessian of a typically large model. Our middle ground between Equations 9 and 6 (Equation 7) makes use of the following approximations:

- We approximate the inverse Hessian with the identity. This approximation is not new; we follow previous work like Lorraine et al. (2020)(Table 3) who explore the use of this approximation because of computational efficiency.

$$\left[\nabla_\theta^2\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right]^{-1} = \lim_{i\to\infty}\sum_{j=0}^{i}\left(\mathbf{I} - \nabla_\theta^2\mathcal{L}_{\text{total}}(\theta^*(\mathbf{w}))\right)^j \approx \mathbf{I}$$

  We are assuming the contribution of terms with $i > 0$ are negligible.

- Instead of training the whole network to convergence, at each time-step, we fix the body of the network and train a special head ϕ^* to convergence on a small batch of end-task training data. We then use $[\theta_{\text{body}}; \phi^*]$ as a proxy for θ^*. This is a computationally feasible work-around to training all of θ to convergence to get a single step gradient estimate. Especially in the continued pre-training setting where a pre-trained *generalist* model like BERT is used as θ_{body}, this approximation is reasonable. To our knowledge, we are the first to suggest this approximation.

$$\nabla_\theta\mathcal{L}_{T^*}^{val}(\theta^*) \to \nabla_\theta\mathcal{L}_{T^*}^{val}([\theta_{\text{body}}; \phi^*])$$

- Above, we have approximated $\theta^* = [\theta_{\text{body}}; \phi^*]$. Since ϕ^* is only used to evaluate end-task (T^*) validation data, it means θ remains unchanged with respect to the training data for task T_i. Thus $\nabla_\theta\mathcal{L}_{T_i}([\theta_{\text{body}}; (\phi^*, \ldots, \phi^i)]) = \nabla_\theta\mathcal{L}_{T_i}([\theta_{\text{body}}; \phi^i]) = \nabla_\theta\mathcal{L}_{T_i}(\theta)$

Bringing it all together, we get Equation 7, repeated here:

$$\frac{\partial\mathcal{L}_{T^*}^{val}(\theta^*(\mathbf{w}))}{\partial w_i} \approx \left(\nabla_\theta\mathcal{L}_{T_i}\right)^T\left(\nabla_\theta\mathcal{L}_{T^*}^{val}([\theta_{\text{body}}; \phi^*]_t)\right)$$

A.2 CALCULATING P-VALUES FROM PERMUTATION TEST

We used the permutation test (Good, 2005; Dror et al., 2018) to test for statistical significance. For each test, we generate 10000 permutations to calculate significance level. This is sufficient to converge to a stable p-value without being a computational burden. We chose this over the common student t-test because :

1. We have only 10 runs per algorithm and permutation tests are more robust at low sample size

2. Permutation test is assumption free. Student t-tests assume that the samples are normally distributed

3. Permutation test is robust to variance in the samples, so even though error-bars can overlap, we still establish significant differences in the samples. Variance in our results is expected due to small dataset sizes of end-tasks.

A.3 ALGORITHM FOR META-TARTAN

Algorithm 1: End-task Aware Training via Meta-learning (META-TARTAN)

Require: T^*, $\mathbf{T}_{\text{aux}}$: End-task, Set of auxiliary pre-training tasks
Require: η, β_1, β_2: Step size hyper-parameters
Initialize :
    Pre-trained RoBERTa as shared network body, θ_{body}
    Task weightings: $w^*, w_i = \frac{1}{|\mathbf{T}_{\text{aux}}|+1}$
Randomly initialize :
    end-task head as ϕ'
    meta head for end-task as ϕ^*
    task head, ϕ^i, for each $T_i \in \mathbf{T}_{\text{aux}}$
while *not done* **do**

    $B_{\text{tr}}^* \sim T_{\text{train}}^*$ // Sample a batch from end-task

    $g_\theta^*, g_\phi^* \leftarrow [\nabla_\theta, \nabla_{\phi'}]\left(\mathcal{L}_{T^*}(\theta, \phi', B_{\text{tr}}^*)\right)$ // Get end-task grads

    $g_\theta^i, g_\phi^i \leftarrow [\nabla_\theta, \nabla_{\phi^i}]\left(\mathcal{L}_{T_i}(\theta, \phi^i, B_i)\right)$ // Get task grads. $\forall i \in [n], \ B_i \sim T_i$

    // Learn a new meta head
    $\phi^* \leftarrow$ estimate_meta_head$(B_{\text{tr}}^*, \beta_2, \theta, \phi^*)$ // $B_{\text{tr}}^* \sim T_{\text{train}}^*$
    $g_{meta}^* \leftarrow \nabla_\theta \mathcal{L}_{T^*}(\theta, \phi^*, B_{\text{val}}^*)$ // $B_{\text{val}}^* \sim T_{\text{val}}^*$
    // Update task weightings
    $w^* \leftarrow w^* + \eta \cos(g_{meta}^*, g_\theta^*)$
    $w_i \leftarrow w_i + \eta \cos(g_{meta}^*, g_\theta^i)$
    // Update task parameters
    $\alpha^*, \alpha_1, \ldots, \alpha_{|\mathbf{T}_{\text{aux}}|} = \text{softmax}(w^*, w_1, \ldots, w_{|\mathbf{T}_{\text{aux}}|})$
    Update $\theta_{\text{body}} \leftarrow \theta_{\text{body}} - \beta_1\left(\alpha^* g_\theta^* + \sum_i \alpha_i g_\theta^i\right)$

    Update $\left(\phi_i \leftarrow \phi_i - \beta_2 g_\phi^i\right), \left(\phi' \leftarrow \phi' - \beta_2 g_\phi^*\right)$

end
Result : θ, ϕ'

A.4 VISION EXPERIMENTS

We validate that the gains from end-task Aware Training are not siloed to only learning from text. We conduct an experiment comparing end-task aware training on images to its end-task agnostic variant. We use the Cifar100 dataset (Krizhevsky et al., 2009). We use the Medium-Sized Mammals superclass (one of the 20 coarse labels) as our main task whilst the other 19 super classes are used as auxiliary data. Our primary task is thus a 5-way classification task of images different types of

Method	Medium-Sized Mammals
Regular (Task-Agnostic) Pre-training	$46.7_{2.2}$
MT-TARTAN	$51.3_{1.2}$
META-TARTAN	$\mathbf{52.3_{3.8}}$

Table 5: We report averages across 3 random seeds. Best average task accuracy is bolded.

medium-sized mammals whilst whilst the remaining 95 classes are grouped into a single auxiliary task.

As can be seen from Table 5, being end-task aware improves over task agnostic pre-training. We find that, again, when our auxiliary task consist of solely domain data and no task data, META-TARTAN performs better than MT-TARTAN (as measured by averaged performance).

A.5 FULL TAPT TABLE WITH SIGNIFICANCE LEVELS

We repeat Table 1 and provide details about levels of statistical signifance.

Task	TAPT	MT-TARTAN	$p-$values	META-TARTAN	$p-$values
ACL-ARC	$67.74_{3.68}$	$\mathbf{70.48_{4.42}}$	0.040	$70.08_{4.70}$	0.069
SCIERC	$79.53_{1.93}$	$\mathbf{80.81_{0.74}}$	0.038	$\mathbf{81.48_{0.82}}$	0.005
CHEMPROT	$82.17_{0.065}$	$\mathbf{84.29_{0.63}}$	0.000	$\mathbf{84.49_{0.50}}$	0.000

Table 6: Duplicate of Table 1. Significance levels as computed from the permutation test. All $p-$values are relative to the TAPT column. Statistically significant performance(p-value from permutation test < 0.05), is boldfaced

A.6 FULL DAPT/DAPT+TAPT TABLE

We repeat Table 3 and provide details about levels of statistical signifance.

Task	DAPT	DAPT+TAPT	MT-TARTAN	p-values	META-TARTAN	p-values
ACL-ARC	$68.60_{2.62}$	$69.12_{5.76}$	$71.58_{1.65}$	0.110	$71.05_{2.37}$	0.174
SCIERC	$76.44_{1.19}$	$77.62_{1.38}$	$\mathbf{81.02_{1.24}}$	0.000	$\mathbf{81.41_{1.70}}$	0.000
CHEMPROT	$80.76_{0.54}$	$78.22_{0.74}$	$\mathbf{83.77_{0.60}}$	0.000	$\mathbf{83.38_{0.89}}$	0.000

Table 7: Duplicate of Table 2. Significance levels as computed from the permutation test. All $p-$values are relative to $\max\big(\text{DAPT}, \text{DAPT} + \text{TAPT}\big)$. Statistically significant performance(p-value from permutation test < 0.05), is boldfaced