A Comparative Study of Unsupervised Adversarial Domain Adaptation Strategies in Multiple-instance Learning Frameworks for Digital Pathology

Abstract

Performance of state-of-the-art deep learning methods is often impacted when evaluated on data coming from unseen acquisition settings, hindering their approval by the regulatory agencies and incorporation to the clinic. In recent years, several techniques have been proposed for improving the generalizability of models by using the target data and their corresponding ground truths. Some of those approaches have been adopted in histopathology, however they either focus on pixel-level predictions or simple tile level classification tasks with or without target labels. In this work, we investigate adversarial strategies in weakly supervised learning frameworks in digital pathology domain without access to the target labels, thereby strengthening the generalizability to unlabeled target domains. We evaluate several strategies on Camelyon dataset for metastatic tumor detection tasks and show that some methods can improve the average F1-score over 10% for the target domain.

1. Introduction

Despite the popularity of computer aided diagnosis tools for Digital Pathology (DP), widespread use of these algorithms is hampered by the inherent variation between images of diverse origin (Howard et al., 2021) (in staining, thickness, patient demographics, etc.) known as *domain shift*. Therefore, a strategy that enables us to build more generalizable models is desired. Among different methods, Marini et al. (2022) propose a Domain Adversarial Neural Network (DANN) (Ganin et al., 2015) to tackle stain heterogeneity with an understanding of domain purely based on color. Also the Conditional Domain Adversarial Network (CDAN) proposed by Long et al. (2017) facilitates domain alignment by utilizing the discriminative information offered by main-task classifier predictions.

In this paper, we focus on Unsupervised Domain Adaptation (UDA) and address the domain shift resulting from scanner variations for the task of metastatic tumor detection in a weakly supervised setting. Particularly, we explore DANN, CDAN and the effect of changing the position of the domain discriminator in attention MIL (Ilse et al., 2018) as well as transMIL (Shao et al.) networks.

2. Methods and Experimentations

We propose to adapt MIL models by combining the discriminators ($\mathcal{G}$) in DANN and CDAN pipelines at two different locations: 1) after a shallow encoder (loc_i), where $\mathcal{G}$ would receive *instance-level* sample as input. In this way, the feature alignment between domains will be

provided by a shallow encoder that will map the embeddings from the frozen encoder into an overlapping latent space; 2) after the embedding aggregation step (loc_b), in which $\mathcal{G}$ is positioned after the attention mechanisms in attention-MIL or final mean pooling of patch tokens after the last transformer layer in TransMIL. Therefore, the domain alignment falls on aggregated instances passed to the final slide-level classifier. The adapted MIL pipeline corresponding to DANN and CDAN are visualized for each of the integration locations in Figure 1(a) and 1(b).

Figure 1: Overview of the two UDA approaches. a) shows loc_b and b) loc_i.

2.1. Experimental Setup

The combination of Camelyon16 and Camelyon17 publicly available datasets (Litjens et al., 2018), was used for the experiments. This data collection contains 1399 WSI of lymph nodes stained with Hematoxylin and Eosin, from three different scanners, and five medical centers, and including both metastatic and healthy samples.

Scanner 1 (S1) data (from three different hospitals digitized by the same scanner) was used as the source ($N_s = 544$), while Scanner 2 (S2) data (from two hospitals) and Scanner 3 (S3) data (from one facility) comprised the target dataset ($N_{t_2} = 253$ and $N_{t_3} = 100$), on which the model is to improve its generalizability. The source dataset was partitioned into 5 non-overlapping subsets (each 20%) stratified by medical center and tumor label, for a 5-fold Cross-Validation (CV). The UDA training used S2 as target and was evaluated on S3.

10,000 tiles at a magnification of 40× were extracted from each WSI. Image patches were stain normalized using Tellez et al. (2019) to account for stain variation from multiple acquisition centers. A pre-trained ResNet-50 (He et al., 2016) model on DP images (via BYOL self-supervised learning strategy (Grill et al., 2020)) was used to extract intermediate features and the backbone weights remained frozen for computational efficiency. The attention network in attention MIL had 5 fully connected layers, followed by batch normalization and dropout (p=0.5). The transformer used Nystrom approximation (Xiong et al., 2021) for Self-Attention (SA) with 3 layers and 8 heads in each multi-head SA block. The main-task classifier had 2 fully connected layers. The discriminator had 3 layers in CDAN and 2 in DANN. ReLU is used as activation function. The Adam optimizer with an equal learning rate of 10^{-3} for the discriminator and the main-task networks was used.

The adversarial contribution to the updates of the network parameters preceding the domain discriminator $\mathcal{G}$ was defined as $\lambda = \frac{2}{1+\exp(-\gamma p)} - 1$, with $p \in (0, 1]$ as the relative progress of the training.

To compare the proposed UDA strategies, three baselines were established: 1) *source only* (S1); 2) *target only* (S2); and 3) *balanced data* (a combination of source and target data which required new stratified dataset). The target labels are not used in our UDA strategies and were only employed to settle the baselines and evaluating the adapted models. The model selection was based on macro-average validation F1-score. In addition to the baseline results based on CV, performance on S3 was obtained by the model with the average F1 closest to scanner 2 in the CV experiments

3. Results and Conclusion

The summary of the results can be found in Table 1. All UDA methods successfully improve the performance on the target, which means they are generally able to retain domain agnostic features. The gap for the F1-score is reduced by at least 10% for S2. After UDA, the models still generalize to S3. There exists a more severe performance gap for S2 than S3. One possible reason, beyond any persisting staining differences after stain normalization, is the slide thickness as explained by our pathologist. Moreover, the visualization of attention heatmaps has shown that using UDA is effective to reduce the bias towards lighter coloring that may not be relevant to the network outcome.

Table 1: Results of different UDA strategies on CAMELYON dataset, 5-fold CV [a]

MIL	Method / Experiment	S1 avg. F1	S1 $\to$ S2[b] avg. F1	S1 $\to$ S2[b] $F1_{S1} - F1_{S2}(\downarrow)$	S3 avg. F1
Attention MIL	*Balanced data*	85.2(1.0)	80.4(3.2)	-	87.8(2.2)
	Source only	86.9(3.6)	68.4(2.1)	19.2(3.9)	83.0
	DANN @ loc_i	83.6(2.6)	74.0(6.3)	9.6(2.0)	82.6
	CDAN @ loc_b	86.2(6.2)	80.2(3.0)	6.0(3.2)	85.2
	DANN @ loc_b	**87.6(4.3)**	**81.4(3.2)**	6.2(1.1)	86.0
	CDAN @ loc_i	83.0(3.2)	79.4(3.0)	3.6(1.2)	83.4
	Target only (S2)	-	-	88.4(6.1)	-
TransMIL	*Balanced data*	88.5	85.1	-	92.9
	Source only	86.3(4.2)	67.6(7.8)	18.7(3.6)	84.0
	DANN @ loc_b	85.6(3.6)	79.3(2.2)	6.3(1.5)	85.8
	CDAN @ loc_b	86.4(2.1)	79.0(2.5)	7.0(0.4)	85.0
	Target only (S2)	-	90.5(5.3)	-	-

[a] All values are percentages (%). Standard deviation in brackets. Best in bold, second best underlined;
[b] Arrow represents direction of the adaptation.

None of the UDA methods clearly outperformed the others, possibly due to limited bandwidth for domain alignment with a frozen backbone. More complex methods with a higher number of hyperparameters may be necessary. UDA resulted in a slight decline in source domain performance that can be addressed by continual learning methods such as Bándi et al. (2022).

References

Péter Bándi, Maschenka C. A. Balkenhol, Marcory van Dijk, Bram van Ginneken, Jeroen van der Laak, and Geert J. S. Litjens. Domain adaptation strategies for cancer-independent detection of lymph node metastases. *ArXiv*, abs/2207.06193, 2022.

Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *Advances in Computer Vision and Pattern Recognition*, 17:189–209, 5 2015. ISSN 21916594. doi: 10.48550/arxiv.1505.07818.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Moham-mad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent: A new approach to self-supervised learning, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

Frederick M. Howard, James Dolezal, Sara Kochanny, Jefree Schulte, Heather Chen, Lara Heij, Dezheng Huo, Rita Nanda, Olufunmilayo I. Olopade, Jakob N. Kather, Nicole Cipriani, Robert L. Grossman, and Alexander T. Pearson. The impact of site-specific digital histology signatures on deep learning model accuracy and bias. *Nature Communications*, 12(1), July 2021. doi: 10.1038/s41467-021-24698-1.

Maximilian Ilse, Jakub Tomczak, and Max Welling. Attention-based deep multiple instance learning. In Jennifer Dy and Andreas Krause, editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 2127–2136. PMLR, 10–15 Jul 2018.

Geert Litjens, Peter Bandi, Babak Ehteshami Bejnordi, Oscar Geessink, Maschenka Balkenhol, Peter Bult, Altuna Halilovic, Meyke Hermsen, Rob van de Loo, Rob Vogels, Quirine F Manson, Nikolas Stathonikos, Alexi Baidoshvili, Paul van Diest, Carla Wauters, Marcory van Dijk, and Jeroen van der Laak. 1399 h&e-stained sentinel lymph node sections of breast cancer patients: the CAMELYON dataset. *GigaScience*, 7(6), May 2018. doi: 10.1093/gigascience/giy065.

Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I. Jordan. Conditional adversarial domain adaptation, 2017.

Niccoì O Marini, Manfredo Atzori, Sebastian Otálora, Stephane Marchand-Maillet, and Henning Müller. He-adversarial network: a convolutional neural network to learn stain-invariant features through hematoxylin eosin regression. 1 2022. doi: 10.48550/arxiv. 2201.06329.

Zhuchen Shao, Hao Bian, Yang Chen, Yifeng Wang, Jian Zhang, Xiangyang Ji, and yong-bing zhang. TransMIL: Transformer based correlated multiple instance learning for whole slide image classification. In M. Ranzato, A. Beygelzimer, Y. Dauphin, P.S. Liang, and

J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, pages 2136–2147. Curran Associates, Inc.

David Tellez, Geert Litjens, Péter Bándi, Wouter Bulten, John-Melle Bokhorst, Francesco Ciompi, and Jeroen van der Laak. Quantifying the effects of data augmentation and stain color normalization in convolutional neural networks for computational pathology. *Medical Image Analysis*, 58:101544, 2019. ISSN 1361-8415. doi: https://doi.org/10.1016/j.media.2019.101544.

Yunyang Xiong, Zhanpeng Zeng, Rudrasis Chakraborty, Mingxing Tan, Glenn Fung, Yin Li, and Vikas Singh. Nyströmformer: A nystöm-based algorithm for approximating self-attention. *Proc. Conf. AAAI Artif. Intell.*, 35(16):14138–14148, May 2021.