Sample-Efficient Reinforcement Learning Is Feasible for Linearly Realizable MDPs with Limited Revisiting

Abstract

Low-complexity models such as linear function representation play a pivotal role in enabling sample-efficient reinforcement learning (RL). The current paper pertains to a scenario with value-based linear representation, which postulates the linear realizability of the optimal Q-function (also called the "linear $Q^\star$ problem"). While linear realizability alone does not allow for sample-efficient solutions in general, the presence of a large sub-optimality gap is a potential game changer, depending on the sampling mechanism in use. Informally, sample efficiency is achievable with a large sub-optimality gap when a generative model is available, but is unfortunately infeasible when we turn to standard online RL settings.

In this paper, we make progress towards understanding this linear $Q^\star$ problem by investigating a new sampling protocol, which draws samples in an online/exploratory fashion but allows one to backtrack and revisit previous states in a controlled and infrequent manner. This protocol is more flexible than the standard online RL setting, while being practically relevant and far more restrictive than the generative model. We develop an algorithm tailored to this setting, achieving a sample complexity that scales polynomially with the feature dimension, the horizon, and the inverse sub-optimality gap, but not the size of the state/action space. Our findings underscore the fundamental interplay between sampling protocols and low-complexity structural representation in RL.

1 Introduction

Emerging reinforcement learning (RL) applications necessitate the design of sample-efficient solutions in order to accommodate the explosive growth of problem dimensionality. Given that the state space and the action space could both be unprecedentedly enormous, it is often infeasible to request a sample size exceeding the fundamental limit set forth by the ambient dimension in the tabular setting, which enumerates all the possible combinations of state-action pairs. As a result, the quest for sample efficiency cannot be achieved in general without exploiting proper low-complexity structures underlying the problem of interest.

Among the studies of low-complexity models for RL, linear function approximation has attracted a flurry of recent activity, mainly due to the promise of dramatic dimension reduction in conjunction with its mathematical tractability (see, e.g., Bertsekas and Tsitsiklis (1995); Wen and Van Roy (2017); Yang and Wang (2019); Jin et al. (2020); Du et al. (2020a) and the references therein). Two families of linear function approximation merit particular attention, which we single out below. Here and throughout, we concentrate on a finite-horizon Markov decision process (MDP), and denote by $\mathcal{S}$, $\mathcal{A}$ and H its state space, action space, and horizon, respectively.

- *Model-based linear representation.* Yang and Wang (2019); Jin et al. (2020); Yang and Wang (2020) studied a stylized scenario when both the probability transition kernel and the reward function of the MDP can be linearly parameterized. This type of MDPs is commonly referred to as linear MDPs. Letting $P_h(\cdot \mid s, a)$ denote the transition probability from state s when action a is executed at time step h, the linear MDP model postulates the existence of a set of predetermined d-dimensional feature vectors $\{\varphi_h(s, a) \in \mathbb{R}^d\}$ and a collection of unknown parameter matrices $\{\mu_h \in \mathbb{R}^{d \times |\mathcal{S}|}\}$ such that

$$\forall (s, a) \in \mathcal{S} \times \mathcal{A} \text{ and } 1 \leq h \leq H : \qquad P_h(\cdot \mid s, a) = \big(\varphi_h(s, a)\big)^\top \mu_h. \tag{1}$$

  Similar assumptions are imposed on the reward function as well. In other words, the linear MDP model posits that the probability transition matrix is low-rank (with rank at most d) with the column space known *a priori*, which forms the basis for sample size saving in comparison to the unstructured setting.

- *Value-based linear realizability.* Rather than relying on linear embedding of the model specification (namely, the transition kernel and the reward function), another class of linear representation assumes that the action-value function (or Q-function) can be well predicted by linear combinations of known feature vectors $\{\varphi_h(s, a) \in \mathbb{R}^d\}$. A concrete framework of this kind assumes linear realizability of the optimal Q-function (denoted by $Q_h^\star$ at time step h from now on), that is, there exist some unknown vectors $\{\theta_h^\star \in \mathbb{R}^d\}$ such that

$$Q_h^\star(s, a) = \big\langle \varphi_h(s, a), \theta_h^\star \big\rangle \tag{2}$$

  holds for any state-action pair (s, a) and any step h. It is self-evident that this framework seeks to represent the optimal Q-function — which is an $|\mathcal{S}||\mathcal{A}|H$-dimensional object — via H parameter vectors each of dimension d. Throughout this work, an MDP obeying this condition is said to be *an MDP with linearly realizable optimal Q-function*, or more concisely, *an MDP with linear $Q^\star$*.

1.1 Sample size barriers with linearly realizable $Q^\star$

The current paper focuses on MDPs with linearly realizable optimal Q-function $Q^\star$. In some sense, this is arguably the weakest assumption one can hope for, otherwise, a linear function approximation should not be adopted in the first place. In stark contrast to linear MDPs that allow for sample-efficient RL (in the sense that the sample complexity is almost independent of $|\mathcal{S}|$ and $|\mathcal{A}|$ but instead depends only polynomially on d, H and possibly the sub-optimality gap Δ_{gap}), MDPs with linear $Q^\star$ do not admit a similar level of sample efficiency in general. To facilitate discussion, we summarize key existing results for a couple of settings; an expanded set of related works are discussed in the supplementary material. Here and below, the notation $f(d) = \Omega(g(d))$ means $f(d)$ is at least on the same order as $g(d)$ when d tends to infinity.

- *Sample inefficiency under a generative model.* Even when a generative model or a simulator is available — so that the learner can freely query an arbitrary state-action pair to draw samples from (Kearns and Singh, 1999) — one can find a hard MDP instance in this class that requires at least $\min\big\{\exp(\Omega(d)), \exp(\Omega(H))\big\}$ samples regardless of the algorithm in use (Weisz et al., 2021b).

- *Sample efficiency with a sub-optimality gap under a generative model.* The aforementioned sample size barrier can be alleviated if, for each state, there exists a sub-optimality gap Δ_{gap} between the value under the optimal action and that under any sub-optimal action. As asserted by Du et al. (2020a, Appendix C), a sample size that scales polynomially in d, H and $1/\Delta_{\mathsf{gap}}$ is sufficient to identify the optimal policy, assuming access to the generative model.

- *Sample inefficiency with a large sub-optimality gap in online RL.* Turning to the standard episodic online RL setting (so that in each episode, the learner is given an initial state and executes the MDP for H steps to obtain a sample trajectory), sample-efficient algorithms are, much to our surprise, infeasible even in the presence of a large sub-optimality gap. As has been formalized in Wang et al. (2021), it is possible to construct a hard MDP instance with a constant sub-optimality gap that cannot be solved without $\min\big\{\exp(\Omega(d)), \exp(\Omega(H))\big\}$ samples.

In conclusion, the linear $Q^\star$ assumption, while succinctly capturing the low-dimensional structure, still presents an undesirable hurdle for RL. The sampling mechanism commonly studied in standard RL formulations precludes sample-efficient solutions even when a favorable sub-optimality gap comes into existence.

1.2 Our contributions

Having observed the exponential separation between the generative model and standard online RL when it comes to the linear $Q^\star$ problem, one might naturally wonder whether there exist practically relevant sampling mechanisms — more flexible than standard online RL yet more restrictive than the generative model — that promise substantial sample size reduction. This motivates the investigation of the current paper, as summarized below.

- *A new sampling protocol: sampling with state revisiting.* We investigate a flexible sampling protocol that is built upon classical online/exploratory formalism but allows for *state revisiting* (detailed in Algorithm 1). In each episode, the learner starts by running the MDP for H steps, and is then allowed to revisit any previously visited state and re-run the MDP from there. The learner is allowed to revisit states for an arbitrary number of times, although executing this feature too often might incur an overly large sampling burden. This sampling protocol accommodates several realistic scenarios; for instance, it captures the "save files" feature in video games that allows players to record player progress and resume from the save points later on.

- *A sample-efficient algorithm.* Focusing on the above sampling protocol, we propose a value-based method — called LinQ-LSVI-UCB — adapted from the LSVI-UCB algorithm (Jin et al., 2020). The algorithm implements the optimism principle in the face of uncertainty, while harnessing the knowledge of the sub-optimality gap to determine whether to backtrack and revisit states. The proposed algorithm provably achieves a sample complexity that scales polynomially in the feature dimension d, the horizon H, and the inverse sub-optimality gap $1/\Delta_{\mathsf{gap}}$, but is otherwise independent of the size of the state space and the action space.

2 Model and assumptions

In this section, we present precise problem formulation, notation, as well as key assumptions. Here and throughout, we denote by $|\mathcal{S}|$ the cardinality of a set $\mathcal{S}$, and adopt the notation $[n] := \{1, \cdots, n\}$.

2.1 Basics of Markov decision processes

Finite-horizon MDP. The focus of this paper is the setting of a finite-horizon MDP, as represented by the quintuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, \{P_h\}_{h=1}^H, \{r_h\}_{h=1}^H, H)$ (Agarwal et al., 2019). Here, $\mathcal{S} := \{1, \cdots, |\mathcal{S}|\}$ represents the state space, $\mathcal{A} := \{1, \cdots, |\mathcal{A}|\}$ denotes the action space, H indicates the time horizon of the MDP, P_h stands for the probability transition kernel at time step $h \in [H]$ (namely, $P_h(\cdot \,|\, s, a)$ is the transition probability from state s upon execution of action a at step h), whereas $r_h : \mathcal{S} \times \mathcal{A} \to [0, 1]$ represents the reward function at step h (namely, we denote by $r_h(s, a)$ the immediate reward received at step h when the current state is s and the current action is a). It is assumed throughout that all rewards $\{r_h(s, a)\}$ are deterministic and reside within $[0, 1]$.

Policy, value function, and Q-function. We let $\pi = \{\pi_h\}_{1 \le h \le H}$ represent a policy or action selection rule. For each time step h, π_h represents a deterministic mapping from $\mathcal{S}$ to $\mathcal{A}$, namely, action $\pi_h(s)$ is taken at step h if the current state is s. The value function associated with policy π at step h is then defined as the cumulative reward received between steps h and H, namely,

$$\forall (s, h) \in \mathcal{S} \times [H]: \qquad V_h^\pi(s) := \mathbb{E}\left[\sum_{t=h}^H r_t(s_t, a_t) \,\Big|\, s_t = s\right]. \tag{3}$$

Here, the expectation is taken over the randomness of an MDP trajectory $\{s_t\}_{t=h}^H$ induced by policy π (namely, $a_t = \pi_t(s_t)$ and $s_{t+1} \sim P(\cdot \,|\, s_t, a_t)$ for any $h \le t \le H$). Similarly, the action-value function (or Q-function) associated with policy π is defined as

$$\forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]: \qquad Q_h^\pi(s, a) := \mathbb{E}\left[\sum_{t=h}^H r_t(s_t, a_t) \,\Big|\, s_h = s, a_h = a\right], \tag{4}$$

which resembles the definition (3) except that the action at step h is frozen to be a. Our normalized reward assumption (i.e., $r_h(s, a) \in [0, 1]$) immediately leads to the trivial bounds

$$\forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]: \qquad 0 \le V_h^\pi(s) \le H \qquad \text{and} \qquad 0 \le Q_h^\pi(s, a) \le H. \tag{5}$$

A recurring goal in reinforcement learning is to search for a policy that maximizes the value funtion and the Q-function. For notational simplicity, we define the optimal value function $V^\star = \{V_h^\star\}_{1 \leq h \leq H}$ and optimal Q-function $Q^\star = \{Q_h^\star\}_{1 \leq h \leq H}$ respectively as follows

$$\forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]: \qquad V_h^\star(s) := \max_\pi V_h^\pi(s) \qquad \text{and} \qquad Q_h^\star(s, a) := \max_\pi Q_h^\pi(s, a),$$

with the optimal policy (i.e., the one that maximizes the value function) represented by $\pi^\star = \{\pi_h^\star\}_{1 \leq h \leq H}$.

2.2 Key assumptions

Linear realizability of $Q^\star$. In order to enable significant reduction of sample complexity, it is crucial to exploit proper low-dimensional structure of the problem. This paper is built upon linear realizability of the optimal Q-function $Q^\star$ as follows.

Assumption 1. *Suppose that there exist a collection of pre-determined feature maps*

$$\varphi = (\varphi_h)_{1 \leq h \leq H}, \qquad \varphi_h : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^d \tag{6}$$

and a set of unknown vectors $\theta_h^\star \in \mathbb{R}^d$ ($1 \leq h \leq H$) such that

$$\forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]: \qquad Q_h^\star(s, a) = \langle \varphi_h(s, a), \theta_h^\star \rangle. \tag{7}$$

In addition, we assume that

$$\forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]: \qquad \|\varphi_h(s, a)\|_2 \leq 1 \quad \text{and} \quad \|\theta_h^\star\|_2 \leq 2H\sqrt{d}. \tag{8}$$

In other words, we assume that $Q^\star = \{Q_h^\star\}_{1 \leq h \leq H}$ can be embedded into a d-dimensional subspace encoded by φ, with $d \leq |\mathcal{S}||\mathcal{A}|$. In fact, we shall often view d as being substantially smaller than the ambient dimension $|\mathcal{S}||\mathcal{A}|$ in order to capture the dramatic degree of potential dimension reduction. It is noteworthy that linear realizability of $Q^\star$ in itself is a considerably weaker assumption compared to the one commonly assumed for linear MDPs (Jin et al., 2020) (which assumes $\{P_h\}_{1 \leq h \leq H}$ and $\{r_h\}_{1 \leq h \leq H}$ are all linearly parameterized). The latter necessarily implies the former, while in contrast the former by no means implies the latter. Additionally, we remark that the assumption (8) is compatible with what is commonly assumed for linear MDPs; see, e.g., Jin et al. (2020, Lemma B.1) for a reasoning of this bound.

Sub-optimality gap. As alluded to previously, another metric that comes into play in our theoretical development is the sub-optimality gap. Specifically, for each state s and each time step h, we define the following metric

$$\Delta_h(s) := \min_{a \notin \mathcal{A}_s^\star} \left\{ V_h^\star(s) - Q_h^\star(s, a) \right\} \qquad \text{with} \quad \mathcal{A}_s^\star := \left\{ a : Q_h^\star(s, a) = V_h^\star(s) \right\}. \tag{9}$$

In words, $\Delta_h(s)$ quantifies the gap — in terms of the resulting Q-values — between the optimal action and the sub-optimal ones. It is worth noting that there might exist multiple optimal actions for a given (s, h) pair, namely, the set $\mathcal{A}_s^\star$ is not necessarily a singleton. Further, we define the minimum gap over all (s, h) pairs as follows

$$\Delta_{\text{gap}} := \min_{s, h \in \mathcal{S} \times [H]} \Delta_h(s), \tag{10}$$

and refer to it as the sub-optimality gap throughout this paper.

2.3 RL under sampling with state revisiting

In standard online episodic RL settings, the learner collects data samples by executing multiple length-H trajectories in the MDP $\mathcal{M}$ via suitably chosen policies; more concretely, in the n-th episode with a given initial state s_0^n, the agent executes a policy to generate a sample trajectory $\{(s_h^n, a_h^n)\}_{1 \leq h \leq H}$, where (s_h^n, a_h^n) denotes the state-action pair at time step h. This setting underscores the importance of trading off exploitation and exploration. As pointed out previously, however, this classical sampling mechanism could be highly inefficient for MDPs with linearly realizable $Q^\star$, even in the face of a constant sub-optimality gap (Wang et al., 2021).

A new sampling protocol with state revisiting. In order to circumvent this sample complexity barrier, the current paper studies a more flexible sampling mechanism that allows one to revisit previous states in the same episode. Concretely, in each episode, the sampling process can be carried out in the following fashion:

Algorithm 1: Sampling protocol for an episode with state revisiting.

1 **Input:** initial state s_1.
2 Select a policy and sample a length-H trajectory $\{(s_t, a_t)\}_{1 \le t \le H}$.
3 **repeat**
4   Pick any previously visited state s_h in this episode;
5   Execute a new trajectory starting from s_h all the way up to step H, namely, $\{(s_t, a_t)\}_{h \le t \le H}$;
     here, we overload notation to simplify presentation.
6 **until** *the learner terminates it.*

As a distinguishing feature, the sampling mechanism described in Algorithm 1 allows one to revisit previous states and retake samples from there, which reveals more information regarding these states. To make apparent its practice relevance, we first note that the generative model proposed in Kearns and Singh (1999); Kakade (2003) — in which one can query a simulator with arbitrary state-action pairs to get samples — is trivially subsumed as a special case of this sampling mechanism. Moving on to a more complicated yet realistic scenario, consider role-playing video games which commonly include built-in "save files" features. This type of features allows the player to record its progress at any given point, so that it can resume the game from this save point later on. In fact, rebooting the game multiple times from a saved point allows an RL algorithm to conduct trial-and-error learning for this particular game point.

As a worthy note, while revisiting a particular state many times certainly yields information gain about this state, it also means that fewer samples can be allocated to other episodes if the total sampling budget is fixed. Consequently, how to design intelligent state revisiting schemes in order to optimize sample efficiency requires careful thinking.

Learning protocol and sample efficiency. We are now ready to describe the learning process — which consists of N episodes — and our goal.

- In the n-th episode ($1 \le n \le N$), the learner is given an initial state $s_1^{(n)}$ (assigned by nature), and executes the sampling protocol in Algorithm 1 until this episode is terminated.

- At the end of the n-th episode, the outcome of the learning process takes the form of a policy $\pi^{(n)}$, which is learned based on all information collected up to the end of this episode.

The quality of the learning outcome $\{\pi^{(n)}\}_{1 \le n \le N}$ is then measured by the cumulative regret over N episodes as follows:

$$\mathsf{Regret}(N) \coloneqq \sum_{n=1}^{N} \left(V_1^{\star}\big(s_1^{(n)}\big) - V_1^{\pi^{(n)}}\big(s_1^{(n)}\big) \right). \tag{11}$$

For any target level $\varepsilon \in [0, H]$, the aim is to achieve $\frac{1}{N}\mathsf{Regret}(N) \le \varepsilon$ using a sample size T no larger than $\mathsf{poly}\big(d, H, \frac{1}{\varepsilon}, \frac{1}{\Delta_{\mathsf{gap}}}\big)$ (but independent of $|\mathcal{S}|$ and $|\mathcal{A}|$). Here and throughout, T stands for the total number of samples observed in the learning process; for instance, a new trajectory $\{(s_t, a_t)\}_{h \le t \le H}$ amounts to $H - h$ new samples. An RL algorithm capable of achieving this level of sample complexity is declared to be sample-efficient, given that the sample complexity does not scale with the ambient dimension of the problem (which could be enormous in contemporary RL).

3 Algorithm and main results

In this section, we put forward an algorithm tailored to the sampling protocol described in Algorithm 1, and demonstrate its desired sample efficiency.

3.1 Algorithm

Our algorithm design is motivated by the method proposed in (Jin et al., 2020) for linear MDPs — called *least-squares value iteration with upper confidence bounds (LSVI-UCB)* — which follows the principle of "optimism in the face of uncertainty". In what follows, we shall begin by briefly reviewing the key update rules of LSVI-UCB, and then discuss how to adapt it to accommodate MDPs with linearly realizable $Q^\star$ when state revisiting is permitted.

Review: LSVI-UCB for linear MDPs. Recall that in linear MDPs, it is assumed that there exist unknown vectors $\mu_h(\cdot) = [\mu_h^{(1)}, \cdots, \mu_h^{(d)}]^\top \in \mathbb{R}^{d \times |\mathcal{S}|}$ and $w_h \in \mathbb{R}^d$ such that

$$\forall (s, a, h) \in \mathcal{S} \times \mathcal{A} \times [H]: \qquad P_h(\cdot \,|\, s, a) = \langle \varphi(s, a), \mu_h(\cdot) \rangle \quad \text{and} \quad r_h(s, a) = \langle \varphi(s, a), w_h(s, a) \rangle.$$

In other words, both the probability transition kernel and the reward function can be linearly represented using the set of feature maps $\{\varphi(s, a)\}$.

LSVI-UCB can be viewed as a generalization of the UCBVI algorithm (Azar et al., 2017) (originally proposed for the tabular setting) to accommodate linear function approximation. In each episode, the learner draws a sample trajectory following the greedy policy w.r.t. the current Q-function estimate with UCB exploration; namely, an MDP trajectory $\{(s_h^n, a_h^n)\}_{1 \le h \le H}$ is observed in the n-th episode. Working backwards (namely, going from step H all the way back to step 1), the LSVI-UCB algorithm in the n-th episode consists of the following key updates:

$$\Lambda_h \;\leftarrow\; \sum_{i=1}^{n} \varphi(s_h^i, a_h^i)\varphi(s_h^i, a_h^i)^\top + \lambda I, \tag{12a}$$

$$\theta_h \;\leftarrow\; \Lambda_h^{-1} \sum_{i=1}^{n} \varphi(s_h^i, a_h^i)\left\{ r_h(s_h^i, a_h^i) + \max_a Q_{h+1}(s_{h+1}^i, a) \right\}, \tag{12b}$$

$$Q_h(\cdot, \cdot) \;\leftarrow\; \min\left\{ \langle \theta_h, \varphi(\cdot, \cdot) \rangle + \beta\sqrt{\varphi(\cdot, \cdot)^\top \Lambda_h^{-1} \varphi(\cdot, \cdot)}, H \right\}, \tag{12c}$$

with the regularization parameter λ set to be 1. Informally speaking, θ_h (cf. (12b)) corresponds to the solution to a ridge-regularized least-squares problem — tailored to solving the Bellman optimality equation with linear parameterization — using all samples collected so far for step h, where the matrix Λ_h (cf. (12a)) captures the (properly regularized) covariance of $\varphi(\cdot, \cdot)$ associated with these samples. In particular, $\langle \theta_h, \varphi(\cdot, \cdot) \rangle$ attempts to estimate the Q-function by exploiting its linear representation for this setting, and the algorithm augments it by an upper confidence bound (UCB) bonus $\beta\sqrt{\varphi(\cdot, \cdot)^\top \Lambda_h^{-1} \varphi(\cdot, \cdot)}$ — a term commonly arising in the linear bandit literature (Lattimore and Szepesvári, 2020) — to promote exploration, where β is a hyper-parameter to control the level of exploration. As a minor remark, the update rule (12c) also ensures that the Q-function estimate never exceeds the trivial upper bound H.

Our algorithm: LinQ-LSVI-UCB for linearly realizable $Q^\star$. Moving from linear MDPs to MDPs with linear $Q^\star$, we need to make proper modification of the algorithm. To facilitate discussion, let us introduce some helpful concepts.

- Whenever we start a new episode or revisit a state (and draw samples thereafter), we say that *a new path* is being collected. The total number of paths we have collected is denoted by K.

- For each k and each step h, we define a set of indices

$$\mathcal{I}_h^k := \left\{ i: \, 1 \le i \le k \mid \theta_h^i \text{ is updated in the } i\text{-th path at time step } h \right\}, \tag{13}$$

  which will also be described precisely in Algorithm 2. As we shall see, the cardinality of $\mathcal{I}_h^k$ is equal to the total number of new samples that have been collected at time step h up to the k-th path.

We are now ready to describe the proposed algorithm. For the k-th path, our algorithm proceeds as follows.

- *Sampling.* Suppose that we start from a state s_h^k at time step h. The learner adopts the greedy policy $\pi^k = \{\pi_j^k\}_{h \leq j \leq H}$ in accordance with the current Q-estimate $\{Q_j^{k-1}\}_{h \leq j \leq H}$, and observes a fresh sample trajectory $\{(s_j^k, a_j^k)\}_{h \leq j \leq H}$ as follows: for $j = h, h+1, \ldots, H$,

$$s_{j+1}^k \sim P_j(\cdot \,|\, s_j^k, a_j^k) \qquad \text{with} \qquad a_j^k = \pi_j^k(s_j^k) \coloneqq \arg\max_a Q_j^{k-1}(s_j^k, a). \tag{14}$$

- *Backtrack and update estimates.* We then work backwards to update our Q-estimates and the θ-estimates (i.e., estimates for the linear representation of $Q^\star$), until the UCB bonus term (which corresponds to the estimated uncertainty level of the Q-estimate) drops below a threshold determined by the sub-optimality gap Δ_{gap}. More precisely, working backwards from $h = H$, we carry out the following calculations if certain conditions (to be described shortly) are met:

$$\Lambda_h^k \leftarrow \sum_{i \in \mathcal{I}_h^k} \varphi_h(s_h^i, a_h^i) \varphi_h(s_h^i, a_h^i)^\top + I, \tag{15a}$$

$$\theta_h^k \leftarrow \left(\Lambda_h^k\right)^{-1} \sum_{i \in \mathcal{I}_h^k} \varphi_h(s_h^i, a_h^i) \Big\{ r_h(s_h^i, a_h^i) + \big\langle \varphi_{h+1}(s_{h+1}^i, a_{h+1}^i), \theta_{h+1}^k \big\rangle \Big\}, \tag{15b}$$

$$b_h^k(\cdot, \cdot) \leftarrow \beta \sqrt{\varphi_h(\cdot, \cdot)^\top \left(\Lambda_h^k\right)^{-1} \varphi_h(\cdot, \cdot)}, \tag{15c}$$

$$Q_h^k(\cdot, \cdot) \leftarrow \min \Big\{ \big\langle \varphi_h(\cdot, \cdot), \theta_h^k \big\rangle + b_h^k(\cdot, \cdot), \, H \Big\}. \tag{15d}$$

Here, we employ the pre-factor

$$\beta = c_\beta \sqrt{dH^4 \log \frac{KH}{\delta}} \tag{16}$$

to adjust the level of "optimism", where $c_\beta > 0$ is taken to be some suitably large constant. Crucially, whether the update (15b) — and hence (15d) — is executed depends on the size of the bonus term b_{h+1}^{k-1} of the last attempt at step $h+1$. Informally, if the bonus term is sufficiently small compared to the sub-optimality gap, then we have confidence that the policy estimate (after time step h) can be trusted in the sense that it is guaranteed to generalize and perform well on unseen states.

The complete algorithm is summarized in Algorithm 2, with some basic auxiliary functions provided in Algorithm 3. To facilitate understanding, an illustration is provided in Figure 1.

Two immediate remarks are in order. In comparison to LSVI-UCB in Jin et al. (2020), the update rule (15b) for θ_h^k employs the linear representation $\big\langle \varphi_{h+1}(s_{h+1}^i, a_{h+1}^i), \theta_{h+1}^k \big\rangle$ *without the UCB bonus* as the Q-value estimate. This subtle difference turns out to be important in the analysis for MDPs with linear $Q^\star$. In addition, LSVI-UCB is equivalent to first obtaining a linear representation of transition kernel P (Agarwal et al., 2019) and then using it to build Q-function estimates and draw samples. In contrast, Algorithm 2 cannot be interpreted as a decoupling of model estimation and planning/exploration stage, and is intrinsically a value-based approach.

3.2 Theoretical guarantees

Equipped with the precise description of Algorithm 2, we are now positioned to present its regret bound and sample complexity analysis. Our result is this:

Theorem 1. *Suppose that Assumption 1 holds, and that $c_\beta \geq 8$ is some fixed constant. Then for any $0 < \delta < 1$, any $0 < \varepsilon < H$, and any initial states $\big\{ s_1^{(n)} \big\}_{1 \leq n \leq N}$, Algorithm 2 achieves a regret (cf. (11)) obeying $\frac{1}{N} \mathsf{Regret}(N) \leq \varepsilon$ with probability at least $1 - \delta$, provided that $N \geq \frac{4c_\beta^2 d^2 H^5 \log^2 \frac{HT}{\delta}}{\Delta_{\mathsf{gap}}^2}$ and the total number T of samples exceeds*

$$T \geq \frac{64 c_\beta^2 d^2 H^7 \log^2 \frac{HT}{\delta}}{\varepsilon^2}. \tag{17}$$

In addition, with probability at least $1 - \delta$, the total number of state revisits satisfies

$$K - N \leq \frac{4 c_\beta^2 d^2 H^5 \log^2 \frac{KH}{\delta}}{\Delta_{\mathsf{gap}}^2}. \tag{18}$$

Algorithm 2: LinQ-LSVI-UCB with state revisiting.

---

1 **inputs:** number of episodes N, sub-optimality gap Δ_{gap}, initial states $\{s_1^{(n)}\}_{1 \leq n \leq N}$.

2 **initialization:** $h = 0$, $n = 0$, $\theta_j^0 = 0$ and $\mathcal{I}_j^0 = \emptyset$ for all $1 \leq j \leq H$.

3 **for** $k = 1, 2, \cdots$ **do**

4   call $\pi^k \leftarrow$ `get-policy()`.

5     $h \leftarrow h + 1$.

6   **if** $h = 1$ **then**

7        $\pi^{(n)} \leftarrow \pi^{k-1}$. // `record the up-to-date policy learned in this`
          `episode.`

8        $n \leftarrow n + 1$. // `Start a new episode.`

9   **if** $n > N$ **then**

10          $K \leftarrow k - 1$ and **return**. // `Terminate after` N `episodes.`

11   Set the initial state $s_1^k = s_1^{(n)}$.

12   call `sampling()`. // `collect new samples from step` h`; see Algorithm 3.`
     // `Backtrack and determine whether to revisit a state.`

13   Set $\theta_{H+1}^k = 0$ and $h = H$.

14   **while** $h > 0$ *and* $b_{h+1}^{k-1}(s_{h+1}^k, a_{h+1}^k) < \Delta_{\mathsf{gap}}/2$ *(cf. (15c))* **do**

15        $\mathcal{I}_h^k \leftarrow \mathcal{I}_h^{k-1} \bigcup \{k\}$. // `Expand` $\mathcal{I}_h^k$ `whenever we need to update` θ_h^k.

16   Update θ_h^k according to (15b).

17        $h \leftarrow h - 1$.

18   call `update-remaining()`. // `keep remaining iterates unchanged; see`
     `Algorithm 3.`

Figure 1: Illustration of the set $\mathcal{I}_h^K$ for a simple scenario where $N = 1$, $H = 3$, and the total number of paths is $K = 4$. After the 1st path, the sampling process revisits state s_3^1 twice (each time drawing one new sample), and then revisits state s_2^1 to draw two samples from there. This episode then terminates as the conditions are met for all steps. A red superscript indicates new state or new actions taken, and the orange line illustrates the sampling process. Here, we have $\mathcal{I}_3^4 = \{1, 2, 3, 4\}$, $\mathcal{I}_2^4 = \{3, 4\}$ and $\mathcal{I}_1^4 = \{4\}$, which record the paths where the linear representations are updated for each respective step.

Theorem 1 characterizes the sample complexity of the proposed algorithm, when the target accuracy is measured in terms of the average regret $\frac{1}{N}\mathsf{Regret}(N)$ (see (11)). Several implications of this theorem are in order.

- *Sample efficiency.* While our sample complexity bound (17) scales as a polynomial function of both d and H, it does not rely on either the state space size or the action space size. This hints at the dramatic sample size reduction when $|\mathcal{S}||\mathcal{A}|$ far exceeds the feature dimension d and the horizon H.

- *A small number of state revisits.* Theorem 1 develops an upper bound (18) on the total number of state revisits, which is gap-dependent but otherwise independent of the target accuracy level ε. As a consequence, as the sample size T increases (or when ε decreases), the ratio of the number of state revisits to the sample size becomes vanishingly small, meaning that our sampling protocol becomes increasingly closer to the standard online RL setting.

Algorithm 3: Simple auxiliary functions.

---

1 **Function** sampling():
   // Sampling from the beginning (if $h = 0$) or from a revisited state
      (if $h > 0$).
   // Do not update samples prior to step h.
2   **for** $j = 1, 2, \ldots, h - 1$ **do**
3   ⌊ Set $a_j^k = a_j^{k-1}$, and $s_{j+1}^k = s_{j+1}^{k-1}$.
   // A new round of sampling from step h.
4   **for** $j = h, h + 1, \cdots, H$ **do**
5   Compute $Q_j^{k-1}(s_j^k, a)$ according to (15d).
6   Take $a_j^k = \arg\max_a Q_j^{k-1}(s_j^k, a)$, and draw $s_{j+1}^k \sim P_j(\cdot \mid s_j^k, a_j^k)$.

7 **Function** update-remaining():
   // Keep the estimates prior to step h unchanged.
8   **for** $j = 1, 2, \ldots, h$ **do**
9   ⌊ Set $\theta_h^k = \theta_h^{k-1}$.

10 **Function** get-policy():
   // Update the Q-estimates.
11   **for** $1 \leq h \leq H$ **do**
12   Set $Q_h^{k-1}(\cdot, \cdot)$ according to (15d).
13     $\pi_h^k(\cdot) \leftarrow \arg\max_a Q_h^{k-1}(\cdot, a)$.

- *Computational complexity and memory complexity.* The computational bottleneck of the proposed algorithm lies in the update of θ_h^k and b_h^k (see (15b) and (15c), respectively), which consists of solving a linear systems of equations and can be accomplished using, say, the conjugate gradient method in time on the order of $d^2 \log T$. In addition, one needs to search over all actions when drawing samples, so the algorithm necessarily depends on $|\mathcal{A}|$. In total, the algorithm has a runtime no larger than $O(d^2 |\mathcal{A}| T \log T)$. In addition, implementing our algorithm requires $O(d^2 H)$ units of memory.

- *Comparison to the case with a generative model.* We find it helpful to compare our findings with the algorithm developed in the presence of a generative model. In a nutshell, the algorithm described in Du et al. (2020a, Appendix C) starts by identifying a "well-behaved" basis of the feature vectors, and then queries the generative model to sample the state-action pairs related to this basis. In contrast, our sampling protocol (cf. Algorithm 1) is substantially more restrictive and does not give us the freedom to sample such a basis. In fact, our algorithm is exploratory in nature, which is far more challenging than the case with a generative model.

4 Discussion

In this paper, we have made progress towards understanding the plausibility of achieving sample-efficient RL when the optimal Q-function is linearly realizable. While prior works suggested an exponential sample size barrier in the standard online RL setting even in the presence of a constant sub-optimality gap, we demonstrate that this barrier can be conquered by permitting state revisiting. An algorithm called LinQ-LSVI-UCB has been developed that provably enjoys a reduced sample complexity, which is polynomial in the feature dimension, the horizon and the inverse sub-optimality gap, but otherwise independent of the dimension of the state/action space.

Note, however, that linear function approximation for online RL remains a rich territory for further exploration and understanding. In contrast to the tabular setting, the feasibility and limitations of online RL might vary drastically across different families of linear function approximation. There are numerous directions that call for further investigation in order to obtain a more complete picture. For instance, can we identify other flexible yet practically relevant online RL sampling mechanisms that also allow for sample size reduction? What if the optimal state-action function is only approximately linearly realizable? We leave all of these to future studies.

References

Abbasi-Yadkori, Y., Pál, D., and Szepesvári, C. (2011). Improved algorithms for linear stochastic bandits. In *NIPS*, volume 11, pages 2312–2320.

Agarwal, A., Jiang, N., Kakade, S. M., and Sun, W. (2019). Reinforcement learning: Theory and algorithms.

Agarwal, A., Kakade, S., Krishnamurthy, A., and Sun, W. (2020a). FLAMBE: Structural complexity and representation learning of low rank MDPs. *arXiv preprint arXiv:2006.10814*.

Agarwal, A., Kakade, S., and Yang, L. F. (2020b). Model-based reinforcement learning with a generative model is minimax optimal. *Conference on Learning Theory*, pages 67–83.

Agarwal, A., Kakade, S. M., Lee, J. D., and Mahajan, G. (2020c). Optimality and approximation with policy gradient methods in Markov decision processes. In *Conference on Learning Theory*, pages 64–66. PMLR.

Ayoub, A., Jia, Z., Szepesvari, C., Wang, M., and Yang, L. (2020). Model-based reinforcement learning with value-targeted regression. In *International Conference on Machine Learning*, pages 463–474. PMLR.

Azar, M. G., Munos, R., and Kappen, H. J. (2013). Minimax PAC bounds on the sample complexity of reinforcement learning with a generative model. *Machine learning*, 91(3):325–349.

Azar, M. G., Osband, I., and Munos, R. (2017). Minimax regret bounds for reinforcement learning. In *International Conference on Machine Learning*, pages 263–272.

Azuma, K. (1967). Weighted sums of certain dependent random variables. *Tohoku Mathematical Journal, Second Series*, 19(3):357–367.

Baird, L. (1995). Residual algorithms: Reinforcement learning with function approximation. In *Machine Learning Proceedings 1995*, pages 30–37. Elsevier.

Bertsekas, D. P. and Tsitsiklis, J. N. (1995). Neuro-dynamic programming: an overview. In *Proceedings of 1995 34th IEEE conference on decision and control*, volume 1, pages 560–564. IEEE.

Dann, C. and Brunskill, E. (2015). Sample complexity of episodic fixed-horizon reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 2818–2826.

Dimakopoulou, M., Zhou, Z., Athey, S., and Imbens, G. (2019). Balanced linear contextual bandits. In *AAAI Conference on Artificial Intelligence*, volume 33, pages 3445–3453.

Du, S. S., Kakade, S. M., Lee, J. D., Lovett, S., Mahajan, G., Sun, W., and Wang, R. (2021). Bilinear classes: A structural framework for provable generalization in RL. *arXiv preprint arXiv:2103.10897*.

Du, S. S., Kakade, S. M., Wang, R., and Yang, L. F. (2020a). Is a good representation sufficient for sample efficient reinforcement learning? In *International Conference on Learning Representations*.

Du, S. S., Lee, J. D., Mahajan, G., and Wang, R. (2020b). Agnostic Q-learning with function approximation in deterministic systems: Tight bounds on approximation error and sample complexity. *Neural Information Processing Systems*.

Even-Dar, E. and Mansour, Y. (2003). Learning rates for Q-learning. *Journal of machine learning Research*, 5(Dec):1–25.

Hao, B., Duan, Y., Lattimore, T., Szepesvári, C., and Wang, M. (2020). Sparse feature selection makes batch reinforcement learning more sample efficient. *arXiv preprint arXiv:2011.04019*.

He, J., Zhou, D., and Gu, Q. (2020). Logarithmic regret for reinforcement learning with linear function approximation. *arXiv preprint arXiv:2011.11566*.

Jaksch, T., Ortner, R., and Auer, P. (2010). Near-optimal regret bounds for reinforcement learning. *Journal of Machine Learning Research*, 11(4).

Jiang, N., Krishnamurthy, A., Agarwal, A., Langford, J., and Schapire, R. E. (2017). Contextual decision processes with low Bellman rank are PAC-learnable. In *International Conference on Machine Learning*, pages 1704–1713. PMLR.

Jin, C., Liu, Q., and Miryoosefi, S. (2021). Bellman Eluder dimension: New rich classes of RL problems, and sample-efficient algorithms. *arXiv preprint arXiv:2102.00815*.

Jin, C., Yang, Z., Wang, Z., and Jordan, M. I. (2020). Provably efficient reinforcement learning with linear function approximation. In *Conference on Learning Theory*, pages 2137–2143. PMLR.

Kakade, S. (2003). *On the sample complexity of reinforcement learning*. PhD thesis, University of London.

Kearns, M. J. and Singh, S. P. (1999). Finite-sample convergence rates for Q-learning and indirect algorithms. In *Advances in neural information processing systems*, pages 996–1002.

Lattimore, T. and Szepesvári, C. (2020). *Bandit algorithms*. Cambridge University Press.

Lattimore, T., Szepesvari, C., and Weisz, G. (2020). Learning with good feature representations in bandits and in RL with a generative model. In *International Conference on Machine Learning*, pages 5662–5670. PMLR.

Li, G., Wei, Y., Chi, Y., Gu, Y., and Chen, Y. (2020). Breaking the sample size barrier in model-based reinforcement learning with a generative model. *Advances in Neural Information Processing Systems*, 33.

Long, J. and Han, J. (2021). An l^2 analysis of reinforcement learning in high dimensions with kernel and neural network approximation. *arXiv preprint arXiv:2104.07794*.

Modi, A., Chen, J., Krishnamurthy, A., Jiang, N., and Agarwal, A. (2021). Model-free representation learning and exploration in low-rank MDPs. *arXiv preprint arXiv:2102.07035*.

Munos, R. (2005). Error bounds for approximate value iteration. In *Proceedings of the National Conference on Artificial Intelligence*, volume 20, pages 1006–1011.

Osband, I. and Van Roy, B. (2014). Model-based reinforcement learning and the Eluder dimension. In *Proceedings of the 27th International Conference on Neural Information Processing Systems-Volume 1*, pages 1466–1474.

Osband, I., Van Roy, B., and Wen, Z. (2016). Generalization and exploration via randomized value functions. In *International Conference on Machine Learning*, pages 2377–2386. PMLR.

Shariff, R. and Szepesvári, C. (2020). Efficient planning in large MDPs with weak linear function approximation. *arXiv preprint arXiv:2007.06184*.

Sidford, A., Wang, M., Wu, X., and Ye, Y. (2018). Variance reduced value iteration and faster algorithms for solving Markov decision processes. In *Proceedings of the Twenty-Ninth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 770–787. SIAM.

Touati, A. and Vincent, P. (2020). Efficient learning in non-stationary linear Markov decision processes. *arXiv preprint arXiv:2010.12870*.

Wainwright, M. J. (2019). Stochastic approximation with cone-contractive operators: Sharp ℓ_∞-bounds for Q-learning. *arXiv preprint arXiv:1905.06265*.

Wang, R., Du, S. S., Yang, L. F., and Salakhutdinov, R. (2020a). On reward-free reinforcement learning with linear function approximation. *arXiv preprint arXiv:2006.11274*.

Wang, R., Salakhutdinov, R. R., and Yang, L. (2020b). Reinforcement learning with general value function approximation: Provably efficient approach via bounded Eluder dimension. *Advances in Neural Information Processing Systems*, 33.

Wang, Y., Wang, R., Du, S. S., and Krishnamurthy, A. (2019). Optimism in reinforcement learning with generalized linear function approximation. *arXiv preprint arXiv:1912.04136*.

Wang, Y., Wang, R., and Kakade, S. M. (2021). An exponential lower bound for linearly-realizable MDPs with constant suboptimality gap. *arXiv preprint arXiv:2103.12690*.

Wei, C.-Y., Jahromi, M. J., Luo, H., and Jain, R. (2021). Learning infinite-horizon average-reward MDPs with linear function approximation. In *International Conference on Artificial Intelligence and Statistics*, pages 3007–3015. PMLR.

Weisz, G., Amortila, P., Janzer, B., Abbasi-Yadkori, Y., Jiang, N., and Szepesvári, C. (2021a). On query-efficient planning in MDPs under linear realizability of the optimal state-value function. *arXiv preprint arXiv:2102.02049*.

Weisz, G., Amortila, P., and Szepesvári, C. (2021b). Exponential lower bounds for planning in MDPs with linearly-realizable optimal action-value functions. In *Algorithmic Learning Theory*, pages 1237–1264. PMLR.

Wen, Z. and Van Roy, B. (2017). Efficient reinforcement learning in deterministic systems with value function generalization. *Mathematics of Operations Research*, 42(3):762–782.

Yang, K., Yang, L., and Du, S. (2021). Q-learning with logarithmic regret. In *International Conference on Artificial Intelligence and Statistics*, pages 1576–1584. PMLR.

Yang, L. and Wang, M. (2019). Sample-optimal parametric Q-learning using linearly additive features. In *International Conference on Machine Learning*, pages 6995–7004.

Yang, L. and Wang, M. (2020). Reinforcement learning in feature space: Matrix bandit, kernels, and regret bound. In *International Conference on Machine Learning*, pages 10746–10756. PMLR.

Yang, Z., Jin, C., Wang, Z., Wang, M., and Jordan, M. I. (2020). Bridging exploration and general function approximation in reinforcement learning: Provably efficient kernel and neural value iterations. *arXiv preprint arXiv:2011.04622*.

Zanette, A., Brandfonbrener, D., Brunskill, E., Pirotta, M., and Lazaric, A. (2020a). Frequentist regret bounds for randomized least-squares value iteration. In *International Conference on Artificial Intelligence and Statistics*, pages 1954–1964. PMLR.

Zanette, A., Lazaric, A., Kochenderfer, M., and Brunskill, E. (2019). Limiting extrapolation in linear approximate value iteration. *Neural Information Processing Systems*.

Zanette, A., Lazaric, A., Kochenderfer, M., and Brunskill, E. (2020b). Learning near optimal policies with low inherent Bellman error. In *International Conference on Machine Learning*, pages 10978–10989. PMLR.

Zhang, Z., Zhou, Y., and Ji, X. (2020). Almost optimal model-free reinforcement learning via reference-advantage decomposition. *Advances in Neural Information Processing Systems*, 33.

Zhou, D., Gu, Q., and Szepesvari, C. (2020). Nearly minimax optimal reinforcement learning for linear mixture Markov decision processes. *arXiv preprint arXiv:2012.08507*.