Generalised Implicit Neural Representations

Abstract

We consider the problem of learning implicit neural representations (INRs) for
signals on non-Euclidean domains. In the Euclidean case, INRs are trained on
a discrete sampling of a signal over a regular lattice. Here, we assume that the
continuous signal exists on some unknown topological space from which we sample
a discrete graph. In the absence of a coordinate system to identify the sampled
nodes, we propose approximating their location with a spectral embedding of the
graph. This allows us to train INRs without knowing the underlying continuous
domain, which is the case for most graph signals in nature, while also making the
INRs equivariant under the symmetry group of the domain. We show experiments
with our method on various real-world signals on non-Euclidean domains.

Figure 1: Given a continuous signal on a non-Euclidean domain, we observe a discrete graph realisation of it. A generalised implicit neural representation is a neural network f_θ trained to map a spectral embedding of each node to the corresponding signal value.

1 Introduction

Implicit neural representations (INRs) are a class of techniques to parametrise signals using neural networks [43, 36, 40, 30]. INRs are trained to map each point in a given domain to the corresponding value of a signal at that point. For example, INRs for images learn to map the 2D coordinates of pixels to their corresponding RGB values. INRs can also be conditioned on a latent vector, typically learned end-to-end as part of the model, that allows them to represent different signals on the same domain. INRs have been successfully applied to model complex signals like images [43, 40], signed distance functions [36], and radiance fields [35].

By expressing a signal as an INR, we obtain a continuous approximation of the signal on the whole domain. This allows us to compute a higher-resolution approximation of the signal by sampling more

points on the domain (*e.g.*, a finer grid of pixels). Additionally, since INRs are fully differentiable, the latent vector of a conditional INR can be optimised with backpropagation and gradient descent to obtain a signal with some desired characteristics. For example, a conditional INR for signed distance functions can be used to design surfaces with a target aerodynamic profile [37].

So far, the literature on INRs has only focused on signals on Euclidean domains. However, signals defined on non-Euclidean domains are ubiquitous in nature and are especially relevant in artificial intelligence, as demonstrated by the recent rise of geometric deep learning [12]. In this paper, we propose an extension of the INR setting to signals on arbitrary non-Euclidean domains.

Contributions We formulate the *generalised* INR problem as the task of learning an implicit representation for a signal on an arbitrary topological space $\mathcal{M}$ where, instead of observing the signal sampled on a regular lattice, we observe a weighted graph (*i.e.*, a discretisation of $\mathcal{M}$) and the corresponding graph signal. In most practical cases, $\mathcal{M}$ is unknown and we cannot represent the sampled vertices using their true coordinates. Even when $\mathcal{M}$ is known (as in the Euclidean case), training an INR on a fixed coordinate system means that the model will not be equivariant under the symmetry group of $\mathcal{M}$. We solve both these issues by identifying the sampled nodes with a spectral embedding obtained from the eigenvectors of the graph Laplacian. We then train a neural network to map the spectral embeddings to the corresponding signal values. Figure 1 shows a schematic view of the method.

Since the eigenvectors of the graph Laplacian are a discrete approximation of the continuous eigen-functions of the Laplace operator on $\mathcal{M}$ (when appropriately rescaled) [5, 10, 7], at inference time we can map arbitrary points on $\mathcal{M}$ to the corresponding approximation of the signal, as long as the discrete graph signal is sampled consistently. This allows us to compute higher-resolution signals or to estimate the signal on different graph realisations of the same phenomenon (*e.g.*, different social networks with a similar structure).

Results In the experiments section, we show concrete examples of learning INRs for signals on graphs and manifolds, using real-world data from biology and social networks. We also show that INRs trained on one instance of a graph can be transferred to different graph realisations of the underlying domain. Then, we show applications of conditional generalised INRs to model different signals on the same irregular domain, and also different signals on different domains. Finally, we conclude the paper with an experiment that consolidates all our results, modelling real-world meteorological signals on the spherical surface of the Earth.

2 Related works

INRs have recently attracted the attention of the machine learning community for their ability to represent complex signals, especially in computer vision, 3D rendering, and image synthesis applications [36, 34, 2, 21, 35, 41, 29]. Recent work has highlighted that INRs benefit from computing sinusoidal transformations of the coordinates, typically called Fourier features or positional encodings (PEs) [46, 44, 35, 47, 8].

However, these transformations are not applicable to non-Euclidean domains and still depend on a choice of coordinate system. A proposal for making INRs equivariant under the SO(3) group has been presented by Deng et al. [15], although this technique does not apply in general to non-Euclidean domains. The field of geometric deep learning has also explored the use of graph PEs similar to the ones we use in this paper, showing their usefulness as node features for graph neural networks [42, 32, 17, 16]. Recent research has also investigated the idea of learnable graph PEs [18, 13].

Related to our work, Belkin and Niyogi [5], Boguna et al. [11] and Levie et al. [28] have studied the geometrical link between graphs and topological spaces. Keriven et al. [24, 25] investigated the convergence, in the limit, of graph neural networks trained on large graphs. An alternative view of graphs as discrete samples of continuous spaces is the concept of graphon, which can be seen both as a generative model and as the limit of a sequence of graphs [33].

3 Method

Standard setting   In the standard INR setting, we consider a signal $f : \mathcal{X} \to \mathcal{Y}$ with $\mathcal{X} \subseteq \mathbb{R}^d$ and $\mathcal{Y} \subseteq \mathbb{R}^p$. We observe a discrete realisation of the signal $f(\mathbf{x}_i)$ for $i = 1, \ldots, n$, where points $\mathbf{x}_i$ are sampled on a regular lattice on $\mathcal{X}$. Then, we train a neural network $f_\theta : \mathcal{X} \to \mathcal{Y}$, with parameters θ, on input-output pairs $(\mathbf{x}_i, f(\mathbf{x}_i))$. Since we know that the signal domain is a subset of $\mathbb{R}^d$, at inference time we can sample points anywhere on $\mathcal{X}$ to compute the approximated value of the signal at those points. For example, an INR for images maps equispaced points in the unit square (pixel coordinates) to points in the unit cube (RGB values normalised between 0 and 1). The specific image on which we train the INR is a realisation of one such signal at a given resolution, and at inference time we can sample a finer lattice to super-resolve the image [43, 40].

Generalised setting   In the generalised setting, we consider a continuous signal $f : \mathcal{M} \to \mathcal{Y}$, with $\mathcal{M}$ an arbitrary topological space. We observe a discrete graph signal $f(v_i)$ on an undirected weighted graph $G = (V, E)$, with node set $V = \{v_i\}$ for $i = 1, \ldots, n$ and edge set $E \subseteq V \times V$. The meaning of sampling G from $\mathcal{M}$ is intuitive in the case of geometric meshes or other physical structures like proteins (in which case we also know the coordinates of v_i on $\mathcal{M}$), but the same reasoning also applies to more complex domains with an abstract meaning (*e.g.*, the space of all possible papers and their citations). We generally assume that the graph describes some measure of closeness between uniformly sampled points on $\mathcal{M}$, be it a function of the coordinates on $\mathcal{M}$ (*e.g.*, a kernel) or some logical or functional relation that is given as part of the data. In general, we don't assume to know the true $\mathcal{M}$ from which G is sampled or the coordinates of v_i on $\mathcal{M}$. We only observe G and the associated graph signal. For an in-depth discussion on the relation between graphs and topological spaces, see references [5], [11], and [28].

Proposed method   We approach the generalised INR problem by mapping v_i to $f(v_i)$ through a spectral embedding obtained from the graph Laplacian. Let $\mathbf{A} \in \mathbb{R}^{n \times n}$ be the weighted adjacency matrix of graph G, $\mathbf{D}$ the diagonal degree matrix, and $\mathbf{L} = \mathbf{D} - \mathbf{A}$ the combinatorial Laplacian. The eigendecomposition of the Laplacian yields and orthonormal basis of eigenvectors $\{\mathbf{u}_k \in \mathbb{R}^n\}$ for $k = 1, \ldots, n$, with a canonical ordering given by their associated eigenvalues $\lambda_1 \leq \lambda_2 \leq \cdots \leq \lambda_n$. We define a generalised spectral embedding of size k for node v_i as

$$\mathbf{e}_i = \sqrt{n} \left[\mathbf{u}_{1,i}, \ldots, \mathbf{u}_{k,i} \right]^\top \in \mathbb{R}^k. \tag{1}$$

The generalised spectral embeddings are a discrete approximation of the eigenfunctions of the continuous Laplace operator on $\mathcal{M}$ and converge to them for $n \to \infty$. See the discussion in references [5], [10], [9], and [7] for a formal analysis. In practice, rescaling the eigenvectors by $\sqrt{n}$ ensures that the embeddings for graphs of different sizes will have the same range component-wise and that similar nodes will have similar embeddings regardless of the graph size. As an example, we show a comparison between the eigenvectors and the generalised spectral embeddings of a path graph in Figure 2.

Figure 2: Laplacian eigenvectors (left) *vs.* rescaled spectral embeddings (right) of a path graph, for $k = 3$ and $n = 100, 1000, 2000$. The curves on the right are shifted to improve visualisation.

We train a neural network $f_\theta : \mathbf{e}_i \mapsto f(v_i)$ on the observed graph signal. Since the generalised spectral embeddings only depend on the relationships between nodes, and not on the coordinates, the INR will also be equivariant under the symmetry group of the underlying topological space.

At inference time, we can compute the approximated value of the signal at an arbitrary location on $\mathcal{M}$ by computing the associated spectral embedding. If we know $\mathcal{M}$, or if we estimate it, we can sample new vertices directly from the domain and apply the same procedure used to construct the training graph. If $\mathcal{M}$ is unknown (*e.g.*, in the case of natural graphs that describe some abstract concept like citations, social interactions, or biological relations), then we just assume to observe a similar graph sampled from $\mathcal{M}$.

Complexity   Although computing the full eigendecomposition of the Laplacian has a complexity of $O(n^3)$, here we are only interested in the first k eigenvectors. Also, the Laplacian of most graphs is very sparse, with nodes having an average degree $\bar{d} \ll n$. We can therefore use the implicitly

Figure 3: Ground truth signals *vs.* signals predicted by the INR. Best viewed in colour.

restarted Lanczos method for eigendecomposition implemented by the ARPACK software, which has a complexity of $O(\bar{d}n^2)$ and can be easily parallelised [27]. In practice, all computations for this paper were easily managed on a commercial laptop with 10 CPU cores, scaling up to graphs in the order of 10^5 nodes.

We also note that at inference time, depending on how the edges are constructed, it could be possible to add new nodes and edges to the training graph instead of sampling an entirely new graph from $\mathcal{M}$. In this case, the spectral embeddings for the new nodes can be estimated using the Nyström method without needing to compute the full eigendecomposition [3, 9].

Alternative approaches   The generalised Laplacian embeddings used in this paper are only one of many possibilities to represent nodes sampled from $\mathcal{M}$. To name a few, locally linear embeddings [38], Isomap [45], Laplacian eigenmaps [6] and diffusion maps [14] are all based on the idea of embedding data using the first few principal eigenvectors of a similarity matrix. Here we focus on the Laplacian since it is well known, sparse, and easy to compute, and its eigendecomposition is stable to graph perturbations. One disadvantage of Laplacian eigenvectors is that they are only unique up to sign, leading to 2^k possible eigenbases for a given $\mathcal{M}$ and the consequent ambiguity when transferring an INR to a different graph realisation. However, simple heuristics can be used to eliminate ambiguity and we did not encounter any practical issues in this regard. An alternative way to resolve the ambiguity is to use random walk PEs [18], which, however, may fail to uniquely identify the nodes in graphs with similar neighbourhood structures (*e.g.*, meshes).

4   Experiments

Research questions   We investigate practical applications of generalised INRs aiming to answer the following questions:

Q1: Can generalised INRs be learned for non-trivial graph signals?
Q2: How does learning depend on the size of the spectral embedding?
Q3: Are generalised INRs transferable to other graphs sampled from $\mathcal{M}$?
Q4: Can generalised INRs learn in the conditional setting?

Setting   We implement the generalised INR as a SIREN multi-layer perceptron [40]. The model has 6 layers with 512 hidden neurons and a skip connection from the input to the middle layer. We use the same hyperparameters and initialisation scheme suggested by Sitzmann et al. [40]. We train the model using Adam [26] with a learning rate of 10^{-4} and an annealing schedule that halves the learning rate if the loss does not improve for 1000 steps. At each step, we sample 5000 nodes randomly from the graph as a mini-batch. We use spectral embeddings of size $k = 100$, a value that we found empirically as a good trade-off between complexity and performance. We report an analysis on the effect of k in Section 4.1. We ran all experiments on an Nvidia Tesla V100 GPU. The code to reproduce our results and the high-resolution version of all figures are available at `https://github.com/<anonymous>`. All deviations from the default setting are documented in the supplementary material.

4.1   Learning generalised INRs

We begin by verifying that a typical INR architecture can successfully learn arbitrary graph signals in the generalised setting (**Q1**). We consider three datasets as test cases.

Table 1: Training R^2 and mean squared error for the bunny, protein, and US election signals.

	Bunny	Protein	US Election
R^2	1.000	1.000	0.999
MSE	$9.141 \cdot 10^{-8}$	$1.177 \cdot 10^{-10}$	$1.455 \cdot 10^{-3}$

Bunny   We generate a texture on the Stanford bunny mesh[1] using the Gray-Scott reaction-diffusion model given by:

$$\Delta\mathbf{a} = -D_a\mathbf{L}\mathbf{a} - \mathbf{a} \odot \mathbf{b} \odot \mathbf{b} + F(\mathbf{1}_n - \mathbf{a}); \;\; \Delta\mathbf{b} = -D_b\mathbf{L}\mathbf{b} + \mathbf{a} \odot \mathbf{b} \odot \mathbf{b} - (F + K)\mathbf{b} \quad (2)$$

for state vectors $\mathbf{a}, \mathbf{b} \in \mathbb{R}^n$ and parameters $D_a, D_b, F, K \in \mathbb{R}$, where $\odot$ indicates element-wise product [20]. The mesh has 34834 nodes and 104288 edges. We configure the system to yield "coral" patterns[2] and evolve the simulation for 10^4 steps starting from random positive values for $\mathbf{a}, \mathbf{b}$. At the end of the evolution, we use vector $\mathbf{a}$ as target graph signal.

Protein   As a real-world domain, we consider the solvent excluded surface of a protein structure.[3] The continuous signal is the value of the electrostatic field generated by the amino acid residues at the surface. Protein function can be largely understood by studying their surfaces and the corresponding chemical features, like the electrostatic charge, so this represents a potentially interesting application of INRs to biology. We use a combination of the MSMS [39] and APBS [23] software packages to estimate the surface, sample the nodes, and get the corresponding signal, following the same workflow of Gainza et al. [19]. The final graph has 11966 nodes and 35892 edges.

US election   Finally, we consider a social network dataset introduced by Jia and Benson [22], in which nodes represent United States counties and edges are estimated using the Facebook Social Connectedness Index. The target signal represents the county-wise outcome of the 2012 US presidential election, as values in the range $[-1, 1]$ (indicating the proportion of votes in favour of one candidate *vs.* the other). The graph has 3106 nodes and 22574 edges.

Results   In all cases, the generalised INR achieves a training R^2 close to 1 indicating that the model is indeed able to learn non-trivial signals on non-Euclidean domains. We report the R^2 and mean squared error for all datasets in Table 1. We report a comparison of the true graph signals and those learned by the INR for the bunny and protein datasets in Figure 3. Note that this experiment only verifies that the model can indeed learn the desired signal, but does not directly evaluate the model's ability to generalise. We will test the transferability of the model in-depth in Section 4.2. Having answered **Q1**, in the following sections we mostly focus on known spaces $\mathcal{M}$ or synthetic graphs so that we can better answer the remaining questions by having full control of the data.

Size of the spectral embeddings   Typical INRs take as input the d-dimensional coordinates of points on the sampled lattice. In our general setting, the dimension k of the spectral embeddings is a hyperparameter of the method. To evaluate the impact of k on the performance of the INR (research question **Q2**), we train the same model for different values of k on the Stanford bunny.

We report the results in Figure 5, showing that the model fails to learn a meaningful representation for $k \leq 3$. This is reasonable because at least 3 non-trivial eigenvectors are needed to correctly distinguish the main structural features of the bunny (ears, tail, etc.) in its 3d ambient space, as shown in Figure 4. We also see that, while the INR has no issues in learning the signal for $k = 100$, for lower values of k the model struggles to represent the signal on the ears. Figure 4 again provides a possible explanation for this result, since the first few eigenvectors tend to collapse on the ears and higher frequency eigenvectors are needed to distinguish points towards the

Figure 4: Spectral drawing of the Stanford bunny using the first three non-trivial eigenvectors.

---

[1]Available at `https://graphics.stanford.edu/data/3Dscanrep/`
[2]$D_a = 0.64, D_b = 0.32, F = 0.06, K = 0.062$
[3]Protein Data Bank identifier: 1AA7

Figure 5: **Left:** R^2 *vs. k*; **Right:** signals learned by the INR for $k = 2, 3, 4$.

narrow tips. We will show another consequence of this in Section 4.2. We also mention that the drop in performance for lower values of k on the other two datasets is less pronounced than on the bunny, likely because of their lack of any high-frequency features.

4.2 Transferability of generalised INRs

Because the generalised spectral embeddings are a discrete approximation of the continuous eigenfunctions of the Laplace operator on $\mathcal{M}$, we can apply a trained INR to a different graph realisation of $\mathcal{M}$ as long as its spectral structure is consistent with the training data.

In practical terms, we need to know 1) how to sample new nodes and 2) how the nodes are connected. If we know $\mathcal{M}$, then the problem simply boils down to choosing a sampling strategy for the points and a suitable measure of closeness (*e.g.* a kernel or edge-generating function like the k-nearest neighbours algorithm). If $\mathcal{M}$ is unknown, then we assume to observe a new graph through the same process that generated the training data (*e.g.*, we observe new social interactions among the same or a similar set of people).

Note that, when sampling a new graph from $\mathcal{M}$, the spectral embeddings will be a slightly different (possibly better) approximation of the continuous eigenfunctions. As this effect is more evident on high-frequency eigenvectors, we empirically observed that training the INR with a smaller k improved its transferability. See the supplementary material for more details.

We investigate **Q3** by studying the transferability of generalised INRs in two settings.

Transferring to similar graphs   As a first example, we study the case in which $\mathcal{M}$ is unknown and we only observe the discrete graphs. We consider a stochastic block model (SBM) with two communities of equal size (in total, $n = 1000$), parametrised by an inter-connection probability p and an intra-connection probability r.

We train an INR on a graph with a strong community structure ($p = 0.1, r = 0.5$) and a graph signal indicating the community of each node (effectively a node classification task). Then, we test the INR on graphs sampled in the ranges $p \in [0.1, 1]$ and $r \in [0.1, 1]$ to test the robustness of the model to changes in the community structure.

We report our results in Figure 6. First, we note that perfectly recovering the correct clusters is only theoretically guaranteed in certain regions of the parameter space [1], delimited with an orange line in the figure.[4] We see that the trained INR transfers perfectly to all graphs sampled in this region and that its performance sharply drops only for $p > r$, where graphs have no community structure (see Figure 6 a, b). Additionally, we see that the INR maintains a good performance also in the region between the theoretical boundary and the line $p = r$, *i.e.*, a region in which graphs still exhibit some community structure although perfect recovery is not guaranteed. Overall, this indicates that training the INR on an instance of a graph allows us to transfer it to graphs with a similar structure.

Super-resolution   As a second test case, we consider the super-resolution of a signal. We consider again the Stanford bunny mesh with the same texture graph signal as Section 4.1 and we apply Loop's method for mesh subdivision to obtain a higher-resolution mesh with 139122 nodes and 416929

---

[4]The region is above curve $r = \ln(n)/n \cdot \left(\sqrt{2} + \sqrt{np/\ln(n)} \right)^2$ [1].

(a) $p = 0.1, r = 0.5$ (b) $p = 0.5, r = 0.1$

Figure 6: **Left:** normalised mutual information at test time, evaluating on graphs with different inter- and intra-connection probabilities. We trained the INR on $p = 0.1$ and $r = 0.5$, marked with $\times$ on the plot. The orange line indicates the theoretical boundary above which it is possible to perfectly recover the true signal. Best viewed in colour. **Right:** the first two non-trivial eigenvectors of two SBMs, respectively exhibiting strong and no community structure.

Figure 7: Zoomed-in comparison between the nodes of the training graph (left) and its super-resolved version (right), plotted on a black surface to aid visualisation. Best viewed in high resolution. An interactive version in vector graphics of this figure is available in the supplementary material.

edges [31]. Then, we compute the spectral embeddings for the new graph and predict the signal with the INR trained on the low-resolution graph.

Because the unit-norm eigenvectors are only unique up to sign, the INR will transfer to a different graph only if its eigenvectors are aligned to the training ones (*i.e.*, similar nodes must have similar spectral embeddings — in the previous experiment, we did not have to deal with this problem due to symmetry in the SBM). For simplicity, here we align the eigenbases of the two graphs manually to ensure that they are compatible. However, in many cases, a simple comparison of the eigenvectors' histograms provides a useful heuristic for automatically aligning them.

Figure 8: Density of the test squared error in the super-resolution experiment.

We show in Figure 7 a qualitative comparison between the training and super-resolved signals, from which we see that the INR can predict the graph signal correctly. Quantitatively, since mesh sub-division does not remove the original nodes from the mesh, we can compute the R^2 between the training signal and part of the super-resolved signal. The model achieves an R^2 of 0.39 compared to a training R^2 of 0.99. However, this apparent drop in performance is mostly due to the high-frequency ears of the bunny, for which the model evidently overfits and cannot tolerate even small changes in the eigenvectors. Figure 8 shows the distribution of the squared error between the ground truth

Figure 9: Signals predicted by the conditional INR $f_\theta(\mathbf{e}_i, t)$ at equispaced time steps $t \in [625, 1625]$. All time steps shown were not part of the training set. Also, each test time step is as far as possible from its two closest training samples (*i.e.*, training samples are at $t = 0 \mod 10$ while test samples are at $t = 5 \mod 10$). An animated version of this figure with 600 predicted samples is available in the supplementary material.

and predicted signal, from which we see that the error is close to zero for most of the nodes (note that the y-axis is logarithmic). By ignoring the nodes above the 90th percentile of the squared error distribution, the R^2 score is 0.94. Increasing the size of the spectral embeddings resulted in a better prediction of the ears region (*cf.* Figure 5) at the cost of worse overall transferability.

4.3 Conditional generalised INRs

For **Q4**, we consider the setting in which a generalised INR is conditioned on a latent vector $\mathbf{z} \in \mathbb{R}^q$ to allow the representation of different signals by the same neural network $f_\theta(\mathbf{e}_i, \mathbf{z})$. Unlike the Euclidean setting, here we can investigate two cases: 1) learning a conditional INR for different signals on the same domain (the typical setting), and 2) learning a conditional INR for different signals on different domains.

Reaction-diffusion process For the first case, we train a generalised INR to approximate the Gray-Scott reaction-diffusion process that we used to generate the graph signal in Section 4.1, given by Equation (2). We consider a signal $f(v_i, t)$, where $t \in \mathbb{N}$ is the number of updates since the start of the simulation. We evolve the system for 3000 steps starting from the same random initialisation used in Section 4.1 and we train the INR $f_\theta(\mathbf{e}_i, t)$ using 300 time steps sampled at $t = 0 \mod 10$. The graph is fixed throughout the evolution, so the INR must learn to exploit the conditioning input t to correctly predict the signal at different times.

At test time, we predict the signal for all time steps $t \neq 0 \mod 10$ and compare the prediction with the ground truth samples that we did not use for training. The INR achieves a test R^2 of 0.999 ± 0.006 indicating that it successfully learned to approximate the true dynamics. We report in Figure 9 a few samples predicted by the INR at test time.

Multi-protein INR For the second case, we consider a dataset $\mathcal{D} = \{(\mathcal{M}_m, f_m)\}$ of protein surfaces $\mathcal{M}_m$ with associated electrostatic signals $f_m : \mathcal{M}_m \to \mathbb{R}$ for $m = 1, \ldots, |\mathcal{D}|$, obtained following the same protocol as Section 4.1. We configure the neural network $f_\theta(\mathbf{e}_i, \mathbf{z}_m)$ as an autodecoder [36] where $\mathbf{z}_m \in \mathbb{R}^z$ is a vector of free parameters learned end-to-end alongside the weights of the neural network. We assign a separate vector $\mathbf{z}_m$ to each training sample, allowing the model to find the best latent representation for the dataset. Since the continuous surface and the associated signals are unique to each protein in the dataset, the latent vector $\mathbf{z}_m$ must capture both aspects. We set the latent vector size $z = 8$, which we empirically found to give consistently good performance across datasets. Larger values of z did not significantly improve the performance.

Figure 10: R^2 *vs.* size of the dataset $|\mathcal{D}|$.

We test the ability of the model to represent datasets of different sizes, by sampling random proteins from the dataset used in reference [19]. Figure 10 shows the R^2 of the model for different values of $|\mathcal{D}|$. Understandably, the performance decreases as the number of samples grows, although the model achieves $R^2 \geq 0.9$ for datasets of up to 500 different proteins. Overall, these results indicate that the model can represent many domains and signals with a single set of weights.

| (a) Temperature | (b) Clouds | (c) Wind |

Figure 11: **Top**: prediction of the INR for $t = 4.5$ (randomly chosen, not in the training data) at the original resolution. **Bottom**: The super-resolved versions of the top row. Note that the apparently lighter colours are simply artifacts of the plotting software. Best viewed in colour and high resolution. An animated and uncompressed version of this figure is available in the supplementary material.

4.4 Weather modelling

As a final experiment, we consolidate all results from previous sections to showcase an application of generalised INRs in a real-world setting. We consider signals $f(\mathbf{v}_i, t)$ representing hourly meteorological measurements on the spherical domain of the Earth's surface. Our goal is to train a conditional INR at a given spatial and temporal resolution and then use it to super-resolve the signal over space and time.

Data   We collected data from the National Oceanic and Atmospheric Administration (NOAA) Operational Model Archive and Distribution System, specifically from the Global Forecast System (GFS). The data consists of three different signals representing: the dew point temperature 2m above-ground measured in K (*dpt2m*), the atmosphere's total cloud cover percentage (*tcdcclm*), and the surface wind speed in m/s (*gustsfc*). We consider a 24-hour period sampled at 1-hour increments over an equiangular spherical grid sampled at 1° voxels.[5] We generate a spherical mesh from the 65160 locations of the grid by computing their convex hull with the Qhull software [4], for a total of 193320 edges.

Results   We train a conditional INR $f_\theta(\mathbf{e}_i, t)$ at the given spatial and temporal resolution, for $t = 0, \ldots, 23$. Then, we evaluate its predictions on a high-resolution spherical mesh with 258480 nodes and 773280 edges (obtained with the same procedure of Section 4.2), and at time increments of 30 minutes. We report in Figure 11 the prediction of the INR for a random test time, on both the original mesh and the high-resolution one. We refer the reader to the animated version of the figure available in the supplementary material for a better appreciation of the results. Overall, our results confirm that generalised INRs can model complex real-world signals on non-Euclidean domains, learning a realistic continuous approximation of the signals from low-resolution samples.

5   Conclusion

We have presented the problem of learning generalised implicit neural representations for signals on non-Euclidean domains. Our method learns a continuous approximation of complex non-Euclidean signals while being equivariant to the symmetry group of the domain. We have shown applications of our method on biological, social, and meteorological data, highlighting the potential usefulness of such INRs in a wide range of scientific fields. We hope that future work will explore more real-world applications of our method.

---

[5]Specifically the period from 00:00 to 23:59 of May 9, 2022. All times t given in the text are in hours relative to the start of the period.

References

[1] Emmanuel Abbe. Community detection and stochastic block models: recent developments. *The Journal of Machine Learning Research*, 18(1):6446–6531, 2017.

[2] Matan Atzmon and Yaron Lipman. Sal: Sign agnostic learning of shapes from raw data. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2565–2574, 2020.

[3] Christopher TH Baker. *The numerical treatment of integral equations*. Oxford University Press, 1977.

[4] C Bradford Barber, David P Dobkin, and Hannu Huhdanpaa. The quickhull algorithm for convex hulls. *ACM Transactions on Mathematical Software (TOMS)*, 22(4):469–483, 1996.

[5] Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps and spectral techniques for embedding and clustering. *Advances in Neural Information Processing Systems*, 14, 2001.

[6] Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps for dimensionality reduction and data representation. *Neural Computation*, 15(6):1373–1396, 2003.

[7] Mikhail Belkin and Partha Niyogi. Convergence of laplacian eigenmaps. *Advances in Neural Information Processing Systems*, 19, 2006.

[8] Nuri Benbarka, Timon Höfer, Andreas Zell, et al. Seeing implicit neural representations as fourier series. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2041–2050, 2022.

[9] Yoshua Bengio, Jean-françcois Paiement, Pascal Vincent, Olivier Delalleau, Nicolas Roux, and Marie Ouimet. Out-of-sample extensions for lle, isomap, mds, eigenmaps, and spectral clustering. *Advances in Neural Information Processing Systems*, 16, 2003.

[10] Yoshua Bengio, Pascal Vincent, Jean-François Paiement, Olivier Delalleau, Marie Ouimet, and Nicolas Le Roux. *Spectral clustering and kernel PCA are learning eigenfunctions*, volume 1239. Citeseer, 2003.

[11] Marian Boguna, Ivan Bonamassa, Manlio De Domenico, Shlomo Havlin, Dmitri Krioukov, and M Serrano. Network geometry. *Nature Reviews Physics*, 3(2):114–135, 2021.

[12] Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 34 (4):18–42, 2017.

[13] Benjamin Chamberlain, James Rowbottom, Davide Eynard, Francesco Di Giovanni, Xiaowen Dong, and Michael Bronstein. Beltrami flow and neural diffusion on graphs. *Advances in Neural Information Processing Systems*, 34, 2021.

[14] Ronald R Coifman, Stephane Lafon, Ann B Lee, Mauro Maggioni, Boaz Nadler, Frederick Warner, and Steven W Zucker. Geometric diffusions as a tool for harmonic analysis and structure definition of data: Diffusion maps. *Proceedings of the National Academy of Sciences*, 102(21): 7426–7431, 2005.

[15] Congyue Deng, Or Litany, Yueqi Duan, Adrien Poulenard, Andrea Tagliasacchi, and Leonidas J Guibas. Vector neurons: A general framework for so (3)-equivariant networks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 12200–12209, 2021.

[16] Vijay Prakash Dwivedi and Xavier Bresson. A generalization of transformer networks to graphs. *arXiv preprint arXiv:2012.09699*, 2020.

[17] Vijay Prakash Dwivedi, Chaitanya K Joshi, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Benchmarking graph neural networks. *arXiv preprint arXiv:2003.00982*, 2020.

[18] Vijay Prakash Dwivedi, Anh Tuan Luu, Thomas Laurent, Yoshua Bengio, and Xavier Bresson. Graph neural networks with learnable structural and positional representations. In *International Conference on Learning Representations*, 2022.

[19] Pablo Gainza, Freyr Sverrisson, Frederico Monti, Emanuele Rodola, D Boscaini, MM Bronstein, and BE Correia. Deciphering interaction fingerprints from protein molecular surfaces using geometric deep learning. *Nature Methods*, 17(2):184–192, 2020.

[20] Peter Gray and Stephen K Scott. Autocatalytic reactions in the isothermal, continuous stirred tank reactor: Oscillations and instabilities in the system a+ 2b→ 3b; b→ c. *Chemical Engineering Science*, 39(6):1087–1097, 1984.

[21] Amos Gropp, Lior Yariv, Niv Haim, Matan Atzmon, and Yaron Lipman. Implicit geometric regularization for learning shapes. In *International Conference on Machine Learning*, pages 3789–3799. PMLR, 2020.

[22] Junteng Jia and Austin R Benson. A unifying generative model for graph learning algorithms: Label propagation, graph convolutions, and combinations. *SIAM Journal on Mathematics of Data Science*, 4(1):100–125, 2022.

[23] Elizabeth Jurrus, Dave Engel, Keith Star, Kyle Monson, Juan Brandi, Lisa E Felberg, David H Brookes, Leighton Wilson, Jiahui Chen, Karina Liles, et al. Improvements to the apbs biomolecular solvation software suite. *Protein Science*, 27(1):112–128, 2018.

[24] Nicolas Keriven, Alberto Bietti, and Samuel Vaiter. Convergence and stability of graph convolutional networks on large random graphs. *Advances in Neural Information Processing Systems*, 33:21512–21523, 2020.

[25] Nicolas Keriven, Alberto Bietti, and Samuel Vaiter. On the universality of graph neural networks on large random graphs. *Advances in Neural Information Processing Systems*, 34, 2021.

[26] Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 2015.

[27] Richard B Lehoucq, Danny C Sorensen, and Chao Yang. *ARPACK users' guide: solution of large-scale eigenvalue problems with implicitly restarted Arnoldi methods*. SIAM, 1998.

[28] Ron Levie, Wei Huang, Lorenzo Bucci, Michael Bronstein, and Gitta Kutyniok. Transferability of spectral graph convolutional neural networks. *Journal of Machine Learning Research*, 22 (272):1–59, 2021.

[29] Yunzhu Li, Shuang Li, Vincent Sitzmann, Pulkit Agrawal, and Antonio Torralba. 3d neural scene representations for visuomotor control. In *Conference on Robot Learning*, pages 112–123. PMLR, 2022.

[30] Yaron Lipman. Phase transitions, distance functions, and implicit neural representations. In *International Conference on Machine Learning*, pages 6702–6712. PMLR, 2021.

[31] Charles Loop. Smooth subdivision surfaces based on triangles. 1987.

[32] Andreas Loukas. What graph neural networks cannot learn: depth vs width. In *International Conference on Learning Representations*, 2019.

[33] László Lovász. *Large networks and graph limits*, volume 60. American Mathematical Soc., 2012.

[34] Lars Mescheder, Michael Oechsle, Michael Niemeyer, Sebastian Nowozin, and Andreas Geiger. Occupancy networks: Learning 3d reconstruction in function space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 4460–4470, 2019.

[35] Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In *European Conference on Computer Vision*, pages 405–421. Springer, 2020.

[36] Jeong Joon Park, Peter Florence, Julian Straub, Richard Newcombe, and Steven Lovegrove. Deepsdf: Learning continuous signed distance functions for shape representation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 165–174, 2019.

[37] Edoardo Remelli, Artem Lukoianov, Stephan Richter, Benoît Guillard, Timur Bagautdinov, Pierre Baque, and Pascal Fua. Meshsdf: Differentiable iso-surface extraction. *Advances in Neural Information Processing Systems*, 33:22468–22478, 2020.

[38] Sam T Roweis and Lawrence K Saul. Nonlinear dimensionality reduction by locally linear embedding. *Science*, 290(5500):2323–2326, 2000.

[39] Michel F Sanner, Arthur J Olson, and Jean-Claude Spehner. Reduced surface: an efficient way to compute molecular surfaces. *Biopolymers*, 38(3):305–320, 1996.

[40] Vincent Sitzmann, Julien Martel, Alexander Bergman, David Lindell, and Gordon Wetzstein. Implicit neural representations with periodic activation functions. *Advances in Neural Information Processing Systems*, 33:7462–7473, 2020.

[41] Ivan Skorokhodov, Savva Ignatyev, and Mohamed Elhoseiny. Adversarial generation of continuous images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10753–10764, 2021.

[42] Balasubramaniam Srinivasan and Bruno Ribeiro. On the equivalence between positional node embeddings and structural graph representations. In *International Conference on Learning Representations*, 2020.

[43] Kenneth O Stanley. Compositional pattern producing networks: A novel abstraction of development. *Genetic Programming and Evolvable Machines*, 8(2):131–162, 2007.

[44] Matthew Tancik, Pratul Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. *Advances in Neural Information Processing Systems*, 33:7537–7547, 2020.

[45] Joshua B Tenenbaum, Vin de Silva, and John C Langford. A global geometric framework for nonlinear dimensionality reduction. *Science*, 290(5500):2319–2323, 2000.

[46] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in Neural Information Processing Systems*, 30, 2017.

[47] Lior Yariv, Yoni Kasten, Dror Moran, Meirav Galun, Matan Atzmon, Basri Ronen, and Yaron Lipman. Multiview neural surface reconstruction by disentangling geometry and appearance. *Advances in Neural Information Processing Systems*, 33:2492–2502, 2020.