Moment Constrained Optimal Transport for Control Applications

Abstract

This paper concerns the application of techniques from optimal transport (OT) to mean field control, in which the probability measures of interest in OT correspond to empirical distributions associated with a large collection of controlled agents. The control objective of interest motivates a one-sided relaxation of OT, in which the first marginal is fixed and the second marginal is constrained to a "moment class": a set of probability measures defined by generalized moment constraints. This relaxation is particularly interesting for control problems as it enables the coordination of agents without the need to know the desired distribution beforehand. The inclusion of an entropic regularizer is motivated by both computational considerations, and also to impose hard constraints on agent behavior. A computational approach inspired by the Sinkhorn algorithm is proposed to solve this problem. This new approach to distributed control is illustrated with an application of charging a fleet of electric vehicles while satisfying grid constraints. An online version is proposed and applied in a case study on the ElaadNL dataset containing 10,000 EV charging transactions in the Netherlands. This empirical validation demonstrates the effectiveness of the proposed approach to optimizing flexibility while respecting grid constraints.

1 INTRODUCTION

We address the following control problem 1, motivated by applications involving the coordination of a large population of electricity-consuming agents subject to global constraints, such as a maximum allowable aggregate power consumption.

Consider a set of K agents, each characterized by a state:

$$X_k = (S_k, W_k) \in \mathcal{X}, \quad 1 \le k \le K.$$

Here, S_k denotes an exogenous variable, while W_k is a fully controllable decision variable.

We adopt a distributed control framework, where a central planner coordinates these agents to minimize a cost $c\colon \mathcal{X} \to \mathbb{R}$. Aggregate constraints are enforced on the system, for example, by requiring that the total power consumption of all agents remain below a prescribed threshold: $\sum_{k=1}^{K} f(X_k) \le 0$, where $f\colon \mathcal{X} \to \mathbb{R}^M$ denotes a function characterizing the consumption profile of a single agent. The optimization problem for the central planner can thus be expressed as

$$\min_{W_k} \left\{ \sum_{k=1}^{K} c(X_k) \ : \ \sum_{k=1}^{K} f(X_k) \le 0 \right\}. \tag{1}$$

The use case considered in Section 3 and 4 is the control of a large population of electric vehicles (EVs) whose state S_k is the EV's arrival time at the parking lot and its initial state of charge, and the control W_k is the starting charging time. The cost c in this case could be seen as a penalty for deviating from a planned schedule.

A major challenge with this class of problems is that the computational complexity grows with the number of agents. For instance, the dataset considered in the following analysis contains several thousand vehicle

transactions. Individually coordinating each agent while satisfying its own specific operational constraints is therefore often impractical or may result in suboptimal choices. A popular approach to address this scalability issue is to adopt a mean-field framework. In this setting, the number of agents is assumed to be sufficiently large so that the impact of any single agent on the aggregate variables becomes negligible Lasry & Lions (2007). What matters is then the control of the entire population, modeled through a probability distribution μ of $X = (S, W)$ over $\mathcal{X}$, and we denote ν, the distribution of the exogenous variable S. This gives us the mean field problem approximating 1 when K is large:

$$\min_\mu \Big\{ \int_\mathcal{X} c(x)d\mu(x) \ : \ \forall s \in \mathcal{S} \int_\mathcal{W} d\mu(s,w) = \nu(s) \ \text{ and } \ \int_\mathcal{X} f(x)d\mu(x) \le 0 \Big\}. \tag{2}$$

It is important to note that the optimization is only done on the control variable W and the distribution ν is not modified; this is what we will subsequently call "preserving the distribution of the exogenous variables".

Looking at equation 2, one may interpret the problem as transporting the probability distribution ν to another distribution, as in the optimal transport theory. The key difference here is that the target distribution is not known a priori. In fact, determining this distribution is precisely the objective of the problem, as it represents the optimal charging policy for the fleet of EVs. The only available information about this distribution comes from the aggregate constraints $\int_\mathcal{X} f(x)\,d\mu(x) \le 0$, which will hereafter be referred to as moment constraints. Recent works have introduced the Moment-Constrained Optimal Transport framework (Alfonsi et al., 2020), in which both the initial and final distributions are required to satisfy moment constraints, with the aim of approximating the classical optimal transport problem. In the present work, we consider a slightly modified formulation in which only the final distribution is required to satisfy the moment constraints. We show, for the first time, that this formulation can be interpreted as a mean-field control problem.

Contributions Our contributions are the following:

- We propose a new problem *Moment Constrained Optimal Transport for Control* (MCOT-C) inspired by Optimal Transport and designed to achieve Mean Field Control goals: (i) Agents are controlled to meet a global constraint (ii) Individually, their many strong constraints must be respected, whether physical (an EV cannot be plugged in before it arrives, and its state of charge on arrival or departing time cannot be controlled) or in terms of quality of service (each EV must be fully charged when leaving).

- We propose an algorithm to solve MCOT-C, with a Sinkhorn update on one side and a gradient descend update on the second side.

- We extend this approach to an online setting, where the data about the EVs is progressively discovered and show its efficiency on a case study with a real data set (OpenDataset, 2019).

- Compared with the existing literature, our model allows to take into account new global constraints (slope of global vehicle consumption, for example), to obtain faster results, especially when the size of the control space is small, and to take into account predictions about the future in the form of probability densities.

Litterature Many academic communities are interested in efficiently transforming probability measures. Examples include the fully probabilistic control design of Kárný (1996) and the related linearly-solvable Markov decision framework (Todorov, 2007). Several methods have been designed in the field of mean field control or ensemble control, with applications ranging from power systems to medicine (Hochberg et al., 2006; Chertkov & Chernyak, 2018). These techniques can also be relaxed (Cammardella et al., 2020; Bušić & Meyn, 2018) or regularized, often via a Kullback-Leibler term (Chertkov & Chernyak, 2018; Todorov, 2007) for computationnal reasons. Similar objectives of controlling a large population of electricity-consuming agents have been explored in the distributed control framework (Chertkov & Chernyak, 2018; Cammardella et al., 2020; Bušić & Meyn, 2018). In some cases, the problem is overly constrained by the global constraints, making it difficult or even impossible to identify feasible solutions. To address this, relaxations of the functions f via quadratic penalties have been proposed (Cammardella et al., 2020; Bušić & Meyn, 2018). Additional examples and surveys can be found in Garrabe & Russo (2022).

Optimal Transport (OT) theory first emerged in the 18th century, and more recently has become a significant tool in the machine learning toolbox (Villani, 2008; Peyré et al., 2019). The goal is simply described: given two random variables X and Y, find a joint probability measure π^* for the pair (X, Y) that preserves the marginals, and minimizes some criterion. Several authors have proposed relaxations of the OT problem, such as unbalanced OT where an entropic penalization of the deviation from the marginals is introduced (Chizat, 2017). Relaxations of marginals have been considered to improve numerical performance or to approximate the OT problem (Balaji et al., 2020; Le et al., 2021; Alfonsi et al., 2020) but, to the best of our knowledge, never as a natural representation of a Mean Field control (MFC) problem.

Connections between optimal transport (OT) and control theory have been well established, most notably through the Benamou–Brenier formulation (Benamou & Brenier, 2000), which bridges OT and fluid mechanics. From a control-theoretic viewpoint, this formulation can be interpreted as an optimal control problem in which an initial distribution (at the beginning of a time horizon) is transported toward a target distribution (at the end of the horizon), while minimizing the cumulative cost incurred along the trajectory. More recent research has further strengthened this link by connecting OT with dynamic programming and multi-marginal formulations (Terpin et al., 2024), thereby showing that certain classes of optimal control problems can be recast as OT problems. In the present work, however, we do not adopt the Benamou–Brenier framework; instead, the distributions considered here should be understood as policies over the course of a day, rather than states being transported.

Notations The state space $\mathcal{X}$ is assumed to be a closed subset of $\mathbb{R}^N$ with $N \geq 1$ and we denote $\mathcal{B}(A)$ the set of Borel probability measures on a given set A. For π a bivariate distribution on $\mathcal{X}$, its marginals will be denoted π_1 and π_2 such that $\forall x \in \mathcal{X}, \pi_1(x) = \int_{\mathcal{X}} \pi(x, dy)$ and $\forall y \in \mathcal{X}, \pi_2(y) = \int_{\mathcal{X}} \pi(dx, y)$. We denote $\mathcal{U}(\mu_1, \mu_2) = \{\pi \in \mathcal{B}(\mathcal{X} \times \mathcal{X}) : \pi_1 = \mu_1, \ \pi_2 = \mu_2\}$, the set $\mathcal{B}(\mathcal{X} \times \mathcal{X})$, the set of bivariate distributions having for marginals μ_1 and μ_2. The scalar product for bivariate distributions π and measurables functions g is defined by $\langle \pi, f \rangle := \int_{\mathcal{X} \times \mathcal{X}} f(x, y) \pi(dx, dy)$.

Solutions of the problem considered will involve a family of probability kernels $\{T^\lambda : \lambda \in \mathbb{R}_+^M\}$ defined in equation 8a. For each λ we define π^λ by $\pi^\lambda(dx, dy) = \mu_1(dx)T^\lambda(dx, dy)$, and let $\mu^\lambda = \pi_2^\lambda$ denote the second marginal:

$$\mu^\lambda(A) := \int \mu_1(dx) T^\lambda(x, A), \qquad A \in \mathcal{B}(\mathcal{X})$$

2 MOMENT CONSTRAINED OPTIMAL TRANSPORT FOR CONTROL

2.1 Statement of the problem

The goal of the Optimal Transport problem introduced by Kantorovich (1942) is to find a transport plan π minimizing a cost $\langle \pi, c \rangle = \int_{\mathcal{X} \times \mathcal{X}} c(x, y) d\pi(x, y)$ subject to the constraint that the marginals of π are exactly μ_1 and μ_2. In this section, we aim to formulate the MFC problem introduced in equation 2, in the framework of Optimal Transport, where the second marginal is not fully specified but must belong to a set of distributions respecting moment constraints.

In this framework, the first marginal π_1 corresponds to a nominal behavior μ_1, which is given, whereas the second marginal, denoted by π_2, corresponds to the optimized distribution within the following *moment class*,

$$\mathcal{P}_f = \{\mu \in \mathcal{B}(\mathcal{X}) : \langle \mu, f^m \rangle \leq 0 \ \forall \ 1 \leq m \leq M\} \tag{3}$$

where $f : \mathcal{X} \to \mathbb{R}^M$ encodes M constraints. An equality constraint $\langle \mu, f^m \rangle = 0$ can be expressed as a pair of inequality constraints, thus equality constraints can also be imposed when required.

Recall that in MFC, the distribution ν of the exogenous variable is fixed. In this framework, this implies that the bivariate distribution π belongs to

$$K(\mu_1) = \{\pi \in \mathcal{B}(\mathcal{X}, \mathcal{X}) : \pi((x_s, x_w), (y_s, y_w)) = \mu_1(dx_s, dx_w) T((x_s, x_w), dy_w) \delta_{x_s}(dy_s)\}$$

where δ is the dirac measure, and T ranges over all probability kernels. That is, if $\pi \in K(\mu_1)$, then $\int_{\mathcal{W}} \pi_2(y_s, dy_w) = \int_{\mathcal{W}} \pi_1(y_s, dx_w) = \nu(y_s)$, which corresponds to our goal of preserving ν on $\mathcal{S}$, for both marginals.

Lastly, we will use the following Kullback Leibler (KL) regularizer, similar to that in Cuturi (2013):

$$D_{\mathrm{KL}}(\pi \| \mu_1 \otimes \mu_2) = \int_{\mathcal{X} \times \mathcal{X}} \log\left(\frac{\pi(x,y)}{\mu_1(x)\mu_2(y)}\right) \pi(dx, dy) \tag{4}$$

However, in our case, μ_2 is not the second marginal of π, but left as a design parameter (in our case the second marginal is not known a priori, as it is only constrained to belong to $\mathcal{P}_f$). This regularizer is introduced for three reasons. First, the minimization of a KL-divergence enforces absolute continuity between μ_2 and π_2, meaning that the support of π_2 is included in the support of μ_2. In practice, one defines the support of μ_2 as the set of physically feasible or desirable states and controls (e.g., ensuring that electric vehicles are charged at the end of their time slot or that charging does not occur before arrival), thereby preventing π_2 from assigning mass to physically impossible or undesirable states. Second, unlike in certain mean-field control methods where the entropic penalization is taken with respect to μ_1 (Bušić & Meyn, 2018), here one has the flexibility to design μ_2. For instance, one may rather rely on a heuristically designed μ_2 that may give faster convergence, or, in the absence of one, choose a uniform distribution over the previously defined support (that may be different than the one of μ_1). Finally, it has a computational interest, as it allows for obtaining explicit solutions, as shown in Section 2.

This allows us to introduce the Mean Field Control problem:

Problem MCOT-C: *Moment Constrained Optimal Transport for Control*

$$\min_{\pi}\big\{\langle \pi, c\rangle + \varepsilon D_{\mathrm{KL}}(\pi \| \mu_1 \otimes \mu_2) : \pi \in K(\mu_1), \ \pi_2 \in \mathcal{P}_f\big\} \tag{5}$$

2.2   Dual problem

This subsection defines the dual and the theoretical properties needed for the algorithm but more details on duality theory and proofs may be found in the appendices A and B. The theoretical results of this problem in the Gaussian case are presented in appendix C. An example that illustrates the impact of regularization can be found in appendix D.

Assumptions   Assumptions are required for the existence of optimizers and desirable properties of the dual:

(A1) $c\colon \mathcal{X} \times \mathcal{X} \to \mathbb{R}_+$ and $f\colon \mathcal{X} \to \mathbb{R}^M$ are continuous, and there is an open neighborhood $N \subset \mathbf{R}^M$ containing 0 such that $\mathcal{P}_{f-r}$ is non-empty for all $r \in N$.

(A2) μ_1 and μ_2 have compact support, and the problem is feasible under perturbations: for any $r \in N$, there is π satisfying $\pi_2 \in \mathcal{P}_{f-r}$ and $\pi_1 = \mu_1$.

(A3) $\Sigma^0 := \mathrm{Cov}\,(Y)$ is positive definite when $Y \sim \mu_2$.

Dual   The dual of MCOT-C is by definition the function $\varphi^*\colon \mathbb{R}_+^M \to \mathbb{R} \cup \{-\infty\}$,

$$\varphi^*(\lambda) = \varepsilon \min_{\pi}\big\{-\varepsilon^{-1}\langle \pi, \ell_0^\lambda\rangle + D_{\mathrm{KL}}(\pi \| \mu_1 \otimes \mu_2) : \pi \in K(\mu_1)\big\} \tag{6}$$

where we introduce the notation $\ell_0^\lambda(x,y) = -\lambda^\intercal f(y) - c(x,y), \quad \forall x, y \in \mathcal{X}$

For each $\lambda \in \mathbb{R}_+^M$, $\varepsilon > 0$ and $x = (x_s, x_w) \in \mathcal{X}$, we denote

$$B_{\lambda,\varepsilon}(x) = \varepsilon \log \int_{y_w \in \mathcal{W}} \exp\big(\varepsilon^{-1}\ell_0^\lambda((x_s, x_w), (x_s, y_w))\big)\mu_2(dy_w) \tag{7}$$

Proposition 1. *Subject to (A1)–(A3),*

(i)   *The infimum equation 6 gives $\varphi^*(\lambda) = -\langle \mu_1, B_{\lambda,\varepsilon}\rangle$.*

(ii)   *The maximizer is $\pi^\lambda(x,y) = T^\lambda(x,y)\mu_1(x)$ with $\forall x = (x_s, y_s) \in \mathcal{X}, \forall y = (x_s, y_s) \in \mathcal{X}$*

$$T^\lambda(x,y) = \mu_2(y)\delta_{x_s}(y_s)\exp(L^\lambda(x,y)), \qquad L^\lambda(x,y) = \varepsilon^{-1}\{l_0^\lambda(x,y) - B_{\lambda,\varepsilon}(x)\}, \tag{8a}$$

and $\mu^\lambda(y) = \pi_2^\lambda(y) \quad \forall y \in \mathcal{X}$

(iii) *There is no duality gap: there is a unique $\lambda^* \in \mathbb{R}_+^M$ satisfying*

$$\varphi^*(\lambda^*) = \min_{\pi} \{\langle \pi, c \rangle + \varepsilon D_{KL}(\pi \| \mu_1 \otimes \mu_2) : \pi \in K(\mu_1), \ \pi_2 \in \mathcal{P}_f\} \tag{8b}$$

It is convenient to make the change of variables $\zeta = \varepsilon^{-1}\lambda$, and consider

$$\mathcal{J}(\zeta) := -\varepsilon^{-1}\varphi^*(\varepsilon\zeta)$$

We turn next to the representation of the derivatives of the dual function. The quantity $\varepsilon^{-1}B_{\varepsilon\zeta,\varepsilon}(x)$ is a log moment generating function for each x; for this reason, it is not difficult to obtain suggestive expressions for the first and second derivatives with respect to ζ.

Proposition 2. *The function $\mathcal{J}$ is convex and continuously differentiable. The first and second derivatives of $\mathcal{J}$ admit the following representations:*

$$\nabla \mathcal{J}(\zeta) = m^\lambda, \qquad \nabla^2 \mathcal{J}(\zeta) = \Sigma^\lambda \tag{9a}$$

in which $m_i^\lambda = \langle \mu^\lambda, f_i \rangle = \mathsf{E}^\lambda[f_i(Y)]$ for each i, and the Hessian equation 9a coincides with the conditional covariance:

$$\Sigma^\lambda = \mathsf{E}^\lambda[f(Y)f(Y)^\intercal] - \mathsf{E}^\lambda\big[\mathsf{E}^\lambda[f(Y) \mid X]\mathsf{E}^\lambda[f(Y) \mid X]^\intercal\big] \tag{9b}$$

It follows that $\mathcal{J}$ is strictly convex:

Lemma 1. *Suppose that (A1)–(A3) hold. Then, the covariance Σ^λ is full rank for any $\lambda \in \mathbb{R}_+^M$.*

2.3 Algorithm: Semi-Sinkhorn with Gradient Descent

Algorithm 1 Semi-Sinkhorn with Gradient Descent

Input: μ_1, C, f
$\zeta^0 \leftarrow \mathbf{0_M}$
$k \leftarrow 0$
while $k \leq Kmax$ **do**
$\quad u_i^{k+1} \leftarrow \mu_{1,i}/\sum_j K_{i,j}e^{-\zeta_k^\intercal f}$
$\quad \zeta^{k+1} \leftarrow \zeta^k + \sum_{i,j} f_j u_i^k K_{i,j}e^{-\zeta^{k^\intercal} f}$
$\quad \zeta^{k+1} \leftarrow \max\{0, \zeta^{k+1}\}$
$\quad k \leftarrow k+1$
end while

For numerical experiments, the state space $\mathcal{X}$ will be discretized and we will denote by N its cardinality. The cost will be represented by a matrix $C \in \mathbb{R}_+^{N \times N}$. The solution to MCOT-C obtained in Proposition 1 may be expressed as

$$\pi_{i,j}^* = u_i K_{i,j} \exp\left(-\zeta^{*\intercal} f_j\right) \tag{10}$$

where K is the Gibbs kernel defined by $K_{i,j} = \exp(-C_{i,j}/\varepsilon)\mu_{2,j}$ and $u_i = \mu_{1,i}/\sum_j C_{i,j}e^{-\zeta^{*\intercal} f}$. As shown in Proposition 2, it is possible to obtain a gradient descent algorithm 1, which looks similar to the Sinkhorn Algorithm (Cuturi, 2013), the difference being the update of ζ^k.

It is also possible to perform Newton's method rather than gradient descent by changing the update of ζ_k by

$$\zeta^{k+1} \leftarrow \zeta^k + (\Sigma^{\varepsilon\zeta_k})^{-1} \sum_{i,j} f_j u_i^k C_{i,j} e^{-\zeta_k^\intercal f}$$

where $\Sigma^{\varepsilon\zeta_k}$ is the Hessian defined in 9b. In cases where the starting point ζ^0 is close to the optimum ζ^*, we can obtain quadratic convergence (C.T.Kelley, 1999).

3 Use Case: EV Charging

3.1 Presentation of the use case

Consider a large fleet of electric vehicles (EVs) arriving to a charging station at random times and with random state of charge, according to an initial law ν_0. There is a central planner whose goal is to maintain

constraints for the aggregate power consumption, as well as constraints for each vehicle owner. The vehicles arrive during the period $[9am, 10:30am]$, and must be fully charged by 5pm.

The goal is power tracking: total power consumption should follow a reference signal (r_t) over a time period $[t_1, t_2]$, with $9am \leq t_1 < t_2 \leq 5pm$. This can be formulated as an MCOT-C problem over the space of distributions on $\mathcal{X} = \mathcal{S} \times \mathcal{W}$ with $\mathcal{S} = [0, T] \times [0, 1]$ and $\mathcal{W} = [0, T]$.

The two first coordinates of $x \in \mathcal{X}$ are the time and the battery state of charge at the arrival and the third is the time when the EV will start charging, called the *plugging time*; so $x \in \mathcal{X}$ is of the form $x = (t_a, b, t_c)$. At each iteration, a gradient is calculated on $\mathcal{X} \times \mathcal{W}$, with complexity of $n_{\text{time}}^3 \times n_{\text{battery}}$, with $n_{\text{time}} = 25$ and $n_{\text{battery}} = 20$, being the number of discretization points in time and battery state of charge. We use the MCOT-C problem presented in Section 2 with $\varepsilon = 0.03$ being a compromise between computational stability and having a low value (as any non-negative value will enforce the physical constraints). We consider a version of problem MCOT-C with μ_1 modeling the naive decision rule in which a vehicle initiates charging on arrival:

$$\mu_1(t_a, b, t_c) = \begin{cases} \nu(t_a, b) \text{ if } t_a = t_c \\ 0 \text{ otherwise} \end{cases}$$

Initiation of charging must be after the arrival time (physical constraint) and every vehicle must be fully charged no later than 5pm (quality of service constraint). The following distribution meets these requirements, $\mu_2(t_a, b, t_c) = \mathbf{Unif}_{[t_a, T - \frac{1-b}{v}]}(t_c)$, with v being the charging speed and $\mathbf{Unif}_{[a,b]}$ being the density of uniform distribution over $[a, b]$. It is assumed that drivers wish to initiate charging as soon as possible: this makes it easier for the driver to manage an unforeseen event and may make it easier for the central planner to respond to a grid contingency. This preference is modeled through the cost $c((., ., t_c^x), (., ., t_c^y)) = (t_c^x - t_c^y)^2$.

3.2 Numerical Results

EV charging without unplugging The first results described here impose an additional constraint: once charging begins, it cannot be interrupted until the vehicle is fully charged. In the following simulations, a constraint on power consumption is imposed for the time period beginning at $t_1 = 10am$ and ending at $t_2 = 12pm$. As the optimizer μ^* will be mutually absolutely continuous with respect to μ_2, both physical constraints and constraints on quality of service are imposed through choice of μ_2. In Figure 1(a), the constraints enforced on μ_2 can be observed:

- Quality of Service constraint: At 5 pm, all EVs must be fully charged. Thus, if a vehicle needs Δt minutes to charge, then the probability of connecting between $5pm - \Delta t$ and 5pm is zero. This is observed by the completely white lower right triangle.

- Physical constraint: Vehicles cannot charge before arriving, so there is no mass probability before 10am for vehicles arriving at 10am.

Figure 1: For vehicles arriving at 10am : (a) μ_1 (b) μ_2 designed to encode physical and quality of service constraints; (c) optimized μ without gradient control; (d) optimized μ with gradient control.

Figure 2: (a) optimized consumption compared to the nominal with unplugging disabled; (b) optimized consumption with unplugging enabled; (c) optimal consumption with constraint infeasible without unplugging.

These constraints are found in the μ_λ showed in Figure 1(b) and 1(c), as μ_λ is a reweighting of μ_2. Aggregated consumption displayed in Fig. 2 (a) shows that the first vehicles to arrive will start charging, but most of those arriving just before 10:00 am will initiate charging only if they arrive with a high battery level so that they are fully charged before the start of the constraint window from 10:00 am to 12:00 pm.

EV charging with unplugging The model can be extended by authorizing a vehicle to interrupt and restart charging. In this case, $\mathcal{X}$ is extended with two extra time dimensions corresponding to an unplugging time and a re-plugging time. A second term is included in c that is quadratic in the difference of these times, designed to discourage charging interruption.

We find that unplugging does not impact significantly the optimal solution. Fig. 2 (a) and (b) provide a comparison. Only a slight difference is visible before 10 am: A number of vehicles start to charge before the constraint, stop at 10pm and restart afterwards. However, in some cases, this extra flexibility in charging is necessary to obtain a feasible solution. Fig. 2 (c) shows results obtained when power consumption is not permitted in the middle of the day. In any feasible solution, a portion of vehicles stop charging for a period before they are fully charged.

Gradient control to flatten the curve For real-life applications, controlling overall consumption over part of the day through equality of consumption to a predefined signal can lead to a peak when the constraint is released. This phenomenon, due to the penalization of distant charging times, is observed in the different plots of Fig. 2. Consumption can be smoothed by introducing the derivative constraints

$$\forall t \in [0, T], |\langle g_t, \mu \rangle| \leq g_{\max}$$

where $g_t = f_{t+1} - f_t$. In this example, $g_{\max} = 0.2$, thus the overall consumption must not increase by more than 0.2 per hour, which is what we observe in Fig. 3: consumption at 12pm increases more slowly. We can also see the impact of the constraint on the gradient by

Figure 3: Optimal consumption with and without gradient control of the overall consumption

looking at the difference between Figure 1(b) and 1(c). In both cases, vehicles arriving with a high battery level are put to charge first. This comes from the quadratic penalty on the start of the charging time: We prefer to charge those which will quickly be completely charged and which will free up space for those which will take longer.

Faster results than HJB methods

Figure 4: Computation time for MCOT and PDMP (PDMP algorithm is stochastic and error bars are computed over 10 simulations)

A common method in the mean-field control literature is to go through Hamilton-Jacobi-Bellman (HJB) equations, discretize these equations and solve them numerically. We compare ourselves here with an article (Seguret et al., 2024) that applies this type of method to EV charging, via a generation of Piecewise Deterministic Markov Processes (PDMP). The case study here is a flat signal, and both methods seek to track this signal. As the PDMP method can only take into account one fixed starting time, we assume that all vehicles arrive at 9am. We note in Figure 4 that our MCOT method is faster in this case, whatever n_{time}. For higher values of n_{time}, MCOT's computation time increases quadratically, and it could be improved by using Monte Carlo methods to simulate trajectories (as the PDMP method does). Apart from computation time, another advantage of the MCOT method is the flexibility of the model considered: in particular, vehicles arriving at different times can be considered.

4 ONLINE MCOT-C FOR EV CHARGING

In this section, we provide an online version of MCOT-C and test it on a real dataset.

4.1 Formulation of Online MCOT-C

First, while some theoretical models assume perfect knowledge of the battery level at each time step (Séguret, 2023), this value is hard to obtain in practice even if estimates are available (Rezvanizaniani et al., 2014) and existing datasets do not take this data into account (Amara-Ouali et al., 2021). Our choice on this subject is to focus on the leaving time t_l and the charging need Δt_n, which is the charging time requested by the EV owner. These parameters are easier to access and are consistent with other articles studying real datasets (He et al., 2012; Sadeghianpourhamami et al., 2018). Arriving EVs are therefore defined on the following state space:

$$\mathcal{S} = \underbrace{[0, 24]}_{\substack{\text{Arriving time} \\ t_a}} \times \underbrace{[0, 24]}_{\substack{\text{Leaving time} \\ t_l}} \times \underbrace{[0, 24]}_{\substack{\text{Charging need} \\ \Delta t_n}} \times \underbrace{\{1, n_{\text{power}}\}}_{\substack{\text{Max power} \\ p_{max}}} \tag{11a}$$

At each time step $t \in [0, 24]$, EVs are controlled through their charging starting time t_c. The control space is thus defined as:

$$\mathcal{W}^{(t)} = \underbrace{[t, 24]}_{\text{Plugging time } t_c} \tag{11b}$$

and we define the product space: $\mathcal{X}^{(t)} = \mathcal{S} \times \mathcal{W}^{(t)}$. At each time step $t \in [0, 24]$, this sequence of actions will take place:

1. New EVs arrive at the charging station and are added to the list of vehicles already present and not charging yet $\{S_i^{(t)}\} = \{S_i : t_a^i \leq t \text{ and } t_c^i \geq t\}$. The empirical $\nu^{(t)}$ is updated:

$$\nu^{(t)}(s) = \begin{cases} \frac{1}{N_t} \sum_i \delta(s - S_i^{(t)}) & \text{if } t_a \leq t \\ \frac{N}{N_t} \nu(s) & \text{if } t_a > t \end{cases} \tag{12a}$$

where $N_t = \int_{\mathcal{S}} \sum_i \delta(s - S_i^{(t)}) ds + N \int_{\mathcal{S}} \nu(s) \mathbf{1}_{t_a > t}(s) ds$ is the number of vehicles already arrived and not charging plus the number of vehicles that are estimated to arrive.

2. $\mu_1^{(t)}$ is defined by the "Plug when Arrive" strategy: $\forall s = (t_a, t_l, \Delta t_n, p) \in \mathcal{S}$,

$$\mu_1^{(t)}(s, t_c) = \nu^{(t)}(s)\delta(t_c - t_a) \tag{12b}$$

3. $\mu_2^{(t)}$ is defined as "Plug with a uniform distribution" strategy:

   $\forall s = (t_a, t_l, \Delta t_n, p) \in \mathcal{S}, \ t_c \in \mathcal{W}$,

$$\mu_2^{(t)}(s, t_c) = \begin{cases} \mathbf{Unif}_{[t_a, t_l - \Delta t_n]}(t_c)\nu^{(t)}(s) & \text{if } t_a > t \\[2mm] \mathbf{Unif}_{[t, t_l - \Delta t_n]}(t_c)\nu^{(t)}(s) & \text{if } t_a \le t \end{cases} \tag{12c}$$

   where $\mathbf{Unif}[a, b]$ is the density of the uniform distribution on the segment $[a, b]$. For the sake of simplicity, we assume that there is no outlier (no vehicle that would require more charging time than the difference between their arrival time and leaving time in particular). As in Section 3, μ_2 is designed to incorporate the strong constraint of respecting the quality of service through the absolute continuity of μ with μ_2 (due to the KL term).

4. The central planner will minimize Equation (5) to obtain:

$$\pi^{(t)} = \underset{\substack{\pi \in K(\mu_1^{(t)}) \\ \pi_2 \in \mathcal{P}_{f^{(t)}}}}{\arg\min} \ \langle \pi, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi \| \mu_1^{(t)} \otimes \mu_2^{(t)})$$

   The function c chosen here is a quadratic penalization: $c((s^x, t_c^x), (s^y, t_c^y)) = (t_c^x - t_c^y)^2$. In this case, as we compare it with the "Plug When Arrive" strategy for which $t_c^x = t_a^x$, c is a penalty for starting charging long after the vehicle arrives.

5. For each vehicle $S_i^{(t)}$, its plugging time t_c^i is randomly chosen according to $\pi_2^{(t)}(S_i^{(t)}, .)$. f is then updated as: $f^{(t+1)} = f^{(t)} + \frac{1}{N} \sum_{t_c^i = t} f(S_i^{(t)})$. Vehicles $S_i^{(t)}$ such that $t_c^i = t$ begin their charging.

4.2 Algorithm

In Algorithm 2, $Alg(\zeta^{(t)}, \mu_1, \mu_2)$ returns $\zeta^{(t+1)}$ the value of Algorithm 1 with the stopping criterion $N_t \|(\langle f^{(t)}, \mu_{\zeta^{(t)}} \rangle)^+\| \le N\kappa$ and $(.)^+$ is the positive part function: $\forall x \in \mathbb{R}^M, (x)_m^+ = \max(0, x_m)$. The norm $\|\|$ can be chosen as desired but a good candidate is the infinite norm. In general, κ is chosen relatively small, and with this norm, $N\kappa$ corresponds to the maximum error on all the vehicles that we can afford to have, we can estimate that this error evolves linearly with N, which explains the multiplication by N (it is important to remember that N is the order of magnitude of the vehicles that will arrive during the day). We define the convergence error at time t as $\mathcal{E}_t(\zeta) = \frac{N_t}{N} \|(\langle f^{(t)}, \mu_{\zeta^{(t)}} \rangle)^+\|$ and ν_r, the real arrival law of EVs. With the definitions of $\mu_2^{(t)}$ and $\mu_1^{(t)}$ in Equations (12) and Proposition 1, we define F_ζ as: $\forall s \in \mathcal{S}, \ F_\zeta(s) =$

$$\begin{cases} \dfrac{\int_{\mathcal{W}} \mu_\zeta^{(t)}(s, t_c) f(s, t_c) dt_c}{\nu^{(t)}(s)} & \text{if } \nu^{(t)}(s) \ne 0 \\[3mm] 0 & \text{otherwise} \end{cases}$$

Algorithm 2 Online MCOT-C

Input: ν, N, $(f_m)_{1 \le m \le M}$, κ
Output: V= {} the list of vehicles with their plugging time
S$\leftarrow$ {}
$\zeta^0 \leftarrow \mathbf{0_M}$
for t **from** 0 **to** T **do**
    Add to S, vehicles that arrived at time t
    Compute N_t
    Update ν, μ_1 and μ_2 as in Equations (12)
    $\zeta_m \leftarrow Alg(\zeta, \mu_1, \mu_2, y)$
    for S_i in S **do**
        t_c is generated according to $\mathrm{Mu}(\zeta, \mu_1, \mu_2, (S_i, .))$

        if $t_c = t$ **then**
            $f \leftarrow f - \frac{1}{N} f(S_i)$
            S_i is removed from S and (S_i, t_c) is added to V
        end if
    end for
end for

Proposition 3. **(i)** $\mathcal{E}_{t+1}(\zeta_t)$ *is bounded by κ, a stochastic term, and a term corresponding to a poor prediction of the law ν:*

$$\mathcal{E}_{t+1}(\zeta_t) \leq \kappa + \left\| \left(\sum_{t_a^i = t+1} \frac{F_\zeta(S_i^{(t+1)})}{N} - \mathbb{E}_{\nu_r}[F_\zeta \mathbf{1}_{t_a=t+1}] \right)^+ \right\| + \left\| \left(\mathbb{E}_{\nu_r}[F_\zeta \mathbf{1}_{t_a=t+1}] - \mathbb{E}_{\nu}[F_\zeta \mathbf{1}_{t_a=t+1}] \right)^+ \right\|$$

(ii) *The second term could be bounded with Bienaymé-Tchebychev inequality to obtain:*

$$\mathbb{P}\left(\left\| \left(\sum_{t_a^i = t+1} \frac{F_\zeta(S_i^{(t+1)})}{N} - \mathbb{E}_{\nu_r}[F_\zeta \mathbf{1}_{t_a=t+1}] \right)^+ \right\| \geq \kappa_0 \right) \leq \frac{\mathbb{V}_{\nu_r}[F_\zeta \mathbf{1}_{t_a=t+1}]}{N \kappa_0^2}$$

Thus, starting from scratch at each time step is unnecessary, and the optimization made in the previous step offers a good ζ to start with. This starting point is better if (i) the estimation of the arrival law of the vehicles ν is close from the real arrival law of vehicles ν_r and (ii) if N, the order of magnitude of EVs is large.

4.3 Data Overview

The dataset used in this paper is composed of 10.000 random transactions from public charging stations operated by EVnetNL in the Netherlands (OpenDataset, 2019), in the year 2019. For each transaction, several pieces of information are provided including the arrival time t_a, the leaving time t_l, the plugging time Δt_n, and the max power P. A more detailed description could be found in (Refa & Hubbers, 2019) and this dataset have already been used for clustering algorithm (Straka & Buzna, 2019) but not yet for Mean Field Control Algorithm.

There is a difference between weekdays and weekend days, so in this paper, we will consider the 7253 transactions happening during weekdays and divide them randomly. 90% of these weekdays will form a training set of 231 days (6540 transactions) and will be considered historical data. A test day is created with the remaining 10% of weekdays (21 days : 674 transactions) by grouping the corresponding 713 vehicle arrivals. The predicted distribution ν is computed on the training set considered historical data and $N = \frac{6210}{9} = 690$ is the number of vehicles expected to arrive on this test day. In (5), we set $\varepsilon = 0.1$ because we want a relatively low value to limit the impact of entropic relaxation (term in Kullback Leibler), but not too low, as this risks posing computational problems (because of the ε^{-1} in the exponential in Proposition 1.

To compute efficiently the gradient $G(\zeta_k)$ at each iteration of Algorithm 2, we need to discretize the state space $\mathcal{X}$: The day is divided into $T + 1 = 97$ steps (indexed from 0 to T) with a stepsize Δt of 15 minutes, which allows rapid grid constraint changes to be taken into account. For the power discretization, we group each EV between 4kW, 7.5kW, and 12kW. This choice of discretization is standard (used for example in (Sadeghianpourhamami et al., 2018)). We assume here that vehicles connected the day before are not affected by our strategy, because they are already connected, but their consumption is taken into account in order to come closer to reality, particularly in the case of controlling the gradient of aggregate consumption. We therefore consider the aggregate consumption of vehicles arriving throughout the day and that of vehicles arriving the day before (this impact is mainly present before 8 a.m.).

4.4 Control of the aggregated consumption

On Fig. 5, the nominal consumption in blue corresponds to what is expected by the charging station, these are the historical data with the plugging strategy μ_1 "Plug when Arrive". On (a), we can see the difference with the consumption for the real arrival of EV during the day with the same plugging strategy. The first peak in the morning lasts longer, while the second peak seems to be weaker. On (b), a constraint imposed by the charging station over the power consumed of $r_f = 650$kW is added through the moment constraints: define for each m the function f_m via $f_m(s, t_c) = p_{\max}$ if $m \in [t_c, t_c + \Delta t_n]$, $f_m(s, t_c) = 0$ otherwise, and impose for each m the constraint $\langle f_m, \mu \rangle - r_f \leq 0$.

This value of 650kW is chosen arbitrarily here, and any other can be chosen as long as it remains realistic. This optimization makes it possible to exploit flexibility while respecting the imposed constraint, despite the

Figure 5: (a) Consumptions for the "Plug When Arrive" μ_1 strategy with the arrival of EV predicted with ν and with the real distribution of EV; (b) Optimized Consumption for a constraint of 650kW for the aggregated consumption; (c) Optimized consumption for the same maximum power constraint and a constraint of 120kW/h for the gradient of the aggregated consumption.

prediction error on the length of the first peak. Peaks above the maximum constraint correspond to unforeseen arrivals of a large number of vehicles that must connect directly. It can also be due to the convergence not completely achieved by the algorithm, which depends on the value of κ here chosen at 10kW.

4.5 Control of the gradient of the aggregated consumption

Another constraint that we want to respect in order to preserve the grid stability is the speed with which consumption will increase or decrease. On Fig. 5 (a) (b), we see a strong peak at the start of the day. We will seek to smooth this peak by imposing a constraint on the gradient of the power consumed. On (c), this constraint imposed by the charging station of $r_g = 100$kW/h is added through the moment constraints: $\forall m \in [0, T-1], \forall (s, t_c) \in \mathcal{X}^{(t)}, g_m(s, t_c) = f_{m+1}(s, t_c) - f_m(s, t_c)$ and we impose: $\forall m \in [0, T-1], -r_g \leq N\langle g_m, \mu \rangle \leq r_g$.

Figure 6: When the prediction ν differs greatly from the reality

This addition of constraints makes it possible to smooth out the slope which begins around 6am. There are always irregularities due to deviation from prediction and the slight excess of the constraint on the first peak can be explained by the maximum exploitation of the flexibility of the vehicles to respect the gradient constraint, which does not leave enough flexibility when vehicles arrive between 9am and 3pm and have to be connected directly.

4.6 Sensitivity to the difference between actual EV arrival and its prediction

This model depends on the quality of the prediction ν made for the rest of the day. In this part, we try to test the robustness against this quality of prediction, by twisting the previous prediction: the central planner expects 30% less vehicles before 12am and 30% more vehicles after. The aggregated power consumption associated to this prediction is shown in blue in Fig. 6. We can thus observe that compliance with the same maximal power constraint of $650kW$ is still obtained and the consumption is very close to Fig. 5 (b). We therefore have a certain robustness of the model concerning the prediction ν. This robustness is

surely obtained here by the fact that we can change the connection time of a previously arrived vehicle as long as it is not connected. The algorithm can therefore, in the event of an unexpected arrival of vehicles to be connected immediately, postpone the connection time of less priority vehicles. But this poorer prediction comes at a cost: when comparing $\langle \pi, c \rangle$ between the case where the prediction is close (shown in figure 5 (a)) and this case, we find that the average time between arrival time t_a and connection time t_c increases from 11 minutes to 12 minutes. Having a less accurate prediction will therefore make less optimal use of flexibility.

4.7 Comparison with a non-predictive algorithm

Other algorithms and methods have been proposed in the literature for charging electric vehicles while respecting global constraints, such as IOCS (Alinia et al., 2022). Compared to this algorithm, our approach allows two new things. Firstly, the formulation as a mean-field control problem allows us to scale up to a very large number of vehicles. Thus, IOCS has a complexity in $O(N^2)$ with N the number of vehicles, whereas ours has a linear complexity $O(N)$. Also, the addition of a prediction allows us to find better solutions. In Fig. 7, we compare our MCOT method with IOCS modified to have the same control (plugging at a given instant). Here, we assume that the global constraint

Figure 7: Comparison with IOCS (no prediction)

cannot be exceeded and that vehicles that cannot be plugged will be rejected. All vehicles have the same priority to connect, and our metric for comparing the two algorithms will therefore be the number of vehicles accepted with the same maximum power constraint of 650kW. On this dataset, MCOT rejects 23 vehicles (3.4% of EVs) while IOCS rejects 33 vehicles (4.9% of EVs). In particular, we see a difference between noon and 3 p.m., when the prediction seems to allow more vehicles to be charged.

5 CONCLUSIONS

One-sided moment relaxation of OT problem provides a very natural representation setting for tracking applications in control. In such applications, the OT problem is often infinite-dimensional (e.g. trajectories of agents). Instead of using approximations techniques for OT, MCOT-C leads to a tractable algorithm by directly considering only the distribution moments that are relevant for control. Furthermore, KL-term has a dual role in MCOT-C: a relaxation term as in many other machine learning algorithms, but it also enables to enforce the constraints on the dynamics via the choice of μ_2 and absolute continuity imposed by KL. There are many directions for future research:

• The "Semi Sinkhorn" algorithm might be improved through the introduction of advanced optimization techniques (e.g., proximal methods or momentum).

• In some problems, the size of state space $\mathcal{X}$ is very large, or even infinite (e.g. cases where a continuous $\mathcal{X}$ space cannot be discretized). As the complexity of the algorithm increases with the size of this state space, it may be necessary to adapt this method to limit computation time, by using Monte Carlo-type methods, i.e. generating a number of trajectories to obtain an approximation of the gradient, instead of calculating it exactly.

• We believe that representing distributions by their moments to perform optimal transport has broader applications in machine learning and control. We aim to explore its potential in other contexts.

References

Aurélien Alfonsi, Rafaël Coyaud, Virginie Ehrlacher, and Damiano Lombardi. Approximation of optimal transport problems with marginal moments constraints. Mathematics of Computation, American Mathematical Society, 2020. doi: 10.1090/mcom/3568.

Bahram Alinia, Mohammad H. Hajiesmaili, Zachary J. Lee, Noel Crespi, and Enrique Mallada. Online ev scheduling algorithms for adaptive charging networks with global peak constraints. IEEE Transactions on Sustainable Computing, 7(3):537–548, 2022. doi: 10.1109/TSUSC.2020.2979854.

Yvenn Amara-Ouali, Yannig Goude, Pascal Massart, Jean-Michel Poggi, and Hui Yan. A review of electric vehicle load open data and models. Energies, 14(8):2233, 2021.

Yogesh Balaji, Rama Chellappa, and Soheil Feizi. Robust optimal transport with applications in generative modeling and domain adaptation. In Advances in Neural Information Processing Systems, volume 33, pp. 12934–12944, 2020.

Jean-David Benamou and Yann Brenier. A computational fluid mechanics solution to the monge-kantorovich mass transfer problem. Numerische Mathematik, 84(3):375–393, 2000.

Ana Bušić and Sean Meyn. Action-constrained Markov decision processes with Kullback-Leibler cost. In Proc. of the Conference on Computational Learning Theory, 2018.

Neil Cammardella, Ana Bušić, and Sean Meyn. Simultaneous allocation and control of distributed energy resources via Kullback-Leibler-Quadratic optimal control. In American Control Conference, pp. 514–520, July 2020. doi: 10.23919/ACC45564.2020.9147402.

Michael Chertkov and Vladimir Y. Chernyak. Ensemble control of cycling energy loads: Markov Decision Approach. In IMA volume on the control of energy markets and grids, 2018.

Lenaic Chizat. Unbalanced optimal transport: Models, numerical methods, applications. PhD thesis, Université Paris sciences et lettres, 2017.

C.T.Kelley. 2. Local Convergence of Newton's Method, pp. 13–37. Frontiers in Applied Mathematics, 1999. doi: 10.1137/1.9781611970920.ch2.

Marco Cuturi. Sinkhorn distances: Lightspeed computation of optimal transport. In Advances in neural information processing systems, volume 26, pp. 2292–2300, 2013.

Amir Dembo and Ofer Zeitouni. Large Deviations Techniques And Applications. Springer-Verlag, New York, 2 edition, 1998.

Emiland Garrabe and Giovanni Russo. Probabilistic design of optimal sequential decision-making algorithms in learning and control. arXiv eprint 2201.05212, January 2022.

Yifeng He, B. Venkatesh, and Ling Guan. Optimal scheduling for charging and discharging of electric vehicles. Smart Grid, IEEE Transactions on, 3:1095–1105, 2012. doi: 10.1109/TSG.2011.2173507.

Leigh R Hochberg, Mijail D Serruya, Gerhard M Friehs, Jon A Mukand, Maryam Saleh, Abraham H Caplan, Almut Branner, David Chen, Richard D Penn, and John P Donoghue. Neuronal ensemble control of prosthetic devices by a human with tetraplegia. Nature, 442(7099):164–171, 2006.

Leonid V Kantorovich. On the translocation of masses. Doklady Akademii Nauk SSSR, 1942.

Miroslav Kárný. Towards fully probabilistic control design. Automatica, 32(12):1719–1722, 1996. ISSN 0005-1098.

Johannes HB. Kemperman. The general moment problem, a geometric approach. Annals of Mathematical Statistics, 39:93–122, 1968.

Jean-Michel Lasry and Pierre-Louis Lions. Mean field games. Japanese journal of mathematics, 2(1):229–260, 2007.

Khang Le, Huy Nguyen, Quang Nguyen, Tung Pham, Hung Bui, and Nhat Ho. On robust optimal transport: Computational complexity and barycenter computation. In Advances in Neural Information Processing Systems, volume 34, 2021.

Giulia Luise, Alessandro Rudi, Massimiliano Pontil, and Carlo Ciliberto. Differential properties of sinkhorn approximation for learning with wasserstein distance. Advances in Neural Information Processing Systems, 31, 2018.

Elaad OpenDataset. Elaad opendataset, 2019. URL `https://platform.elaad.io/analyses/ElaadNL_opendata.php`.

Gabriel Peyré, Marco Cuturi, and et al. Computational optimal transport: With applications to data science. Foundations and Trends in Machine Learning, 11(5-6):355–607, 2019.

Nazir Refa and Nick Hubbers. Impact of smart charging on evs charging behaviour assessed from real charging events, 2019.

Seyed Mohammad Rezvanizaniani, Zongchang Liu, Yan Chen, and Jay Lee. Review and recent advances in battery health monitoring and prognostics technologies for electric vehicle (ev) safety and mobility. Journal of Power Sources, 256:110–124, 2014. ISSN 0378-7753. doi: 10.1016/j.jpowsour.2014.01.085.

Nasrin Sadeghianpourhamami, Nazir Refa, Matthias Strobbe, and Chris Develder. Quantive analysis of electric vehicle flexibility: A data-driven approach. International Journal of Electrical Power & Energy Systems, 95:451–462, 2018.

Adrien Seguret, Thomas Le Corre, and Nadia Oudjane. A decentralized algorithm for a mean field control problem of piecewise deterministic markov processes. ESAIM: PS, 28:22 – 45, 2024. doi: 10.1051/ps/2023021.

Milan Straka and L'uboš Buzna. Clustering algorithms applied to usage related segments of electric vehicle charging stations. In Transportation Research Procedia, volume 40, pp. 1576–1582, 2019. doi: 10.1016/j.trpro.2019.07.218.

Adrien Séguret. Contrôle optimal et incitations pour des systèmes décentralisés de type champ moyen. Optimisation et contrôle [math.oc], Université Paris sciences et lettres, 2023.

Antonio Terpin, Nicolas Lanzetti, and Florian Dörfler. Dynamic programming in probability spaces via optimal transport. SIAM Journal on Control and Optimization, 62(2):1183–1206, 2024.

Emanuel Todorov. Linearly-solvable Markov decision problems. In Proc. Advances in Neural Information Processing Systems, pp. 1369–1376, Cambridge, MA, 2007.

Cédric Villani. Optimal transport: old and new, volume 338. Springer Science & Business Media, 2008.

In this appendix, dualization and proofs are presented in Section A and B. A theoretical extension is presented in appendix C, in the case where the distributions are Gaussian and the moments specified are the means and variances. In appendix D, an experiment involving the transport of a uniform law illustrates the convergence of the regularized problem to the non-regularized problem, when the regularization parameter ε tends to 0.

A   Duality

First, we want to introduce 2 preliminary problems to the MCOT-C problem. The first problem is a variant of the relaxation of (Alfonsi et al., 2020):

Problem 1S-MCOT: *One Sided Moment Constrained Optimal Transport.*

$$d(\mu_1, \mathcal{P}_f) = \min\{\langle \pi, c \rangle : \pi \in \mathcal{U}(\mu_1, \mu), \ \mu \in \mathcal{P}_f\} \tag{13}$$

Problem 1S-RMCOT is regularized using Kullback Leibler divergence:

Problem 1S-RMCOT: *One Sided - Regularized Moment Constrained Optimal Transport (1S-RMCOT).*

$$d_\varepsilon(\mu_1, \mathcal{P}_f) = \min_{\mu, \pi}\{\langle \pi, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi \| \mu_1 \otimes \mu_2) : \pi \in \mathcal{U}(\mu_1, \mu), \ \mu \in \mathcal{P}_f\} \tag{14}$$

where $\varepsilon > 0$.

A.1   Dual for 1S-MCOT

Characterization of a solution to Problem 1S-MCOT is based on a Lagrangian relaxation. Introduce two classes of Lagrange multipliers for equation 13: ψ is for the first marginal constraint, a real-valued measurable function on $\mathcal{X}$, and $\lambda \in \mathbb{R}_+^M$ for the moment constraints. The dual functional is defined as the infimum,

$$\varphi^*(\psi, \lambda) := \inf_\pi \ \langle \pi, c \rangle - \langle \pi_1 - \mu_1, \psi \rangle + \langle \pi_2, \lambda^\intercal f \rangle = \langle \mu_1, \psi \rangle + \inf_{x,y}\{c(x,y) - \psi(x) + \lambda^\intercal f(y)\} \tag{15}$$

The convex dual of equation 13 is defined to be the supremum of $\varphi^*(\psi, \lambda)$ over all ψ and λ. The dual optimization problem admits a familiar representation. Compactness is assumed in Proposition 4 (ii), as in prior work concerning canonical distributions (Kemperman, 1968).

Proposition 4. *If (A1) and (A2) hold, then,*

(i) *With φ^* defined in equation 15, the dual convex program admits the representation*

$$d^* := \sup_{\psi, \lambda} \varphi^*(\psi, \lambda) = \sup_{\psi, \lambda}\{\langle \mu_1, \psi \rangle : \psi(x) - \lambda^\intercal f(y) \le c(x,y) \ \text{ for all } x, y\} \tag{16}$$

On replacing ψ with $\psi^\lambda(x) := \inf_y\{c(x,y) + \lambda^\intercal f(y)\}$ we obtain the equivalent max-min problem

$$d^* = \sup_\lambda \int \inf_y [c(x,y) + \lambda^\intercal f(y)]\mu_1(dx) \tag{17}$$

(ii) *Suppose in addition the set $\mathcal{X}$ is compact. Then the supremum in equation 16 is achieved, and there is no duality gap: for a vector $\lambda^* \in \mathbb{R}_+^M$,*

$$d(\mu_1, \mathcal{P}_f) = d^* = \int \min_y\{c(x,y) - \lambda^{*\intercal}f(y)\}\mu_1(dx)$$

We present here the proof of part (i). The proof of (ii) is based on approximation with solutions to 1S-RMCOT. A summary of the approach is contained in Proposition 6.   □

Once we solve equation 16, we obtain π^* through complementary slackness:

$$0 = \sum_{x,y} \pi^*(x,y)\{\psi^*(x) + \lambda^{*\intercal}f(y) - c(x,y)\}$$

which means that π^* is supported on the set $\{(x,y) : -\lambda^{*\intercal}f(y) + \psi^*(x) = c(x,y)\}$.

A.2   Regularization

Recall that the functional $D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2)$ is used to define the Sinkhorn distance (Cuturi, 2013), and coincides with mutual information when the marginals of π agree with the given probability measures μ_1 and μ_2. In the present paper, the marginal μ_2 is a design parameter.

1S-RMCOT geometry and duality A close cousin to 1S-RMCOT uses the Kullback Leibler divergence as a constraint rather than penalty (Cuturi, 2013). Consider for fixed $\delta > 0$,

$$d_\delta^c(\mu_1, \mathcal{P}_f) = \min \ \langle \pi, c \rangle, \quad \text{s.t.} \ \ \pi \in \mathcal{U}(\mu_1, \mu), \mu \in \mathcal{P}_f, \ D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) \le \delta \tag{18}$$

The parameter $\varepsilon > 0$ in equation 14 may be regarded as a Lagrange multiplier corresponding to the constraint $D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) \le \delta$. Under general conditions there is $\delta(\varepsilon)$ such that the optimizers of equation 18 and equation 14 coincide.

In considering the dual of equation 14 we choose a relaxation of the moment constraints only: letting $\lambda \in \mathbb{R}_+^M$ denote the Lagrange multiplier as before,

$$\varphi^*(\lambda) := \inf_\pi \{\langle \pi, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) + \langle \pi_2, \lambda^\mathsf{T} h \rangle : \pi_1 = \mu_1\} \tag{19}$$

The convex dual of 1S-RMCOT is by definition the supremum of the concave function φ^*. The optimizer, when it exists, is denoted π^λ.

With the notation

$$\ell_0^\lambda(x, y) = -\lambda^\mathsf{T} f(y) - c(x, y), \quad x, y \in \mathcal{X} \tag{20}$$

the dual function may be expressed

$$\varphi^*(\lambda) = -\max_\pi \{\langle \pi, \ell_0^\lambda \rangle - \varepsilon D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) : \pi_1 = \mu_1\}$$

The dual of equation 18 with $d = d(\varepsilon)$ yields better geometric insight. If the maximum above exists, then the maximizer π^λ solves

$$\pi^\lambda \in \arg\max\{\langle \pi, \ell_0^\lambda \rangle : D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) \le \delta, \ \pi_1 = \mu_1\}$$

Figure 8: Dual geometry for OT-FPR

The convex region containing $\mu_1 \otimes \mu_2$ shown in Fig. 8 is the set of all π for which $\pi_1 = \mu_1$ and $D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) \le \delta$. The optimizer π^λ lies on the intersection of this region and the hyperplane shown in the figure, indicated with a dashed line: $\{\pi : \langle \pi, \ell_0^\lambda \rangle = \langle \pi^\lambda, \ell_0^\lambda \rangle\}$. This value of λ does not optimize φ^* because the hyperplane is not the boundary of the half-space shown in the figure.

For computation, it is convenient to make a change of variables: since $\pi_1 = \mu_1$ is constrained, the infimum is over all probability kernels: for $\lambda \in \mathbb{R}_+^M$,

$$\varphi^*(\lambda) := \inf_T \{-\langle \mu_1 T, \ell_0^\lambda \rangle + \varepsilon D_{\mathrm{KL}}(\mu_1 T\|\mu_1 \otimes \mu_2)\} \tag{21}$$

For each $\lambda \in \mathbb{R}_+^M$, $\varepsilon > 0$ and $x \in \mathcal{X}$, denote

$$B_{\lambda,\varepsilon}(x) = \varepsilon \log \int_{y \in \mathcal{X}} \exp\big(\varepsilon^{-1} \ell_0^\lambda(x, y)\big) \mu_2(dy) \tag{22}$$

Proposition 5. *Subject to (A1)–(A3),*

(i) *The infimum equation 21 gives* $\varphi^*(\lambda) = -\langle \mu_1, B_{\lambda,\varepsilon} \rangle$.

(ii) *The probability kernel maximizing equation 21 is*

$$T^\lambda(x, dy) = \mu_2(dy) \exp(L^\lambda(x, y)), \text{ with } L^\lambda(x, y) = \varepsilon^{-1}\{\ell_0^\lambda(x, y) - B_{\lambda,\varepsilon}(x)\} \tag{23a}$$

(iii) *unique $\lambda^* \in \mathbb{R}_+^M$ exists, satisfying*

$$\varphi^*(\lambda^*) = d_\varepsilon(\mu_1, \mathcal{P}_f) \tag{23b}$$

That is, there is no duality gap.

The similarity between Proposition 5 and Proposition 4 is found through examination of equation 17, and the recognition that $-B_{\lambda,\varepsilon}(x)$ is a (μ_2-weighted) soft minimum of $-\ell_0^\lambda(x, y) = c(x, y) - \lambda^\mathsf{T} f(y)$ over $y \in \mathcal{X}$. Subject to this interpretation, the convex dual of 1S-RMCOT can be expressed in a form entirely analogous to equation 17:

$$\max_\lambda \varphi^*(\lambda) = \max_\lambda \int \operatorname{softmin}_y \{c(x, y) + \lambda^\mathsf{T} f(y)\} \mu_1(dx)$$

1S-MCOT approximation

Consider the following procedure to obtain a solution to 1S-MCOT (without regularization), but with $\mathcal{X}$ compact, and the supports of μ_1 and μ_2 each equal to all of $\mathcal{X}$. Let $\{\pi^\varepsilon, \lambda^\varepsilon : \varepsilon > 0\}$ denote primal-dual solutions to 1S-RMCOT, where $\varepsilon > 0$ is the scaling in equation 14. Hence for each $\varepsilon > 0$,

$$d_\varepsilon(\mu_1, \mathcal{P}_f) = \langle \pi^\varepsilon, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi^\varepsilon \| \mu_1 \otimes \mu_2) = -\langle \mu_1, B_{\lambda^\varepsilon, \varepsilon} \rangle$$

Proposition 6. *Suppose that the assumptions of Proposition 4 (ii) hold, so in particular $\mathcal{X}$ is compact. Then, any weak subsequential limit of $\{\pi^\varepsilon, \lambda^\varepsilon : \varepsilon > 0\}$ as $\varepsilon \downarrow 0$ defines a pair (π^0, λ^0) for which π^0 solves 1S-MCOT and λ^0 achieves the supremum in equation 17.*

Furthermore, it is possible to bound the rate of convergence:

$$|d_\varepsilon^*(\mu_1, \mathcal{P}_f) - d^*(\mu_1, \mathcal{P}_f)| \le \varepsilon D_{KL}(\pi^0 \| \mu_1 \otimes \mu_2)$$

A.3   Link with the MCOT-C Problem

Writing the dual of MCOT-C, we get:

$$\varphi^*(\lambda) = \varepsilon \min_\pi \{-\langle \pi, l \rangle + D_{\mathrm{KL}}(\pi \| \mu_1 \otimes \mu_2) : \pi \in K(\mu_1)\}$$

Since $\pi \in K(\mu_1)$ is constrained, the infimum is over all probability kernels T from $\mathcal{X}$ to $\mathcal{W}$:

$$\varphi^*(\lambda) = -\int_x \mu_1(dx) \max_{T(x,.)} \{\langle T(x, .), \ell_0^\lambda(x, .) \rangle_\mathcal{W} - \varepsilon D_{\mathrm{KL}}(T(x, .) \| \mu_2(s^x, .))\}$$

where $\langle ., . \rangle_\mathcal{W}$ is the inner product on $\mathcal{W}$. We obtain Proposition 1, which gives similar results as Prop. 5 with a probability kernel going from $\mathcal{X}$ to $\mathcal{W}$.

B   Proofs

Much of the analysis that follows is based on convex duality between relative entropy and log moment generating functions. For any probability measure μ on $\mathcal{X}$ and function $g: \mathcal{X} \to \mathbb{R}$, the log moment generating function is denoted,

$$\Lambda_\mu(g) = \log\langle \mu, e^g \rangle$$

With μ fixed, this is viewed as an extended-valued, convex functional on the space of Borel measurable functions. Lemma 2 is a standard tool in information theory (Dembo & Zeitouni, 1998), and a reason that relative entropy is popular for use as a regularizer in optimization.

Lemma 2. *Relative entropy and the log moment generating function are related via convex duality:*

For any probability measure p we have

$$D_{KL}(p\|\mu) = \sup_g\{\langle p, g\rangle - \Lambda_\mu(g)\} \tag{24a}$$

If $D_{KL}(p\|\mu) < \infty$ then the supremum is achieved, with optimizer equal to the log likelihood ratio, $g^* = \log(dp/d\mu)$.

For Borel measurable $g\colon \mathcal{X} \to \mathbb{R}$,

$$\Lambda_\mu(g) = \sup_p\{\langle p, g\rangle - D_{KL}(p\|\mu)\} \tag{24b}$$

If $\Lambda_\mu(g) < \infty$ then the supremum is achieved, where the optimizer p^* has log likelihood ratio $\log(dp^*/d\mu) = g - \Lambda_\mu(g)$. □

Proof of Proposition 5   For each λ we have by definition,

$$\varphi^*(\lambda) = \min_T \int_{x\in\mathcal{X}} \mu_1(dx)\Big\{\varepsilon D_{\mathrm{KL}}(T(x,\cdot)\|\mu_2) - \int_{y\in\mathcal{X}} T(x,dy)\ell_0^\lambda(x,y)\Big\} \tag{25}$$

$$= -\varepsilon \max_T \int_{x\in\mathcal{X}} \mu_1(dx)\Big\{\varepsilon^{-1}\int_{y\in\mathcal{X}} T(x,dy)\ell_0^\lambda(x,y) - D_{\mathrm{KL}}(T(x,\cdot)\|\mu_2)\Big\} \tag{26}$$

For each x we have an optimization problem of the form equation 24b. Applying Lemma 2 (ii) gives the representation equation 8a and by substitution (or applying equation 24b) we obtain

$$\Big\{\varepsilon^{-1}\int_{y\in\mathcal{X}} T^\lambda(x,dy)\ell_0^\lambda(x,y) - D_{\mathrm{KL}}(T^\lambda(x,\cdot)\|\mu_2)\Big\} = \varepsilon^{-1}B_{\lambda,\varepsilon}(x) \tag{27}$$

Integrating with respect to μ_1 and applying equation 26 completes the proof. □

Proof of Proposition 1   The proof is the same as the previous one using this expression of the dual:

$$\varphi^*(\lambda) = -\int_x \mu_1(dx)\max_{T(x,.)}\big\{\langle T(x,.), \ell_0^\lambda(x,.)\rangle_{\mathcal{W}} - \varepsilon D_{\mathrm{KL}}(T(x,.)\|\mu_2(s^x,.))\big\}$$

Proof of Proposition 6   Let $(\pi^\varepsilon, \lambda^\varepsilon)$ denote the solution to 1s-RMCOT, with $\varepsilon > 0$ regarded as a variable. We let (π^0, λ^0) denote any weak sub-sequential limit: for a sequence $\{\varepsilon_i \downarrow 0\}$,

$$\pi^{\varepsilon_i} \to \pi^0, \qquad \lambda^{\varepsilon_i} \to \lambda^0, \qquad i \to \infty.$$

Optimality of π^0 is established in the following steps:

- Subject to (A1) and (A2) we know that $\pi^0 \in \mathcal{U}(\mu_1, \mu)$ with $\mu \in \mathcal{P}_f$.

- For any $\pi \in \mathcal{U}(\mu_1, \mu)$ with $\mu \in \mathcal{P}_f$ and $D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2) < \infty$ and any $\varepsilon > 0$ we have

$$\langle\pi^0, c\rangle = \lim_{i\to\infty}\langle\pi^{\varepsilon_i}, c\rangle \le \lim_{i\to\infty}\{\langle\pi^{\varepsilon_i}, c\rangle + \varepsilon_i D_{\mathrm{KL}}(\pi^{\varepsilon_i}\|\mu_1 \otimes \mu_2)\} \le \lim_{i\to\infty}\{\langle\pi, c\rangle + \varepsilon_i D_{\mathrm{KL}}(\pi\|\mu_1 \otimes \mu_2)\} = \langle\pi, c\rangle$$

- Under the support assumption we can approximate in the weak topology any $\pi \in \mathcal{U}(\mu_1, \mu)$ with $\mu \in \mathcal{P}_f$ by π^δ satisfying $D_{\mathrm{KL}}(\pi^\delta\|\mu_1 \otimes \mu_2) < \infty$ and

$$\langle\pi^0, c\rangle \le \langle\pi^\delta, c\rangle \le \langle\pi, c\rangle - \delta$$

Since $\delta > 0$ is arbitrary this establishes optimality.

We next show λ^0 provides an optimal solution. Then, for any λ,

$$\langle \pi^0, c \rangle \geq -\lim_{i \to \infty} \langle \mu_1, B_{\lambda, \varepsilon_i} \rangle = \int \in f_y \{ c(x, y) - \lambda^T f(y) \} \mu_1(dx)$$

The lower bound is achieved using λ^0 by allowing λ to depend on i:

$$\langle \pi^0, c \rangle \leq \lim_{i \to \infty} \{ \langle \pi^{\varepsilon_i}, c \rangle + \varepsilon_i D_{\mathrm{KL}}(\pi^{\varepsilon_i} \| \mu_1 \otimes \mu_2) \} = -\lim_{i \to \infty} \langle \mu_1, B_{\lambda^{\varepsilon_i}, \varepsilon_i} \rangle = \int \inf_y \{ c(x, y) - \lambda^{0^T} f(y) \} \mu_1(dx)$$

To prove the rate of convergence, we adapt results from (Luise et al., 2018) in our context. First, we denote $\pi_\varepsilon = argmin[\langle \pi, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi \| \mu_1 \otimes \mu_2)]$ and by optimality of π_ε, we obtain: $\langle \pi_\varepsilon, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi_\varepsilon \| \mu_1 \otimes \mu_2) \leq \langle \pi_0, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi_0 \| \mu_1 \otimes \mu_2)$

By optimality of π_0 and positivity of the Kullback Leibler divergence, we obtain: $\langle \pi_0, c \rangle \leq \langle \pi_\varepsilon, c \rangle \leq \langle \pi_\varepsilon, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi_\varepsilon \| \mu_1 \otimes \mu_2)$

Combining these inequalities, we get:

$$0 \leq \langle \pi_\varepsilon, c \rangle + \varepsilon D_{\mathrm{KL}}(\pi_\varepsilon \| \mu_1 \otimes \mu_2) - \langle \pi_0, c \rangle \leq \varepsilon D_{\mathrm{KL}}(\pi_0 \| \mu_1 \otimes \mu_2)$$

$$0 \leq d_\varepsilon^*(\mu_1, \mathcal{P}_f) - d^*(\mu_1, \mathcal{P}_f) \leq \varepsilon D_{\mathrm{KL}}(\pi_0 \| \mu_1 \otimes \mu_2)$$

which proves our result.

Proof of Lemma 1 Suppose that $v \in \mathbb{R}^M$ is in the null space: $\Sigma^\lambda v = 0$. From the definition equation 9b it follows that

$$0 = v^\intercal \Sigma^\lambda v = \mathsf{E}^\lambda \big[\{ v^\intercal (f(Y) - \mathsf{E}^\lambda[f(Y) \mid X]) \}^2 \big]$$

Equivalently, there is a function $g \colon \mathcal{X} \to \mathbb{R}$ such that

$$v^\intercal f(Y) = g(X) \qquad a.s. \ [\pi^\lambda]$$

The probability measures π^λ and $\pi^0 := \mu_1 \otimes \mu_2$ are mutually absolutely continuous, so the same equation holds under a.s. $[\pi^0]$. Independence gives

$$v^\intercal f(Y) = \mathsf{E}^0[v^\intercal f(Y) \mid Y] = \mathsf{E}^0[g(X) \mid Y] = \langle \mu_1, g \rangle \qquad a.s. \ [\pi^0]$$

That is, the variance of $v^\intercal f(Y)$ is equal to zero. Under (A3) this is possible only if $v = 0$. $\qquad \square$

Proof of Proposition 2 Recall the notation $\mu^\lambda = \mu_1 T^\lambda$, which is the second marginal of π^λ, and the probabilistic notation defined in the Introduction. Also, by definition we have $\mathcal{J}(\zeta) = \varepsilon^{-1} \langle \mu_1, B_{\varepsilon\zeta, \varepsilon} \rangle$.

We have for each i,

$$\varepsilon^{-1} \frac{\partial}{\partial \zeta_i} B_{\varepsilon\zeta, \varepsilon}(x) = \frac{\int_{y \in \mathcal{X}} \mu_2(y) \exp\big(\{ \zeta^\intercal f(y) - \varepsilon^{-1} c(x, y) \} \big) f^m(y)}{\int_{y \in \mathcal{X}} \mu_2(y) \exp\big(\{ \zeta^\intercal f(y) - \varepsilon^{-1} c(x, y) \} \big)} = T^\lambda f^m(x)$$

Integrating each side over μ_1 gives equation 9a (recall that $\mu^\lambda = \mu_1 T^\lambda$).

To obtain the second derivative of $\mathcal{J}(\zeta)$ requires the first derivative of the log-likelihood:

$$L_j^{\varepsilon\zeta}(x, y) := \frac{\partial}{\partial \zeta_j} L^{\varepsilon\zeta}(x, y) = \frac{\partial}{\partial \zeta_j} \big[\zeta^\intercal f(y) - \varepsilon^{-1} B_{\varepsilon\zeta, \varepsilon}(x) \big] = h_j(y) - T^\lambda h_j(x)$$

From this we obtain,

$$
\begin{aligned}
\frac{\partial^2}{\partial\zeta_i\partial\zeta_j}B_{\varepsilon\zeta,\varepsilon}(x) &= \frac{\partial}{\partial\zeta_j}T^{\varepsilon\zeta}f^m(x) \\
&= \int T^{\varepsilon\zeta}(x,dy)\{L_j^{\varepsilon\zeta}(x,y)f^m(y)\} \\
&= \int T^{\varepsilon\zeta}(x,dy)h_j(y)f^m(y) - T^\lambda h_j(x)\int T^{\varepsilon\zeta}(x,dy)h_j(y) \\
&= \mathsf{E}^\lambda[h_j(Y)f^m(Y)\mid X=x] - \mathsf{E}^\lambda[f^m(Y)\mid X=x]\mathsf{E}^\lambda[h_j(Y)\mid X=x]
\end{aligned}
$$

Integrating each side over μ_1 gives equation 9b. $\qquad\square$

Proposition 7. *The conditional distribution defined in equation 8a is Markovian: for a collection of probability kernels $\{\check{P}_i^\lambda\}$ parameterized by x,*

$$
T^\lambda(x,dy) = \nu_0(dy_0)\prod_{i=1}^M \check{P}_i^\lambda(y_{i-1},dy_i;x) \tag{28}
$$

Proof of Proposition 7 The proof reduces to justifying equation 28, which is one component of Proposition 8 that follows.

Write $L_i^\lambda(x_i,y_i) = \varepsilon^{-1}\{\lambda_i(\mathcal{U}(y_i) - r_i) - \frac{1}{2}\|x_i - y_i\|^2\}$, and for each i consider the positive kernel,

$$
\widehat{P}_i^\lambda(y_{i-1},dy_i) = P_i(y_{i-1},dy_i)\exp\left(L_i^\lambda(x_i,y_i)\right)
$$

Proposition 8. *The conditional distribution defined in equation 8a can be expressed*

$$
T^\lambda(x,dy) = \nu_0(dy_0)\exp\left(-\varepsilon^{-1}B_{\lambda,\varepsilon}(x)\right)\prod_{i=1}^M \widehat{P}_i^\lambda(y_{i-1},dy_i) \tag{29}
$$

Consequently, conditioned on $X = x$, the process Y is of the form equation 28, in which each kernel in the product takes the form,

$$
\check{P}_i^\lambda(y_{i-1},dy_i;x) = \frac{1}{g_{i-1}(y_{i-1};x)}\widehat{P}_i^\lambda(y_{i-1},dy_i)g_i(y_i;x)
$$

The functions $\{g_i : 0 \leq i \leq M\}$ are defined inductively: $g_M(y_M;x) \equiv 1$, and for $1 \leq i \leq M$,

$$
g_{i-1}(y;x) := \int \widehat{P}_i^\lambda(y,dy_i)g_i(y_i;x), \quad y \in \mathsf{X}
$$

This results in $g_0(y_0,x) = \exp\left(\varepsilon^{-1}B_{\lambda,\varepsilon}(x)\right)$.

Proof The representation equation 29 follows from the definition equation 8a and the structure imposed on h and μ_1. It is then immediate that equation 29 can be transformed to equation 28: by construction,

$$
\prod_{i=1}^M \check{P}_i^\lambda(y_{i-1},dy_i;x) = \frac{1}{g_0(y_0;x)}\prod_{i=1}^M \widehat{P}_i^\lambda(y_{i-1},dy_i)
$$

Since $y_0 = x_0$ by construction, it also follows that

$$
\exp\left(\varepsilon^{-1}B_{\lambda,\varepsilon}(x)\right) = g_0(x_0;x)
$$

$\qquad\square$

C   Example: Quadratic Constraints & Gaussian Regularizer

Consider the special case in which the function f is designed to specify all first and second moments for Y. To solve Problem 2 we adopt the following notational conventions for the Lagrange multiplier: $\mathsf{E}[Y_i] = m_i^{\mathbf{1}} \longleftrightarrow \lambda_i^{\mathbf{1}}$ and $\mathsf{E}[Y_i Y_j] = m_{ij}^2 \longleftrightarrow \lambda_{i,j}^2$. Of course we have $m_{ij}^2 = m_{ji}^2$ for each i, j. The total number of constraints is thus $M = n + n(n+1)/2$. For purposes of calculation it is useful to introduce the symmetric matrices M_Y^2 and Λ^2 with respective entries $\{m_{ij}^2\}$ and $\{\lambda_{ij}^2\}$; similar notation is used for m_Y and λ^1, the n-dimensional vectors with entries $\{m_i^{\mathbf{1}}\}$ and $\{\lambda_i^{\mathbf{1}}\}$.

Eq. equation 7 gives $\ell_0^\lambda(x, y) = \lambda^\mathsf{T} f(y) - c(x, y)$ with

$$\lambda^\mathsf{T} f(y) = y^\mathsf{T} \Lambda^2 y - \langle \Lambda^2, M_Y^2 \rangle + y^\mathsf{T} \lambda^1 - m_Y^\mathsf{T} \lambda^1 \tag{30}$$

An explicit solution to problem 1S-RMCOT is obtained when c is quadratic and μ_2 is Gaussian:

Proposition 9. *Consider the 1S-RMCOT optimization problem equation 14 in the following special case: $c(x, y) = \frac{1}{2}\|x - y\|^2$, and $\mu_2 = N(0, I)$ in the regularizer equation 4. Assume that the target covariance $\Sigma_Y := M_Y^2 - m_Y m_Y^\mathsf{T}$ is positive definite.*

Then, for each λ with $\Lambda^2 < \frac{1}{2}(1 + \varepsilon)I$, the probability kernel T^λ is Gaussian: conditioned on $X = x$, the distribution of Y is Gaussian $N(m_{T^\lambda}^x, \Sigma_{T^\lambda})$ with

$$m_{T^\lambda}^x = \varepsilon^{-1} \Sigma_{T^\lambda}[x + \lambda^1], \quad \Sigma_{T^\lambda} = \left[I + \varepsilon^{-1}[I - 2\Lambda^2]\right]^{-1} \tag{31}$$

Proof of Proposition 9   From equation 30 and using $c(x, y) = \frac{1}{2}\|x - y\|^2$ we obtain an expression for the likelihood L^λ appearing in equation 8a:

$$L^\lambda(x, y) = \varepsilon^{-1}\left\{y^\mathsf{T} \Lambda^2 y + y^\mathsf{T} \lambda^1 - \kappa^\lambda - B_{\lambda,\varepsilon}(x)\right\} - \frac{1}{2}(\|x\|^2 - 2x^\mathsf{T} y + \|y\|^2)\} \tag{32}$$

with $\kappa^\lambda = \langle \Lambda^2, M_Y^2 \rangle + m_Y^\mathsf{T} \lambda^1$. The expression for T^λ in equation 8a using $\mu_2 = N(0, I)$ then implies that for any x, $T^\lambda(x, dy)$ admits the Gaussian density

$$\tau^\lambda(y \mid x) = \frac{1}{n^\lambda(x)} \exp\left(-\tfrac{1}{2}\|y\|^2\right) \exp\left(\varepsilon^{-1}\{-\tfrac{1}{2}y^\mathsf{T}[I - 2\Lambda^2]y + y^\mathsf{T}[x + \lambda^1]\}\right) \tag{33}$$

where $n^\lambda(x) = (2\pi)^{n/2} \exp\left(\varepsilon^{-1}\{\kappa^\lambda + B_{\lambda,\varepsilon}(x) + \tfrac{1}{2}\|x\|^2\}\right)$ may be regarded as a normalizing constant. $\square$

Computation for non-Gaussian μ_1   In this case it is necessary to compute the normalizing constant in the definition of T^λ:

$$n^\lambda(x) = n^\lambda(x) \int \tau^\lambda(y \mid x)\, dy = \int \exp\left(-\tfrac{1}{2}y^\mathsf{T} \Sigma_{T^\lambda}^{-1} y + \varepsilon^{-1} y^\mathsf{T}[x + \lambda^1]\right) dy \tag{34}$$

$$= \sqrt{(2\pi)^d \det(\Sigma_{T^\lambda})} \exp\left(\tfrac{1}{2}\varepsilon^{-2}[x + \lambda^1]^\mathsf{T} \Sigma_{T^\lambda}[x + \lambda^1]\right) \tag{35}$$

Monte-Carlo methods can be used to estimate λ^*. Denote for each x,

$$q^\lambda(x) = \int T^\lambda(x, dy) f(y), \quad m^\lambda(x) = \int T^\lambda(x, dy) f(y) f(y)^\mathsf{T}$$

Each have polynomial entries: q_i^λ is a quadratic function of x and $m_{i,j}^\lambda(x)$ is a fourth order polynomial in x for each i, j. Thus, one might take

$$\widetilde{m}^{n+1} = q^{\lambda_n}(X_{n+1}), \qquad \widetilde{\Sigma}^{n+1} = m^{\lambda_n}(X_{n+1}) - \widetilde{m}^{n+1}[\widetilde{m}^{n+1}]^\mathsf{T}$$

These functions will have finite means provided $\mathsf{E}[\|X\|^4]$ is finite under μ_1.

D Convergence rate when transporting from a uniform distribution

We want to illustrate the convergence rate in Proposition 6.

With the same notations as in problems 1S-MCOT and 1S-RMCOT, we define $\mathcal{X} = [0, 1]$. Distributions μ_1 and μ_2 are the uniform distribution on $\mathcal{X}$. We define $f(x) = x - m$ with $m \in \mathcal{X}$ the imposed mean, and impose a unique constraint: $\langle f, \mu \rangle = 0$. The cost c is chosen as : $\forall x, y \in \mathcal{X}, c(x, y) = (x - y)^2$.

For these values, it is possible to obtain an explicit solution to 1S-MCOT, using Proposition 3.1:

Figure 9: For $\varepsilon = 0.01$, μ_1 is transported to π_2 with mean 0.25

$$d^* = \sup_\lambda \int \inf_y [c(x, y) - \lambda f(y)] \mu_1(dx) = \sup_\lambda \int \inf_y [(x - y)^2 - \lambda(y - m)] dx$$

$$= \sup_\lambda \int -\frac{\lambda^2}{4} + \lambda(m - x) dx$$

$$= (m - 0.5)^2$$

The solution π_ε^* may be obtained through gradient descent as explained in section 3. For $m = 0.25$ and a discretization of $\mathcal{X}$ to 100 points (to compute the gradient), the resulting marginal π_2 is shown in Fig. 9, achieving the constraint on the mean.

The values of d^* and $\langle c, \pi_\varepsilon^* \rangle$, were obtained for a range of ε (from 10^{-3} to 10^3). We can observe in Fig. 10 that the convergence to the minimum of the unregularized problem is fast and that it respects the inequality proved in Proposition 6:

Figure 10: Comparison of the costs d^* and $\langle c, \pi_\varepsilon^* \rangle$ for different values of ε

$$|d_\varepsilon^*(\mu_1, \mathcal{P}_f) - d^*(\mu_1, \mathcal{P}_f)| \le \varepsilon D_{\mathrm{KL}}(\pi_0 \| \mu_1 \otimes \mu_2)$$