DEEP POSITIVE UNLABELED LEARNING WITH A SEQUENTIAL BIAS

ABSTRACT

For many domains, from video stream analytics to human activity recognition, only weakly-labeled datasets are available. Worse yet, the given labels are often assigned *sequentially*, resulting in *sequential bias*. Current Positive Unlabeled (PU) classifiers, a state-of-the-art family of robust semi-supervised methods, are ineffective under sequential bias. In this work, we propose *DeepSPU*, the first method to address this sequential bias problem. *DeepSPU* tackles the two interdependent subproblems of learning both the latent labeling process and the true class likelihoods within one architecture. We achieve this by developing a novel iterative learning strategy aided by theoretically-justified cost terms to avoid collapsing into a naive classifier. Our experimental studies demonstrate that *DeepSPU* outperforms state-of-the-art methods by over 10% on diverse real-world datasets.

1 INTRODUCTION

Background. Traditional classifiers assume that every instance in the training set has been assigned a label. However, for many real-world problems it is prohibitively expensive to obtain a completely labeled dataset. Further, there is often *bias* in the labeling process, which makes some instances more likely to be labeled than others. For many domains, such as digital healthcare, assisted living smart systems, and video scene description (Aafaq et al., 2019; Ranasinghe et al., 2016), instances are labeled *sequentially*. Hence, an instance is more likely to be labeled if its neighbors are also labeled, and vice versa. Ours is the first work to study this setting, which we call *sequential bias*.

A prevalent example of how sequential bias arises comes from the *Human Activity Recognition* (HAR) domain (Vaizman et al., 2017). HAR data are collected by asking subjects to report the activities they perform while wearing mobile sensors. When collecting long sequences of such data (perhaps many days worth), most participants do not label every activity, and thus much of the data goes unlabeled. Additionally, since wearable sensors record data rapidly (often many readings per second), large blocks of time get labeled consecutively, resulting in sequential bias. Many other domains, such as video analysis for intrusion detection or medical records for predicting illnesses, have similar labeling mechanics such that the labels are applied sequentially and are thus also susceptible to sequential labeling bias (Rodríguez-Moreno et al., 2019; Schaekermann et al., 2018). This is a crucial issue to address, as existing methods exhibit drastically reduced accuracy when sequential bias is not accounted for (as demonstrated in our Experimental Results).

State-of-the-Art. Positive Unlabeled (PU) classifiers are a family of semi-supervised methods that learn from incompletely-labeled data while not requiring *any* labeled negative examples (Bekker & Davis, 2020; Elkan & Noto, 2008; Li & Liu, 2005; Hsieh et al., 2015; Du Plessis et al., 2015; Kiryo et al., 2017; Bekker & Davis, 2018a; Kato et al., 2019). This is a key strength of PU methods because representative negative examples, typically required by semi-supervised methods, are often not feasible to acquire. For instance, in the HAR example, there are infinitely many activities that an individual is *not* performing at any given time. Consequentially, participants are only expected to provide some *positive* labels for their activities (Vaizman et al., 2017).

Unfortunately, existing PU methods make unrealistically restrictive simplifying assumptions on how the labels were applied. Specifically, they either assume that there is no bias in the labeling process (the probability of a sample being an unlabeled positive instance is uniform) (Elkan & Noto, 2008; Du Plessis et al., 2015; Kiryo et al., 2017) or otherwise only depends on the local attributes of

each instance (Bekker & Davis, 2018a; Kato et al., 2019). This means that existing methods do not model *sequential bias*. And, as we demonstrate in our experiments, these methods are significantly negatively impacted when a sequential bias is present.

Problem Description and Technical Challenges. Given a dataset of sequences, our goal is to predict the true class likelihoods of each instance within the given sequence given a subset of labeled positive instances during training. In particular, we focus on the difficult case where labels have been assigned with a *sequential bias*, with sequential bias defined as the case where the likelihood that a positive instance is labeled varies depending on whether its neighboring instances were labeled.

This problem is challenging due to two difficult interdependent subproblems. First, we have the *dependency* problem: if we had a model of the latent labeling process (which we call the *propensity model*) that allowed us to identify the true unlabeled positive instances, then we could use this propensity model to train a classifier to produce the true class likelihoods. However, we need these same true class likelihoods in order to train the propensity model - causing a cyclic dependency. Second, standard maximum likelihood estimation inherently assumes all instances are labeled, leading to a naive classifier in the presence of labeling bias. To capture unlabeled positive instances, a PU classifier must instead predict an *appropriate* number of positive instances without simply assuming all positives instances are labeled.

Our Approach: DeepSPU. We propose *Deep Sequential PU* (*DeepSPU*), which is the first Positive Unlabeled method to use a propensity score model that predicts the likelihood that any given positive instance is labeled while taking sequential bias into account. The propensity score allows us to train a classifier network given only partially labeled data. We achieve this by developing a novel learning method that overcomes the cyclic dependency problem by iteratively learning the propensity score model and the classifier using weakly-labeled data. Further, we introduce the two novel PU cost terms: the Prior-Matching Costs (PWC) and the Observation-Matching Costs (OMC), which prohibit the propensity model and classifier from collapsing into incorrect naive solutions.

Contributions. The main contributions of our work are:

- We identify *sequential bias*, a labeling pattern characteristic of many real-world labeling processes, and demonstrate how ignoring this bias significantly impacts the performance of state-of-the-art PU classifiers.

- We develop DeepSPU, a novel iterative learning method that tackles sequential bias by jointly learning the two interdependent latent variables: the propensity score and the true class probabilities - even without any direct supervision for either learning task.

- We design the Prior-Weghted Costs and the Observation-Matching Costs, two novel PU cost terms justified by theoretical analysis that prohibit the classifier and propensity score model to collapsing to incorrect adversarial solutions.

2 RELATED WORK

PU classifiers, a special type of semi-supervised models, learn from weakly-labeled training data without requiring any labeled negative examples (Bekker & Davis, 2020). In contrast, semi-supervised methods lean heavily on having access to both labeled positive and labeled negatives to learn from weakly supervised data, making them less robust than PU alternatives (Van Engelen & Hoos, 2020). PU methods are also more robust than a similar family of classifiers known as One Class (OC) classifiers, as general OC classifiers do not make use of unlabeled data during training (Khan & Madden, 2009).

There are many approaches to PU learning, such as re-weighting predictions (Zhang & Lee, 2005; Elkan & Noto, 2008), iteratively identifying reliable examples (Ienco & Pensa, 2016), and most notably risk minimization (Northcutt et al., 2017; Du Plessis et al., 2015; Kiryo et al., 2017). However, all these state-of-the-art approaches share the often-unrealistic assumption that *no bias* exists in the labeling process, sequential or otherwise. When a bias is present, these methods are susceptible to learning skewed decision boundaries and thus are prone to making biased and incorrect classifications (Bekker & Davis, 2020).

A few recent PU methods have begun to model bias in the labeling process, though none have captured *sequential* bias. One approach assumes the likelihood that a given true positive instance is labeled depends solely on its distance from the negative distribution (Kato et al., 2019), while others explore the case when this labeling likelihood depends on the general position of the positive instance in the feature space (Bekker & Davis, 2018a). Our DeepSPU method extends beyond these methods by coping with *both* this feature-level bias *and* the previously-overlooked sequential bias.

3   PROBLEM SETTING

Positive Unlabeled (PU) learning is the task of training a classifier to predict the *true class* of each instance given a set of mostly unlabeled data and only some *labeled positive* instances (Bekker & Davis, 2020). Solving this problem requires modeling the likelihood that any given true positive instance is labeled. This labeling likelihood is referred to as the *propensity score* (Bekker & Davis, 2018a). Estimating the propensity score is *not* the same as predicting whether an instance is labeled, which is often relatively easy. This is because estimating the propensity score corresponds to determining the likelihood that an instance is labeled *conditioned on the instance being a true positive*. We cannot directly estimate this value from the data as *we do not know whether or not any given unlabeled instance is a true positive*.

Formally, let $\mathcal{D} = \{(X^{(j)}, \mathcal{L}^{(j)})\}_{j=1}^{N}$ be a dataset $\mathcal{D}$ of N sequence pairs, where $X^{(j)}$ is a sequence of real values and $\mathcal{L}^{(j)}$ is a sequence of binary label indicators, $\|X^{(j)}\| = \|\mathcal{L}^{(j)}\|$. For readability, we drop the superscript j and describe our approach in terms of one sequence. Let $X = (x_1, x_2, ..., x_T)$ be a sequence of T real values (which we refer to as a sequence of *instances*), and $\mathcal{L} = (\ell_1, \ell_2, ..., \ell_T)$ be an associated sequence of label indicators such that $\ell_i = 1$ if x_i is labeled positive, and is 0 otherwise. Additionally, for each feature-label sequence pair there is an *unobserved* binary true class sequence, $Y = (y_1, y_2, ..., y_T), y_i \in \{0, 1\}$, representing the underlying classes of the instance. In addition to y_i being unavailable during training, $Pr(y_i = 1 | \ell_i = 1) = 1$ as we assume there are no labels for negative instances, while $Pr(\ell_i = 1 | y_i = 1) \neq 0$ as we assume not all positive instances are labeled.

We consider both *feature-level* and *sequential* biases in the labeling process. Feature-level bias assumes the propensity score for a positive instance depends on local features of the instance and thus $Pr(\ell_i = 1 | y_i = 1) \neq Pr(\ell_i = 1 | y_i = 1, x_i)$. Sequential bias assumes the propensity score of a positive instance can also depend on the label status of preceding instances, $\ell_{1:i-1}$, and thus $Pr(\ell_i = 1 | y_i = 1) \neq Pr(\ell_i = 1 | y_i^{(j)} = 1, x_{1:i}, \ell_{1:i-1})$. We call a propensity score that captures sequential and feature-level bias a *sequential propensity score* $q_i = Pr(\ell_i = 1 | y_i = 1, x_{1:i}, \ell_{1:i-1})$. Modeling q_i explicitly enables identification of likely true positives among the unlabeled data. More specifically, an unlabeled instance with a very low propensity score is likely a true positive.

Our goal is to train a classifier $g_\theta(\cdot)$ with parameters θ to solve the binary classification problem, such that $g_\theta(X) = Pr(Y|X)$. During training, only the features X and label status indicator $\mathcal{L}$ are observed while the true class Y is unobserved. Notation used summarized in Appendix A.6.

4   METHODOLOGY

4.1   OVERVIEW

Our proposed model, *DeepSPU*, consists of three sub-networks: 1) the *Representation Network*, which learns a robust representation of the input data, 2) the *Sequential Propensity Network*, which models the likelihood that an instance is labeled given that it is positive, and 3) the *Classification Network*, which models the likelihood that a given instance belongs to the positive class.

The Sequential Propensity Network, used only during the training stage, is crucial in the training of the Classification Network as it allows us to train the Classification Network given only weakly-labeled training data. We employ an innovative Iterative Learning Strategy, training the two prediction networks by minimizing the *positive unlabeled risk* (Bekker & Davis, 2020). This is achieved without explicit feedback for each of the two networks' estimated latent variables. Further, we design two novel PU cost (regularization) terms that are employed during the iterative training. These cost terms prevent the networks from converging on naive solutions which minimize the PU risk but

Figure 1: An overview of the DeepSPU learning process. The Representation Network learns a hidden representation of the input sequence that is fed to both the Classification Network and the Sequential Propensity Network. Networks are alternately trained iteratively, with one being frozen while the other is updated.

do not result in correct probability distributions for the latent target variables. After training, the Classification Network can be deployed without the Sequential Propensity Network to predict the true class of new instances. Detailed pseudo-code is available in the appendix.

4.2 REPRESENTATION NETWORK

The Sequential Propensity Network and the Classification Network both share a common base representation of the input data. This shared representation is modeled by a recurrent neural network (RNN) B_Ω with parameters Ω, such that B_Ω takes in the sequence of input data $X = (x_1, x_2, \cdots, x_T)$ and maps each element of the sequence to a corresponding latent representation $H = (h_1, h_2, \cdots, h_T)$. Each latent representation h_i is given by $h_i = F_h(x_i, h_{i-1})$, with the specific form of F_h determined by the choice of RNN network. Our implementation of *DeepSPU* uses a Gated Recurrent Unit (GRU) for the RNN (Cho et al., 2014), though the same principles apply to other RNN architectures.

4.3 SEQUENTIAL PROPENSITY NETWORK

The aptly-named Sequential Propensity Network models the propensity score conditioned on the local feature values of each instance along with label indicator of all preceding instances. The first component of this sub-network is another GRU that for each label ℓ_i produces a latent representation s_i conditioned on all previous labels. In effect, s_i summarizes the label subsequence ℓ_1 to ℓ_i into one latent variable. This GRU is coupled with a feed-forward network (FFN) that takes in the latent label representation s_{i-1}, the previous label indicator ℓ_{i-1}, and the representation of the input features learned by the Representation Network h_i in order to produce the propensity score q_i of the ith instance. With Φ representing the learnable parameters of the Sequential Propensity Network Q_Φ, Q_Φ models the sequential propensity score as $Q_\Phi(h_i, s_{i-1}, \ell_{i-1}) = q_i = Pr(\ell_i = 1|x_{1:i}, \ell_{1:i-1})$.

4.4 CLASSIFICATION NETWORK

The shared hidden representation h_i is also passed as input into the *DeepSPU classifier subnetwork*, which models the positive class probability given the features of the input data. Our classifier model $g_\Theta(x_i) = p(y_i|x_{1:i}, \Theta)$ with parameters Θ is given by: $g_\Theta(x) = F_g(B_\Omega(x_i); \Theta)$, where F_g is a fully connected network with parameters Θ. The predicted class value for an instance x_i is given by $round(g(x_i))$, where $round(z) = 1$ if $z > 0.5$ and is 0 otherwise. We chose 0.5 as the cutoff as $g_\Theta(x_i)$ represents the *probability* that $y_i = 1$.

4.5 ITERATIVE LEARNING STRATEGY

Typical classifiers for fully-labeled data are trained to minimize the expected value of a loss function C given the class predictions. The expected loss is referred to as the *risk*. If the propensity score

is known then the standard risk R can be expressed in terms of expectations over only positive and unlabeled distributions, instead of the positive and negative distributions (Du Plessis et al., 2015; Bekker & Davis, 2018a). Thus, to train our model we express the *empirical positive unlabeled risk*, R_{PU}, in terms of our novel sequential propensity score q_i as:

$$R_{\text{PU}}(g,q|X,\mathcal{L}) = \frac{1}{T}\Big(\sum_{x_i|\ell_i=1}\Big(\frac{1}{q_i}C^+(g(x_i)) + \Big(1 - \frac{1}{q_i}\Big)C^-(g(x_i))\Big) + \sum_{x_i|\ell_i=0}(C^-(g(x_i)))\Big), \tag{1}$$

where C^+ is the loss incurred from predicting $g(x)$ assuming that the true class is positive, C^- is the loss incurred from predicting $g(x)$ assuming the true class is negative, and $q_i = Pr(\ell_i = 1|x_{1:i}, \ell_{1:i-1})$ is the propensity score of the i-th instance. If our propensity scores are accurate, then minimizing the above equation will correspond to minimizing the true risk. This means that in effect we can learn the same classifier that we would have found if we had been given fully labeled data.

Theorem 1. *If $q_i = Pr(\ell = 1|y_i = 1, x_{1:i}, \ell_{1:i-1})$ for $i = 1 : T$, then $R_{pu}(g, q|X, \mathcal{L})$ is an unbiased estimation of the true risk $R(g|Y)$.*

A proof of this theorem is given in Section A.4 of the Appendix. As stated, Theorem 1 indicates that we can train a classifier on positive and unlabeled data if we have accurate propensity scores. However, our model of the propensity score (given by the Sequential Propensity Network) has no observed variable to use as a target during training, and thus there is no straightforward way to minimize the PU risk. The naive approach would be to simply learn the parameters of the classifier g and propensity network q simultaneously by minimizing Equation 1. However, there is no guarantee that Equation 1 is an unbiased estimate of the true risk if the estimated propensity scores are incorrect (and thus no indication that this would yield a good classification model). We overcome this challenge with a novel *Iterative Learning Strategy*, outlined below.

We begin training the networks by initializing the propensity scores with "good" estimates, acquired by assuming the labeling likelihood $c = Pr(\ell_i = 1|y_i = 1)$ is constant for all positive instances. c is easily computed given a prior on the class $\pi = Pr(y = 1)$ (Bekker & Davis, 2020), and has been shown to be successfully estimated from the initial data set (Jain et al., 2016). We show how to derive c from π in the appendix.

Next, we train the Sequential Propensity Network and the Classification Network iteratively in separate interleaved stages. That is, at each stage of training, either the parameters of the Sequential Propensity Network or Classification Network are updated independently from each other. The Representation Network is trained at both stages because the Sequential Propensity Network and Classification Network both rely on its hidden representation. To avoid the Sequential Propensity Network and Classification Network learning based on different hidden representations than they were trained on, when a network's weights are not being updated a frozen copy of the Representation Network is used to generate the hidden representation for that second network.

4.6 THE *DeepSPU* PU COST TERMS

It is possible to minimize Equation 1 by naively setting $q_i = 1 \,\forall\, i$ and $g(x_i) = \ell_i$. In this case, the classifier does not predict the instance's *true class*, and instead erroneously predicts whether or not an instance is labeled (Bekker & Davis, 2018a). To avoid this adversarial solution, we propose two cost terms. First, we add the *Prior-Matching Costs (PMC)*, which drives the percentage of predicted positives to match the percentage of true positive we expect according to our prior. The PMC is given by the KL divergence between the unconditioned distribution of predicted positives and a Bernoulli distribution parameterized by the true class prior π:

$$PMC(X) = \text{KL}(Pr(\hat{y} = 1|\Theta)||Bern(\pi)). \tag{2}$$

Thus, the number of predicted positives are driven to match the expected number of true positives. By definition, the PMC will be larger than the number of labeled instances, and thus Equation $T1$ will incur a high penalty cost for the *adversarial solution*.

Additionally, if our propensity scores match the true propensity scores, then our propensity score multiplied by the class probability of the i-th instance will equal the probability that the i-th instance is labeled, as stated in Theorem 2. This informs our next cost term.

Theorem 2. *If $q_i = Pr(\ell_i = 1|x_{1:i}, \ell_{1:i-1}, y_i = 1)$ is the sequential propensity score of the i-th instance, then $Pr(\ell_i = 1|x_i, \ell_{i-1}) = q_i \cdot Pr(y_i|x_i)$.*

The proof is given in Appendix A.5.

In short, DeepSPU explicitly encourages the product of the propensity network and predicted class probability to match the observed labels. We accomplish this by adding the Binary Cross Entropy (BCE) between them as next cost term. We refer to this as the *Observation-Matching Costs (OMC)*, as it requires our propensity score and class predictions to match the observed data:

$$OMC(X) = \text{BCE}(Q_\Phi(X)g_\Theta, \mathcal{L}). \tag{3}$$

The final loss function for DeepSPU is thus defined by:

$$L(\Phi, \Theta) = I \cdot J(g_\Theta) + (1 - I) \cdot J(Q_\phi),$$

where I is an indicator variable that equals 1 if we're updating the weights of the classifier network g_Θ and is 0 otherwise, and J is the cost term defined as:

$$J(\cdot) = R_{PU} + \lambda_1 PMC + \lambda_2 OMC,$$

with λ_1 and λ_2 being weights on the corresponding cost terms.

5 EXPERIMENTS

5.1 DATA AND EXPERIMENTAL DETAILS

Datasets. We evaluate our models and a relevant set of baselines on several real-world sequential human activity recognition datasets: UCI HAR[1] (Anguita et al., 2013), Older Healthy (OH) HAR[2] (Torres et al., 2013), and ExtraSensory (ES)[3] (Vaizman et al., 2017). ExtraSensory was subsampled at one reading for every 10 minutes of collected data due to the size of the dataset. Due to extreme class imbalance, we combine the multiple classes into one for some of the datasets. We combine UCI HAR into 3 classes: one representing Walking-related activities, one that combines Going Up and Down Stairs, and one that combines stationary activities. We likewise combine stationary activities in OH HAR. We also evaluate on RealityCommons (RC Flu)[4] (Madan et al., 2011), an in-the-wild health dataset, where the task is to classify whether the individual is experiencing flu symptoms on a given day using mobile sensor data.

Compared methods. We compare DeepSPU to the following state-of-the-art methods:

- *Positive-Negative (PN) Classifier* (Cho et al., 2014): As a baseline, we adopt a standard binary positive-negative classifier that treats all unlabeled instances as negatives. The model otherwise has the same structure as the DeepSPU classification network.

- *uPU* (Du Plessis et al., 2015): uPU is a recent highly-influential approach to training deep networks on PU data. uPU's convex approach minimizes the empirical PU risk. However, this approach assumes *the propensity score is constant*.

- *nnPU* (Kiryo et al., 2017): Similarly to *uPU*, *nnPU* also assumes that the propensity score is constant to minimize the empirical PU risk. Additionally, nnPU clips the risk of the unlabeled instances at 0 to avoid infinitely negative risks and is thus liable to overfit during training.

- *SAR-EM* (Bekker & Davis, 2018a): SAR-EM is the leading PU method for learning under *feature-level biased labeling*. SAR-EM jointly trains a classifier and propensity network using an Expectation-Maximization algorithm, such that the propensity network can handle feature-level but *not* sequential bias.

We do not compare against any general semi-supervised methods. *This is not an oversight*. As per our problem definition, we assume we have no labeled negative examples. This means general semi-supervised methods are inapplicable. (Van Engelen & Hoos, 2020).

---

[1] https://archive.ics.uci.edu/ml/datasets/human+activity+recognition+using+smartphones

[2] https://archive.ics.uci.edu/ml/datasets/Activity+recognition+with+healthy+older+people+using+a+batteryless+wearable+sensor

[3] http://extrasensory.ucsd.edu/

[4] http://realitycommons.media.mit.edu/socialevolution4.html

Datasets:	ES Lying	ES Sitting	ES Walking	ES Sleeping	RealityCommons
PN:	0.68	0.60	0.62	0.66	0.50
uPU:	0.70	0.62	0.65	0.70	0.60
nnPU:	0.70	0.62	0.66	0.72	0.62
SAR EM:	0.66	0.63	0.58	0.69	0.54
DeepSPU:	**0.77**	**0.66**	**0.68**	**0.78**	**0.66**

Table 1: Performance of DeepSPU vs compared methods on naturally weakly labeled real-world datasets experiencing sequential bias. DeepSPU outperforms the others. Results reported as Balanced Accuracy. Higher is better.

Evaluation metric. To measure the performance of our compared methods, we use *balanced accuracy* (BA) (Brodersen et al., 2010), which is defined as $\frac{1}{2} * \left(\frac{TP}{TP+FN} + \frac{TN}{TN+FP} \right)$. BA is similar to the standard accuracy metric, but accounts for class imbalance: a BA of 0.5 is achieved by a naive classifier, regardless of class imbalance. An optimal classifier will achieve a BA of 1.0.

Implementation details. We use an 70%/10%/20% train/validation/test split for each dataset. The base classifier for all methods is a GRU with a 10-dimensional hidden layer. A 1-layer feed-forward neural network uses the GRU's latent representation as input for each instance and serves as the classifier. DeepSPU has an additional 1-layer GRU for the propensity network. Each method is trained until convergence (200 epochs). All methods are implemented in PyTorch and are publicly available [5].

5.2 EXPERIMENTAL STUDY ON CLASSIFYING NATURALLY-UNLABELED DATA

First, we demonstrate *DeepSPU*'s ability to classify data that naturally exhibits sequential bias. This can be clearly shown for the `ExtraSensory` and `RealityCommons` datasets, because both were collected "in the wild" with study participants labeling their own data sequentially. Thus they are thus naturally weakly labeled. Further, due to the study design it is unclear if an instance that is not labeled positive is in fact negative or an unlabeled positive (Chang et al., 2017; Madan et al., 2011), thus fitting the positive unlabeled problem description. For this experiment, we estimate the class prior for *nnPU* and *DeepSPU* using *TIcE* (Bekker & Davis, 2018b). As shown in Table 1, *Deep-SPU* significantly outperforms the state-of-the-art methods for both datasets. This demonstrates that tackling sequential bias inherent in these real-world datasets is impactful. Additionally, the baseline underperforms the PU methods in almost all cases, highlighting the importance of leveraging PU classifiers for these weakly-labeled real-world problems. Overall, these results confirm that the pervasive problem of sequential bias in labeling can be mitigated by *DeepSPU*.

5.3 EXPERIMENTAL STUDY ON LEARNING FROM VARIOUS LEVELS OF LIMITED LABELS

In practice, the percentage of labeled positives available during training will vary from dataset to dataset. Thus, we perform this next experiment to study the impact of the proportion of labeling on each method's performance. In line with much of the recent PU work (Bekker & Davis, 2020; 2018a; Kiryo et al., 2017), we achieve this by removing subsets of labels from each dataset prior to training. We range label availability from 5% to 15% of all positive instances, and remove the labels from all negative instances. To encourage *sequential* bias, unlabeling is done sequentially: A binary Markov Chain decides whether or not to remove the label for each instance in turn. The likelihood the Markov Chain switches from "labeling" to "unlabeling" states is varied according to the desired level of unlabeling. Details of this unlabeling process are in Appendix A.7. As shown in Table 2, *DeepSPU* significantly outperforms all other methods for every level of unlabeling. This demonstrates that even with very few labels, modeling sequential bias leads to significant improvements in performance. As expected, the *Positive Negative* performs the worst, as it does not account for unlabeled positives. Surprisingly, *SAR-EM* is outperformed by *nnPU*, despite *nnPU* assuming that no bias arises in the labeling process. This may be explained by *nnPU*'s natural aversion to overfitting (Kiryo et al., 2017), while *SAR-EM* may learn spurious relationships in the labels while mistakenly modeling sequential bias as feature-level bias.

---

[5]https://anonymous.4open.science/r/250569bb-b723-4e3c-8b37-ed982087c2db/

Method:	PN			uPU			nnPU			SAR-EM			DeepSPU		
% Labeled:	5	10	15	5	10	15	5	10	15	5	10	15	5	10	15
OH Stationary	0.50	0.50	0.51	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	**053**	**0.53**	**0.55**
OH Ambulating	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.51	0.52	0.50	0.50	0.50	0.50	**0.52**	**0.54**
UCI Walking	0.50	0.50	0.50	0.50	0.51	0.53	0.50	0.51	0.52	0.51	0.52	0.54	**0.58**	**0.62**	**0.72**
UCI Stairs	0.50	0.50	0.50	0.59	0.62	0.72	0.64	0.65	0.67	0.52	0.53	0.58	**0.79**	**0.80**	**0.86**
UCI Stationary	0.50	0.51	0.53	0.91	0.91	0.93	0.91	0.91	0.94	0.79	0.79	0.85	**0.96**	**0.96**	**0.97**
ES Walking	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	**0.51**	**0.52**	**0.54**
ES Sitting	0.50	0.50	0.50	0.50	0.50	0.52	0.50	0.50	0.52	0.53	0.53	0.54	**0.55**	**0.58**	**0.60**
ES Sleeping	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.51	0.50	0.50	0.50	**0.58**	**0.65**	**0.66**
ES Lying	0.50	0.50	0.51	0.50	0.50	0.51	0.50	0.51	0.53	0.50	0.50	0.50	**0.62**	**0.69**	**0.72**

Table 2: Classification performance for various levels of labeling on the Older Healthy, UCI HAR, and ExtraSensory HAR datasets. Results reported as Balanced Accuracy (higher is better).

(a) Ablation study	(b) Parameter study

Figure 2: a) The ablation study of *DeepSPU* indicates that each of its major components significantly improves its performance. b) Performance of *DeepSPU* varying values for the class prior π estimate, with the true prior being about 0.36.

5.4 ABLATION STUDY

DeepSPU minimizes PU risk using three components: The iterative training algorithm, the *observation-matching cost* (OMC), and the *prior-matching cost* (PMC). In this experiment, we demonstrate the necessity of each component in an ablation study on the `ExtraSensory Sitting` dataset. Removing any of the three components results in significantly lower classification accuracy. Specifically, removing the iterative training strategy impacts the performance most significantly. This is expected, as without the iterative training strategy the cost function is likely to be biased. We also see that the PMC divergence, which encourages the percentage of predicted positives to match the class prior, is the more important of the two novel cost terms.

5.5 EXPERIMENTAL STUDY EVALUATING PARAMETERS FOR ESTIMATED PRIOR

PU methods rely on prior estimates of class label likelihoods $\pi = Pr(y = 1)$. In particular, *DeepSPU* uses this prior for the PMC term. With this value being estimated (Jain et al., 2016), the selected prior could be inaccurate in a practical setting. Therefore, we now study the impact of poorly-estimated priors on *DeepSPU* by varying this estimation. We train *DeepSPU* on the `ES Sitting` dataset, where the true class prior is about 0.36. As shown in Figure 2b, *DeepSPU* achieves the strongest performance when the estimated prior is closest to the true prior. However, even when the prior is overestimated, the performance is not significantly impacted until the estimated prior becomes severely over or underestimated. This indicates that in practice *DeepSPU* is generally robust even to incorrectly estimated priors.

6 CONCLUSION

We propose *DeepSPU*, the first PU solution learning from weakly labeled data with sequential bias in the labeling. We formulate a novel iterative learning strategy to jointly train a classification model and labeling likelihood (propensity) model, along with designing two theoretically-justified PU cost terms to account for this bias. Through a series of extensive experimental results we demonstrate that the previously-overlooked sequential labeling bias naturally arises in real-world datasets. Also, the state-of-the-art PU methods have poor performance when this type of bias is present, while *DeepSPU* achieves robust classification performance under sequential labeling bias for a rich variety of real-world data sets.

REFERENCES

Nayyer Aafaq, Ajmal Mian, Wei Liu, Syed Zulqarnain Gilani, and Mubarak Shah. Video description: A survey of methods, datasets, and evaluation metrics. *ACM Computing Surveys (CSUR)*, 52(6):1–37, 2019.

Davide Anguita, Alessandro Ghio, Luca Oneto, Xavier Parra, and Jorge Luis Reyes-Ortiz. A public domain dataset for human activity recognition using smartphones. In *Esann*, 2013.

Jessa Bekker and Jesse Davis. Learning from positive and unlabeled data under the selected at random assumption. *Journal of Machine Learning Research*, 2018a.

Jessa Bekker and Jesse Davis. Estimating the class prior in positive and unlabeled data through decision tree induction. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018b.

Jessa Bekker and Jesse Davis. Learning from positive and unlabeled data: a survey. *Mach. Learn.*, 109(4):719–760, 2020.

Kay Henning Brodersen, Cheng Soon Ong, Klaas Enno Stephan, and Joachim M Buhmann. The balanced accuracy and its posterior distribution. In *2010 20th International Conference on Pattern Recognition*, pp. 3121–3124. IEEE, 2010.

Yung-Ju Chang, Gaurav Paruthi, Hsin-Ying Wu, Hsin-Yu Lin, and Mark W Newman. An investigation of using mobile and situated crowdsourcing to collect annotated travel activity data in real-word settings. *International Journal of Human-Computer Studies*, 102:81–102, 2017.

Kyunghyun Cho, Bart van Merriënboer, Caglar Gulcehre, Dzmitry Bahdanau, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning phrase representations using rnn encoder–decoder for statistical machine translation. In *Conference on Empirical Methods in Natural Language Processing*, pp. 1724–1734, 2014.

Marthinus Du Plessis, Gang Niu, and Masashi Sugiyama. Convex formulation for learning from positive and unlabeled data. In *International Conference on Machine Learning*, pp. 1386–1394, 2015.

Charles Elkan and Keith Noto. Learning classifiers from only positive and unlabeled data. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 213–220, 2008.

Cho-Jui Hsieh, Nagarajan Natarajan, and Inderjit S Dhillon. Pu learning for matrix completion. In *ICML*, pp. 2445–2453, 2015.

Dino Ienco and Ruggero G Pensa. Positive and unlabeled learning in categorical data. *Neurocomputing*, 196:113–124, 2016.

Shantanu Jain, Martha White, and Predrag Radivojac. Estimating the class prior and posterior from noisy positives and unlabeled data. In *Advances In Neural Information Processing Systems (NeurIPS)*, pp. 2693–2701, 2016.

Masahiro Kato, Takeshi Teshima, and Junya Honda. Learning from positive and unlabeled data with a selection bias. In *International Conference on Learning Representations*, 2019.

Shehroz S Khan and Michael G Madden. A survey of recent trends in one class classification. In *Irish conference on artificial intelligence and cognitive science*, pp. 188–197. Springer, 2009.

Ryuichi Kiryo, Gang Niu, Marthinus C du Plessis, and Masashi Sugiyama. Positive-unlabeled learning with non-negative risk estimator. In *Advances In Neural Information Processing Systems (NeurIPS)*, pp. 1675–1685, 2017.

Xiao-Li Li and Bing Liu. Learning from positive and unlabeled examples with different data distributions. In *European conference on machine learning*, pp. 218–229. Springer, 2005.

Anmol Madan, Manuel Cebrian, Sai Moturu, Katayoun Farrahi, et al. Sensing the" health state" of a community. *IEEE Pervasive Computing*, 11(4):36–45, 2011.

Curtis Northcutt, Tailin Wu, and Isaac Chuang. Learning with confident examples: Rank pruning for robust classification with noisy labels. In *Proceedings of the Thirty-Third Conference on Uncertainty in Artificial Intelligence*, 2017.

Suneth Ranasinghe, Fadi Al Machot, and Heinrich C Mayr. A review on applications of activity recognition systems with regard to performance and evaluation. *International Journal of Distributed Sensor Networks*, 12(8), 2016.

Itsaso Rodríguez-Moreno, José María Martínez-Otzeta, Basilio Sierra, Igor Rodriguez, and Ekaitz Jauregi. Video activity recognition: State-of-the-art. *Sensors*, 19(14):3160, 2019.

Mike Schaekermann, Edith Law, Kate Larson, and Andrew Lim. Expert disagreement in sequential labeling: A case study on adjudication in medical time series analysis. In *SAD/CrowdBias@ HCOMP*, pp. 55–66, 2018.

Roberto L Shinmoto Torres, Damith C Ranasinghe, Qinfeng Shi, and Alanson P Sample. Sensor enabled wearable rfid technology for mitigating the risk of falls near beds. In *2013 IEEE International Conference on RFID (RFID)*, pp. 191–198. IEEE, 2013.

Yonatan Vaizman, Katherine Ellis, and Gert Lanckriet. Recognizing detailed human context in the wild from smartphones and smartwatches. *IEEE Pervasive Computing*, 16(4):62–74, 2017.

Jesper E Van Engelen and Holger H Hoos. A survey on semi-supervised learning. *Machine Learning*, 109(2):373–440, 2020.

Dell Zhang and Wee Sun Lee. A simple probabilistic approach to learning from positive and unlabeled examples. In *Proceedings of the 5th annual UK workshop on computational intelligence (UKCI)*, pp. 83–87, 2005.

A APPENDIX

A.1 STRATEGIES FOR CALCULATING THE CLASS PRIOR

Our DeepSPU method and the state-of-the-art nnPU method both take in the class prior $\pi = p(y = 1)$ as a parameter. While this can be approximated from PU data (Jain et al., 2016), we calculated this from the true class labels for all experiments. This was done as follows:

$$\hat{\pi} = \frac{\sum_{n=1}^{N} \sum_{t=1}^{T} y_i^{(j)}}{NT},$$

where N is the number of time series in the training set and T is the length of each series.

A.2 DEEPSPU TRAINING

Algorithm 1: DeepSPU Training Process

---

input : Initialized propensity network Q
Initialized classification network G
Initialized shared representation B
Dataset of sequences $\mathcal{D}$ with features X and labels $\mathcal{L}$ of split into batches
Prior estimate $\hat{\pi}$
output: Trained classifier
Trained propensity function
$c = \frac{num\_labeled\_instances}{\hat{\pi}}$
define $frozen\_propensity(x) = c$
$train\_classifier = True$
for $i \leftarrow 1$ **to** max_epochs **do**
    for $batch$ in $num\_batches$ **do**
        if $train\_classifier$ **then**
            $\hat{Y}_{batch} = G(B(X_{batch}))$
            $\hat{Q}_{batch} = frozen\_propensity(frozen\_B(X_{batch}))$
        else
            $\hat{Y}_{batch} = frozen\_classifier(frozen\_B(X_{batch}))$
            $\hat{Q}_{batch} = Q(B(X_{batch}))$
        end
        $loss(\hat{Q}_{batch}, \hat{Y}_{batch}) = \hat{R}_{pu} + BCE + KL_{div}$
    end
    Update weights of B with Adam optimizer using $loss$
    if $train\_classifier$ **then**
        Update weights of G with Adam optimizer using $loss$
    else
        Update weights of Q with Adam optimizer using $loss$
    end
    $train\_classifier = not$ $train\_classifier$
    $frozen\_propensity = copy(Q)$
    $frozen\_classifier = copy(G)$
    $frozen\_B = copy(B)$
end

For the sake of reproducibility we provide the pseudocode for training DeepSPU.

A.3 FINDING LABELING LIKELIHOOD c GIVEN THE CLASS PRIOR

As described in the Methodology section, DeepSPU initially considers the propensity score to be constant for the first few epochs of training. This constant propensity score is found given knowledge of the class prior π as follows:

$$
\begin{aligned}
c &= Pr(\ell = 1 | y = 1) \\
&= \frac{Pr(\ell = 1, y = 1)}{Pr(y = 1)} \\
&= \frac{Pr(\ell = 1)}{Pr(y = 1)} \\
&= \frac{Pr(\ell = 1)}{\pi}
\end{aligned}
$$

Thus, we need only to estimate $Pr(\ell = 1)$ by finding the fraction of labeled instances in the dataset, and dividing this value by the class prior π.

A.4 PROOF OF THEOREM 1

Proof.

$$
\begin{aligned}
\mathbb{E}[R_{PU}(g, q | X, \mathcal{L})] &= \frac{1}{m} \sum_{i=1}^{m} y_i q_i \left(\frac{1}{q_i} L^+(g(x_i)) + (1 - \frac{1}{q_i}) L^-(g(x_i)) \right) + (1 - y_i q_i) L^-(g(x_i)) \\
&= \frac{1}{m} \sum_{i=1}^{m} y_i L^+(g(x_i)) + (1 - y_i) L^-(g(x_i)) \\
&= R(g | Y)
\end{aligned}
$$

$\square$

A.5 PROOF OF THEOREM 2

Proof.

$$
\begin{aligned}
Pr(\ell_i = 1 | x_{1:i}, \ell_{1:i-1}) &= Pr(\ell_i = 1 | x_i, \ell_{1:i-1}, y_i = 1) Pr(y_i = 1 | x_i, \ell_{1:i-1}) \\
&\quad + Pr(\ell_i = 1 | x_i, \ell_{i-1}, y_i = 0) Pr(y_i = 0 | x_i, \ell_{1:i-1}) \\
&= Pr(\ell_i = 1 | x_i, \ell_{i-1}, y_i = 1) Pr(y_i = 1 | x_i, \ell_{1:i-1}) \\
&= Pr(\ell_i = 1 | x_i, \ell_{i-1}, y_i = 1) Pr(y_i = 1 | x_i)
\end{aligned}
$$

$\square$

A.6 TABLE OF NOTATION

Notation	Description
N	Number of sequences in dataset
T	Length of sequence
x_i	Features of ith instance
y_i	Binary class indicator variable for ith instance $y_i = 1$ if y_i is of the positive class, $y_i = 0$ otherwise.
ℓ_i	Binary label indicator variable for ith instance. $\ell_i = 1$ if the timestep was labeled, $\ell_i = 0$ otherwise.
q_i	Sequential propensity score ith instance. $q_i = Pr(\ell_i = 1 \mid x_{1:i}; \ell_{1:i-1}, y_i = 1)$
π	Class prior. $\pi = Pr(y = 1)$
c	Label frequency. $c = Pr(\ell = 1 \mid y = 1)$
Capital letter	Sequence of corresponding variable. i.e., $X = (x_1, \cdots, x_T)$
where $i = 1, \cdots, N$ and $t = 1, \cdots, T$	

Table 3: Reference for symbols used in this work

True Class (y)	0 0 1 1 1 1 1 1 1 1 1 0 0 0 0 0 0 0
Markov Chain	1 1 0 0 0 0 0 0
Labels (ℓ)	0 0 1 1 0 0 0 0 0 0 0 0 0 0 0 0 0 0

Figure 3: An example of unlabeling with Markov chain.

A.7 INTRODUCING SEQUENTIAL BIAS

For each sub-sequence of consecutive positive instances within each sequence, a binary Markov chain was run to decide which instances were to be unlabeled. We initiated the Markov chain at state '1', where state '1' indicates that the corresponding positive instance remains labeled. The Markov chain could transition to state '0' with probability λ. We varied the value of λ to evaluate DeepSPU's performance for various levels of mislabeling. For instances where the Markov chain is in state '0' the corresponding positive instance was set to be unlabeled. The chain has a 1% probability of transitioning back to '1' from state 0. An example of this is shown in figure 3. This process introduces *sequential* bias, as the likelihood that a given instance is mislabeled depends on whether the previous instance is mislabeled (a given instance has a 100 X (1 - λ) % chance of being labeled if the preceding instance is labeled).

Figure 4: Histogram of lengths of consecutive labels (in minutes).

A.8 QUANTITATIVE ANALYSIS ON EXTRASENSORY LABELING PATTERNS

Figure 4 shows the frequency of lengths of labeled subsequences in the ExtraSensory dataset. Clearly, the participants do enter phases of labeling as there are many long subsequences of consecutive labels.