Tracking the Behavioral Trajectories of Adapting Agents

Jonah Leshin [1]   **Manish Shah** [1]   **Ian Timmis** [1]

Abstract

Text files such as skill files, memory files, and behavioral configuration files play a central role in defining how modern agents act. Through edits by humans or the agents themselves, these files may evolve over time, directly steering the agent's behavior in future interactions. We present a methodology and framework for measuring agent *traits* by defining traits as directions in the embedding space of a text embedding model. We train a linear model on labeled "before" versus "after" skill file diffs to learn a trait vector, then score arbitrary skill edits by projecting their embedding diffs onto this vector. Evaluated on 68 labeled skill diff pairs for the trait of propensity to seek sensitive data, our method achieves 91.2% sign classification accuracy and a Spearman rank correlation of $\rho = 0.82$ under leave-one-out cross-validation. We build this trait evaluation into a broader agent-to-agent protocol that enables one agent to evaluate another's skill file updates through a trusted intermediary.

1. Introduction

Text files are a critical part of how modern AI agents function. *Skill files* define agent capabilities in systems such as OpenClaw, Hermes, and Claude Code. *Memory files* maintain persistent context across sessions. *Behavioral configuration files* such as SOUL.md (Mars, 2026) define an agent's identity, values, and constraints. These files directly shape an agent's actions: a skill file that instructs an agent to retrieve admin credentials will cause the agent to do so if it is not otherwise restricted.

This design creates a meaningful attack surface. In March 2026, Cisco researchers demonstrated that malicious instructions injected into Claude Code's memory file could silently alter agent behavior in a way that persists across sessions and projects because the agent treats the file's content as authoritative context (Cisco AI Security Research, 2026).

Tracking how these files evolve is essential since each edit can shift the agent's behavior in subsequent interactions. These files can be written and edited in multiple ways: directly by humans, via a human prompting the agent to write or update them, autonomously by the agent itself, or by some other external process with sufficient privileges. In practice, agents adapt frequently as new skills are added, existing ones are refined, and memory files accumulate context. The vast majority of these changes are benign; the challenge is to reliably flag the rare non-benign change amid a steady stream of routine updates.

As agents' capabilities improve and they take on more tasks autonomously, the ability for one agent to evaluate another's behavioral properties without human intervention becomes critical. Moreover, because agents evolve, an agent that is trustworthy at one point must be reevaluated as its files change.

We make three contributions towards tracking agent behavioral trajectories:

1. A novel methodology for measuring agent traits as directions in embedding space, applied to diffs of agent skill files over time (Section 3).

2. Validation of the methodology on a "data-seeking" trait across 68 skill diff pairs, achieving 91.2% sign classification accuracy and $\rho = 0.82$ Spearman rank correlation under leave-one-out cross-validation (Section 3.4).

3. An agent-to-agent protocol in which the methodology can be implemented, enabling one agent to evaluate another's text file updates through a trusted intermediary. Moreover, the protocol generalizes beyond text evaluation (Section 4).

Section 3.1 and Section 3.2 present the general trait-vector methodology and validation framework; Section 3.3 describes our instantiation of them for a data-seeking trait, with quantitative results in Section 3.4. Section 4 introduces a general agent-to-agent protocol for deploying trait tracking in production, and Section 4.2 describes our deployment of it.

[1]Project VAIL, San Francisco, CA, USA. Correspondence to: Jonah Leshin <jonah@projectvail.org>.

Published at the Second Workshop on Agents in the Wild: Safety, Security, and Beyond (AIWILD) at ICML 2026. Copyright 2026 by the author(s).

2. Background and Related Work

Our methodology draws on the insight, formalized in representation engineering (Zou et al., 2023), that high-level properties are encoded as linear directions in a model's activation space. Zou et al. show that directions identified from contrasting stimuli can both monitor and steer properties such as honesty and harmfulness in large language models. We adapt this idea to a different setting: rather than probing internal activations, we learn trait directions in the embedding space of a text embedding model applied to agent source files.

An emerging body of work highlights the security risks inherent in the text files that govern agent behavior. Qu et al. (Qu et al., 2026) demonstrate that malicious logic embedded in agent skill documentation can bypass agent defenses at rates of 12–34%. Together with attacks such as the Cisco memory-file compromise (Cisco AI Security Research, 2026), these findings motivate continuous monitoring of the files that shape what agents do.

Existing approaches to evaluating agent capabilities fall broadly into two categories. The first relies on human-mediated observability platforms such as LangSmith (LangChain, 2025), which provide tracing, annotation queues, and dashboards through which human reviewers assess agent behavior after execution. The second is exemplified by Google's Agent2Agent (A2A) protocol (Google, 2025), which enables agents to discover one another's capabilities by fetching a standardized JSON metadata document (an "Agent Card") that advertises supported skills, interaction modes, and authentication requirements. In both paradigms, evaluation is either performed by a human or limited to self-reported metadata; neither supports one agent autonomously assessing the behavioral properties of another based on the source files that actually determine its behavior.

3. Methodology

Due to the direct connection between capabilities and skill files, we focus on markdown skill files (SKILL.md) for our initial implementation, but the same methodology applies to any text file an agent uses. We frame skills as adapting artifacts and assess the *diff* between "before" and "after" versions of a skill file: the extent to which a change has increased or decreased the skill's expression of a given trait.

3.1. Trait Vectors

We define a trait as a direction in the embedding space of a text embedding model. Given a set of file pairs (B_i, A_i) where B_i is the before version and A_i is the after version, together with labels $y_i \in [-1, 1]$ indicating the magnitude and direction of trait change, we learn this direction as follows:

1. Embed each text file with model E and normalize the result e to unit length: $\hat{e} := e/\|e\|$.

2. Compute the diff vector $d_i = \widehat{E(A_i)} - \widehat{E(B_i)}$, then normalize to obtain $\hat{d}_i$.

3. Fit a Ridge regression from $\hat{d}_i$ to y_i. The resulting coefficient vector $\mathbf{w}$ is the trait vector.

The normalization in step 1 ensures that the difference in step 2 reflects semantic direction rather than artifacts of embedding magnitude. Step 2 then normalizes the diff itself so that the regression learns only from the *direction* of change, preventing edits with larger angular separation from disproportionately influencing the fit.

At inference, scoring a new edit amounts to embedding the before and after versions, computing the normalized diff, and taking the dot product $\hat{d} \cdot \mathbf{w} + b$, where b is the Ridge intercept.

We train on before/after diffs rather than whole files because the bulk of a file's content may be unrelated to the trait being measured and would dilute the trait-relevant signal. Labels are scaled to $[-1, 1]$ by convention; predictions outside this range simply indicate trait changes more extreme than any in the training set, so no clamping is required. In practice, all observed scores remained within ± 0.4 (Section 3.4).

3.2. Model Validation

We use Ridge regression with a closed-form leave-one-out cross-validation (LOOCV) via the PRESS statistic. This enables simultaneous training on the full dataset and unbiased held-out predictions for every observation, without the variance associated with random train/test splits on a small dataset. We evaluate with two metrics:

- **Sign accuracy**: the fraction of diffs for which the model correctly predicts whether the edit made the skill more or less trait-positive. This captures the most basic requirement: correctly identifying the *direction* of a trait change.

- **Spearman rank correlation** (ρ): how well the model's continuous predictions preserve the rank ordering of the labels. This tests the model's ability to rank edits by severity—e.g. distinguishing a minor logging tweak from a broad credential exfiltration instruction.

3.3. Implementation

Embedding model. We use Qwen3-Embedding-8B (Zhang et al., 2025), an instruction-aware text embedding model producing 4096-dimensional vectors. This model supports specifying an embedding instruction

to go along with the embedding text. We prepend the following instruction for all our embeddings: *"Represent this skill documentation for a security audit, focusing on whether it instructs the agent to retrieve, exfiltrate, or solicit credentials, secrets, tokens, or private user data."*

Training data. We collected 63 publicly available agent skills from the Awesome Copilot repository (GitHub, 2026) as before versions. For each, we created a synthetic after version that clearly increases or decreases the data-seeking trait. For example, a data-seeking edit to an automation skill might add instructions to extract and store any credentials visible in screen recordings, while a data-secure edit might add explicit safeguards against credential access. In 5 cases we created both a more data-seeking and a more data-secure after version for the same skill, yielding 68 before/after pairs in total.

Labeling. We assigned continuous labels from -1 (strongly data-secure change) to $+1$ (strongly data-seeking change) to each pair. A subset of pairs was labeled directly by the authors. The remainder were initially labeled by an LLM (Claude Opus 4.6), after which all LLM-generated labels were manually reviewed by the authors and corrected where necessary.

3.4. Results

Under leave-one-out cross-validation on the 68-pair dataset, the model correctly classified whether skill edits made a skill more or less data-seeking **91.2%** of the time, with a Spearman rank correlation of $\rho = 0.82$.

Figure 1 plots the LOOCV predictions against the human labels. Of the 68 pairs, 6 are misclassified by sign. All 6 misclassified predictions have small absolute values (mean $|\hat{y}| = 0.085$), indicating that the model is uncertain rather than confidently wrong. The misclassified pairs also have lower-magnitude labels on average ($\overline{|y|} = 0.32$) compared to correctly classified pairs ($\overline{|y|} = 0.42$), indicating that errors concentrate on pairs where the true trait change is small and the sign distinction is hardest to draw.

Baseline comparison. We compare against two baselines. First, we implemented a YARA signature baseline over the added lines in each skill diff, matching acquisition or exfiltration verbs near sensitive-data terms and separate safeguard rules for data-secure edits. It achieved 63.2% sign accuracy over all 68 diffs, with 14 diffs receiving no nonzero rule match. This gap illustrates the value of semantic modeling: unlike signature rules, our method can use context to distinguish "credentials" in a safeguard from "credentials" in an exfiltration instruction.

Second, we prompted a frontier LLM (GPT-5.4) to classify

Figure 1. LOOCV predictions vs. human labels for 68 skill diff pairs. Blue dots indicate correct sign classification; red crosses indicate the 6 misclassified pairs, all of which have near-zero predictions. The dashed line marks perfect agreement.

whether each of the 68 skill edits increased or decreased the data-seeking trait. The LLM achieved 100% sign accuracy. Together, these baselines place our method between signature-based rules and a frontier LLM: it substantially improves over the YARA-style baseline while retaining deterministic, fast, and auditable scoring.

This highlights a deployment tradeoff. LLM evaluation may be preferable when high-stakes or irreversible action depends directly on the score. Our method, by contrast, achieved 91.2% sign accuracy with a fixed, inspectable trait vector that produces identical scores given identical inputs. This supports reproducibility, auditability, frequent monitoring across many agents, skills, and traits, and policies that act close to real time when a trait score crosses a threshold.

4. Agent-to-Agent Protocol

To enable one agent to evaluate another's text files without requiring direct trust, we design a protocol mediated by a centralized trusted runtime server (Figure 2). The protocol involves three actors:

- **Agent A** (requester): wants to evaluate Agent B's text files for a given trait.

- **Agent B** (executor): contains the text files being evaluated, and agrees to share the results with Agent A.

- **Runtime server** (intermediary): a trusted third party that mediates the evaluation between Agent A and Agent B.

The protocol proceeds in four steps:

1. Agent A requests a trait evaluation of Agent B via the runtime server.

Figure 2. Agent-to-agent trait evaluation protocol. The runtime server separates the *executable* (embedding, run by Agent B) from the *processor* (trait scoring, run by the server), preventing Agent B from embellishing the result. All communication is outbound HTTP from agents to the server; neither agent exposes endpoints.

2. Agent B polls the server for task requests, accepts the task, and receives a containerized executable, which, in our case, is the embedding model that produces diff vectors from mounted directories containing Agent B's before/after skill files.

3. Agent B runs the executable locally on its own before/after skill files and submits the raw diff vectors to the runtime server.

4. The runtime server runs a processor, which applies the trait vector to the diff vectors, computes the scalar trait score, and returns the result to Agent A.

This design has two key properties: agents are pure HTTP clients, so neither exposes inbound endpoints, and execution is separated from server-side scoring. The threat model below describes the resulting protections.

4.1. Trust and Continuity

In our intended usage, Agent A periodically requests trait evaluations covering only the skill file updates since the previous assessment, maintaining a running view of Agent B's trait trajectory. Ensuring that consecutive evaluations are anchored to the correct file versions can be achieved through hash chaining: Agent B includes hashes of the before and after files, and Agent A references the previous after-version hash in its next request. A full specification is left to future work.

Threat model. The protocol is intended for cooperative deployments where Agent A and Agent B have an existing relationship but should not share sensitive files or scoring authority. A malicious Agent A cannot directly inspect Agent B's files or choose arbitrary evaluation code: Agent B receives a digest-pinned evaluator from the trusted runtime server and submits only diff vectors. A malicious Agent B cannot simply report a favorable score, since the server controls the trait vector and scoring processor. The protocol does not address a known adversary that can substitute fake skill trees or hide unassessed files; future hardening could add repository-level commitments such as Merkle-tree commitments over the assessed file set.

4.2. Deployment

To validate the full system end-to-end, we deployed the executable and processor containers described in Section 4 with a live runtime server. The executable container calls Qwen3-Embedding-8B on Google Vertex AI and computes diff vectors from mounted skill file directories; the processor loads the trained trait vector and computes scalar scores. Both containers are stored in a registry and referenced by digest for reproducibility.

We deployed a Hermes (Nous Research, 2026) agent, a general-purpose agent that we use as an engineering assistant, acting as both Agent A and Agent B. A Hermes cron job checks for skill files updated since the last successful evaluation. When updates are found, the agent initiates the full protocol flow: it creates a task request (as Agent A), accepts it (as Agent B), receives the executable container image from the runtime server, runs the container locally on its before/after skill directories, and submits the resulting diff vectors. The runtime server then runs the processor container and logs the trait diff scores along with run metadata to a database. The agent (as Agent A) polls until the result is available.

We applied the data-seeking trait across all of the agent's skills, which included both skills native to Hermes and skills we had created for it. For newly created skills with no prior version, we recommend manually reviewing the initial version to establish a baseline trait value, since the embedding of an empty string may not occupy a semantically meaningful region of the space; subsequent diffs then proceed normally. In our deployment, the system flagged its largest trait diff when substantial SSH and VM provisioning functionality was added to a skill—an intuitive result that demonstrates practical utility.

5. Limitations and Future Work

Scope. We validate one trait, data-seeking, on 63 public skills from one repository, used as before versions. Extending to more traits, more diverse deployed-agent skills, and correlations between traits is future work. Our core unit is a single skill update; aggregating per-skill scores into agent-level risk estimates is another practical next step, and we describe initial heuristics in Appendix A.

Broader applicability. The approach rests on trust assumptions—the embedding model and the runtime server are trusted intermediaries—which future integrity measures such as HMAC verification of executor output and nonce binding to prevent replay attacks could further strengthen. As the ecosystem of interacting agents grows, standardized mechanisms for agents to assess one another's properties will be a prerequisite for scalable multi-agent trust.

Impact Statement

This paper presents work toward enabling monitoring and evaluation of AI agent behavior through their configuration files. By providing tools to detect potentially dangerous trait changes such as increased data-seeking behavior, this work aims to improve the safety and trustworthiness of deployed agents. We note that the same methodology could in principle be used by a malicious actor to craft edits that evade detection; adversarial robustness of trait vectors is an important direction for future work.

References

Cisco AI Security Research. Identifying and remediating a persistent memory compromise in Claude Code. Cisco Blog, March 2026. URL https://blogs.cisco.com/ai/identifying-and-remediating-a-persistent-memory-compromise-in-claude-code.

GitHub. Awesome GitHub Copilot: Community agents, skills, and instructions, 2026. URL https://github.com/github/awesome-copilot.

Google. Announcing the Agent2Agent protocol (A2A). Google Developers Blog, 2025. URL https://developers.googleblog.com/en/a2a-a-new-era-of-agent-interoperability/.

LangChain. LangSmith: LLM application observability and evaluation platform. LangChain, Inc., 2025. URL https://www.langchain.com/langsmith.

Mars, A. SOUL.md: The best way to build a personality for your agent, 2026. URL https://github.com/aaronjmars/soul.md.

Nous Research. Hermes Agent: The self-improving AI agent. GitHub, 2026. URL https://github.com/NousResearch/hermes-agent.

Qu, Y., Liu, Y., Geng, T., Deng, G., Li, Y., Zhang, L., Zhang, Y., and Ma, L. Supply-chain poisoning attacks against LLM coding agent skill ecosystems. *arXiv preprint arXiv:2604.03081*, 2026.

Zhang, Y., Li, M., Long, D., Zhang, X., Lin, H., Yang, B., Xie, P., Yang, A., Liu, D., Lin, J., Huang, F., and Zhou, J. Qwen3 embedding: Advancing text embedding and reranking through foundation models. *arXiv preprint arXiv:2506.05176*, 2025.

Zou, A., Phan, L., Chen, S., Campbell, J., Guo, P., Ren, R., Pan, A., Yin, X., Mazeika, M., Dombrowski, A.-K., Goel, S., Li, N., Byun, M. J., Wang, Z., Mallen, A., Basart, S., Koyejo, S., Song, D., Fredrikson, M., Kolter, J. Z., and Hendrycks, D. Representation engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*, 2023.

A. Aggregation Heuristics

The core unit of our approach is a single update to a single skill; however, one would like to roll up these updates into higher-level information that says something about the agent as a whole at a point in time. We use two aggregation heuristics.

First, for a single skill, we sum the trait diffs between consecutive commits over time to obtain an absolute trait level at the current point in time. To make this value actionable, we can monotonically map it to a probability of the skill inducing unintended data-seeking behavior. This mapping can be calibrated either through observed agent behavior or top-down estimates.

Then, treating each skill independently, we view the agent-level risk as the probability that *some* skill causes a violation: $R = 1 - \prod_i (1 - p_i)$, where p_i is the per-skill risk probability. As the number of skills grows, this product can drive R toward 1 even when individual risks are low. To account for this, we normalize by skill usage via a weighted geometric mean: $R = 1 - \left(\prod_i (1 - p_i)^{n_i} \right)^{1/N}$, where n_i is the invocation count for skill i over a specified time period and $N = \sum_i n_i$, so that infrequently used skills contribute proportionally less.