Reward-Wise Value Estimation for Multi-Reward Optimization in Large Language Models

Quan Wei[1] **Zhongruo Wang**[2] **Chenliang Li**[3] **Xi Chen**[2] **Oana Frunza**[4] **Yang Katie Zhao**[1] **Mingyi Hong**[1]

Abstract

Value functions play a central role in critic-based reinforcement learning (RL) algorithms such as proximal policy optimization (PPO) and in inference-time scaling for large language models (LLMs). In complex LLM tasks, multiple reward signals are often leveraged to guide RL training and inference. However, existing value function estimation methods either aggregate all rewards into a single scalar, limiting flexibility across reward components, or rely on separate critic models for each reward, which is computationally inefficient. To address these limitations, we propose an efficient and flexible value function estimation method for multi-reward optimization in LLMs. Specifically, we introduce a multi-head critic model architecture that jointly estimates reward-wise value functions within a single model. This design enables fine-grained credit assignment across reward components while maintaining computational efficiency. We further prove that the proposed multi-head critic loss yields lower irreducible error compared to the vanilla single-head critic loss. Experimental results on multi-turn agentic search and mathematical reasoning tasks demonstrate that our reward-wise value estimation approach consistently improves both policy optimization and critic learning in PPO training.

1. Introduction

Reinforcement learning (RL) has become a standard paradigm for aligning large language models (LLMs) on complex reasoning (Guo et al., 2025a; Zeng et al., 2025) and

Figure 1. Comparison between vanilla PPO and reward-wise PPO with a multi-head critic. Vanilla PPO aggregates multiple reward components into a single scalar target and learns a single-head critic, while reward-wise PPO estimates reward-wise value functions with multiple value heads. The reward-wise advantages are computed separately for each reward component and then aggregated for policy optimization, enabling fine-grained value estimation across heterogeneous rewards with minimal additional critic overhead.

agentic tasks (Jin et al., 2025b; Xue et al., 2025). Existing RL algorithms for LLM training can be broadly categorized into critic-free and critic-based methods. Critic-free algorithms, such as Group Relative Policy Optimization (GRPO) (Shao et al., 2024) and REINFORCE Leave-One-Out (RLOO) (Kool et al., 2019; Ahmadian et al., 2024), remove the value function and estimate advantages in a group-relative manner. While this avoids the difficulty of critic training, the resulting advantage signals are typically derived from final rewards and can be coarse-grained, leading to less precise credit assignment (Guo et al., 2025b; Feng et al., 2025; Wei et al., 2025). Critic-based algorithms, such as proximal policy optimization (PPO) (Schulman et al., 2017), leverage value functions to compute generalized advantage estimation (GAE) (Schulman et al., 2015), providing fine-grained advantage signals for policy optimization (Ouyang et al., 2022). Moreover, a well-trained critic can be used to guide inference-time scaling and search (Liu et al., 2024; Yao et al., 2023; Lightman et al., 2023; Setlur et al., 2024), further improving policy performance.

[1]University of Minnesota, USA [2]Independent Researcher [3]Texas A&M University, USA [4]Morgan Stanley, USA. Correspondence to: Mingyi Hong <mhong@umn.edu>.

ICML 2026 Workshop on Decision-Making from Offline Datasets to Online Adaptation: Black-Box Optimization to Reinforcement Learning.

Recently, multiple reward signals have been widely used to guide RL training and inference in LLMs. Beyond answer rewards, auxiliary rewards such as format rewards and process rewards are often incorporated for reward shaping in search (Jin et al., 2025a; Zhao et al., 2025), tool-calling agentic tasks (Li et al., 2025b; Qian et al., 2025), preference learning (Gunjal et al., 2025) and complex multi-agent intelligence (Team et al., 2026). However, these methods typically aggregate all reward components into a single scalar, which limits flexibility across heterogeneous rewards and may lead to unstable training or even training collapse (Wei et al., 2025; Liu et al., 2026). This naive aggregation can lead to poor credit assignment, since the model loses access to reward-specific learning signals and cannot identify which reward components contribute most during optimization. In addition, a critic trained on aggregated rewards can only estimate an overall value function, rather than providing reward-specific value signals for individual components. This limits its flexibility in inference-time scaling, where different reward components may need to be weighted or queried separately.

In this paper, we focus on critic-based RL algorithms for multi-reward settings. On the one hand, optimizing with aggregated rewards can lead to poor credit assignment and results in an inflexible critic that only provides overall value estimates, without reward-specific value signals for individual components. On the other hand, training a separate critic model for each reward component is computationally expensive and memory inefficient. Therefore, this raises the following question:

How can we design critic-based RL algorithms that improve policy optimization while maintaining an efficient and flexible critic model for multi-reward settings?

To address these limitations, we propose an efficient and flexible value function estimation method for multi-reward optimization in LLMs. Our contributions are summarized as follows:

- We introduce a multi-head critic architecture that jointly estimates reward-wise value functions within a single model. This design enables fine-grained value estimation across reward components while maintaining computational efficiency. We prove that the reward-wise critic loss yields lower irreducible error compared to the vanilla single-head critic loss.

- Building on the multi-head critic, we propose reward-wise PPO, which separately estimates GAE for each reward component and aggregates reward-wise advantages for policy optimization, enabling more fine-grained credit assignment across heterogeneous rewards. Figure 1 compares vanilla PPO with a single-

head critic and reward-wise PPO with a multi-head critic.

- Experimental results demonstrate that our reward-wise value estimation approach consistently improves both policy optimization and critic learning in PPO training across different model sizes and datasets on both multi-turn agentic search and math reasoning tasks.

2. Related Work

RL Algorithms for LLMs. For LLM training, existing RL algorithms can be categorized into critic-free methods, such as GPRO (Shao et al., 2024) and RLOO (Kool et al., 2019; Ahmadian et al., 2024), and critic-based methods, such as PPO (Schulman et al., 2017). GRPO-type methods estimate advantages from group-level rollout samples and avoid critic training, resulting in lower memory and computational overhead. However, although they bypass the difficulty of training a critic, their advantage signals are typically derived from final rewards and can lead to coarse-grained trajectory-level advantage estimation, resulting in less precise credit assignment (Guo et al., 2025b; Feng et al., 2025; Wei et al., 2025). Recent studies further suggest that such coarse-grained advantage estimation can lead to unstable training and even training collapse (Wei et al., 2025; Li et al., 2026; Wang et al., 2025; Li et al., 2025a). In contrast, PPO-type methods leverage value functions to compute GAE (Schulman et al., 2015), providing fine-grained credit assignment for policy optimization (Ouyang et al., 2022). Moreover, a well-trained critic can be used to guide or evaluate inference-time scaling and search (Liu et al., 2024; Yao et al., 2023; Lightman et al., 2023; Setlur et al., 2024), further improving performance.

Multi-Reward RL. Recently, RL training and inference-time scaling have moved beyond single-reward optimization. Beyond answer correctness rewards, auxiliary rewards such as format rewards and process rewards are often incorporated for reward shaping in search (Jin et al., 2025a; Zhao et al., 2025), tool-calling agentic tasks (Li et al., 2025b; Qian et al., 2025), and complex multi-agent intelligence (Team et al., 2026). Another important application of multi-reward RL is improving the efficiency of reasoning models while maintaining task performance, primarily by introducing length-based rewards alongside outcome-based rewards (Liu et al., 2025; Aggarwal & Welleck, 2025). In addition, preference learning methods can use different preference rubrics to adapt multiple reward modeling to diverse tasks (Gunjal et al., 2025). However, these methods typically aggregate all reward components into a single scalar, which limits flexibility across heterogeneous rewards and may lead to unstable training or even training collapse (Wei et al., 2025; Liu et al., 2026). The most closely related works are concurrent studies that propose estimating advantages separately

for each reward component in a GRPO-style manner (Liu et al., 2026; Zhu et al., 2026). The key difference is that these methods are critic-free, whereas our work focuses on critic-based RL. Moreover, these GRPO-type methods do not learn critic models, and thus cannot directly provide value functions for inference-time scaling or search.

3. Preliminaries

3.1. Modeling Language Generation as Token-Level MDP

Let $x \sim \mathcal{D}$ denote the input prompt from the dataset $\mathcal{D}$, and $y = [y_1, \ldots, y_T]$ the generated response. Text generation by a language model can be formulated as sampling from a policy in a Markov decision process (MDP), defined as the tuple $\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, r, \gamma)$, where $\mathcal{S}$ denotes the state space, $\mathcal{A}$ the action space, P the transition dynamics, r the reward function, and γ the discount factor. At each time step t, the state is $s_t = (x, y_{<t}) \in \mathcal{S}$, consisting of the prompt x and the previously generated tokens, and the action $a_t = y_t \in \mathcal{A}$ corresponds to selecting the next token from the vocabulary. The transition dynamics P are deterministic: given s_t and a_t, the next state is $s_{t+1} = (x, y_{\leq t})$. The reward function $r_t = r(s_t, a_t)$ assigns a scalar value at each time step. Since it is a common practice to use the discount factor $\gamma = 1$ in RL for LLM training, we omit γ in the subsequent notation for simplicity, unless otherwise specified. The value function is defined as $V(s_t) = \mathbb{E}\left[\sum_{t'=t}^{T} r_{t'}\right]$, representing the expected return from state s_t. RL aims to maximize the expected cumulative reward

$$J(\theta) = \mathbb{E}_{x \sim \mathcal{D}, y \sim \pi_\theta(\cdot|x)} \left[\sum_{t=1}^{T} r_t \right]. \quad (1)$$

In this work, we consider a terminal reward provided only at the end of the sequence, denoted as $\mathcal{R}(x, y)$, i.e., $r_t = 0$ for $t < T$ and $r_T = \mathcal{R}(x, y)$.

3.2. Proximal Policy Optimization

PPO (Schulman et al., 2017) is a popular actor-critic RL algorithm commonly used for LLM training (Ouyang et al., 2022). It optimizes the policy by maximizing the clipped surrogate objective:

$$\mathcal{J}_{\text{PPO}}(\theta) = \mathbb{E}_{x \sim \mathcal{D}, y \sim \pi_{\theta_{\text{old}}}(\cdot|x)}$$
$$\left[\sum_{t=1}^{T} \min(\rho_t A_t, \text{clip}(\rho_t, 1 - \epsilon, 1 + \epsilon) A_t) \right], \quad (2)$$

where $\rho_t = \frac{\pi_\theta(y_t|y_{<t}, x)}{\pi_{\theta_{\text{old}}}(y_t|y_{<t}, x)}$ is the importance sampling ratio between the current policy π_θ and the old policy $\pi_{\theta_{\text{old}}}$, A_t is the advantage term, and ϵ is the clipping parameter. The PPO algorithm mainly consists of two components: advantage estimation and value estimation.

- **Advantage Estimation.** The advantage A_t measures the relative quality of action a_t at state s_t. In PPO, it is typically estimated using GAE (Schulman et al., 2015): $A_t = \sum_{l=0}^{T-t} (\gamma\lambda)^l \delta_{t+l}$, where $\delta_t = r_t + \gamma V(s_{t+1}) - V(s_t)$ is the temporal-difference (TD) error, and $V(s_t)$ denotes the value of state s_t.

- **Value Estimation.** The value function, often referred to as the critic model, estimates the expected return for each state. The objective of the critic is to minimize the discrepancy between its predicted values and the target returns, typically via a mean squared error (MSE) loss:

$$\mathcal{L}_{\text{critic}}(\phi) = \mathbb{E}_t \left[\left(V_\phi(s_t) - R_t \right)^2 \right], \quad (3)$$

where $V_\phi(s_t)$ denotes the predicted value of state s_t parameterized by ϕ, and R_t denotes the target return, which can be estimated using Monte Carlo returns: $R_t = \sum_{t'=t}^{T} r_{t'}$.

3.3. Multi-Reward Modeling

In multi-reward modeling, the reward function in the MDP formulation outputs a K-dimensional vector, i.e., $r : \mathcal{S} \times \mathcal{A} \to \mathbb{R}^K$, where r^k denotes the k-th reward component. The reward components are aggregated into a scalar reward, i.e., $r_t = \sum_{k=1}^{K} r_t^k$, for policy optimization in Eq. (1). When $K = 1$, this formulation reduces to the standard single-reward setting. In the terminal reward setting, each data pair (x, y) is associated with a set of K terminal reward components $\{\mathcal{R}^k(x, y)\}_{k=1}^{K}$. For multi-reward settings, learning an effective critic for policy optimization and inference-time scaling poses significant challenges. On the one hand, aggregating all reward components into a single scalar limits flexibility and obscures the contribution of individual rewards. On the other hand, learning separate critic models for each reward component incurs substantial computational and memory overhead.

4. Reward-Wise Value Estimation and Reward-Wise PPO

4.1. Reward-Wise Value Estimation

To address these limitations, we propose an efficient and flexible value function estimation method for multi-reward optimization in LLMs. Specifically, we introduce a multi-head critic architecture that jointly estimates reward-wise value functions within a single model. Compared to a traditional single-head critic, our multi-head critic shares the same backbone while incorporating multiple value heads, each learning a distinct reward component independently.

Given K Monte Carlo returns R_t^k for $k = 1, 2, \ldots, K$, we

define the reward-wise critic loss as

$$\mathcal{L}_{\text{critic}}^{\text{rw}}(\phi) = \sum_{k=1}^{K} \mathbb{E}_t \left[\left(V_\phi^k(s_t) - R_t^k \right)^2 \right], \qquad (4)$$

where $V_\phi^k(s_t)$ denotes the predicted value of state s_t from the k-th value head corresponding to the k-th reward component. Compared to the vanilla critic loss

$$\mathcal{L}_{\text{critic}}(\phi) = \mathbb{E}_t \left[\left(V_\phi(s_t) - \sum_{k=1}^{K} R_t^k \right)^2 \right], \qquad (5)$$

which estimates the aggregated return across all reward components, the proposed reward-wise critic loss decomposes value estimation into per-reward components, enabling more fine-grained modeling of heterogeneous rewards.

Overhead Analysis. We compare our multi-head critic architecture with the vanilla single-head critic and a multi-critic architecture in terms of parameter count and forward computational cost (FLOPs) in Table 1. For parameter count, all three critic architectures share the same backbone with $12lh^2 + vh$ parameters, which dominates the overall parameter size. The difference arises from the output head: the single-head critic has a single value head with h parameters, the multi-critic architecture replicates the entire backbone K times, and the multi-head critic introduces only K lightweight value heads with Kh parameters. In particular, compared to the single-head critic, the multi-head critic introduces only an additional $(K-1)h$ parameters, which corresponds to a negligible overhead relative to the backbone $12lh^2 + vh$. For forward FLOPs, all three critic architectures share the same backbone cost $l(12sh^2 + 2s^2h)$, which dominates the overall computation. The difference lies in the output head: the single-head critic incurs an additional sh cost, the multi-critic architecture requires K independent forward passes, and the multi-head critic introduces only Ksh additional cost from the value heads. Therefore, the multi-head critic achieves comparable parameter efficiency and computational cost to the single-head critic, while avoiding the K-fold increase in both parameters and FLOPs incurred by the multi-critic architecture.

We provide a theoretical analysis comparing the two critic losses in Eq. (4) and Eq. (5).

Proposition 4.1. *Let each reward-wise return be decomposed as*

$$R_t^k = \mu_t^k + \epsilon_t^k,$$

where $\mu_t^k = \mathbb{E}[R_t^k \mid s_t]$ and ϵ_t^k is zero-mean noise. Let $V_\phi^k(s_t)$ be the reward-wise value estimate and $V_\phi(s_t)$ be the vanilla value estimate for the aggregated return. Define the reward-wise prediction error as $e_t^k = V_\phi^k(s_t) - \mu_t^k$, and the vanilla prediction error as $e_t = V_\phi(s_t) - \sum_{k=1}^K \mu_t^k$.

Then the expected reward-wise critic loss decomposes as

$$\mathbb{E}[\mathcal{L}_{\text{critic}}^{\text{rw}}] = \sum_{k=1}^{K} \mathbb{E}\left[(e_t^k)^2 \right] + \sum_{k=1}^{K} \mathbb{E}\left[(\epsilon_t^k)^2 \right],$$

whereas the expected vanilla critic loss decomposes as

$$\mathbb{E}[\mathcal{L}_{\text{critic}}] = \mathbb{E}\left[e_t^2 \right] + \mathbb{E}\left[\left(\sum_{k=1}^{K} \epsilon_t^k \right)^2 \right].$$

Moreover,

$$\mathbb{E}\left[\left(\sum_{k=1}^{K} \epsilon_t^k \right)^2 \right] = \sum_{k=1}^{K} \mathbb{E}\left[(\epsilon_t^k)^2 \right] + 2 \sum_{i<j} \mathbb{E}\left[\epsilon_t^i \epsilon_t^j \right].$$

Thus, the vanilla critic loss contains cross-component noise terms, while the reward-wise critic loss decomposes the regression problem across individual reward components. In particular, when the reward noise terms are positively correlated, i.e., $\mathbb{E}[\epsilon_t^i \epsilon_t^j] > 0$ for $i \neq j$, the cross-component terms further increase the noise level of the vanilla critic target.

The proof is provided in Appendix B. Here, the noise refers to the randomness in the Monte Carlo return targets induced by policy sampling, environment stochasticity, and reward estimation, formally defined as $\epsilon_t^k = R_t^k - \mathbb{E}[R_t^k \mid s_t]$. This corresponds to the irreducible noise in the critic regression target, which cannot be eliminated by improving the quality of value function estimation. When rewards are aggregated, these component-wise noise terms are also summed, introducing additional cross-component noise through covariance terms. In particular, when reward components are positively correlated, aggregation further amplifies the noise level in the vanilla critic target. In contrast, the reward-wise critic keeps the regression targets separated and therefore avoids such aggregation-induced cross-component noise. As a result, it provides a cleaner supervision signal for critic learning and mitigates interference across heterogeneous reward components.

4.2. Reward-Wise PPO

Building upon our reward-wise value estimation with a multi-head critic, we introduce reward-wise PPO to further improve policy optimization. Specifically, we decompose the advantage function into reward-wise components and aggregate them for policy updates.

We define the reward-wise advantage as

$$A_t = \sum_{k=1}^{K} A_t^k, \qquad (6)$$

Table 1. Parameter and forward FLOPs comparison of different critic architectures. Here, l denotes the number of Transformer layers, h the hidden dimension, v the vocabulary size, s the sequence length, b the batch size, and K the number of reward components. Detailed derivations of the parameter count and forward FLOPs can be found in Appendix A.

Architecture	Parameter Count	Forward FLOPs
single-head critic	$12lh^2 + vh + h$	$b\big[l(12sh^2 + 2s^2h) + sh\big]$
multi-critic	$K(12lh^2 + vh + h)$	$Kb\big[l(12sh^2 + 2s^2h) + sh\big]$
multi-head critic	$12lh^2 + vh + Kh$	$b\big[l(12sh^2 + 2s^2h) + Ksh\big]$

where each reward-wise advantage is estimated using GAE in a component-wise manner:

$$A_t^k = \sum_{l=0}^{T-t}(\gamma\lambda)^l \delta_{t+l}^k, \quad \delta_t^k = r_t^k + \gamma V_\phi^k(s_{t+1}) - V_\phi^k(s_t),$$
(7)

and $V_\phi^k(s_t)$ denotes the value estimate from the k-th value head corresponding to the k-th reward component. The aggregated advantage A_t is then used in the PPO objective in Eq. (2).

Compared to vanilla PPO, which computes advantages from aggregated rewards, reward-wise PPO estimates advantages separately for each reward component and aggregates them at the policy update stage, enabling more fine-grained credit assignment across heterogeneous rewards. Please refer to the algorithm pseudo-code of reward-wise PPO with multi-head critic learning in Algorithm 1 for details.

5. Experiments

We conduct experiments on multi-turn agentic search and mathematical reasoning tasks to demonstrate the effectiveness of our method. We keep all hyperparameters and reward design the same for reward-wise PPO (RW-PPO) and vanilla PPO. All experiments are conducted on 8×H100 GPUs. Due to space limitations, experiments on mathematical reasoning tasks are provided in Appendix C.

5.1. Experimental Settings

Models and Datasets. We compare our proposed RW-PPO with vanilla PPO on multi-turn agentic search tasks. We train Qwen2.5-3B-Instruct and Qwen2.5-7B-Instruct (Team, 2024) on a mixed training dataset constructed from NQ (Karpukhin et al., 2020) and HotpotQA (Yang et al., 2018), and evaluate the trained models on the test sets of NQ (Karpukhin et al., 2020), TriviaQA (Joshi et al., 2017), PopQA (Mallen et al., 2022), HotpotQA (Yang et al., 2018), 2Wiki (Ho et al., 2020), MuSiQue (Trivedi et al., 2022), and Bamboogle (Press et al., 2023), following the Search-R1 setting (Jin et al., 2025b). We use E5 (Wang et al., 2022) as the retriever, and 2018 Wikipedia dump (Karpukhin et al., 2020) as the corpus. We observe training instability and occasional collapse. For fair comparison, we report the

---

Algorithm 1: Reward-Wise PPO with Multi-Head Critic Learning

Input: Policy model π_θ, old policy $\pi_{\theta_{\text{old}}}$, multi-head critic $V_\phi = \{V_\phi^k\}_{k=1}^K$, reward components $\{r_t^k\}_{k=1}^K$

Output: Updated policy parameters θ and critic parameters ϕ

1 **for** *each training iteration* **do**
   // 1. Rollout stage
2   Collect trajectories using $\pi_{\theta_{\text{old}}}$ and obtain reward components $\{r_t^k\}_{k=1}^K$;
   // 2. Training stage
3   Compute reward-wise value estimates $\{V_\phi^k(s_t)\}_{k=1}^K$ using the multi-head critic;
4   **for** *each reward component $k = 1, \ldots, K$* **do**
5   Compute reward-wise advantages A_t^k using reward-wise GAE in Eq. (7);
6   Compute reward-wise returns R_t^k;
7   Aggregate reward-wise advantages $A_t = \sum_{k=1}^K A_t^k$ as in Eq. (6);
8   Update the policy using the PPO objective in Eq. (2) with the aggregated advantage A_t;
9   Update the multi-head critic using the reward-wise critic loss in Eq. (4);
10 Set $\theta_{\text{old}} \leftarrow \theta$;

---

maximum total reward achieved across all training steps.

Reward Design. We design three terminal reward components: (1) *Format correctness.* This reward ensures structural validity by verifying that the outputs in both the final turn and all intermediate turns comply with the specified format. (2) *Retrieval correctness.* This reward evaluates whether any accepted answer appears in at least one search result (from the <information> tag), using case-insensitive string matching. (3) *Answer correctness.* This reward evaluates whether the extracted answer (from the <answer> tag) exactly matches any accepted ground-truth answer after normalization (e.g., lowercasing and whitespace removal). We assign reward values as $\mathcal{R}_{\text{format}} \in \{0, 0.2\}$, $\mathcal{R}_{\text{ret}} \in \{0, 0.3\}$, and $\mathcal{R}_{\text{ans}} \in \{0, 1.0\}$.

Table 2. Parameter and memory comparison of base models and critics. Memory is estimated in BF16 (2 bytes per parameter). Values in parentheses denote the difference compared to the 1-head critic. For Qwen2.5-3B, the LM head is tied with the input embedding, resulting in negligible parameter difference between the full model and the critic. In contrast, Qwen2.5-7B does not tie word embeddings, so removing the LM head leads to a significant reduction in parameters.

Model	Hidden Size	#Params	Memory (GB)
Qwen2.5-3B-Instruct (full)	2048	3,085,938,688	6.17
Critic (1-head)	2048	3,085,940,736	6.17
Critic (3-head)	2048	3,085,944,832 (+4,096)	6.17 (+8 KB)
Qwen2.5-7B-Instruct (full)	3584	7,615,616,512	15.23
Critic (1-head)	3584	7,070,622,720	14.14
Critic (3-head)	3584	7,070,629,888 (+7,168)	14.14 (+14 KB)

Figure 2. Training dynamics on multi-turn agentic search tasks. The top row shows results for Qwen2.5-3B-Instruct, and the bottom row shows results for Qwen2.5-7B-Instruct. From left to right, we report answer reward, format reward, retrieval reward, and total critic values during training. Compared with vanilla PPO, RW-PPO yields more stable reward trajectories and consistently improves the final total reward, especially for the 3B model.

PPO Training. We enable gradient checkpointing and use FSDP2 with CPU offloading. The learning rates of the policy and critic models are set to 1.0×10^{-6} and 1.0×10^{-5}, respectively. Training is performed for one epoch with one update epoch per batch. The total batch size is 512, with policy and critic mini-batch sizes of 256 and a micro-batch size of 4 per GPU. The maximum input length is set to 4,096 tokens, and the maximum generation length is set to 500 tokens. KL loss is disabled. We apply off-policy correction for token-level importance sampling, with the importance ratio clipped at 2.0. Specifically, we use RW-PPO with three value heads and vanilla PPO with a single value head for the critic.

Rollout Generation. We use vLLM with one inference engine per GPU, tensor parallel size 1, and a GPU memory utilization ratio of 0.5. We sample one response per prompt with a temperature of 1.0 and a top-p value of 1.0. We allow up to 4 search turns and retrieve the top 3 documents for each search query.

5.2. Overhead Analysis

As shown in Table 2, we compare the parameter and memory overhead of the multi-head critic with the single-head critic across different model scales. The multi-head critic introduces negligible overhead compared to the single-head critic. Specifically, adding multiple value heads increases the parameter count by only a few thousand parameters (e.g., +4,096 for 3B and +7,168 for 7B), corresponding to only several kilobytes of additional memory. This overhead is negligible relative to the total model size (on the order of billions of parameters and tens of gigabytes).

5.3. Performance Comparison

As shown in Table 4, RW-PPO consistently outperforms vanilla PPO across both model scales and most datasets. Compared to PPO, RW-PPO achieves higher total rewards on all datasets for the 3B model and on nearly all datasets for the 7B model, demonstrating the effectiveness of reward-wise optimization. These gains are primarily driven by improvements in answer reward, which show larger relative

Table 3. Answer reward comparison across methods. We compare GRPO and PPO with a single answer reward in Search-R1, PPO with multiple rewards, and RW-PPO with multiple rewards on multi-turn agentic search benchmarks. [†] and [*] denote in-domain and out-of-domain datasets, respectively.

Method	NQ[†]	TriviaQA[*]	PopQA[*]	HotpotQA[†]	2Wiki[*]	MuSiQue[*]	Bamboogle[*]	Avg
Qwen2.5-3B-Instruct								
GRPO (single-reward)	0.397	0.565	0.391	0.331	0.310	0.124	0.232	0.336
PPO (single-reward)	0.341	0.545	0.378	0.324	0.319	0.103	0.264	0.325
PPO (multi-reward)	0.383	0.572	0.405	0.362	0.350	0.142	0.352	0.366
RW-PPO (multi-reward)	**0.437**	**0.599**	**0.428**	**0.390**	**0.389**	**0.170**	**0.400**	**0.402**
Qwen2.5-7B-Instruct								
GRPO (single-reward)	0.429	0.623	0.427	0.386	0.346	0.162	0.400	0.396
PPO (single-reward)	0.393	0.610	0.397	0.370	0.414	0.146	0.368	0.385
PPO (multi-reward)	0.472	0.649	0.447	0.445	0.399	**0.216**	0.448	0.439
RW-PPO (multi-reward)	**0.482**	**0.661**	**0.468**	**0.453**	**0.437**	0.207	**0.464**	**0.453**

increases than other reward components. The improvements are particularly notable on out-of-domain datasets such as 2Wiki, MuSiQue, and Bamboogle, where RW-PPO yields gains of up to 9.3% in total reward and over 20% in answer reward for the 3B model, indicating better generalization ability. On in-domain datasets (NQ and HotpotQA), RW-PPO also brings consistent improvements, though the gains are relatively smaller, suggesting that the benefits are more pronounced under distribution shift. Overall, RW-PPO improves the average total reward by 6.2% on the 3B model and 2.4% on the 7B model, while achieving larger gains in answer reward (+9.7% and +3.1%, respectively), showing stronger advantages on smaller models.

As shown in Figure 2, RW-PPO achieves more stable reward trajectories than vanilla PPO on multi-turn agentic search tasks. For the 3B model, PPO collapses in answer, format, and retrieval rewards, while RW-PPO keeps these reward components stable. The total return also remains higher under RW-PPO, suggesting that the multi-head critic learns better value estimates for advantage estimation. For the 7B model, training is more stable for both methods, but RW-PPO still yields higher answer reward, retrieval reward, and total return.

5.4. Benchmark with Other RL Methods

We further benchmark against GRPO and PPO with a single answer reward under the Search-R1 setting (Jin et al., 2025a;b). As shown in Table 3, using multiple rewards consistently improves over single-reward training, showing the benefit of reward shaping. RW-PPO further achieves the best average performance on both 3B and 7B models, demonstrating that reward-wise value estimation can better leverage heterogeneous reward signals.

6. Conclusion

In this paper, we propose reward-wise PPO with a multi-head critic for multi-reward RL in LLMs, enabling reward-wise value estimation and advantage computation while sharing a single efficient critic backbone. Our analysis shows that reward-wise critic learning avoids aggregation-induced cross-component noise, and experiments on multi-turn agentic search and mathematical reasoning tasks demonstrate consistent improvements in both answer reward and total reward over vanilla PPO. These results highlight reward-wise value estimation as an efficient and flexible approach for critic-based multi-reward optimization. One limitation of our work is that our experiments consider a relatively small number of reward components. An interesting future direction is to extend our method to large-scale multi-reward RL scenarios with hundreds of reward components.

Acknowledgments

We are especially thankful to CoreWeave, whose purpose-built AI cloud platform powered our experiments.

Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none which we feel must be specifically highlighted here

Table 4. Performance comparison between RW-PPO and PPO on multi-turn agentic search tasks. We report Answer, Format, Retrieval, and Total rewards. Values in parentheses indicate relative improvements over PPO. Avg denotes the average across all datasets. [†] and [*] denote in-domain and out-of-domain datasets, respectively.

Dataset	Method	Answer (0–1)	Format (0–0.2)	Retrieval (0–0.3)	Total (0–1.5)
		Qwen2.5-3B-Instruct			
NQ[†]	PPO	0.3825	0.1914	0.2171	0.7911
	RW-PPO	**0.4371** (+14.3%)	**0.1995**	0.2171	**0.8537** (+7.9%)
TriviaQA[*]	PPO	0.5717	0.1922	0.2229	0.9868
	RW-PPO	**0.5985** (+4.7%)	**0.1991**	**0.2246**	**1.0222** (+3.6%)
PopQA[*]	PPO	0.4046	0.1946	**0.1976**	0.7968
	RW-PPO	**0.4281** (+5.8%)	**0.1995**	0.1972	**0.8247** (+3.5%)
HotpotQA[†]	PPO	0.3618	0.1924	0.1828	0.7369
	RW-PPO	**0.3904** (+7.9%)	**0.1975**	**0.1873**	**0.7752** (+5.2%)
2Wiki[*]	PPO	0.3497	0.1757	0.1523	0.6777
	RW-PPO	**0.3885** (+11.1%)	**0.1889**	**0.1566**	**0.7340** (+8.3%)
MuSiQue[*]	PPO	0.1415	0.1764	0.1089	0.4268
	RW-PPO	**0.1700** (+20.1%)	**0.1820**	**0.1143**	**0.4663** (+9.3%)
Bamboogle[*]	PPO	0.3520	0.2000	0.1464	0.6984
	RW-PPO	**0.4000** (+13.6%)	0.2000	**0.1560**	**0.7560** (+8.2%)
Avg	PPO	0.3663	0.1889	0.1754	0.7306
	RW-PPO	**0.4018** (+9.7%)	**0.1952**	**0.1790**	**0.7760** (+6.2%)
		Qwen2.5-7B-Instruct			
NQ[†]	PPO	0.4723	0.1987	0.2267	0.8977
	RW-PPO	**0.4820** (+2.1%)	**0.2000**	**0.2344**	**0.9164** (+2.1%)
TriviaQA[*]	PPO	0.6491	0.1979	0.2332	1.0802
	RW-PPO	**0.6606** (+1.8%)	**0.1999**	**0.2358**	**1.0962** (+1.5%)
PopQA[*]	PPO	0.4466	0.1992	0.1945	0.8403
	RW-PPO	**0.4683** (+4.9%)	**0.2000**	**0.2030**	**0.8713** (+3.7%)
HotpotQA[†]	PPO	0.4451	0.1965	0.2000	0.8416
	RW-PPO	**0.4528** (+1.7%)	**0.1998**	**0.2040**	**0.8566** (+1.8%)
2Wiki[*]	PPO	0.3985	0.1778	**0.1654**	0.7417
	RW-PPO	**0.4369** (+9.6%)	**0.1986**	0.1606	**0.7960** (+7.3%)
MuSiQue[*]	PPO	**0.2156**	0.1809	**0.1393**	0.5357
	RW-PPO	0.2069 (-4.0%)	**0.1945**	0.1343	0.5357 (+0.0%)
Bamboogle[*]	PPO	0.4480	**0.2000**	**0.1608**	0.8088
	RW-PPO	**0.4640** (+3.6%)	0.1968	0.1536	**0.8144** (+0.7%)
Avg	PPO	0.4393	0.1930	0.1886	0.8209
	RW-PPO	**0.4531** (+3.1%)	**0.1985**	**0.1894**	**0.8410** (+2.4%)

References

Aggarwal, P. and Welleck, S. L1: Controlling how long a reasoning model thinks with reinforcement learning. *arXiv preprint arXiv:2503.04697*, 2025.

Ahmadian, A., Cremer, C., Gallé, M., Fadaee, M., Kreutzer, J., Pietquin, O., Üstün, A., and Hooker, S. Back to basics: Revisiting reinforce-style optimization for learning from human feedback in llms. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 12248–12267, 2024.

DeepSeek-AI. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning, 2025. URL https://arxiv.org/abs/2501.12948.

Feng, L., Xue, Z., Liu, T., and An, B. Group-in-group policy optimization for llm agent training. *arXiv preprint arXiv:2505.10978*, 2025.

Gunjal, A., Wang, A., Lau, E., Nath, V., He, Y., Liu, B., and Hendryx, S. Rubrics as rewards: Reinforcement learning beyond verifiable domains. *arXiv preprint arXiv:2507.17746*, 2025.

Guo, D., Yang, D., Zhang, H., Song, J., Wang, P., Zhu, Q., Xu, R., Zhang, R., Ma, S., Bi, X., et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025a.

Guo, Y., Xu, L., Liu, J., Ye, D., and Qiu, S. Segment policy optimization: Effective segment-level credit assignment in rl for large language models. *arXiv preprint arXiv:2505.23564*, 2025b.

Ho, X., Nguyen, A.-K. D., Sugawara, S., and Aizawa, A. Constructing a multi-hop qa dataset for comprehensive evaluation of reasoning steps. *arXiv preprint arXiv:2011.01060*, 2020.

Jin, B., Yoon, J., Kargupta, P., Arik, S. O., and Han, J. An empirical study on reinforcement learning for reasoning-search interleaved llm agents. *arXiv preprint arXiv:2505.15117*, 2025a.

Jin, B., Zeng, H., Yue, Z., Yoon, J., Arik, S., Wang, D., Zamani, H., and Han, J. Search-r1: Training llms to reason and leverage search engines with reinforcement learning. *arXiv preprint arXiv:2503.09516*, 2025b.

Joshi, M., Choi, E., Weld, D., and Zettlemoyer, L. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In Barzilay, R. and Kan, M.-Y. (eds.), *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1601–1611, Vancouver, Canada, July 2017. Association for Computational Linguistics. doi: 10.18653/v1/P17-1147. URL https://aclanthology.org/P17-1147/.

Karpukhin, V., Oguz, B., Min, S., Lewis, P. S., Wu, L., Edunov, S., Chen, D., and Yih, W.-t. Dense passage retrieval for open-domain question answering. In *EMNLP (1)*, pp. 6769–6781, 2020.

Kool, W., van Hoof, H., and Welling, M. Buy 4 reinforce samples, get a baseline for free! 2019.

Li, C., Elmahdy, A., Boyd, A., Wang, Z., Garcia, A., Bhatia, P., Kass-Hout, T., Xiao, C., and Hong, M. St-ppo: Stabilized off-policy proximal policy optimization for multi-turn agents training. *arXiv preprint arXiv:2511.20718*, 2025a.

Li, X., Zou, H., and Liu, P. Torl: Scaling tool-integrated rl. *arXiv preprint arXiv:2503.23383*, 2025b.

Li, Y., Xu, J., Li, Z., Liu, J., Liu, W., Tong, Y., Zheng, L., Xue, Z., Zhang, Y., Cai, T., et al. The optimal token baseline: Variance reduction for long-horizon llm-rl. *arXiv preprint arXiv:2602.07078*, 2026.

Lightman, H., Kosaraju, V., Burda, Y., Edwards, H., Baker, B., Lee, T., Leike, J., Schulman, J., Sutskever, I., and Cobbe, K. Let's verify step by step. In *The twelfth international conference on learning representations*, 2023.

Liu, S.-Y., Dong, X., Lu, X., Diao, S., Belcak, P., Liu, M., Chen, M.-H., Yin, H., Wang, Y.-C. F., Cheng, K.-T., et al. Gdpo: Group reward-decoupled normalization policy optimization for multi-reward rl optimization. *arXiv preprint arXiv:2601.05242*, 2026.

Liu, W., Zhou, R., Deng, Y., Huang, Y., Liu, J., Deng, Y., Zhang, Y., and He, J. Learn to reason efficiently with adaptive length-based reward shaping. *arXiv preprint arXiv:2505.15612*, 2025.

Liu, Z., Zhou, Z., Wang, Y., Yang, C., and Qiao, Y. Inference-time language model alignment via integrated value guidance. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 4181–4195, 2024.

Mallen, A., Asai, A., Zhong, V., Das, R., Khashabi, D., and Hajishirzi, H. When not to trust language models: Investigating effectiveness of parametric and non-parametric memories. *arXiv preprint arXiv:2212.10511*, 2022.

Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.

Press, O., Zhang, M., Min, S., Schmidt, L., Smith, N. A., and Lewis, M. Measuring and narrowing the compositionality gap in language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 5687–5711, 2023.

Qian, C., Acikgoz, E. C., He, Q., Wang, H., Chen, X., Hakkani-Tür, D., Tur, G., and Ji, H. Toolrl: Reward is all tool learning needs. *arXiv preprint arXiv:2504.13958*, 2025.

Schulman, J., Moritz, P., Levine, S., Jordan, M., and Abbeel, P. High-dimensional continuous control using generalized advantage estimation. *arXiv preprint arXiv:1506.02438*, 2015.

Schulman, J., Wolski, F., Dhariwal, P., Radford, A., and Klimov, O. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Setlur, A., Nagpal, C., Fisch, A., Geng, X., Eisenstein, J., Agarwal, R., Agarwal, A., Berant, J., and Kumar, A. Rewarding progress: Scaling automated process verifiers for llm reasoning. *arXiv preprint arXiv:2410.08146*, 2024.

Shao, Z., Wang, P., Zhu, Q., Xu, R., Song, J., Bi, X., Zhang, H., Zhang, M., Li, Y., Wu, Y., et al. Deepseekmath: Pushing the limits of mathematical reasoning in open language models. *arXiv preprint arXiv:2402.03300*, 2024.

Team, K., Bai, T., Bai, Y., Bao, Y., Cai, S. H., Cao, Y., Charles, Y., Che, H. S., Chen, C., Chen, G., Chen, H., Chen, J., Chen, J., Chen, J., Chen, J., Chen, K., Chen, L., Chen, R., Chen, X., Chen, Y., Chen, Y., Chen, Y., Chen, Y., Chen, Y., Chen, Y., Chen, Y., Chen, Y., Chen, Z., Chen, Z., Cheng, D., Chu, M., Cui, J., Deng, J., Diao, M., Ding, H., Dong, M., Dong, M., Dong, Y., Dong, Y., Du, A., Du, C., Du, D., Du, L., Du, Y., Fan, Y., Fang, S., Feng, Q., Feng, Y., Fu, G., Fu, K., Gao, H., Gao, T., Ge, Y., Geng, S., Gong, C., Gong, X., Gongque, Z., Gu, Q., Gu, X., Gu, Y., Guan, L., Guo, Y., Hao, X., He, W., He, W., He, Y., Hong, C., Hu, H., Hu, J., Hu, Y., Hu, Z., Huang, K., Huang, R., Huang, W., Huang, Z., Jiang, T., Jiang, Z., Jin, X., Jing, Y., Lai, G., Li, A., Li, C., Li, C., Li, F., Li, G., Li, G., Li, H., Li, H., Li, J., Li, J., Li, J., Li, L., Li, M., Li, W., Li, W., Li, X., Li, X., Li, Y., Li, Y., Li, Y., Li, Y., Li, Z., Li, Z., Liao, W., Lin, J., Lin, X., Lin, Z., Lin, Z., Liu, C., Liu, C., Liu, H., Liu, L., Liu, S., Liu, S., Liu, S., Liu, T., Liu, T., Liu, W., Liu, X., Liu, Y., Liu, Y., Liu, Y., Liu, Y., Liu, Y., Liu, Z., Liu, Z., Lu, E., Lu, H., Lu, Z., Luo, J., Luo, T., Luo, Y., Ma, L., Ma, Y., Mao, S., Mei, Y., Men, X., Meng, F., Meng, Z., Miao, Y., Ni, M., Ouyang, K., Pan, S., Pang, B., Qian, Y., Qin, R., Qin, Z., Qiu, J., Qu, B., Shang, Z., Shao, Y., Shen, T., Shen, Z., Shi, J., Shi, L., Shi, S., Song, F., Song, P., Song, T., Song, X., Su, H., Su, J., Su, Z., Sui, L., Sun, J., Sun, J., Sun, T., Sung, F., Tai, Y., Tang, C., Tang, H., Tang, X., Tang, Z., Tao, J., Teng, S., Tian, C., Tian, P., Wang, A., Wang, B., Wang, C., Wang, C., Wang, C., Wang, D., Wang, D., Wang, D., Wang, F., Wang, H., Wang, H., Wang, H., Wang, H., Wang, H., Wang, J., Wang, J., Wang, J., Wang, K., Wang, L., Wang, Q., Wang, S., Wang, S., Wang, S., Wang, W., Wang, X., Wang, X., Wang, Y., Wang, Y., Wang, Y., Wang, Y., Wang, Y., Wang, Y., Wang, Z., Wang, Z., Wang, Z., Wang, Z., Wang, Z., Wang, Z., Wei, C., Wei, M., Wen, C., Wen, Z., Wu, C., Wu, H., Wu, J., Wu, R., Wu, W., Wu, Y., Wu, Y., Wu, Y., Wu, Z., Xiao, C., Xie, J., Xie, X., Xie, Y., Xin, Y., Xing, B., Xu, B., Xu, J., Xu, J., Xu, J., Xu, L. H., Xu, L., Xu, S., Xu, W., Xu, X., Xu, X., Xu, Y., Xu, Y., Xu, Y., Xu, Z., Xu, Z., Yan, J., Yan, Y., Yang, G., Yang, H., Yang, J., Yang, K., Yang, N., Yang, R., Yang, X., Yang, X., Yang, Y., Yang, Y., Yang, Y., Yang, Z., Yang, Z., Yang, Z., Yao, H., Ye, D., Ye, W., Ye, Z., Yin, B., Yu, C., Yu, L., Yu, T., Yu, T., Yuan, E., Yuan, M., Yuan, X., Yue, Y., Zeng, W., Zha, D., Zhan, H., Zhang, D., Zhang, H., Zhang, J., Zhang, P., Zhang, Q., Zhang, R., Zhang, X., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Y., Zhang, Z., Zhao, C., Zhao, F., Zhao, J., Zhao, S., Zhao, X., Zhao, Y., Zhao, Z., Zheng, H., Zheng, R., Zheng, S., Zheng, T., Zhong, J., Zhong, L., Zhong, W., Zhou, M., Zhou, R., Zhou, X., Zhou, Z., Zhu, J., Zhu, L., Zhu, X., Zhu, Y., Zhu, Z., Zhuang, J., Zhuang, W., Zou, Y., and Zu, X. Kimi k2.5: Visual agentic intelligence, 2026. URL https://arxiv.org/abs/2602.02276.

Team, Q. Qwen2.5: A party of foundation models, September 2024. URL https://qwenlm.github.io/blog/qwen2.5/.

Trivedi, H., Balasubramanian, N., Khot, T., and Sabharwal, A. Musique: Multihop questions via single-hop question composition. *Transactions of the Association for Computational Linguistics*, 10:539–554, 2022.

Wang, L., Yang, N., Huang, X., Jiao, B., Yang, L., Jiang, D., Majumder, R., and Wei, F. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.

Wang, Z., Wang, K., Wang, Q., Zhang, P., Li, L., Yang, Z., Jin, X., Yu, K., Nguyen, M. N., Liu, L., et al. Ragen: Understanding self-evolution in llm agents via multi-turn reinforcement learning. *arXiv preprint arXiv:2504.20073*, 2025.

Wei, Q., Zeng, S., Li, C., Brown, W., Frunza, O., Deng, W., Schneider, A., Nevmyvaka, Y., Zhao, Y. K., Garcia, A., and Hong, M. Reinforcing multi-turn reasoning in llm agents via turn-level reward design, 2025. URL https://arxiv.org/abs/2505.11821.

Xue, Z., Zheng, L., Liu, Q., Li, Y., Zheng, X., Ma, Z., and An, B. Simpletir: End-to-end reinforcement learning for multi-turn tool-integrated reasoning. *arXiv preprint arXiv:2509.02479*, 2025.

Yang, Z., Qi, P., Zhang, S., Bengio, Y., Cohen, W. W., Salakhutdinov, R., and Manning, C. D. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. *arXiv preprint arXiv:1809.09600*, 2018.

Yao, S., Yu, D., Zhao, J., Shafran, I., Griffiths, T., Cao, Y., and Narasimhan, K. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822, 2023.

Yu, Q., Zhang, Z., Zhu, R., Yuan, Y., Zuo, X., Yue, Y., Dai, W., Fan, T., Liu, G., Liu, L., et al. Dapo: An open-source llm reinforcement learning system at scale. *arXiv preprint arXiv:2503.14476*, 2025.

Zeng, W., Huang, Y., Liu, Q., Liu, W., He, K., Ma, Z., and He, J. Simplerl-zoo: Investigating and taming zero reinforcement learning for open base models in the wild. *arXiv preprint arXiv:2503.18892*, 2025.

Zhao, S., Yu, T., Xu, A., Singh, J., Shukla, A., and Akkiraju, R. Parallelsearch: Train your llms to decompose query and search sub-queries in parallel with reinforcement learning. *arXiv preprint arXiv:2508.09303*, 2025.

Zhu, J., Su, Y., and Liu, X. Can textual reasoning improve the performance of mllms on fine-grained visual classification? *arXiv preprint arXiv:2601.06993*, 2026.

A. Detailed Derivations of Parameter Count and Forward FLOPs

In this section, we provide detailed derivations of the parameter count and forward computational cost (FLOPs) for a Transformer-based critic model.

A.1. Parameter Count

We consider a Transformer-based critic with hidden dimension h, vocabulary size v, and l Transformer layers. The total parameter count consists of three parts: input embedding, Transformer backbone, and output head.

Table 5. Parameter count of each component in a Transformer-based critic. Here, h denotes the hidden dimension, v the vocabulary size, and l the number of layers.

Component	Parameter Count
Input Embedding	vh
Q, K, V projections	$3h^2$
Output projection	h^2
Feed-Forward Network	$8h^2$
Per-layer total	$12h^2$
Backbone (l layers)	$12lh^2$
Output Head	h
Total	$12lh^2 + vh + h$

The attention module consists of four projection matrices (query, key, value, and output), contributing $4h^2$ parameters per layer. The feed-forward network (FFN) expands the hidden dimension from h to $4h$ and projects it back, contributing $8h^2$ parameters. Therefore, each layer has $12h^2$ parameters, and the total backbone parameter count is $12lh^2$. The embedding layer contributes vh parameters, and the value head contributes h parameters.

A.2. Forward FLOPs

We now derive the forward computational cost (FLOPs). Let b denote the batch size and s the sequence length.

Although the embedding layer can be written as a matrix multiplication with one-hot inputs, it is implemented as a lookup operation in practice and thus incurs negligible FLOPs. For each Transformer layer, the main computational cost comes from linear projections, attention computation, and the feed-forward network, resulting in $12bsh^2 + 2bs^2h$ FLOPs per layer. Therefore, the total backbone cost is $bl(12sh^2 + 2s^2h)$. The output head introduces an additional bsh FLOPs.

Table 6. Forward FLOPs of each component in a Transformer-based critic. Here, b denotes the batch size, s the sequence length, h the hidden dimension, and l the number of layers.

Component	Forward FLOPs
Input Embedding	negligible
Q, K, V projections	$3bsh^2$
Output projection	bsh^2
Attention computation	$2bs^2h$
Feed-Forward Network	$8bsh^2$
Per-layer total	$12bsh^2 + 2bs^2h$
Backbone (l layers)	$bl(12sh^2 + 2s^2h)$
Output Head	bsh
Total	$b\left[l(12sh^2 + 2s^2h) + sh\right]$

A.3. Discussion

From Table 5 and Table 6, we observe that both the parameter count and computational cost are dominated by the Transformer backbone, particularly the $O(lh^2)$ parameters and $O(blsh^2)$ FLOPs. In contrast, the output head contributes negligible overhead. This observation forms the basis for the efficiency of the proposed multi-head critic design.

B. Proof of Proposition 4.1

Proof. For the reward-wise critic loss, we have

$$\mathcal{L}_{\text{critic}}^{\text{rw}} = \sum_{k=1}^{K} \left(V_\phi^k(s_t) - R_t^k \right)^2.$$

Substituting $R_t^k = \mu_t^k + \epsilon_t^k$ yields

$$\mathcal{L}_{\text{critic}}^{\text{rw}} = \sum_{k=1}^{K} \left(V_\phi^k(s_t) - \mu_t^k - \epsilon_t^k \right)^2 = \sum_{k=1}^{K} \left(e_t^k - \epsilon_t^k \right)^2.$$

Taking expectation and using $\mathbb{E}[\epsilon_t^k \mid s_t] = 0$, we obtain

$$\mathbb{E}[\mathcal{L}_{\text{critic}}^{\text{rw}}] = \sum_{k=1}^{K} \mathbb{E}\left[(e_t^k)^2 \right] + \sum_{k=1}^{K} \mathbb{E}\left[(\epsilon_t^k)^2 \right].$$

For the vanilla critic loss, the aggregated return is

$$R_t = \sum_{k=1}^{K} R_t^k = \sum_{k=1}^{K} \mu_t^k + \sum_{k=1}^{K} \epsilon_t^k.$$

Thus,

$$\mathcal{L}_{\text{critic}} = \left(V_\phi(s_t) - \sum_{k=1}^{K} R_t^k \right)^2 = \left(e_t - \sum_{k=1}^{K} \epsilon_t^k \right)^2.$$

Taking expectation and using the zero-mean noise assumption, we obtain

$$\mathbb{E}[\mathcal{L}_{\text{critic}}] = \mathbb{E}\big[e_t^2\big] + \mathbb{E}\left[\left(\sum_{k=1}^{K} \epsilon_t^k\right)^2\right].$$

Expanding the squared sum yields

$$\mathbb{E}\left[\left(\sum_{k=1}^{K} \epsilon_t^k\right)^2\right] = \sum_{k=1}^{K} \mathbb{E}\big[(\epsilon_t^k)^2\big] + 2\sum_{i<j} \mathbb{E}\big[\epsilon_t^i \epsilon_t^j\big],$$

which completes the proof. $\square$

C. Experiments on Math Reasoning

C.1. Experimental Settings

Experimental Setup. We compare our proposed RW-PPO with vanilla PPO on mathematical reasoning tasks. We train DeepSeek-R1-Distill-Qwen-1.5B and DeepSeek-R1-Distill-Qwen-7B (DeepSeek-AI, 2025) on the DAPO-Math-17k (Yu et al., 2025) dataset, and evaluate them on AIME 2024, AIME 2025, AIME 2026, and AMC datasets. The maximum sequence length is set to 8k tokens.

Reward Design. We design three terminal reward components: (1) *Format correctness*: the model is required to produce outputs with the correct structure, i.e., using XML tags to separate the reasoning (`<think>`) and the final answer (`<answer>`). (2) *Integer correctness*: whether the predicted answer is a valid integer. (3) *Answer correctness*: whether the final answer matches the ground-truth answer. We set the reward values as $\mathcal{R}_{\text{format}} \in \{0, 1.0\}$, $\mathcal{R}_{\text{int}} \in \{0, 1.0\}$, and $\mathcal{R}_{\text{ans}} \in \{0, 1.0\}$.

PPO Training. We enable gradient checkpointing and use FSDP with parameter and optimizer offloading. The learning rates of the policy and critic models are set to 1.0×10^{-6} and 1.0×10^{-5}, respectively. Training is performed for one epoch. The total batch size is 1,024, with a mini-batch size of 256 and a micro-batch size of 4 per GPU. The maximum prompt length is set to 2,048 tokens, and the maximum response length is set to 8,192 tokens. KL loss is disabled. We apply token-level importance sampling for rollout correction, with the importance ratio clipped at 2.0. Specifically, we use RW-PPO with three value heads and vanilla PPO with a single value head for the critic.

Rollout Generation. We use vLLM for rollout generation with tensor parallel size 1 and a GPU memory utilization ratio of 0.5. During training, we sample one response per prompt with a temperature of 1.0 and a top-p value of 1.0. During validation, we sample 16 responses per prompt with a temperature of 0.7 and a top-p value of 0.95.

C.2. Experiment Results

As shown in Table 7, RW-PPO consistently outperforms vanilla PPO across all datasets and model scales. RW-PPO achieves higher total rewards on every benchmark for both the 1.5B and 7B models, demonstrating the effectiveness of reward-wise optimization in mathematical reasoning tasks. These improvements are primarily driven by gains in answer reward, which show significantly larger relative increases compared to format and integer rewards that are already near saturation. The improvements are especially pronounced on more challenging benchmarks such as AIME 2025 and AIME 2026, where RW-PPO yields substantial gains in answer reward (e.g., up to 29.0% for the 1.5B model), leading to consistent improvements in total reward. In contrast, format and integer rewards remain close to their upper bounds for both methods, indicating that RW-PPO mainly improves reasoning accuracy rather than surface-level correctness. Overall, RW-PPO improves the average total reward by 2.3% on the 1.5B model and 1.6% on the 7B model, while achieving larger gains in answer reward (+11.3% and +5.5%, respectively), showing stronger benefits on smaller models.

Table 7. Performance comparison between RW-PPO and PPO on mathematical reasoning benchmarks. We report Answer, Format, Integer, and Total rewards averaged over 16 samples. Values in parentheses indicate relative improvements over PPO.

Dataset	Method	Answer (0–1)	Format (0–1)	Integer (0–1)	Total (0–3)
\multicolumn{6}{c}{*DeepSeek-R1-Distill-Qwen-1.5B*}					
AIME 2024	PPO	0.1396	0.9563	0.9563	2.0521
	RW-PPO	**0.1521** (+8.9%)	**0.9667**	**0.9667**	**2.0854** (+1.6%)
AIME 2025	PPO	0.1583	0.9854	0.9833	2.1271
	RW-PPO	**0.2042** (+29.0%)	**0.9979**	**0.9979**	**2.2000** (+3.4%)
AIME 2026	PPO	0.1500	0.9729	0.9729	2.0958
	RW-PPO	**0.1667** (+11.1%)	**0.9917**	**0.9896**	**2.1479** (+2.5%)
AMC	PPO	0.6516	0.9922	0.9906	2.6344
	RW-PPO	**0.7000** (+7.4%)	0.9922	**0.9922**	**2.6844** (+1.9%)
Avg	PPO	0.2749	0.9767	0.9758	2.2274
	RW-PPO	**0.3058** (+11.3%)	**0.9871**	**0.9866**	**2.2794** (+2.3%)
\multicolumn{6}{c}{*DeepSeek-R1-Distill-Qwen-7B*}					
AIME 2024	PPO	0.2313	0.9875	0.9875	2.2062
	RW-PPO	**0.2500** (+8.1%)	**0.9958**	**0.9958**	**2.2417** (+1.6%)
AIME 2025	PPO	0.2792	0.9938	0.9938	2.2667
	RW-PPO	**0.3083** (+10.4%)	**1.0000**	**1.0000**	**2.3083** (+1.8%)
AIME 2026	PPO	0.3229	0.9750	0.9750	2.2729
	RW-PPO	**0.3583** (+11.0%)	**0.9917**	**0.9917**	**2.3417** (+3.0%)
AMC	PPO	0.8281	0.9984	0.9984	2.8250
	RW-PPO	**0.8359** (+0.9%)	**1.0000**	0.9984	**2.8344** (+0.3%)
Avg	PPO	0.4154	0.9887	0.9887	2.3927
	RW-PPO	**0.4381** (+5.5%)	**0.9969**	**0.9965**	**2.4315** (+1.6%)