TreeAgent: A Generalizable Multi-Agent Framework for Automated Bias Labeling in Forestry via Compiled Expert Rules and Vision-Language Models

Shiyi Chen [1]   Nicholas Saban [1]   Collin Hargreaves [1]   Huiqi Wang [1]

Abstract

Human-labeled data are widely used as reference annotations in ML, despite known variability across annotators in many expert-driven domains. In addition, expert annotation is slow, inconsistent, and remains a major bottleneck for scaling tasks like tree height bias classification in forestry remote sensing. We propose a multi-agent system (MAS) that orchestrates expert decision trees with Vision-Language Models (VLMs), treating the decision tree as a structural prior while VLMs perform localized semantic perception at individual nodes, with multi-agent voting to mitigate VLM stochasticity. We formalize a Decoupled Declarative Decision (D3) Framework that enables zero-modification generalization across diverse expert-defined decision structures. On a tree bias classification testbed, our framework outperforms supervised ML baselines and reduces the amount of expert labeling effort required. These results suggest that agentic orchestration of VLMs with expert priors can reproduce expert-defined labeling procedures at substantially lower annotation cost while maintaining interpretability.

1. Introduction

Tree height underpins terrestrial carbon accounting, biomass estimation, and the climate policies that depend on them (Tompalski et al., 2014; Friedlingstein et al., 2025). Yet its three dominant data sources—field measurements, airborne lidar point clouds, and lidar-derived canopy height models (CHMs)—systematically disagree, each with distinct error modes: field crews struggle with tree tops in closed canopies, lidar misses apexes at low pulse density, and CHMs inherit both issues while adding gridding and interpolation artifacts. The true height of a tree is rarely directly observed, and the bias structure is heterogeneous across trees (Wang et al., 2019; Terryn et al., 2024).

To correct these biases at scale, domain experts hand-label individual trees using a rule-based diagnostic that distinguishes seven bias types from the geometry of measurement disagreement and local canopy context. Each tree takes 3–5 minutes of expert time, and inter-expert inconsistency injects noise into the very "reference" data that downstream ML correction models depend on. Across continental-scale inventories, however, this does not scale.

We argue this task is well suited to a multi-agent LLM system. The expert diagnostic is naturally decomposable: retrieve relevant measurements, reason over their numerical disagreement against a structured rule set, and inspect point-cloud or CHM figures only when the numbers are ambiguous. This decomposition lets us encode expert rules symbolically rather than hoping an LLM internalizes them from prompts, and invokes a vision-language model only at the perceptual steps where it is needed—yielding decisions auditable against the same rule book the experts use.

Naively encoding expert rules, however, creates a new bottleneck: symbolic classifiers tightly couple domain logic with implementation, so every threshold revision or taxonomy change requires re-engineering. We address this with the **Decoupled Declarative Decision (D3) framework**, which separates *what* to decide from *how* to decide it. D3 has two components: a *Logic Primitive Inventory* (LPI) defining a closed vocabulary of atomic execution primitives, and a *Neural Rule Transpiler* (NRT) that compiles natural-language expert rules into executable, validatable decision graphs over the LPI (Yang et al., 2024; Górski et al., 2025). Rule revisions become configuration edits; every decision is traceable to the rule that produced it.

Concretely, we ask: **(RQ1)** Can a VLM reliably detect the perceptual cues, canopy overlap, ground outliers, that experts rely on? **(RQ2)** Can a multi-agent system, given expert rules, classify the seven bias types end-to-end? **(RQ3)** Does the resulting system outperform conventional ML classifiers on this task?

We instantiate D3 as **TreeAgent**, a multi-agent system that answers these questions affirmatively. Our contributions are:

[1]University of California, Berkeley, California, United States. Correspondence to: Huiqi Wang <huiqiwang@berkeley.edu>.

Proceedings of the 43rd International Conference on Machine Learning, Seoul, South Korea. PMLR 306, 2026. Copyright 2026 by the author(s).

(C1) the *D3 framework* for decoupling expert classification logic from execution, with a closed LPI and an LLM-based NRT that compiles expert rules into validated, auditable decision graphs; **(C2)** *TreeAgent*, an instantiation encoding a forestry expert's seven-class bias diagnostic, with a majority-vote VLM agent handling the graph's perceptual nodes; and **(C3)** an *empirical evaluation* on expert-labeled trees from two held-out NEON sites showing TreeAgent reaches 67.6% Macro-F1 at ∼0.040 minutes per tree, against a tuned tabular ML baseline at 36.2% macro-F1 despite extensive feature engineering, imbalance correction, and tabular foundation-model substitution.

Beyond forestry, D3 offers a general recipe for scientific labeling workflows where expert reasoning is structured, evolving, and requires occasional perceptual judgment—a regime where end-to-end models discard interpretability and single-prompt LLMs discard reliability.

2. Related Work

LLMs as compilers for expert knowledge. A growing line of work integrates expert knowledge into LLM-driven pipelines as structured programs rather than free-form prompts (Górski et al., 2025). D3 sits in this lineage but enforces a closed primitive inventory at compile time, so every executable graph is statically validatable before deployment.

Tabular ML and small-data scientific labeling. Gradient-boosted trees remain the dominant model family on small tabular tasks (Breiman, 2001; Chen & Guestrin, 2016; Ke et al., 2017; Grinsztajn et al., 2022); recent tabular foundation models extend this regime with in-context learning (Hollmann et al., 2025). We use these as the supervised baseline and show that even with imbalance correction (Chawla et al., 2002; Lin et al., 2017) and transductive adaptation (Lee, 2013), a tuned ensemble does not match the agent system on the seven-class target.

Forestry remote sensing. The NEON Airborne Observation Platform and the broader literature on LiDAR-derived canopy products document the standard data products and their uncertainties (Duncanson et al., 2015; Thorpe et al., 2016); per-tree bias-source classification has not previously been attempted at scale.

3. Methods

3.1. The D3 Framework

Continuous efforts have been made to integrate expert knowledge into structured forms using LLMs (Górski et al., 2025). We propose **Decoupled Declarative Decision (D3) Framework**, which, as the architectural backbone

of TreeAgent, adopts and expands this idea to also include VLMs. D3 separates *what* a domain expert wants to decide from *how* the system executes that decision. The expert writes a rule ρ in structured natural language; D3 compiles it into a typed graph $\mathcal{T}$ over a fixed, finite **Logic Primitive Inventory** ($\mathcal{V}$); and an orchestrator runs $\mathcal{T}$ on incoming samples (Figure 1). Two practical properties follow: **verifiability** — every classification is traceable to the rule node that produced it, since the rule is compiled into an inspectable graph rather than absorbed into model weights — and **zero-modification generalizability** — when an expert revises a condition or the diagnostic flow, the change is a configuration edit, not a code change.

3.1.1. LOGIC PRIMITIVE INVENTORY (LPI)

The LPI defines a fixed, finite set of node classes $\mathcal{V} = \mathcal{V}_{\text{det}} \cup \mathcal{V}_{\text{vlm}} \cup \mathcal{V}_{\text{exit}}$, partitioned by *execution type* $\omega(v) \in \{\texttt{det}, \texttt{vlm}, \texttt{exit}\}$. The execution type determines *how* the orchestrator will evaluate a node: $\texttt{det}$ nodes are resolved by a closed-form arithmetic predicate; $\texttt{vlm}$ nodes are resolved by querying the vision-language model agent; $\texttt{exit}$ nodes terminate execution and return a class label. Each node class $v \in \mathcal{V}$ is a tuple

$$v = \langle \text{id}(v), \ \omega(v), \ \varepsilon(v), \ \vartheta(v) \rangle, \tag{1}$$

where $\varepsilon(v) \subseteq \mathcal{F} \cup \mathcal{I}$ is the *expected input signature*—the subset of tabular metric fields $\mathcal{F}$ and/or image modalities $\mathcal{I}$ that the node's evaluation kernel requires—and $\vartheta(v)$ is the *evaluation kernel*: a predicate or prompt whose output is always binary ($\{0, 1\}$), forming the branching condition that routes the traversal to one of two successor nodes.

Deterministic nodes ($\mathcal{V}_{\text{det}}$) evaluate a closed-form predicate over $\varepsilon(v) \subseteq \mathcal{F}$, giving an exact, side-effect-free outcome $o_v = \vartheta(v)(x_{\varepsilon(v)}) \in \{0, 1\}$. **VLM nodes** ($\mathcal{V}_{\text{vlm}}$) dispatch $\vartheta(v)$ as a natural-language prompt to a vision-language agent operating on the image modalities in $\varepsilon(v)$; the agent returns a binary outcome. **Exit nodes** ($\mathcal{V}_{\text{exit}}$) carry a class label $\vartheta(v) \in \mathcal{L}$ and terminate execution.

3.1.2. TREE CONFIGURATION

A *tree configuration* $\mathcal{T}$ is a directed acyclic graph instantiated over $\mathcal{V}$:

$$\mathcal{T} = \langle \texttt{tree\_id}, r, N, E \rangle, \tag{2}$$

where $\texttt{tree\_id}$ uniquely identifies the configuration, $r \in N$ is the root node, N is a multiset of node instances drawn from $\mathcal{V}$, and

$$E \subseteq N_{\neg\text{exit}} \times \{0, 1\} \times N \tag{3}$$

is the edge relation mapping each non-exit node and binary outcome to a unique successor. A valid $\mathcal{T}$ satisfies two

Figure 1. **Overview of the D3 Framework.** The architecture decouples domain-specific logic through a fixed Logic Primitive Inventory (LPI). **Top:** the Neural Rule Transpiler (NRT) translates an unstructured expert rule ρ into a structured JSON tree configuration $\mathcal{T}$ via a single inference call. **Bottom:** distinct expert strategies (ρ_A, ρ_B) are compiled into different executable tree structures without altering the underlying Orchestrator or VLM Agent code, achieving zero-modification generalizability.

well-formedness conditions: (1) **Completeness**: every $n \in N_{\neg\text{exit}}$ has exactly one outgoing edge for each outcome in $\{0, 1\}$; and (2) **Vocabulary closure**: the class of every $n \in N$ is an element of $\mathcal{V}$, enforced by a deterministic post-compilation validator (Section 3.1.3).

3.1.3. NEURAL RULE TRANSPILER (NRT)

Given an expert rule ρ expressed in structured natural language and a tree identifier `tree_id`, the NRT produces a tree configuration:

$$\mathcal{C}_\theta : (\rho, \text{tree\_id}) \longmapsto \mathcal{T}, \qquad (4)$$

where $\mathcal{C}_\theta$ is an LLM with parameters θ, prompted with the full vocabulary $\mathcal{V}$ and the JSON schema of $\mathcal{T}$. The model is constrained to output only the JSON serialisation of $\mathcal{T}$; the output space is therefore restricted to $\{\mathcal{T} : \forall n \in N, \text{class}(n) \in \mathcal{V}\}$. Compilation is a single inference call with no agentic loop. Appendix A includes the prompts for the NRT.

Two properties follow from this design. **Verifiability.** Because $\mathcal{V}$ is finite and known at compile time, the validator runs in $O(|N|)$ by checking class membership for each node. Any $\mathcal{T}$ that fails validation is rejected before reaching the orchestrator, guaranteeing that only structurally valid trees are executed. **Semantic alignment without schema exposure.** $\mathcal{C}_\theta$ performs implicit field grounding: natural-language variable references in ρ (e.g. "field-measured tree height") are mapped to canonical identifiers in $\mathcal{F}$ (e.g. `h_field`) as a by-product of compilation. The interface to the domain expert is therefore unrestricted prose ρ; the interface to the orchestrator is a fully typed, validated $\mathcal{T}$. No schema knowledge is required of the expert.

3.1.4. ORCHESTRATOR EXECUTION

The orchestrator traverses $\mathcal{T}$ given a sample $\mathbf{x} = (\mathbf{x}_\mathcal{F}, \mathbf{x}_\mathcal{I})$:

$$n_{t+1} = \text{succ}(n_t,\ o_{n_t}(\mathbf{x})), \qquad (5)$$

$$o_{n_t}(\mathbf{x}) = \begin{cases} \vartheta(n_t)\big(\mathbf{x}_{\varepsilon(n_t)}\big) \\ \qquad \text{if } \omega(n_t) = \text{det}, \\ \mathcal{A}_{\text{vlm}}\big(\vartheta(n_t), \mathbf{x}_{\varepsilon(n_t)}, \text{tree\_id}\big) \\ \qquad \text{if } \omega(n_t) = \text{vlm}, \end{cases} \qquad (6)$$

where $\text{succ}(n, o)$ looks up the successor of node n under outcome o in E. Execution terminates when $\omega(n_t) = \text{exit}$, at which point $\vartheta(n_t) \in \mathcal{L}$ is returned as the classification label. The orchestrator contains no expert rules and is entirely agnostic to the structure of $\mathcal{T}$.

Figure 2. **The VLM agent.** Each VLM node receives a node-specific prompt $\vartheta(v)$, image modalities, and structured fields. To suppress stochasticity, $K=3$ independent samples at temperature $\tau=0.2$ are aggregated by majority vote. Two node classes use deterministic fallbacks when the input alone is sufficient.

3.1.5. CONFIGURATION GENERALIZABILITY

The central property of the D3 Framework is zero-modification reconfigurability within a domain whose decision logic can be expressed using the available primitive inventory: for any expert rule ρ' from the same domain, the full pipeline

$$\rho' \xrightarrow{\mathcal{C}_\theta} \mathcal{T}' \xrightarrow{\text{orchestrator}} \hat{y} \qquad (7)$$

requires no changes to $\mathcal{V}$, $\mathcal{C}_\theta$, the validator, or the orchestrator, provided ρ' can be expressed as a binary decision process over $\mathcal{F} \cup \mathcal{I}$. This holds because the orchestrator's traversal (Eq. 6) is parameterised entirely by $\mathcal{T}$, not hard-coded to any particular rule.

To evaluate zero-modification reconfigurability independently of end-to-end performance, we authored five expert rules in natural language with varying root nodes, branching order, and subsets of $\mathcal{V}$ classes, and passed each to the NRT in a single inference call. All compilations produced tree configurations that passed both manual inspection and the automated vocabulary-closure / completeness validator described in Section 3.1.3.

3.2. The VLM Agent Architecture

VLM agent. Each VLM node delegates to a vision-language agent $\mathcal{A}_{\text{vlm}}$ that receives the prompt $\vartheta(v)$, image inputs $x_{\mathcal{I}(v)}$, and the tree_id. To mitigate sampling variance, we wrap the base model in a $K = 3$ majority vote at temperature $\tau = 0.2$: $o_v = \mathbf{1}\left[\sum_k \hat{o}_v^{(k)} \geq K/2\right]$, with each $\hat{o}_v^{(k)} \in \{0, 1\}$ parsed by regex from the model's response (Figure 2).

VLM Input Figures. For each tree the agent receives (i) a bird's-eye CHM window with crown polygons drawn as

dashed circles, stems as brown dots, and canopy height as a color gradient; and (ii) a two-panel transect cross-section through the stem in the N–S and E–W directions, with returns colored by LiDAR class.

3.3. VLM Prompt Design

Two VLM node classes require visual judgment that cannot be reduced to a formula. Appendix B includes the prompts for the two VLM nodes.

CrownOverlap requires deciding whether a neighboring tree's dashed crown-delineation circle intersects the target tree's crown in a bird's-eye CHM rendering, a judgment that depends on visual context (relative crown sizes, partial occlusion, plot edge effects) and cannot be reduced to a closed-form predicate over the available tabular fields.

GroundPcdOutlier checks whether the ground elevation for a tree in a given year is abnormally high compared to other survey years. A false high ground reading compresses the tree height and requires inspection of a time series transect image of ground elevation across years to spot the outlier.

We test four prompt versions on CrownOverlap to determine how much guidance the model needs to make this call reliably.

VLM Input Figures. Each tree in the evaluation set is represented by two figures passed as visual context:

(i) a bird's-eye canopy height model (CHM) window, with individual tree crown boundaries shown as dashed circles, stem locations as brown dots, and canopy height as a color gradient.

(ii) a two-panel transect cross-section showing the full point cloud in the N–S and E–W directions through the target stem, with returns colored by LiDAR class (ground, low vegetation, high vegetation) and the field-survey measurement point annotated as a red circle.

VLM Prompt variants. We test four prompt versions of increasing detail; full text is in Appendix B. Table 1 shows which components each includes.

Minimal is a bare question with no system context.

V1 adds a system prompt explaining the two figures (color scale, dashed crown circles, stem dots).

V2 keeps the V1 system prompt and adds a five-step chain-of-thought (Wei et al., 2022, p. 2): read axes, locate the target crown, check for circle intersection in Figure 1, compare neighbor heights, and inspect the Figure 2 transect.

V3 replaces the system prompt with expert framing ("experienced forestry and LiDAR analyst") and provides the

most detailed per-figure reading instructions, with explicit disambiguation of crown-circle overlap versus stem-circle containment.

Test setup. We test all four prompt versions on 50 OSBS trees sampled to cover 34 plot–year combinations (random seed 42), ensuring the test set spans different plots and survey years rather than drawing from a single context. Labels were assigned manually and marked for crown overlap, yielding 22 positives and 28 negatives. We report overall accuracy, recall (true-positive rate), and specificity (true-negative rate).

Table 1. Components present in each `CrownOverlap` prompt variant. ✓ = included; − = absent.

Variant	Figure description	Chain-of-thought	Expert framing	`taller` in output
Minimal	−	−	−	−
V1	✓	−	−	−
V2	✓	✓	−	✓
V3	✓	✓	✓	✓

Table 2. Step-by-step reasoning instructions given to the model in V2 and V3.

Step	Action
1	Read Figure 1 axes and canopy height color scale
2	Locate the target tree's crown circle in the bird's-eye map
3	Check whether any neighboring crown circle overlaps the target
4	If overlap: is that neighbor's canopy visually taller?
5	Check Figure 2 cross-section for canopy returns above the target apex

3.4. Supervised ML Baseline

We train a tabular classifier on hand-engineered features summarizing each tree's three height sources and its local point-cloud and DTM context, and use it as the supervised baseline against which we compare TreeAgent. The baseline answers a question distinct from the agent's: *how far does a small-data expert-feature pipeline go on its own?* Its per-class errors also identify which decisions in the expert diagnostic resolve from summary statistics and which require the spatial perception that VLM nodes provide.

Bias taxonomy. Each tree carries one of seven labels assigned by an expert from the disagreement pattern among three height sources: H_{field} (the field-based height), H_{chm} (the canopy height model raster value), and H_{pcd} (the maximum point-cloud return inside the crown buffer). All these three values are absolute elevation, with base of tree elevation added. The labels are: `bias_1`, H_{field} underestimation (the survey reads short); `bias_2`, H_{field} overestimation (the survey reads tall); `bias_3`, H_{chm} overestimation (the CHM is inflated by a taller neighboring canopy); `bias_4`, H_{chm}

underestimation with H_{pcd} matching the field height (the rasterized CHM misses the apex but the raw LiDAR points capture it); `bias_5`, both H_{chm} and H_{pcd} underestimate; `no_bias`, all three sources agree; and `unknown`, the expert could not place the tree in any of the above categories within their five-minute labeling budget.

Data and split. The dataset contains 283 expert-labeled trees from three NEON sites (Thorpe et al., 2016): OSBS (Florida pine-oak), WREF (Washington temperate conifers), and SRER (Arizona desert shrubs). We train on all 136 OSBS trees and test on the 147 WREF and SRER trees, predicting the full seven-class taxonomy. The split is geographic by design: it tests whether a classifier trained in one ecosystem generalises to structurally dissimilar ones, which is the operationally relevant question for continental-scale deployment. We retain the `unknown` class as a target so the classifier predicts over the same label space the experts produced.

Features. We summarize each tree with 25 features grouped by source. From the NEON Vegetation Structure field survey (Thorpe et al., 2016): four numeric measurements (`height`, `stemDiameter`, `crownRadius`, `adjElevation`) and four categorical descriptors (`canopyPosition`, `plantStatus`, `growthForm`, `taxonID`). From the canopy height model raster: `chm_height`, the single-pixel CHM value at the field-survey coordinate, and `chm_height_buff`, the maximum CHM value within a circular buffer of radius $0.9 \times$ `crownRadius` (minimum 1 m) centered on the stem; the buffered version recovers the canopy apex when the stem is offset from the tallest pixel, as is common for leaning trees. From the LiDAR point cloud: `Z_pointcloud` (the mean elevation of returns classified as ground, i.e. LAS classification code 2, inside the per-tree buffer; this is a local terrain height); `std_pointcloud` (the standard deviation of those ground-point elevations, a local terrain roughness); `pointdensity_ground_tree` (the count of ground points per unit area); and three Digital Terrain Model (DTM) quality measures: `dtm_nn` (the elevation reported by the nearest defined DTM grid cell), `dtm_nn_dist` (the distance to that cell, where large values flag unreliable terrain interpolation), and `dtm_buffer` (the mean DTM elevation inside the per-tree buffer). The remaining nine features are derived ratios and differences (Appendix C): notably `diff_chm_survey` ($H_{\text{chm}} - H_{\text{field}}$), `diff_chm_buff_survey`, `ground_elevation_diff`, and `height_to_crown_ratio`.

Models. LightGBM (Ke et al., 2017) is the primary model, motivated by the dominance of gradient-boosted decision trees on small tabular tasks (Grinsztajn et al., 2022). Class

weights are set to inverse class frequency to handle the 4-to-46 sample imbalance across the seven classes. Hyperparameters are fixed (maximum depth 3, 300 boosting rounds, L_1/L_2 regularization $= 2.0$, subsample $= 0.7$); we do not cross-validate given $n_{\text{train}} = 136$. Appendix D reports XGBoost (Chen & Guestrin, 2016), Random Forest (Breiman, 2001), CatBoost, HistGradientBoosting, a stacking ensemble (LightGBM, RF, and XGBoost feeding a logistic regression meta-learner with out-of-fold predictions), and the TabPFN tabular foundation model (Hollmann et al., 2025) as model-family ablations.

Point cloud as features. The hand-engineered features encode substantial expert knowledge: which CHM neighbourhood to read (buffered max, not point), which ground-quality summaries discriminate, and how to enforce scale-invariance across ecosystems. We isolate the value of this expert pipeline by asking the complementary question: can a learned representation, trained end-to-end on the same raw point clouds, recover this performance from labels alone? A negative result supports the framing of D3, which assumes the expert rules carry information small-data learning cannot easily extract. For each tree we crop the LAS tile to a circular buffer at the field-survey coordinate (radius $= \max(\texttt{crownRadius}, 2\text{m})$), then sample or pad to 1024 points, with the LAS classification code retained as additional feature alongside. Extraction succeeds for all 283 trees. The model is a stripped-down PointNet (Qi et al., 2017) with three Conv1D layers, batch normalisation, max-pool over points, two FC layers, and dropout; we omit the T-Net because it overfits at this scale. Training uses AdamW with cosine LR decay, balanced class weights, and augmentation by random rotation around the vertical axis, jitter, and 5% point dropout. We grid-search hidden width $\in \{32, 64, 128\}$ and learning rate $\in \{10^{-3}, 3 \times 10^{-4}\}$ for 80 epochs each. The split and target match the supervised baseline.

4. Results

4.1. TreeAgent Evaluation

We evaluate TreeAgent on 147 expert-labeled trees from the SRER and WREF sites drawn from the NEON API, treating human-assigned bias labels as reference labels produced under the expert diagnostic protocol. We compare against the supervised ML baseline of Section 3.4 and the single-VLM prompt results of Section 4.2.

TreeAgent's behaviour depends on the natural-language rule passed to the NRT, and a single expert diagnostic admits several semantically plausible phrasings of the $\texttt{NoDiff}$ tolerance — $<$ vs $\leq$, and normalisation by H_{field} (elevation of the tree apex) vs $\texttt{survey\_height}$ (tree height value). To avoid conditioning the headline on a post-hoc rule choice,

we freeze a single rule *a priori* on procedural grounds and report that as the headline, then report the three remaining variants as a sensitivity check. The frozen-rule layer is the apples-to-apples comparison against the LightGBM baseline.

Headline rule (chosen *a priori*). The human annotators used a tolerance of 2% of the survey height with non-strict inequality when assigning the $\texttt{NoDiff}$ label. We therefore freeze

$$(\{H_{\text{chm}}, H_{\text{pcd}}\} - H_{\text{field}})/\texttt{survey\_height} \leq 0.02$$

as the headline rule because it matches the annotation procedure that generated the ground-truth labels. We emphasise that this rule was selected for procedural fidelity, *not* because it maximised any test metric.

Headline result. Under the frozen rule, TreeAgent reaches **67.6%** Macro-F1 with an average per-tree runtime of **0.040** minutes (Table 3), against 36.2% Macro-F1 for the tuned LightGBM baseline (Section 4.3) and roughly 5 minutes per tree for human annotation. Per-class recalls under this rule are in Table 4.

Table 3. TreeAgent under the frozen headline rule, against the supervised baseline and human annotation (reference). Human labeling is included as a time-cost reference baseline only.

Method	Time (min)	Macro-F1
TreeAgent (frozen rule)	0.040 ± 0.007	67.6%
Supervised ML (LightGBM)	N/A	36.2%
Human Labeling (reference)	5.0 ± 2.0	N/A

Table 4. Per-class recall under the frozen headline rule. n is the number of test trees in each class.

Bias class	Recall	N
1 H_FIELD UNDERESTIMATION	$72.2 \pm 17.2\%$	18
2 H_FIELD OVERESTIMATION	$65.9 \pm 9.0\%$	41
3 H_CHM OVERESTIMATION	$71.4 \pm 25.2\%$	7
4 H_CHM UNDERESTIMATION ONLY	$66.7 \pm 20.7\%$	9
5 H_CHM AND H_PCD UNDERESTIMATION	$66.7 \pm 16.0\%$	12
6 NO DIFFERENCE	$85.7 \pm 0.0\%$	14
7 UNKNOWN	$72.2 \pm 8.6\%$	46

Human-label variability. We acknowledge that in practice, trees in complex situations may receive different labels from experts with varying domain experience and training quality. The labels are therefore better viewed as expert reference annotations than as objective ground truth. Since our evaluation assumes a single expert annotation per tree, the reported Macro-F1 should be interpreted as agreement with one expert-generated reference label rather than as an estimate of absolute labeling correctness. Collecting multiple

independent annotations per tree and measuring inter-expert agreement would provide a stronger benchmark for future studies.

Sensitivity to fidelity of expert rule. To check whether the headline result is an artifact of how the `NoDiff` predicate is phrased, we re-ran the full pipeline under three additional variants of the same predicate, varying the inequality ($<$ vs $\leq$) and the normalizer (H_{field} vs `survey_height`). All four variants were specified prior to evaluation; we did not search for the rule that maximized the performance of the test. Table 5 reports per-variant Macro-F1 on the same SRER+WREF test set; we report each variant individually rather than summary statistics, since with $n=4$ a mean or percentile would overstate what we can conclude.

Table 5. TreeAgent Macro-F1 under four rule phrasings of the `NoDiff` predicate, on the SRER+WREF test set. The headline rule is frozen *a priori* for procedural fidelity to the annotation procedure.

RULE FOR NODIFF	MACRO-F1
$(\{H_{\text{chm}}, H_{\text{pcd}}\} - H_{\text{field}}) / H_{\text{field}} < 0.02$	29.2%
$(\{H_{\text{chm}}, H_{\text{pcd}}\} - H_{\text{field}}) / H_{\text{field}} \leq 0.02$	21.9%
$(\{H_{\text{chm}}, H_{\text{pcd}}\} - H_{\text{field}}) / \text{SURVEY\_HEIGHT} < 0.02$	35.2%
$(\{H_{\text{chm}}, H_{\text{pcd}}\} - H_{\text{field}}) / \text{SURVEY\_HEIGHT} \leq 0.02$ **(HEADLINE)**	**67.6%**
LIGHTGBM BASELINE (SEC. 4.3)	36.2%

The four variants span 21.9–67.6% Macro-F1, with the headline rule, the last of the four. Given a faithfully-encoded rule, the headline rule clearly outperforms the LightGBM baseline; the other three variants reach 21.9–35.2% and either match or fall below 36.2%. The four rules are mathematically distinct decision procedures: the headline rule remains the closest to the annotation procedure used to generate the reference labels, while the other three answer subtly different questions. The system's accuracy therefore depends on the fidelity between the encoded rule and the rule used by annotators. This is a deliberate design choice — D3 is built to faithfully execute expert rules, not to be robust to misspecification of them — and it places the burden on rule elicitation rather than on the executor.

Limitations of deterministic rules on edge cases. Despite operating as a deterministic rule-based system at $\mathcal{V}_{\text{det}}$ nodes, TreeAgent misclassifies 2 trees in the `NoDiff` class (Bias 6) under the headline rule. Both cases are edge-case violations of the 2% tolerance. Routing boundary instances to a VLM node for adjudication is one option, but introducing VLM calls at deterministic nodes would substantially increase per-tree cost and latency. This points to an inherent tension in rule-driven agent systems: hard symbolic thresholds are brittle at their boundaries, but softening them with learned or visual adjudication carries a non-trivial computational cost. The rarity of these cases suggests the current design is a reasonable operating point; future work could

consider lightweight confidence scoring on deterministic predicates to flag boundary cases for targeted VLM escalation.

4.2. VLM Evaluation

Table 6 reports the `CrownOverlap` prompt version results. All four versions tend to predict overlap: the **Minimal** prompt achieves perfect recall (100%) but only 7.1% specificity, flagging 26 of 28 negative trees as positive. More detailed prompts reduce false positives: V1 cuts false positives from 26 to 21 and raises specificity to 25.0%, while V3 reduces false positives to 17 and achieves 39.3% specificity, the highest of any version.

This comes at a recall cost. V3 misses 2 true overlaps that every other version catches; V2 misses 1. We adopt **V1** as the default prompt for the `CrownOverlap` node because it keeps recall high (100%, zero missed overlaps) while cutting false positives, and missing a real overlap is a worse outcome than a false alarm when a human is reviewing the flags anyway. V3 yields the highest overall accuracy (62%) but its missed cases mean real overlaps go unflagged.

When the model prediction clearly contradicts the image, this reflects a VLM limitation. General-purpose VLMs are pretrained predominantly on natural imagery and have not been exposed to LiDAR-specific rendering conventions (Weng et al., 2025), making it harder to interpret complicated crown boundaries where the decision to label crown overlap is marginal. Fine-tuning an image model on domain-specific LiDAR data is a natural next step. We also note that some ground-truth labels in this set may contain human labeling error.

Table 6. Prompt version results on $n=50$ OSBS trees (22 positive, 28 negative). Model: `claude-sonnet-4-6`. FP = false positives; FN = false negatives.

Version	Accuracy	Recall	Specificity	FP / FN
Minimal	48.0%	100.0%	7.1%	26 / 0
V1	58.0%	100.0%	25.0%	21 / 0
V2	52.0%	95.5%	17.9%	23 / 1
V3	62.0%	90.9%	39.3%	17 / 2

4.3. ML Baseline: Headline 7-Class Result

On the geographic split (train OSBS $n = 136$, test WREF $n = 79$ + SRER $n = 68$), LightGBM with class-weighted training reaches a test **macro-F1 of 36.2%** on the seven-class bias taxonomy. Per-site, the model attains 40.8% on WREF and 14.2% on SRER (Table 7). Train macro-F1 reaches 86%: the model fits OSBS well, but the fit does not fully transfer to either test ecosystem. The dominant per-class failure is `bias_2` (H_{field} overestimation) being

predicted as `bias_4` (H_{chm} underestimation only). Both classes produce $H_{\text{chm}} < H_{\text{field}}$ and are indistinguishable from summary statistics, discriminating between them requires spatial evidence (was a neighboring crown inflating the field reading? did rasterization miss the apex?) that the tabular features discard. The `unknown` class is also hard to predict: it captures trees the experts could not place in any mechanism category within five minutes, so the class spans the same feature space as the other six rather than occupying a coherent region.

Table 7. Supervised ML baseline on the seven-class bias taxonomy. Train: OSBS ($n = 136$). Test: WREF ($n = 79$), SRER ($n = 68$). Numbers are test macro-F1.

Site	Test macro-F1 ↑
WREF	40.8%
SRER	14.2%
Combined (WREF + SRER)	**36.2%**

Robustness of the headline. The 36.2% macro-F1 result is stable across the configuration space; no single intervention pushes performance meaningfully past it. Five interaction features targeting the dominant `bias_2`/`bias_4` confusion lift macro-F1 to 37.3%; SMOTE (Chawla et al., 2002) and its Borderline and ADASYN variants drop it to 30.0%–34.1%; focal-style reweighting (Lin et al., 2017) reaches 34.5%; transductive and `unknown`-only pseudo-labeling (Lee, 2013) stay in 34.9%–35.1%. Model-family substitutions (CatBoost 35.3%; HistGradientBoosting 26.3%; LightGBM+RF+XGBoost stacking (Breiman, 2001; Chen & Guestrin, 2016) 20.9%) and a tabular foundation model (TabPFN (Hollmann et al., 2025), 24.6%) all underperform LightGBM. Adding the per-tree point-cloud maximum H_{pcd} together with seven derived percentile statistics drops macro-F1 to 32.4%, and PointNet (Qi et al., 2017) on the cropped raw point clouds underperforms the expert-feature baseline. The largest single performance lift comes from abandoning the cross-site split: a pooled classifier on stratified 20% per-site holdouts reaches $45.1\% \pm 7.0\%$ macro-F1 over five seeds, an +8.9-point lift over the 36.2% headline. Cross-site ecosystem shift therefore accounts for roughly a quarter of the gap to within-site performance, with the remainder reflecting absolute training-set size. Per-configuration numbers, the reversed-split robustness check, and full ablation are in Appendix D.

Limitations. Four caveats apply. First, $n_{\text{train}} = 136$ trees come from a single site (OSBS); the numbers reflect a worst-case single-site training scenario. Second, the training set is too small for reliable held-out hyperparameter tuning, so we fix hyperparameters by hand. Third, results depend on the specific site pairing of the geographic split; the reversed-split numbers in Appendix D are the closest available ro-

bustness check. Fourth, we report point estimates without confidence intervals; bootstrap CIs would tighten the per-site comparisons given the single-digit test counts on some bias categories.

5. Conclusion

We presented TreeAgent, a multi-agent framework for automated tree-level bias labeling in forest remote sensing that combines expert decision rules with Vision-Language Models under the Decoupled Declarative Decision (D3) framework. TreeAgent achieves substantially higher agreement with expert-provided reference labels than the supervised ML baseline (67.6% vs. 36.2% Macro-F1) and reproduces expert-defined labels at 0.040 minutes per tree, compared with approximately 5 minutes of expert annotation effort. These results demonstrate that agentic orchestration of structured expert priors with VLMs is a viable path toward scalable, interpretable annotation in domains where ground truth is expensive.

Two complementary findings characterize the system's current ceiling. First, **VLM output is the dominant source of labeling error**: recall is highest in classes resolved by deterministic nodes alone and degrades progressively with VLM involvement. This bottleneck is not a structural flaw of D3, the deterministic layer performs reliably, but a reflection of the limits of current general-purpose VLMs on specialized forestry imagery. Second, the deterministic layer itself exhibits **brittleness at threshold boundaries**: two no-difference trees that nominally fall under a pure arithmetic rule are misclassified because their measurements sit at the edge of the 2% tolerance, a regime where no symbolic rule can yet substitute for genuine perceptual judgment.

These findings suggest two directions for future work. On the VLM side, domain adaptation, through fine-tuning on labeled CHM and LiDAR transect imagery or retrieval-augmented prompting with similar resolved cases, could close the accuracy gap in visually ambiguous classes without changing the D3 framework. On the rule side, augmenting the `NoDiff` and other threshold predicates with lightweight confidence scores could enable selective VLM escalation, targeting only the cases where the deterministic predicate is genuinely uncertain. While evaluated only in forestry, D3 suggests a possible recipe for scientific labeling workflows in domains where expert reasoning is structured and evolving but occasional perceptual judgment is unavoidable. By separating what to decide from how to decide it, the framework accommodates rule revisions without re-engineering and produces decisions that are auditable against the same diagnostic logic domain experts apply—properties that matter as much for trust and reproducibility as for accuracy in high-stakes annotation pipelines.

Impact Statement

This work aims to scale expert-driven scientific labeling in forest remote sensing, where tree-height bias correction underpins biomass and carbon estimates used in climate policy. By orchestrating expert rules with VLMs, TreeAgent reduces annotation cost while preserving auditability—each decision traces to an expert rule rather than opaque model weights. To our knowledge, this is the first agent system designed for this purpose in forestry, with the potential to quantify height-induced biases in tree biomass estimation at national scale far faster than current expert workflows allow. Although demonstrated only in forestry, the framework may be applicable to other domains where expert decision procedures can be formalized into structured rules. We caution that the system's labels are not a substitute for expert review in high-stakes inventories: VLM errors on perceptual nodes propagate to downstream carbon estimates, and the D3 framework inherits whatever biases exist in the encoded expert rules.

References

Breiman, L. Random forests. *Machine Learning*, 45(1): 5–32, 2001. doi: 10.1023/A:1010933404324.

Chawla, N. V., Bowyer, K. W., Hall, L. O., and Kegelmeyer, W. P. SMOTE: Synthetic minority over-sampling technique. *Journal of Artificial Intelligence Research*, 16: 321–357, 2002. doi: 10.1613/jair.953.

Chen, T. and Guestrin, C. XGBoost: A scalable tree boosting system. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 785–794, 2016. doi: 10.1145/2939672.2939785.

Duncanson, L. I., Dubayah, R. O., Cook, B. D., Rosette, J., and Parker, G. The importance of spatial detail: Assessing the utility of individual crown information and scaling approaches for lidar-based biomass density estimation. *Remote Sensing of Environment*, 168:102–112, 2015. doi: 10.1016/j.rse.2015.06.021.

Friedlingstein, P., O'Sullivan, M., Jones, M. W., et al. Global carbon budget 2024. *Earth System Science Data*, 17(3):965–1039, 2025. doi: 10.5194/essd-17-965-2025. URL https://essd.copernicus.org/articles/17/965/2025/.

Górski, F., Wysocki, O., Valentino, M., and Freitas, A. Integrating expert knowledge into logical programs via llms. In *arXiv Preprint*, 2025. doi: 10.48550/arXiv.2502.12275.

Grinsztajn, L., Oyallon, E., and Varoquaux, G. Why do tree-based models still outperform deep learning on typ-ical tabular data? In *Advances in Neural Information Processing Systems*, volume 35, 2022.

Hollmann, N., Müller, S., Purucker, L., Krishnakumar, A., Körfer, M., Hoo, S. B., Schirrmeister, R. T., and Hutter, F. Accurate predictions on small data with a tabular foundation model. *Nature*, 637(8045):319–326, 2025. doi: 10.1038/s41586-024-08328-6.

Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., and Liu, T.-Y. LightGBM: A highly efficient gradient boosting decision tree. In *Advances in Neural Information Processing Systems*, volume 30, pp. 3146–3154, 2017.

Lee, D.-H. Pseudo-label: The simple and efficient semi-supervised learning method for deep neural networks. In *Workshop on Challenges in Representation Learning, ICML*, 2013.

Lin, T.-Y., Goyal, P., Girshick, R., He, K., and Dollár, P. Focal loss for dense object detection. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, pp. 2999–3007, 2017. doi: 10.1109/ICCV.2017.324.

Qi, C. R., Su, H., Mo, K., and Guibas, L. J. PointNet: Deep learning on point sets for 3D classification and segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 77–85, 2017. doi: 10.1109/CVPR.2017.16.

Terryn, L., Calders, K., Meunier, F., Bauters, M., Boeckx, P., Brede, B., Burt, A., Chave, J., da Costa, A. C. L., D'hont, B., Disney, M., Jucker, T., Lau, A., Laurance, S. G. W., Maeda, E. E., Meir, P., Krishna Moorthy, S. M., Nunes, M. H., Shenkin, A., Sibret, T., Verhelst, T. E., Wilkes, P., and Verbeeck, H. New tree height allometries derived from terrestrial laser scanning reveal substantial discrepancies with forest inventory methods in tropical rainforests. *Global Change Biology*, 30(8):e17473, 2024. doi: https://doi.org/10.1111/gcb.17473. URL https://onlinelibrary.wiley.com/doi/abs/10.1111/gcb.17473. e17473 GCB-24-1584.R1.

Thorpe, A. S., Barnett, D. T., Elmendorf, S. C., Hinckley, E.-L. S., Hoekman, D., Jones, K. D., LeVan, K. E., Meier, C. L., Stanish, L. F., and Thibault, K. M. Introduction to the sampling designs of the National Ecological Observatory Network Terrestrial Observation System. *Ecosphere*, 7(12):e01627, 2016. doi: 10.1002/ecs2.1627.

Tompalski, P., Coops, N. C., White, J. C., and Wulder, M. A. Simulating the impacts of error in species and height upon tree volume derived from airborne laser scanning data. *Forest Ecology and*

Management, 327:167–177, 2014. ISSN 0378-1127. doi: https://doi.org/10.1016/j.foreco.2014.05.011. URL https://www.sciencedirect.com/science/article/pii/S0378112714002916.

Wang, Y., Lehtomäki, M., Liang, X., Pyörälä, J., Kukko, A., Jaakkola, A., Liu, J., Feng, Z., Chen, R., and Hyyppä, J. Is field-measured tree height as reliable as believed – a comparison study of tree height estimates from field measurement, airborne laser scanning and terrestrial laser scanning in a boreal forest. *ISPRS Journal of Photogrammetry and Remote Sensing*, 147:132–145, 2019. ISSN 0924-2716. doi: https://doi.org/10.1016/j.isprsjprs.2018.11.008. URL https://www.sciencedirect.com/science/article/pii/S0924271618303046.

Wei, J., Wang, X., Schuurmans, D., Bosma, M., Ichter, B., Xia, F., Chi, E., Le, Q. V., and Zhou, D. Chain-of-thought prompting elicits reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 35, pp. 24824–24837, 2022.

Weng, X., Pang, C., and Xia, G.-S. Vision-language modeling meets remote sensing: Models, datasets and perspectives. *arXiv preprint arXiv:2505.14361*, 2025.

Yang, A. Z., Takashima, Y., Paulsen, B., Dodds, J., and Kroening, D. Vert: Verified equivalent rust transpilation with large language models as few-shot learners, 2024. URL https://arxiv.org/html/2404.18852v2.

A. D3 Framework Neural Rule Transpiler Prompt

System prompt:

```
You are a converter that translates an expert-defined classification rule (written in
    markdown) into a JSON TreeConfig for a multi-agent tree classifier.

Available Node Classes

Each node has a fixed id, type, fields, and condition. You must use ONLY these classes:

Deterministic nodes (evaluate numeric conditions from CSV data and/or presence of data)
- HeightComparatorChmPcd -> id: "chm_pcd" | true if h_chm < h_pcd
# ...
# Full node-class definitions withheld pending separate publication.

VLM nodes (require visual inspection of images)
- CrownOverlap -> id: "crown_overlap" | true if crown overlap detected
- GroundPcdOutlier -> id: "ground_pcd_outlier" | true if ground point cloud outlier
    detected

End nodes (classification result)
- FieldUnderestimation -> id: "1" | label: H_field Underestimation
- FieldOverestimation -> id: "2" | label: H_field Overestimation
- ChmOverestimation -> id: "3" | label: H_chm Overestimation
- ChmUnderestimation -> id: "4" | label: H_chm Underestimation
- ChmPcdUnderestimation -> id: "5" | label: H_chm and H_pcd Underestimation
- NoDifference -> id: "6" | label: No Difference
- Unknown -> id: "7" | label: Unknown

Output Format

Output ONLY valid JSON, **no explanation, no markdown fences**. The format is:

{
  "tree_id": "<tree_id provided by user>",
  "root": "<node_id of the first node>",
  "nodes": {
    "<node_id>": {
      "class": "<NodeClassName>",
      "edges": {
        "True": "<next_node_id>",
        "False": "<next_node_id>"
      }
    },
    ...
    "<end_node_id>": {
      "class": "<EndNodeClassName>"
    }
  }
}

Rules
- End nodes do NOT have edges.
- Every non-end node MUST have edges with "true" and "false" keys.
- All node ids referenced in edges must exist as keys in "nodes".
- Use the exact node ids listed above (e.g. "chm_pcd", "crown_overlap", "1", "7").
- End nodes (type "end") may share ids across the tree since they have no edges.
- Non-end nodes must have globally unique ids. If the same logical check appears
  at multiple positions with different children, append a suffix to distinguish them,
  e.g. "chm_pcd_1", "chm_pcd_2". The "class" field still indicates which Node class to
      use.
- tree_id must be exactly the string passed in by the user.
```

User prompt:

```
tree_id: {tree_id}

Expert rule:
      {rule_markdown}

Output ONLY valid JSON, no explanation, no markdown fences.
```

B. CrownOverlap Prompt Variants

Minimal

System prompt: none.

User turn:

```
Is there crown overlap between the target tree and any neighboring tree?

Return ONLY this JSON:
{
  "crown_overlap_detected": <true|false>,
  "confidence": <0.0-1.0>
}
```

V1

System prompt:

```
You are analyzing two LiDAR figures of a forest plot.

Figure 1 - bird's-eye canopy height model (CHM):
 - Background color shows canopy height. Warmer / lighter = taller canopy.
 - Dashed circles show individual tree crown boundaries.
 - Brown dots show stem locations (trunk base).
 - The target tree is identified by its ID in the image title.

Figure 2 - transect cross-section (two side-by-side panels):
 - Left panel: N-S cross-section. Right panel: E-W cross-section.
 - Point cloud colored by LiDAR class:
     Dark gray = ground returns.
     Yellow / orange = low vegetation.
     Green = high vegetation / canopy.
 - Red circles mark survey measurement points.

Output ONLY valid JSON. No prose, no markdown fences.
```

User turn:

```
Does any neighboring tree's crown circle overlap the target tree's crown circle?

Return exactly this JSON:
{
  "crown_overlap_detected": <true|false>,
  "overlap_description": "<brief description of what you see>",
  "confidence": <0.0-1.0>
}
```

V2

System prompt: same as V1.

User turn:

```
Does any neighboring tree's crown circle intersect or overlap the target tree's
crown circle, and is that neighbor taller?

Step 1 - Read Figure 1 axes and color scale.
Step 2 - Locate the target tree's dashed crown circle in Figure 1.
Step 3 - Do any OTHER crown circles intersect or overlap the TARGET CROWN
      CIRCLE? (Circles cross or one partially covers the other. NOT
      whether a circle covers a stem dot.)
Step 4 - If overlap found: is that neighbor's CHM color warmer / lighter?
Step 5 - In Figure 2: are there green (Class 5) returns at a HIGHER elevation
      than the target apex, within the lateral extent of the target crown?

Return exactly this JSON:
{
  "crown_overlap_detected": <true|false>,
  "taller_neighbor_detected": <true|false>,
  "overlap_description": "<2-3 sentences citing specific visual evidence>",
  "confidence": <0.0-1.0>
}

Rules:
  - crown_overlap_detected = true if dashed circles cross, regardless of
    stem positions.
  - taller_neighbor_detected = true only if the overlapping neighbor is
    visually taller.
  - When evidence is ambiguous, default both to false and set confidence < 0.5.
```

V3

System prompt:

```
You are an experienced forestry and LiDAR expert. Your task is to determine
whether a target tree's height measurement could be inflated by a taller
neighboring tree's crown.

Figure 1 - bird's-eye canopy height model (CHM):
  - Background color shows canopy height. Warmer / lighter = taller canopy.
  - Dashed circles show individual tree crown boundaries.
  - Brown dots show stem locations (trunk base).
  - The target tree is identified by its ID in the image title.

Figure 2 - transect cross-section (two side-by-side panels):
  - Left panel: N-S transect (X = Northing, Y = elevation in meters).
  - Right panel: E-W transect (X = Easting, Y = elevation in meters).
  - Point cloud colored by LiDAR class:
      Class 1 (dark gray): ground returns.
      Class 2 (yellow / orange): low vegetation.
      Class 5 (green): high vegetation / canopy.
  - Red circles mark survey measurement points.

Output ONLY valid JSON. No prose, no markdown fences.
```

User turn:

```
Determine whether any neighboring tree's crown circle intersects or overlaps
the target tree's crown circle, and whether any such neighbor is taller.

Step 1 - Read Figure 1 axes and scale (Easting, Northing, height color range).
Step 2 - Locate the target tree's dashed crown circle; note if identification
      is clear or ambiguous.
Step 3 - From Figure 1: do any OTHER crown circles intersect or overlap the
      TARGET CROWN CIRCLE? (Circles cross or one partially covers the
      other -- NOT whether a circle covers a stem dot.) If yes, is that
```

```
          neighbor's CHM color warmer / lighter (taller)?
Step 4 - From Figure 2: locate the grey cylinder (target trunk/crown). Are
          there substantial green (Class 5) returns at a HIGHER elevation than
          the target apex within the lateral extent of the target crown?

Return exactly this JSON:
{
  "crown_overlap_detected": <true|false>,
  "taller_neighbor_detected": <true|false>,
  "overlap_description": "<2-3 sentences citing specific visual evidence>",
  "confidence": <0.0-1.0>
}

Rules:
  - crown_overlap_detected = true if dashed circles cross or one partially
    covers the other, regardless of stem positions.
  - taller_neighbor_detected = true only if such a neighbor is visually taller.
  - When evidence is ambiguous, default both to false and set confidence < 0.5.
```

C. Full feature list for the supervised ML baseline

Table 8 lists all 25 features used by the supervised ML baseline (Section 3.4), with their source and a brief description.

Table 8. Complete feature list for the supervised ML baseline. *Source* indicates whether the feature comes from the NEON Vegetation Structure field survey (Survey), the canopy height model raster (CHM), the LiDAR point cloud (PCD), or is derived from combinations of the above (Derived).

Name	Source	Description
height	Survey	Field-tape tree height H_{field} (m)
stemDiameter	Survey	Diameter at breast height (cm)
crownRadius	Survey	Crown radius (m)
adjElevation	Survey	Adjusted ground elevation reported in the field record (m)
canopyPosition	Survey	Categorical: dominant, codominant, intermediate, suppressed, open
plantStatus	Survey	Categorical: live, dead, broken, etc.
growthForm	Survey	Categorical: single bole tree, multi-bole tree, sapling, etc.
taxonID	Survey	Categorical: NEON species code (e.g. PIPA2, QULA2)
chm_height	CHM	Single-pixel CHM value at the field-survey coordinate (m)
chm_height_buff	CHM	Maximum CHM value within a buffer of radius $0.9 \times$ crownRadius around the stem (m)
Z_pointcloud	PCD	Mean elevation of LiDAR returns classified as ground (LAS class 2) inside the per-tree buffer (m)
std_pointcloud	PCD	Standard deviation of those ground-point elevations (m)
pointdensity_ground_tree	PCD	Ground-point density inside the per-tree buffer (points/m^2)
dtm_nn	PCD	Elevation reported by the nearest defined Digital Terrain Model grid cell (m)
dtm_nn_dist	PCD	Distance from the field-survey coordinate to that nearest DTM cell (m); large values flag unreliable terrain interpolation
dtm_buffer	PCD	Mean DTM elevation inside the per-tree buffer (m)
diff_chm_survey	Derived	chm_height − height (m)
diff_chm_survey_pct	Derived	diff_chm_survey/height (unitless)
abs_diff_chm_survey	Derived	|diff_chm_survey| (m)
diff_chm_buff_survey	Derived	chm_height_buff − height (m)
ground_elevation_diff	Derived	adjElevation − Z_pointcloud (m)
ground_std_to_density	Derived	std_pointcloud/pointdensity_ground_tree
dtm_nn_vs_buffer	Derived	dtm_nn − dtm_buffer (m); large values mean DTM disagrees with local LiDAR
height_to_crown_ratio	Derived	height/crownRadius (canopy slenderness)
height_to_dbh_ratio	Derived	height/stemDiameter

The five interaction features evaluated in the engineered-features ablation (Section D) build on this base

set: `chm_apex_drift = diff_chm_survey − diff_chm_buff_survey` (apex offset from the stem), `ground_noise = std_pointcloud/pointdensity_ground_tree` (local terrain noise), `rel_chm_gap = diff_chm_survey/height` (scale-invariant gap), `shape_x_gap = height_to_crown_ratio ×` |`diff_chm_survey`| (slenderness × gap), and `dtm_dist_x_gap = dtm_nn_dist ×` |`diff_chm_survey`| (DTM unreliability × gap).

D. Tabular ML ablations: full results

This appendix contains the per-configuration ablation numbers summarized in Section 4.3. All numbers are test macro-F1 on the OSBS-train, WREF+SRER-test geographic split unless otherwise noted; per-site columns give WREF and SRER.

Reversed split. Swapping train and test (train WREF+SRER, test OSBS) yields a 7-class macro-F1 of 29.1%. Cross-site difficulty is roughly symmetric in magnitude: the gap is not an artifact of training on the smallest site, even though OSBS is slightly easier as a training set than as a test set.

Within-site evaluation. The cross-site geographic split is the deployment-relevant question, but it conflates two sources of difficulty: small training sets and structural shift between ecosystems. To isolate the structural-shift cost, we hold out a stratified 20% test subset within each of the three sites, train on the union of the within-site train sets, and evaluate on the union of the test sets (one pooled classifier). Macro-F1 averaged over five seeds reaches $45.1\% \pm 7\%$ — a +8.9% lift over the cross-site headline of 36.2%. The result is stable across split fractions $\{10\%, 20\%, 30\%, 40\%\}$ (within $\pm 0.5\%$ of the 20% number).

Site-specific classifiers. Training one LightGBM per site (using the same within-site 80/20 split) and reporting the macro-average of the three per-site test scores reaches only $34.6\% \pm 4.5\%$. Pooling across sites lifts macro-F1 by 10% over per-site fitting, even when test data is held out within-site. The signal is therefore in shared structure across ecosystems rather than in site-specific patterns the per-site classifiers could learn from ~ 65–109 training trees apiece.

Engineered features. Five interaction features target the `bias_2` vs. `bias_4` confusion that dominates the per-class error: `chm_apex_drift` (the difference between the buffered-crown CHM maximum and the at-stem CHM value, flagging trees whose tallest pixel is offset from the survey coordinate), `ground_noise` (the local LiDAR ground-elevation standard deviation divided by ground-point density, flagging noisy DTM regions), `rel_chm_gap` ($\texttt{diff\_chm\_survey}/H_{\text{field}}$, scale-invariant across short and tall trees), `shape_x_gap` (`height_to_crown_ratio` multiplied by the absolute CHM–field gap, coupling canopy slenderness with disagreement magnitude), and `dtm_dist_x_gap` (`dtm_nn_dist` multiplied by the absolute CHM–field gap, up-weighting gaps where the DTM is unreliable). Adding these to the headline feature set raises 7-class macro-F1 from 36.2% to 37.3% and lifts SRER macro-F1 from 14.2% to 16.7%. The lift is small because the features target the `bias_2`/`bias_4` confusion and do not help the `unknown` class.

Class imbalance. The 4-to-46 imbalance across the seven classes invites two strategy families: oversampling and loss reweighting. SMOTE (Chawla et al., 2002) interpolates new minority-class points between real ones; we test it together with its borderline and ADASYN variants. All three drop 7-class macro-F1 (30.4%–34.1%), because the dominant failure is class overlap rather than imbalance: synthetic `bias_5` samples interpolated between two real `bias_5` trees still sit inside the `bias_4` region. Focal-loss-style reweighting (Lin et al., 2017) reweights each sample's contribution to the loss by $(1/p_c)^{1.5}$, where p_c is the class frequency; this also drops macro-F1 (0.345). Inverse- frequency class weighting (already used in the headline) handles imbalance well enough on this data; aggressive minority oversampling does more harm than good.

Cross-site adaptation. Transductive pseudo-labeling (Lee, 2013) adds the model's most confident test predictions back into training and refits. On the 7-class target this slightly degrades macro-F1 (34.9%) but raises SRER macro-F1 (17.1%). A leak-free variant pseudo-labels only the 23 training-set rows tagged `unknown` (using a model fit on the labeled rows only), holding all test data out, and reaches macro-F1 35.1% with WREF macro-F1 43.0%. Both variants help WREF and SRER unevenly without lifting the overall 7-class number, since the headline classifier's confident predictions on `unknown` test rows propagate into the augmented training set as noise.

Model family. CatBoost (35.3%) and HistGradientBoosting (26.3%) underperform LightGBM. A stacking ensemble (LightGBM, RF, and XGBoost feeding a logistic regression meta-learner with out-of-fold predictions) underperforms further

Table 9. Full ablation summary on the seven-class bias taxonomy. All numbers are test macro-F1 on the geographic split (OSBS train, WREF+SRER test) unless noted; per-site columns give WREF and SRER. The headline number is the supervised baseline (top row).

CONFIGURATION	MACRO-F1 ↑	WREF	SRER
7-CLASS BASELINE (HEADLINE)	**36.2%**	40.8%	14.2%
+ ENGINEERED FEATURES	37.3%	40.5%	16.7%
+ H_{pcd} POINT-CLOUD FEATURES	32.4%	33.3%	13.6%
Reversed split (train WREF+SRER, test OSBS only)			
7-CLASS	29.1%	—	—
Within-site split (mean $\pm$ std over 5 seeds, 80/20 test)			
POOLED (ONE CLASSIFIER, ALL THREE SITES)	45.1% $\pm$ 7.0%	47.3%	30.5%
SITE-SPECIFIC (PER-SITE, MACRO-AVG)	34.6% $\pm$ 4.5%	40.0%	32.1%
Class imbalance on the original split			
+ FOCAL-STYLE $(1/p_c)^{1.5}$ REWEIGHTING	34.5%	39.3%	12.0%
+ SMOTE	31.5%	39.3%	8.7%
+ BORDERLINE-SMOTE	30.4%	34.8%	11.0%
+ ADASYN	34.1%	44.1%	7.9%
Cross-site adaptation			
PSEUDO-LABELING ON TEST (TRANSDUCTIVE)	34.9%	37.8%	17.1%
PSEUDO-LABELING ON UNKNOWN POOL	35.1%	43.0%	11.3%
Model family			
CATBOOST	35.3%	39.3%	14.3%
HISTGRADIENTBOOSTING	26.3%	30.3%	11.6%
STACKING (LGBM+RF+XGB→LR)	20.9%	28.2%	11.8%
TABPFN END-TO-END	24.6%	30.2%	13.2%
TABPFN PSEUDO → LIGHTGBM	21.6%	23.5%	13.5%

(20.9%), because the meta-learner overfits small out-of-fold predictions on classes with as few as four training examples.

Tabular foundation model. TabPFN (Hollmann et al., 2025) run end-to-end reaches macro-F1 24.6%, well below LightGBM. Its synthetic-tabular prior does not capture the cross-ecosystem structural shift between OSBS, WREF, and SRER. Using TabPFN to pseudo-label the most confident 30% of test rows and retraining LightGBM on the union (21.6%) does not recover; on the 7-class target the prior's confident wrong predictions on the unknown class propagate as label noise.

Adding raw point-cloud canopy maximum. Extracting the per-tree maximum canopy height (H_{pcd}) and adding it together with seven derived point-cloud statistics (98th and 95th percentile heights, mean and standard deviation of return heights, canopy and ground point counts, and the mean ground elevation) drops 7-class macro-F1 to 32.4%. Two factors explain this: partial redundancy with the ground-quality features the expert labeling process already encodes, plus overfitting from adding eight new features to a 136-row training set. The result reinforces D3's framing: even with the canopy maximum in hand, summary statistics do not resolve the mechanism distinction between bias_2 (H_{field} overestimation), bias_4 (H_{chm} raster underestimation), and bias_5 (H_{chm} and H_{pcd} both underestimate).

Raw-data baseline (PointNet). PointNet (Qi et al., 2017) trained directly on the cropped point clouds underperforms the expert-feature LightGBM on the 7-class target. Every grid configuration peaks within the first 10–50 epochs and then overfits, and larger hidden widths underperform smaller ones. Concatenating PointNet's max-pooled features with the tabular features and feeding them to LightGBM *degrades* the tabular-only baseline. At $n_{\text{train}} \sim 100$, the engineered features encode ecological domain knowledge the network does not recover from labels at this scale.