Inducing Document Representations with Graph-Based Methods: A Blueprint

Abstract

Representing textual documents in continuous numerical spaces is a crucial task in NLP. Early practitioners of NLP built their approach around capturing statistical patterns within documents and utilizing them as features in rich feature spaces. In contrast, contemporary state-of-the-art techniques leverage large neural networks and learn the document representations self-supervised. However, while these approaches excel at learning contextual word representations, they often overlook implicit document-to-document relations that can arise in real-world settings. We propose a blueprint method for constructing document representations that explicitly accounts for implicit document-to-document relations to address this issue.

1 Introduction

In contemporary NLP, researchers usually model documents as sequential collections of words using techniques such as (recurrent) neural networks (Mikolov et al. (2013b;a); Peters et al. (2018)) or attention-based transformer neural networks (Devlin et al. (2018); Liu et al. (2019)) to capture contextual relationships between words. Alternative methods for constructing document representations involve building graphs from co-occurring words and using them to represent the documents (Bunke & Riesen (2011); Sonawane & Kulkarni (2014); Yao et al. (2019); Osman & Barukub (2020)). These graph-based document representations have shown promise in capturing not only the sequential relationships between words but also the global structure of the document, performing on-par with language model approaches (Zhang et al. (2020); Ragesh et al. (2021); Wang et al. (2023)), allowing for more effective and interpretable representations that can be useful in various downstream NLP tasks (like document similarity (Paul et al. (2016)), topic modeling (Xie et al. (2021)) and document understanding (Gemelli et al. (2023))). Huang et al. (2022) presented a method that enhances the language model's representation by incorporating information from a sub-word co-occurrence graph, by utilizing shared loss funciton. For tasks that involve analyzing documents within a network structure, such as identifying fake news (Han et al. (2020)) or recommending items based on textual reviews Fan et al. (2019), Graph Neural Networks (GNNs) have proven to be highly effective (Wu et al. (2023)). However, real-world documents often lack explicit connections between them, making it difficult to apply GNNs. To address this, we present a framework for constructing a doocument-to-document network and demonstrate how various GNNs can be applied to this structure.

2 Graphs of documents and where to find them?

Let $G = (V, E)$ be a graph, where V is the set of nodes (in our case, the set of documents) and E is the set of edges. In our case the set of edges E is not given and the goal is to construct it with the exmaination of the potential of documents to form links. The first step of our method is to transform the documents from raw texts to d-dimensional continuous vector space $L \in \mathbb{R}^d$. Next, we calculate the the edge weight as follows:

$$e_{i,j} = sim(L(v_i), L(v_j)) \text{ where } L \text{ denotes the latent document embedding}$$

Here, v_i and v_j denote two documents, and $L(v_i)$ and $L(v_j)$ represent the latent embeddings of these documents. The function sim measures the similarity between these embeddings, and the resulting value $e_{i,j} \in \{0, 1\}$ represents the weight of the edge between documents v_i and v_j. After this step

we obtain initial adjacency matrix which we later threshold and obtain edges that are $\geq$ than some threshold $thresh \in \{0, 1\}$.

Algorithm 1 doocument-to-document network construction algorithm

---

Require: Documents, SimilarityFunction, LatentEmbedding, Threshold, kNeighbours
   documentNetwork $\leftarrow$ Empty
   documentEmbeddings $\leftarrow$ LatentEmbedding(Documents)
   searchTree $\leftarrow$ KDTree(documentEmbeddings)
   for document $\in$ TargetDocuments **do**
      TargetDocuments $\leftarrow$ KDTree(document, kNeighbours)
      for targetDocument $\in$ TargetDocuments **do**
         edgeWeight $\leftarrow$ SimilarityFunction(document, targetDocument)
         if edgeWeight $\geq$ Threshold **then**
            network.makeEdge(document, targetDocument)
         end if
      end for
   end for
   return documentNetwork

We examine two different scenarios for obtaining representation of a new document: a transductive and inductive. The approach is visualized in Figure 1.

2.1 EVERYTHING AND ALL AT ONCE

In the first scenario, we construct a graph between all the documents in the corpus. We consider building the graph between documents by first computing their latent embeddings and later calculating their similarities. Since computing the adjacency matrix A can be computationally expensive, we hypothesize that a given document will have strong connections only with a small subset of the total number of documents. To address this, we relax the constraints and compute the closest k documents for each document in D. To accomplish this task efficiently, we normalize the documents and construct a KDTree[1] of distances. By doing so, the closest k documents are the most similar ones in terms of cosine distance. We apply several GNN models to the constructed graph to learn to classify the nodes. Translating the problem from document classification to node classification on the proposed graph. Specifically, we experiment with GCN (Kipf & Welling (2016)) and GAT (Veličković et al. (2017)) networks and node embedding via NetMF (Qiu et al. (2018)) method.

2.2 THE WHOLE IS THE SAME AS THE SUM OF ITS PARTS

In the second scenario, we attempt to induce representations for new, previously unseen documents using the existing graph structure. We follow the steps described in the previous Subsection and construct a doocument-to-document network only from the training set of documents. We begin by constructing the graph using the approach from the first scenario, using labeled data. Next, we use the NetMF embedding to obtain node (document) representations. To induce a representation for a new document, we first query the KDTree to retrieve the k closest neighbors of the document. We then obtain the corresponding node embeddings of the retrieved neighbors, which we next average and induce the new document embedding.

---

[1] https://scikit-learn.org/stable/modules/generated/sklearn.neighbors.KDTree.html

Figure 1: The proposed methodology aims to create a network of related documents robustly.

3 EXPERIMENTAL SETUP AND EVALUATION

To evaluate our method we choose 6 different text classificaiton datasets of whom 2 are binary and 4 are multilabel. We benchmark our proposed method against two state-of-the-art language models, namely LinkBERT (Yasunaga et al. (2022)) and RoBERTa (Liu et al. (2019)), both fine-tuned for 10 *epochs* with default parameters. We initialize our document-to-document framework with LatentEmbedding = MPNet sentence-transformers embedding (Reimers & Gurevych (2019)). We explore a grid of hyper-parameters for our method with threshold values ranging from 0.1 to 0.9, and k-Nearest Neighbors values ranging from 5 to 100. We conduct experiments with 10 different random seeds and report the average results. For the transductive models, we use the Spektral [2] implementation of GCN and GAT with default parameters. For NetMF, we use the implementation by Škrlj et al. (2020) and train a LogisticRegression[3] classifier with C=1. In all evaluation scenarios we use the models that performed the best on the dev set with respect to the F1-Macro score[4] to be evaluated on the test set used for comparison. Table 1 presents a summary of the evaluation problems and their corresponding performance metrics.

Table 1: Dataset information and averaged test data evaluation on the 10 runs.

	Dataset description				Language Models		Transductive D2D		Inductive D2D
Dataset	Train Size	Dev Size	Test Size	Classes	LinkBERT	RoBERTa	GAT	GCN	NetMF
BBC (Greene & Cunningham (2006))	790	264	352	4	**0.9863**	0.9815	0.6404	0.7937	0.9460
MBTI (Myers (1962))	4879	1627	2169	16	**0.5695**	0.3468	0.5072	0.1341	0.2116
AAAI-FN (Patwa et al. (2021))	6420	2140	2140	2	0.9802	**0.9819**	0.8229	0.7380	0.9120
PAN-Age (Rangel et al. (2016))	225	76	101	5	0.3881	0.4356	**0.7335**	0.3445	0.4554
PAN-Gender (Rangel et al. (2017))	2024	675	900	4	**0.7523**	0.7444	0.6823	0.5669	0.6078
PAN-FakeNews (Rangel et al. (2020))	270	30	200	2	0.6475	**0.6725**	0.6697	0.5629	0.6450

4 CONCLUSION AND FURTHER WORK

In this study we proposed a framework for creating document-to-document networks that can generate document representations using both transductive and inductive approaches. Our method performs comparably with some of the state-of-the-art techniques, especially in scenarios where there are numerous classes and small number of samples. Nevertheless, the performance of our falls in comparison to the pre-trained models when more data is available. To further improve our method, we propose applying more focus on deriving better document-to-document network by improving the thresholding step, adding more layers to the network (either via different embedding methods or via metadata when available).

5 AVAILABILITY

Will be added after review.

---

[2] https://github.com/danielegrattarola/spektral
[3] https://scikit-learn.org/stable/modules/generated/sklearn.linear_model.LogisticRegression.html
[4] https://scikit-learn.org/stable/modules/generated/sklearn.metrics.f1_score.html

ACKNOWLEDGMENTS

Will be added after review.

REFERENCES

Horst Bunke and Kaspar Riesen. Recent advances in graph-based pattern recognition with applications in document analysis. *Pattern Recognition*, 44(5):1057–1067, 2011.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Wenqi Fan, Yao Ma, Qing Li, Yuan He, Eric Zhao, Jiliang Tang, and Dawei Yin. Graph neural networks for social recommendation. In *The World Wide Web Conference*, WWW '19, pp. 417–426, New York, NY, USA, 2019. Association for Computing Machinery. ISBN 9781450366748. doi: 10.1145/3308558.3313488. URL https://doi.org/10.1145/3308558.3313488.

Andrea Gemelli, Sanket Biswas, Enrico Civitelli, Josep Lladós, and Simone Marinai. Doc2graph: A task agnostic document understanding framework based on graph neural networks. In *Computer Vision–ECCV 2022 Workshops: Tel Aviv, Israel, October 23–27, 2022, Proceedings, Part IV*, pp. 329–344. Springer, 2023.

Derek Greene and Pádraig Cunningham. Practical solutions to the problem of diagonal dominance in kernel document clustering. In *Proceedings of the 23rd international conference on Machine learning*, pp. 377–384, 2006.

Yi Han, Shanika Karunasekera, and Christopher Leckie. Graph neural networks with continual learning for fake news detection from social media. *arXiv preprint arXiv:2007.03316*, 2020.

Yen-Hao Huang, Yi-Hsin Chen, and Yi-Shin Chen. ConTextING: Granting document-wise contextual embeddings to graph neural networks for inductive text classification. In *Proceedings of the 29th International Conference on Computational Linguistics*, pp. 1163–1168, Gyeongju, Republic of Korea, October 2022. International Committee on Computational Linguistics. URL https://aclanthology.org/2022.coling-1.100.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013a.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. *Advances in neural information processing systems*, 26, 2013b.

Isabel Briggs Myers. The myers-briggs type indicator: Manual (1962). 1962.

Ahmed Hamza Osman and Omar Mohammed Barukub. Graph-based text representation and matching: A review of the state of the art and future challenges. *IEEE Access*, 8:87562–87583, 2020.

Parth Patwa, Shivam Sharma, Srinivas Pykl, Vineeth Guptha, Gitanjali Kumari, Md Shad Akhtar, Asif Ekbal, Amitava Das, and Tanmoy Chakraborty. Fighting an infodemic: Covid-19 fake news dataset. In Tanmoy Chakraborty, Kai Shu, H. Russell Bernard, Huan Liu, and Md Shad Akhtar (eds.), *Combating Online Hostile Posts in Regional Languages during Emergency Situation*, pp. 21–29, Cham, 2021. Springer International Publishing. ISBN 978-3-030-73696-5.

Christian Paul, Achim Rettinger, Aditya Mogadala, Craig A Knoblock, and Pedro Szekely. Efficient graph-based document similarity. In *The Semantic Web. Latest Advances and New Domains: 13th International Conference, ESWC 2016, Heraklion, Crete, Greece, May 29–June 2, 2016, Proceedings 13*, pp. 334–349. Springer International Publishing, 2016.

Matthew E. Peters, Mark Neumann, Mohit Iyyer, Matt Gardner, Christopher Clark, Kenton Lee, and Luke Zettlemoyer. Deep contextualized word representations. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 2227–2237, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1202. URL `https://aclanthology.org/N18-1202`.

Jiezhong Qiu, Yuxiao Dong, Hao Ma, Jian Li, Kuansan Wang, and Jie Tang. Network embedding as matrix factorization: Unifying deepwalk, line, pte, and node2vec. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining*, WSDM '18, pp. 459–467, New York, NY, USA, 2018. Association for Computing Machinery. ISBN 9781450355810. doi: 10.1145/3159652.3159706. URL `https://doi.org/10.1145/3159652.3159706`.

Rahul Ragesh, Sundararajan Sellamanickam, Arun Iyer, Ramakrishna Bairi, and Vijay Lingam. Hetegcn: heterogeneous graph convolutional networks for text classification. In *Proceedings of the 14th ACM international conference on web search and data mining*, pp. 860–868, 2021.

Francisco Rangel, Paolo Rosso, Ben Verhoeven, Walter Daelemans, Martin Potthast, and Benno Stein. Overview of the 4th author profiling task at pan 2016: cross-genre evaluations. In *Working Notes Papers of the CLEF 2016 Evaluation Labs. CEUR Workshop Proceedings/Balog, Krisztian [edit.]; et al.*, pp. 750–784, 2016.

Francisco Rangel, Paolo Rosso, Martin Potthast, and Benno Stein. Overview of the 5th author profiling task at pan 2017: Gender and language variety identification in twitter. *Working notes papers of the CLEF*, 48, 2017.

Francisco Rangel, Anastasia Giachanou, Bilal Hisham Hasan Ghanem, and Paolo Rosso. Overview of the 8th author profiling task at pan 2020: Profiling fake news spreaders on twitter. In *CEUR workshop proceedings*, volume 2696, pp. 1–18. Sun SITE Central Europe, 2020.

Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*, 2019.

Blaž Škrlj, Jan Kralj, and Nada Lavrač. Embedding-based silhouette community detection. *Machine Learning*, 109:2161–2193, 2020.

Sheetal S Sonawane and Parag A Kulkarni. Graph based representation and analysis of text document: A survey of techniques. *International Journal of Computer Applications*, 96(19), 2014.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Yizhao Wang, Chenxi Wang, Jieyu Zhan, Wenjun Ma, and Yuncheng Jiang. Text fcg: Fusing contextual information via graph learning for text classification. *Expert Systems with Applications*, pp. 119658, 2023.

Lingfei Wu, Yu Chen, Kai Shen, Xiaojie Guo, Hanning Gao, Shucheng Li, Jian Pei, Bo Long, et al. Graph neural networks for natural language processing: A survey. *Foundations and Trends® in Machine Learning*, 16(2):119–328, 2023.

Qianqian Xie, Jimin Huang, Pan Du, Min Peng, and Jian-Yun Nie. Graph topic neural network for document representation. In *Proceedings of the Web Conference 2021*, pp. 3055–3065, 2021.

Liang Yao, Chengsheng Mao, and Yuan Luo. Graph convolutional networks for text classification. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 7370–7377, 2019.

Michihiro Yasunaga, Jure Leskovec, and Percy Liang. Linkbert: Pretraining language models with document links. In *Association for Computational Linguistics (ACL)*, 2022.

Yufeng Zhang, Xueli Yu, Zeyu Cui, Shu Wu, Zhongzhen Wen, and Liang Wang. Every document owns its structure: Inductive text classification via graph neural networks. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 334–339, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.31. URL `https://aclanthology.org/2020.acl-main.31`.