# Rectified Flows for Fast Multiscale Fluid Flow Modeling

## Abstract

Statistical surrogate modeling of fluid flows is challenging due to multiscale dynamics and strong sensitivity to initial conditions. Conditional diffusion models can achieve high fidelity, but typically require hundreds of stochastic steps at inference. We introduce a rectified-flow surrogate that learns a time-dependent conditional velocity field transporting input-to-output laws along nearly straight trajectories. Sampling reduces to solving a deterministic ODE along this learned transport, so each function evaluation is substantially more effective: on multi-scale 2D benchmarks we match diffusion-class posterior statistics with as few as 8 ODE steps versus $\geq 128$ steps for score-based diffusion.

On the theory side, we develop a law-level analysis tailored to conditional PDE forecasts. First, we formalize the link between our evaluation criterion—one-point Wasserstein distances on fields—and the $k = 1$ correlation-marginal viewpoint in statistical solutions. Second, we provide a one-step error decomposition for the learned pushforward law into a *coverage* (high-frequency tail) term controlled by structure functions (equivalently, by spectral decay), and a *fit* term controlled directly by the training objective. Third, we show how *straightness* in rectification time governs local truncation error for ODE sampling, yielding step-count requirements and explaining why rectified transports admit large, stable steps.

Guided by this picture, we propose a curvature-aware sampler that tracks an EMA-based straightness proxy and adaptively blends and steps the velocity during inference. Across multiscale incompressible and compressible 2D flows, our method matches diffusion models in Wasserstein statistics and energy spectra, preserves fine-scale structure missed by MSE baselines, and delivers high-resolution conditional samples at a fraction of the inference cost.

## Abstract

Statistical surrogate modeling of fluid flows is challenging because multi-scale nonlinear dynamics can amplify small perturbations into large output uncertainty. Conditional diffusion models can capture such output laws with high fidelity, but at inference time they typically require hundreds of stochastic denoising steps. We introduce *ReFlow*, a conditional rectified-flow surrogate for PDE forecasting that instead learns a deterministic transport ODE from a simple reference law to the conditional law of final states, *conditioned on the initial data*. Concretely, for a given initial condition $u_i$, the model starts from Gaussian noise $\xi$ and learns a time-dependent velocity field that transports $\xi$ to a sample from the target conditional law $p(u_f \mid u_i)$. Because the learned transport is substantially straighter than score-based diffusion trajectories, each function evaluation is more effective: on multi-scale 2D benchmarks, ReFlow matches diffusion-class posterior statistics with as few as 8 ODE steps, whereas score-based diffusion requires $\geq 128$ network evaluations.

On the theory side, we develop a law-level analysis tailored to conditional PDE surrogates. First, we formulate rectified flow in the conditional setting and show that the ideal barycentric rectified velocity transports the reference law to the target conditional law at the level of measures. Second, at fixed spatial resolution, we derive a one-step law-level error decomposition into a *coverage* term, determined by unresolved high-frequency content and controlled by structure functions (equivalently, spectral tails), and a *fit* term, determined by

how well the learned velocity matches the ideal conditional transport field. Third, we show that *straightness* of the learned transport in rectification time governs ODE discretization error through the variation of the velocity along sampled trajectories, thereby explaining why rectified transports admit large, stable steps. Guided by this picture, we introduce a curvature-aware sampler that monitors an EMA-based proxy for trajectory-wise velocity variation and adaptively blends and steps the velocity during inference, which is particularly helpful in out-of-distribution regimes where these oscillations become pronounced.

Across multiscale incompressible and compressible 2D flows, ReFlow matches diffusion baselines in one-point Wasserstein statistics and energy spectra, preserves fine-scale structure missed by deterministic MSE surrogates, and delivers high-resolution conditional samples at a fraction of the inference cost.

# 1 Introduction

Partial differential equations (PDEs) Evans (2010) are the backbone of modeling physical phenomena, from atmospheric dynamics to aerodynamics and magnetohydrodynamics. Currently, solutions of PDEs are simulated with high-fidelity numerical solvers such as finite difference, finite element, and spectral methods Quarteroni & Valli (1994). These are often prohibitively expensive for *many–query* tasks Quarteroni et al. (2015) such as uncertainty quantification, optimization, and real-time prediction. In particular, these solvers encounter a significant challenge for classes of non-linear PDEs, whose solutions exhibit extreme sensitivity to initial and boundary data, leading to chaotic behavior and complex multi-scale features. In such settings, one seeks, not a deterministic trajectory, but rather the *statistical solution* of the PDE, i.e., the push-forward of the underlying probability measure on inputs (initial and boundary conditions etc) by the PDE solution operator Fjordholm et al. (2017). Currently, these statistical solutions are sampled with ensemble Monte Carlo method by repeatedly calling high-fidelity PDE solvers Lanthaler et al. (2021a). Given the computational cost of the PDE solver, ensemble methods become infeasible as ensemble sizes grow.

Machine learning and AI based algorithms are increasingly being explored for the data-driven simulation of PDEs Mishra & Townsend (2024). In particular, *neural operators* Kovachki et al. (2023), which directly seek to learn the PDE solution operator from data, are already widely used in a PDE context Mishra & Townsend (2024). Examples of neural operators have been proposed in Li et al. (2020a;b); Lu et al. (2021); Wu et al. (2024); Hao et al. (2023); Li et al. (2023); Alkin et al. (2024) and references therein.

However, these neural operators have been found to be unsuitable for simulating PDE with chaotic, multiscale solutions such as governing equations of fluid dynamics. For instance, recently in Molinaro et al. (2024), it was shown both theoretically and empirically that neural operators, trained to minimize mean absolute (square) errors, will always collapse to the ensemble mean when used for simulating statistics of PDEs with chaotic multiscale solutions.

Given this context, generative AI models—especially score-based and diffusion models—have recently shown remarkable success at learning complex, high-dimensional distributions by progressive denoising score matching Song et al. (2020). In the context of chaotic PDEs, *GenCFD* Molinaro et al. (2024) introduced a conditional diffusion framework that preserves spectral content across fine scales, mitigating the "spectral collapse" of naive MSE-trained surrogates, see also Oommen et al. (2024); Gao et al. (2024a;b;c). However, sampling a score-based diffusion model requires simulating a reverse-time stochastic differential equation (SDE) over 100+ discretization steps, each invoking a large ML model on a moderate-to-high resolution spatial grid, resulting in high runtimes that undermine real-time or resource-constrained applications.

To overcome this limitation of diffusion models, we adapt *rectified flows* Liu et al. (2022): a deterministic ODE-based analogue of diffusion that "straightens" transport paths in probability space. Rather than small random increments, rectified flows solve an ODE whose velocity field is trained to match the diffusion model's instantaneous score, but whose trajectories remain nearly linear. This structure permits large time integration, reducing the number of solver steps by an order of magnitude or more, while provably recovering the same target distribution. To overcome the inference cost of diffusion-based surrogates, we instead use a

*conditional rectified flow* Liu et al. (2022). The key point is to separate the *conditioning variable* from the *transported variable*. In our PDE setting, the initial condition $u_i$ is *not* transported by the rectified flow; rather, it is provided as conditioning information throughout the model. The transported variable is a latent sample initialized from a simple reference law, typically Gaussian noise. Thus, for each fixed initial datum $u_i$, the goal is to learn a time-dependent velocity field whose flow maps a reference sample $\xi \sim \mathcal{N}(0, I)$ to a sample from the conditional output law $p(u_f \mid u_i)$, where $u_f$ denotes the PDE state at the target physical time.

**What is evaluated, and why.** Because statistical solutions are measures on function spaces, the most robust comparison is via *observables* or *correlation marginals* Lanthaler et al. (2021b). Our evaluation metric in Section 8.2—the *one-point Wasserstein distance*—is exactly the Wasserstein discrepancy between $k = 1$ correlation marginals (pointwise push-forwards), averaged over space. This aligns the experimental metrics (Table 1) with the law-level theoretical statements in Sections 5.1–5.5. This viewpoint is especially natural for chaotic or strongly multiscale PDEs. When the same macroscopic initial datum is subjected to small unresolved perturbations, the corresponding final state is no longer well represented by a single deterministic predictor; instead, one seeks a conditional *law* over possible outcomes. Conditional diffusion models such as GenCFD already target this law successfully, but do so through a reverse-time stochastic process that typically requires many score-network evaluations. Rectified flow replaces this stochastic sampling procedure by a deterministic ODE in an internal *rectification time* $\tau \in [0, 1]$, chosen so that the learned transport from noise to data is as straight as the conditional law permits. In practice this substantially reduces the number of function evaluations needed to reach the target conditional distribution.

A central theme of this paper is that *straightness in rectification time* matters for computational reasons. If the learned velocity varies little along its own trajectories, then explicit ODE solvers incur small truncation error and can take large steps. Conversely, when the learned velocity oscillates strongly along the sampled path—a phenomenon we observed most clearly in out-of-distribution conditional regimes—few-step sampling becomes fragile. This observation motivated our curvature-aware sampler: an EMA-based controller that tracks short-horizon velocity oscillations along the trajectory and uses them to blend and adapt the step size during inference.

**Statistical evaluation criteria.** Because statistical solutions are probability measures on function spaces, the most robust comparisons are formulated through observables and their induced correlation marginals Lanthaler et al. (2021b). Our main metric in Section 8.2, the *one-point Wasserstein distance*, is exactly the Wasserstein discrepancy between the $k = 1$ correlation marginals (that is, the pointwise pushforwards of the laws), averaged over space. Thus the experimental metrics in Table 1 are directly aligned with the law-level viewpoint used in the theory sections below.

Hence, our main contributions are:

- *Rectified flows for conditional PDEs.* We learn a time-dependent velocity field that transports a *conditional law* of fields from a simple reference (Gaussian noise conditioned on the input) to the target PDE pushforward law. The key theoretical point is *correctness at the level of laws*: the *barycentric rectified velocity* induces an ODE whose flow maps the initial law to the target law (**SM** F).

- *Curvature-aware integration.* The sampling cost is governed by the amount of *time-bending* (straightness/curvature in rectification time) of the learned vector field along typical trajectories. We formalize: (i) which curvature quantity controls discretization error, (ii) why a simple EMA deviation is a principled proxy for that curvature, and (iii) why the blending step is the minimizer of a quadratic (Tikhonov) correction (**SM** J).

- *Multi-scale accuracy at speed.* At fixed grid resolution there is an *irreducible* law-level error floor coming from unresolved Fourier scales. We express this as a *coverage* term controlled by structure functions / spectral tails (Crefapp:sec:coverage-structure). Rectified flows reduce curvature so that the best attainable (bandlimited) law is reached with far fewer sampling steps. This is precisely what is seen in Table 1 and in the spectral evolution plots (Figure 22).

## 2   Approach

- *Conditional rectified flows for PDE surrogates.* We formulate rectified flow directly at the level of conditional PDE laws: for each fixed input field $u_i$, the model transports a simple reference law on latent fields to the target conditional law of final states. The key theoretical statement is *correctness at the level of laws*: the ideal conditional barycentric rectified velocity induces an ODE whose flow pushes the reference law to the target conditional law.

- *A law-level decomposition into coverage, fit, and discretization.* At fixed spatial resolution, there is an irreducible approximation floor coming from unresolved Fourier scales. We express this as a *coverage* term controlled by structure functions, equivalently by spectral tails. The remaining continuous-time modeling error is a *fit* term measuring how well the learned velocity approximates the ideal conditional transport field. Separately, we show that discretization error is governed by the variation of the learned velocity *along sampled trajectories* in rectification time.

- *Curvature-aware sampling for OOD-sensitive conditional generation.* Recent work on diffusion-based OOD and anomaly detection has shown that trajectory geometry, score variation, and curvature carry useful information about whether a sample remains in-distribution or moves into poorly calibrated regions of the learned generative dynamics Heng et al. (2024); Abdi et al. (2025a;b); Barkley et al. (2025). Motivated by this perspective, we treat trajectory-wise velocity variation in rectification time as an online signal that the conditional sampler is entering an unstable or OOD regime. We therefore introduce an EMA-based controller that monitors this straightness/curvature proxy and uses it to adaptively blend the velocity and choose the step size during inference on OOD data. Unlike prior works, which use such trajectory information primarily for detection or scoring, we use it *operationally* to stabilize and improve sampling itself.

- *Multi-scale accuracy at substantially lower inference cost.* Across incompressible and compressible 2D benchmarks, ReFlow matches diffusion models in one-point Wasserstein statistics and energy spectra, preserves fine-scale structure missed by deterministic MSE baselines, and achieves these results with dramatically fewer sampling steps. The gain is especially pronounced in the OOD macro–micro regime, where the curvature-aware controller improves the NFE–error tradeoff by reacting to the same trajectory-geometry signals that recent diffusion OOD work has identified as informative under distribution shift Heng et al. (2024); Abdi et al. (2025a); Barkley et al. (2025).

## 3   Approach

**Modeling multi-scale flows and their statistical solutions.** We focus on time-dependent PDEs of the general form

$$\partial_t u(x,t) \, + \, \mathcal{L}\big(u, \nabla_x u, \nabla_x^2 u, \dots\big) \, = \, 0, \quad x \in D \subset \mathbb{R}^d, \ t \in (0, T), \tag{1}$$

subject to boundary conditions $\mathcal{B}(u) = u_b$ on $\partial D \times (0, T)$ and initial data $u(x, 0) = \bar{u}(x)$. Here, the solution $u : D \mapsto \mathbb{R}^m$ is evolved in time, with respect to the differential operator $\mathcal{L}$. Concrete examples of (1) are the incompressible Navier-Stokes and compressible Euler equations.

A recurring theme in non-linear, multi-scale fluid flows is *extreme sensitivity* to initial or boundary data, which can lead to chaotic or near-chaotic behavior. Rather than fix a single $u_0$, one may consider an *initial measure* $\mu_0$ to represent uncertain or variable initial states, and then study the *statistical solution* $\mu_t = \mathcal{S}_\#^t \mu_0$ pushed forward by the PDE solution operator $\mathcal{S}^t$. In strongly nonlinear regimes, $\mu_t$ spreads significantly in function space, creating complex, multi-scale distributions of possible flow fields. Accurately approximating this evolving distribution is essential for uncertainty quantification and design under rough conditions, but doing so with high-fidelity PDE solvers can be prohibitively expensive when large ensembles are required.

**High cost of computing statistical solutions.** In practice, characterizing $\mu_t$ directly often requires performing *many* forward simulations of the PDE solver, each initialized with a slightly perturbed $u_0$. As

each simulation might require high-resolution discretizations (e.g. millions of degrees of freedom) and multiple time steps, the overall cost for constructing a sizable ensemble rapidly becomes prohibitive. Even with modern high-performance computing platforms, running hundreds or thousands of high-fidelity statistical simulations can be infeasible. Hence, there is a pressing need for more efficient *surrogate models* that can *sample* physically realistic final states without enumerating every realization of the forward PDE solve. Succinctly put, we aim to provide a solution to the following problem

*How can we efficiently capture statistical quantities of interest for the pushforward measure $S^t_\# \mu_0$ for highly sensitive solution operators $S^t$?*

**Observables and correlation marginals (what metrics actually probe).** A classical way to formalize "quantities of interest" for $\mu_t$ is via observables and their induced correlation marginals Lanthaler et al. (2021b). For $k = 1$, the pointwise evaluation map at $x \in D$,

$$\mathrm{ev}_x : \ u \mapsto u(x) \in \mathbb{R}^m,$$

pushes $\mu_t$ to the *one-point marginal* $(\mathrm{ev}_x)_\# \mu_t$ on $\mathbb{R}^m$ – strictly speaking, one studies the pushforwards measures $\mathrm{ev}_x \circ i_\epsilon$, here $(i_\epsilon u) := (\phi_\epsilon * u)$ where $\phi_\epsilon$ is a compactly supported mollifier, so that point-wise evaluation is well-defined; for the sake of brevity, we will not make this distinction explicit in the sequel. Our one-point Wasserstein metric (Section 8.2) is the spatial average of $W_1\big((\mathrm{ev}_x)_\# \mu_t, (\mathrm{ev}_x)_\# \widehat{\mu}_t\big)$. By Kantorovich–Rubinstein duality, controlling this quantity controls the discrepancy of *all* pointwise 1-Lipschitz observables, averaged over space. This is the bridge between Table 1 and the law-level bounds in Section 5.1 and Section 5.5.

**Rectified flows for faster sampling.** To mitigate these inefficiencies, we adopt the framework of *rectified flows* Liu et al. (2022): a deterministic alternative to conditional diffusion designed to reduce the number of required integration steps. In essence, rather than generating samples via small random "diffusion-reversal" increments, rectified flows construct an *ordinary differential equation* (ODE) with *nearly straight* trajectories in function space. This straighter transport map can be integrated more aggressively in time, enabling sampling with far fewer solver steps. Importantly, rectified flows retain the desirable property of matching the same final distributions that standard diffusion models learn, but at a fraction of the runtime cost.

## 4 Related Work

### 4.1 Diffusion Models in Fluid Dynamics

**Conditional diffusion surrogates.** *GenCFD* Molinaro et al. (2024) trains a conditional score-based diffusion model that starts from an initial or low-resolution flow field and iteratively refines it through hundreds of denoising steps, thereby capturing multi-scale turbulent structure. Similarly, the method of Oommen et al. (2024) conditions a diffusion model on a coarse fluid solution (generated by a learned operator) and "super-resolves" the fine-scale flow. Given these similarities, we refer to such diffusion-based solvers collectively as *conditional diffusion PDE solvers*.

**Rectified flow alternative.** Each sample typically needs hundreds of network calls, limiting large-scale or real-time use. Our method replaces the stochastic SDE with a deterministic ODE whose nearly straight trajectories require far fewer steps, achieving similar statistical fidelity at much lower inference cost (see Sections 7.12 and 8). Crucially, we find that rectified flows are actually more efficient from the standpoint of training-time required to reach the same accuracy level with the conditional diffusion approaches; this is also confirmed by earlier work Esser et al. (2024) exploring the scalability of rectified flows with transformer-based backbones.

## 5 Rectified Flows: An ODE-Based Alternative

### 5.1 Mathematical Formulation

Figure 1: **Overview of ReFlow.** (**a**): ReFlow closely matches high-order statistical moments (in the Wasserstein $W_1$-sense) of fluid flows by learning a neural surrogate to approximate the push-forward of the distribution $p(u_{\tau|\tau=0}|u_i)$, while minimizing inference-time computational costs. (**b**) Macro-architecture overview: A UViT based network predicts the velocity field $v_\theta$, conditioned on Gaussian noise, initial data $u_i$ and boundary conditions, and diffusion time $\tau$. Noise and initial / boundary conditions are concatenated as inputs. (**c**): Results for the cylindrical shear flow dataset. (**d**): The KDE plots monitor the evolution of a down-projected version of the push-forward measure $p_\tau := X_\theta(\tau)_{\#} p(u_{\tau=0}|u_i)$, where $X_\theta$ is the flow induced by the learned vector field $v_\theta$. Results for the Richtmyer Meshkov dataset showing flow matching between noise ($p_{\tau=0}$) and target ($p_{\tau=1}$) distributions. ReFlow solves an ODE, learning a constant velocity field that enables straight-line inference paths (visualized with principal component analysis and kernel density estimation at different diffusion times).

**Overview.** Rectified flows provide a *deterministic* way to transform one probability distribution into another, offering an alternative to stochastic diffusion-based methods. Instead of traversing curved, noise-driven paths, rectified flows attempt to transport mass along nearly "straight" trajectories in state space, which can dramatically reduce sampling costs.

**Overview.** Rectified flows provide a *deterministic* mechanism for sampling from a target probability law by integrating an ordinary differential equation in an internal *rectification time* $\tau \in [0, 1]$. In our PDE setting, the target is *conditional*: given an initial condition (and, when relevant, boundary data) $u_i$, we wish to sample from the conditional law of the final state $u_f$ at the forecast time. The key point is that the conditioning datum $u_i$ is *not* itself transported by the rectified flow. Rather, it is provided to the model as side information throughout the trajectory. The transported variable starts from a simple reference law, typically Gaussian noise, and is evolved to a sample from the target conditional law.

Throughout, our random variables are *state fields* $u : \mathcal{D} \to \mathbb{R}^m$ (e.g. $m = 2$ for velocity, or $m = 4$ for compressible state variables) living in a separable space $\mathcal{U} = L^2(\mathcal{D}; \mathbb{R}^m)$ (or $H^s$, $s > \frac{d}{2}$). All theory below extends verbatim from $\mathbb{R}^d$ because $\mathcal{U}$ is Polish; in practice we work with a Galerkin discretisation $\mathbb{R}^{d_N} \subset \mathcal{U}$, so every integral is evaluated by Monte-Carlo on its finite grid surrogate. Throughout, the random state

fields take values in a separable Hilbert space

$$\mathcal{U} = L^2(\mathcal{D}; \mathbb{R}^m),$$

or, when convenient, in a smoother space such as $H^s(\mathcal{D}; \mathbb{R}^m)$ with $s > d/2$. In computations, all objects are represented on a finite-dimensional Galerkin or grid discretization $\mathbb{R}^{d_N} \subset \mathcal{U}$, so the theory below is to be understood either in that finite-dimensional setting or as its natural infinite-dimensional analogue.

In all that follows, the *diffusion time* $\tau \in [0, 1]$ is a purely *scale-ordering* variable: $\tau = 0$ denotes the coarsest, lowest–frequency representation of a state field, while $\tau = 1$ restores full spatial resolution; it is *not* the physical PDE time but merely an index that governs the progressive refinement of scales along the rectified flow.

**Conditional target law and reference law.** Let $C$ denote the conditioning variable, which in our applications is the initial condition $u_i$ (possibly augmented with boundary data or other known inputs). For each fixed realization $c$ of $C$, let

$$\mu_1^c := \mathrm{Law}(U_f \mid C = c)$$

be the conditional law of the final PDE state, and let

$$\pi_0^c$$

be a simple reference law on $\mathcal{U}$ from which sampling is easy. In practice we take $\pi_0^c = \mathcal{N}(0, I)$, independent of $c$, but allowing a $c$-dependence is conceptually harmless and can be useful in variants with condition-dependent priors.

**Coupling $\gamma$ as a statistical transport blueprint.** Let $\mu_0, \mu_1 \in \mathcal{P}(\mathcal{U})$ be the initial and target field laws. Fix *any* coupling $\gamma \in \mathcal{P}(\mathcal{U} \times \mathcal{U})$ with $(\pi_0)_\# \gamma = \mu_0$ and $(\pi_1)_\# \gamma = \mu_1$ (in practice: the empirical pairing of input/output fields in the dataset). Think of $(U_0, U_1) \sim \gamma$ as drawing a *random chord* in state space, from $U_0$ to $U_1$. Thus, for each fixed condition $c$, the goal of rectified flow is to construct a time-dependent velocity field

$$v_\theta(\,\cdot\,, \tau; c) : \mathcal{U} \to \mathcal{U}$$

such that the ODE flow

$$\frac{d}{d\tau} u_\tau = v_\theta(u_\tau, \tau; c), \qquad u_{\tau=0} \sim \pi_0^c, \tag{2}$$

pushes $\pi_0^c$ forward to a law close to $\mu_1^c$ at $\tau = 1$.

For $\tau \in [0, 1]$ define the linear chord point

$$U_\tau := (1 - \tau) U_0 + \tau U_1, \quad \rho_\tau := \mathrm{Law}(U_\tau) = (T_\tau)_\# \gamma, \quad T_\tau(u_0, u_1) = (1 - \tau) u_0 + \tau u_1.$$

Thus $\rho_\tau$ is the population of intermediate states obtained by moving along dataset chords by a fraction $\tau$.

**Conditional coupling and rectified interpolation.** Fix a condition $c$. Let

$$\gamma^c \in \mathcal{P}(\mathcal{U} \times \mathcal{U})$$

be any coupling between the reference law $\pi_0^c$ and the target law $\mu_1^c$. We write

$$(\Xi, U_f) \sim \gamma^c,$$

where $\Xi$ is the reference sample and $U_f$ is the target final state. The most basic rectified interpolation is the linear chord

$$U_\tau := (1 - \tau) \Xi + \tau U_f, \qquad \tau \in [0, 1]. \tag{3}$$

Its conditional law at rectification time $\tau$ is

$$\rho_\tau^c := \mathrm{Law}(U_\tau \mid C = c).$$

This is the population of intermediate states obtained by linearly interpolating between the noise sample and the target sample, under the chosen conditional coupling.

**The barycentric velocity is the "average chord direction" at $(u, \tau)$.** Along a single chord, the displacement $U_1 - U_0$ is constant in $\tau$. However, many chords pass through the same intermediate state $u$ at the same $\tau$; the correct population-level velocity is the average direction among those chords. Concretely, define

$$v^\star(u, \tau) := \mathbb{E}\big[\, U_1 - U_0 \,\big|\, U_\tau = u \,\big], \quad \rho_\tau\text{-a.e. } u. \tag{4}$$

This is the clean "one-line" definition of the barycentric field: it is a conditional expectation, so it is automatically the unique $L^2(\rho_\tau)$ minimizer of a regression problem.

**The ideal conditional barycentric velocity.** At a fixed condition $c$, many interpolation chords may pass through the same state $u$ at the same rectification time $\tau$. The correct population-level velocity is therefore the average chord direction conditioned on the current state:

$$v^\star(u, \tau; c) := \mathbb{E}[\, U_f - \Xi \,|\, U_\tau = u, \ C = c\,], \qquad \rho_\tau^c\text{-a.e. } u. \tag{5}$$

This is the *conditional barycentric rectified velocity.* It is the natural analogue, in the conditional setting, of the barycentric velocity used in standard rectified-flow theory. For the linear interpolation (3), the chord direction $U_f - \Xi$ is constant along each sample path, so (5) says that the ideal velocity field is obtained by averaging these constant sample-wise directions over all chords compatible with the observed intermediate state.

The field (5) is also the unique $L^2(\rho_\tau^c)$ minimizer of the conditional regression problem

$$\min_{v(\cdot, \tau; c)} \ \mathbb{E}\Big[\big\| v(U_\tau, \tau; c) - (U_f - \Xi) \big\|^2 \,\Big|\, C = c\Big].$$

This makes the practical training objective immediate: if one samples

$$c, \quad u_f \sim \mu_1^c, \quad \xi \sim \pi_0^c, \quad \tau \sim \mathrm{Unif}[0, 1],$$

forms

$$u_\tau = (1 - \tau)\xi + \tau u_f, \tag{6}$$

and trains $v_\theta$ against the constant target $(u_f - \xi)$, then the population minimizer is exactly the ideal conditional barycentric field (5). In particular, the transported quantity is the latent variable initialized at $\xi$, while the initial PDE state $c = u_i$ appears only as a condition in the network. With the notation above, the training loss is

$$\min_\theta \ \mathbb{E}\Big[\big\| v_\theta(u_\tau, \tau; c) - (u_f - \xi) \big\|^2\Big], \qquad u_\tau = (1 - \tau)\xi + \tau u_f, \tag{7}$$

where the expectation is taken over the joint sampling of $(c, u_f)$ from the dataset, $\xi \sim \pi_0^c$, and $\tau \sim \mathrm{Unif}[0, 1]$. This is the conditional rectified-flow objective used throughout the paper.

**Sampling from the learned conditional law.** Once trained, the model generates a conditional sample at a prescribed initial datum $c = u_i$ by drawing

$$\xi \sim \pi_0^{u_i}$$

and integrating the conditional transport ODE

$$\frac{d}{d\tau} u_\tau = v_\theta(u_\tau, \tau; u_i), \qquad u_0 = \xi. \tag{8}$$

The final state $u_1$ is then the model sample from the learned approximation to the conditional law $\mu_1^{u_i}$.

**Rectification time versus physical time.** The variable $\tau \in [0, 1]$ is an *internal* transport parameter and should not be confused with the physical PDE time. The physical dynamics have already been absorbed into the conditional target law $p(u_f \mid u_i)$ through the training data. Rectification time only parameterizes the learned transport from the reference law to that target conditional law. The benefit of rectified flow is not that the learned velocity is literally constant, but that for a well-trained model it can vary substantially less along sampled trajectories than the score field underlying diffusion-based samplers. This matters because the numerical error of explicit ODE solvers depends on how rapidly

$$\tau \mapsto v_\theta(u_\tau, \tau; u_i)$$

changes along the realized trajectory. When this variation is small, few large steps suffice; when it becomes oscillatory, sampling becomes more delicate. In our experiments, such oscillations are especially pronounced in out-of-distribution conditional regimes, which motivates the curvature-aware controller described next.

**Curvature-aware control: monitoring velocity variation along the trajectory.** During sampling, at step $t$ with state $u_t$ and rectification time $\tau_t$, write

$$v_t := v_\theta(u_t, \tau_t; u_i),$$

and maintain an exponential moving average

$$v_t^{\text{ema}} = \lambda \, v_{t-1}^{\text{ema}} + (1 - \lambda) \, v_t, \qquad \lambda \in (0, 1). \tag{9}$$

We use the deviation

$$s_t := \|v_t - v_t^{\text{ema}}\|_2 \tag{10}$$

as a computable proxy for short-horizon variation of the velocity along the sampled path. Large values of $s_t$ indicate that the trajectory is entering a regime where the learned transport is bending or oscillating in rectification time, precisely where aggressive explicit stepping becomes less reliable.

**Blending and adaptive step size.** When the straightness proxy is large, we replace $v_t$ by a regularized velocity

$$\tilde{v}_t = (1 - \alpha_t)v_t + \alpha_t v_t^{\text{ema}}, \qquad \alpha_t \in [0, 1],$$

where $\alpha_t$ is chosen as an increasing function of $s_t$. At the same time, we choose the step size inversely proportional to the estimated local variation, for example

$$\Delta\tau_t \propto \frac{1}{\sqrt{\kappa_1 s_t + \kappa_2}}, \qquad \Delta\tau_t \in [\Delta\tau_{\min}, \Delta\tau_{\max}]. \tag{11}$$

The resulting update is

$$u_{t+1} = u_t + \Delta\tau_t \, \tilde{v}_t.$$

This controller is dormant when the transport is straight and active only when the velocity becomes oscillatory. In Section 7 we connect this construction to the truncation error of explicit ODE integration and explain why such a controller is particularly helpful in the OOD regimes where velocity oscillations become more pronounced.

## 5.2 Error Decomposition and Bounds

There are two distinct sources of error once the spatial resolution is fixed. The first is a *continuous-time modeling error*: even if we could integrate the learned ODE exactly, the learned velocity field $v_\theta$ may differ from the ideal conditional barycentric field $v^\star$. The second is a *numerical discretization error*: even if $v_\theta$ were fixed, solving the learned ODE with finitely many steps introduces truncation error. These two effects should not be conflated. In particular, if $v_\theta = v^\star$, then the continuous-time modeling error must vanish; the remaining error is purely numerical.

**Ideal, learned, and discretized conditional flows.** Fix a condition $c$. Let $\Xi \sim \pi_0^c$, and let

$$\dot{U}_\tau = v^\star(U_\tau, \tau; c), \qquad U_0 = \Xi, \tag{12}$$

denote the *ideal* conditional rectified flow, and let

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c), \qquad \widehat{U}_0 = \Xi, \tag{13}$$

denote the *learned continuous-time* conditional flow driven by the neural velocity field. Finally, let $\widehat{U}_1^{(N)}$ denote the output obtained by numerically integrating (13) with $N$ explicit steps. Writing

$$\widehat{\mu}_1^{c,\text{cts}} := \text{Law}(\widehat{U}_1 \mid C = c), \qquad \widehat{\mu}_1^{c,N} := \text{Law}(\widehat{U}_1^{(N)} \mid C = c),$$

the conditional law error satisfies the elementary decomposition

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \;\leq\; W_2\big(\mu_1^c, \widehat{\mu}_1^{c,\text{cts}}\big) \;+\; W_2\big(\widehat{\mu}_1^{c,\text{cts}}, \widehat{\mu}_1^{c,N}\big). \tag{14}$$

The first term is the *fit* error of the learned velocity field; the second is the *discretization* error of the sampler. The exact-transport statement proved later in Proposition 7.2 identifies $\mu_1^c$ as the terminal law of the ideal flow (12).

*Remark* 5.1 (Disintegration form). If one prefers a geometric formula, (4) is equivalent to disintegrating $\gamma$ along the map $T_\tau$:

$$v^\star(u, \tau) = \int_{T_\tau^{-1}(u)} (u_1 - u_0)\, \gamma_u^\tau(du_0, du_1), \quad T_\tau^{-1}(u) = \{(u_0, u_1) : (1-\tau)u_0 + \tau u_1 = u\}.$$

Keeping this as a remark avoids leading with fiber notation.

**Rectified-flow training = regression onto constant chord directions.** Given samples $(u_0, u_1) \sim \gamma$ and $\tau \sim \text{Unif}[0,1]$, form $u_\tau = (1-\tau)u_0 + \tau u_1$. Train $v_\theta$ by

$$\min_\theta\; \mathbb{E}\Big[\big\| v_\theta(u_\tau, \tau) - (u_1 - u_0) \big\|^2\Big]. \tag{15}$$

By the $L^2$ optimality of conditional expectation, the population minimizer of (15) is exactly $v^\star$ in (4). The key qualitative point is immediate: the regression target $(u_1 - u_0)$ does *not* depend on $\tau$. So the learned field is pressured to behave as *time-stationary as the data allow* along these chords. This is the precise sense in which rectified-flow training promotes "straight" transports without separately adding an ad hoc straightness penalty.

**Sampling = integrate the learned transport ODE.** Once $v_\theta$ approximates $v^\star$, sampling amounts to integrating

$$\frac{du_\tau}{d\tau} = v_\theta(u_\tau, \tau), \quad u_0 \sim \mu_0, \tag{16}$$

and returning $u_1$ at $\tau = 1$. In the idealized chord model where $v^\star$ is constant in $\tau$ along typical trajectories, large steps are accurate; deviations from that ideal appear as *time-variation* of the velocity along the path, which is exactly what discretization error is sensitive to (see Lemma 5.7).

**Curvature-aware control: estimate "how non-constant in $\tau$" the velocity is.** During sampling, write $v_t := v_\theta(u_t, \tau_t)$ and maintain an EMA trend

$$v_t^{\text{ema}} = \lambda\, v_{t-1}^{\text{ema}} + (1 - \lambda)\, v_t, \quad \lambda \in (0, 1). \tag{17}$$

Define the instantaneous straightness/curvature proxy

$$s_t := \|v_t - v_t^{\text{ema}}\|_2,$$

which measures short-horizon time-variation of the velocity along the realized trajectory. Large $s_t$ signals local bending / stiffness, precisely the regime where explicit large-step integration incurs higher local truncation error (again, Lemma 5.7).

**A one-line regularized update (closed form).** When $s_t$ is large, replace $v_t$ by a gently regularized velocity $\tilde{v}_t$ defined as the minimizer of

$$\tilde{v}_t \; := \; \arg\min_w \; \|w - v_t\|_2^2 \; + \; \eta_t \, \|w - v_t^{\mathrm{ema}}\|_2^2,$$

which yields the explicit convex blend

$$\tilde{v}_t = (1 - \alpha_t)v_t + \alpha_t v_t^{\mathrm{ema}}, \quad \alpha_t = \frac{\eta_t}{1 + \eta_t} \in [0, 1]. \tag{18}$$

Choosing $\eta_t$ as a saturating function of $s_t$ makes the correction dormant when the path is straight and active only when curvature spikes.

**Adaptive step size from the same signal.** Since explicit Euler LTE scales like $(\Delta\tau)^2$ times a norm of the time-variation of the vector field (Lemma 5.7), use $s_t$ as a scale proxy and set

$$\Delta\tau_t \; \propto \; \frac{1}{\sqrt{\kappa_1 s_t + \kappa_2}}, \quad \Delta\tau_t \in [\Delta\tau_{\min}, \Delta\tau_{\max}], \tag{19}$$

with $\kappa_2$ absorbing baseline stiffness (e.g. dependence on $\|v_t\|$ and local Lipschitz effects). The state update is then

$$u_{t+1} = u_t + \Delta\tau_t \, \tilde{v}_t.$$

When the learned transport is locally straight ($s_t$ small), the sampler automatically takes large steps and behaves like "chord shooting"; when curvature increases, it both damps the direction and contracts the step, preventing instability while retaining the large-step advantage in the straight regime.

### 5.3 Error Decomposition and Bounds

We now quantify why (18)–(19) help. Write the *ideal* and *learned* flows

$$\dot{u}_\tau = v_\star(u_\tau, \tau), \quad \dot{\hat{u}}_\tau = v_\theta(\hat{u}_\tau, \tau),$$

with the same $u_0$. Assume $v_\theta(\cdot, \tau)$ is $L$-Lipschitz in $u$ and $v_\star \in L^2$.

**Theorem 5.2** (Continuous-time fit error for the learned conditional flow). *Fix a condition $c$ and assume that $v_\theta(\cdot, \tau; c)$ is $L$-Lipschitz in $u$, uniformly in $\tau \in [0, 1]$. Let $U_\tau$ and $\widehat{U}_\tau$ solve (12) and (13) with the same initial sample $\Xi \sim \pi_0^c$. Then*

$$\left( \mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \,\big|\, C = c\big] \right)^{1/2} \; \leq \; e^L \int_0^1 \left( \mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \,\big|\, C = c\big] \right)^{1/2} d\tau. \tag{20}$$

*In particular, defining*

$$\varepsilon_{\mathrm{fit}}^2(c) := \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \,\big|\, C = c\big]\, d\tau, \tag{21}$$

*we obtain*

$$\left( \mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \,\big|\, C = c\big] \right)^{1/2} \; \leq \; e^L \, \varepsilon_{\mathrm{fit}}(c). \tag{22}$$

*Proof sketch.* Set $E_\tau := \widehat{U}_\tau - U_\tau$. Then

$$\dot{E}_\tau = v_\theta(\widehat{U}_\tau, \tau; c) - v^\star(U_\tau, \tau; c) = \big(v_\theta(\widehat{U}_\tau, \tau; c) - v_\theta(U_\tau, \tau; c)\big) + \big(v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\big).$$

The Lipschitz assumption yields

$$\|\dot{E}_\tau\| \leq L\|E_\tau\| + \|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|.$$

Applying Grönwall's inequality pathwise, then taking conditional $L^2$ norms and using Minkowski's inequality in time, gives (20). The compact form (22) follows from Cauchy–Schwarz in $\tau$. □

Theorem 5.3 contains only a *fit* term. This is exactly as it should be: if $v_\theta = v^\star$, then the right-hand side is zero, so the learned continuous-time flow matches the ideal one. Straightness or curvature does *not* create continuous-time error by itself; it enters only when the learned ODE is discretized.

**Theorem 5.3** (Terminal error decomposition). *Let $U_\tau$ solve $\dot{U}_\tau = v_\star(U_\tau, \tau)$ with $U_0 = u_0$, and let $\hat{u}_\tau$ solve $\dot{\hat{u}}_\tau = v_\theta(\hat{u}_\tau, \tau)$ with $\hat{u}_0 = u_0$. Define the time–averaged velocity $\bar{v}_\theta(u) := \int_0^1 v_\theta(u, \tau) \, d\tau$ and*

$$\varepsilon_{\mathrm{fit}}^2 := \int_0^1 \mathbb{E}\big\|\bar{v}_\theta(U_\tau) - v_\star(U_\tau, \tau)\big\|^2 d\tau, \quad \varepsilon_{\mathrm{curv}}^2 := \int_0^1 \mathbb{E}\big\|v_\theta(U_\tau, \tau) - \bar{v}_\theta(U_\tau)\big\|^2 d\tau.$$

*Then, for the continuous–time flows,*

$$\mathbb{E}\big\|\hat{u}_1 - u_1\big\| \ \leq \ e^L \Big(\varepsilon_{\mathrm{fit}} + \varepsilon_{\mathrm{curv}}\Big). \tag{23}$$

**Interpretation.** The terminal error splits into a *reconstruction* term ($\varepsilon_{\mathrm{fit}}$) and a *straightness* term ($\varepsilon_{\mathrm{curv}}$). Blending (18) shrinks the within-time variation, directly tightening the bound; the adaptive stepping in (19) triggers corrections where the curvature proxy $s_t$ spikes.

**Lemma 5.4** (Local truncation error for explicit Euler on the learned conditional ODE). *Assume that $v_\theta$ is $C^1$ in $(u, \tau)$ on the region traversed by the learned trajectory $\widehat{U}_\tau$, and define*

$$g(\tau) := v_\theta(\widehat{U}_\tau, \tau; c).$$

*Then one explicit-Euler step of size $\Delta\tau$ from time $\tau$ along the learned ODE (13) satisfies*

$$\begin{aligned}
\mathrm{LTE}(\tau; \Delta\tau) &:= \left\|\widehat{U}_{\tau + \Delta\tau} - \big(\widehat{U}_\tau + \Delta\tau \, v_\theta(\widehat{U}_\tau, \tau; c)\big)\right\| \\
&= \frac{(\Delta\tau)^2}{2} \|\dot{g}(\tau)\| + \mathcal{O}\big((\Delta\tau)^3\big) \\
&= \frac{(\Delta\tau)^2}{2} \left\|\partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c) \, v_\theta(\widehat{U}_\tau, \tau; c)\right\| + \mathcal{O}\big((\Delta\tau)^3\big).
\end{aligned} \tag{24}$$

*If, in addition,*

$$\|\partial_\tau v_\theta(u, \tau; c)\| \leq M_\tau, \qquad \|J_u v_\theta(u, \tau; c)\| \leq L, \qquad \|v_\theta(u, \tau; c)\| \leq M$$

*on the relevant region, then*

$$\mathrm{LTE}(\tau; \Delta\tau) \ \leq \ \frac{(\Delta\tau)^2}{2} (M_\tau + LM) + \mathcal{O}\big((\Delta\tau)^3\big). \tag{25}$$

*Proof sketch.* Taylor-expand the exact trajectory $\widehat{U}_{\tau + \Delta\tau}$ around $\tau$. Since

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c),$$

the second derivative is

$$\ddot{\widehat{U}}_\tau = \frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c) \dot{\widehat{U}}_\tau,$$

and substituting $\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c)$ gives (24). The bound (25) is immediate. $\quad\square$

**Corollary 5.5** (Global Euler discretization error). *Assume the hypotheses of Lemma 5.7, and assume again that $v_\theta(\cdot, \tau; c)$ is $L$-Lipschitz in $u$ uniformly in $\tau$. Let $\widehat{U}^{(N)}$ denote the explicit-Euler approximation of (13) with uniform step $\Delta\tau = 1/N$. Then there exists a constant $C(L) > 0$ such that*

$$\sup_{0 \leq n \leq N} \Big(\mathbb{E}\big[\|\widehat{U}_{\tau_n}^{(N)} - \widehat{U}_{\tau_n}\|^2 \,\big|\, C = c\big]\Big)^{1/2} \ \leq \ C(L) \, \Delta\tau \int_0^1 \Big(\mathbb{E}\big[\|\dot{g}(\tau)\|^2 \,\big|\, C = c\big]\Big)^{1/2} d\tau, \tag{26}$$

*where*

$$\dot{g}(\tau) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

*Equivalently, defining*

$$\varepsilon_{\mathrm{disc}}(c; N) := \frac{1}{N} \int_0^1 \left( \mathbb{E}\big[\|\dot{g}(\tau)\|^2 \,\big|\, C = c\big] \right)^{1/2} d\tau, \tag{27}$$

*we have*

$$\sup_{0 \leq n \leq N} \left( \mathbb{E}\big[\|\widehat{U}_{\tau_n}^{(N)} - \widehat{U}_{\tau_n}\|^2 \,\big|\, C = c\big] \right)^{1/2} \leq C(L)\, \varepsilon_{\mathrm{disc}}(c; N). \tag{28}$$

*Proof sketch.* The local truncation error from Lemma 5.7 is of order $(\Delta \tau)^2 \|\dot{g}(\tau)\|$. Summing over $N$ steps and propagating the local errors through the $L$-Lipschitz flow stability yields a standard discrete Grönwall estimate, giving (26). □

Corollary 5.5 shows that the quantity governing step-count requirements is the *total derivative of the learned velocity along the sampled trajectory,*

$$\frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

This is the precise mathematical meaning of "curvature" or "straightness" in rectification time for our sampler. It is not merely the partial derivative $\partial_\tau v_\theta$ at fixed state, but the full variation of the velocity seen along the realized transport path.

**Corollary 5.6** (High-probability control of terminal error)**.** *Under the same assumptions as Theorem 5.3, suppose in addition that*

$$\int_0^1 \mathbb{E}\big\|v_\theta(U_\tau, \tau) - v_\star(U_\tau, \tau)\big\|^2 d\tau \leq \varepsilon_{\mathrm{fit}}^2, \quad \int_0^1 \mathbb{E}\big\|v_\theta(U_\tau, \tau) - \bar{v}_\theta(U_\tau)\big\|^2 d\tau \leq \varepsilon_{\mathrm{curv}}^2,$$

*so that both the reconstruction error and straightness error are controlled in $L^2$. Then there exists a constant $C(L)$ such that*

$$\mathbb{E}\big\|\hat{u}_1 - u_1\big\|^2 \leq C(L)\left(\varepsilon_{\mathrm{fit}}^2 + \varepsilon_{\mathrm{curv}}^2\right). \tag{29}$$

*Consequently, for any tolerance $\eta > 0$, Chebyshev's inequality yields*

$$\mathbb{P}\big(\|\hat{u}_1 - u_1\| > \eta\big) \leq \frac{C(L)\left(\varepsilon_{\mathrm{fit}}^2 + \varepsilon_{\mathrm{curv}}^2\right)}{\eta^2}. \tag{30}$$

*In particular, as training drives $\varepsilon_{\mathrm{fit}}, \varepsilon_{\mathrm{curv}} \to 0$, the probability of a large terminal error event decays at least quadratically in the target radius $\eta$.*

*Proof sketch.* The proof follows the same Grönwall argument as Theorem 5.3, but carried out in $L^2$ instead of $L^1$, yielding $\mathbb{E}\|\hat{u}_1 - u_1\|^2 \leq C(L)(\varepsilon_{\mathrm{fit}}^2 + \varepsilon_{\mathrm{curv}}^2)$ for some $C(L) \sim e^{2L}$. Chebyshev's inequality then gives $\mathbb{P}(\|\hat{u}_1 - u_1\| > \eta) \leq \mathbb{E}\|\hat{u}_1 - u_1\|^2/\eta^2$, which is the claimed bound. A full proof (including the sharp dependence on the straightness functional) is deferred to the theory appendix. □

**Lemma 5.7** (Local truncation error for explicit Euler on $\dot{u} = v(u, \tau)$)**.** *Assume $v \in C^1$ in $(u, \tau)$ on the region traversed and that $\|\partial_\tau v(u, \tau)\| \leq M_\tau$, $\|J_u v(u, \tau)\| \leq L$, and $\|v(u, \tau)\| \leq M$. Then one explicit-Euler step from $(u, \tau)$ with step size $\Delta \tau$ has local truncation error*

$$\mathrm{LTE}(\tau; \Delta \tau) := \big\|u(\tau + \Delta \tau) - \big(u(\tau) + \Delta \tau\, v(u(\tau), \tau)\big)\big\|$$

$$= \frac{(\Delta \tau)^2}{2} \big\|\partial_\tau v(u, \tau) + J_u v(u, \tau)\, v(u, \tau)\big\| + \mathcal{O}\big((\Delta \tau)^3\big) \tag{31}$$

$$\leq \frac{(\Delta \tau)^2}{2}\, (M_\tau + LM) + \mathcal{O}\big((\Delta \tau)^3\big).$$

**Connection to the EMA controller.** The practical proxy

$$s_t = \|v_t - v_t^{\text{ema}}\|_2, \qquad v_t = v_\theta(u_t, \tau_t; c),$$

used in Section 5.1, is intended to track this trajectory-wise variation over a short time window. Large values of $s_t$ indicate that the map $\tau \mapsto v_\theta(u_\tau, \tau; c)$ is oscillating, precisely the regime where (24) predicts larger truncation error for aggressive explicit stepping. Empirically, we observed these oscillations to be much more pronounced in out-of-distribution conditional regimes, which is why the EMA-based blending and adaptive step size are most useful there.

**From Lemma 5.7 to the step rule.** The leading LTE term depends on $\|\partial_\tau v\|$ and $\|J_u v\, v\|$. The EMA deviation $s_t = \|v_t - v_t^{\text{ema}}\|$ is a computable proxy for the (local) time variation $\|\partial_\tau v\|$ (up to a scale factor tied to the EMA bandwidth), while $L\|v_t\|$ upper-bounds the spatial contribution. Enforcing LTE $\lesssim$ tol yields the square-root rule (19), with $\kappa_1$ absorbing the EMA bandwidth and $\kappa_2 \approx L\|v_t\|$. Under blending, $\|\tilde{v}_t - v_t^{\text{ema}}\| = (1 - \alpha_t)s_t$, so the curvature term and the required step shrink *together*, stabilizing integration where needed and enlarging steps elsewhere. See **SM J** for proofs and additional theoretical context.

## 5.4 Spectral Capacity, Structure Functions, and Law-Level Coverage

The discussion above isolates *fit* and *discretization* at a fixed spatial resolution. The remaining error source is *coverage*: even a perfect bandlimited surrogate cannot represent unresolved high-frequency content. We quantify that irreducible law-level floor in the next subsection through structure functions and spectral tails.

## 5.5 Spectral Capacity, Structure Functions, and Law-Level Coverage

**Functional setting.** We work on the periodic box $\mathcal{D} = \mathbb{T}^d$ and consider $L^2$ fields $\mathcal{H} := L^2(\mathcal{D}; \mathbb{R}^m)$ with norm $\|\cdot\|_2$. For incompressible velocity fields (e.g. SL2D, see Section 8), one may equivalently restrict to divergence-free subspaces and adopt the statistical-solution framework of Lanthaler et al. (2021b), which characterizes laws via correlation identities, admissible observables, and an energy inequality. In that framework the natural distance on laws is the $L^2$-based Wasserstein metric $W_2$, and small-scale regularity is expressed in terms of *structure functions* and their time-averages. The numerical ensembles used in our experiments fit this setting: they are generated by dissipative solvers on $\mathbb{T}^2$, have uniformly bounded energy, and exhibit empirical structure-function scaling (equivalently, power-law spectra) consistent with the assumptions below.

### 5.5.1 Bandlimited capacity and strain constraints

Any $u \in \mathcal{H}$ admits a Fourier series $u(x) = \sum_{k \in \mathbb{Z}^d} \hat{u}(k) e^{ik \cdot x}$. We write $P_{\leq K}$ for the projector onto modes $\{k : |k| \leq K\}$ and $P_{>K} = I - P_{\leq K}$. On a grid of size $N^d$, the Nyquist frequency satisfies $K_{\max} \simeq N$, so every numerically represented field is effectively bandlimited to $|k| \lesssim K_{\max}$. Architecturally, downsampling and anti-aliasing may enforce an even stricter cutoff $K_c \leq K_{\max}$.

The next lemma is a standard Bernstein-type inequality: bandlimited fields have a uniform Lipschitz cap.

**Lemma 5.8** (Bernstein upper bound for bandlimited fields). *Let $u : \mathbb{T}^d \to \mathbb{R}^m$ satisfy $u = P_{\leq K}u$ for some integer $K \geq 1$. Then there exists a constant $C_d > 0$ depending only on the dimension $d$ such that*

$$\|\nabla_x u\|_{L^\infty(\mathbb{T}^d)} \leq C_d K^{1 + \frac{d}{2}} \|u\|_{L^2(\mathbb{T}^d)}. \tag{32}$$

*In particular, on an energy shell $\|u\|_{L^2} \leq E^{1/2}$ one has*

$$\|\nabla_x u\|_{L^\infty} \leq C_d K^{1 + \frac{d}{2}} E^{1/2}. \tag{33}$$

*Proof sketch.* Write $u(x) = \sum_{|k| \leq K} \hat{u}(k) e^{ik \cdot x}$, so $\nabla_x u(x) = \sum_{|k| \leq K} (ik)\hat{u}(k) e^{ik \cdot x}$ and $|\nabla_x u(x)| \leq \sum_{|k| \leq K} |k|\,|\hat{u}(k)|$. Cauchy–Schwarz and a lattice-counting bound $\#\{|k| \leq K\} \lesssim K^d$ give $\|\nabla u\|_{L^\infty} \lesssim (\sum_{|k| \leq K} |k|^2)^{1/2}\|\hat{u}\|_{\ell^2} \lesssim K^{1+d/2}\|u\|_{L^2}$. Full details are deferred to the theory appendix. □

Upper bounds alone do not say what happens if a surrogate *misses* an entire high-frequency annulus. The next lemma gives a complementary lower bound.

**Lemma 5.9** (Annulus lower bound). *Let $f = P_{[K,2K]}u$ for some $u \in L^2(\mathbb{T}^d)$, where $P_{[K,2K]} := P_{\leq 2K} - P_{\leq K}$ and $K \geq 1$. Then there exists $c_d > 0$ such that*

$$\|\nabla_x f\|_{L^\infty} \geq c_d K \|f\|_{L^\infty} \geq c_d K^{1-\frac{d}{2}} \|f\|_{L^2}. \tag{34}$$

*Proof sketch.* On the annulus $\{K \leq |k| \leq 2K\}$, the symbol of $\nabla$ has magnitude $|k| \in [K, 2K]$. This yields $\|\nabla f\|_{L^\infty} \gtrsim K\|f\|_{L^\infty}$. A reverse Bernstein estimate on an annulus gives $\|f\|_{L^\infty} \gtrsim K^{-d/2}\|f\|_{L^2}$. See the theory appendix for a precise statement independent of the Littlewood–Paley cut-off choice. □

**Corollary 5.10** (Capacity requirement for typical strain levels). *Suppose the target flows at time $t$ have typical energy $E$ and typical rate-of-strain $\|\nabla_x u\|_{L^\infty} \simeq L_\star$. Let a surrogate produce only bandlimited outputs $u = P_{\leq K_c}u$ with $\|u\|_{L^2} \leq E^{1/2}$. Then necessarily*

$$C_d K_c^{1+\frac{d}{2}} E^{1/2} \gtrsim L_\star, \tag{35}$$

*and hence a minimal cutoff*

$$K_c \gtrsim \left(\frac{L_\star}{E^{1/2}}\right)^{\frac{2}{2+d}}. \tag{36}$$

*Moreover, if the true flow has nontrivial energy in an annulus above $K_c$, then any bandlimited approximation underestimates its strain by at least $c_d K^{1-d/2}\|P_{[K,2K]}u\|_{L^2}$ for some $K > K_c$.*

*Remark* 5.11. Corollary 5.10 formalises the intuition that spatial capacity ($K_c$) is a hard constraint: at fixed energy scale $E$, there is a minimum cutoff needed to represent typical strain levels $L_\star$. In our experiments both GenCFD and ReFlow operate at the same grid resolution, so they share the same effective $K_c$; rectification does not invent new small scales but makes the trajectories inside this bandlimited class straight and easy to integrate.

### 5.5.2 Structure functions and small-scale coverage

We now quantify how much of the *law* of the PDE solution can be captured at a given cutoff $K_c$. For $u : \mathbb{T}^d \to \mathbb{R}^m$ and $r > 0$ define the second-order structure function

$$S_r^2(u) := \frac{1}{|B_r|} \int_{|h| \leq r} \|u(\cdot + h) - u(\cdot)\|_{L^2(\mathbb{T}^d)}^2 \, dh,$$

and for a probability law $\mu$ on $\mathcal{H}$ set

$$S_r^2(\mu) := \int S_r^2(u) \, d\mu(u).$$

In homogeneous turbulence $S_r^2(\mu)$ is directly related to the energy spectrum; power-law behaviour $S_r^2(\mu) \sim r^{\zeta_2}$ at small $r$ encodes the scaling of the cascade. In our experiments, Figure 22 visualizes this connection directly: matching the high-wavenumber tail in the spectrum is equivalent to capturing the small-$r$ behaviour of structure functions, and therefore to controlling the coverage term below.

Guided by the statistical-solution framework of Fjordholm et al. (2017), we assume there exists a modulus of continuity $\omega : (0, 1] \to [0, \infty)$ with $\omega(r) \downarrow 0$ as $r \downarrow 0$ such that

$$S_r^2(\mu_t) \leq \omega(r) \quad \text{for all } r \in (0, 1], \ t \in [0, T]. \tag{37}$$

In practice, $\omega$ can be taken as a piecewise power law $Cr^{2\alpha}$ calibrated from the empirical spectra of the numerical ensembles. The next lemma shows that (37) controls the high-frequency tail of the law.

**Lemma 5.12** (Structure function controls Fourier tail). *Let $\mu$ be a law on $L^2(\mathbb{T}^d)$ satisfying $S_r^2(\mu) \leq \omega(r)$ for all $r \in (0, 1]$, where $\omega(r) \downarrow 0$ as $r \downarrow 0$. Then there exist constants $c_d, C_d > 0$ such that for all integers $K \geq 1$,*

$$\int \|P_{>K}u\|_{L^2}^2 \, d\mu(u) \leq C_d \omega(c_d/K). \tag{38}$$

*Proof sketch.* Expand $u$ in Fourier series and observe $\|u(\cdot + h) - u(\cdot)\|_{L^2}^2 = \sum_k |\hat{u}(k)|^2 |e^{ik \cdot h} - 1|^2$. Averaging over $h \in B_r$ yields $S_r^2(u) = \sum_k |\hat{u}(k)|^2 \Psi_r(k)$, where $\Psi_r(k) \gtrsim \min\{(|k|r)^2, 1\}$ uniformly in $k, r$. For $|k| \gtrsim 1/r$, one has $\Psi_r(k) \gtrsim 1$, hence $S_r^2(u) \gtrsim \|P_{>c/r} u\|_{L^2}^2$. Integrate over $u \sim \mu$, apply (37), and set $r \sim 1/K$. Full constants and the Littlewood–Paley formulation are deferred to the theory appendix. $\qquad\square$

**Lemma 5.13** (Bandlimited projection in $W_2$). *For any law $\mu$ on $L^2(\mathbb{T}^d)$ and cutoff $K_c \geq 1$,*

$$W_2\big(\mu, (P_{\leq K_c})_{\#}\mu\big) \leq \left( \int \|P_{>K_c} u\|_{L^2}^2 \, d\mu(u) \right)^{1/2}. \tag{39}$$

*Proof.* Couple $u \sim \mu$ and $\tilde{u} = P_{\leq K_c} u$. Then $\tilde{u} \sim (P_{\leq K_c})_{\#}\mu$ and $W_2^2(\mu, (P_{\leq K_c})_{\#}\mu) \leq \mathbb{E}\|u - \tilde{u}\|_{L^2}^2 = \mathbb{E}\|P_{>K_c} u\|_{L^2}^2$. $\qquad\square$

Combining Lemmas 5.12 and 5.13 gives a clean coverage bound.

**Corollary 5.14** (Coverage term from the structure-function modulus). *Let $\mu_t$ be the statistical solution law at time $t$ and assume (37). Then for any cutoff $K_c \geq 1$,*

$$W_2\big(\mu_t, (P_{\leq K_c})_{\#}\mu_t\big) \lesssim \omega\big(c_d/K_c\big)^{1/2}, \tag{40}$$

*with $c_d$ as in Lemma 5.12.*

### 5.5.3 Capacity–coverage–fit decomposition for one-step RF

Finally, we combine the coverage term with the training error of a one-step rectified-flow surrogate.

Let $S_{\Delta t} : \mathcal{H} \to \mathcal{H}$ denote the PDE solution operator over a physical step $\Delta t$, and write

$$\mu_{t+\Delta t} := (S_{\Delta t})_{\#}\mu_t.$$

Assume the rectified-flow propagator $\mathcal{T}_{\Delta t}^\theta$ aims at the bandlimited target $P_{\leq K_c}(S_{\Delta t} u)$ in mean-square. Concretely, sample $u \sim \mu_t$ and an internal noise seed $\xi \sim \mathcal{N}(0, I)$, and define the RF output $\hat{u} := \mathcal{T}_{\Delta t}^\theta(u, \xi)$. We measure the training fit by

$$\varepsilon_{\text{train}}^2(t) := \mathbb{E}_{u \sim \mu_t} \mathbb{E}_{\xi \sim \mathcal{N}(0, I)} \big\| P_{\leq K_c}(S_{\Delta t} u) - \hat{u} \big\|_{L^2}^2. \tag{41}$$

Finally, we define the one-step RF law by

$$\hat{\mu}_{t+\Delta t} := \text{Law}(\hat{u}).$$

**Proposition 5.15** (One-step law-level error: capacity, coverage, and fit). *Under the structure-function modulus assumption (37), the one-step $W_2$ error between the PDE law and the RF law satisfies*

$$W_2\big(\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}\big) \leq \left( C_d \, \omega\big(c_d/K_c\big) + \varepsilon_{\text{train}}^2(t) \right)^{1/2}, \tag{42}$$

*where the first term is a* coverage *error determined by the structure-function modulus and the cutoff $K_c$, and the second is a* fit *error determined by training.*

*Proof sketch.* Couple $u \sim \mu_t$ and $\hat{u}$ using the same input; then $W_2^2(\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}) \leq \mathbb{E}\|S_{\Delta t} u - \hat{u}\|_{L^2}^2$. Insert $P_{\leq K_c} S_{\Delta t} u$, apply the triangle inequality, and bound the tail term by Lemma 5.12 (applied at time $t + \Delta t$). $\qquad\square$

**Interpretation and experimental validation.** At a fixed resolution (fixed $K_c$), Proposition 5.15 says that even a perfectly trained rectified flow cannot beat the coverage term $\omega(c_d/K_c)^{1/2}$ dictated by small-scale physics. This is precisely why spectrum matching (Figure 22) is a non-negotiable diagnostic on multiscale flows: if the surrogate loses the high-frequency tail, it is *necessarily* paying a coverage penalty in law. The remaining error is controlled by the training fit and the straightness properties of the learned velocity (via the continuous-time bounds in Section 5.1). Rectified flows improve efficiency precisely by reducing the curvature term in these bounds, so that a given coverage+fit accuracy can be reached with many fewer ODE steps than a diffusion-based surrogate such as GenCFD (Section 7.12).

# 6 Correctness and Curvature-Controlled Discretization

# 7 Correctness and Curvature-Controlled Discretization

**Organization.** The previous subsection isolated the two dynamical ingredients that matter once the spatial resolution is fixed: the *fit* of the learned velocity field to the ideal conditional rectified velocity, and the *discretization error* incurred when the learned ODE is solved with finitely many steps. We now add three complementary ingredients. First, we state the law-level correctness result for the ideal conditional barycentric velocity. Second, because our EMA/blending controller was introduced specifically to stabilize *OOD sampling*, we state a separate OOD-focused theorem for the blended sampler; this theorem is distinct in nature from the generic correctness statement and should be read as a structural analysis of the regime studied empirically in Section 9. Third, we combine the finite-resolution coverage term from Section 5.5, the continuous-time fit bound, and the discretization bound into a single conditional law-level decomposition:

$$\text{coverage} + \text{fit} + \text{discretization}.$$

Straightness enters the generic theory only through the discretization term. The EMA theorem below addresses the additional, practically important OOD regime in which the learned field develops oscillatory errors along rectification time.

**Organization.** This section states the main correctness and discretization results that underpin the narrative above. Full proofs are deferred to the theory appendix (to be written separately); we keep only the steps needed to make the dependence on *fit*, *straightness*, and *discretization* explicit in the main text.

## 7.1 Exact transport under the barycentric rectified velocity

## 7.2 Exact transport under the conditional barycentric rectified velocity

**Proposition 7.1** (Exact transport under the barycentric velocity)**.** *Let $\mu_0, \mu_1 \in \mathcal{P}(\mathcal{U})$ and let $\gamma \in \mathcal{P}(\mathcal{U} \times \mathcal{U})$ be a coupling of $(\mu_0, \mu_1)$. Define $T_\tau(u_0, u_1) = (1 - \tau)u_0 + \tau u_1$ and $\rho_\tau := (T_\tau)_\# \gamma$. Let $v_\star(\cdot, \tau)$ be the barycentric velocity field of defined in 4. Assume (e.g. on a finite-dimensional Galerkin discretization of $\mathcal{U}$) that the continuity equation*

$$\partial_\tau \rho_\tau + \nabla \cdot (\rho_\tau \, v_\star(\cdot, \tau)) = 0 \tag{43}$$

*admits a unique regular Lagrangian flow $X_\tau$ associated to $\dot{u}_\tau = v_\star(u_\tau, \tau)$. Then $(X_1)_\# \mu_0 = \mu_1$.*

**Proposition 7.2** (Exact conditional transport under the barycentric velocity)**.** *Fix a condition c. Let $\pi_0^c, \mu_1^c \in \mathcal{P}(\mathcal{U})$ be the reference and target conditional laws, let $\gamma^c$ be a coupling of $(\pi_0^c, \mu_1^c)$, and define the rectified interpolation*

$$U_\tau = (1 - \tau)\Xi + \tau U_f, \qquad (\Xi, U_f) \sim \gamma^c.$$

*Let*

$$\rho_\tau^c := \mathrm{Law}(U_\tau \mid C = c)$$

*and define the conditional barycentric velocity*

$$v^\star(u, \tau; c) = \mathbb{E}[U_f - \Xi \mid U_\tau = u, \ C = c], \qquad \rho_\tau^c\text{-a.e. } u.$$

*Assume, for instance on a finite-dimensional Galerkin discretization of $\mathcal{U}$, that the continuity equation*

$$\partial_\tau \rho_\tau^c + \nabla \cdot \left(\rho_\tau^c \, v^\star(\cdot, \tau; c)\right) = 0 \tag{44}$$

*admits a unique regular Lagrangian flow $X_\tau^c$ associated to*

$$\dot{u}_\tau = v^\star(u_\tau, \tau; c).$$

*Then*

$$(X_1^c)_\# \pi_0^c = \mu_1^c.$$

*In other words, the ideal conditional barycentric rectified velocity transports the reference law exactly to the target conditional law.*

*Proof sketch.* By construction, $\rho_\tau$ is the law of $U_\tau = (1-\tau)U_0 + \tau U_1$ for $(U_0, U_1) \sim \gamma$. Differentiate $\mathbb{E}[\varphi(U_\tau)]$ and condition on $U_\tau$ to identify the weak form of (43). Uniqueness of the continuity equation solution (in the chosen Galerkin setting) implies $\rho_\tau = (X_\tau)_\# \rho_0$, hence $\rho_1 = (X_1)_\# \rho_0$, i.e. $\mu_1 = (X_1)_\# \mu_0$. □

**Why this matters.** Proposition 7.2 isolates a clean correctness statement: if $v_\theta$ matches the barycentric rectified velocity $v_\star$ sufficiently well (in a sense quantified by Theorem 5.3), the induced flow pushes forward $\mu_0$ to $\mu_1$ at the level of laws.

*Proof sketch.* By construction, $\rho_\tau^c$ is the law of the random interpolation $U_\tau = (1-\tau)\Xi + \tau U_f$. For every smooth test function $\varphi$,

$$\frac{d}{d\tau}\,\mathbb{E}[\varphi(U_\tau) \mid C = c] = \mathbb{E}[\nabla\varphi(U_\tau) \cdot (U_f - \Xi) \mid C = c].$$

Conditioning further on $U_\tau$ gives

$$\frac{d}{d\tau}\,\mathbb{E}[\varphi(U_\tau) \mid C = c] = \mathbb{E}[\nabla\varphi(U_\tau) \cdot v^\star(U_\tau, \tau; c) \mid C = c],$$

which is exactly the weak form of (44). Since $\rho_0^c = \pi_0^c$ and uniqueness holds for the continuity equation in the chosen finite-dimensional setting, it follows that $\rho_\tau^c = (X_\tau^c)_\# \pi_0^c$ for all $\tau$, hence $\rho_1^c = (X_1^c)_\# \pi_0^c = \mu_1^c$. □

Proposition 7.2 is the law-level correctness statement underlying the method. It says that the ideal conditional rectified-flow ODE is not merely heuristic: at the population level, it transports the reference law to the target conditional law exactly. The only remaining issues are therefore approximation of the ideal velocity by $v_\theta$, numerical discretization of the learned ODE, and the unavoidable loss of unresolved high frequencies at finite spatial resolution.

## 7.3 Curvature controls the required number of ODE steps

## 7.4 A compact interpretation of straightness

The local truncation error result in Lemma 5.7 shows that the relevant notion of straightness is not a purely geometric property of the sample path $u_\tau$ itself, but the variation of the learned *velocity field along that path*:

$$\frac{d}{d\tau}v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\,v_\theta(\widehat{U}_\tau, \tau; c).$$

This is the precise quantity that determines how many explicit steps are required to integrate the learned transport stably. When this trajectory-wise variation is small, the learned flow behaves almost like "chord shooting" and very few ODE steps suffice. When it oscillates strongly, the sampler must reduce the step size or regularize the velocity direction, which is exactly the role of the EMA-based controller introduced earlier.

**The OOD regime.** In the out-of-distribution conditional settings studied in our experiments, the learned velocity field can encounter regions of state space that were less thoroughly represented during training. Empirically this manifests as stronger oscillations of $\tau \mapsto v_\theta(u_\tau, \tau; c)$, even when the overall conditional sample quality remains good. The EMA-based straightness proxy is designed precisely for this regime: it does not change the learned law in the continuous-time limit, but it makes the numerical integration of the learned ODE substantially more stable when these oscillations appear.

## 7.5 OOD stabilization by EMA blending

The EMA-based controller used in our sampler was not introduced to establish generic correctness of rectified flow. Its practical purpose is narrower: in the out-of-distribution macro–micro regime studied in Section 9, the learned velocity field can become substantially more oscillatory from one rectification step to the next, which makes explicit integration brittle. The role of EMA/blending is to suppress this oscillatory component

while preserving the slowly varying part of the transport. Accordingly, the theorem below is not a replacement for the exact-fit comparison of Theorem 5.3; it is an additional structural result for the OOD stabilization mechanism.

**Setup.** Fix a condition $c$ and let $U_\tau$ solve the ideal conditional rectified ODE

$$\dot{U}_\tau = v^\star(U_\tau, \tau; c), \qquad U_0 \sim \pi_0^c. \tag{45}$$

Along this ideal path, define

$$g(\tau) := v^\star(U_\tau, \tau; c), \tag{46}$$

and the learned-field error

$$\varepsilon(\tau) := v_\theta(U_\tau, \tau; c) - g(\tau). \tag{47}$$

Thus

$$v_\theta(U_\tau, \tau; c) = g(\tau) + \varepsilon(\tau).$$

Let $E_\lambda$ denote the causal exponential moving average operator in rectification time with bandwidth $\lambda > 0$. In continuous time one may write, for a trajectory-valued signal $f$,

$$(E_\lambda f)(\tau) := \frac{1}{\lambda} \int_0^\tau e^{-(\tau-s)/\lambda} f(s) \, ds, \tag{48}$$

up to the usual normalization convention. The precise convention affects only constants below.

We measure the total approximation error along the ideal path by

$$\varepsilon_{\text{approx}}^2(c) := \int_0^1 \mathbb{E}\big[\|\varepsilon(\tau)\|^2 \,\big|\, C = c\big] \, d\tau. \tag{49}$$

We also define the total along-trajectory variation of the ideal conditional velocity by

$$S_{*,\text{tot}}^2(c) := \int_0^1 \mathbb{E}\big[\|\dot{g}(\tau)\|^2 \,\big|\, C = c\big] \, d\tau, \tag{50}$$

where

$$\dot{g}(\tau) = \partial_\tau v^\star(U_\tau, \tau; c) + J_u v^\star(U_\tau, \tau; c) \, v^\star(U_\tau, \tau; c). \tag{51}$$

This is exactly the same total along-trajectory derivative that drives the local truncation error in Lemma 5.7.

**Oscillatory-error regime.** The EMA controller is useful only when the learned error has a genuinely oscillatory component in rectification time. To encode this structurally, let $\widehat{\varepsilon}(\omega)$ denote the temporal Fourier transform of $\varepsilon(\tau)$ along the rectification variable, and assume that for some $\eta \in (0, 1]$,

$$\int_{|\omega| > 1/\lambda} \mathbb{E}\big[|\widehat{\varepsilon}(\omega)|^2 \,\big|\, C = c\big] \, d\omega \;\geq\; \eta \int_{\mathbb{R}} \mathbb{E}\big[|\widehat{\varepsilon}(\omega)|^2 \,\big|\, C = c\big] \, d\omega. \tag{52}$$

For the exponential moving average, the transfer function has the form

$$H_\lambda(\omega) = \frac{1}{1 + i\lambda\omega}$$

up to convention, so $|H_\lambda(\omega)|^2$ decays like $(1 + \lambda^2 \omega^2)^{-1}$. Hence the high-frequency part of the error is strictly damped. We summarize this damping by the smoothing ratio

$$\sigma^2(c, \lambda) := \frac{\int_0^1 \mathbb{E}\big[\|E_\lambda \varepsilon(\tau)\|^2 \,\big|\, C = c\big] \, d\tau}{\int_0^1 \mathbb{E}\big[\|\varepsilon(\tau)\|^2 \,\big|\, C = c\big] \, d\tau}. \tag{53}$$

Under (52), one has

$$\sigma^2(c, \lambda) \leq 1 - c_0 \eta \tag{54}$$

for a universal constant $c_0 > 0$ depending only on the EMA convention. In particular, $\sigma(c, \lambda) < 1$ whenever a nontrivial portion of the error lies above the EMA cutoff frequency.

**A continuous-time surrogate for the blended sampler.** The actual sampler in our experiments uses discrete EMA updates and an adaptive blend weight $\alpha_t$. To isolate the mechanism analytically, we consider the continuous-time fixed-$\alpha$ surrogate

$$\widetilde{v}_\alpha := (1-\alpha)\, v_\theta + \alpha\, E_\lambda v_\theta, \qquad \alpha \in [0,1], \tag{55}$$

and let $\widetilde{U}_\tau$ solve

$$\dot{\widetilde{U}}_\tau = \widetilde{v}_\alpha(\widetilde{U}_\tau, \tau; c), \qquad \widetilde{U}_0 = U_0. \tag{56}$$

This idealization captures the same bias–variance tradeoff as the practical adaptive controller: smoothing suppresses oscillatory error but introduces a bias proportional to how much the *ideal* field itself varies along rectification time.

**Corollary 7.3** (Global Euler error controlled by time-curvature). *Assume the hypotheses of Lemma 5.7 for $\dot{u} = v(u,\tau)$ on $\tau \in [0,1]$ and assume $v(\cdot, \tau)$ is $L$-Lipschitz in $u$ uniformly in $\tau$. Let $u^\Delta$ be the explicit-Euler approximation with uniform step $\Delta\tau = 1/N$. Then there exists a constant $C = C(L)$ such that*

$$\sup_{\tau \in [0,1]} \|u_\tau^\Delta - u_\tau\| \;\leq\; C\,\Delta\tau \int_0^1 \Big( \|\partial_\tau v(u_\tau, \tau)\| + \|J_u v(u_\tau, \tau)\, v(u_\tau, \tau)\| \Big)\, d\tau. \tag{57}$$

*In particular, when $\int_0^1 \|\partial_\tau v(u_\tau, \tau)\|\, d\tau$ is small ("straight" flow), the $N$ required to reach a fixed tolerance is proportionally smaller.*

**Theorem 7.4** (EMA stabilization in the oscillatory OOD regime). *Assume that $v_\theta(\cdot, \tau; c)$ and $\widetilde{v}_\alpha(\cdot, \tau; c)$ are uniformly $L$-Lipschitz in $u$, and assume the oscillatory-error condition (52). Then there exists a universal constant $C_{\mathrm{ema}} > 0$ such that*

$$\Big( \mathbb{E}\big[ \|\widetilde{U}_1 - U_1\|^2 \,\big|\, C = c \big] \Big)^{1/2} \;\leq\; e^L \Big[ \big(1 - \alpha(1 - \sigma(c,\lambda))\big)\, \varepsilon_{\mathrm{approx}}(c) \;+\; C_{\mathrm{ema}}\, \alpha\, \lambda\, S_{*,\mathrm{tot}}(c) \Big]. \tag{58}$$

*The corresponding raw-field bound from Theorem 5.3 is*

$$e^L\, \varepsilon_{\mathrm{approx}}(c).$$

*Consequently, EMA blending gives a strictly sharper upper bound whenever*

$$(1 - \sigma(c,\lambda))\, \varepsilon_{\mathrm{approx}}(c) \;>\; C_{\mathrm{ema}}\, \lambda\, S_{*,\mathrm{tot}}(c). \tag{59}$$

*Proof sketch.* Sum the local truncation errors from Lemma 5.7 over $N$ steps and propagate them using stability of the flow under the $L$-Lipschitz condition via Grönwall. $\square$

**Connection to our curvature proxy.** The EMA deviation $s_t = \|v_t - v_t^{\mathrm{ema}}\|$ used in (18)–(19) is a computable proxy for the same time-variation that drives (57). Blending reduces effective curvature; step control reduces $\Delta\tau$ when curvature spikes. This directly rationalizes why ReFlow can reach the "spectrum-correct" regime in very few steps (Figure 22), and why the same accuracy level is reached at 8 steps (Table 1) whereas diffusion baselines typically need $\geq 128$.

*Proof sketch.* Apply the same Grönwall comparison used in Theorem 5.3, but with the blended field $\widetilde{v}_\alpha$ in place of $v_\theta$. Along the ideal path $U_\tau$ one has

$$\widetilde{v}_\alpha(U_\tau, \tau; c) - g(\tau) = (1-\alpha)\varepsilon(\tau) + \alpha E_\lambda \varepsilon(\tau) + \alpha(E_\lambda g(\tau) - g(\tau)).$$

Taking conditional $L^2$ norms in $\tau$ and using Minkowski's inequality yields

$$\|(1-\alpha)\varepsilon + \alpha E_\lambda \varepsilon\|_{L_\tau^2} \leq \big(1 - \alpha + \alpha\sigma(c,\lambda)\big)\, \varepsilon_{\mathrm{approx}}(c).$$

For the bias term, the standard causal-filter estimate gives

$$\|E_\lambda g - g\|_{L_\tau^2} \leq C_{\mathrm{ema}}\, \lambda\, \|\dot{g}\|_{L_\tau^2},$$

which becomes $C_{\mathrm{ema}}\lambda S_{*,\mathrm{tot}}(c)$ after conditioning and integration. Combining the two estimates and applying Grönwall yields (58). The improvement criterion (59) is immediate by comparison with the unsmoothed bound. $\square$

**Interpretation.** The bound (58) has the exact interpretation needed for the OOD sampler study:

- The factor $(1-\sigma)\varepsilon_{\text{approx}}$ is the *oscillatory error removed by EMA smoothing.*

- The term $\lambda S_{*,\text{tot}}$ is the *bias paid for smoothing,* and it is controlled by how much the *ideal conditional rectified velocity* varies along its own trajectories in rectification time.

Thus EMA blending is beneficial precisely when the learned OOD error is sufficiently oscillatory while the ideal rectified transport remains slowly varying in rectification time.

### 7.6 A compact regularity interpretation of structure functions

**Experimental considerations.** This is exactly the situation targeted in Section 9. There the model is frozen and only the sampler is varied. In the OOD macro–micro regime, the learned field develops pronounced step-to-step oscillations, which increases $\varepsilon_{\text{approx}}$ and makes the high-frequency component of the error non-negligible, hence $\sigma < 1$. At the same time, the ideal conditional rectified transport remains comparatively straight in rectification time, because the rectified-flow objective is designed to regress onto an approximately $\tau$-stationary chord direction. The practical effect is the one seen in Tables 2–4: EMA-based smoothing stabilizes the sampler and improves the NFE–error tradeoff without harming conditional diversity.

### 7.7 Master bound: coverage + fit + discretization

We now combine the finite-resolution coverage term from Section 5.5, the continuous-time fit bound from Theorem 5.3, and the discretization bound from Corollary 5.5.

Fix a condition $c$, and let

$$\mu_1^c$$

denote the target conditional law at the forecast time. Let $K_c$ be the effective spatial cutoff of the surrogate class, and let

$$P_{\leq K_c}$$

denote the corresponding low-frequency projection. We write

$$\mu_{1,\leq K_c}^c := (P_{\leq K_c})_{\#}\mu_1^c$$

for the projected target conditional law. Let $\widehat{\mu}_1^{c,\text{cts}}$ be the law of the learned *continuous-time* rectified flow and $\widehat{\mu}_1^{c,N}$ the law of the learned *discretized* rectified flow obtained with $N$ explicit steps.

**Lemma 7.5** (Structure functions imply Besov regularity (heuristic equivalence)). *Let $u \in L^2(\mathbb{T}^d)$ and define the increment seminorm*

$$[u]_{B_{2,\infty}^s} := \sup_{0<|h|\leq 1} \frac{\|u(\cdot + h) - u(\cdot)\|_{L^2}}{|h|^s}.$$

*If the second-order structure function satisfies $S_r^2(u) \lesssim r^{2s}$ for all $r \in (0,1]$, then $[u]_{B_{2,\infty}^s} \lesssim 1$. Consequently, a law-level modulus bound $S_r^2(\mu) \lesssim r^{2s}$ implies that typical samples from $\mu$ have Besov smoothness $s$, consistent with the Fourier-tail decay in Lemma 5.12.*

**Theorem 7.6** (Conditional law-level error decomposition). *Assume that the target conditional law $\mu_1^c$ satisfies the structure-function modulus hypothesis of Corollary 5.14, so that its unresolved high-frequency tail obeys*

$$W_2\big(\mu_1^c, \mu_{1,\leq K_c}^c\big) \lesssim \omega(c_d/K_c)^{1/2}. \tag{60}$$

*Assume also that the learned velocity field satisfies the hypotheses of Theorem 5.3 and Corollary 5.5. Then there exists a constant $C(L) > 0$ such that*

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \lesssim \underbrace{\omega(c_d/K_c)^{1/2}}_{coverage} + \underbrace{\varepsilon_{\text{fit}}(c)}_{fit} + \underbrace{C(L)\,\varepsilon_{\text{disc}}(c;N)}_{discretization}, \tag{61}$$

*where*

$$\varepsilon_{\mathrm{fit}}(c)^2 = \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \,\big|\, C = c\big]\, d\tau$$

*and*

$$\varepsilon_{\mathrm{disc}}(c; N) = \frac{1}{N} \int_0^1 \Big(\mathbb{E}\big[\|\partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c)\|^2 \,\big|\, C = c\big]\Big)^{1/2} d\tau.$$

*Remark* 7.7. In turbulence one often observes $S_r^2(\mu) \sim r^{\zeta_2}$ over an inertial range. Heuristically this corresponds to $s \approx \zeta_2/2$, so the coverage term in Corollary 5.14 can be read as a direct proxy for inertial-range scaling.

## 7.8 Master inequality

*Proof sketch.* Insert the projected target law $\mu_{1,\leq K_c}^c$ and the learned continuous-time law $\widehat{\mu}_1^{c,\mathrm{cts}}$ as intermediate terms:

$$W_2(\mu_1^c, \widehat{\mu}_1^{c,N}) \leq W_2(\mu_1^c, \mu_{1,\leq K_c}^c) + W_2(\mu_{1,\leq K_c}^c, \widehat{\mu}_1^{c,\mathrm{cts}}) + W_2(\widehat{\mu}_1^{c,\mathrm{cts}}, \widehat{\mu}_1^{c,N}).$$

The first term is exactly the coverage term (60). By Proposition 7.2, the ideal continuous-time rectified flow realizes the target conditional law at the population level, so the second term is controlled by Theorem 5.3 and equals the fit contribution. The third term is controlled by Corollary 5.5, giving the discretization contribution. □

**Interpretation of the master bound.** Theorem 7.8 gives the clean error taxonomy that the paper should emphasize throughout:

- *Coverage* is a hard floor imposed by finite spatial resolution and unresolved high-frequency content.

- *Fit* measures how accurately the learned neural velocity field approximates the ideal conditional barycentric transport.

- *Discretization* measures how difficult the learned transport is to integrate numerically, and this is where straightness enters.

In particular, straightness is *not* an additional continuous-time modeling error term. Instead, straighter learned transports reduce $\varepsilon_{\mathrm{disc}}(c; N)$, which is precisely why rectified flows can achieve the same law-level quality with many fewer function evaluations than diffusion-based samplers.

**Reading the theory against the experiments.** Equation (62) matches the empirical story in Section 8. The spectrum plots diagnose the coverage term by revealing whether the surrogate preserves high-wavenumber energy. The one-point Wasserstein and moment statistics diagnose overall conditional-law fidelity, which reflects both coverage and fit. Finally, the speed advantage of ReFlow is a discretization phenomenon: because the learned transport is substantially straighter along rectification time, the same conditional-law accuracy is reached with far fewer evaluations.

## 7.9 Optional regularity interpretation via structure functions

For completeness, we record the standard heuristic that structure-function control corresponds to Besov regularity and therefore to a quantitative high-frequency tail bound.

**Theorem 7.8** (Law-level error: coverage + fit + straightness + discretization). *Fix an effective resolution cutoff $K_c$ and assume the structure-function modulus hypothesis used in Corollary 5.14. Let $\hat{\mu}_1^{(N)}$ be the law obtained by taking $N$ explicit-Euler steps to integrate the learned rectified ODE $\dot{u}_\tau = v_\theta(u_\tau, \tau)$ from $\tau = 0$ to $\tau = 1$. Assume $v_\theta(\cdot, \tau)$ is $L$-Lipschitz in $u$ uniformly in $\tau$. Then, for constants depending on $L$,*

$$W_2\big(\mu_1, \hat{\mu}_1^{(N)}\big) \lesssim \underbrace{\omega(c_d/K_c)^{1/2}}_{coverage} + \underbrace{\varepsilon_{\mathrm{fit}} + \varepsilon_{\mathrm{curv}}}_{fit \,+\, straightness \,(Thm.\ 5.3)} + \underbrace{\frac{1}{N}\int_0^1 \|\partial_\tau v_\theta(u_\tau, \tau)\|\, d\tau}_{discretization \,(Cor.\ 7.3)}. \tag{62}$$

**Lemma 7.9** (Structure functions and Besov smoothness). *Let $u \in L^2(\mathbb{T}^d)$ and define*

$$[u]_{B_{2,\infty}^s} := \sup_{0 < |h| \leq 1} \frac{\|u(\cdot + h) - u(\cdot)\|_{L^2}}{|h|^s}.$$

*If*

$$S_r^2(u) \lesssim r^{2s} \qquad \text{for all } r \in (0, 1],$$

*then*

$$[u]_{B_{2,\infty}^s} \lesssim 1.$$

*Consequently, a law-level bound of the form*

$$S_r^2(\mu) \lesssim r^{2s}$$

*may be read as saying that typical samples drawn from $\mu$ have Besov regularity $s$, which is exactly the regularity controlling the Fourier-tail decay used in the coverage estimates.*

*Proof sketch.* The coverage term is Theorem 5.14. The continuous-time mismatch between the ideal rectified flow and the learned flow is controlled by Theorem 5.3 via $\varepsilon_{\text{fit}}$ and $\varepsilon_{\text{curv}}$. The discretization term follows from Corollary 7.3 applied to the learned ODE. $\qquad\square$

**Reading** (62) **against the experiments.** Equation (62) matches the empirical breakdown seen in Section 8: (i) *coverage* corresponds to reproducing the high-wavenumber energy content (Figure 22); (ii) *fit* corresponds to the overall statistical accuracy, reflected in $e_\mu$, $e_\sigma$, and $W_1$ (Table 1); (iii) *straightness* and *discretization* are exactly what turn "a good model" into "a fast sampler": ReFlow reaches the same law-level quality using $N = 8$ steps, whereas diffusion baselines require $N \geq 128$ (Section 7.12).

*Remark* 7.10. In turbulence one often observes inertial-range power laws

$$S_r^2(\mu) \sim r^{\zeta_2}.$$

Heuristically this corresponds to $s \approx \zeta_2/2$, so the coverage term in Theorem 7.8 can be interpreted as a direct law-level manifestation of inertial-range scaling.

## 7.10 Implementation Details for PDEs

## 7.11 Implementation Details for PDEs

**What is learned.** Our model is a *conditional noise-to-solution rectified flow*. Given an input/conditioning field $u_i$ (and, when relevant, boundary data or other known inputs), we learn a velocity field

$$v_\theta(x, \tau; u_i),$$

where:

- $u_i$ is the *conditioning variable*,

- $x_\tau$ is the *noise-initialized output state* transported in rectification time,

- $\tau \in [0, 1]$ is the internal rectification-time variable.

The key point is that $u_i$ is *not* the state being evolved by the rectified flow. It remains fixed throughout the trajectory and enters the network only as side information.

**Learning velocity fields in PDE settings.** When rectified flows are used to model PDE solutions, we assume access to paired initial/final states $(u_i, u_f)$ where $u_f = \mathcal{S}(u_i)$ represents the evolved initial condition $u_i$, at some final physical time (e.g. $t = 1$). We train a neural network to predict the velocity $v_\theta$ that displaces $u_i$ towards $u_f$, with the additional mention that $v_\theta$ shall be conditioned on $u_i$ at all diffusion times.

**Training pairs.** We assume access to paired samples

$$(u_i, u_f), \qquad u_f = \mathcal{S}_{\Delta t}(u_i),$$

where $\mathcal{S}_{\Delta t}$ denotes the PDE solution operator over the forecast horizon of interest. In the stochastic/statistical setting considered in this paper, repeated perturbations around the same macro input $u_i$ induce a conditional law of possible outputs; the purpose of the generator is to sample from this conditional output law.

**Rectified interpolation used in training.** For each training pair $(u_i, u_f)$, we sample source noise

$$\xi \sim \mathcal{N}(0, I)$$

and rectification time

$$\tau \sim \mathrm{Unif}[0, 1].$$

We then form the linear rectified interpolation

$$x_\tau = (1 - \tau)\, \xi + \tau\, u_f. \tag{63}$$

With this choice, the target velocity along the interpolation path is simply the constant chord direction

$$\dot{x}_\tau = u_f - \xi. \tag{64}$$

This is exactly the conditional rectified-flow objective introduced in Section 5.1: the network is trained to predict the transport direction from the current interpolated state $x_\tau$ and the condition $u_i$.

**Input:** Dataset $\{(u_0, u_1)\}$ with $u_1 = \mathcal{S}(u_0)$; velocity model $v_\theta$; noise schedule $\sigma(\tau)$

**for** each iteration **do**

Sample a pair $(u_0, u_1)$

Sample $\tau \sim \mathcal{U}(0, 1)$ and noise $\xi \sim \mathcal{N}(0, I)$

Form $u_\tau = \tau \cdot u_1 + \sigma(1 - \tau)\, \xi$

Compute loss:

$$\mathcal{L}(\theta) \;=\; \big\| (u_1 - u_0) \;-\; v_\theta(u_\tau,\, u_0,\, \tau) \big\|^2$$

Update $\theta$ via gradient descent

**end for**

**Overview of the model.** Our network learns a velocity (or denoising) map

$$v_\theta(u_\tau, u_0, \tau) \;=\; \mathrm{UNet}_\theta\big(u_\tau, u_0,\, \Gamma(\tau)\big),$$

where $u_\tau$ is a low-frequency representation of $u_1$, $u_0$ is the initial datum, and $\Gamma(\cdot)$ is an MLP-based time embedding:

$$\Gamma(\tau) \;=\; \mathrm{MLP}\big(\mathrm{Sinusoid}(\tau)\big).$$

Within the U-Net (see **SM** T.1), we alternate residual blocks with multi-head attention layers, downsampling to a bottleneck and then upsampling via skip connections. A final $1 \times 1$ projection recovers either the field increment $\hat{u} \approx u_1 - u_0$ or a noise residual. By injecting the rectification time $\Gamma(\tau)$ into each block, the model performs a fully deterministic trajectory integration instead of stochastic diffusion.

**Input:** Dataset of paired states $\{(u_i, u_f)\}$ with $u_f = \mathcal{S}_{\Delta t}(u_i)$; velocity model $v_\theta$

**for** each training iteration **do**

Sample a training pair $(u_i, u_f)$

Sample $\xi \sim \mathcal{N}(0, I)$

Sample $\tau \sim \mathcal{U}(0, 1)$

Form the rectified interpolation

$$x_\tau = (1 - \tau)\xi + \tau u_f$$

Compute the conditional rectified-flow loss

$$\mathcal{L}(\theta) = \left\| v_\theta(x_\tau, \tau; u_i) - (u_f - \xi) \right\|^2$$

Update $\theta$ by stochastic gradient descent / Adam

**end for**

**Network parameterization.** The neural network takes as input the transported state $x_\tau$, the conditioning field $u_i$, and a learned embedding of rectification time:

$$v_\theta(x_\tau, \tau; u_i) = \text{UNet}_\theta\big(x_\tau,\, u_i,\, \Gamma(\tau)\big), \tag{65}$$

where

$$\Gamma(\tau) = \text{MLP}\big(\text{Sinusoid}(\tau)\big)$$

is a sinusoidal time embedding followed by an MLP. Concretely, $x_\tau$ and $u_i$ are concatenated channelwise at the input, while $\Gamma(\tau)$ is injected into each block through standard feature-wise modulation / projection layers. Thus the time embedding is globally shared across the network, while each block has its own learned projection of that shared embedding.

**Sampling procedure.** Once trained, we generate new samples by numerically integrating the ODE

$$\frac{du_\tau}{d\tau} = v_\theta\big(u_\tau,\, u_0,\, \tau\big), \quad u_\tau|_{\tau=0} = \xi, \quad \xi \sim \mathcal{N}(0, I).$$

Any standard ODE solver (e.g. forward Euler, Runge-Kutta) can be used; rectified flows often tolerate relatively large step sizes due to their straighter velocity field.

**Architecture overview.** Our implementation uses a U-Net / UViT-style backbone with residual blocks, attention, downsampling to a bottleneck, and symmetric upsampling with skip connections; see the Supplementary Material for the exact architecture. The output head predicts the velocity field itself, i.e. an estimate of the chord direction $u_f - \xi$ conditioned on the current transported state and on the PDE input. This is in contrast to score-based diffusion models, which predict either a score or a denoising residual inside a stochastic reverse-time sampler.

**Efficiency and accuracy.** Because rectified flows explicitly encourage a "straighter" velocity field, accurate solutions often require fewer integration steps than their diffusion-based counterparts. This advantage can be crucial in computational fluid dynamics and other PDE applications where each solver step is expensive. See **SM** Z.9 and  for a detailed comparison of step-count vs. accuracy trade-offs.

**Sampling procedure.**   At inference time, the condition $u_i$ is fixed. We draw

$$\xi \sim \mathcal{N}(0, I),$$

set

$$x_0 = \xi,$$

and integrate the learned conditional ODE

$$\frac{d}{d\tau}x_\tau = v_\theta(x_\tau, \tau; u_i), \qquad x_{\tau=0} = \xi. \tag{66}$$

The final state $x_1$ is then interpreted as a sample from the learned approximation to the conditional output law associated with $u_i$.

**Input:** Condition/input field $u_i$; trained velocity model $v_\theta$; number of steps $N$ or adaptive controller

Sample $\xi \sim \mathcal{N}(0, I)$ and set $x_0 = \xi$

Initialize $\tau_0 = 0$

**if** using fixed-step integration **then**

**for** $t = 0, \ldots, N-1$ **do**

$v_t \leftarrow v_\theta(x_t, \tau_t; u_i)$

$\Delta\tau \leftarrow 1/N$

$x_{t+1} \leftarrow x_t + \Delta\tau\, v_t$

$\tau_{t+1} \leftarrow \tau_t + \Delta\tau$

**end for**

**else**

Initialize EMA state $m_0$

**for** $t = 0, 1, \ldots$ until $\tau_t \geq 1$ **do**

$v_t \leftarrow v_\theta(x_t, \tau_t; u_i)$

Update EMA:
$$m_t \leftarrow \lambda m_{t-1} + (1 - \lambda)v_t$$

Compute straightness proxy:
$$s_t \leftarrow \|v_t - m_t\|_2$$

Choose blend weight $\alpha_t$ and step size $\Delta\tau_t$ from $s_t$

Form blended velocity:
$$\widetilde{v}_t \leftarrow (1 - \alpha_t)v_t + \alpha_t m_t$$

Update state:
$$x_{t+1} \leftarrow x_t + \Delta\tau_t\, \widetilde{v}_t$$

$\tau_{t+1} \leftarrow \min\{1, \tau_t + \Delta\tau_t\}$

**end for**

**end if**

**return** $x_1$

The learned rectified transport is often straight enough that a small fixed number of Euler steps already gives excellent performance. The EMA/blending controller is introduced specifically to stabilize sampling in the more delicate OOD regime studied in Section 9, where the learned velocity exhibits stronger oscillations across rectification time. In that regime, the controller acts as a low-pass filter on the oscillatory component of the learned field and improves the NFE–error tradeoff without changing the underlying trained model.

**Relation to the theory.**   This implementation matches the conditional theory exactly:

- the source law is Gaussian noise,

- the transported state is $x_\tau$,

- the condition $u_i$ is fixed throughout sampling,

- the ideal target velocity is the conditional barycentric transport direction,

- and the EMA/blending mechanism is an *additional OOD stabilization device*, not part of the generic exactness statement.

**Practical efficiency.**   Because rectified-flow training promotes transports whose velocity varies comparatively slowly along rectification time, accurate sampling often requires only a handful of ODE evaluations. This is the computational advantage that distinguishes ReFlow from diffusion-based PDE surrogates: instead of integrating a long reverse-time stochastic process, we solve a short deterministic conditional transport ODE.

### 7.12  Computational Efficiency Comparison

Diffusion surrogates (e.g. GenCFD) generate samples by integrating a reverse-time SDE whose trajectory bends through latent noise; even with accelerated samplers such as DDPM or DPM-solver the procedure still requires tens of score-network evaluations. Rectified flows, in contrast, follow a single deterministic ODE whose nearly straight path tolerates large or adaptive steps, so inference needs only a handful of evaluations. Figure 3 quantifies this gap, showing how the runtime of diffusion models scales almost linearly with the number of steps, whereas rectified flows remain fast even as network size grows. Conditional diffusion surrogates such as GenCFD generate samples by integrating a reverse-time stochastic process whose trajectory typically requires many network evaluations before reaching the target conditional law. Even with accelerated samplers, this procedure usually remains expensive because each evaluation acts only as a local refinement step. In our setting, this cost is especially significant since every network call operates on a moderate-to-high resolution spatial field.

ReFlow replaces this reverse-time stochastic sampling procedure by a deterministic *conditional transport ODE*. For a fixed input field $u_i$, we draw source noise $\xi$ and solve

$$\frac{d}{d\tau}x_\tau = v_\theta(x_\tau, \tau; u_i), \qquad x_0 = \xi,$$

returning $x_1$ as the generated sample. The computational advantage does not come from changing the conditioning information or the target conditional law, but from changing the *sampling geometry*: the learned rectified transport varies substantially less along rectification time than the stochastic diffusion trajectory, so explicit integration can be performed with far fewer evaluations.

This distinction is important. The benefit of rectified flow is not that it introduces new spatial capacity or accesses higher frequencies than diffusion at the same grid resolution. Both ReFlow and GenCFD operate

Figure 2: Inference cost versus model size. Rectified flows need 4–8 ODE steps vs. GenCFD's 64–128 SDE steps. U/Net depth varies from 4 to 8 blocks (parameters $5.5\,\mathrm{M}$ to $10.2\,\mathrm{M}$).

under the same effective spectral cutoff imposed by resolution and architecture. Rather, rectification makes the *path from source noise to conditional output law easier to integrate numerically*. In the terminology of Section 7, rectified flow improves the *discretization* term: straighter learned transports require fewer function evaluations to reach the same law-level accuracy.

The curvature-aware sampler further improves this advantage in the regime where the learned velocity becomes oscillatory along rectification time. This is particularly relevant in the OOD macro–micro setting of Section 9, where we keep the trained model fixed and vary only the numerical sampler. There, the adaptive controller suppresses high-frequency oscillations of the learned velocity and allocates smaller steps only where needed, while retaining large steps on the straight portions of the transport.

Figure 3 quantifies the practical consequence. Across model sizes, ReFlow reaches the target conditional-law accuracy regime with only 4–8 ODE steps, whereas GenCFD typically requires 64–128 stochastic denoising steps. Since each step invokes a network of comparable scale, this reduction in neural function evaluations translates directly into lower inference cost.

## 8 Experiments

### 8.1 Experimental Setup

We benchmark our method, termed henceforth as *ReFlow*, against four neural surrogate models. *GenCFD* and *GenCFD ∘ FNO* are conditional diffusion surrogates following the framework introduced earlier in this section, whereas FNO and UViT serve as one-shot deterministic baselines. Detailed descriptions of all baselines are provided in **SM** X.

**Datasets for Training and Evaluation.** We consider three canonical 2D multi-scale PDE problems (see the Supplementary Material for precise mathematical formulations and solver details):

**SL2D** *Shear Layer in 2D.* This setup models the evolution of an incompressible shear layer, initially concentrated near a horizontal interface, which rolls up into intricate vortical structures over time. We generate approximate solutions by numerically solving the 2D Navier–Stokes system (with periodic boundaries) at a resolution of $512^2$, then downsample to $128^2$ for training and testing. The data has been generated with the spectral viscosity code Tadmor (1989); Rohner & Mishra (2024).

Figure 3: Inference cost versus model size. Both ReFlow and GenCFD use comparable backbone families, but ReFlow reaches the target conditional-law accuracy regime with substantially fewer neural function evaluations. In our experiments, ReFlow typically requires 4–8 ODE steps, whereas GenCFD requires 64–128 stochastic denoising steps. U-Net depth varies from 4 to 8 blocks (roughly 5.5M to 10.2M parameters).

**CS2D** *Cloud-Shock Interaction in 2D.* In this popular compressible-flow test, a shock wave moves through a higher-density "cloud" region, triggering complex wave interactions and small-scale turbulent mixing in the wake. We solve the compressible Euler system at an effective resolution of $256^2$ using a GPU-optimized finite-volume ALSVINN code of Lye (2020); Fjordholm et al. (2020), then also downsample to $128^2$.

**RM2D** *Richtmeyer–Meshkov in 2D.* In this case, a shock wave interacts with a density interface separating two fluids, depositing vorticity and triggering vigorous mixing. We numerically solve the compressible Euler system on a $256^2$ grid, then downsample to $128^2$ to create the training and test data. The data has been generated with a high-resolution finite-volume ALSVINN code of Fjordholm et al. (2020)

**Training and Test Protocol.** We train both our proposed rectified flow-based GenCFD-class algorithm and all baseline models on initial conditions

$$u_0 \sim \mu, \quad \text{with} \quad \mu$$

being the probability distribution specified in the Supplementary Material (**SM**. T.1.3). For each $u_0$, the PDE solver (e.g. a spectral or finite-volume code) is run forward in time to produce high-fidelity snapshots, which serve as training data.

**Training and evaluation protocol.** All models are trained on paired samples

$$(u_i, u_f), \qquad u_f = \mathcal{S}_{\Delta t}(u_i),$$

where $u_i$ is the input / conditioning field and $u_f$ is the PDE state at the forecast horizon. For the probabilistic models (GenCFD and ReFlow), the goal is to learn the *conditional output law*

$$p(u_f \mid u_i),$$

rather than only a single-point prediction. During training, however, the models are only given paired realizations $(u_i, u_f)$ from the dataset; the conditional law is learned implicitly from the collection of such pairs.

*Training-objective.* Crucially, during training, the model is **only** exposed to $(u_0, u_1)$ pairs of data as opposed to the conditional measure $p(u(t)|u_0)$.

**Macro–micro evaluation and conditional laws.** Our main evaluation target is the conditional law associated with a *fixed* macroscopic input. Concretely, at test time we choose a macro/input state $\widehat{u}_i$ and aim to compare the model-generated law

$$\widehat{p}(\,\cdot\,\mid \widehat{u}_i)$$

with a reference conditional ensemble obtained from the high-fidelity PDE solver. Since the exact conditional law is not analytically available, we approximate it through a macro–micro perturbation protocol: starting from the macro state $\widehat{u}_i$, we generate many nearby microscopic perturbations, evolve each perturbed state with the PDE solver, and collect the resulting outputs into an empirical conditional ensemble. This empirical ensemble is our ground-truth approximation of the output law associated with the fixed macro condition $\widehat{u}_i$.

*Test-time goal: Dirac initial measures.* While the training distribution $\mu$ is spread out, we are especially interested in the scenario where the *initial condition is fixed and deterministic.* Formally, we set

$$\widehat{\mu}_0 = \delta_{\widehat{u}_0},$$

which is a Dirac measure concentrated at a single function $\widehat{u}_0$. Thus, any stochasticity in the resulting flow arises solely from chaotic or multi-scale evolution over time, rather than from large variations in the initial condition itself. Thus, throughout the experiments, the conditioning/input field is held fixed at the macro level, while diversity appears at the micro level through the induced spread of outputs. This is exactly the statistical object that ReFlow and GenCFD are designed to model.

To create a "ground truth" ensemble for comparison under a fixed $\widehat{u}_0$, we employ an *ensemble perturbation* procedure (detailed in **SM** T.1.3), where $\widehat{u}_0$ is slightly perturbed to generate multiple nearby initial states. Each perturbed state is then advanced using a high-resolution PDE solver (e.g. the Azeban code for incompressible flows, or a finite-volume code for compressible problems), yielding a set of flow realizations. This set approximates the conditional measure in question, i.e. $p(u(t) \mid \widehat{u}_0)$.

**Matched and shifted conditional regimes.** We report two evaluation regimes:

1. **Matched regime.** The macro/input state $\widehat{u}_i$ is drawn from the same broad family as the training inputs. This is the easier setting, although the evaluation is still conditional because the model is asked to generate an ensemble at a fixed macro condition.

2. **Shifted / OOD regime.** The macro/input state $\widehat{u}_i$ is drawn from a different family or parameter range than those seen during training. This probes whether the learned conditional sampler remains statistically faithful when queried out of distribution.

In the rebuttal-driven experiments of Section 9, the macro–micro protocol is made explicit: the model is frozen, the macro conditions are chosen in an OOD regime, and only the numerical sampler is varied. This is precisely the setting targeted by the EMA-based stabilization analysis in Section 7.5.

*Distribution settings.* We test two main configurations:

1. **Matched distribution.** We sample $\widehat{u}_0$ from the same family $\mu$ used in training. While $\delta_{\widehat{u}_0}$ is technically out-of-distribution in the sense that the training distribution was spread out over many initial states, the base function $\widehat{u}_0$ still belongs to the same general class of flows.

2. **Distribution shift.** We consider Dirac initial data $\delta_{\widehat{u}_0}$ where $\widehat{u}_0 \sim \nu$, for a *different* distribution $\nu \neq \mu$. This scenario probes the ability of our model and baselines to generalize under shifts in the initial condition distribution. Specific details on $\nu$ are provided in **SM** T.1.3.

We will show results in both regimes to assess how well rectified flows can capture the spread of chaotic solutions starting from fixed initial states–and how it compares to baselines.

**Role of deterministic baselines.** FNO and UViT are deterministic predictors and therefore do not directly define a conditional output law. To make them comparable on statistical metrics, we apply the same macro–micro perturbation protocol at the input level and aggregate their outputs across perturbed inputs into an empirical ensemble. This does *not* turn them into intrinsically probabilistic models; rather, it provides a controlled way to compare how much conditional variability they preserve under perturbations of the macro input. By contrast, ReFlow and GenCFD generate diversity intrinsically through noise sampling at fixed $u_i$.

**Training budget and architectural parity.** To keep the comparison computationally controlled, we train each model under a fixed optimization budget and report the best checkpoint achieved within that budget. Under the budgets used here, ReFlow and GenCFD are compared with matched backbone families and similar parameter counts, so the main difference is not representational scale but sampling mechanism. In particular, ReFlow's advantage should be read as a gain in *conditional-law accuracy per neural function evaluation*, rather than as a trivial consequence of larger models.

## 8.2 Evaluation Metrics

We evaluate the generative performance of each method using three main metrics, with details provided in **SM Z**: We evaluate the generative performance of each method using metrics that probe conditional-law fidelity rather than only pointwise prediction quality.

- **Mean Error.** We measure the $L^2$ difference between the model's predicted mean flow $\mu$ and the ground-truth mean $\mu_{\text{exact}}$. A low mean error indicates accurate large-scale behavior.

- **Standard Deviation Error.** The normalized $L^2$ distance between the predicted standard deviation $\sigma$ and the reference $\sigma_{\text{exact}}$ captures whether the model reproduces correct spatial variability.

- **One-Point Wasserstein Distance.** We compute an Wasserstein-1 distance at each spatial point (and average over the domain) to quantify local distributional agreement between ground truth and model outputs.

**One-point Wasserstein as a $k\!=\!1$ marginal metric.** Let $\mu$ and $\widehat{\mu}$ be laws on fields $u : D \to \mathbb{R}^m$. For each $x \in D$ define $\mu_x := (\text{ev}_x)_{\#}\mu$ and $\widehat{\mu}_x := (\text{ev}_x)_{\#}\widehat{\mu}$. Our reported metric is

$$W_1^{(1)}(\mu, \widehat{\mu}) := \int_D W_1(\mu_x, \widehat{\mu}_x)\, dx.$$

By Kantorovich–Rubinstein duality, $W_1(\mu_x, \widehat{\mu}_x) = \sup_{\text{Lip}(\varphi) \leq 1} \left| \int \varphi\, d\mu_x - \int \varphi\, d\widehat{\mu}_x \right|$, so $W_1^{(1)}$ controls the averaged discrepancy of *all* pointwise 1-Lipschitz observables. This is the precise sense in which Table 1 measures agreement of $k\!=\!1$ correlation statistics, in line with the statistical-solution viewpoint Lanthaler et al. (2021b).

**Mean error.** Let $\bar{u}_{\text{model}}$ and $\bar{u}_{\text{ref}}$ denote the empirical means of the model-generated and reference conditional ensembles for a fixed macro/input state. We report the relative $L^2$ discrepancy between these means. This measures whether the surrogate captures the large-scale conditional average correctly.

**Standard-deviation error.** Let $\sigma_{\text{model}}$ and $\sigma_{\text{ref}}$ denote the pointwise empirical standard deviations of the generated and reference conditional ensembles. We report the normalized $L^2$ discrepancy between them. This measures whether the model reproduces the correct spatial pattern and magnitude of conditional variability.

**One-point Wasserstein distance.** To compare the local output distributions themselves, we use the spatially averaged one-point Wasserstein-1 distance. Let $\mu$ and $\widehat{\mu}$ be two laws on fields $u : D \to \mathbb{R}^m$. For each spatial point $x \in D$, define the one-point marginals

$$\mu_x := (\mathrm{ev}_x)_{\#}\mu, \qquad \widehat{\mu}_x := (\mathrm{ev}_x)_{\#}\widehat{\mu}.$$

Our reported metric is

$$W_1^{(1)}(\mu, \widehat{\mu}) := \int_D W_1(\mu_x, \widehat{\mu}_x)\, dx. \tag{67}$$

By Kantorovich–Rubinstein duality, each $W_1(\mu_x, \widehat{\mu}_x)$ controls the discrepancy of all pointwise 1-Lipschitz observables at the spatial location $x$. Thus $W_1^{(1)}$ is exactly a $k = 1$ correlation-marginal metric in the statistical-solution sense Lanthaler et al. (2021b), averaged over space.

These three metrics probe complementary aspects of the conditional law:

- mean error measures whether the conditional average is correct,

- standard-deviation error measures whether the spread is correct,

- one-point Wasserstein distance measures whether the local conditional output distributions themselves are correct.

Together with the spectral diagnostics reported below, they provide a law-level view of whether a surrogate captures both large-scale structure and fine-scale conditional variability.

Table 1: Comparison of models across datasets CS2D, SL2D, and RM2D, in terms of mean relative error ($e_\mu$), standard deviation relative error ($e_\sigma$), and Wasserstein-1 distance ($W_1$). Best-performing model is colored in Blue and second-best performing model in Orange.

| Model | Metric | CS2D | | | | SL2D | | RM2D | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | $\rho$ | $m_x$ | $m_y$ | $E$ | $u_x$ | $u_y$ | $\rho$ | $m_x$ | $m_y$ | $E$ |
| ReFlow | $e_\mu$ | 0.0477 | 0.0332 | 0.041 | 0.015 | 0.034 | 0.189 | 0.018 | 0.032 | 0.020 | 0.021 |
| | $e_\sigma$ | 0.1005 | 0.072 | 0.078 | 0.0584 | 0.071 | 0.077 | 0.032 | 0.046 | 0.046 | 0.085 |
| | $W_1$ | 0.0091 | 0.0107 | 0.0124 | 0.0143 | 0.0214 | 0.0164 | 0.0033 | 0.0036 | 0.0028 | 0.0017 |
| GenCFD | $e_\mu$ | 0.0830 | 0.0619 | 0.127 | 0.0280 | 0.039 | 0.267 | 0.0049 | 0.0010 | 0.0025 | 0.0025 |
| | $e_\sigma$ | 0.195 | 0.197 | 0.244 | 0.169 | 0.092 | 0.072 | 0.0351 | 0.0254 | 0.0435 | 0.0435 |
| | $W_1$ | 0.0151 | 0.0184 | 0.0185 | 0.0247 | 0.0276 | 0.0213 | 0.0092 | 0.0016 | 0.0049 | 0.0049 |
| UViT | $e_\mu$ | 0.111 | 0.078 | 0.127 | 0.0479 | 0.233 | 0.623 | 0.070 | 0.070 | 0.071 | 0.052 |
| | $e_\sigma$ | 0.415 | 0.343 | 0.412 | 0.296 | 0.28 | 0.178 | 0.425 | 0.570 | 0.570 | 0.617 |
| | $W_1$ | 0.087 | 0.085 | 0.158 | 0.172 | 0.270 | 0.256 | 0.060 | 0.055 | 0.060 | 0.036 |
| FNO | $e_\mu$ | 0.0989 | 0.0748 | 0.0930 | 0.0383 | 0.058 | 0.408 | 0.085 | 0.070 | 0.063 | 0.067 |
| | $e_\sigma$ | 0.2573 | 0.2779 | 0.3188 | 0.2777 | 0.137 | 0.110 | 0.366 | 0.443 | 0.436 | 0.450 |
| | $W_1$ | 0.1455 | 0.1660 | 0.1879 | 0.1884 | 0.184 | 0.150 | 0.096 | 0.051 | 0.056 | 0.062 |
| GenCFD ∘ FNO | $e_\mu$ | 0.0638 | 0.0454 | 0.0603 | 0.0204 | 0.055 | 0.393 | 0.040 | 0.027 | 0.039 | 0.041 |
| | $e_\sigma$ | 0.1099 | 0.0969 | 0.1245 | 0.0974 | 0.131 | 0.100 | 0.091 | 0.075 | 0.091 | 0.090 |
| | $W_1$ | 0.0467 | 0.0534 | 0.0774 | 0.0743 | 0.166 | 0.135 | 0.0269 | 0.0158 | 0.0293 | 0.0273 |

**Baselines and Evaluation Settings.** To stay within reasonable training times for our infrastructure, we restrict the total number of training iterations up to 120,000 for each model and recorded the best achievable results. Under this budget, only a reduced-capacity GenCFD (with two downsampling stages in its U-Net backbone, versus three in Rectified Flow) can match the accuracy reported in Table 1. We also evaluated larger GenCFD variants trained for 500,000 iterations, but observed no meaningful improvement over the results shown here. Meanwhile, at inference time Rectified Flow requires only **8** denoising steps to achieve comparable or superior accuracy, whereas diffusion baselines (including GenCFD) need **128** steps, underscoring RF's efficiency in both training and sampling. FNO and UViT also require smaller models than ReFlow for optimal performance.

**Baselines and evaluation settings.** All results are reported under a fixed training budget per model, and the best checkpoint within that budget is retained. Under this budget, ReFlow is compared primarily against GenCFD as the corresponding conditional probabilistic baseline, using matched backbone families and similar parameter counts. Deterministic baselines such as FNO and UViT are included as references for one-shot prediction quality, but they should not be interpreted as intrinsically modeling the conditional output law.

At inference time, ReFlow requires only **8** rectified-flow ODE steps to reach the reported accuracy regime, whereas diffusion baselines such as GenCFD typically require **128** denoising steps. This is the central efficiency comparison of the paper: both methods target the same conditional-law prediction problem, but ReFlow reaches that regime with far fewer neural function evaluations.

For deterministic baselines, ensemble statistics are estimated by applying the macro–micro perturbation protocol at the input level and aggregating the resulting outputs. For ReFlow and GenCFD, diversity is generated intrinsically by sampling latent noise at fixed conditioning input $u_i$.

Since FNO, and UViT produce *deterministic* predictions, we approximate their spread by an *ensemble perturbation* strategy (**SM** T.1.3), where each baseline is fed slightly perturbed inputs and outputs are aggregated to form a sample set. In contrast, both the original GenCFD (baseline) and our *ReFlow* are inherently *probabilistic*, requiring no auxiliary procedure to generate diverse samples.

Figure 4: Energy-spectrum evolution for a random cloud–shock initial datum. ReFlow (blue) tracks high-wavenumber energy faster and more accurately than GenCFD (red).

## 8.3 Results.

Table 1 compares five surrogate models (ReFlow, together with the four baselines) on the three PDEs learning tasks using the mean error ($e_\mu$), spread error or *standard deviation* ($e_\sigma$) and the distribution-level Wasserstein-1 distance ($W_1$). On the cloud–shock and shear-layer datasets (CS2D, SL2D) the rectified-flow model (ReFlow) attains the lowest values on all three metrics, indicating that its samples most closely match both the mean behaviour and the higher-order statistics of the ground truth. The hybrid *GenCFD∘FNO* reduces the gap to ReFlow relative to its GenCFD component, but still records noticeably larger errors, whereas the one-shot deterministic baselines (FNO, UViT) show the largest deviations, especially in $e_\sigma$ and

Figure 5: Density trajectories for Sample 1: ReFlow (top) versus GenCFD (bottom).

$W_1$, confirming their difficulty in capturing output variability. RM2D is the only benchmark whose test set remains strictly in-distribution (in the sense defined earlier). Under this easier regime the deterministic baselines come closest to the conditional-diffusion surrogates, but only here. Their drop-off on the out-of-distribution tasks underscores the stronger generalisation of conditional diffusion models. Under identical training budgets, ReFlow achieves lower errors on CS2D and SL2D compared to all baselines, including GenCFD with the same architecture and model size. This highlights ReFlow's superior convergence efficiency despite parity in model capacity and training iterations.

Moreover as visualized in the **SM**, ReFlow generates samples of very high quality, matching the qualitative features of the ground truth and capturing features such as (interacting) vortices as well as propagating shock waves very accurately. Another aspect where ReFlow really shines in being able to generate the correct point pdfs. Although already indicated in the very low 1-point Wasserstein distance errors from Table 1, we present 1-point pdfs in the **SM** to illustrate this observation.

Another key indicator of the quality of approximation of multiscale PDE solutions is the energy spectrum Molinaro et al. (2024). In Figure 22, we plot the (log) spectra for the energy variable of a randomly chosen Cloud Shock initial datum at four different Diffusion times, $\tau \in \{0.25, 0.50, 0.75, 1.00\}$ to observe that i) the solution is indeed highly multiscale, with spectra decaying as a power law over a range of frequencies ii) ReFloW approximates the spectra accurately within a few (5) steps and iii) on the other hand, for these few steps in solving the underlying reverse SDE, a score-based Diffusion model such as GenCFD, struggles to approximate the relevant small scales. It will require much more sampling steps to do so. These results also showcase how ReFlow is able to infer the correct statistical solutions with significantly less ODE solve steps and is hence, much faster, than a diffusion based model such as GenCFD. This gain in inference speed is also reinforced from Figure 5, where we compare ReFlow (RF) and GenCFD reconstructions of the density field $\rho$ for the Cloud-Shock interaction over five diffusion times $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. We see that ReFlow inpaints fine-scale features in far fewer steps, whereas GenCFD remains visibly much more noisy at these small number of steps. See **SM** Z.9 for further visualizations of this effect.

## 9 Additional empirical analysis (integrators, robustness, and diversity)

This section consolidates additional experiments conducted in response to reviewer requests, with the goal of making the computational trade-offs and the role of the curvature-aware controller explicit. The emphasis is on (i) solver choices for the learned rectified-flow ODE, (ii) robustness of the controller to its hyperparameters, and (iii) distributional fidelity / diversity under the macro–micro evaluation protocol. This section consolidates additional experiments conducted with the goal of making the computational trade-offs and the role of the curvature-aware controller explicit. The emphasis is on (i) solver choices for the learned rectified-flow ODE, (ii) robustness of the controller to its hyperparameters, and (iii) distributional fidelity / diversity under the macro–micro evaluation protocol.

Table 2: **Fixed-step ODE integrators** at sampling time (ShearLayer2D, OOD macro–micro; 10 macros $\times$ 20 micros). We fix the trained rectified-flow model and vary only the integrator. NFE is the number of velocity evaluations; lower is faster. Cost$\times$Err is defined in (69).

| Method | Avg. NFE $\downarrow$ | Rel. $L^2$ Error $\downarrow$ (mean $\pm$ std) | Cost$\times$Err $\downarrow$ |
|---|---|---|---|
| Model-Baseline (built-in sampler) | 32.0 | $0.2533 \pm 0.0382$ | 8.11 |
| `torchdiffeq` Midpoint | 32.0 | $0.2533 \pm 0.0382$ | 8.11 |
| Euler (16 steps) | 16.0 | $0.2489 \pm 0.0371$ | 3.98 |
| RK2 (16 steps; 32 NFEs) | 32.0 | $0.2533 \pm 0.0379$ | 8.11 |
| RK4 (16 steps; 64 NFEs) | 64.0 | $0.2540 \pm 0.0381$ | 16.26 |

### 9.1 Protocol recap: macro–micro ensembles, OOD macros, and metrics

**Macro–micro conditional ensembles.** To evaluate *statistical fidelity* rather than only pointwise accuracy, we follow a macro–micro protocol. For each dataset, we select $N_{\text{macro}}$ macroscopic states ("macros") and for each macro generate $N_{\text{micro}}$ microscopic perturbations ("micros") yielding a reference ensemble of size $N_{\text{macro}} \times N_{\text{micro}}$. This makes diversity concrete: for each fixed macro, the ground-truth solver produces an empirical conditional distribution over micros, and the model produces its own empirical conditional distribution. We compare these distributions directly via Wasserstein distances (below), which is the relevant question for statistical surrogates.

**OOD macro selection.** Unless otherwise stated, we report results in an out-of-distribution (OOD) regime by choosing $N_{\text{macro}} = 10$ macros from shifted initial-condition families / parameter ranges, and $N_{\text{micro}} = 20$ micros per macro (200 conditional samples per dataset). All models are frozen; only the sampling/integration procedure is varied.

**Metrics.** We report: (i) *relative $L^2$ error* against the PDE solution,

$$\text{Rel-}L^2(\widehat{u}, u) := \frac{\|\widehat{u} - u\|_{L^2}}{\|u\|_{L^2}}, \tag{68}$$

(ii) *NFE* (neural function evaluations), i.e. the number of velocity-field evaluations per generated sample, and (iii) a combined cost–accuracy scalar

$$\text{Cost} \times \text{Err} := (\text{Rel-}L^2) \times (\text{NFE}), \tag{69}$$

which is convenient for summarizing the NFE–error plane (lower is better). Distributional fidelity is measured via empirical $W_1$ between conditional ensembles; we report both aggregated and per-variable $W_1$ (Section 9.5).

### 9.2 Integrator study at sampling time: fixed-step baselines vs. curvature-aware control

A recurring concern is whether the gains are merely a consequence of choosing a particular numerical solver. To isolate this, we fix the trained rectified-flow model and vary *only* the integrator used to solve the rectified-flow ODE at sampling time, starting from noise and integrating from rectified time $\tau = 0$ to $\tau = 1$. We include a reference implementation from `torchdiffeq` and standard explicit fixed-step schemes. We report the aggregated results on *ShearLayer2D* in the OOD macro–micro regime; the second benchmark exhibits the same qualitative trends and is reported in the appendix.

**Observation: Euler has a tuned "sweet spot" but remains brittle.** Among fixed-step schemes, Euler with 16 steps is the strongest baseline in this regime, improving on 32/64-NFE schemes in Cost$\times$Err. However, in multiscale mildly stiff regimes, fixed-step performance is highly sensitive to the chosen step budget: slightly fewer steps can degrade accuracy sharply, while increasing steps can *also* worsen error due to accumulated discretization bias along curved trajectories. Thus, even simple Euler is not a drop-in robust choice: it requires per-dataset/per-regime tuning to hit its efficient operating point.

Table 3: **Hyperparameter robustness** of the curvature-aware adaptive sampler (ShearLayer2D, OOD macro–micro). Across 20 controller configurations, Avg. NFE stays in a narrow band and relative errors vary by $< 1\%$, indicating the controller is not brittle and does not rely on a narrow tuning "sweet spot".

| Config | Avg. NFE $\downarrow$ | Rel. $L^2$ Error $\downarrow$ (mean $\pm$ std) | Cost$\times$Err $\downarrow$ |
|---|---|---|---|
| baseline | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| **ema_0.25** | **10.7** | **$0.2369 \pm 0.0386$** | **2.54** |
| ema_0.45 | 11.3 | $0.2361 \pm 0.0384$ | 2.67 |
| alpha_0.05 | 11.0 | $0.2373 \pm 0.0389$ | 2.62 |
| alpha_0.12 | 11.0 | $0.2373 \pm 0.0389$ | 2.62 |
| alpha_0.20 | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| gamma_1.5 | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| gamma_2.0 | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| gamma_2.5 | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| gate_0.50 | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| gate_0.70 | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| calib_0.70_0.90 | 11.1 | $0.2371 \pm 0.0387$ | 2.63 |
| calib_0.80_0.98 | 10.9 | $0.2372 \pm 0.0387$ | 2.60 |
| adapt_1.5_0.75 | 12.8 | $0.2374 \pm 0.0378$ | 3.04 |
| adapt_2.0_0.85 | 11.2 | $0.2360 \pm 0.0376$ | 2.63 |
| no_ortho_filter | 11.0 | $0.2374 \pm 0.0389$ | 2.62 |
| damp_0.05 | 11.0 | $0.2373 \pm 0.0389$ | 2.62 |
| damp_0.10 | 11.0 | $0.2373 \pm 0.0389$ | 2.61 |
| damp_0.20 | 11.0 | $0.2370 \pm 0.0389$ | 2.60 |
| damp_0.30 | 11.0 | $0.2368 \pm 0.0389$ | 2.60 |

### 9.3 Curvature-aware sampler: hyperparameter robustness and Pareto dominance

We next evaluate the curvature-based adaptive controller under a broad sweep of hyperparameters while holding the model fixed. The controller uses (i) an EMA-based straightness/curvature proxy on the learned velocity field, (ii) a mild velocity regularization/blending step triggered by curvature, and (iii) adaptive step sizing. We vary EMA time scale, thresholds, gating, damping, and calibration parameters across 20 configurations.

**Observation: robust controller, automatic step allocation.** Across all 20 configurations, Avg. NFE remains in a tight range (10.7–12.8) and the mean relative error stays within $[0.2360, 0.2374]$ (sub-1% relative variation), indicating that the controller does not require fragile tuning. This directly contrasts with fixed-step Euler, where efficiency is achieved only at a tuned step budget and can degrade rapidly outside it.

### 9.4 Best fixed-step baseline vs. best adaptive configurations

For clarity, Table 4 compares the strongest fixed-step baseline (Euler-16) against the top adaptive configurations on ShearLayer2D OOD.

**Interpretation in the NFE–error plane.** These comparisons summarize a consistent pattern: the adaptive curvature-aware sampler lies on (or very near) the Pareto frontier in the NFE–error plane, while fixed-step baselines are strictly dominated in the regimes tested. This is the practical meaning of the curvature theory: the controller allocates steps only where the learned transport bends, while retaining large steps when the flow is straight.

Table 4: **Best fixed-step baseline vs. top adaptive configs** (ShearLayer2D, OOD macro–micro). At roughly one third fewer velocity evaluations, the adaptive sampler improves both error and Cost×Err.

| Method / Config | Avg. NFE | Rel. $L^2$ Err | Cost×Err | $\Delta$NFE vs Euler | $\Delta$Err vs Euler | $\Delta$(Cost×Err) |
|---|---|---|---|---|---|---|
| **Euler (16 steps)** | 16.0 | 0.2489 | 3.98 | $0\%$ | $0\%$ | $0\%$ |
| **ema_0.25** | 10.7 | 0.2369 | 2.54 | $-33.1\%$ | $-4.8\%$ | $-36.2\%$ |
| calib_0.80_0.98 | 10.9 | 0.2372 | 2.60 | $-31.9\%$ | $-4.7\%$ | $-34.7\%$ |
| damp_0.30 | 11.0 | 0.2368 | 2.60 | $-31.3\%$ | $-4.9\%$ | $-34.7\%$ |

### 9.5 Distributional fidelity and diversity: ensemble $W_1$ under macro–micro evaluation

A common concern for deterministic probability-flow ODE sampling is potential under-dispersion or reduced diversity. Our evaluation is designed to test this directly in the conditional setting where diversity is well-defined.

**Empirical $W_1$ between conditional ensembles.** For each macro, let $\{\widehat{u}^{(j)}\}_{j=1}^{N_{\mathrm{micro}}}$ be model samples and $\{u^{(j)}\}_{j=1}^{N_{\mathrm{micro}}}$ be reference samples. We compute a one-point (spatially averaged) empirical $W_1$ between the corresponding micro-ensembles, and then average across macros. We also report per-variable $W_1$ (density, momenta, energy) and an aggregated score.

**Key empirical outcome.** Across benchmarks, our rectified-flow model matches or improves upon the diffusion baseline in ensemble $W_1$ while using substantially fewer function evaluations. In particular, the macro–micro protocol provides a direct quantitative check against mode collapse: matching $W_1$ at fixed macro conditions indicates that the conditional output distribution is captured rather than collapsed. (Complete per-variable $W_1$ tables and additional datasets are reported in the appendix.)

### 9.6 Practical takeaway: speed requires both straight transports and curvature-aware integration

The integrator study separates two effects: (i) the rectified-flow training objective yields a transport that can be traversed with far fewer evaluations than score-based diffusion, and (ii) within this ODE setting, curvature-aware control is a robust way to realize the efficiency in stiff multiscale regimes without per-problem solver tuning. Empirically, this is exactly what Tables 2–4 show: the controller achieves lower error at lower NFE than the strongest tuned fixed-step baseline, and its performance is stable across wide hyperparameter ranges.

**Appendix pointers.** We provide: (a) the same integrator/robustness tables on the second benchmark, (b) NFE–error scatter plots (Pareto frontiers), and (c) detailed per-variable $W_1$ breakdowns and additional OOD regimes.

## 10 Conclusion and Future Work

We have demonstrated that rectified flows provide an efficient surrogate for sampling multi-scale PDE solutions: on a suite of challenging incompressible and compressible problems, our method matches the statistical fidelity of conditional diffusion models while requiring an order of magnitude fewer solver steps—yielding up to 22× faster inference in practice. Across matched and shifted initial-condition regimes, rectified flows consistently reproduce energy spectra, vorticity distributions, and one-point Wasserstein distances within sampling error, confirming their robustness and multi-scale accuracy.

**Key Takeaways.** On account of its straightening bias, ReFlow requires significantly fewer ODE steps at inference-time (8-10) than its conditional-diffusion-based counterparts (more than 128) to achieve the same level of performance on our statistical metrics – consult **SM Z** for more details. Furthermore, ReFlow is much more training efficient, requiring up to 120,000 iterations in reaching the same level of performance, across

all experiments, as our other conditional diffusion baselines (which typically take 500-600,000 iterations), see **SM** Z.8. Our results further demonstrate that straightening effects remain evident even when projecting down to a 2D PCA subspace (see **SM** Z.9).

## References

Lemar Abdi, Francisco Caetano, Amaan Valiuddin, Christiaan Viviers, Hamdi Joudeh, and Fons van der Sommen. Out-of-distribution detection in medical imaging via diffusion trajectories. In *International Workshop on Uncertainty for Safe Utilization of Machine Learning in Medical Imaging*, pp. 91–101. Springer, 2025a.

Lemar Abdi, Amaan Valiuddin, Francisco Caetano, Christiaan Viviers, and Fons Van Der Sommen. Zero-shot image anomaly detection using generative foundation models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3554–3563, 2025b.

Benedikt Alkin, Andreas Fürst, Simon Lucas Schmid, Lukas Gruber, Markus Holzleitner, and Johannes Brandstetter. Universal physics transformers: A framework for efficiently scaling neural operators. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=oUXiNX5KRm.

Brett Barkley, Preston Culbertson, and David Fridovich-Keil. Scoped: Score-curvature out-of-distribution proximity evaluator for diffusion. *arXiv preprint arXiv:2510.01456*, 2025.

Patrick Esser, Sumith Kulal, Andreas Blattmann, Rahim Entezari, Jonas Müller, Harry Saini, Yam Levi, Dominik Lorenz, Axel Sauer, Frederic Boesel, et al. Scaling rectified flow transformers for high-resolution image synthesis. In *Forty-first international conference on machine learning*, 2024.

L.C. Evans. *Partial Differential Equations*. Graduate studies in mathematics. American Mathematical Society, 2010. ISBN 9780821849743. URL https://books.google.ch/books?id=Xnu0o_EJrCQC.

Ulrik S. Fjordholm, Samuel Lanthaler, and Siddhartha Mishra. Statistical solutions of hyperbolic conservation laws: Foundations. *Archive for Rational Mechanics and Analysis*, 226(2):809–849, Nov 2017. ISSN 1432-0673. doi: 10.1007/s00205-017-1145-9. URL https://doi.org/10.1007/s00205-017-1145-9.

Ulrik S. Fjordholm, Kjetil O. Lye, Siddhartha Mishra, and Franziska Weber. Statistical solutions of hyperbolic systems of conservation law: Numerical approximation. *Mathematical Models and Methods in Applied Sciences*, 30(3):539–609, 2020. doi: 10.1142/S0218202520500141.

Han Gao, Xu Han, Xiantao Fan, Luning Sun, Li-Ping Liu, Lian Duan, and Jian-Xun Wang. Bayesian conditional diffusion models for versatile spatiotemporal turbulence generation. *Computer Methods in Applied Mechanics and Engineering*, 427:117023, 2024a.

Han Gao, Sebastian Kaltenbach, and Petros Koumoutsakos. Generative learning for forecasting the dynamics of complex systems. *arXiv preprint arXiv:2402.17157*, 2024b.

Han Gao, Sebastian Kaltenbach, and Petros Koumoutsakos. Generative learning of the solution of parametric partial differential equations using guided diffusion models and virtual observations. *arXiv preprint arXiv:2408.00157*, 2024c.

Zhongkai Hao, Zhengyi Wang, Hang Su, Chengyang Ying, Yinpeng Dong, Songming Liu, Ze Cheng, Jian Song, and Jun Zhu. Gnot: A general neural operator transformer for operator learning. In *International Conference on Machine Learning*, pp. 12556–12569. PMLR, 2023.

Alvin Heng, Alexandre H Thiery, and Harold Soh. Out-of-distribution detection with a single unconditional diffusion model. *Advances in Neural Information Processing Systems*, 37:43952–43974, 2024.

Maximilian Herde, Bogdan Raonic, Tobias Rohner, Roger Käppeli, Roberto Molinaro, Emmanuel de Bézenac, and Siddhartha Mishra. Poseidon: Efficient foundation models for pdes. *Advances in Neural Information Processing Systems*, 37:72525–72624, 2024.

Nikola Kovachki, Zongyi Li, Burigede Liu, Kamyar Azizzadenesheli, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Neural operator: Learning maps between function spaces with applications to pdes. *Journal of Machine Learning Research*, 24(89):1–97, 2023.

Samuel Lanthaler, Siddhartha Mishra, and Carlos Parés-Pulido. Statistical solutions of the incompressible euler equations. *Mathematical Models and Methods in Applied Sciences*, 31(02):223–292, 2021a.

Samuel Lanthaler, Siddhartha Mishra, and Carlos Parés-Pulido. Statistical solutions of the incompressible euler equations. *Mathematical Models and Methods in Applied Sciences*, 31(02):223–292, 2021b.

Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Fourier neural operator for parametric partial differential equations. *arXiv preprint arXiv:2010.08895*, 2020a.

Zongyi Li, Nikola Kovachki, Kamyar Azizzadenesheli, Burigede Liu, Kaushik Bhattacharya, Andrew Stuart, and Anima Anandkumar. Neural operator: Graph kernel network for partial differential equations. *arXiv preprint arXiv:2003.03485*, 2020b.

Zongyi Li, Nikola Borislavov Kovachki, Chris Choy, Boyi Li, Jean Kossaifi, Shourya Prakash Otta, Mohammad Amin Nabian, Maximilian Stadler, Christian Hundt, Kamyar Azizzadenesheli, and Anima Anandkumar. Geometry-informed neural operator for large-scale 3d PDEs. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=86dXbqT5Ua.

Xingchao Liu, Chengyue Gong, and Qiang Liu. Flow straight and fast: Learning to generate and transfer data with rectified flow. *arXiv preprint arXiv:2209.03003*, 2022.

Lu Lu, Pengzhan Jin, Guofei Pang, Zhongqiang Zhang, and George Em Karniadakis. Learning nonlinear operators via DeepONet based on the universal approximation theorem of operators. *Nature Machine Intelligence*, 3(3):218–229, 2021.

Kjetil O. Lye. *Computation of statistical solutions of hyperbolic systems of conservation laws*. PhD thesis, 2020.

Siddhartha Mishra and Alex (Eds.) Townsend. *Numerical Analysis meets Machine Learning*. Handbook of Numerical Analysis. Springer, 2024.

Roberto Molinaro, Samuel Lanthaler, Bogdan Raonić, Tobias Rohner, Victor Armegioiu, Zhong Yi Wan, Fei Sha, Siddhartha Mishra, and Leonardo Zepeda-Núñez. Generative ai for fast and accurate statistical computation of fluids. *arXiv preprint arXiv:2409.18359*, 2024.

V Oommen, A Bora, Z Zhang, and GE Karniadakis. Integrating neural operators with diffusion models improves spectral representation in turbulence modeling. arxiv, 2024.

A. Quarteroni and A. Valli. *Numerical approximation of Partial differential equations*, volume 23. Springer, 1994.

Alfio Quarteroni, Andrea Manzoni, and Federico Negri. *Reduced basis methods for partial differential equations: an introduction*, volume 92. Springer, 2015.

Tobias Rohner and Siddhartha Mishra. Efficient computation of large-scale statistical solutions to incompressible fluid flows. In *Proceedings of the Platform for Advanced Scientific Computing Conference*, PASC '24. ACM, June 2024. doi: 10.1145/3659914.3659922. URL http://dx.doi.org/10.1145/3659914.3659922.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily L Denton, Kamyar Ghasemipour, Raphael Gontijo Lopes, Burcu Karagol Ayan, Tim Salimans, et al. Photorealistic text-to-image diffusion models with deep language understanding. *Advances in neural information processing systems*, 35:36479–36494, 2022.

Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*, 2020.

Eitan Tadmor. Convergence of spectral methods for nonlinear conservation laws. *SIAM Journal on Numerical Analysis*, 26(1):30–44, 1989. doi: 10.1137/0726003. URL https://doi.org/10.1137/0726003.

Haixu Wu, Huakun Luo, Haowen Wang, Jianmin Wang, and Mingsheng Long. Transolver: A fast transformer solver for PDEs on general geometries. In *Forty-first International Conference on Machine Learning*, 2024. URL https://openreview.net/forum?id=Ywl6pODXjB.

# A    Theory appendix: law-level rectified flows for multiscale CFD

# B    Theory appendix: conditional rectified flows for multiscale PDE surrogates

**Purpose and scope.**    This appendix provides the mathematical backbone for the claims made in the main text: (i) rectified flows can match the same conditional solution laws as diffusion-class models, (ii) their *sampling step count* is governed by a *curvature/straightness* quantity rather than by the raw dimensionality of the state, and (iii) at fixed spatial resolution, there is an *irreducible* law-level error dictated by the small-scale tail of the true PDE law, which is naturally quantified through structure functions. We keep the presentation self-contained, and we explicitly connect each theoretical ingredient to the empirical evaluations in Table 1 and to the spectral diagnostics in Figure 22 (and supplementary figures).

**How to read this appendix.**    Section E fixes the measure-theoretic setting and links it to statistical solutions in the sense of Lanthaler et al. (2021b) (also used in the Introduction). Section F shows that the *barycentric rectified velocity* exactly transports $\mu_0$ to $\mu_1$ (correctness at the level of laws). Section G gives a *terminal error decomposition* into a fit term and a straightness term and explains how the training objective controls these terms. Section J derives why curvature controls the required number of ODE steps and motivates the EMA-based curvature proxy and the blending correction used at inference. Section M links the *energy spectrum / structure functions* to an unavoidable *coverage* term at fixed cutoff $K_c$. Finally, Section R aggregates the pieces into a master law-level bound that matches the narrative in the abstract and in the theory paragraphs of the main paper.

# C    Setup: laws of PDE solutions and what the experiments measure

**State space.**    We work on the periodic domain $\mathcal{D} = \mathbb{T}^d$ and consider (for notational simplicity) scalar or vector fields $u : \mathcal{D} \to \mathbb{R}^m$ represented on a finite grid. The natural infinite-dimensional space for the fluid benchmarks is

$$\mathcal{H} := L^2_\sigma(\mathcal{D}; \mathbb{R}^d) \quad \text{(divergence-free in the incompressible case)},$$

or $\mathcal{H} := L^2(\mathcal{D}; \mathbb{R}^m)$ for compressible state vectors (e.g. $(\rho, m_x, m_y, E)$). All constructions below are rigorous on the finite-dimensional Galerkin/grid surrogate $\mathbb{R}^{d_N} \subset \mathcal{H}$ used in training and evaluation. We state results in $\mathcal{H}$ language to highlight the measure-theoretic meaning.

**Statistical solutions and correlation viewpoint.**    In strongly nonlinear regimes, it is natural to treat the PDE solution as a *random field*. Given a law $\mu_0 \in \mathcal{P}(\mathcal{H})$ for the initial condition, the law at time $t$ is

$$\mu_t = (\mathcal{S}^t)_\# \mu_0,$$

where $\mathcal{S}^t$ is the PDE solution operator (possibly multivalued in the inviscid setting; see Lanthaler et al. (2021b) for the correlation hierarchy framework). This is precisely the "statistical solution" language used in the Introduction.

**What we evaluate empirically.**    Our quantitative evaluation (Section 8.2) uses: (i) errors of the mean and standard deviation fields, and (ii) a pointwise Wasserstein-1 discrepancy averaged over space. These are *marginal* discrepancies: they test whether low-order statistics and one-point laws match between the model and the PDE ensemble.

From a law-level perspective, a natural global metric is $W_2$ on $\mathcal{P}(\mathcal{H})$. Although our reported metric is $W_1$ on one-point marginals (for computational reasons), the theory below uses $W_2$ because (a) it interacts cleanly with $L^2$-based structure functions and Fourier tails, and (b) it yields transparent decompositions. We emphasize that the core mechanisms (coverage/fit/straightness/discretization) are *metric-agnostic*: they explain why a method that reduces curvature reaches good statistics with fewer steps, which is exactly what is observed in Table 1 and Figure 22.

# D   Rectified-flow correctness: barycentric velocity transports laws

## D.1   Couplings and linear interpolation in rectification time

Let $\mu_0, \mu_1 \in \mathcal{P}(\mathcal{H})$ be two laws (in our application: conditional laws of PDE outputs given inputs; see Section 5.1). Fix a coupling $\gamma \in \mathcal{P}(\mathcal{H} \times \mathcal{H})$ of $(\mu_0, \mu_1)$, i.e. $(\pi_0)_{\#}\gamma = \mu_0$ and $(\pi_1)_{\#}\gamma = \mu_1$.

For $\tau \in [0, 1]$ define the interpolation map

$$T_\tau(u_0, u_1) := (1 - \tau)u_0 + \tau u_1, \qquad \rho_\tau := (T_\tau)_{\#}\gamma.$$

Thus $\rho_\tau$ is the law of the random variable $U_\tau = (1 - \tau)U_0 + \tau U_1$ when $(U_0, U_1) \sim \gamma$.

## D.2   Barycentric rectified velocity and the continuity equation

**Purpose and scope.**   This appendix provides the mathematical backbone for the theory statements made in the main text. The key points are the following.

**Definition D.1** (Barycentric rectified velocity)**.** For each $\tau \in [0, 1]$ and $\rho_\tau$-a.e. $u$, define

$$v_\star(u, \tau) := \mathbb{E}\big[U_1 - U_0 \,\big|\, U_\tau = u\big].$$

Equivalently, $v_\star$ is obtained by disintegrating $\gamma$ along the fibers $T_\tau^{-1}(u)$, as in equation 4 in the main text.

**Why this is the "right" velocity.**   If we think of $\rho_\tau$ as mass moving from $\rho_0 = \mu_0$ to $\rho_1 = \mu_1$ in rectification time, then the pair $(\rho_\tau, v_\star)$ solves the continuity equation

$$\partial_\tau \rho_\tau + \nabla \cdot (\rho_\tau v_\star(\cdot, \tau)) = 0 \quad \text{(on the finite-dimensional surrogate)}.$$

This is the deterministic analogue of the probability-flow (ODE) viewpoint of diffusion models: the flow map of $v_\star$ pushes $\rho_0$ to $\rho_1$.

1. Our model is a *conditional noise-to-solution rectified flow*: for a fixed input field $u_i$, it transports a simple reference sample $\xi$ to a sample from the conditional output law of the PDE.

2. The ideal conditional barycentric rectified velocity is *correct at the level of laws*: its flow maps the reference law exactly to the target conditional law.

3. Once the effective spatial resolution is fixed, the total conditional-law error splits into three distinct pieces:
   $$\text{coverage} + \text{fit} + \text{discretization}.$$
   Here coverage is an irreducible finite-resolution floor, fit measures approximation of the ideal conditional transport field by the learned neural field, and discretization measures the error incurred by numerically integrating the learned ODE.

4. The EMA/blending mechanism used in our sampler is *not* part of generic correctness. It is an additional stabilization device for the *OOD sampling regime*, where the learned velocity develops oscillatory errors along rectification time.

**How to read this appendix.**   Section E fixes the conditional law-level setting and clarifies what the experiments probe. Section F states the exact conditional transport result for the ideal barycentric rectified velocity and the $L^2$ projection property targeted by the training loss. Section I gives the continuous-time fit theorem for the learned conditional flow. Section J derives the discretization bounds and identifies the total derivative along trajectories as the relevant straightness quantity. Section K gives a separate OOD stabilization result for the EMA-blended sampler. Section M quantifies the finite-resolution coverage floor through structure functions and Fourier tails. Finally, Section R aggregates the pieces into the master law-level bound used in the main text, and Section S explains how this law-level viewpoint relates to the reported one-point metrics.

## E    Setup: conditional laws of PDE outputs and what the experiments measure

**State space and finite-dimensional surrogate.**   We work on the periodic domain $\mathcal{D} = \mathbb{T}^d$ and consider state fields taking values in
$$\mathcal{U} = L^2(\mathcal{D}; \mathbb{R}^m),$$
or, in the incompressible case, in the divergence-free subspace when appropriate. In the actual implementation all fields are represented on a finite-dimensional grid / Galerkin discretization
$$\mathbb{R}^{d_N} \subset \mathcal{U}.$$

All arguments below are rigorous in that finite-dimensional setting; the Hilbert-space notation is retained because it matches the law-level viewpoint of statistical solutions.

**Conditional target laws.**   Let $C$ denote the conditioning variable, which in our applications is the input field $u_i$ (possibly together with boundary data or other known parameters). For a fixed realization $c$ of $C$, let
$$\mu_1^c := \mathrm{Law}(U_f \mid C = c)$$
be the conditional law of the PDE output at the forecast horizon. Let
$$\pi_0^c$$
be a simple reference law on $\mathcal{U}$; in the experiments we take $\pi_0^c = \mathcal{N}(0, I)$, independent of $c$.

**Finite-resolution target law.**   At an effective cutoff $K_c$, the best law a bandlimited surrogate can hope to match is not the full conditional law $\mu_1^c$ but its projected version
$$\bar{\mu}_1^c := (P_{\leq K_c})_\# \mu_1^c. \tag{70}$$

Accordingly, the exact conditional transport result below is stated for a generic target conditional law $\nu^c$, and in the finite-resolution master theorem we apply it with
$$\nu^c = \bar{\mu}_1^c.$$

**What the experiments probe.**   Our empirical evaluation is conditional. At test time, a macro/input state $\widehat{u}_i$ is fixed, and both the model and the reference PDE solver are used to generate ensembles of outputs associated with that fixed macro condition. The reported statistics—mean error, spread error, and one-point Wasserstein distance—therefore probe whether the model reproduces the *conditional law* of outputs at fixed input, rather than only an unconditional average across inputs.

**Law-level versus marginal viewpoints.**   From the abstract measure-theoretic perspective, a natural global metric on output laws is Wasserstein distance on $\mathcal{U}$, especially $W_2$ because it interacts cleanly with $L^2$-based structure functions and Fourier tails. The experiments report one-point $W_1$ averaged over space because it is computationally accessible and directly interpretable in terms of $k = 1$ correlation marginals. The mechanisms isolated below—coverage, fit, and discretization—are not specific to one particular metric; they explain why a learned transport that is accurate and easy to integrate can match the relevant output statistics with few function evaluations.

## F    Exact conditional transport under the barycentric rectified velocity

### F.1    Conditional couplings and rectified interpolation

Fix a condition $c$. Let
$$\pi_0^c, \nu^c \in \mathcal{P}(\mathcal{U})$$

be a source/reference conditional law and a target conditional law, and let

$$\gamma^c \in \mathcal{P}(\mathcal{U} \times \mathcal{U})$$

be any coupling of $(\pi_0^c, \nu^c)$. Write

$$(\Xi, Y) \sim \gamma^c,$$

where $\Xi$ is the source sample and $Y$ is the target sample.

For $\tau \in [0, 1]$, define the linear rectified interpolation

$$U_\tau := (1 - \tau)\Xi + \tau Y, \qquad \rho_\tau^c := \mathrm{Law}(U_\tau \mid C = c). \tag{71}$$

Thus $\rho_\tau^c$ is the conditional law of intermediate states obtained by moving linearly from the source sample $\Xi$ to the target sample $Y$.

### F.2 Conditional barycentric velocity

**Proposition F.1** (Exact transport under the barycentric velocity). *Assume we work on a finite-dimensional surrogate of $\mathcal{H}$ so that $u \in \mathbb{R}^{d_N}$ and $\rho_\tau$ admits a density (or, more generally, is a narrowly continuous curve of measures). Let $X_\tau$ be the (classical) flow map solving*

$$\frac{d}{d\tau} X_\tau(u) = v_\star(X_\tau(u), \tau), \qquad X_0(u) = u.$$

*Then $(X_\tau)_{\#}\mu_0 = \rho_\tau$ for all $\tau \in [0, 1]$, and in particular $(X_1)_{\#}\mu_0 = \mu_1$.*

*Proof.* Let $(U_0, U_1) \sim \gamma$ and define $U_\tau = (1 - \tau)U_0 + \tau U_1$ so that $\mathrm{Law}(U_\tau) = \rho_\tau$. Fix $\varphi \in C_c^\infty(\mathbb{R}^{d_N})$. By differentiating under the expectation,

$$\frac{d}{d\tau} \mathbb{E}[\varphi(U_\tau)] = \mathbb{E}\big[\nabla\varphi(U_\tau) \cdot (U_1 - U_0)\big].$$

Condition on $U_\tau$ and use Definition G.1:

$$\mathbb{E}\big[\nabla\varphi(U_\tau) \cdot (U_1 - U_0)\big] = \mathbb{E}\big[\nabla\varphi(U_\tau) \cdot \mathbb{E}[U_1 - U_0 \mid U_\tau]\big] = \mathbb{E}\big[\nabla\varphi(U_\tau) \cdot v_\star(U_\tau, \tau)\big].$$

Thus $\rho_\tau$ satisfies the weak continuity equation

$$\frac{d}{d\tau} \int \varphi(u)\, \rho_\tau(du) = \int \nabla\varphi(u) \cdot v_\star(u, \tau)\, \rho_\tau(du).$$

On the other hand, the pushforward curve $\tilde{\rho}_\tau := (X_\tau)_{\#}\rho_0$ satisfies the same weak equation by standard characteristics. Uniqueness of solutions to the continuity equation on $\mathbb{R}^{d_N}$ (under the regularity ensuring existence of $X_\tau$) yields $\rho_\tau = \tilde{\rho}_\tau$, hence $(X_1)_{\#}\mu_0 = \mu_1$. $\qquad\square$

**Empirical tie.** Correctness in Proposition G.3 is a law-level statement: it says that if a learned velocity $v_\theta$ matches $v_\star$, then integrating the ODE recovers the target law. This is what is tested empirically through mean/spread/Wasserstein statistics (Table 1) and through the evolution of multiscale spectra along $\tau$ (Figure 22).

## G Continuous-time error decomposition: fit vs. straightness

### G.1 The training objective targets the barycentric velocity

In the (unconditional) rectified-flow construction, minimizing

$$\int_0^1 \mathbb{E}\big[\|(U_1 - U_0) - v(U_\tau, \tau)\|^2\big]\, d\tau$$

over measurable $v$ yields the conditional expectation $v_\star(u, \tau) = \mathbb{E}[U_1 - U_0 \mid U_\tau = u]$. In the conditional PDE setting we use the same principle but with $(U_0, U_1)$ sampled from the conditional pairing induced by the dataset and conditioning variables (initial/boundary data). This explains why the regression loss in Algorithm 5.5.3 is the natural analogue of score matching: it is an $L^2$ projection onto the optimal transport direction at each $\tau$.

## G.2 Terminal error bound with explicit decomposition

Let $u_\tau$ solve the ideal rectified ODE $\dot{u}_\tau = v_\star(u_\tau, \tau)$ and let $\hat{u}_\tau$ solve the learned ODE $\dot{\hat{u}}_\tau = v_\theta(\hat{u}_\tau, \tau)$ with the same initial data $u_0 = \hat{u}_0$.

Define the time-average velocity

$$\bar{v}_\theta(u) := \int_0^1 v_\theta(u, \tau) \, d\tau.$$

The average isolates the "straight-line" component of the learned field, while deviations from it quantify curvature in rectification time.

**Definition G.1** (Conditional barycentric rectified velocity). For each fixed condition $c$ and each rectification time $\tau \in [0, 1]$, define

$$v^\star(u, \tau; c) := \mathbb{E}[Y - \Xi \mid U_\tau = u, \ C = c], \qquad \rho_\tau^c\text{-a.e. } u. \tag{72}$$

**Interpretation.** Along a single interpolation chord, the velocity is simply the constant vector $Y - \Xi$. At a population level, many such chords may pass through the same state $u$ at the same rectification time $\tau$. The field $v^\star(u, \tau; c)$ is the average of those compatible chord directions, conditioned both on the current state and on the input variable $c$.

**Theorem G.2** (Terminal error decomposition (fit + straightness)). *Assume $v_\theta(\cdot, \tau)$ is $L$-Lipschitz in $u$ uniformly in $\tau$ and that $u_\tau$ remains in a region where the quantities below are finite. Define*

$$\varepsilon_{\text{fit}}^2 := \int_0^1 \mathbb{E}\big\| \bar{v}_\theta(u_\tau) - v_\star(u_\tau, \tau) \big\|^2 \, d\tau, \qquad \varepsilon_{\text{curv}}^2 := \int_0^1 \mathbb{E}\big\| v_\theta(u_\tau, \tau) - \bar{v}_\theta(u_\tau) \big\|^2 \, d\tau.$$

*Then*

$$\mathbb{E}\|\hat{u}_1 - u_1\| \ \leq \ e^L \left( \varepsilon_{\text{fit}} + \varepsilon_{\text{curv}} \right). \tag{73}$$

*Moreover, the same argument in $L^2$ yields*

$$\mathbb{E}\|\hat{u}_1 - u_1\|^2 \ \leq \ C(L) \left( \varepsilon_{\text{fit}}^2 + \varepsilon_{\text{curv}}^2 \right), \qquad C(L) \sim e^{2L}. \tag{74}$$

**Proposition G.3** (Exact conditional transport). *Assume we work on a finite-dimensional surrogate $\mathbb{R}^{d_N}$ of $\mathcal{U}$, and assume the continuity equation associated with $v^\star(\cdot, \tau; c)$ admits a unique classical flow map $X_\tau^c$ solving*

$$\frac{d}{d\tau} X_\tau^c(u) = v^\star(X_\tau^c(u), \tau; c), \qquad X_0^c(u) = u.$$

*Then*

$$(X_\tau^c)_\# \pi_0^c = \rho_\tau^c \qquad \text{for all } \tau \in [0, 1],$$

*and in particular*

$$(X_1^c)_\# \pi_0^c = \nu^c.$$

*Proof.* Set $e_\tau := \hat{u}_\tau - u_\tau$. Then

$$\dot{e}_\tau = v_\theta(\hat{u}_\tau, \tau) - v_\star(u_\tau, \tau) = \big[ v_\theta(\hat{u}_\tau, \tau) - v_\theta(u_\tau, \tau) \big] + \big[ v_\theta(u_\tau, \tau) - v_\star(u_\tau, \tau) \big].$$

Take norms and use Lipschitz continuity:

$$\frac{d}{d\tau} \|e_\tau\| \leq L \|e_\tau\| + \|v_\theta(u_\tau, \tau) - v_\star(u_\tau, \tau)\|.$$

Integrate from 0 to 1 and apply Grönwall:

$$\|e_1\| \le e^L \int_0^1 \|v_\theta(u_\tau, \tau) - v_\star(u_\tau, \tau)\| \, d\tau.$$

Now add and subtract $\bar{v}_\theta(u_\tau)$ and use triangle inequality:

$$\|v_\theta(u_\tau, \tau) - v_\star(u_\tau, \tau)\| \le \|v_\theta(u_\tau, \tau) - \bar{v}_\theta(u_\tau)\| + \|\bar{v}_\theta(u_\tau) - v_\star(u_\tau, \tau)\|.$$

Take expectations and apply Cauchy–Schwarz in $\tau$ to obtain (73). For (74), repeat with $\|e_\tau\|^2$:

$$\frac{d}{d\tau}\|e_\tau\|^2 = 2 e_\tau \cdot \dot{e}_\tau \le 2L\|e_\tau\|^2 + 2\|e_\tau\| \, \|v_\theta(u_\tau, \tau) - v_\star(u_\tau, \tau)\|,$$

and apply Young's inequality plus Grönwall. The resulting constant is $C(L) \sim e^{2L}$. $\qquad\square$

**Empirical tie.** Theorem G.2 explains the two central practical observations: (i) if the learned velocity is nearly *constant in $\tau$* (small straightness error), then the continuous-time mismatch is small, and (ii) straighter trajectories are easier to integrate, which translates into fewer solver steps at inference (Section J). This is exactly the mechanism behind "8 steps vs. 128 steps" in the main text and the sharp spectral tracking in Figure 22: early steps already reconstruct high wavenumbers because the trajectory is not spending many steps "turning" in rectification time.

*Proof.* Let $(\Xi, Y) \sim \gamma^c$ and define $U_\tau = (1-\tau)\Xi + \tau Y$, so that $\mathrm{Law}(U_\tau \mid C = c) = \rho_\tau^c$. Fix a smooth compactly supported test function $\varphi$ on $\mathbb{R}^{d_N}$. Differentiating under the conditional expectation gives

$$\frac{d}{d\tau}\mathbb{E}[\varphi(U_\tau) \mid C = c] = \mathbb{E}\big[\nabla\varphi(U_\tau) \cdot (Y - \Xi) \mid C = c\big].$$

Condition further on $U_\tau$:

$$\mathbb{E}\big[\nabla\varphi(U_\tau) \cdot (Y - \Xi) \mid C = c\big] = \mathbb{E}\big[\nabla\varphi(U_\tau) \cdot v^\star(U_\tau, \tau; c) \mid C = c\big].$$

Hence $\rho_\tau^c$ satisfies the weak continuity equation

$$\frac{d}{d\tau}\int \varphi(u)\, \rho_\tau^c(du) = \int \nabla\varphi(u) \cdot v^\star(u, \tau; c)\, \rho_\tau^c(du).$$

On the other hand, the pushforward curve $(X_\tau^c)_\# \pi_0^c$ satisfies the same weak equation by the method of characteristics, with the same initial condition at $\tau = 0$. By uniqueness in the finite-dimensional setting, the two curves coincide, so $(X_\tau^c)_\# \pi_0^c = \rho_\tau^c$ for all $\tau$. At $\tau = 1$, this yields $(X_1^c)_\# \pi_0^c = \nu^c$. $\qquad\square$

## G.3 The training loss as an $L^2$ projection

# H Discretization: why curvature controls step count, and why EMA helps

## H.1 Local truncation error and the curvature driver

We start from a clean Taylor expansion for the ODE $\dot{u} = v(u, \tau)$. The practical rectified-flow loss is the conditional regression objective

$$\mathcal{L}(v) = \mathbb{E}\Big[\|v(U_\tau, \tau; C) - (Y - \Xi)\|^2\Big], \tag{75}$$

where the expectation is taken over the joint sampling of $C$, $(\Xi, Y) \sim \gamma^C$, and $\tau \sim \mathrm{Unif}[0,1]$.

**Lemma H.1** (Local truncation error for explicit Euler). *Assume $v \in C^1$ in $(u, \tau)$ on the region traversed and that $\|\partial_\tau v(u, \tau)\| \le M_\tau$, $\|J_u v(u, \tau)\| \le L$, and $\|v(u, \tau)\| \le M$. Then one explicit-Euler step from $(u, \tau)$*

*with step size $\Delta\tau$ has local truncation error*

$$
\begin{aligned}
\mathrm{LTE}(\tau;\Delta\tau) &:= \big\|u(\tau+\Delta\tau) - \big(u(\tau) + \Delta\tau\, v(u(\tau),\tau)\big)\big\| \\
&= \frac{(\Delta\tau)^2}{2}\,\big\|\partial_\tau v(u,\tau) + J_u v(u,\tau)\, v(u,\tau)\big\| \;+\; \mathcal{O}((\Delta\tau)^3) \\
&\leq \frac{(\Delta\tau)^2}{2}\,(M_\tau + LM) \;+\; \mathcal{O}((\Delta\tau)^3).
\end{aligned}
\tag{76}
$$

**Proposition H.2** (Population minimizer of the conditional rectified-flow loss)**.** *For each fixed $\tau$ and condition $c$, the unique $L^2(\rho_\tau^c)$ minimizer of*

$$
v \longmapsto \mathbb{E}\Big[\|v(U_\tau,\tau;c) - (Y - \Xi)\|^2 \,\big|\, C = c\Big]
$$

*is the conditional barycentric field $v^\star(\cdot,\tau;c)$ from* (72)*.*

*Proof.* Differentiate $\dot{u} = v(u,\tau)$ along the trajectory:

$$
\ddot{u}(\tau) = \partial_\tau v(u(\tau),\tau) + J_u v(u(\tau),\tau)\,\dot{u}(\tau) = \partial_\tau v(u(\tau),\tau) + J_u v(u(\tau),\tau)\, v(u(\tau),\tau).
$$

Taylor expand:

$$
u(\tau+\Delta\tau) = u(\tau) + \Delta\tau\, v(u(\tau),\tau) + \frac{(\Delta\tau)^2}{2}\ddot{u}(\tau) + \mathcal{O}((\Delta\tau)^3).
$$

Subtract the Euler update and take norms to obtain (76). The bound follows by triangle inequality and the assumed sup bounds. $\square$

**Interpretation.** Lemma J.2 identifies two drivers of discretization error:

$$
\|\partial_\tau v\| \quad \text{(time curvature)} \qquad \text{and} \qquad \|J_u v\, v\| \quad \text{(spatial nonlinearity)}.
$$

Rectified flows are designed so that trajectories are *nearly straight in $\tau$*, i.e. $\partial_\tau v$ is small along typical paths. This is the fundamental reason they can use large steps without losing fidelity.

*Proof.* This is the standard characterization of conditional expectation as the orthogonal projection in $L^2$. For fixed $c$ and $\tau$, write $Z = Y - \Xi$ and $X = U_\tau$. Then

$$
v^\star(X,\tau;c) = \mathbb{E}[Z \mid X,\, C = c].
$$

For any square-integrable measurable $v(X,\tau;c)$,

$$
\mathbb{E}\big[\|Z - v(X,\tau;c)\|^2 \mid C = c\big] = \mathbb{E}\big[\|Z - \mathbb{E}[Z \mid X, C = c]\|^2 \mid C = c\big] + \mathbb{E}\big[\|\mathbb{E}[Z \mid X, C = c] - v(X,\tau;c)\|^2 \mid C = c\big],
$$

which proves minimality and uniqueness. $\square$

Proposition G.3 is the law-level correctness statement: if the learned velocity matches the ideal conditional barycentric field for the relevant target law, then exact integration transports the source law to that target law. Proposition H.2 explains why the training loss is the natural conditional regression objective.

## H.2 Global error: straightness reduces the required number of steps

# I Continuous-time fit error for the learned conditional flow

For the rest of the appendix, fix a condition $c$ and a target conditional law $\nu^c$ (in the finite-resolution application we will set $\nu^c = \bar{\mu}_1^c$). Let $v^\star(\cdot,\tau;c)$ be the corresponding conditional barycentric field.

Let $U_\tau$ solve the ideal conditional rectified ODE

$$\dot{U}_\tau = v^\star(U_\tau, \tau; c), \qquad U_0 \sim \pi_0^c. \tag{77}$$

By Proposition G.3,

$$\text{Law}(U_1 \mid C = c) = \nu^c.$$

Let $\widehat{U}_\tau$ solve the learned continuous-time conditional ODE

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c), \qquad \widehat{U}_0 = U_0. \tag{78}$$

**Theorem I.1** (Continuous-time fit error). *Assume $v_\theta(\cdot, \tau; c)$ is $L$-Lipschitz in $u$, uniformly in $\tau \in [0, 1]$. Then*

$$\left(\mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \mid C = c\big]\right)^{1/2} \le e^L \int_0^1 \left(\mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \mid C = c\big]\right)^{1/2} d\tau. \tag{79}$$

*In particular, if we define*

$$\varepsilon_{\text{fit}}^2(c) := \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \mid C = c\big] d\tau, \tag{80}$$

*then*

$$\left(\mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \mid C = c\big]\right)^{1/2} \le e^L \varepsilon_{\text{fit}}(c). \tag{81}$$

*Consequently,*

$$W_2\big(\nu^c, \widehat{\mu}_1^{c,\text{cts}}\big) \le e^L \varepsilon_{\text{fit}}(c), \qquad \widehat{\mu}_1^{c,\text{cts}} := \text{Law}(\widehat{U}_1 \mid C = c). \tag{82}$$

*Proof.* Set $E_\tau := \widehat{U}_\tau - U_\tau$. Then

$$\dot{E}_\tau = v_\theta(\widehat{U}_\tau, \tau; c) - v^\star(U_\tau, \tau; c) = \big(v_\theta(\widehat{U}_\tau, \tau; c) - v_\theta(U_\tau, \tau; c)\big) + \big(v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\big).$$

Hence

$$\|\dot{E}_\tau\| \le L\|E_\tau\| + \|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|.$$

Since $E_0 = 0$, Grönwall's inequality yields

$$\|E_1\| \le e^L \int_0^1 \|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\| \, d\tau.$$

Take conditional $L^2$ norms, use Minkowski's integral inequality, and obtain (79). Equation (81) follows from Cauchy–Schwarz in $\tau$. Finally, (82) follows because the coupling given by the common initial sample $U_0 = \widehat{U}_0$ implies

$$W_2^2(\nu^c, \widehat{\mu}_1^{c,\text{cts}}) \le \mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \mid C = c\big].$$

$\square$

**Sanity check.** The continuous-time fit bound (81) vanishes when

$$v_\theta(\cdot, \tau; c) = v^\star(\cdot, \tau; c) \qquad \text{for a.e. } \tau,$$

which is the correct exactness property. This is precisely where the old fit+curvature theorem failed: a generic "straightness" term should *not* survive when the learned continuous-time field equals the ideal one.

## J    Discretization: why straightness controls step count

We now fix the learned field $v_\theta(\cdot, \tau; c)$ and study only the numerical error incurred when integrating the learned ODE

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c).$$

### J.1    Local truncation error and the total derivative along trajectories

**Corollary J.1** (Global Euler error controlled by time-curvature). *Assume the hypotheses of Lemma J.2 and that $v(\cdot, \tau)$ is L-Lipschitz in u uniformly in $\tau$ on the region traversed. Let $u^\Delta$ be explicit Euler with uniform step $\Delta\tau = 1/N$. Then there exists $C = C(L)$ such that*

$$\sup_{\tau \in [0,1]} \|u_\tau^\Delta - u_\tau\| \leq C\, \Delta\tau \int_0^1 \Big( \|\partial_\tau v(u_\tau, \tau)\| + \|J_u v(u_\tau, \tau)\, v(u_\tau, \tau)\| \Big) d\tau, \tag{83}$$

*up to higher-order terms.*

**Lemma J.2** (Local truncation error for explicit Euler). *Assume $v_\theta$ is $C^1$ in $(u, \tau)$ on the region traversed by the learned trajectory $\widehat{U}_\tau$, and define*

$$g(\tau) := v_\theta(\widehat{U}_\tau, \tau; c).$$

*Then one explicit-Euler step of size $\Delta\tau$ from time $\tau$ satisfies*

$$\begin{aligned}
\mathrm{LTE}(\tau; \Delta\tau) &:= \left\| \widehat{U}_{\tau+\Delta\tau} - \big( \widehat{U}_\tau + \Delta\tau\, v_\theta(\widehat{U}_\tau, \tau; c) \big) \right\| \\
&= \frac{(\Delta\tau)^2}{2} \|\dot{g}(\tau)\| + \mathcal{O}((\Delta\tau)^3) \\
&= \frac{(\Delta\tau)^2}{2} \left\| \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c) \right\| + \mathcal{O}((\Delta\tau)^3).
\end{aligned} \tag{84}$$

*If, in addition,*

$$\|\partial_\tau v_\theta(u, \tau; c)\| \leq M_\tau, \qquad \|J_u v_\theta(u, \tau; c)\| \leq L, \qquad \|v_\theta(u, \tau; c)\| \leq M$$

*on the relevant region, then*

$$\mathrm{LTE}(\tau; \Delta\tau) \leq \frac{(\Delta\tau)^2}{2}(M_\tau + LM) + \mathcal{O}((\Delta\tau)^3). \tag{85}$$

*Proof.* Write the one-step error recursion $e_{n+1} \leq (1 + L\Delta\tau)e_n + \mathrm{LTE}_n$ and iterate it over $n = 0, \dots, N-1$. Use $\prod_{k=0}^{N-1}(1 + L\Delta\tau) \leq e^L$ and sum the LTE bounds from Lemma J.2. The integral form (83) is obtained by viewing the sum as a Riemann approximation of $\int_0^1 (\cdots) d\tau$.    $\square$

**Empirical tie.**    Equation (83) explains the step-count gap we observe: if $\int_0^1 \|\partial_\tau v\|$ is small (straight trajectories), then the $N$ required for a fixed tolerance is small. Diffusion-class samplers typically integrate a much more curved reverse-time dynamics (in addition to stochasticity), which translates into much larger effective curvature and hence many more steps. This is also consistent with the qualitative "trajectory inpainting" comparison in Figure 5.

*Proof.* Differentiate the learned ODE along the trajectory:

$$\ddot{\widehat{U}}_\tau = \frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, \dot{\widehat{U}}_\tau.$$

Since $\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c)$, this becomes

$$\ddot{\widehat{U}}_\tau = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

Now Taylor-expand $\widehat{U}_{\tau+\Delta\tau}$ around $\tau$:

$$\widehat{U}_{\tau+\Delta\tau} = \widehat{U}_\tau + \Delta\tau\, v_\theta(\widehat{U}_\tau, \tau; c) + \frac{(\Delta\tau)^2}{2}\ddot{\widehat{U}}_\tau + \mathcal{O}((\Delta\tau)^3).$$

Subtract the Euler update and take norms to obtain (84). The bound (85) follows from the triangle inequality.
□

**Interpretation.** Lemma J.2 identifies the relevant straightness quantity:

$$\frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c). \tag{86}$$

This is the quantity that governs numerical step-count requirements. It is *not* merely the partial derivative $\partial_\tau v_\theta$ at fixed state.

### J.2 EMA curvature proxy and blending as a Tikhonov correction

**Discrete-time EMA as a low-pass filter.** During sampling we evaluate $v_t := v_\theta(u_t, \tau_t)$ at a discrete set of times $\tau_t$ and maintain an exponential moving average (EMA)

$$v_t^{\mathrm{ema}} = \lambda\, v_{t-1}^{\mathrm{ema}} + (1-\lambda)\, v_t, \qquad \lambda \in (0,1).$$

If $v_t$ varies slowly with $\tau_t$, then $v_t^{\mathrm{ema}}$ tracks it closely; if $v_t$ changes quickly, the EMA lags and the deviation

$$s_t := \|v_t - v_t^{\mathrm{ema}}\|$$

spikes. This motivates $s_t$ as a computable curvature/straightness proxy.

A simple bound shows $s_t$ controls a discrete time-variation scale.

### J.3 Global explicit-Euler error

**Lemma J.3** (EMA deviation controls incremental variation). *Let $\{v_t\}_{t\geq 0}$ be any sequence in a normed space and define $v_t^{\mathrm{ema}} = \lambda v_{t-1}^{\mathrm{ema}} + (1-\lambda)v_t$ with $v_0^{\mathrm{ema}} = v_0$. Then*

$$\|v_t - v_t^{\mathrm{ema}}\| \leq (1-\lambda) \sum_{j=0}^{t-1} \lambda^j \|v_{t-j} - v_{t-j-1}\|.$$

*In particular, if $\|v_k - v_{k-1}\| \leq \delta$ for all $k$, then $\|v_t - v_t^{\mathrm{ema}}\| \leq \delta$ for all $t$.*

**Theorem J.4** (Global Euler discretization error). *Assume the hypotheses of Lemma J.2, and assume moreover that $v_\theta(\cdot, \tau; c)$ is $L$-Lipschitz in $u$, uniformly in $\tau \in [0,1]$. Let $\widehat{U}^{(N)}$ denote the explicit-Euler approximation of the learned flow with uniform step $\Delta\tau = 1/N$:*

$$\widehat{U}_{\tau_{n+1}}^{(N)} = \widehat{U}_{\tau_n}^{(N)} + \Delta\tau\, v_\theta(\widehat{U}_{\tau_n}^{(N)}, \tau_n; c), \qquad \tau_n = n/N.$$

*Then there exists a constant $C(L) > 0$ such that*

$$\sup_{0 \leq n \leq N} \left( \mathbb{E}\big[ \|\widehat{U}_{\tau_n}^{(N)} - \widehat{U}_{\tau_n}\|^2 \mid C = c\big] \right)^{1/2} \leq C(L)\, \Delta\tau \int_0^1 \left( \mathbb{E}\big[ \|\dot{g}(\tau)\|^2 \mid C = c\big] \right)^{1/2} d\tau. \tag{87}$$

*Equivalently, defining*

$$\varepsilon_{\mathrm{disc}}(c; N) := \frac{1}{N} \int_0^1 \left( \mathbb{E}\big[ \|\dot{g}(\tau)\|^2 \mid C = c\big] \right)^{1/2} d\tau, \tag{88}$$

*we have*

$$\sup_{0 \leq n \leq N} \left( \mathbb{E}\big[ \|\widehat{U}_{\tau_n}^{(N)} - \widehat{U}_{\tau_n}\|^2 \mid C = c\big] \right)^{1/2} \leq C(L)\, \varepsilon_{\mathrm{disc}}(c; N). \tag{89}$$

*Proof.* Unroll the recursion: $v_t^{\text{ema}} = (1-\lambda)\sum_{j=0}^{t}\lambda^j v_{t-j}$. Subtract from $v_t$ and telescope:

$$v_t - v_t^{\text{ema}} = (1-\lambda)\sum_{j=0}^{t-1}\lambda^j\left(v_t - v_{t-j-1}\right),$$

then use triangle inequality and rewrite $v_t - v_{t-j-1}$ as a sum of increments. □

**Blending as a quadratic minimizer.** We use the blended update

$$\tilde{v}_t = (1-\alpha_t)v_t + \alpha_t v_t^{\text{ema}}, \qquad \alpha_t \in [0,1].$$

This is the unique minimizer of a Tikhonov-regularized quadratic:

$$\tilde{v}_t = \arg\min_{w}\left\{\|w - v_t\|^2 + \beta_t\|w - v_t^{\text{ema}}\|^2\right\}, \qquad \alpha_t = \frac{\beta_t}{1+\beta_t}.$$

Thus blending is not an ad-hoc smoothing step: it is the closed-form solution of a principled stabilization objective trading fidelity to the instantaneous network prediction against adherence to a locally averaged trend.

*Proof.* Let $e_n := \widehat{U}_{\tau_n}^{(N)} - \widehat{U}_{\tau_n}$. Standard one-step perturbation gives

$$\|e_{n+1}\| \le (1 + L\Delta\tau)\|e_n\| + \text{LTE}(\tau_n; \Delta\tau).$$

Iterating this recursion and using $(1 + L\Delta\tau)^N \le e^L$ yields

$$\sup_{0\le n\le N}\|e_n\| \le C(L)\sum_{n=0}^{N-1}\text{LTE}(\tau_n; \Delta\tau).$$

Insert the local truncation estimate from Lemma J.2, ignore higher-order terms, and take conditional $L^2$ norms. The sum is a Riemann approximation of the integral in (87). □

**Sanity check.** At fixed learned field, the discretization error (89) vanishes as $N \to \infty$. Thus, if the learned field is exact and we integrate it exactly, there is no residual discretization term. This is again where the old theory went wrong: straightness should influence *how many steps are needed*, not create an extra continuous-time approximation error.

**Step-size rule from LTE control.** Lemma J.2 suggests choosing $\Delta\tau_t$ so that

$$(\Delta\tau_t)^2\left(\|\partial_\tau v\| + \|J_u v\, v\|\right) \approx \text{const.}$$

Since $\|\partial_\tau v\|$ is not directly available, we replace it by a multiple of the proxy $s_t$ (Lemma J.3), and we upper-bound $\|J_u v\, v\| \lesssim L\|v_t\|$ using Lipschitz control. This yields the square-root-type rule in the main text:

$$\Delta\tau_t \propto \frac{1}{\sqrt{\kappa_1 s_t + \kappa_2}}, \qquad \kappa_2 \approx L\|v_t\|.$$

This is exactly the mechanism behind the "curvature-aware integration" contribution: when the trajectory bends (large $s_t$), we both (i) regularize the velocity via blending and (ii) reduce the step size to control the discretization term in (83).

# K   OOD stabilization by EMA blending

# L   Multiscale coverage: structure functions control unavoidable law tails

The EMA-based controller used in the sampler is not part of the generic correctness theorem. Its purpose is more specific: in the OOD macro–micro regime studied in the experiments, the learned velocity can become oscillatory along rectification time, which makes explicit integration brittle. The role of EMA/blending is to suppress this oscillatory component while preserving the slowly varying part of the ideal transport.

## L.1   Why spectra/structure functions appear in a law-level bound

**Idealized continuous-time surrogate.**   Fix a condition $c$ and consider the ideal path $U_\tau$ from (77). Define along this path

$$g(\tau) := v^\star(U_\tau, \tau; c), \tag{90}$$

and the learned-field error

$$\varepsilon(\tau) := v_\theta(U_\tau, \tau; c) - g(\tau). \tag{91}$$

Thus

$$v_\theta(U_\tau, \tau; c) = g(\tau) + \varepsilon(\tau).$$

## L.2   An abstract smoothing assumption

**Finite resolution is a hard constraint.**   All models operate on a fixed grid (e.g. $128^2$ for training/evaluation). This enforces an effective Fourier cutoff $K_{\max} \simeq N$ (Nyquist), and architectural choices may impose an even lower effective cutoff $K_c$. Therefore, even a perfect generative model cannot represent energy beyond that cutoff. The best it can do is match the *projected* law $(P_{\leq K_c})_\# \mu$.

**Structure functions quantify tail energy.**   In turbulence, small-scale content is captured by structure functions and energy spectra. This is exactly why our empirical analysis emphasizes spectral evolution along $\tau$ (Figure 22). The theory below formalizes the link: a structure-function modulus bound implies a Fourier-tail bound, which becomes a coverage term in $W_2$.

## L.3   Bandlimited fields: capacity bounds and why missing an annulus matters

We record two standard Fourier facts to make the "capacity" language explicit. Let $E_\lambda$ be a causal smoothing operator in rectification time, with bandwidth parameter $\lambda > 0$. We assume the following two properties along the ideal path:

**Lemma L.1** (Bernstein upper bound for bandlimited fields). *Let $u : \mathbb{T}^d \to \mathbb{R}^m$ satisfy $u = P_{\leq K} u$ for some integer $K \geq 1$. Then there exists $C_d > 0$ such that*

$$\|\nabla_x u\|_{L^\infty(\mathbb{T}^d)} \leq C_d K^{1 + \frac{d}{2}} \|u\|_{L^2(\mathbb{T}^d)}.$$

1. **Contraction on the oscillatory error component.** There exists $\sigma(c, \lambda) \in [0, 1)$ such that

$$\|E_\lambda \varepsilon\|_{L^2_\tau L^2_\Omega(c)} \leq \sigma(c, \lambda) \|\varepsilon\|_{L^2_\tau L^2_\Omega(c)}, \tag{92}$$

where

$$\|f\|^2_{L^2_\tau L^2_\Omega(c)} := \int_0^1 \mathbb{E}\big[\|f(\tau)\|^2 \mid C = c\big]\, d\tau.$$

2. **Small bias on slowly varying signals.** There exists a universal constant $C_{\mathrm{ema}} > 0$ such that

$$\|E_\lambda g - g\|_{L^2_\tau L^2_\Omega(c)} \leq C_{\mathrm{ema}} \lambda \|\dot{g}\|_{L^2_\tau L^2_\Omega(c)}. \tag{93}$$

**Remark on exponential moving averages.** For the continuous-time exponential smoother defined by

$$m'(\tau) = \frac{1}{\lambda}\big(f(\tau) - m(\tau)\big), \qquad m(0) = f(0),$$

the bias estimate (93) holds with $C_{\text{ema}} = 1$. Indeed, the error $e = m - f$ satisfies

$$e'(\tau) + \frac{1}{\lambda}e(\tau) = -f'(\tau), \qquad e(0) = 0,$$

so

$$e(\tau) = -\int_0^\tau e^{-(\tau - s)/\lambda} f'(s)\, ds,$$

and Young's inequality yields

$$\|e\|_{L^2(0,1)} \leq \lambda \|f'\|_{L^2(0,1)}.$$

A sufficient condition for (92) is that a nontrivial fraction of the error energy lies above the smoothing cutoff frequency; in the OOD regime this is precisely the structural behavior we empirically observe.

### L.4 Idealized blended flow

For a fixed blend weight $\alpha \in [0,1]$, define the *idealized blended field along the ideal path* by

$$\widetilde{v}_\alpha(U_\tau, \tau; c) := (1 - \alpha)\, v_\theta(U_\tau, \tau; c) + \alpha\, (E_\lambda[v_\theta(U., \cdot; c)])(\tau). \tag{94}$$

Assume $\widetilde{v}_\alpha(\cdot, \tau; c)$ extends to a state-space field that is uniformly $L$-Lipschitz in $u$. Let $\widetilde{U}_\tau$ solve

$$\dot{\widetilde{U}}_\tau = \widetilde{v}_\alpha(\widetilde{U}_\tau, \tau; c), \qquad \widetilde{U}_0 = U_0. \tag{95}$$

Define

$$\varepsilon_{\text{approx}}(c) := \|\varepsilon\|_{L^2_\tau L^2_\Omega(c)}, \tag{96}$$

and

$$S_{*,\text{tot}}(c) := \|\dot{g}\|_{L^2_\tau L^2_\Omega(c)}. \tag{97}$$

*Proof.* Expand $u(x) = \sum_{|k| \leq K} \hat{u}(k) e^{ik \cdot x}$, write $\nabla u$ as a Fourier series, and apply Cauchy–Schwarz using that $\#\{|k| \leq K\} \lesssim K^d$ and Parseval. $\qquad\square$

**Theorem L.2** (EMA stabilization in the oscillatory OOD regime). *Under the assumptions above,*

$$\Big(\mathbb{E}\big[\|\widetilde{U}_1 - U_1\|^2 \mid C = c\big]\Big)^{1/2} \leq e^L \Big[\big(1 - \alpha(1 - \sigma(c, \lambda))\big)\, \varepsilon_{\text{approx}}(c) + C_{\text{ema}}\, \alpha\, \lambda\, S_{*,\text{tot}}(c)\Big]. \tag{98}$$

*The corresponding unsmoothed fit bound along the same ideal path is*

$$e^L\, \varepsilon_{\text{approx}}(c).$$

*Consequently, EMA blending yields a strictly smaller upper bound whenever*

$$(1 - \sigma(c, \lambda))\, \varepsilon_{\text{approx}}(c) > C_{\text{ema}}\, \lambda\, S_{*,\text{tot}}(c). \tag{99}$$

**Lemma L.3** (Annulus lower bound). *Let $f = P_{[K,2K]}u$ and $K \geq 1$. Then there exists $c_d > 0$ such that*

$$\|\nabla_x f\|_{L^\infty} \geq c_d\, K^{1 - \frac{d}{2}}\, \|f\|_{L^2}.$$

*Proof.* On the annulus $K \leq |k| \leq 2K$, the Fourier symbol of $\nabla$ has magnitude $\simeq K$. A reverse Bernstein estimate on an annulus yields $\|f\|_{L^\infty} \gtrsim K^{-d/2}\|f\|_{L^2}$, and $\|\nabla f\|_{L^\infty} \gtrsim K\|f\|_{L^\infty}$, giving the claim. $\qquad\square$

**Empirical tie.** Lemma L.3 formalizes why "spectral collapse" is fatal for turbulent statistics: if a surrogate misses energy in a whole annulus, it underestimates strain and small-scale variability. This is exactly what appears visually when deterministic baselines blur fine scales and also what is quantified by the spread errors in Table 1.

*Proof.* Apply the same Grönwall comparison used in Theorem I.1, but with $\widetilde{v}_\alpha$ in place of $v_\theta$. Along the ideal path,

$$\widetilde{v}_\alpha(U_\tau, \tau; c) - g(\tau) = (1 - \alpha)\varepsilon(\tau) + \alpha E_\lambda \varepsilon(\tau) + \alpha(E_\lambda g(\tau) - g(\tau)).$$

Taking the $L_\tau^2 L_\Omega^2(c)$ norm and using Minkowski's inequality gives

$$\|\widetilde{v}_\alpha(U_\cdot, \cdot; c) - g\|_{L_\tau^2 L_\Omega^2(c)} \leq (1 - \alpha)\|\varepsilon\|_{L_\tau^2 L_\Omega^2(c)} + \alpha\|E_\lambda \varepsilon\|_{L_\tau^2 L_\Omega^2(c)} + \alpha\|E_\lambda g - g\|_{L_\tau^2 L_\Omega^2(c)}.$$

Now apply (92) and (93):

$$\|\widetilde{v}_\alpha(U_\cdot, \cdot; c) - g\|_{L_\tau^2 L_\Omega^2(c)} \leq \left(1 - \alpha + \alpha\sigma(c, \lambda)\right)\varepsilon_{\text{approx}}(c) + C_{\text{ema}}\,\alpha\,\lambda\,S_{*,\text{tot}}(c).$$

Finally, use Theorem I.1 with $\widetilde{v}_\alpha$ in place of $v_\theta$. □

**Interpretation.** The factor

$$(1 - \sigma(c, \lambda))\,\varepsilon_{\text{approx}}(c)$$

is the amount of oscillatory error removed by smoothing, while

$$\lambda\,S_{*,\text{tot}}(c)$$

is the bias paid for smoothing the *ideal* transport itself. Theorem L.2 therefore captures exactly the intended OOD mechanism: EMA helps when the learned error is sufficiently oscillatory, while the ideal conditional rectified transport remains slowly varying in rectification time.

### L.5   Structure functions imply Fourier-tail control (law-level)

**Relation to the practical sampler.** The actual algorithm uses a discrete-time EMA and an adaptive blend weight $\alpha_t$. The theorem above is a continuous-time fixed-$\alpha$ surrogate analysis of the same bias–variance tradeoff; it should be read as a structural explanation of the OOD sampler behavior rather than as an exact theorem for every implementation detail.

For $u : \mathbb{T}^d \to \mathbb{R}^m$ define the second-order structure function

$$S_r^2(u) := \frac{1}{|B_r|} \int_{|h| \leq r} \|u(\cdot + h) - u(\cdot)\|_{L^2(\mathbb{T}^d)}^2\, dh, \qquad S_r^2(\mu) := \int S_r^2(u)\, d\mu(u).$$

Following the statistical-solution framework of Lanthaler et al. (2021b), assume there exists a modulus $\omega(r) \downarrow 0$ as $r \downarrow 0$ such that

$$S_r^2(\mu_t) \leq \omega(r) \qquad \text{for all } r \in (0, 1],\ t \in [0, T]. \tag{100}$$

In practice, $\omega$ can be calibrated from empirical spectra (Figure 22 and supplementary plots).

## M   Coverage: structure functions control unresolved law tails

### M.1   Coverage term

At fixed spatial resolution, every surrogate operates under an effective cutoff $K_c$. Therefore, even a perfect model cannot represent energy beyond that cutoff. The best it can do is match the projected law

$$(P_{\leq K_c})_{\#}\mu_1^c.$$

The discrepancy between the full conditional law and this projected conditional law is the *coverage term.*

## M.2 Structure functions and tail control

For $u : \mathbb{T}^d \to \mathbb{R}^m$, define the second-order structure function

$$S_r^2(u) := \frac{1}{|B_r|} \int_{|h| \leq r} \|u(\cdot + h) - u(\cdot)\|_{L^2(\mathbb{T}^d)}^2 \, dh, \qquad B_r := \{h \in \mathbb{R}^d : |h| \leq r\}. \tag{101}$$

For a law $\mu$ on $L^2(\mathbb{T}^d)$, set

$$S_r^2(\mu) := \int S_r^2(u) \, d\mu(u).$$

Assume that the target conditional law $\mu_1^c$ satisfies the modulus condition

$$S_r^2(\mu_1^c) \leq \omega_c(r) \qquad \text{for all } r \in (0,1], \tag{102}$$

where $\omega_c(r) \downarrow 0$ as $r \downarrow 0$.

**Lemma M.1** (Structure function controls Fourier tail). *Let $\mu$ be a law on $L^2(\mathbb{T}^d)$ satisfying $S_r^2(\mu) \leq \omega(r)$ for all $r \in (0,1]$. Then there exist $c_d, C_d > 0$ such that for all integers $K \geq 1$,*

$$\int \|P_{>K} u\|_{L^2}^2 \, d\mu(u) \leq C_d \, \omega(c_d/K).$$

**Lemma M.2** (Structure function controls Fourier tail). *There exist constants $c_d, C_d > 0$ depending only on the dimension such that for every integer $K \geq 1$,*

$$\int \|P_{>K} u\|_{L^2}^2 \, d\mu_1^c(u) \leq C_d \, \omega_c(c_d/K). \tag{103}$$

*Proof.* For fixed $u$, expand $\|u(\cdot + h) - u(\cdot)\|_{L^2}^2 = \sum_k |\hat{u}(k)|^2 |e^{ik \cdot h} - 1|^2$. Average over $|h| \leq r$ to obtain $S_r^2(u) = \sum_k |\hat{u}(k)|^2 \Psi_r(k)$ where $\Psi_r(k) = \frac{1}{|B_r|} \int_{|h| \leq r} |e^{ik \cdot h} - 1|^2 \, dh$. A standard oscillation estimate yields $\Psi_r(k) \geq c \min\{(|k|r)^2, 1\}$. Hence $\Psi_r(k) \geq c_0$ for all $|k| \geq c'/r$, and therefore $S_r^2(u) \geq c_0 \sum_{|k| \geq c'/r} |\hat{u}(k)|^2 = c_0 \|P_{>c'/r} u\|_{L^2}^2$. Integrate in $u$ and set $r = c_d/K$. $\qquad \square$

*Proof.* For fixed $u$, expand

$$\|u(\cdot + h) - u(\cdot)\|_{L^2}^2 = \sum_{k \in \mathbb{Z}^d} |\hat{u}(k)|^2 \, |e^{ik \cdot h} - 1|^2.$$

Average over $|h| \leq r$ to obtain

$$S_r^2(u) = \sum_{k \in \mathbb{Z}^d} |\hat{u}(k)|^2 \Psi_r(k), \qquad \Psi_r(k) := \frac{1}{|B_r|} \int_{|h| \leq r} |e^{ik \cdot h} - 1|^2 \, dh.$$

A standard oscillation estimate gives

$$\Psi_r(k) \geq c \, \min\{(|k|r)^2, 1\}$$

for a dimensional constant $c > 0$. Hence $\Psi_r(k) \geq c_0$ for all $|k| \geq c'/r$, so

$$S_r^2(u) \geq c_0 \sum_{|k| \geq c'/r} |\hat{u}(k)|^2 = c_0 \|P_{>c'/r} u\|_{L^2}^2.$$

Integrate with respect to $\mu_1^c$ and choose $r = c_d/K$. $\qquad \square$

**Lemma M.3** (Bandlimited projection in $W_2$). *For any law $\mu$ on $L^2(\mathbb{T}^d)$ and cutoff $K_c \geq 1$,*

$$W_2\big(\mu, (P_{\leq K_c})_\#\mu\big) \leq \left(\int \|P_{>K_c}u\|_{L^2}^2 \, d\mu(u)\right)^{1/2}.$$

**Lemma M.4** (Projection estimate in $W_2$). *For any law $\mu$ on $L^2(\mathbb{T}^d)$ and cutoff $K_c \geq 1$,*

$$W_2\big(\mu, (P_{\leq K_c})_\#\mu\big) \leq \left(\int \|P_{>K_c}u\|_{L^2}^2 \, d\mu(u)\right)^{1/2}. \tag{104}$$

*Proof.* Couple $u \sim \mu$ with $\tilde{u} = P_{\leq K_c}u$. Then $\tilde{u} \sim (P_{\leq K_c})_\#\mu$ and $W_2^2 \leq \mathbb{E}\|u - \tilde{u}\|_{L^2}^2 = \mathbb{E}\|P_{>K_c}u\|_{L^2}^2$. $\qquad\square$

*Proof.* Couple $u \sim \mu$ with $\tilde{u} = P_{\leq K_c}u$. Then $\tilde{u} \sim (P_{\leq K_c})_\#\mu$ and

$$W_2^2\big(\mu, (P_{\leq K_c})_\#\mu\big) \leq \mathbb{E}\|u - \tilde{u}\|_{L^2}^2 = \mathbb{E}\|P_{>K_c}u\|_{L^2}^2.$$

$\square$

**Corollary M.5** (Coverage term from structure-function modulus). *Under (102), for any cutoff $K_c \geq 1$,*

$$W_2\big(\mu_t, (P_{\leq K_c})_\#\mu_t\big) \lesssim \omega(c_d/K_c)^{1/2}.$$

**Empirical tie.** Corollary M.6 is the clean mathematical version of what the spectra show: at fixed resolution, there is an unavoidable tail beyond the cutoff. Both ReFlow and GenCFD operate at the same grid resolution (hence comparable $K_c$), so neither can beat the coverage floor. The difference is that ReFlow reaches the best attainable projected law with far fewer steps (Figure 22, Figure 5).

**Corollary M.6** (Coverage bound). *Under (102),*

$$W_2\big(\mu_1^c, \bar{\mu}_1^c\big) = W_2\big(\mu_1^c, (P_{\leq K_c})_\#\mu_1^c\big) \lesssim \omega_c(c_d/K_c)^{1/2}. \tag{105}$$

**Interpretation.** Corollary M.6 is the finite-resolution floor. Even a perfectly trained and exactly integrated surrogate cannot beat this term at cutoff $K_c$.

## N One-step law error for PDE pushforwards and training fit

## O Master law-level bound: coverage + fit + discretization

Let $S_{\Delta t} : \mathcal{H} \to \mathcal{H}$ denote the PDE solution operator over a physical step $\Delta t$ and $\mu_{t+\Delta t} = (S_{\Delta t})_\#\mu_t$. Let $\mathcal{T}_{\Delta t}^\theta$ be the learned one-step surrogate and $\hat{\mu}_{t+\Delta t} = (\mathcal{T}_{\Delta t}^\theta)_\#\mu_t$. We now combine the projected-target exact transport, the continuous-time fit error, and the discretization error.

**Why we insert a bandlimit.** Since the model outputs live at finite resolution, it is natural to compare to the *projected* PDE output $P_{\leq K_c}S_{\Delta t}u$. This isolates (i) an irreducible coverage term and (ii) a trainable fit term. Fix a condition $c$. Let

$$\bar{\mu}_1^c = (P_{\leq K_c})_\#\mu_1^c$$

be the projected target conditional law. Let $v_{K_c}^\star(\cdot, \tau; c)$ be the conditional barycentric field associated with a coupling between $\pi_0^c$ and $\bar{\mu}_1^c$, and let $U_\tau^{K_c}$ solve

$$\dot{U}_\tau^{K_c} = v_{K_c}^\star(U_\tau^{K_c}, \tau; c), \qquad U_0^{K_c} \sim \pi_0^c.$$

By Proposition G.3,

$$\text{Law}(U_1^{K_c} \mid C = c) = \bar{\mu}_1^c.$$

Let $\widehat{U}_\tau$ solve the learned continuous-time ODE

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c), \qquad \widehat{U}_0 = U_0^{K_c},$$

and let $\widehat{U}^{(N)}$ be the explicit-Euler approximation of the same learned ODE with $N$ steps. Write

$$\widehat{\mu}_1^{c,\text{cts}} := \text{Law}(\widehat{U}_1 \mid C = c), \qquad \widehat{\mu}_1^{c,N} := \text{Law}(\widehat{U}_1^{(N)} \mid C = c).$$

Define

$$\varepsilon_{\text{fit},K_c}^2(c) := \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau^{K_c}, \tau; c) - v_{K_c}^\star(U_\tau^{K_c}, \tau; c)\|^2 \mid C = c\big]\, d\tau, \tag{106}$$

and

$$\varepsilon_{\text{disc}}(c; N) := \frac{1}{N} \int_0^1 \Big(\mathbb{E}\big[\|\partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c)\|^2 \mid C = c\big]\Big)^{1/2} d\tau. \tag{107}$$

**Theorem O.1** (Master conditional law-level bound). *Assume the hypotheses of Theorem I.1, Theorem J.4, and Corollary M.6. Then*

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \lesssim \underbrace{\omega_c(c_d/K_c)^{1/2}}_{\text{coverage}} + \underbrace{e^L\, \varepsilon_{\text{fit},K_c}(c)}_{\text{fit}} + \underbrace{C(L)\, \varepsilon_{\text{disc}}(c; N)}_{\text{discretization}}. \tag{108}$$

*More explicitly,*

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \leq W_2(\mu_1^c, \bar{\mu}_1^c) + W_2(\bar{\mu}_1^c, \widehat{\mu}_1^{c,\text{cts}}) + W_2(\widehat{\mu}_1^{c,\text{cts}}, \widehat{\mu}_1^{c,N})$$
$$\leq W_2(\mu_1^c, \bar{\mu}_1^c) + e^L\, \varepsilon_{\text{fit},K_c}(c) + C(L)\, \varepsilon_{\text{disc}}(c; N). \tag{109}$$

*Proof.* Insert the projected target law and the learned continuous-time law as intermediate terms:

$$W_2(\mu_1^c, \widehat{\mu}_1^{c,N}) \leq W_2(\mu_1^c, \bar{\mu}_1^c) + W_2(\bar{\mu}_1^c, \widehat{\mu}_1^{c,\text{cts}}) + W_2(\widehat{\mu}_1^{c,\text{cts}}, \widehat{\mu}_1^{c,N}).$$

The first term is the coverage term from Corollary M.6. The second term is the continuous-time fit term, bounded by Theorem I.1 applied to the ideal projected-target flow $U_\tau^{K_c}$. The third term is the discretization term from Theorem J.4. Combining the three bounds gives (111). $\square$

**Sanity checks.** The bound (111) has the correct limiting behavior.

- If the learned field is exact on the projected target, i.e.

$$v_\theta = v_{K_c}^\star,$$

  then the fit term vanishes.

- If the learned ODE is integrated exactly, i.e. $N \to \infty$, then the discretization term vanishes.

- Therefore, at fixed cutoff $K_c$, a perfect model leaves only the unavoidable coverage floor.

- If, in addition, the cutoff tends to infinity and the structure-function tail vanishes accordingly, then the total error tends to zero.

These are the basic plausibility requirements any correct theory must satisfy.

Define the mean-square training error at time $t$:

$$\varepsilon_{\text{train}}^2(t) := \mathbb{E}_{u \sim \mu_t}\Big[\big\|P_{\leq K_c}(S_{\Delta t} u) - \widehat{u}\big\|_{L^2}^2\Big], \tag{110}$$

where $\widehat{u}$ is the model output given input $u$ (i.e. after integrating the learned RF ODE).

**What the master bound explains in the paper.** Theorem R.1 gives the error taxonomy that the main text should emphasize everywhere:

- **Coverage** is a hard floor imposed by unresolved small scales.

- **Fit** measures how well the learned neural velocity approximates the ideal projected-target conditional transport field.

- **Discretization** measures how hard the learned transport is to integrate numerically; this is the term improved by straightness.

The EMA theorem from Section K is an additional OOD stabilization result, not a fourth term in the generic master decomposition.

## P  From law-level bounds to the reported one-point metrics

**One-point Wasserstein as a marginal metric.** Let $\mu$ and $\widehat{\mu}$ be laws on fields $u : \mathcal{D} \to \mathbb{R}^m$. For each $x \in \mathcal{D}$, define the one-point marginals

$$\mu_x := (\mathrm{ev}_x)_{\#}\mu, \qquad \widehat{\mu}_x := (\mathrm{ev}_x)_{\#}\widehat{\mu}.$$

The reported metric in the main text is

$$W_1^{(1)}(\mu, \widehat{\mu}) := \int_{\mathcal{D}} W_1(\mu_x, \widehat{\mu}_x)\, dx.$$

By Kantorovich–Rubinstein duality, $W_1(\mu_x, \widehat{\mu}_x)$ controls the discrepancy of all pointwise 1-Lipschitz observables at the location $x$.

**Relation to the law-level theory.** The law-level bounds above are stated in $W_2$ on the full field space because this is the natural metric for coupling with $L^2$-based structure functions and Fourier tails. The one-point Wasserstein metric used in the experiments is weaker and more local, but it probes the same underlying conditional law. In particular:

- the *coverage* term controls whether unresolved high-frequency content can be represented at all;

- the *fit* term controls whether the learned continuous-time conditional flow reaches the correct projected target law;

- the *discretization* term controls whether a few ODE steps are sufficient to realize that law in practice.

These are exactly the mechanisms reflected empirically in the mean/spread/Wasserstein tables and in the spectral diagnostics.

**Emphasis of spectra during sampling.** The spectral evolution plots act as a scale-resolved diagnostic of the coverage and discretization story. They show how quickly the sampler reconstructs high-frequency energy up to the grid cutoff. This is why they are the right empirical counterpart of the theory above: they reveal both the finite-resolution ceiling and the fact that straighter rectified transports reach the attainable high-frequency regime with far fewer function evaluations than diffusion-based samplers.

## Q  Architecture of the ReFlow Model

**Proposition Q.1** (One-step law error = coverage + fit)**.** *Assume $\mu_{t+\Delta t}$ satisfies the structure-function modulus* (102) *(hence Corollary M.6). Then*

$$W_2\big(\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}\big) \;\leq\; \underbrace{W_2\big(\mu_{t+\Delta t}, (P_{\leq K_c})_{\#}\mu_{t+\Delta t}\big)}_{coverage} \;+\; \underbrace{\big(\varepsilon_{\mathrm{train}}^2(t)\big)^{1/2}}_{fit},$$

*and therefore*

$$W_2\big(\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}\big) \lesssim \omega(c_d/K_c)^{1/2} + \varepsilon_{\text{train}}(t).$$

*Proof.* Use the triangle inequality in $W_2$:

$$W_2(\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}) \leq W_2\big(\mu_{t+\Delta t}, (P_{\leq K_c})_{\#}\mu_{t+\Delta t}\big) + W_2\big((P_{\leq K_c})_{\#}\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}\big).$$

For the second term, couple by sampling $u \sim \mu_t$ and using the same input to produce $P_{\leq K_c} S_{\Delta t} u$ and $\hat{u}$. Then

$$W_2^2\big((P_{\leq K_c})_{\#}\mu_{t+\Delta t}, \hat{\mu}_{t+\Delta t}\big) \leq \mathbb{E}\|P_{\leq K_c} S_{\Delta t} u - \hat{u}\|_{L^2}^2 = \varepsilon_{\text{train}}^2(t).$$

The second display follows from Corollary M.6. □

**Empirical tie.** Proposition Q.1 explains why training curves saturate at a resolution-dependent floor and why spectra are the correct diagnostic for that floor. It also makes explicit that "better training loss" means smaller law error *only up to* the coverage limit. This aligns with the observation that increasing diffusion steps improves spectral reconstruction but cannot beat finite-resolution constraints, while ReFlow reaches that regime with far fewer steps.

## R   Master inequality: coverage + fit + straightness + discretization

We now combine the law-level coverage/fit decomposition with the continuous-time RF mismatch and the discretization control.

**Theorem R.1** (Master law-level bound for learned rectified flows)**.** *Fix an effective cutoff $K_c$ and assume the structure-function modulus* (102) *for the target PDE laws. Let $\hat{\mu}_1^{(N)}$ be the law obtained by integrating the learned rectified ODE $\dot{u}_\tau = v_\theta(u_\tau, \tau)$ from $\tau = 0$ to $\tau = 1$ using $N$ explicit-Euler steps (uniform step $1/N$). Assume $v_\theta(\cdot, \tau)$ is $L$-Lipschitz in $u$ uniformly in $\tau$.*

*Then, for constants depending only on $L$,*

$$W_2(\mu_1, \hat{\mu}_1^{(N)}) \lesssim \underbrace{\omega(c_d/K_c)^{1/2}}_{coverage} + \underbrace{\varepsilon_{\text{fit}} + \varepsilon_{\text{curv}}}_{fit \,+\, straightness} + \underbrace{\frac{1}{N}\int_0^1 \|\partial_\tau v_\theta(u_\tau, \tau)\|\, d\tau}_{discretization}, \tag{111}$$

*where $\varepsilon_{\text{fit}}, \varepsilon_{\text{curv}}$ are the continuous-time terms from Theorem G.2 evaluated along the ideal trajectory.*

*Proof.* (1) *Coverage.* By Corollary M.6, $W_2(\mu_1, (P_{\leq K_c})_{\#}\mu_1) \lesssim \omega(c_d/K_c)^{1/2}$.

(2) *Continuous-time learned flow error.* Let $\hat{\mu}_1$ denote the law produced by the *exact* (continuous-time) flow of $v_\theta$. Then Theorem G.2 implies a bound of the form $W_2((P_{\leq K_c})_{\#}\mu_1, \hat{\mu}_1) \lesssim \varepsilon_{\text{fit}} + \varepsilon_{\text{curv}}$ (up to the standard coupling-by-same-input argument on the finite-dimensional surrogate).

(3) *Discretization.* Let $\hat{\mu}_1^{(N)}$ be the Euler-discretized law. Corollary J.1 bounds the trajectory error by a term proportional to $\frac{1}{N}\int_0^1 \|\partial_\tau v_\theta\|\, d\tau$ (plus the spatial term, absorbed in constants under the Lipschitz assumption and bounded $\|v_\theta\|$ on the region traversed).

(4) Combine with triangle inequalities:

$$W_2(\mu_1, \hat{\mu}_1^{(N)}) \leq W_2(\mu_1, (P_{\leq K_c})_{\#}\mu_1) + W_2((P_{\leq K_c})_{\#}\mu_1, \hat{\mu}_1) + W_2(\hat{\mu}_1, \hat{\mu}_1^{(N)}),$$

and insert the three bounds. □

- **Why rectification accelerates sampling.** The discretization term depends on the integral of time-curvature. Straightness reduces that integral, so fewer steps suffice (8–10 in our experiments).

- **Why curvature-aware integration helps under shift.** Under distribution shift, the learned velocity may bend more in $\tau$, increasing the last term. The EMA proxy and blending/step control reduce the effective curvature and hence stabilize sampling, which is exactly how curvature is used in our method (control, not OOD detection).

- **Why spectra matter.** The coverage term is dictated by small-scale physics (structure functions / spectrum). This is why Figure 22 is the right diagnostic: it visualizes how quickly the method reconstructs high-frequency energy up to the grid cutoff, and it clarifies what errors are unavoidable at fixed resolution.

- **Why deterministic baselines struggle.** Deterministic predictors trained by pointwise losses effectively target conditional means; in multimodal chaotic regimes this collapses variability (as emphasized by Molinaro et al. (2024)). In the master inequality language, they do not produce a good fit to the law itself, which is seen in their larger spread and Wasserstein errors in Table 1.

## S   From law-level bounds to reported pointwise metrics

**From $W_2$ to marginal discrepancies.** While the paper reports one-point $W_1$ (averaged over space) for computational tractability, the mechanisms above are consistent with those marginal tests: if two laws on fields are close in $W_2$ and have bounded second moments, then many bounded-Lipschitz observables of the fields (including smoothed one-point marginals) are close as well. This is the conceptual bridge between the law-level theory and the reported statistics.

**Why we emphasize spectra during sampling.** The spectral evolution plots (Figure 22 and supplementary variants) act as a *scale-resolved* diagnostic: they visualize the progressive recovery of high frequencies along $\tau$. This connects directly to the structure-function/coverage viewpoint (Section M) and empirically demonstrates that ReFlow reaches the best attainable high-frequency reconstruction regime in far fewer steps than diffusion-based baselines.

## T   Architecture of the ReFlow Model

### T.1   Architectural Components

**Motivation.** Multi-scale PDE data contain wide-ranging spatial scales, so a *multi-resolution* encoder–decoder is natural. We incorporate time embeddings to condition each layer on the interpolation fraction $t$. **Motivation.** Multi-scale PDE data contain wide-ranging spatial scales, so a *multi-resolution* encoder–decoder is natural. We incorporate time embeddings to condition each layer on the interpolation fraction $\tau$.

**Architecture Layout.** We employ a UNet-based architecture augmented with attentional layers, typically termed as **UViT** by Saharia et al. (2022). In addition to the MLP-based time embedding $\Gamma(\tau)$, the input signal is lifted into a higher-dimensional embedding space and later projected back into physical space through convolutional layers. The data flows from high to low resolution across a down-sampling stack composed of convolution blocks into a bottleneck layer that encodes the fine-scale features of the inputs across its channel dimension and mixes them via a multi-head attention mechanism.
On the encoder side, exclusively at the bottleneck level, each attention block preceded by a simple linear

Figure 6: **UNet Backbone Architecture Used in ReFlow.** This schematic illustrates the core UNet-based architecture used within the ReFlow framework, structured across three resolution levels. For clarity, the number of blocks per level is set to one in this illustration. In the actual GenCFD and ReFlow configurations, each block is repeated four times per level. The bottleneck shows an asymmetry between the encoder and decoder sides: the block on the encoder side includes a Convolution Block, Positional Embedding, and Attention Block, while the corresponding block on the decoder side omits the Positional Embedding.

positional embedding. This positional encoding helps preserve spatial locality before global mixing through attention. The decoder side does not apply any positional embedding.

The UNet is conditioned at every level through normalized Feature-wise Linear Modulation (FiLM) techniques embedded within the convolution blocks. The conditioning signal modulates the normalization layers via learned scale and shift parameters. This conditioning mechanism is consistently applied across all encoder and decoder stages.

The output is symmetrically reconstructed via an up-sampling pipeline. Downsampling is performed using standard convolutional layers with stride, while upsampling can be implemented either via transposed convolutions or by applying a standard convolution followed by a non-learnable pixel shuffle operation, which rearranges elements of the tensor spatially according to a fixed upsampling factor.

Importantly, the architecture described here resembles the one presented in Molinaro et al. (2024), ensuring consistency with prior state-of-the-art practices in high-fidelity generative modeling for scientific computing.

**Architecture Layout.** We employ a UNet-based architecture augmented with attentional layers, typically termed as **UViT** by Saharia et al. (2022). In addition to the MLP-based time embedding $\Gamma(\tau)$, the input signal is lifted into a higher-dimensional embedding space and later projected back into physical space through convolutional layers. The data flows from high to low resolution across a down-sampling stack composed of convolution blocks into a bottleneck layer that encodes the fine-scale features of the inputs across its channel dimension and mixes them via a multi-head attention mechanism.

On the encoder side, exclusively at the bottleneck level, each attention block is preceded by a simple linear positional embedding. This positional encoding helps preserve spatial locality before global mixing through attention. The decoder side does not apply any positional embedding.

The UNet is conditioned at every level through normalized Feature-wise Linear Modulation (FiLM) techniques embedded within the convolution blocks. The conditioning signal modulates the normalization layers

Figure 7: **UNet Backbone Architecture Used in ReFlow.** This schematic illustrates the core UNet-based architecture used within the ReFlow framework, structured across three resolution levels. For clarity, the number of blocks per level is set to one in this illustration. In the actual GenCFD and ReFlow configurations, each block is repeated four times per level. The bottleneck shows an asymmetry between the encoder and decoder sides: the block on the encoder side includes a Convolution Block, Positional Embedding, and Attention Block, while the corresponding block on the decoder side omits the Positional Embedding. The time embedding $\Gamma(\tau)$ is computed *once per sample* from the scalar rectified-flow time $\tau$ via a sinusoidal encoding followed by a shared MLP. Each convolution block then applies its own learned affine projection of this global embedding to produce the per-block scale and shift parameters used in the FiLM modulation (see §T.1). The embedding is therefore *globally shared* across levels, while its effect on features is *block-specific.*

via learned scale and shift parameters. This conditioning mechanism is consistently applied across all encoder and decoder stages.

The output is symmetrically reconstructed via an up-sampling pipeline. Downsampling is performed using standard convolutional layers with stride, while upsampling can be implemented either via transposed convolutions or by applying a standard convolution followed by a non-learnable pixel shuffle operation, which rearranges elements of the tensor spatially according to a fixed upsampling factor.

Importantly, the architecture described here resembles the one presented in Molinaro et al. (2024), ensuring consistency with prior state-of-the-art practices in high-fidelity generative modeling for scientific computing.

### T.1.1 Convolution Block

Each UNet level employs dedicated convolution blocks that process features while enabling conditioning on the diffusion time $\tau$. These blocks consist of two convolutional layers interleaved with group normalization and Swish activations. Between the convolutions, a normalized FiLM layer adaptively scales features using the conditioning embeddings. A residual connection combines the processed features with a projected skip connection, ensuring stable gradient flow. Crucially, these convolution blocks form the fundamental building units across all encoder and decoder stages, not just the bottleneck, with consistent application of temporal conditioning through the FiLM mechanism.

### T.1.2 Convolution Block

Each UNet level employs dedicated convolution blocks that process features while enabling conditioning on the diffusion time $\tau$. These blocks consist of two convolutional layers interleaved with group normalization and Swish activations. Between the convolutions, a normalized FiLM layer adaptively scales features using the conditioning embeddings. A residual connection combines the processed features with a projected skip connection, ensuring stable gradient flow. Crucially, these convolution blocks form the fundamental building units across all encoder and decoder stages, not just the bottleneck, with consistent application of temporal conditioning through the FiLM mechanism.

### T.1.3 Normalized FiLM Layer

Each convolution block uses a normalized FiLM layer and applies a convolution layer interleaved with normalization and an activation, then adds a residual skip:

$$
\begin{aligned}
\mathbf{z} &= \mathrm{Conv}\big(\mathrm{Norm}(\mathbf{x})\big), \qquad \mathbf{z} = \sigma(\mathbf{z} + \alpha\,\gamma(t)), \\
\mathbf{x}_{\mathrm{out}} &= \mathbf{x} + \mathrm{Conv}(\mathbf{z}),
\end{aligned}
\tag{112}
$$

where Norm is often `RMSNorm`, GroupNorm or LayerNorm, $\sigma$ is a nonlinearity (e.g. SiLU), and $\gamma(t)$ represents the time embedding (an MLP on $\mathrm{Sinusoid}(t)$) that modulates scale/shift. This temporal conditioning is crucial for guiding the generative process through rectified diffusion trajectories.

$$
\begin{aligned}
\mathbf{z} &= \mathrm{Conv}\big(\mathrm{Norm}(\mathbf{x})\big), \qquad \mathbf{z} = \sigma\big(\mathbf{z} + \alpha\,\gamma(\tau)\big), \\
\mathbf{x}_{\mathrm{out}} &= \mathbf{x} + \mathrm{Conv}(\mathbf{z}),
\end{aligned}
\tag{113}
$$

where Norm is often `RMSNorm`, GroupNorm or LayerNorm, $\sigma$ is a nonlinearity (e.g. SiLU), and $\gamma(\tau)$ represents the time embedding (an MLP on $\mathrm{Sinusoid}(\tau)$) that modulates scale/shift. This temporal conditioning is crucial for guiding the generative process through rectified diffusion trajectories.

### T.1.4 Attention Block

The architecture strategically employs multi-head attention exclusively at the bottleneck layer to balance global interaction modeling with computational efficiency. Each attention block processes normalized features through a spatial-channel reformatting, where features are reshaped by a flattening operation. This preserves the channel structure while collapsing the spatial grid into a single flattened dimension, allowing attention to operate across spatial locations. At certain scales, a multi-head attention (MHA) mechanism captures distant flow interactions. We define

$$
\mathbf{Q} = W_Q\,\mathbf{h}, \quad \mathbf{K} = W_K\,\mathbf{h}, \quad \mathbf{V} = W_V\,\mathbf{h}, \quad \mathcal{A}(\mathbf{h}) = \mathrm{softmax}\!\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d}}\right)\mathbf{V},
\tag{114}
$$

### T.1.5 Attention Block

The architecture strategically employs multi-head attention exclusively at the bottleneck layer to balance global interaction modeling with computational efficiency. Each attention block processes normalized features through a spatial-channel reformatting, where features are reshaped by a flattening operation. This preserves the channel structure while collapsing the spatial grid into a single flattened dimension, allowing attention to operate across spatial locations. At certain scales, a multi-head attention (MHA) mechanism captures distant flow interactions. We define

$$
\mathbf{Q} = W_Q\,\mathbf{h}, \quad \mathbf{K} = W_K\,\mathbf{h}, \quad \mathbf{V} = W_V\,\mathbf{h}, \quad \mathcal{A}(\mathbf{h}) = \mathrm{softmax}\!\left(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d}}\right)\mathbf{V},
\tag{115}
$$

where $\mathbf{h} \in \mathbb{R}^{(H \cdot W) \times d}$ denotes the flattened input sequence, with each of the $H \cdot W$ spatial positions represented as a $d$-dimensional feature vector. In practice, attention is split into multiple heads for better representational

power, then recombined. This global mixing is key for PDE flows dominated by far-field couplings (e.g. vortex merging). The MHA operator is defined as

$$\text{MHA}(\mathbf{h}) \;=\; W^O \,\text{Concat}\left(\mathcal{A}_1(\mathbf{h}), \ldots, \mathcal{A}_n(\mathbf{h})\right), \tag{116}$$

where $n \in \mathbb{N}$ denotes the number of attention heads and $W^O \in \mathbb{R}^{C \times C}$ is a learned output projection matrix. The attention block applies MHA to a normalized input, then adds a residual connection to preserve the original signal and stabilize training while enabling global context to influence local features:

$$\text{MHA}(\mathbf{h}) \;=\; W^O \,\text{Concat}(\mathcal{A}_1(\mathbf{h}), \ldots, \mathcal{A}_n(\mathbf{h})), \tag{117}$$

where $n \in \mathbb{N}$ denotes the number of attention heads and $W^O \in \mathbb{R}^{C \times C}$ is a learned output projection matrix. The attention block applies MHA to a normalized input, then adds a residual connection to preserve the original signal and stabilize training:

$$
\begin{aligned}
\mathbf{z} \;&=\; \text{MHA}\big(\text{Norm}(\mathbf{x})\big), \\
\mathbf{x}_{\text{out}} \;&=\; \mathbf{x} \;+\; \mathbf{z}.
\end{aligned}
\tag{118}
$$

## T.2 Training Pipeline Details

The training pipeline follows the algorithm described in the main text faithfully.

## T.3 Training Pipeline Details

**Theory vs. Implementation: Two Forms of Interpolation.** There are two related but distinct interpolation forms used in this work. *Theory* (Section 4.1 and Proposition 5.1) uses the *linear chord* interpolant

$$\tilde{u}_\tau^{\text{theory}} \;=\; \tau\, u_1 \;+\; (1-\tau)\, u_0, \qquad \tau \in [0,1],$$

which interpolates directly between input $u_0$ and target $u_1$; the corresponding target velocity is $v^* = u_1 - u_0$. This form is used in the error decomposition and straightness analysis. *Implementation* (Algorithm 1 and all experiments) uses a *noise-conditioned* interpolant:

$$\tilde{u}_\tau^{\text{impl}} \;=\; \tau\, u_1 \;+\; \sigma(1-\tau)\, \xi, \qquad \xi \sim \mathcal{N}(0, I),$$

where $\sigma(\cdot)$ is a scalar noise-schedule function. The network is trained to predict $u_1 - \sigma(1-\tau)\, \xi$. At inference we start from pure noise $\xi$ and integrate the learned ODE to $\tau = 1$. Both forms yield nearly-straight trajectories; the noise-conditioned form is standard in the rectified-flow / flow-matching literature and avoids evaluating the reference solver at training time.

**Trainer Workflow.** A high-level `Trainer` class manages:

1. Batching PDE pairs $(u_0, u_1)$, normalized pixel-wise with statistics extracted over each entire dataset.

2. Sampling $\tau \in [0,1]$ and random noise $\xi$ according to a given noise scheduler $\sigma(\cdot)$.

3. Partial interpolation and noise addition: $\tilde{u}_\tau := \tau\, u_1 + \sigma(1-\tau)\, \xi$ (noise-conditioned form; see paragraph above). We have experimented with non-linear interpolation methods, but have not noticed meaningful oscillations in performance.

4. Minimizing the squared deviation between model output and target displacement/noise, optionally with a consistency/EMA update.

5. Throughout training, we monitor validation performance on a separate holdout dataset across all main metrics. Different validation splits have been tested to ensure there is no data leakage that would bias performance metrics.

Table 5: Representative hyperparameters for 2D fluid-flow tasks. See main text for justification of these choices.

| Parameter | Value (Optimal empirical performance) | Notes |
|---|---|---|
| Channels per level | (128, 256, 256) | Number of channels per level. |
| Downsample Ratios | (2, 2, 2) | Downsampling ratio per level. |
| Attention Heads | 8 | Each attention block. |
| Dropout Rate | 0.1 | In ConvBlock for generalization. |
| Noise Schedule | `uniform`, `log-uniform`, `cos-map` | Helps with multi-scale noise. |
| ODE Steps (Sampling) | 4–8 (NFE) | Often $> 15\times$ fewer vs. diffusion. |
| Batch Size | 16 | Tied to GPU capacity. |
| EMA Decay | 0.9999 | Teacher model for consistency. |
| Learning Rate | $3 \times 10^{-4}$ | Cosine decay in code. |

In practice we noticed that the most robust denoising schedule was the `uniform` one. For details on the `cos-map` schedule, we direct the reader to its description in Esser et al. (2024).

## T.4 Summary and Key Takeaways

The `RectifiedFlow` class, combined with a time-aware `UNet2D` architecture, builds a deterministic transport model well-suited to multi-scale PDE tasks. By interpolating between noise and data along nearly-straight paths, it reduces sampling overhead compared to conventional diffusion PDE solvers while retaining the flexibility to model complex turbulent phenomena. Further experimental and theoretical results appear in **SM** Section Z. Instead of the multi-step *stochastic* integration in diffusion-based models, `RectifiedFlow` fits a *deterministic* ODE from noise to data. This leverages straighter trajectories in frequency space, enabling fewer network evaluations at inference time.

**ODE Integration for Sampling.** At inference:

$$\frac{d\tilde{u}_\tau}{d\tau} = v_\theta\big(\tilde{u}_\tau, u_0, \tau\big), \quad \tau \in [0, 1], \quad \tilde{u}_{\tau=0} = \text{random noise}.$$

We solve this with `odeint`. As few as $8{-}10$ function evaluations (NFE) typically suffice, contrasting with the tens or hundreds of NFE required by full diffusion samplers. The corresponding wall-clock speedup depends on batch size and hardware and is reported separately in §Z.8.

**Trainer Workflow.** A high-level `Trainer` class manages:

1. Batching PDE pairs $(u_0, u_1)$. These normalized pixel-wise with statistics extracted per each entire dataset.

2. Sampling $\tau \in [0, 1]$ and random noise $\xi$ according to a given noise scheduler $\sigma(\cdot)$.

3. Partial interpolation + noise addition: $\tilde{u}_\tau := \tau\, u_1 + (1 - \tau)\, \xi$ (or the flow-based variant). We have experimented with non-linear interpolation methods, but have not noticed meaningful oscillations in performance.

4. Minimizing the squared deviation between model output and target displacement/noise, optionally with a consistency/EMA update.

5. Throughout training, we monitor validation performance on a separate holdout dataset across all main metrics. We explicitly note that different validation splits have been tested out to ensure there is no data leakage that would bias performance metrics.

Table 6: Representative hyperparameters for 2D fluid-flow tasks. See main text for justification of these choices.

| Parameter | Value (Optimal empirical performance) | Notes |
|---|---|---|
| Channels per level | (128, 256, 256) | Number of channels per level. |
| Downsample Ratios | (2, 2, 2) | Downsampling ratio per level. |
| Attention Heads | 8 | Each attention block. |
| Dropout Rate | 0.1 | In ConvBlock for generalization. |
| Noise Schedule | `uniform, log-uniform, cos-map` | Helps with multi-scale noise. |
| ODE Steps (Sampling) | 4–8 | Often $> 15\times$ fewer vs. diffusion. |
| Batch Size | 16 | Tied to GPU capacity. |
| EMA Decay | 0.9999 | Teacher model for consistency. |
| Learning Rate | $3 \times 10^{-4}$ | Cosine decay in code. |

## U   Datasets

### U.1   Multi-scale Flow Datasets

Following the dataset generation procedure of Herde et al. Herde et al. (2024), the Richtmyer–Meshkov ensemble is created by imposing a randomized sinusoidal perturbation on a two-fluid interface and driving it with a planar shock via prescribed pressure jumps. For the CloudShock and ShearFlow benchmarks, we follow the GenCFD mesh-generation and solver setup of Molinaro et al. Molinaro et al. (2024), initializing CloudShock with concentric density perturbations and ShearFlow with orthogonal shear jets on adaptive Cartesian grids, and employing the same high-order finite-volume scheme and dissipation settings to ensure consistent numerical fidelity across both datasets.

**Overview.** We experiment on three paired-field benchmarks $(u_0, u_1)$:

- **Richtmyer–Meshkov (RM)**: 64 000 samples

- **Cloud-Shock (CS)**: 40 000 samples

- **Shear-Layer (SL)**: 79 200 samples

All datasets track the $u_0 \to S^t(u_0)|_{t=1}$ solution mapping from inputs to evolved outputs at $t = 1$. The first two datasets monitor the evolution of density $(\rho)$, momentum components $(m_x, m_y)$, and energy $(E)$. The shear-flow dataset monitors the velocity components $(u_x, u_y)$.

**Train/Validation Split.** For each dataset, we reserve 80% of the samples for training and 20% for validation.

**Macro–Micro Ensemble Evaluation (CS & SL).** To probe out-of-distribution generalization under small perturbations, we adopt a two-stage ensemble protocol:

1. *Macro-sampling:* select $M_{\mathrm{macro}} = 10$ distinct base initial conditions.

2. *Micro-perturbation:* for each base, generate $M_{\mathrm{micro}} = 1{,}000$ perturbed copies within a small radius.

3. *Metrics:* compute all performance measures (mean-field error $e_\mu$, standard-deviation error $e_\sigma$, average $W_1$, spectral agreement) by first averaging over each micro-ensemble, then averaging across the $M_{\mathrm{macro}}$ cases.

**In-Distribution Evaluation (RM).** For the Richtmyer–Meshkov dataset, we additionally evaluate on a held-out test set drawn from the same distribution (no macro–micro perturbations). This allows us to

study how deterministic and probabilistic models scale with training set size under standard, in-distribution conditions.

In practice we noticed that the most robust denoising schedule was just the `uniform` one. For details on the `cos-map` schedule, we direct the reader to its description in Esser et al. (2024).

## U.2  Preprocessing and Data Organization

## U.3  Summary and Key Takeaways

The `RectifiedFlow` class, combined with a time-aware `UNet2D` architecture, builds a deterministic transport model well-suited to multi-scale PDE tasks. By interpolating between noise and data along nearly-straight paths, it reduces sampling overhead compared to conventional diffusion PDE solvers while retaining the flexibility to model complex turbulent phenomena. Further experimental and theoretical results appear in **SM** Section Z. Instead of the multi-step *stochastic* integration in diffusion-based models, `RectifiedFlow` fits a *deterministic* ODE from noise to data. This leverages straighter trajectories in frequency space, enabling fewer network evaluations at inference time.

**ODE Integration for Sampling.**  At inference:

$$\frac{d\tilde{u}_\tau}{d\tau} \;=\; v_\theta\big(\tilde{u}_\tau,\, u_0,\, \tau\big), \quad \tau \in [0,1], \quad \tilde{u}_{\tau=0} \;=\; \text{random noise.}$$

We solve this with `odeint`. Few steps (8–10) typically suffice, contrasting with the tens or hundreds required by full diffusion samplers.

# V  Datasets

## V.1  Multi-scale Flow Datasets

### Data Processing

Following the dataset generation procedure of Herde et al. Herde et al. (2024), the Richtmyer–Meshkov ensemble is created by imposing a randomized sinusoidal perturbation on a two-fluid interface and driving it with a planar shock via prescribed pressure jumps. For the CloudShock and ShearFlow benchmarks, we follow the GenCFD mesh-generation and solver setup of Molinaro et al. Molinaro et al. (2024), initializing CloudShock with concentric density perturbations and ShearFlow with orthogonal shear jets on adaptive Cartesian grids, and employing the same high-order finite-volume scheme and dissipation settings to ensure consistent numerical fidelity across both datasets.

**Overview.** We experiment on three paired-field benchmarks $(u_0, u_1)$:

- **Richtmyer–Meshkov (RM)**: $64\,000$ samples
- **Cloud-Shock (CS)**: $40\,000$ samples
- **Shear-Layer (SL)**: $79\,200$ samples

All datasets track the $u_0 \to S^t(u_0)|_{t=1}$ solution mapping from inputs to the evolved outputs at $t = 1$. The first two datasets monitor the evolution of density $(\rho)$, momentum components $(m_x, m_y)$, and energy respectively $(E)$. The shear-flow dataset monitors the velocity components of the flow $(u_x, u_y)$.

**Train/Validation Split.** For each dataset, we reserve 80% of the samples for training and 20% for validation.

**Macro–Micro Ensemble Evaluation (CS & SL).** To probe out-of-distribution generalization under small perturbations, we adopt a two-stage ensemble protocol:

1. *Macro-sampling:* select $M_{\text{macro}} = 10$ distinct base initial conditions.

2. *Micro-perturbation:* for each base, generate $M_{\text{micro}} = 1{,}000$ perturbed copies within a small radius.

3. *Metrics:* compute all performance measures (mean-field error $e_\mu$, standard-deviation error $e_\sigma$, average $W_1$, spectral agreement) by first averaging over each micro-ensemble, then averaging across the $M_{\text{macro}}$ cases.

**In-Distribution Evaluation (RM).** For the Richtmyer–Meshkov dataset, we additionally evaluate on a held-out test set drawn from the same distribution (no macro–micro perturbations). This allows us to study how deterministic and probabilistic models scale with training set size under standard, in-distribution conditions.

### V.2  Preprocessing and Data Organization

**Data Processing**

Before training, we compute and store global, channel-wise statistics over the entire training dataset. Concretely, for each physical variable $c$ we calculate

$$\mu_c = \frac{1}{N_{\text{train}} \, H \, W \, [D]} \sum_{i=1}^{N_{\text{train}}} \sum_{x,y,[z]} u_c^{(i)}(x, y, [z], t_0),$$

$$\sigma_c = \sqrt{\frac{1}{N_{\text{train}} \, H \, W \, [D]} \sum_{i=1}^{N_{\text{train}}} \sum_{x,y,[z]} \left( u_c^{(i)}(x, y, [z], t_0) - \mu_c \right)^2}.$$

where $N_{\text{train}}$ is the number of training samples, $H \times W \, [\times D]$ the spatial grid size, and $u_c(x, y, [z], t_0)$ the initial field for channel $c$. We average over all spatial locations to yield a single mean $\mu_c$ and standard deviation $\sigma_c$ per channel. The same statistics are also computed over the final-time fields $u_c(t_f)$, producing $\mu_c'$ and $\sigma_c'$ for the output channels. Before training, we compute and store global, channel-wise statistics over the entire training dataset. Concretely, for each physical variable $c$ we calculate

$$\mu_c = \frac{1}{N_{\text{train}} \, H \, W \, [D]} \sum_{i=1}^{N_{\text{train}}} \sum_{x,y,[z]} u_c^{(i)}(x, y, [z], t_0),$$

$$\sigma_c = \sqrt{\frac{1}{N_{\text{train}} \, H \, W \, [D]} \sum_{i=1}^{N_{\text{train}}} \sum_{x,y,[z]} \left( u_c^{(i)}(x, y, [z], t_0) - \mu_c \right)^2},$$

where $N_{\text{train}}$ is the number of training samples, $H \times W \, [\times D]$ the spatial grid size, and $u_c(x, y, [z], t_0)$ the initial field for channel $c$. We average over all spatial locations to yield a single mean $\mu_c$ and standard deviation $\sigma_c$ per channel. The same statistics are also computed over the final-time fields $u_c(t_f)$, producing $\mu_c'$ and $\sigma_c'$ for the output channels.

During both training and evaluation, each input field $u_c$ is standardized via

$$\tilde{u}_c = \frac{u_c \ - \ \mu_c}{\sigma_c + 10^{-16}}, \qquad \tilde{v}_c = \frac{v_c \ - \ \mu_c'}{\sigma_c' + 10^{-16}},$$

where $u_c$ and $v_c$ denote the initial and target fields, respectively. We then concatenate $\{\tilde{u}_c\}$ and $\{\tilde{v}_c\}$ along the channel axis before feeding them to the network. Because we always apply the same pre-computed statistics at test time, no information from the evaluation set ever influences these normalization parameters. where $u_c$ and $v_c$ denote the initial and target fields, respectively. We then concatenate $\{\tilde{u}_c\}$ and $\{\tilde{v}_c\}$ along the channel axis before feeding them to the network. Because we always apply the same pre-computed statistics at test time, no information from the evaluation set ever influences these normalization parameters.

**Test-time ensemble perturbation (evaluation only).**  We adopt the same testing setup proposed in *GenCFD* Molinaro et al. (2024). To evaluate how well our model captures the *distribution* of solutions $u(t)$ arising from a fixed, chaotic initial field $\bar{u}$, we generate a small perturbed ensemble around $\bar{u}$ and evolve each member with a high-fidelity PDE solver—*but only at evaluation time.* Specifically:

1. **Micro-ensemble generation.** Around the test initial condition $\bar{u}$, draw $M_{\text{micro}}$ perturbed copies $\{\bar{u}_j\}_{j=1}^{M_{\text{micro}}}$ by sampling uniformly in a ball of radius $\varepsilon$ centered at $\bar{u}$.

2. **Reference propagation.** Integrate each perturbed field $\bar{u}_j$ forward to time $t$ using the reference solver, producing end-states $\{u_j(t)\}$.

3. **Empirical conditional law.** Form the empirical measure

$$\hat{P}_t(\,\cdot\mid\bar{u}) \;=\; \frac{1}{M_{\text{micro}}} \sum_{j=1}^{M_{\text{micro}}} \delta_{u_j(t)},$$

which approximates the true chaotic conditional law $P_t(\,\cdot\mid\bar{u})$.

When the input distribution itself is non-degenerate, one would first draw $M_{\text{macro}}$ base fields from that distribution and then apply the micro-ensemble procedure to each. For our Dirac initial-condition tests we set $M_{\text{macro}} = 1$.

**Training vs. evaluation.**  During training the model only ever sees independent pairs $(u_0, u_1)$—one target per input—and never observes any ensemble. The above ensemble perturbation is used *only* to construct a ground-truth distribution at test time.

## W    Models and Baselines

We tested our method against four other baselines, of which two (GenCFD and its FNO-conditioned variant) are diffusion-based algorithms of the same kind. The other two rely on traditional operator learning, with the UViT baseline also serving as an ablation that quantifies the gain from adding diffusion.

**Shared Backbone.** All UNet-based models (ReFlow, GenCFD, GenCFD ∘ FNO, and UViT) use the *identical* UViT backbone specified in Table 6: channels $(128, 256, 256)$, 3 resolution levels, 4 blocks per level, 8 attention heads — approximately **5M trainable parameters** in every case. The architecture is illustrated schematically in Figure 7.

### GenCFD

GenCFD Molinaro et al. (2024) is an end-to-end conditional score-based diffusion model that directly learns the mapping from an input flow field $u_0$ to the target field $u_1$. It uses the same UViT backbone described in Table 6, with noise levels $\sigma_\tau$ corresponding to the standard deviation of the added Gaussian perturbation, in contrast to our ReFlow model which evolves over a rectified diffusion time $\tau \in [0, 1]$. Common choices for noise schedulers include exponential and tangent formulations. In our case, we consistently adopted an exponential noise schedule, as it yielded the best results across all datasets and metrics reported. In all GenCFD models, we opted for a variance-exploding (VE) formulation throughout. During training we minimize the denoising score-matching loss over $(u_0, u_1)$ pairs sampled uniformly in $\tau \in [0, 1]$, using Adam with initial learning rate $3 \times 10^{-4}$ (cosine decay), batch size 16, and EMA decay 0.9999. We applied denoiser preconditioning and used uniform weighting across noise levels. At inference we solve the corresponding SDE via an Euler–Maruyama scheme with 128 discretization steps, and incorporate reconstruction guidance to condition on $u_0$ so that we recover the conditional posterior measure $p(u_1|u_0)$.

### GenCFD ∘ FNO

In this hybrid approach, a Fourier Neural Operator (FNO) Li et al. (2020a) is first trained under an $\ell_2$ loss to predict $u_1$ from $u_0$. Its output $\hat{u}_1^{\text{FNO}}$ is concatenated channel-wise with $u_0$ and fed into the GenCFD score network at both train and test time. All other architectural and optimization settings (backbone, scheduler, SDE sampler) remain identical to GenCFD, allowing the FNO to provide fast low-frequency priors while the diffusion stage refines fine-scale turbulent features.

**Custom implementation.** This schematic closely parallels the pipeline of Oommen et al. (2024), but with two key distinctions. First, we fully replace both the diffusion backbone and its denoising stages with GenCFD. Second, and most importantly, we condition not only on the FNO's coarse solution but also on the original high-resolution initial condition, ensuring that fine-scale structures are not lost.

### FNO

Our FNO baseline follows Li *et al.* Li et al. (2020a) and is implemented in PyTorch. Each spatial location of the input field $u_0$ is lifted from $C_{\text{in}}$ to 256 channels via a two-layer MLP with a SiLU activation, then projected down to a 128-channel hidden representation. This is followed by four `FnoResBlock`s: in each block, the hidden features undergo a Conditional LayerNorm (time embedding size 128), SiLU, and two spectral convolutions (`SpectralConv`) with $num\_modes = (24, 24)$, combined through a learnable "soft-gate" residual skip. Finally, a two-layer projection MLP ($128 \to 256 \to C_{\text{out}}$, with SiLU in between) produces the output field $\hat{u}_1$. We train for 100k iterations minimizing $\|u_1 - \hat{u}_1\|_2^2$ with Adam (learning rate $10^{-3}$, batch size 16), and perform inference in one forward pass.

### UViT

Our UViT surrogate Saharia et al. (2022) uses the identical UNet2D backbone of Table 6, injecting time embeddings and employing 8-head multi-head attention at the bottleneck. It is trained deterministically with MSE loss on $(u_0, u_1)$, using Adam at $3 \times 10^{-4}$, batch size 16, for 100k iterations (EMA 0.9999). For multi-step forecasting we roll out autoregressively. This ablates the diffusion component while matching all other design choices.

### Baseline Model Summary

Table 8 summarizes key architectural settings for all models. These configurations were selected to reflect the strongest performance achievable within a shared training budget of up to 120,000 iterations, as used in the quantitative comparison reported in Table 1.

**Padding and boundary conditions.** Each dataset required padding choices tailored to its physical boundary conditions. SL and RM, which exhibit periodic boundaries, use circular padding in all convolutional layers. In contrast, CS features non-periodic boundaries and is trained with standard zero padding. These choices apply to all UNet-based architectures except ReFlow, which uniformly uses zero padding across all datasets.

1. **Micro-ensemble generation.** Around the test initial condition $\bar{u}$, draw $M_{\text{micro}}$ perturbed copies $\{\bar{u}_j\}_{j=1}^{M_{\text{micro}}}$ by sampling uniformly in a ball of radius $\varepsilon$ centered at $\bar{u}$.

2. **Reference propagation.** Integrate each perturbed field $\bar{u}_j$ forward to time $t$ using the reference solver, producing end-states $\{u_j(t)\}$.

3. **Empirical conditional law.** Form the empirical measure

$$\hat{P}_t(\,\cdot\mid\bar{u}) \;=\; \frac{1}{M_{\text{micro}}} \sum_{j=1}^{M_{\text{micro}}} \delta_{u_j(t)},$$

which approximates the true chaotic conditional law $P_t(\,\cdot\mid\bar{u})$.

When the input distribution itself is non-degenerate, one would first draw $M_{\mathrm{macro}}$ base fields from that distribution and then apply the micro-ensemble procedure to each. For our Dirac initial-condition tests we set $M_{\mathrm{macro}} = 1$.

**Training vs. evaluation.** During training the model only ever sees independent pairs $(u_0, u_1)$—one target per input—and never observes any ensemble. The above ensemble perturbation is used *only* to construct a ground-truth distribution at test time.

## X  Models and baselines

We tested our method against 4 other baselines, out of which 2 (namely GenCFD and its FNO-conditioned variant) are diffusion-based algorithms of the same kind. The other two baselines rely on traditional operator learning setup, with the UViT baseline satisfying also the purpose of an ablation study that quantifies the gain obtained by adding diffusion on top.

**Shared Backbone**. We stress that for GenCFD, GenCFD ∘ FNO and UViT we use the exact same UViT backbone architecture outlined in the earlier parameterization of our rectified flow as in Table 6 for the sake of consistency. The architecture is further illustrated schematically in Figure 7, which shows the UNet-based design in detail.

### GenCFD

GenCFD Molinaro et al. (2024) is an end-to-end conditional score-based diffusion model that directly learns the mapping from an input flow field $u_0$ to the target field $u_1$. It uses the same UViT backbone described in Table 6, with noise levels $\sigma_\tau$ corresponding to the standard deviation of the added Gaussian perturbation, in contrast to our ReFlow model which evolves over a rectified diffusion time $\tau \in [0, 1]$. Common choices for noise schedulers include exponential and tangent formulations. In our case, we consistently adopted an exponential noise schedule, as it yielded the best results across all datasets and metrics reported. For score-based diffusion models, either variance-exploding (VE) or variance-preserving (VP) formulations are typically used. In all GenCFD models, we opted for the VE setting throughout. During training we minimize the denoising score-matching loss over $(u_0, u_1)$ pairs sampled uniformly in $\tau \in [0, 1]$, using Adam with initial learning rate $3 \times 10^{-4}$ (cosine decay), batch size 16, and EMA decay 0.9999. As is common in score-based diffusion models, we applied denoiser preconditioning and used uniform weighting across noise levels. At inference we solve the corresponding SDE (via an Euler-Maruyama scheme with discretization 128 steps) and incorporate reconstruction guidance to condition on $u_0$ so that we recover the conditional posterior measure $p(u_1|u_0)$.

### GenCFD ∘ FNO

In this hybrid approach, a Fourier Neural Operator (FNO) Li et al. (2020a) is first trained under an $\ell_2$ loss to predict $u_1$ from $u_0$. Its output $\hat{u}_1^{\mathrm{FNO}}$ is concatenated channel-wise with $u_0$ and fed into the GenCFD score network at both train and test time. All other architectural and optimization settings (backbone, scheduler, SDE sampler) remain identical to GenCFD, allowing the FNO to provide fast low-frequency priors while the diffusion stage refines fine-scale turbulent features.

**Custom implementation.** This schematic closely parallels the pipeline of Oommen et al. (2024), but with two key distinctions. First, we fully replace both the diffusion backbone and its denoising stages with GenCFD. Second, and most important, we condition not only on the FNO's coarse solution but also on the original high-resolution initial condition. This ensures that our model retains fine-scale structures that would otherwise be lost if we relied solely on the FNO predictions.

## FNO

Our FNO baseline follows Li *et al.* Li et al. (2020a) and is implemented in PyTorch. First, each spatial location of the input field $u_0$ is lifted from $C_{\text{in}}$ to 256 channels via a two-layer MLP with a SiLU activation, then projected down to a 128-channel hidden representation. This is followed by four `FnoResBlock`s: in each block, the hidden features undergo a Conditional LayerNorm (time embedding size 128), SiLU, and two spectral convolutions (`SpectralConv`) with $num\_modes = (24, 24)$, combined through a learnable "soft-gate" residual skip. Finally, a two-layer projection MLP ($128 \to 256 \to C_{\text{out}}$, with SiLU in between) produces the output field $\hat{u}_1$. We train for 100k iterations minimizing $\|u_1 - \hat{u}_1\|_2^2$ with Adam (learning rate $10^{-3}$, batch size 16), and perform inference in one forward pass—no diffusion or autoregression is used.

## UViT

Our UViT surrogate Saharia et al. (2022) uses the identical UNet2D backbone of Table 6, injecting time embeddings and employing 8-head multi-head attention at the bottleneck. It is trained deterministically with MSE loss on $(u_0, u_1)$, using Adam at $3 \times 10^{-4}$, batch size 16, for 100 k iterations (EMA 0.9999). For multi-step forecasting we roll out autoregressively, feeding each prediction back as the next input. This ablates out the diffusion component while matching all other design choices.

### Baseline Model Summary and Implementation Setup

Table 8 summarizes key architectural settings for all baseline models considered in this work. These configurations were selected to reflect the strongest performance achievable within a shared training budget of up to 120,000 iterations, as used in the quantitative comparison reported in Table 1.

**Padding and boundary conditions.** Each dataset required padding choices tailored to its physical boundary conditions. SL and RM, which exhibit periodic boundaries, use circular padding in all convolutional layers. This significantly improved the performance of the diffusion-based models. In contrast, CS features non-periodic boundaries and is thus trained with standard zero padding. These padding choices apply to all UNet-based architectures except ReFlow, which uniformly uses zero padding across all datasets regardless of boundary conditions.

Table 7: Summary of architectural depth and approximated parameter count for each model evaluated. All UNet-based models (ReFlow, GenCFD, GenCFD ∘ FNO, and UViT) share a consistent backbone design to ensure consistency across diffusion and non-diffusion baselines, while the FNO baseline uses a structurally different architecture. These configurations reflect the best-performing settings under a training budget of up to 120,000 iterations, as used in the statistical comparisons reported in Table 1.

| Model | # Levels | # Blocks | # Params | Noise Schedule | Diffusion Scheme |
|---|---|---|---|---|---|
| ReFlow | 3 | 4 | 22M | uniform | rectified continuous time variable $t \in [0, 1]$ |
| GenCFD | 2 | 4 | 5M | exponential | variance-exploding |
| GenCFD ∘ FNO | 2 | 4 | 5M | exponential | variance-exploding |
| UViT | 2 | 4 | 5M | — | — |
| FNO | — | 4 | 11M | — | — |

Table 8: Summary of architectural depth and parameter count for each model. All UNet-based models share a consistent backbone design — channels $(128, 256, 256)$, 3 levels, 4 blocks/level, 8 attention heads — yielding $\approx 5\mathrm{M}$ parameters each. The FNO baseline uses a structurally different architecture.

| Model | # Levels | # Blocks | # Params | Noise Schedule | Diffusion Scheme |
|---|---|---|---|---|---|
| ReFlow | 3 | 4 | 5M | uniform | rectified continuous time variable $\tau \in [0, 1]$ |
| GenCFD | 3 | 4 | 5M | exponential | variance-exploding |
| GenCFD ∘ FNO | 3 | 4 | 5M | exponential | variance-exploding |
| UViT | 3 | 4 | 5M | — | — |
| FNO | — | 4 | 11M | — | — |

## Y  Results

### Y.1  Performance Metrics

## Z  Results

### Z.1  Performance Metrics

To compare our generated ensembles against the reference Monte Carlo samples, we employ three complementary measures:

- **Mean-field error.** Let $\mu_{\mathrm{ref}}(x)$ and $\mu_{\mathrm{model}}(x)$ denote the pointwise spatial means of the reference and model ensembles, respectively. We measure their discrepancy by the $L^2$-norm

$$e_\mu = \left\| \mu_{\mathrm{ref}} - \mu_{\mathrm{model}} \right\|_2.$$

- **Standard-deviation error.** Similarly, let $\sigma_{\mathrm{ref}}(x)$ and $\sigma_{\mathrm{model}}(x)$ be the pointwise standard deviations. We therefore compute

$$e_\sigma = \left\| \sigma_{\mathrm{ref}} - \sigma_{\mathrm{model}} \right\|_2,$$

  Both metrics are reported after normalization by the $L^2$ norm of the ground truth.

- **Average 1-Wasserstein distance.** For a fixed initial condition $u_0$, let $\{u_{\mathrm{ref}}^{(j)}(x)\}_{j=1}^N$ and $\{u_{\mathrm{model}}^{(j)}(x)\}_{j=1}^N$ be the ensembles of final-time values produced by the reference solver and our model, respectively. Since these fields are discretized on $M$ spatial points $\{x_i\}_{i=1}^M$, we obtain two empirical 1D distributions at each $x_i$. Denoting their inverse CDFs by $F_{\mathrm{ref}}^{-1}(\cdot\,; x_i)$ and $F_{\mathrm{model}}^{-1}(\cdot\,; x_i)$, the pointwise Wasserstein-1 distance is

$$W_1\big(p_{\mathrm{ref}}(\cdot \mid x_i),\, p_{\mathrm{model}}(\cdot \mid x_i)\big) = \int_0^1 \big| F_{\mathrm{ref}}^{-1}(q; x_i) - F_{\mathrm{model}}^{-1}(q; x_i) \big|\, \mathrm{d}q.$$

  We then report the spatial average

$$\overline{W}_1 = \frac{1}{M} \sum_{i=1}^M W_1\big(p_{\mathrm{ref}}(\cdot \mid x_i),\, p_{\mathrm{model}}(\cdot \mid x_i)\big).$$

**Energy spectra.** Finally, to assess how well different scales are captured, we compute the discrete energy spectrum of each velocity field. Given a sample $u(x)$ on a $d$-dimensional periodic grid with spacing $\Delta$, let $\widehat{u}_k$

be its Fourier coefficient at integer wavevector $k \in \mathbb{Z}^d$. We bin modes by their $\ell_1$ radius $|k|_1 = k_1 + \cdots + k_d$, defining

$$E_r = \frac{\Delta^d}{2} \sum_{\substack{k \in \mathbb{Z}^d \\ |k|_1 = r}} \|\widehat{u}_k\|^2, \quad r = 0, 1, 2, \ldots$$

and compare the ensemble-average spectra of reference and model. Our plots show $E_r$ versus $r$ on log–log axes to highlight scale-by-scale agreement.

- **Mean-field error.** Let $\mu_{\mathrm{ref}}(x)$ and $\mu_{\mathrm{model}}(x)$ denote the pointwise spatial means of the reference and model ensembles, respectively. We measure their discrepancy by the $L^2$-norm

$$e_\mu = \left\| \mu_{\mathrm{ref}} - \mu_{\mathrm{model}} \right\|_2.$$

- **Standard-deviation error.** Similarly, let $\sigma_{\mathrm{ref}}(x)$ and $\sigma_{\mathrm{model}}(x)$ be the pointwise standard deviations:

$$e_\sigma = \left\| \sigma_{\mathrm{ref}} - \sigma_{\mathrm{model}} \right\|_2.$$

Both metrics are reported after normalization by the $L^2$ norm of the ground truth.

- **Average 1-Wasserstein distance.** For a fixed initial condition $u_0$, let $\{u_{\mathrm{ref}}^{(j)}(x)\}_{j=1}^N$ and $\{u_{\mathrm{model}}^{(j)}(x)\}_{j=1}^N$ be the ensembles of final-time values. Since these fields are discretized on $M$ spatial points $\{x_i\}_{i=1}^M$, we obtain two empirical 1D distributions at each $x_i$. Denoting their inverse CDFs by $F_{\mathrm{ref}}^{-1}(\cdot\,;x_i)$ and $F_{\mathrm{model}}^{-1}(\cdot\,;x_i)$, the pointwise Wasserstein-1 distance is

$$W_1\big(p_{\mathrm{ref}}(\cdot \mid x_i),\, p_{\mathrm{model}}(\cdot \mid x_i)\big) = \int_0^1 \big| F_{\mathrm{ref}}^{-1}(q; x_i) - F_{\mathrm{model}}^{-1}(q; x_i) \big| \, \mathrm{d}q,$$

and we report the spatial average $\overline{W}_1 = \frac{1}{M} \sum_{i=1}^M W_1\big(p_{\mathrm{ref}}(\cdot \mid x_i),\, p_{\mathrm{model}}(\cdot \mid x_i)\big)$.

**Energy spectra.** To assess how well different scales are captured, we compute the discrete energy spectrum of each velocity field. Given a sample $u(x)$ on a $d$-dimensional periodic grid with spacing $\Delta$, let $\widehat{u}_k$ be its Fourier coefficient at integer wavevector $k \in \mathbb{Z}^d$. We bin modes by their $\ell_1$ radius $|k|_1 = k_1 + \cdots + k_d$, defining

$$E_r = \frac{\Delta^d}{2} \sum_{\substack{k \in \mathbb{Z}^d \\ |k|_1 = r}} \|\widehat{u}_k\|^2, \quad r = 0, 1, 2, \ldots$$

and compare the ensemble-average spectra of reference and model on log–log axes.

## Z.2 Metric Variability Across Sampling Seeds

## Z.3 Training Efficiency Observations

To assess training efficiency, we compare ReFlow with GenCFD. For fairness, we use a GenCFD variant with the same setup and parameter count (22M), matching the three-level UViT architecture of ReFlow instead of its standard lightweight configuration (5M). Both models were trained for up to 160,000 iterations with a batch size of 16.

Figure 9 summarizes performance over the training trajectory. At approximately 100,000 steps, ReFlow consistently outperforms GenCFD across all key metrics: relative $L^2$ error in the mean ($e_\mu$), relative $L^2$ error in the standard deviation ($e_\sigma$), and the average pointwise Wasserstein-1 (W1) distance—evaluated for both $u_x$ and $u_y$ velocity components. Notably, the $y$-axis uses a logarithmic scale to emphasize differences in error magnitude across training steps.

Across all metrics, ReFlow begins to outperform GenCFD at around 100,000 training steps and continues to improve at a sharper rate. While neither model reaches full convergence within 160,000 iterations, ReFlow

consistently exhibits lower errors and more favorable metric trajectories in later stages of training. These results support the observation that ReFlow is more training-efficient within a fixed compute budget and ultimately achieves stronger generalization performance in this setting.

To further probe the long-term capabilities of GenCFD, we extended its training to 600,000 iterations and checked whether it eventually surpasses ReFlow's performance at its final recorded checkpoint (150,000 steps). Table 14 summarizes the earliest training steps at which GenCFD overtakes ReFlow for each evaluation metric. While GenCFD does catch up and exceed ReFlow in several cases, it never surpasses ReFlow on the Wasserstein-1 distance for $u_y$ within the training horizon considered. To quantify sampling variance, we repeated each evaluation with five independent random-noise seeds. Table 10 reports mean $\pm$ std. The relative standard deviation is below 0.5% for all $e_\mu$ and $e_\sigma$ entries, and below 0.1% for all $\overline{W}_1$ entries, confirming that the results in Table 1 are highly stable with respect to stochastic sampling.

Table 9: Number of training iterations at which GenCFD surpasses ReFlow's performance at 150,000 iterations. If not surpassed, indicated by "—".

| Metric | GenCFD Iteration | GenCFD Value | ReFlow Value @ 150,000 iter. |
|---|---|---|---|
| $u_x$ Mean Error ($e_\mu$) | 280,000 | $3.33 \times 10^{-2}$ | $3.45 \times 10^{-2}$ |
| $u_y$ Mean Error ($e_\mu$) | 400,000 | $1.70 \times 10^{-1}$ | $1.88 \times 10^{-1}$ |
| $u_x$ Std Error ($e_\sigma$) | 400,000 | $6.48 \times 10^{-2}$ | $7.24 \times 10^{-2}$ |
| $u_y$ Std Error ($e_\sigma$) | 340,000 | $7.91 \times 10^{-2}$ | $7.97 \times 10^{-2}$ |
| $u_x$ Wasserstein-1 ($W_1$) | 200,000 | $3.89 \times 10^{-2}$ | $3.95 \times 10^{-2}$ |
| $u_y$ Wasserstein-1 ($W_1$) | — | — | $4.11 \times 10^{-2}$ |

Table 10: ReFlow metric variability across 5 independent sampling seeds (mean $\pm$ std).

| Dataset | Variable | $e_\mu$ | $e_\sigma$ | $\overline{W}_1$ |
|---|---|---|---|---|
| ShearLayer2D | $u_x$ | $0.0340 \pm 0.0001$ | $0.0716 \pm 0.0002$ | $(1.76 \pm 0.003) \times 10^{-3}$ |
| | $u_y$ | $0.1893 \pm 0.0010$ | $0.0776 \pm 0.0003$ | $(1.41 \pm 0.001) \times 10^{-3}$ |
| CloudShock2D | $\rho$ | $0.0468 \pm 0.0001$ | $0.0999 \pm 0.0002$ | $(1.14 \pm 0.001) \times 10^{-3}$ |
| | $m_x$ | $0.0317 \pm 0.0001$ | $0.0717 \pm 0.0002$ | $(1.23 \pm 0.001) \times 10^{-3}$ |
| | $m_y$ | $0.0392 \pm 0.0001$ | $0.0812 \pm 0.0002$ | $(1.39 \pm 0.001) \times 10^{-3}$ |
| | $E$ | $0.0138 \pm 0.00002$ | $0.0576 \pm 0.0001$ | $(1.50 \pm 0.001) \times 10^{-3}$ |

### Z.4 Noise Schedule Sensitivity

We evaluated nine inference-time noise schedules — `uniform`, `log-uniform`, `cos-map`, `exponential`, `tangent`, `quadratic`, `sqrt`, `sigmoid`, and `linear-beta` — on both ShearLayer2D and CloudShock2D. The results are shown in Table 11.

### Z.5 Experimental Advantages of Straightness

This subsection presents empirical evidence that the "rectified" trajectories generated by our Rectified Flow model (ReFlow) enable faster convergence and yield higher-fidelity reconstructions compared to the baseline GenCFD diffusion approach.

The learned rectified velocity field produces trajectories sufficiently straight that the choice of inference-time schedule has no measurable effect on sample quality. This invariance is a direct consequence of the straightening bias: once the velocity field is nearly straight, the time-discretization grid is irrelevant for integration accuracy. This contrasts with score-based diffusion, where schedule choice critically affects performance because the learned score is highly curved near $\tau = 0$.

### Z.6 ODE Integrator Comparison

Figure 8: **Training efficiency comparison.** Performance of ReFlow and GenCFD on the Macro-Micro SL ensemble dataset evaluated at multiple training checkpoints. Metrics match those used in the main text: relative $L^2$ error of the mean ($e_\mu$) and standard deviation ($e_\sigma$), and the average 1-point Wasserstein-1 distance (W1), computed for both velocity components ($u_x$, $u_y$). The $y$-axis uses a logarithmic scale, while the $x$-axis (training iteration) is linear.

Table 11: ReFlow performance across 9 inference-time noise schedules. All 9 schedules produce identical metrics; values shown are the common result.

| Dataset | Variable | $e_\mu$ | $e_\sigma$ | $\overline{W}_1$ |
|---------|----------|---------|------------|------------------|
| ShearLayer2D | $u_x$ | 0.1153 | 0.3674 | 0.0022 |
| | $u_y$ | 0.2346 | 0.3820 | 0.0021 |
| CloudShock2D | $\rho$ | 0.1525 | 0.2320 | 0.0011 |
| | $m_x$ | 0.1083 | 0.2034 | 0.0012 |
| | $m_y$ | 0.1039 | 0.2077 | 0.0015 |
| | $E$ | 0.0452 | 0.1852 | 0.0015 |

**Evaluation settings.** We use the CloudShock dataset throughout for exposition purposes. However, we stress that the same results hold across datasets. For each initial condition, both ReFlow and GenCFD are allotted $T = 10$ diffusion steps over normalized **diffusion time** $\tau \in [0, 1]$. We record the model outputs at five evenly spaced timesteps $t = \{0.0, 0.25, 0.50, 0.75, 1.0\}$ and analyze:

- *Trajectory inpainting* of the density field $\rho$.

- *Latent-Space Trajectory Visualization via PCA* via PCA.

- *Per-Sample Average Error Evolution*: average MSE across physical channels.

- *Evolution of the Energy Spectrum*: radial power-spectrum of energy $E$ as inpaintig progresses.

All other components (backbone, noise schedule, batch size) are held equal for fair comparison. Tables 12 and 13 compare fixed-step Euler, second- and fourth-order Runge–Kutta (RK2, RK4), and the adaptive curvature-aware sampler on ShearLayer2D and CloudShock2D respectively. Times are measured on a single NVIDIA Quadro RTX 6000.

**Why higher-order integrators do not outperform Euler.** We are not integrating an exact physical ODE with a known vector field; we are integrating a *learned* generative ODE whose velocity field $v_\theta$ carries finite approximation error. A higher-order solver more faithfully follows local imperfections of the learned field, which can move samples farther from the data manifold. By contrast, the first-order Euler method has a mild regularizing effect that tends to keep trajectories in high-density regions. The practical gain therefore comes not from solver order but from the *adaptive curvature-aware sampler*, which selectively refines steps where the learned velocity curves — achieving the lowest absolute error at the fewest NFE.

Table 12: ODE integrator comparison on **ShearLayer2D** (OOD). Error = mean relative $L^2$ over $u_x, u_y$; Cost×Err = NFE × Error.

| Method | Steps | NFE | Error $\pm$ Std | Cost×Err | Time (ms) |
|--------|-------|-----|------------------|----------|-----------|
| Euler | 8 | 8 | $0.2359 \pm 0.053$ | 1.89 | 161 |
| Euler | 16 | 16 | $0.2475 \pm 0.055$ | 3.96 | 355 |
| Euler | 32 | 32 | $0.2541 \pm 0.056$ | 8.13 | 745 |
| RK2 | 8 | 16 | $0.2603 \pm 0.057$ | 4.16 | 355 |
| RK4 | 8 | 32 | $0.2621 \pm 0.058$ | 8.39 | 745 |
| RK4 | 32 | 128 | $0.2616 \pm 0.058$ | 33.49 | 3083 |
| Adaptive-EMA | 10 | 10 | $0.2090 \pm 0.041$ | 2.09 | 448 |
| Adaptive-EMA | 13 | 13 | **0.1762** | **2.29** | 524 |

Across both datasets, RK4 at 32 NFE is strictly worse than Euler at 32 NFE. The adaptive sampler achieves the lowest absolute error at 10–13 NFE, well below the budget of any fixed-step baseline. This is because error

Table 13: ODE integrator comparison on **CloudShock2D** (OOD). Same metrics as Table 12.

| Method | Steps | NFE | Error $\pm$ Std | Cost$\times$Err | Time (ms) |
|---|---|---|---|---|---|
| Euler | 8 | 8 | $0.2211 \pm 0.021$ | 1.77 | 150 |
| Euler | 16 | 16 | $0.2261 \pm 0.021$ | 3.62 | 330 |
| Euler | 32 | 32 | $0.2289 \pm 0.021$ | 7.32 | 694 |
| RK2 | 8 | 16 | $0.2319 \pm 0.021$ | 3.71 | 331 |
| RK4 | 8 | 32 | $0.2323 \pm 0.021$ | 7.43 | 693 |
| RK4 | 32 | 128 | $0.2322 \pm 0.021$ | 29.72 | 2873 |
| Adaptive-EMA | 11 | 11 | $0.2259 \pm 0.017$ | 2.48 | 440 |
| Adaptive-EMA | 13 | 13 | $\mathbf{0.2121 \pm 0.016}$ | **2.76** | 486 |

saturates quickly with NFE once the velocity field is sufficiently straight; additional steps in high-straightness regions yield no further benefit.

**Trajectory Inpainting**

We compare Rectified Flow (ReFlow) and GenCFD reconstructions of the density field $\rho$ over five normalized **diffusion** timesteps $t \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. ReFlow inpaints fine-scale features in far fewer steps, while GenCFD remains overly diffusive. The leftmost panel corresponds to the initial condition $u_0$ upon which both model are conditioned, while the following panels showcase the evolution of the model's output as diffusion time progresses.

## Z.7   Relation to ODE-Based Diffusion Samplers

A natural question is whether ReFlow's efficiency can be matched simply by applying a probability-flow ODE (PF-ODE) sampler — such as DPM-Solver or the Heun-based solver of Karras et al. — to the existing GenCFD score model. We address this directly.

PF-ODE methods accelerate sampling of a *fixed* learned score model; they do not change the learned dynamics. Our method trains a *different* conditional transport field $v_\theta$, whose objective promotes straighter trajectories in rectified time, yielding a smoother, less stiff field that can be integrated accurately in very few steps. The efficiency gain comes from *learning a straighter field*, not from choosing an ODE solver.

To verify this, we re-evaluated GenCFD using the PF-ODE with a second-order Heun solver at $4, 8, 16, 32, 64$, and 128 NFE. On ShearLayer2D at 128 NFE, PF-ODE was worse than the standard SDE sampler on both $e_\mu$ and $e_\sigma$, confirming that the stiffness of the score field — not the choice of solver — is the bottleneck for GenCFD. The rectified-flow velocity field learned by ReFlow is intrinsically less stiff, which is why it integrates accurately in 8–10 steps regardless of solver choice.

## Z.8   Training Efficiency Observations

To assess training efficiency, we compare ReFlow with GenCFD using a matched parameter count ($\approx$5M) and three-level UViT architecture. Both models were trained for up to 160,000 iterations with a batch size of 16.

Figure 9 summarizes performance over the training trajectory. At approximately 100,000 steps, ReFlow consistently outperforms GenCFD across all key metrics: $e_\mu$, $e_\sigma$, and $\overline{W}_1$ for both $u_x$ and $u_y$. The $y$-axis uses a logarithmic scale to emphasize differences in error magnitude.

To further probe the long-term capabilities of GenCFD, we extended its training to 600,000 iterations. Table 14 summarizes the earliest step at which GenCFD overtakes ReFlow's performance at 150,000 steps. While GenCFD catches up in several cases, it never surpasses ReFlow on $\overline{W}_1$ for $u_y$ within the training horizon considered.

Table 14: Number of training iterations at which GenCFD surpasses ReFlow's performance at 150,000 iterations. "—" indicates GenCFD never surpasses ReFlow within the training horizon.

| Metric | GenCFD Iteration | GenCFD Value | ReFlow @ 150k |
|---|---|---|---|
| $u_x$ Mean Error ($e_\mu$) | 280,000 | $3.33 \times 10^{-2}$ | $3.45 \times 10^{-2}$ |
| $u_y$ Mean Error ($e_\mu$) | 400,000 | $1.70 \times 10^{-1}$ | $1.88 \times 10^{-1}$ |
| $u_x$ Std Error ($e_\sigma$) | 400,000 | $6.48 \times 10^{-2}$ | $7.24 \times 10^{-2}$ |
| $u_y$ Std Error ($e_\sigma$) | 340,000 | $7.91 \times 10^{-2}$ | $7.97 \times 10^{-2}$ |
| $u_x$ Wasserstein-1 ($W_1$) | 200,000 | $3.89 \times 10^{-2}$ | $3.95 \times 10^{-2}$ |
| $u_y$ Wasserstein-1 ($W_1$) | — | — | $4.11 \times 10^{-2}$ |

Figure 9: **Training efficiency comparison.** Performance of ReFlow and GenCFD on the Macro-Micro SL ensemble dataset at multiple training checkpoints. Metrics: relative $L^2$ error of the mean ($e_\mu$) and standard deviation ($e_\sigma$), and the average 1-point Wasserstein-1 distance ($\overline{W}_1$), for both velocity components ($u_x$, $u_y$). The $y$-axis is logarithmic; the $x$-axis (training iteration) is linear.

## Z.9 Experimental Advantages of Straightness

This subsection presents empirical evidence that the rectified trajectories generated by ReFlow enable faster convergence and higher-fidelity reconstructions compared to GenCFD.

**Evaluation settings.** We use the CloudShock dataset throughout; the same results hold across datasets. For each initial condition, both ReFlow and GenCFD are allotted $T = 10$ diffusion steps over normalized diffusion time $\tau \in [0, 1]$. We record outputs at five evenly spaced timesteps $\tau \in \{0.0, 0.25, 0.50, 0.75, 1.0\}$ and analyze: trajectory inpainting of the density field $\rho$; latent-space trajectory visualization via PCA; per-sample average MSE evolution; and evolution of the energy spectrum. All other components (backbone, noise schedule, batch size) are held equal.

### Trajectory Inpainting

We compare ReFlow and GenCFD reconstructions of the density field $\rho$ over five normalized diffusion timesteps $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. ReFlow inpaints fine-scale features in far fewer steps, while GenCFD remains overly diffusive. The leftmost panel corresponds to the initial condition $u_0$ upon which both models are conditioned; the following panels show the evolution of the model output as diffusion time progresses.

Figure 10: Density trajectories for Sample 1: ReFlow (top) vs. GenCFD (bottom). ReFlow already recovers sharp shock fronts by diffusion time $t = 1.0$.

Figure 11: Density trajectories for Sample 1: ReFlow (top) vs. GenCFD (bottom). ReFlow recovers sharp shock fronts by diffusion time $\tau = 1.0$.

Figure 12: Density trajectories for Sample 2.

Figure 13: Density trajectories for Sample 2.

Figure 14: Density trajectories for Sample 3.

Figure 15: Density trajectories for Sample 3.

**Latent-Space Trajectory Visualization via PCA**

To quantify how directly each model moves through the data manifold, we flatten the $(H \times W \times C)$ field at each timestep into a single feature vector, stack all Rectified Flow and GenCFD vectors, fit a 3-component PCA, and then project each timestep into PC1/PC2/PC3. A straighter path indicates fewer diffusive detours.

**Latent-Space Trajectory Visualization via PCA**

To quantify how directly each model moves through the data manifold, we flatten the $(H \times W \times C)$ field at each timestep into a single feature vector, stack all ReFlow and GenCFD vectors, fit a 3-component PCA, and project each timestep into PC1/PC2/PC3. A straighter path indicates fewer diffusive detours. Because the ReFlow trajectory is much shorter in the projected space, it may visually appear as a tight cluster near the endpoint; this compactness is itself evidence of rectification — the model reaches its target in very few, nearly-collinear steps.

Figure 16: **3D PCA latent-space trajectories (Samples 1–6).** We project the flattened snapshots at each of $T$ timesteps into the top three PCA components. Rectified Flow (blue) consistently traces a straighter path than GenCFD (red), confirming its "rectified" evolution. Circles mark $t = 0$, squares mark $t = 1$, and intermediate timesteps are annotated.

To further illustrate the nature of each model's generative dynamics, we visualize single-sample generation trajectories from both models in a 2D PCA space for the RM dataset (Figure 19). For each physical channel $(\rho, m_x, m_y, p)$, we apply PCA to the full set of ground truth snapshots to define a common projection basis. We then overlay the generative trajectory of a single sample in this space. To contextualize the generated

dynamics, we add kernel density estimates (KDEs) showing the empirical data distribution in the same projected space.

ReFlow (top) again traces a straighter, more compact path over just 10 rectified steps, moving coherently along the data manifold. GenCFD (bottom), by contrast, uses 128 stochastic denoising steps and produces a more diffuse and nonlinear trajectory, often deviating from high-density regions of the ground truth distribution. While the PCA projection inherently reduces dimensional complexity, the consistent difference in shape and alignment supports the conclusion that ReFlow's rectified flow better preserves manifold structure and sample efficiency.

(a) Sample 1          (b) Sample 2          (c) Sample 3

(d) Sample 4          (e) Sample 5          (f) Sample 6

Figure 17: **3D PCA latent-space trajectories (Samples 1–6).** Flattened snapshots at each of $T$ timesteps projected into the top three PCA components. ReFlow (blue) consistently traces a straighter path than GenCFD (red). Circles mark $\tau = 0$, squares mark $\tau = 1$; intermediate timesteps are annotated.

To further illustrate generative dynamics, we visualize single-sample generation trajectories from both models in a 2D PCA space for the RM dataset (Figure 19). For each physical channel ($\rho$, $m_x$, $m_y$, $p$), we apply PCA to the full set of ground truth snapshots to define a common projection basis, then overlay the generative trajectory of a single sample. Kernel density estimates (KDEs) show the empirical data distribution in the same projected space. ReFlow (top) traces a straighter, more compact path over 10 rectified steps; GenCFD (bottom) uses 128 stochastic steps and produces a more diffuse, nonlinear trajectory.

Figure 18: **2D PCA latent-space trajectories.** We project the flattened velocity snapshots from the RM dataset into a 2D PCA space, computed independently for each channel ($\rho$, $m_x$, $m_y$, $p$) across all $T$ time steps. To visualize the underlying distribution of target fields, we apply kernel density estimation (KDE) per channel. The ReFlow model (top) evolves over 10 rectified time steps, producing visibly straighter and more structured trajectories compared to the score-based diffusion model GenCFD (bottom), which uses 128 stochastic steps. Although the projection into two principal components necessarily truncates the high-dimensional dynamics, the qualitative difference remains evident, illustrating the smoother and more directed progression learned by ReFlow.

Figure 19: **2D PCA latent-space trajectories.** Flattened velocity snapshots from the RM dataset projected into a 2D PCA space, computed independently per channel ($\rho$, $m_x$, $m_y$, $p$). KDE overlays show the distribution of target fields. ReFlow (top, 10 steps) evolves along straighter, more structured trajectories than GenCFD (bottom, 128 steps).

## Per-Sample Average Error Evolution

We compute the mean-squared error at each timestep $t$ and average across all $C$ channels:

$$\overline{\mathrm{MSE}}(t) = \frac{1}{C} \sum_{c=1}^{C} \mathrm{MSE}_c(t).$$

Figure 21 shows, for Samples 1–6, the log-scaled average MSE (left) and the normalized error $\overline{\mathrm{MSE}}(t)/\overline{\mathrm{MSE}}(0)$ (right). Rectified Flow (blue) consistently reduces error faster and to a lower residual than GenCFD (red).

## Per-Sample Average Error Evolution

We compute the mean-squared error at each timestep $\tau$ and average across all $C$ channels:

$$\overline{\mathrm{MSE}}(\tau) = \frac{1}{C} \sum_{c=1}^{C} \mathrm{MSE}_c(\tau).$$

Figure 21 shows, for Samples 1–6, the log-scaled average MSE (left half of each subfigure) and the normalized error $\overline{\mathrm{MSE}}(\tau)/\overline{\mathrm{MSE}}(0)$ (right half). ReFlow (blue) consistently reduces error faster and to a lower residual than GenCFD (red).

(a) Sample 1          (b) Sample 2

(c) Sample 3          (d) Sample 4

(e) Sample 5          (f) Sample 6

Figure 20: **Per-sample average MSE evolution.** Each subfigure plots, left half: $\log_{10} \overline{\mathrm{MSE}}(t)$; right half: $\overline{\mathrm{MSE}}(t)/\overline{\mathrm{MSE}}(0)$. Rectified Flow (blue) rapidly drives error down and keeps it orders of magnitude below GenCFD (red) across all samples.

Figure 21: **Per-sample average MSE evolution.** Left half: $\log_{10} \overline{\mathrm{MSE}}(\tau)$; right half: $\overline{\mathrm{MSE}}(\tau)/\overline{\mathrm{MSE}}(0)$. ReFlow (blue) rapidly drives error down and maintains it orders of magnitude below GenCFD (red) across all samples.

**Evolution of the Energy Spectrum**

We examine the 2D radial power spectrum of the energy field $E$ at five normalized diffusion times $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. Each figure below shows log–log power vs. wavenumber for Rectified Flow (blue), GenCFD (red), and the ground-truth target (black dashed), with inset log-MSE error annotations. The leftmost snapshot corresponds to the spectrum of the initial data $u_0$ upon which the model is conditioned. Subsequent panels track the spectral evolution of the model predictions, as diffusion time progresses.

**Evolution of the Energy Spectrum**

We examine the 2D radial power spectrum of the energy field $E$ at five normalized diffusion times $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. Each figure shows log–log power vs. wavenumber for ReFlow (blue), GenCFD (red), and the ground-truth target (black dashed), with inset log-MSE error annotations. The leftmost panel corresponds to the spectrum of the initial condition $u_0$; subsequent panels track spectral evolution as $\tau$ progresses.

Figure 22: Energy spectrum evolution for Sample 1. ReFlow (blue) outperforms GenCFD (red) in capturing high-wavenumber energy.

Figure 23: Energy spectrum evolution for Sample 2. ReFlow remains closer to the ground truth (dashed) than GenCFD throughout.

Figure 24: Energy spectrum evolution for Sample 3. Inset log-MSE annotations quantify ReFlow's advantage at each $\tau$.

Figure 25: Energy spectrum evolution for Sample 4. ReFlow's spectrum approaches the target as $\tau \to 1.0$.

Figure 26: Energy spectrum evolution for Sample 5. ReFlow's superior high-$k$ fidelity is evident throughout.

Figure 27: Energy spectrum evolution for Sample 6. ReFlow better captures the ground-truth spectrum's slope across all timesteps.

## Computational Considerations

All ReFlow models for 2D fluid-flow tasks use the network configuration in Table 6 and have approximately 5M trainable parameters with identical layer-wise dimensions. We ran each training job for 100,000 iterations on a single NVIDIA Quadro RTX 6000 (Driver 570.124.06, CUDA 12.8) in persistence mode. Resource utilization averaged over the full 100 h training window is reported in Table 16.

Figure 28: Energy spectrum evolution for Sample 2. ReFlow (blue) remains closer to the ground truth (dashed) than GenCFD (red).

Figure 29: Energy spectrum evolution for Sample 3. The inset log-MSE annotations quantify ReFlow's advantage at each $t$.

Figure 30: Energy spectrum evolution for Sample 4. ReFlow's spectrum (blue) gets closer to the target (dashed) as $\tau \rightarrow 1.0$.

Figure 31: Energy spectrum evolution for Sample 5. ReFlow's superior high-$k$ fidelity is evident throughout.

Figure 32: Energy spectrum evolution for Sample 6. ReFlow better captures the ground-truth spectrum's slope across all timesteps.

Table 15: Aggregate hardware utilization across all training runs.

| Metric | Range | Typical |
|---|---|---|
| GPU power draw (W) | 200–260 | 230 |
| GPU utilization (%) | 30–80 | 55 |
| GPU memory allocated (GB) | 12–17 | 15 |
| GPU temperature (°C) | 40–60 | 50 |
| Process GPU memory usage (%) | 60–80 | 70 |
| Process GPU memory access time (%) | 10–50 | 30 |
| Process CPU threads in use | 7 | 7 |
| System CPU utilization (per core, %) | 60–100 | 80 |
| Process memory in use (GB) | up to 50 | 25 |
| Disk I/O read (MB total) | up to $1.2 \times 10^6$ | $5 \times 10^5$ |
| Disk utilization (%) | 70–75 | 72 |
| Network traffic (bytes total) | $\approx 3 \times 10^{13}$ | $3 \times 10^{13}$ |

## Computational Considerations

Since all datasets are paired with models of identical size and the hardware envelope is effectively the same across runs, any observed performance differences are attributable to the sampling strategy (noise schedule, ODE steps) rather than to model-size or hardware variations. (Network traffic is due to Wandb logging.)

All of our ReFlow models for 2D fluid-flow tasks use the same network configuration summarized in Table 6 (channels $(128, 256, 256)$, downsample ratios $(2, 2, 2)$, 8 attention heads, dropout 0.1, batch size 16, etc.). Consequently, every model—regardless of dataset—has the same total parameter count (approximately 8–10M parameters) and identical layer-wise dimensions. We ran each training job for 100 000 iterations on a single NVIDIA Quadro RTX 6000 (Driver 570.124.06, CUDA 12.8) in persistence mode. Resource utilization averaged as follows over the full 100 h window: We explored architectures ranging from approximately 5M to 10M trainable parameters; across this range we observed no significant differences in final predictive performance or convergence behavior. All other hyperparameters were held fixed across comparisons, ensuring that differences in accuracy and runtime reflect only the conditioning and sampling strategies under study.

Table 16: Aggregate hardware utilization for all "usual-setup" runs.

| Metric | Range | Typical |
|---|---|---|
| GPU power draw (W) | 200–260 | 230 |
| GPU utilization (%) | 30–80 | 55 |
| GPU memory allocated (GB) | 12–17 | 15 |
| GPU temperature (°C) | 40–60 | 50 |
| Process GPU memory usage (%) | 60–80 | 70 |
| Process GPU memory access time (%) | 10–50 | 30 |
| Process CPU threads in use | 7 | 7 |
| System CPU utilization (per core, %) | 60–100 | 80 |
| Process memory in use (GB) | up to 50 | 25 |
| Disk I/O read (MB total) | up to $1.2 \times 10^6$ | $5 \times 10^5$ |
| Disk utilization (%) | 70–75 | 72 |
| Network traffic (bytes total) | $\approx 3 \times 10^{13}$ | $3 \times 10^{13}$ |

Since all datasets are paired with models of identical size and the hardware envelope (GPU power, memory, temperature, CPU threads, I/O) is effectively the same across runs, any observed performance differences are attributable to the sampling strategy (noise schedule, ODE steps) rather than to model-size or hardware variations (the network traffic is due to Wandb usage).

## Code and Data Availability

Prior to acceptance, we will make available all three datasets, the complete data-processing scripts, and a fully functional training and evaluation pipeline for ReFlow, including a model checkpoint that can be loaded and tested directly. A more comprehensive, user-friendly code release will follow shortly thereafter.

## Additional Visualizations

All experiments were run on a single NVIDIA Quadro RTX 6000 GPU (Driver 570.124.06, CUDA 12.8), operating in persistence mode.

**Test-time ensemble perturbation (evaluation only).** Following the protocol of *GenCFD* Molinaro et al. (2024), we construct small micro-ensembles around each test initial condition $\bar{u}$ by sampling $M_{\text{micro}}$ perturbed fields uniformly in an $\varepsilon$-ball centered at $\bar{u}$. Each perturbed member is advanced to evaluation time $t$ with a high-fidelity PDE solver to produce a reference ensemble $\{u_{\text{ref}}^{(j)}(t)\}_{j=1}^{M_{\text{micro}}}$. Our model generates a corresponding ensemble $\{u_{\text{model}}^{(j)}(t)\}_{j=1}^{M_{\text{micro}}}$ from the same perturbed inputs, but without ever observing ensembles during training. We compare these via $e_\mu$, $e_\sigma$, and $\overline{W}_1$ (see §Z).

Each model was trained for 100 000 iterations. We explored architectures ranging from approximately 5 million to 10 million trainable parameters; across this range we observed no significant differences i n final predictive performance or convergence behavior. All other hyperparameters (learning rate schedules, batch sizes, noise schedules, etc.) were held fixed when evaluated against each other, ensuring that differences in accuracy and runtime reflect only the conditioning and sampling strategies under study.

**Out-of-distribution testing (cloud-shock and shear-flow).** Because the micro-perturbations render each initial field slightly OOD, this evaluation probes generalization under small chaotic perturbations. Our ReFlow ensemble closely tracks the reference uncertainty and multiscale statistics, whereas deterministic baselines collapse to a single trajectory and fail to capture the conditional variability.

**Test-time ensemble perturbation (evaluation only).** Following the protocol of *GenCFD* Molinaro et al. (2024), we construct small "micro-ensembles" around each test initial condition $\bar{u}$ by sampling $M_{\text{micro}}$ perturbed fields uniformly in an $\varepsilon$–ball centered at $\bar{u}$. Each perturbed member is then advanced to the evaluation time $t$ with a high-fidelity PDE solver to produce a reference ensemble $\{u_{\text{ref}}^{(j)}(t)\}_{j=1}^{M_{\text{micro}}}$. Our model generates a corresponding ensemble $\{u_{\text{model}}^{(j)}(t)\}_{j=1}^{M_{\text{micro}}}$ from the same perturbed inputs, but without ever observing ensembles during training (which only uses independent pairs $(u_0, u_1)$). We compare these two ensembles via mean-field error $e_\mu$, standard-deviation error $e_\sigma$, and spatially averaged 1-Wasserstein distance $\overline{W}_1$ (see **SM** §Z). **In-distribution scaling (Richtmyer–Meshkov).** For the RM dataset, we additionally

study the effect of training set size on a held-out test set from the same distribution. Even deterministic approaches improve with more data, but still underperform on the micro-ensemble test, requiring significantly larger training sets to match ReFlow's accuracy and exhibiting poor calibration under small perturbations.

**Out-of-distribution testing (cloud–shock and shear-flow).** Because the micro-perturbations render each initial field slightly OOD, this evaluation probes the model's ability to generalize under small chaotic perturbations. In these tasks, our Rectified Flow ensemble closely tracks the reference uncertainty and

multiscale statistics, whereas deterministic baselines collapse to a single trajectory and fail to capture the conditional variability.

**In-distribution scaling (Richtmyer–Meshkov).** For the Richtmyer–Meshkov dataset, we additionally study the effect of training set size using a held-out test set from the same distribution. Here, even deterministic approaches improve with more data, but still underperform on the micro-ensemble test: they require significantly larger training sets to match ReFlow's accuracy and exhibit poor calibration under small perturbations.

In this appendix we provide a comprehensive set of qualitative comparisons between the baselines (GenCFD variants, UViT, FNO) models and our Rectified Flow (ReFlow) approach across three representative 2D fluid-flow benchmarks (Richtmyer–Meshkov, shear layer roll-up, and cloud-shock interaction). For each task we show: In this appendix we provide comprehensive qualitative comparisons between all baselines (GenCFD variants, UViT, FNO) and ReFlow across three 2D fluid-flow benchmarks. For each task we show:

- **Mean fields** Ensemble averages reveal how each deterministic model diffuses fine-scale features (UVit/FNO) versus perserving sharp interfaces (ReFlow, GenCFD variants).

- **Uncertainty maps** Per-pixel standard deviations illustrate whether uncertainty localizes in physically meaningful regions (e.g. shocks, shear interfaces) or remains overly diffuse.

- **Random samples** To qualitatively assess generative fidelity, we include representative random samples from ReFlow alongside outputs from selected baselines, specifically the deterministic FNO and the hybrid GenCFD ∘ FNO. The latter combines FNO's low-frequency structural prediction with GenCFD's generative modeling of fine-scale turbulence. This comparison highlights ReFlow's ability to produce realistic, high-resolution flow fields that preserve physical coherence across different scales.

- **Spectral & pointwise comparisons** (Fig. 36: Richtmyer–Meshkov global $E(k)$, local spectra, and pointwise density histograms; Fig. 39: Shear-layer global $u_x$ spectra and pointwise $u_x$ distributions; Fig. 43: Cloud–shock global $m_y$ spectra and pointwise energy distributions) — combined Fourier-space and histogram panels quantify multiscale fidelity and calibration of the predictive ensembles.

Together, these visualizations underscore ReFlow's ability to maintain sharper physical structures, produce better-calibrated uncertainties, and faithfully reproduce multiscale spectral statistics.

- **Mean fields.** Ensemble averages reveal how deterministic models (UViT/FNO) diffuse fine-scale features versus preserving sharp interfaces (ReFlow, GenCFD variants).

- **Uncertainty maps.** Per-pixel standard deviations illustrate whether uncertainty localizes in physically meaningful regions (shocks, shear interfaces) or remains overly diffuse.

- **Random samples.** Representative samples from ReFlow alongside the deterministic FNO and the hybrid GenCFD ∘ FNO, highlighting ReFlow's ability to produce realistic, high-resolution flow fields that preserve physical coherence across scales.

- **Spectral and pointwise comparisons.** (Fig. 36: RM global $E(k)$, local spectra, and pointwise density histograms; Fig. 39: SL global $u_x$ spectra and pointwise $u_x$ distributions; Fig. 43: CS global $m_y$ spectra and pointwise energy distributions.) Combined Fourier-space and histogram panels quantify multiscale fidelity and calibration.

Together, these visualizations underscore ReFlow's ability to maintain sharper physical structures, produce better-calibrated uncertainties, and faithfully reproduce multiscale spectral statistics.

Figure 35: **Richtmyer–Meshkov Individual Sample Comparison**: A representative random test sample from the Richtmyer–Meshkov dataset, visualized across all four physical channels ($\rho$, $m_x$, $m_y$, $p$). All models produce physically plausible results, with only little variation in fidelity to fine-scale structures. ReFlow offers the closest visual match to the ground truth, preserving coherent details and sharp interfaces. Notably, the GenCFD ○ FNO hybrid enhances spectral richness by reconstructing high-frequency features based on a low-frequency FNO prior, illustrating its capacity to recover sharper modes even when starting from a coarse prediction.

(a) UVit global $E(k)$.

(b) RF global $E(k)$.

(c) UVit local at $(120, 44)$.

(d) RF local at $(120, 44)$.

(e) UVit $\rho$ at $(60, 12)$, $W_1 = 0.0278$.

(f) RF $\rho$ at $(60, 12)$, $W_1 = 0.0005$.

Figure 36: Richtmyer–Meshkov: spectral and pointwise distribution comparisons between UVit and Rectified Flow.

(a) **mean-field** $\mu$ (b) **standard-deviation** $\sigma$

Figure 37: **Shear-Layer Mean and Standard Deviation Comparison**: Visualization of mean-field ($\mu$) and standard-deviation ($\sigma$) predictions for the Shear-Layer dataset across both velocity components ($u_x$, $u_y$). For each model, the left half shows the predicted mean fields and the right half shows per-pixel standard deviations. The top row contains the reference ground truth. Despite the reduced channel complexity of this

(a) FNO $E_{u_x}(r)$.

(b) RF $E_{u_x}(r)$.

(c) FNO $u_x$ at $(36, 8)$.

(d) RF $u_x$ at $(36, 8)$.

Figure 39: Shear-layer: global $u_x$ spectra and pointwise $u_x$ distributions.

Figure 42: **Cloud–Shock Individual Sample Comparison**: A representative random test sample from the Cloud–Shock dataset, displayed across all physical channels. While all models produce plausible results, ReFlow and the hybrid GenCFD ∘ FNO most closely align with the ground truth, particularly in preserving fine-scale detail. The spectral reconstruction effect of the hybrid model is especially evident, recovering high-frequency structures from the coarse FNO prediction and enhancing the overall visual fidelity.

(a) UVit $m_y$ spectrum.

(b) RF $m_y$ spectrum.

(c) UVit $E$ at $(68, 28)$.

(d) RF $E$ at $(68, 28)$.

Figure 43: Cloud-shock: spectral and pointwise energy comparisons.