Rectified Flows for Fast Multiscale Fluid Flow Modeling

Abstract

Statistical surrogate modeling of fluid flows is challenging because multi-scale nonlinear dynamics can amplify small perturbations into large output uncertainty. Conditional diffusion models can capture such output laws with high fidelity, but at inference time they typically require hundreds of stochastic denoising steps. We introduce *ReFlow*, a conditional rectified-flow surrogate for PDE forecasting that instead learns a deterministic transport ODE from a simple reference law to the conditional law of final states, *conditioned on the initial data*. Concretely, for a given initial condition u_i, the model starts from Gaussian noise ξ and learns a time-dependent velocity field that transports ξ to a sample from the target conditional law $p(u_f \mid u_i)$. Because the learned transport is substantially straighter than score-based diffusion trajectories, each function evaluation is more effective: on multi-scale 2D benchmarks, ReFlow matches diffusion-class posterior statistics with as few as 8 ODE steps, whereas score-based diffusion requires ≥ 128 network evaluations.

On the theory side, we develop a law-level analysis tailored to conditional PDE surrogates. First, we formulate rectified flow in the conditional setting and show that the ideal barycentric rectified velocity transports the reference law to the target conditional law at the level of measures. Second, at fixed spatial resolution, we derive a one-step law-level error decomposition into a *coverage* term, determined by unresolved high-frequency content and controlled by structure functions (equivalently, spectral tails), and a *fit* term, determined by how well the learned velocity matches the ideal conditional transport field. Third, we show that *straightness* of the learned transport in rectification time governs ODE discretization error through the variation of the velocity along sampled trajectories, thereby explaining why rectified transports admit large, stable steps. Guided by this picture, we introduce a curvature-aware sampler that monitors an EMA-based proxy for trajectory-wise velocity variation and adaptively blends and steps the velocity during inference, which is particularly helpful in out-of-distribution regimes where these oscillations become pronounced.

Across multiscale incompressible and compressible 2D flows, ReFlow matches diffusion baselines in one-point Wasserstein statistics and energy spectra, preserves fine-scale structure missed by deterministic MSE surrogates, and delivers high-resolution conditional samples at a fraction of the inference cost.

1 Introduction

Partial differential equations (PDEs) [6] are the backbone of modeling physical phenomena, from atmospheric dynamics to aerodynamics and magnetohydrodynamics. Currently, solutions of PDEs are simulated with high-fidelity numerical solvers such as finite difference, finite element, and spectral methods [27]. These are often prohibitively expensive for *many–query* tasks [28] such as uncertainty quantification, optimization, and real-time prediction. In particular, these solvers encounter a significant challenge for classes of non-linear PDEs, whose solutions exhibit extreme sensitivity to initial and boundary data, leading to chaotic behavior and complex multi-scale features. In such settings, one seeks, not a deterministic trajectory, but rather the *statistical solution* of the PDE, i.e., the push-forward of the underlying probability measure on inputs (initial and boundary conditions etc) by the PDE solution operator [7]. Currently, these statistical solutions are sampled with ensemble Monte Carlo method by repeatedly calling high-fidelity PDE solvers [16]. Given the computational cost of the PDE solver, ensemble methods become infeasible as ensemble sizes grow.

Machine learning and AI based algorithms are increasingly being explored for the data-driven simulation of PDEs [24]. In particular, *neural operators* [15], which directly seek to learn the PDE solution operator from data, are already widely used in a PDE context [24]. Examples of neural operators have been proposed in [18, 20, 22, 33, 12, 19, 3] and references therein.

However, these neural operators have been found to be unsuitable for simulating PDE with chaotic, multiscale solutions such as governing equations of fluid dynamics. For instance, recently in [25], it was shown both theoretically and empirically that neural operators, trained to minimize mean absolute (square) errors, will always collapse to the ensemble mean when used for simulating statistics of PDEs with chaotic multiscale solutions.

Given this context, generative AI models—especially score-based and diffusion models—have recently shown remarkable success at learning complex, high-dimensional distributions by progressive denoising score matching [31]. In the context of chaotic PDEs, *GenCFD* [25] introduced a conditional diffusion framework that preserves spectral content across fine scales, mitigating the "spectral collapse" of naive MSE-trained surrogates, see also [26, 11, 9, 10]. However, sampling a score-based diffusion model requires simulating a reverse-time stochastic differential equation (SDE) over 100+ discretization steps, each invoking a large ML model on a moderate-to-high resolution spatial grid, resulting in high runtimes that undermine real-time or resource-constrained applications.

To overcome the inference cost of diffusion-based surrogates, we instead use a *conditional rectified flow* [21]. The key point is to separate the *conditioning variable* from the *transported variable.* In our PDE setting, the initial condition u_i is *not* transported by the rectified flow; rather, it is provided as conditioning information throughout the model. The transported variable is a latent sample initialized from a simple reference law, typically Gaussian noise. Thus, for each fixed initial datum u_i, the goal is to learn a time-dependent velocity field whose flow maps a reference sample $\xi \sim \mathcal{N}(0, I)$ to a sample from the conditional output law $p(u_f \mid u_i)$, where u_f denotes the PDE state at the target physical time.

This viewpoint is especially natural for chaotic or strongly multiscale PDEs. When the same macroscopic initial datum is subjected to small unresolved perturbations, the corresponding final state is no longer well represented by a single deterministic predictor; instead, one seeks a conditional *law* over possible outcomes. Conditional diffusion models such as GenCFD already target this law successfully, but do so through a reverse-time stochastic process that typically requires many score-network evaluations. Rectified flow replaces this stochastic sampling procedure by a deterministic ODE in an internal *rectification time* $\tau \in [0, 1]$, chosen so that the learned transport from noise to data is as straight as the conditional law permits. In practice this substantially reduces the number of function evaluations needed to reach the target conditional distribution.

A central theme of this paper is that *straightness in rectification time* matters for computational reasons. If the learned velocity varies little along its own trajectories, then explicit ODE solvers incur small truncation error and can take large steps. Conversely, when the learned velocity oscillates strongly along the sampled path—a phenomenon we observed most clearly in out-of-distribution conditional regimes—few-step sampling becomes fragile. This observation motivated our curvature-aware sampler: an EMA-based controller that tracks short-horizon velocity oscillations along the trajectory and uses them to blend and adapt the step size during inference.

Statistical evaluation criteria. Because statistical solutions are probability measures on function spaces, the most robust comparisons are formulated through observables and their induced correlation marginals [17]. Our main metric in Section 6.2, the *one-point Wasserstein distance*, is exactly the Wasserstein discrepancy between the $k = 1$ correlation marginals (that is, the pointwise pushforwards of the laws), averaged over space. Thus the experimental metrics in Table 1 are directly aligned with the law-level viewpoint used in the theory sections below.

Hence, our main contributions are:

- *Conditional rectified flows for PDE surrogates.* We formulate rectified flow directly at the level of conditional PDE laws: for each fixed input field u_i, the model transports a simple reference law on latent fields to the target conditional law of final states. The key theoretical statement is *correctness*

at the level of laws: the ideal conditional barycentric rectified velocity induces an ODE whose flow pushes the reference law to the target conditional law.

- *A law-level decomposition into coverage, fit, and discretization.* At fixed spatial resolution, there is an irreducible approximation floor coming from unresolved Fourier scales. We express this as a *coverage* term controlled by structure functions, equivalently by spectral tails. The remaining continuous-time modeling error is a *fit* term measuring how well the learned velocity approximates the ideal conditional transport field. Separately, we show that discretization error is governed by the variation of the learned velocity *along sampled trajectories* in rectification time.

- *Curvature-aware sampling for OOD-sensitive conditional generation.* Recent work on diffusion-based OOD and anomaly detection has shown that trajectory geometry, score variation, and curvature carry useful information about whether a sample remains in-distribution or moves into poorly calibrated regions of the learned generative dynamics [13, 1, 2, 4]. Motivated by this perspective, we treat trajectory-wise velocity variation in rectification time as an online signal that the conditional sampler is entering an unstable or OOD regime. We therefore introduce an EMA-based controller that monitors this straightness/curvature proxy and uses it to adaptively blend the velocity and choose the step size during inference on OOD data. Unlike prior works, which use such trajectory information primarily for detection or scoring, we use it *operationally* to stabilize and improve sampling itself.

- *Multi-scale accuracy at substantially lower inference cost.* Across incompressible and compressible 2D benchmarks, ReFlow matches diffusion models in one-point Wasserstein statistics and energy spectra, preserves fine-scale structure missed by deterministic MSE baselines, and achieves these results with dramatically fewer sampling steps. The gain is especially pronounced in the OOD macro–micro regime, where the curvature-aware controller improves the NFE–error tradeoff by reacting to the same trajectory-geometry signals that recent diffusion OOD work has identified as informative under distribution shift [13, 1, 4].

2 Approach

Modeling multi-scale flows and their statistical solutions. We focus on time-dependent PDEs of the general form

$$\partial_t u(x,t) \ + \ \mathcal{L}\big(u, \nabla_x u, \nabla_x^2 u, \dots \big) \ = \ 0, \quad x \in D \subset \mathbb{R}^d, \ t \in (0, T), \tag{1}$$

subject to boundary conditions $\mathcal{B}(u) = u_b$ on $\partial D \times (0, T)$ and initial data $u(x, 0) = \bar{u}(x)$. Here, the solution $u : D \mapsto \mathbb{R}^m$ is evolved in time, with respect to the differential operator $\mathcal{L}$. Concrete examples of (1) are the incompressible Navier-Stokes and compressible Euler equations.

A recurring theme in non-linear, multi-scale fluid flows is *extreme sensitivity* to initial or boundary data, which can lead to chaotic or near-chaotic behavior. Rather than fix a single u_0, one may consider an *initial measure* μ_0 to represent uncertain or variable initial states, and then study the *statistical solution* $\mu_t = \mathcal{S}_\#^t \mu_0$ pushed forward by the PDE solution operator $\mathcal{S}^t$. In strongly nonlinear regimes, μ_t spreads significantly in function space, creating complex, multi-scale distributions of possible flow fields. Accurately approximating this evolving distribution is essential for uncertainty quantification and design under rough conditions, but doing so with high-fidelity PDE solvers can be prohibitively expensive when large ensembles are required.

High cost of computing statistical solutions. In practice, characterizing μ_t directly often requires performing *many* forward simulations of the PDE solver, each initialized with a slightly perturbed u_0. As each simulation might require high-resolution discretizations (e.g. millions of degrees of freedom) and multiple time steps, the overall cost for constructing a sizable ensemble rapidly becomes prohibitive. Even with modern high-performance computing platforms, running hundreds or thousands of high-fidelity statistical simulations can be infeasible. Hence, there is a pressing need for more efficient *surrogate models* that can *sample* physically realistic final states without enumerating every realization of the forward PDE solve. Succinctly put, we aim to provide a solution to the following problem

How can we efficiently capture statistical quantities of interest for the pushforward measure $S_\#^t \mu_0$ for highly sensitive solution operators S^t?

Observables and correlation marginals (what metrics actually probe). A classical way to formalize "quantities of interest" for μ_t is via observables and their induced correlation marginals [17]. For $k = 1$, the pointwise evaluation map at $x \in D$,

$$\mathrm{ev}_x : \ u \mapsto u(x) \in \mathbb{R}^m,$$

pushes μ_t to the *one-point marginal* $(\mathrm{ev}_x)_\# \mu_t$ on $\mathbb{R}^m$ – strictly speaking, one studies the pushforwards measures $\mathrm{ev}_x \circ i_\epsilon$, here $(i_\epsilon u) := (\phi_\epsilon * u)$ where ϕ_ϵ is a compactly supported mollifier, so that point-wise evaluation is well-defined; for the sake of brevity, we will not make this distinction explicit in the sequel. Our one-point Wasserstein metric (Section 6.2) is the spatial average of $W_1\big((\mathrm{ev}_x)_\# \mu_t, (\mathrm{ev}_x)_\# \widehat{\mu}_t\big)$. By Kantorovich–Rubinstein duality, controlling this quantity controls the discrepancy of *all* pointwise 1-Lipschitz observables, averaged over space. This is the bridge between Table 1 and the law-level bounds in Section 4.1 and Section 4.3.

Rectified flows for faster sampling. To mitigate these inefficiencies, we adopt the framework of *rectified flows* [21]: a deterministic alternative to conditional diffusion designed to reduce the number of required integration steps. In essence, rather than generating samples via small random "diffusion-reversal" increments, rectified flows construct an *ordinary differential equation* (ODE) with *nearly straight* trajectories in function space. This straighter transport map can be integrated more aggressively in time, enabling sampling with far fewer solver steps. Importantly, rectified flows retain the desirable property of matching the same final distributions that standard diffusion models learn, but at a fraction of the runtime cost.

3 Related Work

3.1 Diffusion Models in Fluid Dynamics

Conditional diffusion surrogates. *GenCFD* [25] trains a conditional score-based diffusion model that starts from an initial or low-resolution flow field and iteratively refines it through hundreds of denoising steps, thereby capturing multi-scale turbulent structure. Similarly, the method of [26] conditions a diffusion model on a coarse fluid solution (generated by a learned operator) and "super-resolves" the fine-scale flow. Given these similarities, we refer to such diffusion-based solvers collectively as *conditional diffusion PDE solvers*.

Rectified flow alternative. Each sample typically needs hundreds of network calls, limiting large-scale or real-time use. Our method replaces the stochastic SDE with a deterministic ODE whose nearly straight trajectories require far fewer steps, achieving similar statistical fidelity at much lower inference cost (see Sections 5.7 and 6). Crucially, we find that rectified flows are actually more efficient from the standpoint of training-time required to reach the same accuracy level with the conditional diffusion approaches; this is also confirmed by earlier work [5] exploring the scalability of rectified flows with transformer-based backbones.

4 Rectified Flows: An ODE-Based Alternative

4.1 Mathematical Formulation

Overview. Rectified flows provide a *deterministic* mechanism for sampling from a target probability law by integrating an ordinary differential equation in an internal *rectification time* $\tau \in [0, 1]$. In our PDE setting, the target is *conditional*: given an initial condition (and, when relevant, boundary data) u_i, we wish to sample from the conditional law of the final state u_f at the forecast time. The key point is that the conditioning datum u_i is *not* itself transported by the rectified flow. Rather, it is provided to the model as side information throughout the trajectory. The transported variable starts from a simple reference law, typically Gaussian noise, and is evolved to a sample from the target conditional law.

Throughout, the random state fields take values in a separable Hilbert space

$$\mathcal{U} = L^2(\mathcal{D}; \mathbb{R}^m),$$

Figure 1: **Overview of ReFlow.** (**a**): ReFlow closely matches high-order statistical moments (in the Wasserstein W_1-sense) of fluid flows by learning a neural surrogate to approximate the push-forward of the distribution $p(u_{\tau|\tau=0}|u_i)$, while minimizing inference-time computational costs. (**b**) Macro-architecture overview: A UViT based network predicts the velocity field v_θ, conditioned on Gaussian noise, initial data u_i and boundary conditions, and diffusion time τ. Noise and initial / boundary conditions are concatenated as inputs. (**c**): Results for the cylindrical shear flow dataset. (**d**): The KDE plots monitor the evolution of a down-projected version of the push-forward measure $p_\tau := X_\theta(\tau)_\#p(u_{\tau=0}|u_i)$, where X_θ is the flow induced by the learned vector field v_θ. Results for the Richtmyer Meshkov dataset showing flow matching between noise ($p_{\tau=0}$) and target ($p_{\tau=1}$) distributions. ReFlow solves an ODE, learning a constant velocity field that enables straight-line inference paths (visualized with principal component analysis and kernel density estimation at different diffusion times).

or, when convenient, in a smoother space such as $H^s(\mathcal{D}; \mathbb{R}^m)$ with $s > d/2$. In computations, all objects are represented on a finite-dimensional Galerkin or grid discretization $\mathbb{R}^{d_N} \subset \mathcal{U}$, so the theory below is to be understood either in that finite-dimensional setting or as its natural infinite-dimensional analogue.

Conditional target law and reference law. Let C denote the conditioning variable, which in our applications is the initial condition u_i (possibly augmented with boundary data or other known inputs). For each fixed realization c of C, let

$$\mu_1^c := \mathrm{Law}(U_f \mid C = c)$$

be the conditional law of the final PDE state, and let

$$\pi_0^c$$

be a simple reference law on $\mathcal{U}$ from which sampling is easy. In practice we take $\pi_0^c = \mathcal{N}(0, I)$, independent of c, but allowing a c-dependence is conceptually harmless and can be useful in variants with condition-dependent priors.

Thus, for each fixed condition c, the goal of rectified flow is to construct a time-dependent velocity field

$$v_\theta(\,\cdot\,, \tau; c) : \mathcal{U} \to \mathcal{U}$$

such that the ODE flow

$$\frac{d}{d\tau}u_\tau = v_\theta(u_\tau, \tau; c), \qquad u_{\tau=0} \sim \pi_0^c, \tag{2}$$

pushes π_0^c forward to a law close to μ_1^c at $\tau = 1$.

Conditional coupling and rectified interpolation. Fix a condition c. Let

$$\gamma^c \in \mathcal{P}(\mathcal{U} \times \mathcal{U})$$

be any coupling between the reference law π_0^c and the target law μ_1^c. We write

$$(\Xi, U_f) \sim \gamma^c,$$

where Ξ is the reference sample and U_f is the target final state. The most basic rectified interpolation is the linear chord

$$U_\tau := (1-\tau)\,\Xi + \tau\,U_f, \qquad \tau \in [0,1]. \tag{3}$$

Its conditional law at rectification time τ is

$$\rho_\tau^c := \mathrm{Law}(U_\tau \mid C = c).$$

This is the population of intermediate states obtained by linearly interpolating between the noise sample and the target sample, under the chosen conditional coupling.

The ideal conditional barycentric velocity. At a fixed condition c, many interpolation chords may pass through the same state u at the same rectification time τ. The correct population-level velocity is therefore the average chord direction conditioned on the current state:

$$v^\star(u, \tau; c) := \mathbb{E}[\, U_f - \Xi \mid U_\tau = u, \ C = c\,], \qquad \rho_\tau^c\text{-a.e. } u. \tag{4}$$

This is the *conditional barycentric rectified velocity*. It is the natural analogue, in the conditional setting, of the barycentric velocity used in standard rectified-flow theory. For the linear interpolation (3), the chord direction $U_f - \Xi$ is constant along each sample path, so (4) says that the ideal velocity field is obtained by averaging these constant sample-wise directions over all chords compatible with the observed intermediate state.

The field (4) is also the unique $L^2(\rho_\tau^c)$ minimizer of the conditional regression problem

$$\min_{v(\cdot, \tau; c)} \ \mathbb{E}\Big[\big\|v(U_\tau, \tau; c) - (U_f - \Xi)\big\|^2 \ \Big| \ C = c\Big].$$

This makes the practical training objective immediate: if one samples

$$c, \quad u_f \sim \mu_1^c, \quad \xi \sim \pi_0^c, \quad \tau \sim \mathrm{Unif}[0,1],$$

forms

$$u_\tau = (1-\tau)\xi + \tau u_f, \tag{5}$$

and trains v_θ against the constant target $(u_f - \xi)$, then the population minimizer is exactly the ideal conditional barycentric field (4). In particular, the transported quantity is the latent variable initialized at ξ, while the initial PDE state $c = u_i$ appears only as a condition in the network. With the notation above, the training loss is

$$\min_\theta \ \mathbb{E}\Big[\big\|v_\theta(u_\tau, \tau; c) - (u_f - \xi)\big\|^2\Big], \qquad u_\tau = (1-\tau)\xi + \tau u_f, \tag{6}$$

where the expectation is taken over the joint sampling of (c, u_f) from the dataset, $\xi \sim \pi_0^c$, and $\tau \sim \mathrm{Unif}[0,1]$. This is the conditional rectified-flow objective used throughout the paper.

Sampling from the learned conditional law. Once trained, the model generates a conditional sample at a prescribed initial datum $c = u_i$ by drawing

$$\xi \sim \pi_0^{u_i}$$

and integrating the conditional transport ODE

$$\frac{d}{d\tau} u_\tau = v_\theta(u_\tau, \tau; u_i), \qquad u_0 = \xi. \tag{7}$$

The final state u_1 is then the model sample from the learned approximation to the conditional law $\mu_1^{u_i}$.

Rectification time versus physical time. The variable $\tau \in [0, 1]$ is an *internal* transport parameter and should not be confused with the physical PDE time. The physical dynamics have already been absorbed into the conditional target law $p(u_f \mid u_i)$ through the training data. Rectification time only parameterizes the learned transport from the reference law to that target conditional law. The benefit of rectified flow is not that the learned velocity is literally constant, but that for a well-trained model it can vary substantially less along sampled trajectories than the score field underlying diffusion-based samplers. This matters because the numerical error of explicit ODE solvers depends on how rapidly

$$\tau \mapsto v_\theta(u_\tau, \tau; u_i)$$

changes along the realized trajectory. When this variation is small, few large steps suffice; when it becomes oscillatory, sampling becomes more delicate. In our experiments, such oscillations are especially pronounced in out-of-distribution conditional regimes, which motivates the curvature-aware controller described next.

Curvature-aware control: monitoring velocity variation along the trajectory. During sampling, at step t with state u_t and rectification time τ_t, write

$$v_t := v_\theta(u_t, \tau_t; u_i),$$

and maintain an exponential moving average

$$v_t^{\text{ema}} = \lambda\, v_{t-1}^{\text{ema}} + (1 - \lambda)\, v_t, \qquad \lambda \in (0, 1). \tag{8}$$

We use the deviation

$$s_t := \|v_t - v_t^{\text{ema}}\|_2 \tag{9}$$

as a computable proxy for short-horizon variation of the velocity along the sampled path. Large values of s_t indicate that the trajectory is entering a regime where the learned transport is bending or oscillating in rectification time, precisely where aggressive explicit stepping becomes less reliable.

Blending and adaptive step size. When the straightness proxy is large, we replace v_t by a regularized velocity

$$\tilde{v}_t = (1 - \alpha_t)v_t + \alpha_t v_t^{\text{ema}}, \qquad \alpha_t \in [0, 1],$$

where α_t is chosen as an increasing function of s_t. At the same time, we choose the step size inversely proportional to the estimated local variation, for example

$$\Delta\tau_t \propto \frac{1}{\sqrt{\kappa_1 s_t + \kappa_2}}, \qquad \Delta\tau_t \in [\Delta\tau_{\min}, \Delta\tau_{\max}]. \tag{10}$$

The resulting update is

$$u_{t+1} = u_t + \Delta\tau_t\, \tilde{v}_t.$$

This controller is dormant when the transport is straight and active only when the velocity becomes oscillatory. In Section 5 we connect this construction to the truncation error of explicit ODE integration and explain why such a controller is particularly helpful in the OOD regimes where velocity oscillations become more pronounced.

4.2 Error Decomposition and Bounds

There are two distinct sources of error once the spatial resolution is fixed. The first is a *continuous-time modeling error*: even if we could integrate the learned ODE exactly, the learned velocity field v_θ may differ from the ideal conditional barycentric field $v^\star$. The second is a *numerical discretization error*: even if v_θ were fixed, solving the learned ODE with finitely many steps introduces truncation error. These two effects should not be conflated. In particular, if $v_\theta = v^\star$, then the continuous-time modeling error must vanish; the remaining error is purely numerical.

Ideal, learned, and discretized conditional flows. Fix a condition c. Let $\Xi \sim \pi_0^c$, and let

$$\dot{U}_\tau = v^\star(U_\tau, \tau; c), \qquad U_0 = \Xi, \tag{11}$$

denote the *ideal* conditional rectified flow, and let

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c), \qquad \widehat{U}_0 = \Xi, \tag{12}$$

denote the *learned continuous-time* conditional flow driven by the neural velocity field. Finally, let $\widehat{U}_1^{(N)}$ denote the output obtained by numerically integrating (12) with N explicit steps. Writing

$$\widehat{\mu}_1^{c,\text{cts}} := \text{Law}(\widehat{U}_1 \mid C = c), \qquad \widehat{\mu}_1^{c,N} := \text{Law}(\widehat{U}_1^{(N)} \mid C = c),$$

the conditional law error satisfies the elementary decomposition

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \leq W_2\big(\mu_1^c, \widehat{\mu}_1^{c,\text{cts}}\big) + W_2\big(\widehat{\mu}_1^{c,\text{cts}}, \widehat{\mu}_1^{c,N}\big). \tag{13}$$

The first term is the *fit* error of the learned velocity field; the second is the *discretization* error of the sampler. The exact-transport statement proved later in Proposition 5.1 identifies μ_1^c as the terminal law of the ideal flow (11).

Theorem 4.1 (Continuous-time fit error for the learned conditional flow). *Fix a condition c and assume that $v_\theta(\cdot, \tau; c)$ is L-Lipschitz in u, uniformly in $\tau \in [0,1]$. Let U_τ and $\widehat{U}_\tau$ solve (11) and (12) with the same initial sample $\Xi \sim \pi_0^c$. Then*

$$\left(\mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \,\big|\, C = c\big]\right)^{1/2} \leq e^L \int_0^1 \left(\mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \,\big|\, C = c\big]\right)^{1/2} d\tau. \tag{14}$$

In particular, defining

$$\varepsilon_{\text{fit}}^2(c) := \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \,\big|\, C = c\big] \, d\tau, \tag{15}$$

we obtain

$$\left(\mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \,\big|\, C = c\big]\right)^{1/2} \leq e^L \, \varepsilon_{\text{fit}}(c). \tag{16}$$

Proof sketch. Set $E_\tau := \widehat{U}_\tau - U_\tau$. Then

$$\dot{E}_\tau = v_\theta(\widehat{U}_\tau, \tau; c) - v^\star(U_\tau, \tau; c) = \big(v_\theta(\widehat{U}_\tau, \tau; c) - v_\theta(U_\tau, \tau; c)\big) + \big(v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\big).$$

The Lipschitz assumption yields

$$\|\dot{E}_\tau\| \leq L\|E_\tau\| + \|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|.$$

Applying Grönwall's inequality pathwise, then taking conditional L^2 norms and using Minkowski's inequality in time, gives (14). The compact form (16) follows from Cauchy–Schwarz in τ. □

Theorem 4.1 contains only a *fit* term. This is exactly as it should be: if $v_\theta = v^\star$, then the right-hand side is zero, so the learned continuous-time flow matches the ideal one. Straightness or curvature does *not* create continuous-time error by itself; it enters only when the learned ODE is discretized.

Lemma 4.2 (Local truncation error for explicit Euler on the learned conditional ODE). *Assume that v_θ is C^1 in (u, τ) on the region traversed by the learned trajectory $\widehat{U}_\tau$, and define*

$$g(\tau) := v_\theta(\widehat{U}_\tau, \tau; c).$$

Then one explicit-Euler step of size $\Delta\tau$ from time τ along the learned ODE (12) satisfies

$$\begin{aligned}
\mathrm{LTE}(\tau; \Delta\tau) &:= \left\| \widehat{U}_{\tau+\Delta\tau} - \left(\widehat{U}_\tau + \Delta\tau\, v_\theta(\widehat{U}_\tau, \tau; c) \right) \right\| \\
&= \frac{(\Delta\tau)^2}{2} \|\dot{g}(\tau)\| + \mathcal{O}\big((\Delta\tau)^3\big) \\
&= \frac{(\Delta\tau)^2}{2} \left\| \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c) \right\| + \mathcal{O}\big((\Delta\tau)^3\big).
\end{aligned} \tag{17}$$

If, in addition,

$$\|\partial_\tau v_\theta(u, \tau; c)\| \le M_\tau, \qquad \|J_u v_\theta(u, \tau; c)\| \le L, \qquad \|v_\theta(u, \tau; c)\| \le M$$

on the relevant region, then

$$\mathrm{LTE}(\tau; \Delta\tau) \ \le\ \frac{(\Delta\tau)^2}{2}\,(M_\tau + LM) + \mathcal{O}\big((\Delta\tau)^3\big). \tag{18}$$

Proof sketch. Taylor-expand the exact trajectory $\widehat{U}_{\tau+\Delta\tau}$ around τ. Since

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c),$$

the second derivative is

$$\ddot{\widehat{U}}_\tau = \frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, \dot{\widehat{U}}_\tau,$$

and substituting $\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c)$ gives (17). The bound (18) is immediate. $\qquad\square$

Corollary 4.3 (Global Euler discretization error). *Assume the hypotheses of Lemma 4.2, and assume again that $v_\theta(\cdot, \tau; c)$ is L-Lipschitz in u uniformly in τ. Let $\widehat{U}^{(N)}$ denote the explicit-Euler approximation of (12) with uniform step $\Delta\tau = 1/N$. Then there exists a constant $C(L) > 0$ such that*

$$\sup_{0 \le n \le N} \left(\mathbb{E}\big[\|\widehat{U}^{(N)}_{\tau_n} - \widehat{U}_{\tau_n}\|^2 \,\big|\, C = c \big] \right)^{1/2} \ \le\ C(L)\, \Delta\tau \int_0^1 \left(\mathbb{E}\big[\|\dot{g}(\tau)\|^2 \,\big|\, C = c \big] \right)^{1/2} d\tau, \tag{19}$$

where

$$\dot{g}(\tau) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

Equivalently, defining

$$\varepsilon_{\mathrm{disc}}(c; N) := \frac{1}{N} \int_0^1 \left(\mathbb{E}\big[\|\dot{g}(\tau)\|^2 \,\big|\, C = c \big] \right)^{1/2} d\tau, \tag{20}$$

we have

$$\sup_{0 \le n \le N} \left(\mathbb{E}\big[\|\widehat{U}^{(N)}_{\tau_n} - \widehat{U}_{\tau_n}\|^2 \,\big|\, C = c \big] \right)^{1/2} \ \le\ C(L)\, \varepsilon_{\mathrm{disc}}(c; N). \tag{21}$$

Proof sketch. The local truncation error from Lemma 4.2 is of order $(\Delta\tau)^2 \|\dot{g}(\tau)\|$. Summing over N steps and propagating the local errors through the L-Lipschitz flow stability yields a standard discrete Grönwall estimate, giving (19). $\qquad\square$

Corollary 4.3 shows that the quantity governing step-count requirements is the *total derivative of the learned velocity along the sampled trajectory,*

$$\frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

This is the precise mathematical meaning of "curvature" or "straightness" in rectification time for our sampler. It is not merely the partial derivative $\partial_\tau v_\theta$ at fixed state, but the full variation of the velocity seen along the realized transport path.

Connection to the EMA controller. The practical proxy

$$s_t = \|v_t - v_t^{\text{ema}}\|_2, \qquad v_t = v_\theta(u_t, \tau_t; c),$$

used in Section 4.1, is intended to track this trajectory-wise variation over a short time window. Large values of s_t indicate that the map $\tau \mapsto v_\theta(u_\tau, \tau; c)$ is oscillating, precisely the regime where (17) predicts larger truncation error for aggressive explicit stepping. Empirically, we observed these oscillations to be much more pronounced in out-of-distribution conditional regimes, which is why the EMA-based blending and adaptive step size are most useful there.

The discussion above isolates *fit* and *discretization* at a fixed spatial resolution. The remaining error source is *coverage*: even a perfect bandlimited surrogate cannot represent unresolved high-frequency content. We quantify that irreducible law-level floor in the next subsection through structure functions and spectral tails.

4.3 Spectral Capacity, Structure Functions, and Law-Level Coverage

Functional setting. We work on the periodic box $\mathcal{D} = \mathbb{T}^d$ and consider L^2 fields $\mathcal{H} := L^2(\mathcal{D}; \mathbb{R}^m)$ with norm $\|\cdot\|_2$. For incompressible velocity fields (e.g. SL2D, see Section 6), one may equivalently restrict to divergence-free subspaces and adopt the statistical-solution framework of [17], which characterizes laws via correlation identities, admissible observables, and an energy inequality. In that framework the natural distance on laws is the L^2-based Wasserstein metric W_2, and small-scale regularity is expressed in terms of *structure functions* and their time-averages. The numerical ensembles used in our experiments fit this setting: they are generated by dissipative solvers on $\mathbb{T}^2$, have uniformly bounded energy, and exhibit empirical structure-function scaling (equivalently, power-law spectra) consistent with the assumptions below.

4.3.1 Bandlimited capacity and strain constraints

Any $u \in \mathcal{H}$ admits a Fourier series $u(x) = \sum_{k \in \mathbb{Z}^d} \hat{u}(k) e^{ik \cdot x}$. We write $P_{\leq K}$ for the projector onto modes $\{k : |k| \leq K\}$ and $P_{>K} = I - P_{\leq K}$. On a grid of size N^d, the Nyquist frequency satisfies $K_{\max} \simeq N$, so every numerically represented field is effectively bandlimited to $|k| \lesssim K_{\max}$. Architecturally, downsampling and anti-aliasing may enforce an even stricter cutoff $K_c \leq K_{\max}$.

The next lemma is a standard Bernstein-type inequality: bandlimited fields have a uniform Lipschitz cap.

Lemma 4.4 (Bernstein upper bound for bandlimited fields). *Let $u : \mathbb{T}^d \to \mathbb{R}^m$ satisfy $u = P_{\leq K}u$ for some integer $K \geq 1$. Then there exists a constant $C_d > 0$ depending only on the dimension d such that*

$$\|\nabla_x u\|_{L^\infty(\mathbb{T}^d)} \leq C_d K^{1+\frac{d}{2}} \|u\|_{L^2(\mathbb{T}^d)}. \tag{22}$$

In particular, on an energy shell $\|u\|_{L^2} \leq E^{1/2}$ one has

$$\|\nabla_x u\|_{L^\infty} \leq C_d K^{1+\frac{d}{2}} E^{1/2}. \tag{23}$$

Proof sketch. Write $u(x) = \sum_{|k| \leq K} \hat{u}(k) e^{ik \cdot x}$, so $\nabla_x u(x) = \sum_{|k| \leq K} (ik) \hat{u}(k) e^{ik \cdot x}$ and $|\nabla_x u(x)| \leq \sum_{|k| \leq K} |k| |\hat{u}(k)|$. Cauchy–Schwarz and a lattice-counting bound $\#\{|k| \leq K\} \lesssim K^d$ give $\|\nabla u\|_{L^\infty} \lesssim (\sum_{|k| \leq K} |k|^2)^{1/2} \|\hat{u}\|_{\ell^2} \lesssim K^{1+d/2} \|u\|_{L^2}$. Full details are deferred to the theory appendix. □

Upper bounds alone do not say what happens if a surrogate *misses* an entire high-frequency annulus. The next lemma gives a complementary lower bound.

Lemma 4.5 (Annulus lower bound). *Let $f = P_{[K,2K]}u$ for some $u \in L^2(\mathbb{T}^d)$, where $P_{[K,2K]} := P_{\leq 2K} - P_{\leq K}$ and $K \geq 1$. Then there exists $c_d > 0$ such that*

$$\|\nabla_x f\|_{L^\infty} \geq c_d K \|f\|_{L^\infty} \geq c_d K^{1-\frac{d}{2}} \|f\|_{L^2}. \tag{24}$$

Proof sketch. On the annulus $\{K \leq |k| \leq 2K\}$, the symbol of ∇ has magnitude $|k| \in [K, 2K]$. This yields $\|\nabla f\|_{L^\infty} \gtrsim K \|f\|_{L^\infty}$. A reverse Bernstein estimate on an annulus gives $\|f\|_{L^\infty} \gtrsim K^{-d/2} \|f\|_{L^2}$. See the theory appendix for a precise statement independent of the Littlewood–Paley cut-off choice. □

Corollary 4.6 (Capacity requirement for typical strain levels)**.** *Suppose the target flows at time t have typical energy E and typical rate-of-strain $\|\nabla_x u\|_{L^\infty} \simeq L_\star$. Let a surrogate produce only bandlimited outputs $u = P_{\leq K_c} u$ with $\|u\|_{L^2} \leq E^{1/2}$. Then necessarily*

$$C_d\, K_c^{1+\frac{d}{2}}\, E^{1/2} \; \gtrsim \; L_\star, \tag{25}$$

and hence a minimal cutoff

$$K_c \; \gtrsim \; \Big(\frac{L_\star}{E^{1/2}}\Big)^{\frac{2}{2+d}}. \tag{26}$$

Moreover, if the true flow has nontrivial energy in an annulus above K_c, then any bandlimited approximation underestimates its strain by at least $c_d K^{1-d/2}\|P_{[K,2K]}u\|_{L^2}$ for some $K > K_c$.

Remark 4.7. Corollary 4.6 formalises the intuition that spatial capacity (K_c) is a hard constraint: at fixed energy scale E, there is a minimum cutoff needed to represent typical strain levels $L_\star$. In our experiments both GenCFD and ReFlow operate at the same grid resolution, so they share the same effective K_c; rectification does not invent new small scales but makes the trajectories inside this bandlimited class straight and easy to integrate.

4.3.2   Structure functions and small-scale coverage

We now quantify how much of the *law* of the PDE solution can be captured at a given cutoff K_c. For $u : \mathbb{T}^d \to \mathbb{R}^m$ and $r > 0$ define the second-order structure function

$$S_r^2(u) := \frac{1}{|B_r|} \int_{|h| \leq r} \|u(\cdot + h) - u(\cdot)\|_{L^2(\mathbb{T}^d)}^2 \, dh,$$

and for a probability law μ on $\mathcal{H}$ set

$$S_r^2(\mu) := \int S_r^2(u) \, d\mu(u).$$

In homogeneous turbulence $S_r^2(\mu)$ is directly related to the energy spectrum; power-law behaviour $S_r^2(\mu) \sim r^{\zeta_2}$ at small r encodes the scaling of the cascade. In our experiments, Figure 13 visualizes this connection directly: matching the high-wavenumber tail in the spectrum is equivalent to capturing the small-r behaviour of structure functions, and therefore to controlling the coverage term below.

Guided by the statistical-solution framework of [7], we assume there exists a modulus of continuity $\omega : (0, 1] \to [0, \infty)$ with $\omega(r) \downarrow 0$ as $r \downarrow 0$ such that

$$S_r^2(\mu_t) \; \leq \; \omega(r) \quad \text{for all } r \in (0, 1], \ t \in [0, T]. \tag{27}$$

In practice, ω can be taken as a piecewise power law $Cr^{2\alpha}$ calibrated from the empirical spectra of the numerical ensembles. The next lemma shows that (27) controls the high-frequency tail of the law.

Lemma 4.8 (Structure function controls Fourier tail)**.** *Let μ be a law on $L^2(\mathbb{T}^d)$ satisfying $S_r^2(\mu) \leq \omega(r)$ for all $r \in (0, 1]$, where $\omega(r) \downarrow 0$ as $r \downarrow 0$. Then there exist constants $c_d, C_d > 0$ such that for all integers $K \geq 1$,*

$$\int \|P_{>K}u\|_{L^2}^2 \, d\mu(u) \; \leq \; C_d\, \omega\big(c_d/K\big). \tag{28}$$

Proof sketch. Expand u in Fourier series and observe $\|u(\cdot + h) - u(\cdot)\|_{L^2}^2 = \sum_k |\hat{u}(k)|^2 |e^{ik \cdot h} - 1|^2$. Averaging over $h \in B_r$ yields $S_r^2(u) = \sum_k |\hat{u}(k)|^2 \Psi_r(k)$, where $\Psi_r(k) \gtrsim \min\{(|k|r)^2, 1\}$ uniformly in k, r. For $|k| \gtrsim 1/r$, one has $\Psi_r(k) \gtrsim 1$, hence $S_r^2(u) \gtrsim \|P_{>c/r}u\|_{L^2}^2$. Integrate over $u \sim \mu$, apply (27), and set $r \sim 1/K$. Full constants and the Littlewood–Paley formulation are deferred to the theory appendix. $\square$

Lemma 4.9 (Bandlimited projection in W_2)**.** *For any law μ on $L^2(\mathbb{T}^d)$ and cutoff $K_c \geq 1$,*

$$W_2\big(\mu, (P_{\leq K_c})_\# \mu\big) \; \leq \; \Big(\int \|P_{>K_c}u\|_{L^2}^2 \, d\mu(u)\Big)^{1/2}. \tag{29}$$

Proof. Couple $u \sim \mu$ and $\tilde{u} = P_{\leq K_c} u$. Then $\tilde{u} \sim (P_{\leq K_c})_{\#}\mu$ and $W_2^2(\mu, (P_{\leq K_c})_{\#}\mu) \leq \mathbb{E}\|u - \tilde{u}\|_{L^2}^2 = \mathbb{E}\|P_{>K_c}u\|_{L^2}^2$. $\qquad\square$

Combining Lemmas 4.8 and 4.9 gives a clean coverage bound.

Corollary 4.10 (Coverage term from the structure-function modulus)**.** *Let μ_t be the statistical solution law at time t and assume* (27)*. Then for any cutoff $K_c \geq 1$,*

$$W_2\big(\mu_t, (P_{\leq K_c})_{\#}\mu_t\big) \lesssim \omega\big(c_d/K_c\big)^{1/2}, \tag{30}$$

with c_d as in Lemma 4.8.

4.3.3 Capacity–coverage–fit decomposition for one-step RF

Finally, we combine the coverage term with the training error of a one-step rectified-flow surrogate.

Let $S_{\Delta t} : \mathcal{H} \to \mathcal{H}$ denote the PDE solution operator over a physical step Δt, and write

$$\mu_{t+\Delta t} := (S_{\Delta t})_{\#}\mu_t.$$

Assume the rectified-flow propagator $\mathcal{T}_{\Delta t}^{\theta}$ aims at the bandlimited target $P_{\leq K_c}(S_{\Delta t}u)$ in mean-square. Concretely, sample $u \sim \mu_t$ and an internal noise seed $\xi \sim \mathcal{N}(0, I)$, and define the RF output $\widehat{u} := \mathcal{T}_{\Delta t}^{\theta}(u, \xi)$. We measure the training fit by

$$\varepsilon_{\text{train}}^2(t) := \mathbb{E}_{u \sim \mu_t} \mathbb{E}_{\xi \sim \mathcal{N}(0,I)} \big\| P_{\leq K_c}(S_{\Delta t}u) - \widehat{u} \big\|_{L^2}^2. \tag{31}$$

Finally, we define the one-step RF law by

$$\widehat{\mu}_{t+\Delta t} := \text{Law}(\widehat{u}).$$

Proposition 4.11 (One-step law-level error: capacity, coverage, and fit)**.** *Under the structure-function modulus assumption* (27)*, the one-step W_2 error between the PDE law and the RF law satisfies*

$$W_2\big(\mu_{t+\Delta t}, \widehat{\mu}_{t+\Delta t}\big) \leq \Big(C_d\,\omega\big(c_d/K_c\big) + \varepsilon_{\text{train}}^2(t)\Big)^{1/2}, \tag{32}$$

where the first term is a coverage *error determined by the structure-function modulus and the cutoff K_c, and the second is a* fit *error determined by training.*

Proof sketch. Couple $u \sim \mu_t$ and $\widehat{u}$ using the same input; then $W_2^2(\mu_{t+\Delta t}, \widehat{\mu}_{t+\Delta t}) \leq \mathbb{E}\|S_{\Delta t}u - \widehat{u}\|_{L^2}^2$. Insert $P_{\leq K_c}S_{\Delta t}u$, apply the triangle inequality, and bound the tail term by Lemma 4.8 (applied at time $t+\Delta t$). $\qquad\square$

Interpretation and experimental validation. At a fixed resolution (fixed K_c), Proposition 4.11 says that even a perfectly trained rectified flow cannot beat the coverage term $\omega(c_d/K_c)^{1/2}$ dictated by small-scale physics. This is precisely why spectrum matching (Figure 13) is a non-negotiable diagnostic on multiscale flows: if the surrogate loses the high-frequency tail, it is *necessarily* paying a coverage penalty in law. The remaining error is controlled by the training fit and the straightness properties of the learned velocity (via the continuous-time bounds in Section 4.1). Rectified flows improve efficiency precisely by reducing the curvature term in these bounds, so that a given coverage+fit accuracy can be reached with many fewer ODE steps than a diffusion-based surrogate such as GenCFD (Section 5.7).

5 Correctness and Curvature-Controlled Discretization

Organization. The previous subsection isolated the two dynamical ingredients that matter once the spatial resolution is fixed: the *fit* of the learned velocity field to the ideal conditional rectified velocity, and the *discretization error* incurred when the learned ODE is solved with finitely many steps. We now add

three complementary ingredients. First, we state the law-level correctness result for the ideal conditional barycentric velocity. Second, because our EMA/blending controller was introduced specifically to stabilize *OOD sampling*, we state a separate OOD-focused theorem for the blended sampler; this theorem is distinct in nature from the generic correctness statement and should be read as a structural analysis of the regime studied empirically in Section 7. Third, we combine the finite-resolution coverage term from Section 4.3, the continuous-time fit bound, and the discretization bound into a single conditional law-level decomposition:

$$\text{coverage} + \text{fit} + \text{discretization}.$$

Straightness enters the generic theory only through the discretization term. The EMA theorem below addresses the additional, practically important OOD regime in which the learned field develops oscillatory errors along rectification time.

5.1 Exact transport under the conditional barycentric rectified velocity

Proposition 5.1 (Exact conditional transport under the barycentric velocity)**.** *Fix a condition c. Let $\pi_0^c, \mu_1^c \in \mathcal{P}(\mathcal{U})$ be the reference and target conditional laws, let γ^c be a coupling of (π_0^c, μ_1^c), and define the rectified interpolation*

$$U_\tau = (1 - \tau)\Xi + \tau U_f, \qquad (\Xi, U_f) \sim \gamma^c.$$

Let

$$\rho_\tau^c := \text{Law}(U_\tau \mid C = c)$$

and define the conditional barycentric velocity

$$v^\star(u, \tau; c) = \mathbb{E}[U_f - \Xi \,|\, U_\tau = u,\, C = c], \qquad \rho_\tau^c\text{-a.e. } u.$$

Assume, for instance on a finite-dimensional Galerkin discretization of $\mathcal{U}$, that the continuity equation

$$\partial_\tau \rho_\tau^c + \nabla \cdot \left(\rho_\tau^c \, v^\star(\cdot, \tau; c)\right) = 0 \tag{33}$$

admits a unique regular Lagrangian flow X_τ^c associated to

$$\dot{u}_\tau = v^\star(u_\tau, \tau; c).$$

Then

$$(X_1^c)_\# \pi_0^c = \mu_1^c.$$

In other words, the ideal conditional barycentric rectified velocity transports the reference law exactly to the target conditional law.

Proof sketch. By construction, ρ_τ^c is the law of the random interpolation $U_\tau = (1 - \tau)\Xi + \tau U_f$. For every smooth test function φ,

$$\frac{d}{d\tau} \mathbb{E}[\varphi(U_\tau) \mid C = c] = \mathbb{E}[\nabla\varphi(U_\tau) \cdot (U_f - \Xi) \,|\, C = c].$$

Conditioning further on U_τ gives

$$\frac{d}{d\tau} \mathbb{E}[\varphi(U_\tau) \mid C = c] = \mathbb{E}[\nabla\varphi(U_\tau) \cdot v^\star(U_\tau, \tau; c) \,|\, C = c],$$

which is exactly the weak form of (33). Since $\rho_0^c = \pi_0^c$ and uniqueness holds for the continuity equation in the chosen finite-dimensional setting, it follows that $\rho_\tau^c = (X_\tau^c)_\# \pi_0^c$ for all τ, hence $\rho_1^c = (X_1^c)_\# \pi_0^c = \mu_1^c$. $\quad\square$

Proposition 5.1 is the law-level correctness statement underlying the method. It says that the ideal conditional rectified-flow ODE is not merely heuristic: at the population level, it transports the reference law to the target conditional law exactly. The only remaining issues are therefore approximation of the ideal velocity by v_θ, numerical discretization of the learned ODE, and the unavoidable loss of unresolved high frequencies at finite spatial resolution.

5.2 A compact interpretation of straightness

The local truncation error result in Lemma 4.2 shows that the relevant notion of straightness is not a purely geometric property of the sample path u_τ itself, but the variation of the learned *velocity field along that path*:

$$\frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

This is the precise quantity that determines how many explicit steps are required to integrate the learned transport stably. When this trajectory-wise variation is small, the learned flow behaves almost like "chord shooting" and very few ODE steps suffice. When it oscillates strongly, the sampler must reduce the step size or regularize the velocity direction, which is exactly the role of the EMA-based controller introduced earlier.

The OOD regime. In the out-of-distribution conditional settings studied in our experiments, the learned velocity field can encounter regions of state space that were less thoroughly represented during training. Empirically this manifests as stronger oscillations of $\tau \mapsto v_\theta(u_\tau, \tau; c)$, even when the overall conditional sample quality remains good. The EMA-based straightness proxy is designed precisely for this regime: it does not change the learned law in the continuous-time limit, but it makes the numerical integration of the learned ODE substantially more stable when these oscillations appear.

5.3 OOD stabilization by EMA blending

The EMA-based controller used in our sampler was not introduced to establish generic correctness of rectified flow. Its practical purpose is narrower: in the out-of-distribution macro–micro regime studied in Section 7, the learned velocity field can become substantially more oscillatory from one rectification step to the next, which makes explicit integration brittle. The role of EMA/blending is to suppress this oscillatory component while preserving the slowly varying part of the transport. Accordingly, the theorem below is not a replacement for the exact-fit comparison of Theorem 4.1; it is an additional structural result for the OOD stabilization mechanism.

Setup. Fix a condition c and let U_τ solve the ideal conditional rectified ODE

$$\dot{U}_\tau = v^\star(U_\tau, \tau; c), \qquad U_0 \sim \pi_0^c. \tag{34}$$

Along this ideal path, define

$$g(\tau) := v^\star(U_\tau, \tau; c), \tag{35}$$

and the learned-field error

$$\varepsilon(\tau) := v_\theta(U_\tau, \tau; c) - g(\tau). \tag{36}$$

Thus

$$v_\theta(U_\tau, \tau; c) = g(\tau) + \varepsilon(\tau).$$

Let E_λ denote the causal exponential moving average operator in rectification time with bandwidth $\lambda > 0$. In continuous time one may write, for a trajectory-valued signal f,

$$(E_\lambda f)(\tau) := \frac{1}{\lambda} \int_0^\tau e^{-(\tau-s)/\lambda} f(s)\, ds, \tag{37}$$

up to the usual normalization convention. The precise convention affects only constants below.

We measure the total approximation error along the ideal path by

$$\varepsilon_{\text{approx}}^2(c) := \int_0^1 \mathbb{E}\big[\|\varepsilon(\tau)\|^2 \,\big|\, C = c\big]\, d\tau. \tag{38}$$

We also define the total along-trajectory variation of the ideal conditional velocity by

$$S_{*,\text{tot}}^2(c) := \int_0^1 \mathbb{E}\big[\|\dot{g}(\tau)\|^2 \,\big|\, C = c\big]\, d\tau, \tag{39}$$

where

$$\dot{g}(\tau) = \partial_\tau v^\star(U_\tau, \tau; c) + J_u v^\star(U_\tau, \tau; c)\, v^\star(U_\tau, \tau; c). \tag{40}$$

This is exactly the same total along-trajectory derivative that drives the local truncation error in Lemma 4.2.

Oscillatory-error regime. The EMA controller is useful only when the learned error has a genuinely oscillatory component in rectification time. To encode this structurally, let $\widehat{\varepsilon}(\omega)$ denote the temporal Fourier transform of $\varepsilon(\tau)$ along the rectification variable, and assume that for some $\eta \in (0, 1]$,

$$\int_{|\omega|>1/\lambda} \mathbb{E}\big[|\widehat{\varepsilon}(\omega)|^2 \,\big|\, C = c\big]\, d\omega \;\geq\; \eta \int_{\mathbb{R}} \mathbb{E}\big[|\widehat{\varepsilon}(\omega)|^2 \,\big|\, C = c\big]\, d\omega. \tag{41}$$

For the exponential moving average, the transfer function has the form

$$H_\lambda(\omega) = \frac{1}{1 + i\lambda\omega}$$

up to convention, so $|H_\lambda(\omega)|^2$ decays like $(1 + \lambda^2\omega^2)^{-1}$. Hence the high-frequency part of the error is strictly damped. We summarize this damping by the smoothing ratio

$$\sigma^2(c, \lambda) := \frac{\int_0^1 \mathbb{E}\big[\|E_\lambda \varepsilon(\tau)\|^2 \,\big|\, C = c\big]\, d\tau}{\int_0^1 \mathbb{E}\big[\|\varepsilon(\tau)\|^2 \,\big|\, C = c\big]\, d\tau}. \tag{42}$$

Under (41), one has

$$\sigma^2(c, \lambda) \leq 1 - c_0\eta \tag{43}$$

for a universal constant $c_0 > 0$ depending only on the EMA convention. In particular, $\sigma(c, \lambda) < 1$ whenever a nontrivial portion of the error lies above the EMA cutoff frequency.

A continuous-time surrogate for the blended sampler. The actual sampler in our experiments uses discrete EMA updates and an adaptive blend weight α_t. To isolate the mechanism analytically, we consider the continuous-time fixed-α surrogate

$$\widetilde{v}_\alpha := (1 - \alpha)\, v_\theta + \alpha\, E_\lambda v_\theta, \qquad \alpha \in [0, 1], \tag{44}$$

and let $\widetilde{U}_\tau$ solve

$$\dot{\widetilde{U}}_\tau = \widetilde{v}_\alpha(\widetilde{U}_\tau, \tau; c), \qquad \widetilde{U}_0 = U_0. \tag{45}$$

This idealization captures the same bias–variance tradeoff as the practical adaptive controller: smoothing suppresses oscillatory error but introduces a bias proportional to how much the *ideal* field itself varies along rectification time.

Theorem 5.2 (EMA stabilization in the oscillatory OOD regime)**.** *Assume that $v_\theta(\cdot, \tau; c)$ and $\widetilde{v}_\alpha(\cdot, \tau; c)$ are uniformly L-Lipschitz in u, and assume the oscillatory-error condition* (41)*. Then there exists a universal constant $C_{\mathrm{ema}} > 0$ such that*

$$\Big(\mathbb{E}\big[\|\widetilde{U}_1 - U_1\|^2 \,\big|\, C = c\big]\Big)^{1/2} \;\leq\; e^L \Big[\big(1 - \alpha(1 - \sigma(c, \lambda))\big)\, \varepsilon_{\mathrm{approx}}(c) \;+\; C_{\mathrm{ema}}\, \alpha\, \lambda\, S_{*,\mathrm{tot}}(c)\Big]. \tag{46}$$

The corresponding raw-field bound from Theorem 4.1 is

$$e^L\, \varepsilon_{\mathrm{approx}}(c).$$

Consequently, EMA blending gives a strictly sharper upper bound whenever

$$(1 - \sigma(c, \lambda))\, \varepsilon_{\mathrm{approx}}(c) \;>\; C_{\mathrm{ema}}\, \lambda\, S_{*,\mathrm{tot}}(c). \tag{47}$$

Proof sketch. Apply the same Grönwall comparison used in Theorem 4.1, but with the blended field $\widetilde{v}_\alpha$ in place of v_θ. Along the ideal path U_τ one has

$$\widetilde{v}_\alpha(U_\tau, \tau; c) - g(\tau) = (1 - \alpha)\varepsilon(\tau) + \alpha E_\lambda \varepsilon(\tau) + \alpha(E_\lambda g(\tau) - g(\tau)).$$

Taking conditional L^2 norms in τ and using Minkowski's inequality yields

$$\|(1 - \alpha)\varepsilon + \alpha E_\lambda \varepsilon\|_{L^2_\tau} \leq \left(1 - \alpha + \alpha\sigma(c, \lambda)\right)\varepsilon_{\text{approx}}(c).$$

For the bias term, the standard causal-filter estimate gives

$$\|E_\lambda g - g\|_{L^2_\tau} \leq C_{\text{ema}}\,\lambda\,\|\dot{g}\|_{L^2_\tau},$$

which becomes $C_{\text{ema}}\lambda S_{*,\text{tot}}(c)$ after conditioning and integration. Combining the two estimates and applying Grönwall yields (46). The improvement criterion (47) is immediate by comparison with the unsmoothed bound. $\square$

Interpretation. The bound (46) has the exact interpretation needed for the OOD sampler study:

- The factor $(1 - \sigma)\varepsilon_{\text{approx}}$ is the *oscillatory error removed by EMA smoothing.*

- The term $\lambda S_{*,\text{tot}}$ is the *bias paid for smoothing*, and it is controlled by how much the *ideal conditional rectified velocity* varies along its own trajectories in rectification time.

Thus EMA blending is beneficial precisely when the learned OOD error is sufficiently oscillatory while the ideal rectified transport remains slowly varying in rectification time.

Experimental considerations. This is exactly the situation targeted in Section 7. There the model is frozen and only the sampler is varied. In the OOD macro–micro regime, the learned field develops pronounced step-to-step oscillations, which increases $\varepsilon_{\text{approx}}$ and makes the high-frequency component of the error non-negligible, hence $\sigma < 1$. At the same time, the ideal conditional rectified transport remains comparatively straight in rectification time, because the rectified-flow objective is designed to regress onto an approximately τ-stationary chord direction. The practical effect is the one seen in Tables 2–4: EMA-based smoothing stabilizes the sampler and improves the NFE–error tradeoff without harming conditional diversity.

5.4 Master bound: coverage + fit + discretization

We now combine the finite-resolution coverage term from Section 4.3, the continuous-time fit bound from Theorem 4.1, and the discretization bound from Corollary 4.3.

Fix a condition c, and let

$$\mu_1^c$$

denote the target conditional law at the forecast time. Let K_c be the effective spatial cutoff of the surrogate class, and let

$$P_{\leq K_c}$$

denote the corresponding low-frequency projection. We write

$$\mu_{1,\leq K_c}^c := (P_{\leq K_c})_{\#}\mu_1^c$$

for the projected target conditional law. Let $\widehat{\mu}_1^{c,\text{cts}}$ be the law of the learned *continuous-time* rectified flow and $\widehat{\mu}_1^{c,N}$ the law of the learned *discretized* rectified flow obtained with N explicit steps.

Theorem 5.3 (Conditional law-level error decomposition)**.** *Assume that the target conditional law μ_1^c satisfies the structure-function modulus hypothesis of Corollary 4.10, so that its unresolved high-frequency tail obeys*

$$W_2\big(\mu_1^c, \mu_{1,\leq K_c}^c\big) \;\lesssim\; \omega(c_d/K_c)^{1/2}. \tag{48}$$

Assume also that the learned velocity field satisfies the hypotheses of Theorem 4.1 and Corollary 4.3. Then there exists a constant $C(L) > 0$ such that

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \;\lesssim\; \underbrace{\omega(c_d/K_c)^{1/2}}_{coverage} + \underbrace{\varepsilon_{\mathrm{fit}}(c)}_{fit} + \underbrace{C(L)\,\varepsilon_{\mathrm{disc}}(c;N)}_{discretization}, \tag{49}$$

where

$$\varepsilon_{\mathrm{fit}}(c)^2 = \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau,\tau;c) - v^\star(U_\tau,\tau;c)\|^2 \,\big|\, C = c\big]\,d\tau$$

and

$$\varepsilon_{\mathrm{disc}}(c;N) = \frac{1}{N}\int_0^1 \Big(\mathbb{E}\big[\|\partial_\tau v_\theta(\widehat{U}_\tau,\tau;c) + J_u v_\theta(\widehat{U}_\tau,\tau;c)\,v_\theta(\widehat{U}_\tau,\tau;c)\|^2 \,\big|\, C = c\big]\Big)^{1/2}\,d\tau.$$

Proof sketch. Insert the projected target law $\mu_{1,\leq K_c}^c$ and the learned continuous-time law $\widehat{\mu}_1^{c,\mathrm{cts}}$ as intermediate terms:

$$W_2(\mu_1^c, \widehat{\mu}_1^{c,N}) \leq W_2(\mu_1^c, \mu_{1,\leq K_c}^c) + W_2(\mu_{1,\leq K_c}^c, \widehat{\mu}_1^{c,\mathrm{cts}}) + W_2(\widehat{\mu}_1^{c,\mathrm{cts}}, \widehat{\mu}_1^{c,N}).$$

The first term is exactly the coverage term (48). By Proposition 5.1, the ideal continuous-time rectified flow realizes the target conditional law at the population level, so the second term is controlled by Theorem 4.1 and equals the fit contribution. The third term is controlled by Corollary 4.3, giving the discretization contribution. □

Interpretation of the master bound. Theorem 5.3 gives the clean error taxonomy that the paper should emphasize throughout:

- *Coverage* is a hard floor imposed by finite spatial resolution and unresolved high-frequency content.

- *Fit* measures how accurately the learned neural velocity field approximates the ideal conditional barycentric transport.

- *Discretization* measures how difficult the learned transport is to integrate numerically, and this is where straightness enters.

In particular, straightness is *not* an additional continuous-time modeling error term. Instead, straighter learned transports reduce $\varepsilon_{\mathrm{disc}}(c;N)$, which is precisely why rectified flows can achieve the same law-level quality with many fewer function evaluations than diffusion-based samplers.

Reading the theory against the experiments. Equation (49) matches the empirical story in Section 6. The spectrum plots diagnose the coverage term by revealing whether the surrogate preserves high-wavenumber energy. The one-point Wasserstein and moment statistics diagnose overall conditional-law fidelity, which reflects both coverage and fit. Finally, the speed advantage of ReFlow is a discretization phenomenon: because the learned transport is substantially straighter along rectification time, the same conditional-law accuracy is reached with far fewer evaluations.

5.5 Optional regularity interpretation via structure functions

For completeness, we record the standard heuristic that structure-function control corresponds to Besov regularity and therefore to a quantitative high-frequency tail bound.

Lemma 5.4 (Structure functions and Besov smoothness)**.** *Let $u \in L^2(\mathbb{T}^d)$ and define*

$$[u]_{B_{2,\infty}^s} := \sup_{0 < |h| \leq 1} \frac{\|u(\cdot + h) - u(\cdot)\|_{L^2}}{|h|^s}.$$

If

$$S_r^2(u) \lesssim r^{2s} \qquad \text{for all } r \in (0,1],$$

then

$$[u]_{B_{2,\infty}^s} \lesssim 1.$$

Consequently, a law-level bound of the form

$$S_r^2(\mu) \lesssim r^{2s}$$

may be read as saying that typical samples drawn from μ have Besov regularity s, which is exactly the regularity controlling the Fourier-tail decay used in the coverage estimates.

Remark 5.5. In turbulence one often observes inertial-range power laws

$$S_r^2(\mu) \sim r^{\zeta_2}.$$

Heuristically this corresponds to $s \approx \zeta_2/2$, so the coverage term in Theorem 5.3 can be interpreted as a direct law-level manifestation of inertial-range scaling.

5.6 Implementation Details for PDEs

What is learned.   Our model is a *conditional noise-to-solution rectified flow.* Given an input/conditioning field u_i (and, when relevant, boundary data or other known inputs), we learn a velocity field

$$v_\theta(x, \tau; u_i),$$

where:

- u_i is the *conditioning variable,*

- x_τ is the *noise-initialized output state* transported in rectification time,

- $\tau \in [0,1]$ is the internal rectification-time variable.

The key point is that u_i is *not* the state being evolved by the rectified flow. It remains fixed throughout the trajectory and enters the network only as side information.

Training pairs.   We assume access to paired samples

$$(u_i, u_f), \qquad u_f = \mathcal{S}_{\Delta t}(u_i),$$

where $\mathcal{S}_{\Delta t}$ denotes the PDE solution operator over the forecast horizon of interest. In the stochastic/statistical setting considered in this paper, repeated perturbations around the same macro input u_i induce a conditional law of possible outputs; the purpose of the generator is to sample from this conditional output law.

Rectified interpolation used in training.   For each training pair (u_i, u_f), we sample source noise

$$\xi \sim \mathcal{N}(0, I)$$

and rectification time

$$\tau \sim \text{Unif}[0,1].$$

We then form the linear rectified interpolation

$$x_\tau = (1 - \tau)\,\xi + \tau\,u_f. \tag{50}$$

With this choice, the target velocity along the interpolation path is simply the constant chord direction

$$\dot{x}_\tau = u_f - \xi. \tag{51}$$

This is exactly the conditional rectified-flow objective introduced in Section 4.1: the network is trained to predict the transport direction from the current interpolated state x_τ and the condition u_i.

Algorithm 1 Conditional Rectified-Flow Training (PDE Setting)

Require: Dataset of paired states $\{(u_i, u_f)\}$ with $u_f = \mathcal{S}_{\Delta t}(u_i)$; velocity model v_θ

1: **for** each training iteration **do**
2:     Sample a training pair (u_i, u_f)
3:     Sample $\xi \sim \mathcal{N}(0, I)$
4:     Sample $\tau \sim \mathcal{U}(0, 1)$
5:     Form the rectified interpolation
$$x_\tau = (1 - \tau)\xi + \tau u_f$$
6:     Compute the conditional rectified-flow loss
$$\mathcal{L}(\theta) = \big\| v_\theta(x_\tau, \tau; u_i) - (u_f - \xi) \big\|^2$$
7:     Update θ by stochastic gradient descent / Adam
8: **end for**

Network parameterization.   The neural network takes as input the transported state x_τ, the conditioning field u_i, and a learned embedding of rectification time:

$$v_\theta(x_\tau, \tau; u_i) = \mathrm{UNet}_\theta\big(x_\tau,\, u_i,\, \Gamma(\tau)\big), \tag{52}$$

where

$$\Gamma(\tau) = \mathrm{MLP}\big(\mathrm{Sinusoid}(\tau)\big)$$

is a sinusoidal time embedding followed by an MLP. Concretely, x_τ and u_i are concatenated channelwise at the input, while $\Gamma(\tau)$ is injected into each block through standard feature-wise modulation / projection layers. Thus the time embedding is globally shared across the network, while each block has its own learned projection of that shared embedding.

Architecture overview.   Our implementation uses a U-Net / UViT-style backbone with residual blocks, attention, downsampling to a bottleneck, and symmetric upsampling with skip connections; see the Supplementary Material for the exact architecture. The output head predicts the velocity field itself, i.e. an estimate of the chord direction $u_f - \xi$ conditioned on the current transported state and on the PDE input. This is in contrast to score-based diffusion models, which predict either a score or a denoising residual inside a stochastic reverse-time sampler.

Sampling procedure.   At inference time, the condition u_i is fixed. We draw

$$\xi \sim \mathcal{N}(0, I),$$

set

$$x_0 = \xi,$$

and integrate the learned conditional ODE

$$\frac{d}{d\tau} x_\tau = v_\theta(x_\tau, \tau; u_i), \qquad x_{\tau=0} = \xi. \tag{53}$$

Algorithm 2 Conditional Rectified-Flow Sampling with Optional Curvature-Aware Control

---

Require: Condition/input field u_i; trained velocity model v_θ; number of steps N or adaptive controller

1: Sample $\xi \sim \mathcal{N}(0, I)$ and set $x_0 = \xi$
2: Initialize $\tau_0 = 0$
3: **if** using fixed-step integration **then**
4:     **for** $t = 0, \ldots, N - 1$ **do**
5:         $v_t \leftarrow v_\theta(x_t, \tau_t; u_i)$
6:         $\Delta\tau \leftarrow 1/N$
7:         $x_{t+1} \leftarrow x_t + \Delta\tau\, v_t$
8:         $\tau_{t+1} \leftarrow \tau_t + \Delta\tau$
9:     **end for**
10: **else**
11:     Initialize EMA state m_0
12:     **for** $t = 0, 1, \ldots$ until $\tau_t \geq 1$ **do**
13:         $v_t \leftarrow v_\theta(x_t, \tau_t; u_i)$
14:         Update EMA:
$$m_t \leftarrow \lambda m_{t-1} + (1 - \lambda)v_t$$
15:         Compute straightness proxy:
$$s_t \leftarrow \|v_t - m_t\|_2$$
16:         Choose blend weight α_t and step size $\Delta\tau_t$ from s_t
17:         Form blended velocity:
$$\widetilde{v}_t \leftarrow (1 - \alpha_t)v_t + \alpha_t m_t$$
18:         Update state:
$$x_{t+1} \leftarrow x_t + \Delta\tau_t\, \widetilde{v}_t$$
19:         $\tau_{t+1} \leftarrow \min\{1, \tau_t + \Delta\tau_t\}$
20:     **end for**
21: **end if**
22: **return** x_1

The final state x_1 is then interpreted as a sample from the learned approximation to the conditional output law associated with u_i.

The learned rectified transport is often straight enough that a small fixed number of Euler steps already gives excellent performance. The EMA/blending controller is introduced specifically to stabilize sampling in the more delicate OOD regime studied in Section 7, where the learned velocity exhibits stronger oscillations across rectification time. In that regime, the controller acts as a low-pass filter on the oscillatory component of the learned field and improves the NFE–error tradeoff without changing the underlying trained model.

Relation to the theory. This implementation matches the conditional theory exactly:

- the source law is Gaussian noise,

- the transported state is x_τ,

- the condition u_i is fixed throughout sampling,

- the ideal target velocity is the conditional barycentric transport direction,

- and the EMA/blending mechanism is an *additional OOD stabilization device*, not part of the generic exactness statement.

Practical efficiency. Because rectified-flow training promotes transports whose velocity varies comparatively slowly along rectification time, accurate sampling often requires only a handful of ODE evaluations. This is the computational advantage that distinguishes ReFlow from diffusion-based PDE surrogates: instead of integrating a long reverse-time stochastic process, we solve a short deterministic conditional transport ODE.

5.7 Computational Efficiency Comparison

Conditional diffusion surrogates such as GenCFD generate samples by integrating a reverse-time stochastic process whose trajectory typically requires many network evaluations before reaching the target conditional law. Even with accelerated samplers, this procedure usually remains expensive because each evaluation acts only as a local refinement step. In our setting, this cost is especially significant since every network call operates on a moderate-to-high resolution spatial field.

ReFlow replaces this reverse-time stochastic sampling procedure by a deterministic *conditional transport ODE*. For a fixed input field u_i, we draw source noise ξ and solve

$$\frac{d}{d\tau} x_\tau = v_\theta(x_\tau, \tau; u_i), \qquad x_0 = \xi,$$

returning x_1 as the generated sample. The computational advantage does not come from changing the conditioning information or the target conditional law, but from changing the *sampling geometry*: the learned rectified transport varies substantially less along rectification time than the stochastic diffusion trajectory, so explicit integration can be performed with far fewer evaluations.

This distinction is important. The benefit of rectified flow is not that it introduces new spatial capacity or accesses higher frequencies than diffusion at the same grid resolution. Both ReFlow and GenCFD operate under the same effective spectral cutoff imposed by resolution and architecture. Rather, rectification makes the *path from source noise to conditional output law easier to integrate numerically*. In the terminology of Section 5, rectified flow improves the *discretization* term: straighter learned transports require fewer function evaluations to reach the same law-level accuracy.

The curvature-aware sampler further improves this advantage in the regime where the learned velocity becomes oscillatory along rectification time. This is particularly relevant in the OOD macro–micro setting of Section 7, where we keep the trained model fixed and vary only the numerical sampler. There, the adaptive controller suppresses high-frequency oscillations of the learned velocity and allocates smaller steps only where needed, while retaining large steps on the straight portions of the transport.

Figure 2: Inference cost versus model size. Both ReFlow and GenCFD use comparable backbone families, but ReFlow reaches the target conditional-law accuracy regime with substantially fewer neural function evaluations. In our experiments, ReFlow typically requires 4–8 ODE steps, whereas GenCFD requires 64–128 stochastic denoising steps. U-Net depth varies from 4 to 8 blocks (roughly 5.5M to 10.2M parameters).

Figure 2 quantifies the practical consequence. Across model sizes, ReFlow reaches the target conditional-law accuracy regime with only 4–8 ODE steps, whereas GenCFD typically requires 64–128 stochastic denoising steps. Since each step invokes a network of comparable scale, this reduction in neural function evaluations translates directly into lower inference cost.

6 Experiments

6.1 Experimental Setup

We benchmark our method, termed henceforth as *ReFlow*, against four neural surrogate models. *GenCFD* and *GenCFD ∘ FNO* are conditional diffusion surrogates following the framework introduced earlier in this section, whereas FNO and UViT serve as one-shot deterministic baselines. Detailed descriptions of all baselines are provided in **SM** L.

Datasets for Training and Evaluation. We consider three canonical 2D multi-scale PDE problems (see the Supplementary Material for precise mathematical formulations and solver details):

SL2D *Shear Layer in 2D.* This setup models the evolution of an incompressible shear layer, initially concentrated near a horizontal interface, which rolls up into intricate vortical structures over time. We generate approximate solutions by numerically solving the 2D Navier–Stokes system (with periodic boundaries) at a resolution of 512^2, then downsample to 128^2 for training and testing. The data has been generated with the spectral viscosity code [32, 29].

CS2D *Cloud-Shock Interaction in 2D.* In this popular compressible-flow test, a shock wave moves through a higher-density "cloud" region, triggering complex wave interactions and small-scale turbulent mixing in the wake. We solve the compressible Euler system at an effective resolution of 256^2 using a GPU-optimized finite-volume ALSVINN code of [23, 8], then also downsample to 128^2.

RM2D *Richtmeyer–Meshkov in 2D.* In this case, a shock wave interacts with a density interface separating two fluids, depositing vorticity and triggering vigorous mixing. We numerically solve the compressible Euler system on a 256^2 grid, then downsample to 128^2 to create the training and test data. The data has been generated with a high-resolution finite-volume ALSVINN code of [8]

Training and evaluation protocol. All models are trained on paired samples

$$(u_i, u_f), \qquad u_f = \mathcal{S}_{\Delta t}(u_i),$$

where u_i is the input / conditioning field and u_f is the PDE state at the forecast horizon. For the probabilistic models (GenCFD and ReFlow), the goal is to learn the *conditional output law*

$$p(u_f \mid u_i),$$

rather than only a single-point prediction. During training, however, the models are only given paired realizations (u_i, u_f) from the dataset; the conditional law is learned implicitly from the collection of such pairs.

Macro–micro evaluation and conditional laws. Our main evaluation target is the conditional law associated with a *fixed* macroscopic input. Concretely, at test time we choose a macro/input state $\widehat{u}_i$ and aim to compare the model-generated law

$$\widehat{p}(\,\cdot\,\mid \widehat{u}_i)$$

with a reference conditional ensemble obtained from the high-fidelity PDE solver. Since the exact conditional law is not analytically available, we approximate it through a macro–micro perturbation protocol: starting from the macro state $\widehat{u}_i$, we generate many nearby microscopic perturbations, evolve each perturbed state with the PDE solver, and collect the resulting outputs into an empirical conditional ensemble. This empirical ensemble is our ground-truth approximation of the output law associated with the fixed macro condition $\widehat{u}_i$.

Thus, throughout the experiments, the conditioning/input field is held fixed at the macro level, while diversity appears at the micro level through the induced spread of outputs. This is exactly the statistical object that ReFlow and GenCFD are designed to model.

Matched and shifted conditional regimes. We report two evaluation regimes:

1. **Matched regime.** The macro/input state $\widehat{u}_i$ is drawn from the same broad family as the training inputs. This is the easier setting, although the evaluation is still conditional because the model is asked to generate an ensemble at a fixed macro condition.

2. **Shifted / OOD regime.** The macro/input state $\widehat{u}_i$ is drawn from a different family or parameter range than those seen during training. This probes whether the learned conditional sampler remains statistically faithful when queried out of distribution.

In the rebuttal-driven experiments of Section 7, the macro–micro protocol is made explicit: the model is frozen, the macro conditions are chosen in an OOD regime, and only the numerical sampler is varied. This is precisely the setting targeted by the EMA-based stabilization analysis in Section 5.3.

Role of deterministic baselines. FNO and UViT are deterministic predictors and therefore do not directly define a conditional output law. To make them comparable on statistical metrics, we apply the same macro–micro perturbation protocol at the input level and aggregate their outputs across perturbed inputs into an empirical ensemble. This does *not* turn them into intrinsically probabilistic models; rather, it provides a controlled way to compare how much conditional variability they preserve under perturbations of the macro input. By contrast, ReFlow and GenCFD generate diversity intrinsically through noise sampling at fixed u_i.

Training budget and architectural parity. To keep the comparison computationally controlled, we train each model under a fixed optimization budget and report the best checkpoint achieved within that budget. Under the budgets used here, ReFlow and GenCFD are compared with matched backbone families and similar parameter counts, so the main difference is not representational scale but sampling mechanism. In particular, ReFlow's advantage should be read as a gain in *conditional-law accuracy per neural function evaluation*, rather than as a trivial consequence of larger models.

6.2 Evaluation Metrics

We evaluate the generative performance of each method using metrics that probe conditional-law fidelity rather than only pointwise prediction quality.

Mean error. Let $\bar{u}_{\text{model}}$ and $\bar{u}_{\text{ref}}$ denote the empirical means of the model-generated and reference conditional ensembles for a fixed macro/input state. We report the relative L^2 discrepancy between these means. This measures whether the surrogate captures the large-scale conditional average correctly.

Standard-deviation error. Let σ_{model} and σ_{ref} denote the pointwise empirical standard deviations of the generated and reference conditional ensembles. We report the normalized L^2 discrepancy between them. This measures whether the model reproduces the correct spatial pattern and magnitude of conditional variability.

One-point Wasserstein distance. To compare the local output distributions themselves, we use the spatially averaged one-point Wasserstein-1 distance. Let μ and $\widehat{\mu}$ be two laws on fields $u : D \to \mathbb{R}^m$. For each spatial point $x \in D$, define the one-point marginals

$$\mu_x := (\text{ev}_x)_{\#}\mu, \qquad \widehat{\mu}_x := (\text{ev}_x)_{\#}\widehat{\mu}.$$

Our reported metric is

$$W_1^{(1)}(\mu, \widehat{\mu}) := \int_D W_1(\mu_x, \widehat{\mu}_x)\, dx. \tag{54}$$

By Kantorovich–Rubinstein duality, each $W_1(\mu_x, \widehat{\mu}_x)$ controls the discrepancy of all pointwise 1-Lipschitz observables at the spatial location x. Thus $W_1^{(1)}$ is exactly a $k = 1$ correlation-marginal metric in the statistical-solution sense [17], averaged over space.

These three metrics probe complementary aspects of the conditional law:

- mean error measures whether the conditional average is correct,

- standard-deviation error measures whether the spread is correct,

- one-point Wasserstein distance measures whether the local conditional output distributions themselves are correct.

Together with the spectral diagnostics reported below, they provide a law-level view of whether a surrogate captures both large-scale structure and fine-scale conditional variability.

Baselines and evaluation settings. All results are reported under a fixed training budget per model, and the best checkpoint within that budget is retained. Under this budget, ReFlow is compared primarily against GenCFD as the corresponding conditional probabilistic baseline, using matched backbone families and similar parameter counts. Deterministic baselines such as FNO and UViT are included as references for one-shot prediction quality, but they should not be interpreted as intrinsically modeling the conditional output law.

At inference time, ReFlow requires only **8** rectified-flow ODE steps to reach the reported accuracy regime, whereas diffusion baselines such as GenCFD typically require **128** denoising steps. This is the central efficiency comparison of the paper: both methods target the same conditional-law prediction problem, but ReFlow reaches that regime with far fewer neural function evaluations.

For deterministic baselines, ensemble statistics are estimated by applying the macro–micro perturbation protocol at the input level and aggregating the resulting outputs. For ReFlow and GenCFD, diversity is generated intrinsically by sampling latent noise at fixed conditioning input u_i.

Since FNO, and UViT produce *deterministic* predictions, we approximate their spread by an *ensemble perturbation* strategy (**SM** K.2), where each baseline is fed slightly perturbed inputs and outputs are aggregated to form a sample set. In contrast, both the original GenCFD (baseline) and our *ReFlow* are inherently *probabilistic*, requiring no auxiliary procedure to generate diverse samples.

Table 1: Comparison of models across datasets CS2D, SL2D, and RM2D, in terms of mean relative error (e_μ), standard deviation relative error (e_σ), and Wasserstein-1 distance (W_1). Best-performing model is colored in Blue and second-best performing model in Orange.

Model	Metric	CS2D				SL2D		RM2D			
		ρ	m_x	m_y	E	u_x	u_y	ρ	m_x	m_y	E
ReFlow	e_μ	0.0477	0.0332	0.041	0.015	0.034	0.189	0.018	0.032	0.020	0.021
	e_σ	0.1005	0.072	0.078	0.0584	0.071	0.077	0.032	0.046	0.046	0.085
	W_1	0.0091	0.0107	0.0124	0.0143	0.0214	0.0164	0.0033	0.0036	0.0028	0.0017
GenCFD	e_μ	0.0830	0.0619	0.127	0.0280	0.039	0.267	0.0049	0.0010	0.0025	0.0025
	e_σ	0.195	0.197	0.244	0.169	0.092	0.072	0.0351	0.0254	0.0435	0.0435
	W_1	0.0151	0.0184	0.0185	0.0247	0.0276	0.0213	0.0092	0.0016	0.0049	0.0049
UViT	e_μ	0.111	0.078	0.127	0.0479	0.233	0.623	0.070	0.070	0.071	0.052
	e_σ	0.415	0.343	0.412	0.296	0.28	0.178	0.425	0.570	0.570	0.617
	W_1	0.087	0.085	0.158	0.172	0.270	0.256	0.060	0.055	0.060	0.036
FNO	e_μ	0.0989	0.0748	0.0930	0.0383	0.058	0.408	0.085	0.070	0.063	0.067
	e_σ	0.2573	0.2779	0.3188	0.2777	0.137	0.110	0.366	0.443	0.436	0.450
	W_1	0.1455	0.1660	0.1879	0.1884	0.184	0.150	0.096	0.051	0.056	0.062
GenCFD ∘ FNO	e_μ	0.0638	0.0454	0.0603	0.0204	0.055	0.393	0.040	0.027	0.039	0.041
	e_σ	0.1099	0.0969	0.1245	0.0974	0.131	0.100	0.091	0.075	0.091	0.090
	W_1	0.0467	0.0534	0.0774	0.0743	0.166	0.135	0.0269	0.0158	0.0293	0.0273

Figure 3: Energy-spectrum evolution for a random cloud–shock initial datum. ReFlow (blue) tracks high-wavenumber energy faster and more accurately than GenCFD (red).

6.3 Results.

Table 1 compares five surrogate models (ReFlow, together with the four baselines) on the three PDEs learning tasks using the mean error (e_μ), spread error or *standard deviation* (e_σ) and the distribution-level Wasserstein-1 distance (W_1). On the cloud–shock and shear-layer datasets (CS2D, SL2D) the rectified-flow model (ReFlow) attains the lowest values on all three metrics, indicating that its samples most closely match both the mean behaviour and the higher-order statistics of the ground truth. The hybrid *GenCFD∘FNO*

Figure 4: Density trajectories for Sample 1: ReFlow (top) versus GenCFD (bottom).

reduces the gap to ReFlow relative to its GenCFD component, but still records noticeably larger errors, whereas the one-shot deterministic baselines (FNO, UViT) show the largest deviations, especially in e_σ and W_1, confirming their difficulty in capturing output variability. RM2D is the only benchmark whose test set remains strictly in-distribution (in the sense defined earlier). Under this easier regime the deterministic baselines come closest to the conditional-diffusion surrogates, but only here. Their drop-off on the out-of-distribution tasks underscores the stronger generalisation of conditional diffusion models. Under identical training budgets, ReFlow achieves lower errors on CS2D and SL2D compared to all baselines, including GenCFD with the same architecture and model size. This highlights ReFlow's superior convergence efficiency despite parity in model capacity and training iterations.

Moreover as visualized in the **SM**, ReFlow generates samples of very high quality, matching the qualitative features of the ground truth and capturing features such as (interacting) vortices as well as propagating shock waves very accurately. Another aspect where ReFlow really shines in being able to generate the correct point pdfs. Although already indicated in the very low 1-point Wasserstein distance errors from Table 1, we present 1-point pdfs in the **SM** to illustrate this observation.

Another key indicator of the quality of approximation of multiscale PDE solutions is the energy spectrum [25]. In Figure 13, we plot the (log) spectra for the energy variable of a randomly chosen Cloud Shock initial datum at four different Diffusion times, $\tau \in \{0.25, 0.50, 0.75, 1.00\}$ to observe that i) the solution is indeed highly multiscale, with spectra decaying as a power law over a range of frequencies ii) ReFloW approximates the spectra accurately within a few (5) steps and iii) on the other hand, for these few steps in solving the underlying reverse SDE, a score-based Diffusion model such as GenCFD, struggles to approximate the relevant small scales. It will require much more sampling steps to do so. These results also showcase how ReFlow is able to infer the correct statistical solutions with significantly less ODE solve steps and is hence, much faster, than a diffusion based model such as GenCFD. This gain in inference speed is also reinforced from Figure 4, where we compare ReFlow (RF) and GenCFD reconstructions of the density field ρ for the Cloud-Shock interaction over five diffusion times $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. We see that ReFlow inpaints fine-scale features in far fewer steps, whereas GenCFD remains visibly much more noisy at these small number of steps. See **SM** M.7 for further visualizations of this effect.

7   Additional empirical analysis (integrators, robustness, and diversity)

This section consolidates additional experiments conducted with the goal of making the computational trade-offs and the role of the curvature-aware controller explicit. The emphasis is on (i) solver choices for the learned rectified-flow ODE, (ii) robustness of the controller to its hyperparameters, and (iii) distributional fidelity / diversity under the macro–micro evaluation protocol.

Table 2: **Fixed-step ODE integrators** at sampling time (ShearLayer2D, OOD macro–micro; 10 macros $\times$ 20 micros). We fix the trained rectified-flow model and vary only the integrator. NFE is the number of velocity evaluations; lower is faster. Cost$\times$Err is defined in (56).

Method	Avg. NFE $\downarrow$	Rel. L^2 Error $\downarrow$ (mean $\pm$ std)	Cost$\times$Err $\downarrow$
Model-Baseline (built-in sampler)	32.0	0.2533 ± 0.0382	8.11
`torchdiffeq` Midpoint	32.0	0.2533 ± 0.0382	8.11
Euler (16 steps)	16.0	0.2489 ± 0.0371	3.98
RK2 (16 steps; 32 NFEs)	32.0	0.2533 ± 0.0379	8.11
RK4 (16 steps; 64 NFEs)	64.0	0.2540 ± 0.0381	16.26

7.1 Protocol recap: macro–micro ensembles, OOD macros, and metrics

Macro–micro conditional ensembles. To evaluate *statistical fidelity* rather than only pointwise accuracy, we follow a macro–micro protocol. For each dataset, we select N_{macro} macroscopic states ("macros") and for each macro generate N_{micro} microscopic perturbations ("micros") yielding a reference ensemble of size $N_{\text{macro}} \times N_{\text{micro}}$. This makes diversity concrete: for each fixed macro, the ground-truth solver produces an empirical conditional distribution over micros, and the model produces its own empirical conditional distribution. We compare these distributions directly via Wasserstein distances (below), which is the relevant question for statistical surrogates.

OOD macro selection. Unless otherwise stated, we report results in an out-of-distribution (OOD) regime by choosing $N_{\text{macro}} = 10$ macros from shifted initial-condition families / parameter ranges, and $N_{\text{micro}} = 20$ micros per macro (200 conditional samples per dataset). All models are frozen; only the sampling/integration procedure is varied.

Metrics. We report: (i) *relative L^2 error* against the PDE solution,

$$\text{Rel-}L^2(\widehat{u}, u) := \frac{\|\widehat{u} - u\|_{L^2}}{\|u\|_{L^2}}, \tag{55}$$

(ii) *NFE* (neural function evaluations), i.e. the number of velocity-field evaluations per generated sample, and (iii) a combined cost–accuracy scalar

$$\text{Cost} \times \text{Err} := (\text{Rel-}L^2) \times (\text{NFE}), \tag{56}$$

which is convenient for summarizing the NFE–error plane (lower is better). Distributional fidelity is measured via empirical W_1 between conditional ensembles; we report both aggregated and per-variable W_1 (Section 7.5).

7.2 Integrator study at sampling time: fixed-step baselines vs. curvature-aware control

A recurring concern is whether the gains are merely a consequence of choosing a particular numerical solver. To isolate this, we fix the trained rectified-flow model and vary *only* the integrator used to solve the rectified-flow ODE at sampling time, starting from noise and integrating from rectified time $\tau = 0$ to $\tau = 1$. We include a reference implementation from `torchdiffeq` and standard explicit fixed-step schemes. We report the aggregated results on *ShearLayer2D* in the OOD macro–micro regime; the second benchmark exhibits the same qualitative trends and is reported in the appendix.

Observation: Euler has a tuned "sweet spot" but remains brittle. Among fixed-step schemes, Euler with 16 steps is the strongest baseline in this regime, improving on 32/64-NFE schemes in Cost$\times$Err. However, in multiscale mildly stiff regimes, fixed-step performance is highly sensitive to the chosen step budget: slightly fewer steps can degrade accuracy sharply, while increasing steps can *also* worsen error due to accumulated discretization bias along curved trajectories. Thus, even simple Euler is not a drop-in robust choice: it requires per-dataset/per-regime tuning to hit its efficient operating point.

Table 3: **Hyperparameter robustness** of the curvature-aware adaptive sampler (ShearLayer2D, OOD macro–micro). Across 20 controller configurations, Avg. NFE stays in a narrow band and relative errors vary by $< 1\%$, indicating the controller is not brittle and does not rely on a narrow tuning "sweet spot".

Config	Avg. NFE ↓	Rel. L^2 Error ↓ (mean ± std)	Cost×Err ↓
baseline	11.0	0.2374 ± 0.0389	2.62
ema_0.25	**10.7**	**0.2369 ± 0.0386**	**2.54**
ema_0.45	11.3	0.2361 ± 0.0384	2.67
alpha_0.05	11.0	0.2373 ± 0.0389	2.62
alpha_0.12	11.0	0.2373 ± 0.0389	2.62
alpha_0.20	11.0	0.2374 ± 0.0389	2.62
gamma_1.5	11.0	0.2374 ± 0.0389	2.62
gamma_2.0	11.0	0.2374 ± 0.0389	2.62
gamma_2.5	11.0	0.2374 ± 0.0389	2.62
gate_0.50	11.0	0.2374 ± 0.0389	2.62
gate_0.70	11.0	0.2374 ± 0.0389	2.62
calib_0.70_0.90	11.1	0.2371 ± 0.0387	2.63
calib_0.80_0.98	10.9	0.2372 ± 0.0387	2.60
adapt_1.5_0.75	12.8	0.2374 ± 0.0378	3.04
adapt_2.0_0.85	11.2	0.2360 ± 0.0376	2.63
no_ortho_filter	11.0	0.2374 ± 0.0389	2.62
damp_0.05	11.0	0.2373 ± 0.0389	2.62
damp_0.10	11.0	0.2373 ± 0.0389	2.61
damp_0.20	11.0	0.2370 ± 0.0389	2.60
damp_0.30	11.0	0.2368 ± 0.0389	2.60

7.3 Curvature-aware sampler: hyperparameter robustness and Pareto dominance

We next evaluate the curvature-based adaptive controller under a broad sweep of hyperparameters while holding the model fixed. The controller uses (i) an EMA-based straightness/curvature proxy on the learned velocity field, (ii) a mild velocity regularization/blending step triggered by curvature, and (iii) adaptive step sizing. We vary EMA time scale, thresholds, gating, damping, and calibration parameters across 20 configurations.

Observation: robust controller, automatic step allocation. Across all 20 configurations, Avg. NFE remains in a tight range (10.7–12.8) and the mean relative error stays within $[0.2360, 0.2374]$ (sub-1% relative variation), indicating that the controller does not require fragile tuning. This directly contrasts with fixed-step Euler, where efficiency is achieved only at a tuned step budget and can degrade rapidly outside it.

7.4 Best fixed-step baseline vs. best adaptive configurations

For clarity, Table 4 compares the strongest fixed-step baseline (Euler-16) against the top adaptive configurations on ShearLayer2D OOD.

Interpretation in the NFE–error plane. These comparisons summarize a consistent pattern: the adaptive curvature-aware sampler lies on (or very near) the Pareto frontier in the NFE–error plane, while fixed-step baselines are strictly dominated in the regimes tested. This is the practical meaning of the curvature theory: the controller allocates steps only where the learned transport bends, while retaining large steps when the flow is straight.

Table 4: **Best fixed-step baseline vs. top adaptive configs** (ShearLayer2D, OOD macro–micro). At roughly one third fewer velocity evaluations, the adaptive sampler improves both error and Cost×Err.

Method / Config	Avg. NFE	Rel. L^2 Err	Cost×Err	ΔNFE vs Euler	ΔErr vs Euler	Δ(Cost×Err)
Euler (16 steps)	16.0	0.2489	3.98	0%	0%	0%
ema_0.25	10.7	0.2369	2.54	-33.1%	-4.8%	-36.2%
calib_0.80_0.98	10.9	0.2372	2.60	-31.9%	-4.7%	-34.7%
damp_0.30	11.0	0.2368	2.60	-31.3%	-4.9%	-34.7%

7.5 Distributional fidelity and diversity: ensemble W_1 under macro–micro evaluation

A common concern for deterministic probability-flow ODE sampling is potential under-dispersion or reduced diversity. Our evaluation is designed to test this directly in the conditional setting where diversity is well-defined.

Empirical W_1 between conditional ensembles. For each macro, let $\{\widehat{u}^{(j)}\}_{j=1}^{N_{\mathrm{micro}}}$ be model samples and $\{u^{(j)}\}_{j=1}^{N_{\mathrm{micro}}}$ be reference samples. We compute a one-point (spatially averaged) empirical W_1 between the corresponding micro-ensembles, and then average across macros. We also report per-variable W_1 (density, momenta, energy) and an aggregated score.

Key empirical outcome. Across benchmarks, our rectified-flow model matches or improves upon the diffusion baseline in ensemble W_1 while using substantially fewer function evaluations. In particular, the macro–micro protocol provides a direct quantitative check against mode collapse: matching W_1 at fixed macro conditions indicates that the conditional output distribution is captured rather than collapsed. (Complete per-variable W_1 tables and additional datasets are reported in the appendix.)

7.6 Practical takeaway: speed requires both straight transports and curvature-aware integration

The integrator study separates two effects: (i) the rectified-flow training objective yields a transport that can be traversed with far fewer evaluations than score-based diffusion, and (ii) within this ODE setting, curvature-aware control is a robust way to realize the efficiency in stiff multiscale regimes without per-problem solver tuning. Empirically, this is exactly what Tables 2–4 show: the controller achieves lower error at lower NFE than the strongest tuned fixed-step baseline, and its performance is stable across wide hyperparameter ranges.

Appendix pointers. We provide: (a) the same integrator/robustness tables on the second benchmark, (b) NFE–error scatter plots (Pareto frontiers), and (c) detailed per-variable W_1 breakdowns and additional OOD regimes.

8 Conclusion and Future Work

We have demonstrated that rectified flows provide an efficient surrogate for sampling multi-scale PDE solutions: on a suite of challenging incompressible and compressible problems, our method matches the statistical fidelity of conditional diffusion models while requiring an order of magnitude fewer solver steps—yielding up to 22× faster inference in practice. Across matched and shifted initial-condition regimes, rectified flows consistently reproduce energy spectra, vorticity distributions, and one-point Wasserstein distances within sampling error, confirming their robustness and multi-scale accuracy.

Key Takeaways. On account of its straightening bias, ReFlow requires significantly fewer ODE steps at inference-time (8-10) than its conditional-diffusion-based counterparts (more than 128) to achieve the same level of performance on our statistical metrics – consult **SM** M for more details. Furthermore, ReFlow is much more training efficient, requiring up to 120,000 iterations in reaching the same level of performance, across

all experiments, as our other conditional diffusion baselines (which typically take 500-600,000 iterations), see **SM** M.6. Our results further demonstrate that straightening effects remain evident even when projecting down to a 2D PCA subspace (see **SM** M.7).

References

[1] Lemar Abdi et al. "Out-of-distribution detection in medical imaging via diffusion trajectories". In: *International Workshop on Uncertainty for Safe Utilization of Machine Learning in Medical Imaging.* Springer. 2025, pp. 91–101.

[2] Lemar Abdi et al. "Zero-Shot Image Anomaly Detection Using Generative Foundation Models". In: *Proceedings of the IEEE/CVF International Conference on Computer Vision.* 2025, pp. 3554–3563.

[3] Benedikt Alkin et al. "Universal Physics Transformers: A Framework For Efficiently Scaling Neural Operators". In: *The Thirty-eighth Annual Conference on Neural Information Processing Systems.* 2024. URL: https://openreview.net/forum?id=oUXiNX5KRm.

[4] Brett Barkley, Preston Culbertson, and David Fridovich-Keil. "SCOPED: Score-Curvature Out-of-distribution Proximity Evaluator for Diffusion". In: *arXiv preprint arXiv:2510.01456* (2025).

[5] Patrick Esser et al. "Scaling rectified flow transformers for high-resolution image synthesis". In: *Forty-first international conference on machine learning.* 2024.

[6] L.C. Evans. *Partial Differential Equations.* Graduate studies in mathematics. American Mathematical Society, 2010. ISBN: 9780821849743. URL: https://books.google.ch/books?id=Xnu0o_EJrCQC.

[7] Ulrik S. Fjordholm, Samuel Lanthaler, and Siddhartha Mishra. "Statistical Solutions of Hyperbolic Conservation Laws: Foundations". In: *Archive for Rational Mechanics and Analysis* 226.2 (Nov. 2017), pp. 809–849. ISSN: 1432-0673. DOI: 10.1007/s00205-017-1145-9. URL: https://doi.org/10.1007/s00205-017-1145-9.

[8] Ulrik S. Fjordholm et al. "Statistical solutions of hyperbolic systems of conservation law: Numerical approximation". In: *Mathematical Models and Methods in Applied Sciences* 30.3 (2020), pp. 539–609. DOI: 10.1142/S0218202520500141.

[9] Han Gao, Sebastian Kaltenbach, and Petros Koumoutsakos. "Generative Learning for Forecasting the Dynamics of Complex Systems". In: *arXiv preprint arXiv:2402.17157* (2024).

[10] Han Gao, Sebastian Kaltenbach, and Petros Koumoutsakos. "Generative Learning of the Solution of Parametric Partial Differential Equations Using Guided Diffusion Models and Virtual Observations". In: *arXiv preprint arXiv:2408.00157* (2024).

[11] Han Gao et al. "Bayesian conditional diffusion models for versatile spatiotemporal turbulence generation". In: *Computer Methods in Applied Mechanics and Engineering* 427 (2024), p. 117023.

[12] Zhongkai Hao et al. "Gnot: A general neural operator transformer for operator learning". In: *International Conference on Machine Learning.* PMLR. 2023, pp. 12556–12569.

[13] Alvin Heng, Alexandre H Thiery, and Harold Soh. "Out-of-distribution detection with a single unconditional diffusion model". In: *Advances in Neural Information Processing Systems* 37 (2024), pp. 43952–43974.

[14] Maximilian Herde et al. "Poseidon: Efficient foundation models for pdes". In: *Advances in Neural Information Processing Systems* 37 (2024), pp. 72525–72624.

[15] Nikola Kovachki et al. "Neural operator: Learning maps between function spaces with applications to pdes". In: *Journal of Machine Learning Research* 24.89 (2023), pp. 1–97.

[16] Samuel Lanthaler, Siddhartha Mishra, and Carlos Parés-Pulido. "Statistical solutions of the incompressible Euler equations". In: *Mathematical Models and Methods in Applied Sciences* 31.02 (2021), pp. 223–292.

[17] Samuel Lanthaler, Siddhartha Mishra, and Carlos Parés-Pulido. "Statistical solutions of the incompressible Euler equations". In: *Mathematical Models and Methods in Applied Sciences* 31.02 (2021), pp. 223–292.

[18] Zongyi Li et al. "Fourier neural operator for parametric partial differential equations". In: *arXiv preprint arXiv:2010.08895* (2020).

[19] Zongyi Li et al. "Geometry-Informed Neural Operator for Large-Scale 3D PDEs". In: *Thirty-seventh Conference on Neural Information Processing Systems*. 2023. URL: https://openreview.net/forum?id=86dXbqT5Ua.

[20] Zongyi Li et al. "Neural operator: Graph kernel network for partial differential equations". In: *arXiv preprint arXiv:2003.03485* (2020).

[21] Xingchao Liu, Chengyue Gong, and Qiang Liu. "Flow straight and fast: Learning to generate and transfer data with rectified flow". In: *arXiv preprint arXiv:2209.03003* (2022).

[22] Lu Lu et al. "Learning nonlinear operators via DeepONet based on the universal approximation theorem of operators". In: *Nature Machine Intelligence* 3.3 (2021), pp. 218–229.

[23] Kjetil O. Lye. "Computation of statistical solutions of hyperbolic systems of conservation laws". PhD thesis. 2020.

[24] Siddhartha Mishra and Alex (Eds.) Townsend. *Numerical Analysis meets Machine Learning*. Handbook of Numerical Analysis. Springer, 2024.

[25] Roberto Molinaro et al. "Generative AI for fast and accurate Statistical Computation of Fluids". In: *arXiv preprint arXiv:2409.18359* (2024).

[26] V Oommen et al. *Integrating neural operators with diffusion models improves spectral representation in turbulence modeling. arxiv*. 2024.

[27] A. Quarteroni and A. Valli. *Numerical approximation of Partial differential equations*. Vol. 23. Springer, 1994.

[28] Alfio Quarteroni, Andrea Manzoni, and Federico Negri. *Reduced basis methods for partial differential equations: an introduction*. Vol. 92. Springer, 2015.

[29] Tobias Rohner and Siddhartha Mishra. "Efficient Computation of Large-Scale Statistical Solutions to Incompressible Fluid Flows". In: *Proceedings of the Platform for Advanced Scientific Computing Conference*. PASC '24. ACM, June 2024. DOI: 10.1145/3659914.3659922. URL: http://dx.doi.org/10.1145/3659914.3659922.

[30] Chitwan Saharia et al. "Photorealistic text-to-image diffusion models with deep language understanding". In: *Advances in neural information processing systems* 35 (2022), pp. 36479–36494.

[31] Yang Song et al. "Score-based generative modeling through stochastic differential equations". In: *arXiv preprint arXiv:2011.13456* (2020).

[32] Eitan Tadmor. "Convergence of Spectral Methods for Nonlinear Conservation Laws". In: *SIAM Journal on Numerical Analysis* 26.1 (1989), pp. 30–44. DOI: 10.1137/0726003. URL: https://doi.org/10.1137/0726003.

[33] Haixu Wu et al. "Transolver: A Fast Transformer Solver for PDEs on General Geometries". In: *Forty-first International Conference on Machine Learning*. 2024. URL: https://openreview.net/forum?id=Ywl6pODXjB.

A   Theory appendix: conditional rectified flows for multiscale PDE surrogates

Purpose and scope.   This appendix provides the mathematical backbone for the theory statements made in the main text. The key points are the following.

1. Our model is a *conditional noise-to-solution rectified flow*: for a fixed input field u_i, it transports a simple reference sample ξ to a sample from the conditional output law of the PDE.

2. The ideal conditional barycentric rectified velocity is *correct at the level of laws*: its flow maps the reference law exactly to the target conditional law.

3. Once the effective spatial resolution is fixed, the total conditional-law error splits into three distinct pieces:

$$\text{coverage} + \text{fit} + \text{discretization}.$$

   Here coverage is an irreducible finite-resolution floor, fit measures approximation of the ideal conditional transport field by the learned neural field, and discretization measures the error incurred by numerically integrating the learned ODE.

4. The EMA/blending mechanism used in our sampler is *not* part of generic correctness. It is an additional stabilization device for the *OOD sampling regime*, where the learned velocity develops oscillatory errors along rectification time.

How to read this appendix.   Section B fixes the conditional law-level setting and clarifies what the experiments probe. Section C states the exact conditional transport result for the ideal barycentric rectified velocity and the L^2 projection property targeted by the training loss. Section D gives the continuous-time fit theorem for the learned conditional flow. Section E derives the discretization bounds and identifies the total derivative along trajectories as the relevant straightness quantity. Section F gives a separate OOD stabilization result for the EMA-blended sampler. Section G quantifies the finite-resolution coverage floor through structure functions and Fourier tails. Finally, Section H aggregates the pieces into the master law-level bound used in the main text, and Section I explains how this law-level viewpoint relates to the reported one-point metrics.

B   Setup: conditional laws of PDE outputs and what the experiments measure

State space and finite-dimensional surrogate.   We work on the periodic domain $\mathcal{D} = \mathbb{T}^d$ and consider state fields taking values in

$$\mathcal{U} = L^2(\mathcal{D}; \mathbb{R}^m),$$

or, in the incompressible case, in the divergence-free subspace when appropriate. In the actual implementation all fields are represented on a finite-dimensional grid / Galerkin discretization

$$\mathbb{R}^{d_N} \subset \mathcal{U}.$$

All arguments below are rigorous in that finite-dimensional setting; the Hilbert-space notation is retained because it matches the law-level viewpoint of statistical solutions.

Conditional target laws.   Let C denote the conditioning variable, which in our applications is the input field u_i (possibly together with boundary data or other known parameters). For a fixed realization c of C, let

$$\mu_1^c := \text{Law}(U_f \mid C = c)$$

be the conditional law of the PDE output at the forecast horizon. Let

$$\pi_0^c$$

be a simple reference law on $\mathcal{U}$; in the experiments we take $\pi_0^c = \mathcal{N}(0, I)$, independent of c.

Finite-resolution target law. At an effective cutoff K_c, the best law a bandlimited surrogate can hope to match is not the full conditional law μ_1^c but its projected version

$$\bar{\mu}_1^c := (P_{\leq K_c})_\# \mu_1^c. \tag{57}$$

Accordingly, the exact conditional transport result below is stated for a generic target conditional law ν^c, and in the finite-resolution master theorem we apply it with

$$\nu^c = \bar{\mu}_1^c.$$

What the experiments probe. Our empirical evaluation is conditional. At test time, a macro/input state $\widehat{u}_i$ is fixed, and both the model and the reference PDE solver are used to generate ensembles of outputs associated with that fixed macro condition. The reported statistics—mean error, spread error, and one-point Wasserstein distance—therefore probe whether the model reproduces the *conditional law* of outputs at fixed input, rather than only an unconditional average across inputs.

Law-level versus marginal viewpoints. From the abstract measure-theoretic perspective, a natural global metric on output laws is Wasserstein distance on $\mathcal{U}$, especially W_2 because it interacts cleanly with L^2-based structure functions and Fourier tails. The experiments report one-point W_1 averaged over space because it is computationally accessible and directly interpretable in terms of $k = 1$ correlation marginals. The mechanisms isolated below—coverage, fit, and discretization—are not specific to one particular metric; they explain why a learned transport that is accurate and easy to integrate can match the relevant output statistics with few function evaluations.

C   Exact conditional transport under the barycentric rectified velocity

C.1   Conditional couplings and rectified interpolation

Fix a condition c. Let

$$\pi_0^c, \nu^c \in \mathcal{P}(\mathcal{U})$$

be a source/reference conditional law and a target conditional law, and let

$$\gamma^c \in \mathcal{P}(\mathcal{U} \times \mathcal{U})$$

be any coupling of (π_0^c, ν^c). Write

$$(\Xi, Y) \sim \gamma^c,$$

where Ξ is the source sample and Y is the target sample.

For $\tau \in [0, 1]$, define the linear rectified interpolation

$$U_\tau := (1 - \tau)\Xi + \tau Y, \qquad \rho_\tau^c := \mathrm{Law}(U_\tau \mid C = c). \tag{58}$$

Thus ρ_τ^c is the conditional law of intermediate states obtained by moving linearly from the source sample Ξ to the target sample Y.

C.2   Conditional barycentric velocity

Definition C.1 (Conditional barycentric rectified velocity)**.** For each fixed condition c and each rectification time $\tau \in [0, 1]$, define

$$v^\star(u, \tau; c) := \mathbb{E}[Y - \Xi \mid U_\tau = u, \, C = c], \qquad \rho_\tau^c\text{-a.e. } u. \tag{59}$$

Interpretation. Along a single interpolation chord, the velocity is simply the constant vector $Y - \Xi$. At a population level, many such chords may pass through the same state u at the same rectification time τ. The field $v^{\star}(u, \tau; c)$ is the average of those compatible chord directions, conditioned both on the current state and on the input variable c.

Proposition C.2 (Exact conditional transport). *Assume we work on a finite-dimensional surrogate $\mathbb{R}^{d_N}$ of $\mathcal{U}$, and assume the continuity equation associated with $v^{\star}(\cdot, \tau; c)$ admits a unique classical flow map X_{τ}^{c} solving*

$$\frac{d}{d\tau} X_{\tau}^{c}(u) = v^{\star}(X_{\tau}^{c}(u), \tau; c), \qquad X_{0}^{c}(u) = u.$$

Then

$$(X_{\tau}^{c})_{\#} \pi_{0}^{c} = \rho_{\tau}^{c} \qquad \text{for all } \tau \in [0, 1],$$

and in particular

$$(X_{1}^{c})_{\#} \pi_{0}^{c} = \nu^{c}.$$

Proof. Let $(\Xi, Y) \sim \gamma^{c}$ and define $U_{\tau} = (1 - \tau)\Xi + \tau Y$, so that $\mathrm{Law}(U_{\tau} \mid C = c) = \rho_{\tau}^{c}$. Fix a smooth compactly supported test function φ on $\mathbb{R}^{d_N}$. Differentiating under the conditional expectation gives

$$\frac{d}{d\tau} \mathbb{E}[\varphi(U_{\tau}) \mid C = c] = \mathbb{E}\big[\nabla\varphi(U_{\tau}) \cdot (Y - \Xi) \mid C = c\big].$$

Condition further on U_{τ}:

$$\mathbb{E}\big[\nabla\varphi(U_{\tau}) \cdot (Y - \Xi) \mid C = c\big] = \mathbb{E}\big[\nabla\varphi(U_{\tau}) \cdot v^{\star}(U_{\tau}, \tau; c) \mid C = c\big].$$

Hence ρ_{τ}^{c} satisfies the weak continuity equation

$$\frac{d}{d\tau} \int \varphi(u) \, \rho_{\tau}^{c}(du) = \int \nabla\varphi(u) \cdot v^{\star}(u, \tau; c) \, \rho_{\tau}^{c}(du).$$

On the other hand, the pushforward curve $(X_{\tau}^{c})_{\#} \pi_{0}^{c}$ satisfies the same weak equation by the method of characteristics, with the same initial condition at $\tau = 0$. By uniqueness in the finite-dimensional setting, the two curves coincide, so $(X_{\tau}^{c})_{\#} \pi_{0}^{c} = \rho_{\tau}^{c}$ for all τ. At $\tau = 1$, this yields $(X_{1}^{c})_{\#} \pi_{0}^{c} = \nu^{c}$. $\qquad \square$

C.3 The training loss as an L^2 projection

The practical rectified-flow loss is the conditional regression objective

$$\mathcal{L}(v) = \mathbb{E}\Big[\|v(U_{\tau}, \tau; C) - (Y - \Xi)\|^2\Big], \tag{60}$$

where the expectation is taken over the joint sampling of C, $(\Xi, Y) \sim \gamma^{C}$, and $\tau \sim \mathrm{Unif}[0, 1]$.

Proposition C.3 (Population minimizer of the conditional rectified-flow loss). *For each fixed τ and condition c, the unique $L^2(\rho_{\tau}^{c})$ minimizer of*

$$v \longmapsto \mathbb{E}\Big[\|v(U_{\tau}, \tau; c) - (Y - \Xi)\|^2 \,\big|\, C = c\Big]$$

is the conditional barycentric field $v^{\star}(\cdot, \tau; c)$ from (59).

Proof. This is the standard characterization of conditional expectation as the orthogonal projection in L^2. For fixed c and τ, write $Z = Y - \Xi$ and $X = U_{\tau}$. Then

$$v^{\star}(X, \tau; c) = \mathbb{E}[Z \mid X, \ C = c].$$

For any square-integrable measurable $v(X, \tau; c)$,

$$\mathbb{E}\big[\|Z - v(X, \tau; c)\|^2 \mid C = c\big] = \mathbb{E}\big[\|Z - \mathbb{E}[Z \mid X, C = c]\|^2 \mid C = c\big] + \mathbb{E}\big[\|\mathbb{E}[Z \mid X, C = c] - v(X, \tau; c)\|^2 \mid C = c\big],$$

which proves minimality and uniqueness. $\qquad \square$

Proposition C.2 is the law-level correctness statement: if the learned velocity matches the ideal conditional barycentric field for the relevant target law, then exact integration transports the source law to that target law. Proposition C.3 explains why the training loss is the natural conditional regression objective.

D Continuous-time fit error for the learned conditional flow

For the rest of the appendix, fix a condition c and a target conditional law ν^c (in the finite-resolution application we will set $\nu^c = \bar{\mu}_1^c$). Let $v^\star(\cdot, \tau; c)$ be the corresponding conditional barycentric field.

Let U_τ solve the ideal conditional rectified ODE

$$\dot{U}_\tau = v^\star(U_\tau, \tau; c), \qquad U_0 \sim \pi_0^c. \tag{61}$$

By Proposition C.2,

$$\text{Law}(U_1 \mid C = c) = \nu^c.$$

Let $\widehat{U}_\tau$ solve the learned continuous-time conditional ODE

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c), \qquad \widehat{U}_0 = U_0. \tag{62}$$

Theorem D.1 (Continuous-time fit error). *Assume $v_\theta(\cdot, \tau; c)$ is L-Lipschitz in u, uniformly in $\tau \in [0, 1]$. Then*

$$\left(\mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \mid C = c\big] \right)^{1/2} \le e^L \int_0^1 \left(\mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \mid C = c\big] \right)^{1/2} d\tau. \tag{63}$$

In particular, if we define

$$\varepsilon_{\text{fit}}^2(c) := \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|^2 \mid C = c\big] \, d\tau, \tag{64}$$

then

$$\left(\mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \mid C = c\big] \right)^{1/2} \le e^L \, \varepsilon_{\text{fit}}(c). \tag{65}$$

Consequently,

$$W_2\big(\nu^c, \widehat{\mu}_1^{c,\text{cts}}\big) \le e^L \, \varepsilon_{\text{fit}}(c), \qquad \widehat{\mu}_1^{c,\text{cts}} := \text{Law}(\widehat{U}_1 \mid C = c). \tag{66}$$

Proof. Set $E_\tau := \widehat{U}_\tau - U_\tau$. Then

$$\dot{E}_\tau = v_\theta(\widehat{U}_\tau, \tau; c) - v^\star(U_\tau, \tau; c) = \big(v_\theta(\widehat{U}_\tau, \tau; c) - v_\theta(U_\tau, \tau; c)\big) + \big(v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\big).$$

Hence

$$\|\dot{E}_\tau\| \le L\|E_\tau\| + \|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\|.$$

Since $E_0 = 0$, Grönwall's inequality yields

$$\|E_1\| \le e^L \int_0^1 \|v_\theta(U_\tau, \tau; c) - v^\star(U_\tau, \tau; c)\| \, d\tau.$$

Take conditional L^2 norms, use Minkowski's integral inequality, and obtain (63). Equation (65) follows from Cauchy–Schwarz in τ. Finally, (66) follows because the coupling given by the common initial sample $U_0 = \widehat{U}_0$ implies

$$W_2^2(\nu^c, \widehat{\mu}_1^{c,\text{cts}}) \le \mathbb{E}\big[\|\widehat{U}_1 - U_1\|^2 \mid C = c\big].$$

$\square$

Sanity check. The continuous-time fit bound (65) vanishes when

$$v_\theta(\cdot, \tau; c) = v^\star(\cdot, \tau; c) \qquad \text{for a.e. } \tau,$$

which is the correct exactness property. This is precisely where the old fit+curvature theorem failed: a generic "straightness" term should *not* survive when the learned continuous-time field equals the ideal one.

E   Discretization: why straightness controls step count

We now fix the learned field $v_\theta(\cdot, \tau; c)$ and study only the numerical error incurred when integrating the learned ODE

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c).$$

E.1   Local truncation error and the total derivative along trajectories

Lemma E.1 (Local truncation error for explicit Euler). *Assume v_θ is C^1 in (u, τ) on the region traversed by the learned trajectory $\widehat{U}_\tau$, and define*

$$g(\tau) := v_\theta(\widehat{U}_\tau, \tau; c).$$

Then one explicit-Euler step of size $\Delta\tau$ from time τ satisfies

$$
\begin{aligned}
\mathrm{LTE}(\tau; \Delta\tau) &:= \left\| \widehat{U}_{\tau+\Delta\tau} - \left(\widehat{U}_\tau + \Delta\tau\, v_\theta(\widehat{U}_\tau, \tau; c) \right) \right\| \\
&= \frac{(\Delta\tau)^2}{2} \|\dot{g}(\tau)\| + \mathcal{O}((\Delta\tau)^3) \\
&= \frac{(\Delta\tau)^2}{2} \left\| \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c) \right\| + \mathcal{O}((\Delta\tau)^3).
\end{aligned}
\tag{67}
$$

If, in addition,

$$\|\partial_\tau v_\theta(u, \tau; c)\| \le M_\tau, \qquad \|J_u v_\theta(u, \tau; c)\| \le L, \qquad \|v_\theta(u, \tau; c)\| \le M$$

on the relevant region, then

$$\mathrm{LTE}(\tau; \Delta\tau) \le \frac{(\Delta\tau)^2}{2}(M_\tau + LM) + \mathcal{O}((\Delta\tau)^3).
\tag{68}$$

Proof. Differentiate the learned ODE along the trajectory:

$$\ddot{\widehat{U}}_\tau = \frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, \dot{\widehat{U}}_\tau.$$

Since $\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c)$, this becomes

$$\ddot{\widehat{U}}_\tau = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).$$

Now Taylor-expand $\widehat{U}_{\tau+\Delta\tau}$ around τ:

$$\widehat{U}_{\tau+\Delta\tau} = \widehat{U}_\tau + \Delta\tau\, v_\theta(\widehat{U}_\tau, \tau; c) + \frac{(\Delta\tau)^2}{2} \ddot{\widehat{U}}_\tau + \mathcal{O}((\Delta\tau)^3).$$

Subtract the Euler update and take norms to obtain (67). The bound (68) follows from the triangle inequality. $\square$

Interpretation.   Lemma E.1 identifies the relevant straightness quantity:

$$\frac{d}{d\tau} v_\theta(\widehat{U}_\tau, \tau; c) = \partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c).
\tag{69}$$

This is the quantity that governs numerical step-count requirements. It is *not* merely the partial derivative $\partial_\tau v_\theta$ at fixed state.

E.2 Global explicit-Euler error

Theorem E.2 (Global Euler discretization error)**.** *Assume the hypotheses of Lemma E.1, and assume moreover that $v_\theta(\cdot, \tau; c)$ is L-Lipschitz in u, uniformly in $\tau \in [0, 1]$. Let $\widehat{U}^{(N)}$ denote the explicit-Euler approximation of the learned flow with uniform step $\Delta\tau = 1/N$:*

$$\widehat{U}^{(N)}_{\tau_{n+1}} = \widehat{U}^{(N)}_{\tau_n} + \Delta\tau \, v_\theta(\widehat{U}^{(N)}_{\tau_n}, \tau_n; c), \qquad \tau_n = n/N.$$

Then there exists a constant $C(L) > 0$ such that

$$\sup_{0 \le n \le N} \left(\mathbb{E}\big[\|\widehat{U}^{(N)}_{\tau_n} - \widehat{U}_{\tau_n}\|^2 \mid C = c \big] \right)^{1/2} \le C(L)\,\Delta\tau \int_0^1 \left(\mathbb{E}\big[\|\dot{g}(\tau)\|^2 \mid C = c \big] \right)^{1/2} d\tau. \tag{70}$$

Equivalently, defining

$$\varepsilon_{\mathrm{disc}}(c; N) := \frac{1}{N} \int_0^1 \left(\mathbb{E}\big[\|\dot{g}(\tau)\|^2 \mid C = c \big] \right)^{1/2} d\tau, \tag{71}$$

we have

$$\sup_{0 \le n \le N} \left(\mathbb{E}\big[\|\widehat{U}^{(N)}_{\tau_n} - \widehat{U}_{\tau_n}\|^2 \mid C = c \big] \right)^{1/2} \le C(L)\, \varepsilon_{\mathrm{disc}}(c; N). \tag{72}$$

Proof. Let $e_n := \widehat{U}^{(N)}_{\tau_n} - \widehat{U}_{\tau_n}$. Standard one-step perturbation gives

$$\|e_{n+1}\| \le (1 + L\Delta\tau)\|e_n\| + \mathrm{LTE}(\tau_n; \Delta\tau).$$

Iterating this recursion and using $(1 + L\Delta\tau)^N \le e^L$ yields

$$\sup_{0 \le n \le N} \|e_n\| \le C(L) \sum_{n=0}^{N-1} \mathrm{LTE}(\tau_n; \Delta\tau).$$

Insert the local truncation estimate from Lemma E.1, ignore higher-order terms, and take conditional L^2 norms. The sum is a Riemann approximation of the integral in (70). $\qquad\square$

Sanity check. At fixed learned field, the discretization error (72) vanishes as $N \to \infty$. Thus, if the learned field is exact and we integrate it exactly, there is no residual discretization term. This is again where the old theory went wrong: straightness should influence *how many steps are needed*, not create an extra continuous-time approximation error.

F OOD stabilization by EMA blending

The EMA-based controller used in the sampler is not part of the generic correctness theorem. Its purpose is more specific: in the OOD macro–micro regime studied in the experiments, the learned velocity can become oscillatory along rectification time, which makes explicit integration brittle. The role of EMA/blending is to suppress this oscillatory component while preserving the slowly varying part of the ideal transport.

Idealized continuous-time surrogate. Fix a condition c and consider the ideal path U_τ from (61). Define along this path

$$g(\tau) := v^\star(U_\tau, \tau; c), \tag{73}$$

and the learned-field error

$$\varepsilon(\tau) := v_\theta(U_\tau, \tau; c) - g(\tau). \tag{74}$$

Thus

$$v_\theta(U_\tau, \tau; c) = g(\tau) + \varepsilon(\tau).$$

F.1 An abstract smoothing assumption

Let E_λ be a causal smoothing operator in rectification time, with bandwidth parameter $\lambda > 0$. We assume the following two properties along the ideal path:

1. **Contraction on the oscillatory error component.** There exists $\sigma(c, \lambda) \in [0, 1)$ such that

$$\|E_\lambda \varepsilon\|_{L^2_\tau L^2_\Omega(c)} \le \sigma(c, \lambda) \|\varepsilon\|_{L^2_\tau L^2_\Omega(c)}, \tag{75}$$

   where

$$\|f\|^2_{L^2_\tau L^2_\Omega(c)} := \int_0^1 \mathbb{E}\big[\|f(\tau)\|^2 \mid C = c\big] \, d\tau.$$

2. **Small bias on slowly varying signals.** There exists a universal constant $C_{\mathrm{ema}} > 0$ such that

$$\|E_\lambda g - g\|_{L^2_\tau L^2_\Omega(c)} \le C_{\mathrm{ema}} \, \lambda \, \|\dot{g}\|_{L^2_\tau L^2_\Omega(c)}. \tag{76}$$

Remark on exponential moving averages. For the continuous-time exponential smoother defined by

$$m'(\tau) = \frac{1}{\lambda}\big(f(\tau) - m(\tau)\big), \qquad m(0) = f(0),$$

the bias estimate (76) holds with $C_{\mathrm{ema}} = 1$. Indeed, the error $e = m - f$ satisfies

$$e'(\tau) + \frac{1}{\lambda} e(\tau) = -f'(\tau), \qquad e(0) = 0,$$

so

$$e(\tau) = -\int_0^\tau e^{-(\tau - s)/\lambda} f'(s) \, ds,$$

and Young's inequality yields

$$\|e\|_{L^2(0,1)} \le \lambda \|f'\|_{L^2(0,1)}.$$

A sufficient condition for (75) is that a nontrivial fraction of the error energy lies above the smoothing cutoff frequency; in the OOD regime this is precisely the structural behavior we empirically observe.

F.2 Idealized blended flow

For a fixed blend weight $\alpha \in [0, 1]$, define the *idealized blended field along the ideal path* by

$$\widetilde{v}_\alpha(U_\tau, \tau; c) := (1 - \alpha) \, v_\theta(U_\tau, \tau; c) + \alpha \, (E_\lambda[v_\theta(U., \cdot; c)])(\tau). \tag{77}$$

Assume $\widetilde{v}_\alpha(\cdot, \tau; c)$ extends to a state-space field that is uniformly L-Lipschitz in u. Let $\widetilde{U}_\tau$ solve

$$\dot{\widetilde{U}}_\tau = \widetilde{v}_\alpha(\widetilde{U}_\tau, \tau; c), \qquad \widetilde{U}_0 = U_0. \tag{78}$$

Define

$$\varepsilon_{\mathrm{approx}}(c) := \|\varepsilon\|_{L^2_\tau L^2_\Omega(c)}, \tag{79}$$

and

$$S_{*,\mathrm{tot}}(c) := \|\dot{g}\|_{L^2_\tau L^2_\Omega(c)}. \tag{80}$$

Theorem F.1 (EMA stabilization in the oscillatory OOD regime)**.** *Under the assumptions above,*

$$\Big(\mathbb{E}\big[\|\widetilde{U}_1 - U_1\|^2 \mid C = c\big]\Big)^{1/2} \le e^L\Big[\big(1 - \alpha(1 - \sigma(c, \lambda))\big) \varepsilon_{\mathrm{approx}}(c) + C_{\mathrm{ema}} \, \alpha \, \lambda \, S_{*,\mathrm{tot}}(c)\Big]. \tag{81}$$

The corresponding unsmoothed fit bound along the same ideal path is

$$e^L \, \varepsilon_{\mathrm{approx}}(c).$$

Consequently, EMA blending yields a strictly smaller upper bound whenever

$$(1 - \sigma(c, \lambda)) \, \varepsilon_{\mathrm{approx}}(c) > C_{\mathrm{ema}} \, \lambda \, S_{*,\mathrm{tot}}(c). \tag{82}$$

Proof. Apply the same Grönwall comparison used in Theorem D.1, but with $\widetilde{v}_\alpha$ in place of v_θ. Along the ideal path,

$$\widetilde{v}_\alpha(U_\tau, \tau; c) - g(\tau) = (1 - \alpha)\varepsilon(\tau) + \alpha E_\lambda \varepsilon(\tau) + \alpha(E_\lambda g(\tau) - g(\tau)).$$

Taking the $L_\tau^2 L_\Omega^2(c)$ norm and using Minkowski's inequality gives

$$\|\widetilde{v}_\alpha(U_\cdot, \cdot; c) - g\|_{L_\tau^2 L_\Omega^2(c)} \leq (1 - \alpha)\|\varepsilon\|_{L_\tau^2 L_\Omega^2(c)} + \alpha\|E_\lambda \varepsilon\|_{L_\tau^2 L_\Omega^2(c)} + \alpha\|E_\lambda g - g\|_{L_\tau^2 L_\Omega^2(c)}.$$

Now apply (75) and (76):

$$\|\widetilde{v}_\alpha(U_\cdot, \cdot; c) - g\|_{L_\tau^2 L_\Omega^2(c)} \leq \left(1 - \alpha + \alpha\sigma(c, \lambda)\right)\varepsilon_{\mathrm{approx}}(c) + C_{\mathrm{ema}}\,\alpha\,\lambda\,S_{*,\mathrm{tot}}(c).$$

Finally, use Theorem D.1 with $\widetilde{v}_\alpha$ in place of v_θ. $\qquad\square$

Interpretation. The factor

$$(1 - \sigma(c, \lambda))\,\varepsilon_{\mathrm{approx}}(c)$$

is the amount of oscillatory error removed by smoothing, while

$$\lambda\,S_{*,\mathrm{tot}}(c)$$

is the bias paid for smoothing the *ideal* transport itself. Theorem F.1 therefore captures exactly the intended OOD mechanism: EMA helps when the learned error is sufficiently oscillatory, while the ideal conditional rectified transport remains slowly varying in rectification time.

Relation to the practical sampler. The actual algorithm uses a discrete-time EMA and an adaptive blend weight α_t. The theorem above is a continuous-time fixed-α surrogate analysis of the same bias–variance tradeoff; it should be read as a structural explanation of the OOD sampler behavior rather than as an exact theorem for every implementation detail.

G   Coverage: structure functions control unresolved law tails

G.1   Coverage term

At fixed spatial resolution, every surrogate operates under an effective cutoff K_c. Therefore, even a perfect model cannot represent energy beyond that cutoff. The best it can do is match the projected law

$$(P_{\leq K_c})_\# \mu_1^c.$$

The discrepancy between the full conditional law and this projected conditional law is the *coverage term*.

G.2   Structure functions and tail control

For $u : \mathbb{T}^d \to \mathbb{R}^m$, define the second-order structure function

$$S_r^2(u) := \frac{1}{|B_r|} \int_{|h| \leq r} \|u(\cdot + h) - u(\cdot)\|_{L^2(\mathbb{T}^d)}^2 \, dh, \qquad B_r := \{h \in \mathbb{R}^d : |h| \leq r\}. \tag{83}$$

For a law μ on $L^2(\mathbb{T}^d)$, set

$$S_r^2(\mu) := \int S_r^2(u) \, d\mu(u).$$

Assume that the target conditional law μ_1^c satisfies the modulus condition

$$S_r^2(\mu_1^c) \leq \omega_c(r) \qquad \text{for all } r \in (0, 1], \tag{84}$$

where $\omega_c(r) \downarrow 0$ as $r \downarrow 0$.

Lemma G.1 (Structure function controls Fourier tail). *There exist constants $c_d, C_d > 0$ depending only on the dimension such that for every integer $K \geq 1$,*

$$\int \|P_{>K} u\|_{L^2}^2 \, d\mu_1^c(u) \leq C_d \, \omega_c(c_d/K). \tag{85}$$

Proof. For fixed u, expand

$$\|u(\cdot + h) - u(\cdot)\|_{L^2}^2 = \sum_{k \in \mathbb{Z}^d} |\hat{u}(k)|^2 \, |e^{ik \cdot h} - 1|^2.$$

Average over $|h| \leq r$ to obtain

$$S_r^2(u) = \sum_{k \in \mathbb{Z}^d} |\hat{u}(k)|^2 \Psi_r(k), \qquad \Psi_r(k) := \frac{1}{|B_r|} \int_{|h| \leq r} |e^{ik \cdot h} - 1|^2 \, dh.$$

A standard oscillation estimate gives

$$\Psi_r(k) \geq c \, \min\{(|k|r)^2, 1\}$$

for a dimensional constant $c > 0$. Hence $\Psi_r(k) \geq c_0$ for all $|k| \geq c'/r$, so

$$S_r^2(u) \geq c_0 \sum_{|k| \geq c'/r} |\hat{u}(k)|^2 = c_0 \|P_{>c'/r} u\|_{L^2}^2.$$

Integrate with respect to μ_1^c and choose $r = c_d/K$. $\qquad \square$

Lemma G.2 (Projection estimate in W_2). *For any law μ on $L^2(\mathbb{T}^d)$ and cutoff $K_c \geq 1$,*

$$W_2\big(\mu, (P_{\leq K_c})_\# \mu\big) \leq \left(\int \|P_{>K_c} u\|_{L^2}^2 \, d\mu(u) \right)^{1/2}. \tag{86}$$

Proof. Couple $u \sim \mu$ with $\tilde{u} = P_{\leq K_c} u$. Then $\tilde{u} \sim (P_{\leq K_c})_\# \mu$ and

$$W_2^2\big(\mu, (P_{\leq K_c})_\# \mu\big) \leq \mathbb{E}\|u - \tilde{u}\|_{L^2}^2 = \mathbb{E}\|P_{>K_c} u\|_{L^2}^2.$$

$\qquad \square$

Corollary G.3 (Coverage bound). *Under* (84),

$$W_2\big(\mu_1^c, \bar{\mu}_1^c\big) = W_2\big(\mu_1^c, (P_{\leq K_c})_\# \mu_1^c\big) \lesssim \omega_c(c_d/K_c)^{1/2}. \tag{87}$$

Interpretation. Corollary G.3 is the finite-resolution floor. Even a perfectly trained and exactly integrated surrogate cannot beat this term at cutoff K_c.

H   Master law-level bound: coverage + fit + discretization

We now combine the projected-target exact transport, the continuous-time fit error, and the discretization error.

Fix a condition c. Let

$$\bar{\mu}_1^c = (P_{\leq K_c})_\# \mu_1^c$$

be the projected target conditional law. Let $v_{K_c}^\star(\cdot, \tau; c)$ be the conditional barycentric field associated with a coupling between π_0^c and $\bar{\mu}_1^c$, and let $U_\tau^{K_c}$ solve

$$\dot{U}_\tau^{K_c} = v_{K_c}^\star(U_\tau^{K_c}, \tau; c), \qquad U_0^{K_c} \sim \pi_0^c.$$

By Proposition C.2,

$$\mathrm{Law}(U_1^{K_c} \mid C = c) = \bar{\mu}_1^c.$$

Let $\widehat{U}_\tau$ solve the learned continuous-time ODE

$$\dot{\widehat{U}}_\tau = v_\theta(\widehat{U}_\tau, \tau; c), \qquad \widehat{U}_0 = U_0^{K_c},$$

and let $\widehat{U}^{(N)}$ be the explicit-Euler approximation of the same learned ODE with N steps. Write

$$\widehat{\mu}_1^{c,\mathrm{cts}} := \mathrm{Law}(\widehat{U}_1 \mid C = c), \qquad \widehat{\mu}_1^{c,N} := \mathrm{Law}(\widehat{U}_1^{(N)} \mid C = c).$$

Define

$$\varepsilon_{\mathrm{fit},K_c}^2(c) := \int_0^1 \mathbb{E}\big[\|v_\theta(U_\tau^{K_c}, \tau; c) - v_{K_c}^\star(U_\tau^{K_c}, \tau; c)\|^2 \mid C = c\big]\, d\tau, \tag{88}$$

and

$$\varepsilon_{\mathrm{disc}}(c; N) := \frac{1}{N} \int_0^1 \Big(\mathbb{E}\big[\|\partial_\tau v_\theta(\widehat{U}_\tau, \tau; c) + J_u v_\theta(\widehat{U}_\tau, \tau; c)\, v_\theta(\widehat{U}_\tau, \tau; c)\|^2 \mid C = c\big]\Big)^{1/2} d\tau. \tag{89}$$

Theorem H.1 (Master conditional law-level bound)**.** *Assume the hypotheses of Theorem D.1, Theorem E.2, and Corollary G.3. Then*

$$W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) \lesssim \underbrace{\omega_c(c_d/K_c)^{1/2}}_{coverage} + \underbrace{e^L\, \varepsilon_{\mathrm{fit},K_c}(c)}_{fit} + \underbrace{C(L)\, \varepsilon_{\mathrm{disc}}(c; N)}_{discretization}. \tag{90}$$

More explicitly,

$$\begin{aligned}
W_2\big(\mu_1^c, \widehat{\mu}_1^{c,N}\big) &\leq W_2(\mu_1^c, \bar{\mu}_1^c) + W_2(\bar{\mu}_1^c, \widehat{\mu}_1^{c,\mathrm{cts}}) + W_2(\widehat{\mu}_1^{c,\mathrm{cts}}, \widehat{\mu}_1^{c,N}) \\
&\leq W_2(\mu_1^c, \bar{\mu}_1^c) + e^L\, \varepsilon_{\mathrm{fit},K_c}(c) + C(L)\, \varepsilon_{\mathrm{disc}}(c; N).
\end{aligned} \tag{91}$$

Proof. Insert the projected target law and the learned continuous-time law as intermediate terms:

$$W_2(\mu_1^c, \widehat{\mu}_1^{c,N}) \leq W_2(\mu_1^c, \bar{\mu}_1^c) + W_2(\bar{\mu}_1^c, \widehat{\mu}_1^{c,\mathrm{cts}}) + W_2(\widehat{\mu}_1^{c,\mathrm{cts}}, \widehat{\mu}_1^{c,N}).$$

The first term is the coverage term from Corollary G.3. The second term is the continuous-time fit term, bounded by Theorem D.1 applied to the ideal projected-target flow $U_\tau^{K_c}$. The third term is the discretization term from Theorem E.2. Combining the three bounds gives (90). □

Sanity checks. The bound (90) has the correct limiting behavior.

- If the learned field is exact on the projected target, i.e.

$$v_\theta = v_{K_c}^\star,$$

  then the fit term vanishes.

- If the learned ODE is integrated exactly, i.e. $N \to \infty$, then the discretization term vanishes.

- Therefore, at fixed cutoff K_c, a perfect model leaves only the unavoidable coverage floor.

- If, in addition, the cutoff tends to infinity and the structure-function tail vanishes accordingly, then the total error tends to zero.

These are the basic plausibility requirements any correct theory must satisfy.

What the master bound explains in the paper. Theorem H.1 gives the error taxonomy that the main text should emphasize everywhere:

- **Coverage** is a hard floor imposed by unresolved small scales.

- **Fit** measures how well the learned neural velocity approximates the ideal projected-target conditional transport field.

- **Discretization** measures how hard the learned transport is to integrate numerically; this is the term improved by straightness.

The EMA theorem from Section F is an additional OOD stabilization result, not a fourth term in the generic master decomposition.

I   From law-level bounds to the reported one-point metrics

One-point Wasserstein as a marginal metric. Let μ and $\widehat{\mu}$ be laws on fields $u : \mathcal{D} \to \mathbb{R}^m$. For each $x \in \mathcal{D}$, define the one-point marginals

$$\mu_x := (\mathrm{ev}_x)_{\#}\mu, \qquad \widehat{\mu}_x := (\mathrm{ev}_x)_{\#}\widehat{\mu}.$$

The reported metric in the main text is

$$W_1^{(1)}(\mu, \widehat{\mu}) := \int_{\mathcal{D}} W_1(\mu_x, \widehat{\mu}_x)\, dx.$$

By Kantorovich–Rubinstein duality, $W_1(\mu_x, \widehat{\mu}_x)$ controls the discrepancy of all pointwise 1-Lipschitz observables at the location x.

Relation to the law-level theory. The law-level bounds above are stated in W_2 on the full field space because this is the natural metric for coupling with L^2-based structure functions and Fourier tails. The one-point Wasserstein metric used in the experiments is weaker and more local, but it probes the same underlying conditional law. In particular:

- the *coverage* term controls whether unresolved high-frequency content can be represented at all;

- the *fit* term controls whether the learned continuous-time conditional flow reaches the correct projected target law;

- the *discretization* term controls whether a few ODE steps are sufficient to realize that law in practice.

These are exactly the mechanisms reflected empirically in the mean/spread/Wasserstein tables and in the spectral diagnostics.

Emphasis of spectra during sampling. The spectral evolution plots act as a scale-resolved diagnostic of the coverage and discretization story. They show how quickly the sampler reconstructs high-frequency energy up to the grid cutoff. This is why they are the right empirical counterpart of the theory above: they reveal both the finite-resolution ceiling and the fact that straighter rectified transports reach the attainable high-frequency regime with far fewer function evaluations than diffusion-based samplers.

J   Architecture of the ReFlow Model

J.1   Architectural Components

Motivation. Multi-scale PDE data contain wide-ranging spatial scales, so a *multi-resolution* encoder–decoder is natural. We incorporate time embeddings to condition each layer on the interpolation fraction τ.

Figure 5: **UNet Backbone Architecture Used in ReFlow.** This schematic illustrates the core UNet-based architecture used within the ReFlow framework, structured across three resolution levels. For clarity, the number of blocks per level is set to one in this illustration. In the actual GenCFD and ReFlow configurations, each block is repeated four times per level. The bottleneck shows an asymmetry between the encoder and decoder sides: the block on the encoder side includes a Convolution Block, Positional Embedding, and Attention Block, while the corresponding block on the decoder side omits the Positional Embedding. The time embedding $\Gamma(\tau)$ is computed *once per sample* from the scalar rectified-flow time τ via a sinusoidal encoding followed by a shared MLP. Each convolution block then applies its own learned affine projection of this global embedding to produce the per-block scale and shift parameters used in the FiLM modulation (see §J.1). The embedding is therefore *globally shared* across levels, while its effect on features is *block-specific*.

Architecture Layout. We employ a UNet-based architecture augmented with attentional layers, typically termed as **UViT** by [30]. In addition to the MLP-based time embedding $\Gamma(\tau)$, the input signal is lifted into a higher-dimensional embedding space and later projected back into physical space through convolutional layers. The data flows from high to low resolution across a down-sampling stack composed of convolution blocks into a bottleneck layer that encodes the fine-scale features of the inputs across its channel dimension and mixes them via a multi-head attention mechanism.

On the encoder side, exclusively at the bottleneck level, each attention block is preceded by a simple linear positional embedding. This positional encoding helps preserve spatial locality before global mixing through attention. The decoder side does not apply any positional embedding.

The UNet is conditioned at every level through normalized Feature-wise Linear Modulation (FiLM) techniques embedded within the convolution blocks. The conditioning signal modulates the normalization layers via learned scale and shift parameters. This conditioning mechanism is consistently applied across all encoder and decoder stages.

The output is symmetrically reconstructed via an up-sampling pipeline. Downsampling is performed using standard convolutional layers with stride, while upsampling can be implemented either via transposed convolutions or by applying a standard convolution followed by a non-learnable pixel shuffle operation, which rearranges elements of the tensor spatially according to a fixed upsampling factor.

Importantly, the architecture described here resembles the one presented in [25], ensuring consistency with prior state-of-the-art practices in high-fidelity generative modeling for scientific computing.

J.1.1 Convolution Block

Each UNet level employs dedicated convolution blocks that process features while enabling conditioning on the diffusion time τ. These blocks consist of two convolutional layers interleaved with group normalization and Swish activations. Between the convolutions, a normalized FiLM layer adaptively scales features using the conditioning embeddings. A residual connection combines the processed features with a projected skip connection, ensuring stable gradient flow. Crucially, these convolution blocks form the fundamental building units across all encoder and decoder stages, not just the bottleneck, with consistent application of temporal conditioning through the FiLM mechanism.

J.1.2 Normalized FiLM Layer

Each convolution block uses a normalized FiLM layer and applies a convolution layer interleaved with normalization and an activation, then adds a residual skip:

$$
\begin{aligned}
\mathbf{z} &= \mathrm{Conv}\big(\mathrm{Norm}(\mathbf{x})\big), \qquad \mathbf{z} = \sigma\big(\mathbf{z} + \alpha\,\gamma(\tau)\big), \\
\mathbf{x}_{\mathrm{out}} &= \mathbf{x} + \mathrm{Conv}\big(\mathbf{z}\big),
\end{aligned}
\tag{92}
$$

where Norm is often `RMSNorm`, GroupNorm or LayerNorm, σ is a nonlinearity (e.g. SiLU), and $\gamma(\tau)$ represents the time embedding (an MLP on Sinusoid(τ)) that modulates scale/shift. This temporal conditioning is crucial for guiding the generative process through rectified diffusion trajectories.

J.1.3 Attention Block

The architecture strategically employs multi-head attention exclusively at the bottleneck layer to balance global interaction modeling with computational efficiency. Each attention block processes normalized features through a spatial-channel reformatting, where features are reshaped by a flattening operation. This preserves the channel structure while collapsing the spatial grid into a single flattened dimension, allowing attention to operate across spatial locations. At certain scales, a multi-head attention (MHA) mechanism captures distant flow interactions. We define

$$
\mathbf{Q} = W_Q\,\mathbf{h}, \quad \mathbf{K} = W_K\,\mathbf{h}, \quad \mathbf{V} = W_V\,\mathbf{h}, \quad \mathcal{A}(\mathbf{h}) = \mathrm{softmax}\Big(\frac{\mathbf{Q}\mathbf{K}^\top}{\sqrt{d}}\Big)\mathbf{V},
\tag{93}
$$

where $\mathbf{h} \in \mathbb{R}^{(H \cdot W) \times d}$ denotes the flattened input sequence, with each of the $H \cdot W$ spatial positions represented as a d-dimensional feature vector. In practice, attention is split into multiple heads for better representational power, then recombined. This global mixing is key for PDE flows dominated by far-field couplings (e.g. vortex merging). The MHA operator is defined as

$$
\mathrm{MHA}(\mathbf{h}) = W^O\,\mathrm{Concat}(\mathcal{A}_1(\mathbf{h}), \dots, \mathcal{A}_n(\mathbf{h})),
\tag{94}
$$

where $n \in \mathbb{N}$ denotes the number of attention heads and $W^O \in \mathbb{R}^{C \times C}$ is a learned output projection matrix. The attention block applies MHA to a normalized input, then adds a residual connection to preserve the original signal and stabilize training:

$$
\begin{aligned}
\mathbf{z} &= \mathrm{MHA}\big(\mathrm{Norm}(\mathbf{x})\big), \\
\mathbf{x}_{\mathrm{out}} &= \mathbf{x} + \mathbf{z}.
\end{aligned}
\tag{95}
$$

J.2 Training Pipeline Details

Theory vs. Implementation: Two Forms of Interpolation. There are two related but distinct interpolation forms used in this work. *Theory* (Section 4.1 and Proposition 5.1) uses the *linear chord* interpolant

$$
\tilde{u}_\tau^{\mathrm{theory}} = \tau\,u_1 + (1 - \tau)\,u_0, \qquad \tau \in [0, 1],
$$

which interpolates directly between input u_0 and target u_1; the corresponding target velocity is $v^* = u_1 - u_0$. This form is used in the error decomposition and straightness analysis. *Implementation* (Algorithm 1 and all experiments) uses a *noise-conditioned* interpolant:

$$
\tilde{u}_\tau^{\mathrm{impl}} = \tau\,u_1 + \sigma(1 - \tau)\,\xi, \qquad \xi \sim \mathcal{N}(0, I),
$$

where $\sigma(\cdot)$ is a scalar noise-schedule function. The network is trained to predict $u_1 - \sigma(1-\tau)\,\xi$. At inference we start from pure noise ξ and integrate the learned ODE to $\tau = 1$. Both forms yield nearly-straight trajectories; the noise-conditioned form is standard in the rectified-flow / flow-matching literature and avoids evaluating the reference solver at training time.

Trainer Workflow. A high-level `Trainer` class manages:

1. Batching PDE pairs (u_0, u_1), normalized pixel-wise with statistics extracted over each entire dataset.

2. Sampling $\tau \in [0, 1]$ and random noise ξ according to a given noise scheduler $\sigma(\cdot)$.

3. Partial interpolation and noise addition: $\tilde{u}_\tau := \tau\,u_1 + \sigma(1 - \tau)\,\xi$ (noise-conditioned form; see paragraph above). We have experimented with non-linear interpolation methods, but have not noticed meaningful oscillations in performance.

4. Minimizing the squared deviation between model output and target displacement/noise, optionally with a consistency/EMA update.

5. Throughout training, we monitor validation performance on a separate holdout dataset across all main metrics. Different validation splits have been tested to ensure there is no data leakage that would bias performance metrics.

Table 5: Representative hyperparameters for 2D fluid-flow tasks. See main text for justification of these choices.

Parameter	Value (Optimal empirical performance)	Notes
Channels per level	(128, 256, 256)	Number of channels per level.
Downsample Ratios	(2, 2, 2)	Downsampling ratio per level.
Attention Heads	8	Each attention block.
Dropout Rate	0.1	In ConvBlock for generalization.
Noise Schedule	`uniform`, `log-uniform`, `cos-map`	Helps with multi-scale noise.
ODE Steps (Sampling)	4–8 (NFE)	Often $> 15\times$ fewer vs. diffusion.
Batch Size	16	Tied to GPU capacity.
EMA Decay	0.9999	Teacher model for consistency.
Learning Rate	3×10^{-4}	Cosine decay in code.

In practice we noticed that the most robust denoising schedule was the `uniform` one. For details on the `cos-map` schedule, we direct the reader to its description in [5].

J.3 Summary and Key Takeaways

The `RectifiedFlow` class, combined with a time-aware `UNet2D` architecture, builds a deterministic transport model well-suited to multi-scale PDE tasks. By interpolating between noise and data along nearly-straight paths, it reduces sampling overhead compared to conventional diffusion PDE solvers while retaining the flexibility to model complex turbulent phenomena. Further experimental and theoretical results appear in **SM** Section M. Instead of the multi-step *stochastic* integration in diffusion-based models, `RectifiedFlow` fits a *deterministic* ODE from noise to data. This leverages straighter trajectories in frequency space, enabling fewer network evaluations at inference time.

ODE Integration for Sampling. At inference:

$$\frac{d\tilde{u}_\tau}{d\tau} \;=\; v_\theta\big(\tilde{u}_\tau,\, u_0,\, \tau\big), \quad \tau \in [0,1], \quad \tilde{u}_{\tau=0} \;=\; \text{random noise.}$$

We solve this with `odeint`. As few as $8-10$ function evaluations (NFE) typically suffice, contrasting with the tens or hundreds of NFE required by full diffusion samplers. The corresponding wall-clock speedup depends on batch size and hardware and is reported separately in §M.6.

K Datasets

K.1 Multi-scale Flow Datasets

Following the dataset generation procedure of Herde et al. [14], the Richtmyer–Meshkov ensemble is created by imposing a randomized sinusoidal perturbation on a two-fluid interface and driving it with a planar shock via prescribed pressure jumps. For the CloudShock and ShearFlow benchmarks, we follow the GenCFD mesh-generation and solver setup of Molinaro et al. [25], initializing CloudShock with concentric density perturbations and ShearFlow with orthogonal shear jets on adaptive Cartesian grids, and employing the same high-order finite-volume scheme and dissipation settings to ensure consistent numerical fidelity across both datasets.

Overview. We experiment on three paired-field benchmarks (u_0, u_1):

- **Richtmyer–Meshkov (RM)**: 64 000 samples

- **Cloud-Shock (CS)**: 40 000 samples

- **Shear-Layer (SL)**: $79\,200$ samples

All datasets track the $u_0 \to S^t(u_0)|_{t=1}$ solution mapping from inputs to evolved outputs at $t = 1$. The first two datasets monitor the evolution of density (ρ), momentum components (m_x, m_y), and energy (E). The shear-flow dataset monitors the velocity components (u_x, u_y).

Train/Validation Split. For each dataset, we reserve 80% of the samples for training and 20% for validation.

Macro–Micro Ensemble Evaluation (CS & SL). To probe out-of-distribution generalization under small perturbations, we adopt a two-stage ensemble protocol:

1. *Macro-sampling:* select $M_{\text{macro}} = 10$ distinct base initial conditions.

2. *Micro-perturbation:* for each base, generate $M_{\text{micro}} = 1{,}000$ perturbed copies within a small radius.

3. *Metrics:* compute all performance measures (mean-field error e_μ, standard-deviation error e_σ, average W_1, spectral agreement) by first averaging over each micro-ensemble, then averaging across the M_{macro} cases.

In-Distribution Evaluation (RM). For the Richtmyer–Meshkov dataset, we additionally evaluate on a held-out test set drawn from the same distribution (no macro–micro perturbations). This allows us to study how deterministic and probabilistic models scale with training set size under standard, in-distribution conditions.

K.2 Preprocessing and Data Organization

Data Processing

Before training, we compute and store global, channel-wise statistics over the entire training dataset. Concretely, for each physical variable c we calculate

$$\mu_c = \frac{1}{N_{\text{train}} \, H \, W \, [D]} \sum_{i=1}^{N_{\text{train}}} \sum_{x,y,[z]} u_c^{(i)}\big(x, y, [z], t_0\big),$$

$$\sigma_c = \sqrt{\frac{1}{N_{\text{train}} \, H \, W \, [D]} \sum_{i=1}^{N_{\text{train}}} \sum_{x,y,[z]} \left(u_c^{(i)}\big(x, y, [z], t_0\big) - \mu_c \right)^2},$$

where N_{train} is the number of training samples, $H \times W \, [\times D]$ the spatial grid size, and $u_c(x, y, [z], t_0)$ the initial field for channel c. We average over all spatial locations to yield a single mean μ_c and standard deviation σ_c per channel. The same statistics are also computed over the final-time fields $u_c(t_f)$, producing μ_c' and σ_c' for the output channels.

During both training and evaluation, each input field u_c is standardized via

$$\tilde{u}_c = \frac{u_c - \mu_c}{\sigma_c + 10^{-16}}, \qquad \tilde{v}_c = \frac{v_c - \mu_c'}{\sigma_c' + 10^{-16}},$$

where u_c and v_c denote the initial and target fields, respectively. We then concatenate $\{\tilde{u}_c\}$ and $\{\tilde{v}_c\}$ along the channel axis before feeding them to the network. Because we always apply the same pre-computed statistics at test time, no information from the evaluation set ever influences these normalization parameters.

Test-time ensemble perturbation (evaluation only). We adopt the same testing setup proposed in *GenCFD* [25]. To evaluate how well our model captures the *distribution* of solutions $u(t)$ arising from a fixed, chaotic initial field $\bar{u}$, we generate a small perturbed ensemble around $\bar{u}$ and evolve each member with a high-fidelity PDE solver—*but only at evaluation time.* Specifically:

1. **Micro-ensemble generation.** Around the test initial condition $\bar{u}$, draw M_{micro} perturbed copies $\{\bar{u}_j\}_{j=1}^{M_{\mathrm{micro}}}$ by sampling uniformly in a ball of radius ε centered at $\bar{u}$.

2. **Reference propagation.** Integrate each perturbed field $\bar{u}_j$ forward to time t using the reference solver, producing end-states $\{u_j(t)\}$.

3. **Empirical conditional law.** Form the empirical measure

$$\hat{P}_t(\,\cdot\mid\bar{u})\ =\ \frac{1}{M_{\mathrm{micro}}}\sum_{j=1}^{M_{\mathrm{micro}}}\delta_{u_j(t)},$$

which approximates the true chaotic conditional law $P_t(\,\cdot\mid\bar{u})$.

When the input distribution itself is non-degenerate, one would first draw M_{macro} base fields from that distribution and then apply the micro-ensemble procedure to each. For our Dirac initial-condition tests we set $M_{\mathrm{macro}}=1$.

Training vs. evaluation. During training the model only ever sees independent pairs (u_0,u_1)—one target per input—and never observes any ensemble. The above ensemble perturbation is used *only* to construct a ground-truth distribution at test time.

L   Models and Baselines

We tested our method against four other baselines, of which two (GenCFD and its FNO-conditioned variant) are diffusion-based algorithms of the same kind. The other two rely on traditional operator learning, with the UViT baseline also serving as an ablation that quantifies the gain from adding diffusion.

Shared Backbone. All UNet-based models (ReFlow, GenCFD, GenCFD ∘ FNO, and UViT) use the *identical* UViT backbone specified in Table 5: channels $(128, 256, 256)$, 3 resolution levels, 4 blocks per level, 8 attention heads — approximately **5M trainable parameters** in every case. The architecture is illustrated schematically in Figure 5.

GenCFD

GenCFD [25] is an end-to-end conditional score-based diffusion model that directly learns the mapping from an input flow field u_0 to the target field u_1. It uses the same UViT backbone described in Table 5, with noise levels σ_τ corresponding to the standard deviation of the added Gaussian perturbation, in contrast to our ReFlow model which evolves over a rectified diffusion time $\tau\in[0,1]$. Common choices for noise schedulers include exponential and tangent formulations. In our case, we consistently adopted an exponential noise schedule, as it yielded the best results across all datasets and metrics reported. In all GenCFD models, we opted for a variance-exploding (VE) formulation throughout. During training we minimize the denoising score-matching loss over (u_0,u_1) pairs sampled uniformly in $\tau\in[0,1]$, using Adam with initial learning rate 3×10^{-4} (cosine decay), batch size 16, and EMA decay 0.9999. We applied denoiser preconditioning and used uniform weighting across noise levels. At inference we solve the corresponding SDE via an Euler–Maruyama scheme with 128 discretization steps, and incorporate reconstruction guidance to condition on u_0 so that we recover the conditional posterior measure $p(u_1|u_0)$.

GenCFD ∘ FNO

In this hybrid approach, a Fourier Neural Operator (FNO) [18] is first trained under an ℓ_2 loss to predict u_1 from u_0. Its output $\hat{u}_1^{\mathrm{FNO}}$ is concatenated channel-wise with u_0 and fed into the GenCFD score network

at both train and test time. All other architectural and optimization settings (backbone, scheduler, SDE sampler) remain identical to GenCFD, allowing the FNO to provide fast low-frequency priors while the diffusion stage refines fine-scale turbulent features.

Custom implementation. This schematic closely parallels the pipeline of [26], but with two key distinctions. First, we fully replace both the diffusion backbone and its denoising stages with GenCFD. Second, and most importantly, we condition not only on the FNO's coarse solution but also on the original high-resolution initial condition, ensuring that fine-scale structures are not lost.

FNO

Our FNO baseline follows Li *et al.* [18] and is implemented in PyTorch. Each spatial location of the input field u_0 is lifted from C_{in} to 256 channels via a two-layer MLP with a SiLU activation, then projected down to a 128-channel hidden representation. This is followed by four `FnoResBlock`s: in each block, the hidden features undergo a Conditional LayerNorm (time embedding size 128), SiLU, and two spectral convolutions (`SpectralConv`) with $num\_modes = (24, 24)$, combined through a learnable "soft-gate" residual skip. Finally, a two-layer projection MLP ($128 \rightarrow 256 \rightarrow C_{\text{out}}$, with SiLU in between) produces the output field $\hat{u}_1$. We train for 100k iterations minimizing $\|u_1 - \hat{u}_1\|_2^2$ with Adam (learning rate 10^{-3}, batch size 16), and perform inference in one forward pass.

UViT

Our UViT surrogate [30] uses the identical UNet2D backbone of Table 5, injecting time embeddings and employing 8-head multi-head attention at the bottleneck. It is trained deterministically with MSE loss on (u_0, u_1), using Adam at 3×10^{-4}, batch size 16, for 100k iterations (EMA 0.9999). For multi-step forecasting we roll out autoregressively. This ablates the diffusion component while matching all other design choices.

Baseline Model Summary

Table 6 summarizes key architectural settings for all models. These configurations were selected to reflect the strongest performance achievable within a shared training budget of up to 120,000 iterations, as used in the quantitative comparison reported in Table 1.

Padding and boundary conditions. Each dataset required padding choices tailored to its physical boundary conditions. SL and RM, which exhibit periodic boundaries, use circular padding in all convolutional layers. In contrast, CS features non-periodic boundaries and is trained with standard zero padding. These choices apply to all UNet-based architectures except ReFlow, which uniformly uses zero padding across all datasets.

Table 6: Summary of architectural depth and parameter count for each model. All UNet-based models share a consistent backbone design — channels $(128, 256, 256)$, 3 levels, 4 blocks/level, 8 attention heads — yielding ≈ 5M parameters each. The FNO baseline uses a structurally different architecture.

Model	# Levels	# Blocks	# Params	Noise Schedule	Diffusion Scheme
ReFlow	3	4	5M	uniform	rectified continuous time variable $\tau \in [0, 1]$
GenCFD	3	4	5M	exponential	variance-exploding
GenCFD ∘ FNO	3	4	5M	exponential	variance-exploding
UViT	3	4	5M	—	—
FNO	—	4	11M	—	—

M Results

M.1 Performance Metrics

To compare our generated ensembles against the reference Monte Carlo samples, we employ three complementary measures:

- **Mean-field error.** Let $\mu_{\text{ref}}(x)$ and $\mu_{\text{model}}(x)$ denote the pointwise spatial means of the reference and model ensembles, respectively. We measure their discrepancy by the L^2-norm

$$e_\mu = \big\| \mu_{\text{ref}} - \mu_{\text{model}} \big\|_2.$$

- **Standard-deviation error.** Similarly, let $\sigma_{\text{ref}}(x)$ and $\sigma_{\text{model}}(x)$ be the pointwise standard deviations:

$$e_\sigma = \big\| \sigma_{\text{ref}} - \sigma_{\text{model}} \big\|_2.$$

  Both metrics are reported after normalization by the L^2 norm of the ground truth.

- **Average 1-Wasserstein distance.** For a fixed initial condition u_0, let $\{u_{\text{ref}}^{(j)}(x)\}_{j=1}^N$ and $\{u_{\text{model}}^{(j)}(x)\}_{j=1}^N$ be the ensembles of final-time values. Since these fields are discretized on M spatial points $\{x_i\}_{i=1}^M$, we obtain two empirical 1D distributions at each x_i. Denoting their inverse CDFs by $F_{\text{ref}}^{-1}(\cdot\,; x_i)$ and $F_{\text{model}}^{-1}(\cdot\,; x_i)$, the pointwise Wasserstein-1 distance is

$$W_1\big(p_{\text{ref}}(\cdot \mid x_i),\, p_{\text{model}}(\cdot \mid x_i)\big) = \int_0^1 \big| F_{\text{ref}}^{-1}(q; x_i) - F_{\text{model}}^{-1}(q; x_i)\big|\, dq,$$

  and we report the spatial average $\overline{W}_1 = \frac{1}{M} \sum_{i=1}^M W_1\big(p_{\text{ref}}(\cdot \mid x_i),\, p_{\text{model}}(\cdot \mid x_i)\big)$.

Energy spectra. To assess how well different scales are captured, we compute the discrete energy spectrum of each velocity field. Given a sample $u(x)$ on a d-dimensional periodic grid with spacing Δ, let $\widehat{u}_k$ be its Fourier coefficient at integer wavevector $k \in \mathbb{Z}^d$. We bin modes by their ℓ_1 radius $|k|_1 = k_1 + \cdots + k_d$, defining

$$E_r = \frac{\Delta^d}{2} \sum_{\substack{k \in \mathbb{Z}^d \\ |k|_1 = r}} \big\|\widehat{u}_k\big\|^2, \quad r = 0, 1, 2, \dots$$

and compare the ensemble-average spectra of reference and model on log–log axes.

M.2 Metric Variability Across Sampling Seeds

To quantify sampling variance, we repeated each evaluation with five independent random-noise seeds. Table 7 reports mean $\pm$ std. The relative standard deviation is below 0.5% for all e_μ and e_σ entries, and below 0.1% for all $\overline{W}_1$ entries, confirming that the results in Table 1 are highly stable with respect to stochastic sampling.

M.3 Noise Schedule Sensitivity

We evaluated nine inference-time noise schedules — `uniform`, `log-uniform`, `cos-map`, `exponential`, `tangent`, `quadratic`, `sqrt`, `sigmoid`, and `linear-beta` — on both ShearLayer2D and CloudShock2D. The results are shown in Table 8.

The learned rectified velocity field produces trajectories sufficiently straight that the choice of inference-time schedule has no measurable effect on sample quality. This invariance is a direct consequence of the straightening bias: once the velocity field is nearly straight, the time-discretization grid is irrelevant for integration accuracy. This contrasts with score-based diffusion, where schedule choice critically affects performance because the learned score is highly curved near $\tau = 0$.

Table 7: ReFlow metric variability across 5 independent sampling seeds (mean $\pm$ std).

Dataset	Variable	e_μ	e_σ	$\overline{W}_1$
ShearLayer2D	u_x	0.0340 ± 0.0001	0.0716 ± 0.0002	$(1.76 \pm 0.003) \times 10^{-3}$
	u_y	0.1893 ± 0.0010	0.0776 ± 0.0003	$(1.41 \pm 0.001) \times 10^{-3}$
CloudShock2D	ρ	0.0468 ± 0.0001	0.0999 ± 0.0002	$(1.14 \pm 0.001) \times 10^{-3}$
	m_x	0.0317 ± 0.0001	0.0717 ± 0.0002	$(1.23 \pm 0.001) \times 10^{-3}$
	m_y	0.0392 ± 0.0001	0.0812 ± 0.0002	$(1.39 \pm 0.001) \times 10^{-3}$
	E	0.0138 ± 0.00002	0.0576 ± 0.0001	$(1.50 \pm 0.001) \times 10^{-3}$

Table 8: ReFlow performance across 9 inference-time noise schedules. All 9 schedules produce identical metrics; values shown are the common result.

Dataset	Variable	e_μ	e_σ	$\overline{W}_1$
ShearLayer2D	u_x	0.1153	0.3674	0.0022
	u_y	0.2346	0.3820	0.0021
CloudShock2D	ρ	0.1525	0.2320	0.0011
	m_x	0.1083	0.2034	0.0012
	m_y	0.1039	0.2077	0.0015
	E	0.0452	0.1852	0.0015

M.4 ODE Integrator Comparison

Tables 9 and 10 compare fixed-step Euler, second- and fourth-order Runge–Kutta (RK2, RK4), and the adaptive curvature-aware sampler on ShearLayer2D and CloudShock2D respectively. Times are measured on a single NVIDIA Quadro RTX 6000.

Why higher-order integrators do not outperform Euler. We are not integrating an exact physical ODE with a known vector field; we are integrating a *learned* generative ODE whose velocity field v_θ carries finite approximation error. A higher-order solver more faithfully follows local imperfections of the learned field, which can move samples farther from the data manifold. By contrast, the first-order Euler method has a mild regularizing effect that tends to keep trajectories in high-density regions. The practical gain therefore comes not from solver order but from the *adaptive curvature-aware sampler*, which selectively refines steps where the learned velocity curves — achieving the lowest absolute error at the fewest NFE.

Table 9: ODE integrator comparison on **ShearLayer2D** (OOD). Error = mean relative L^2 over u_x, u_y; Cost$\times$Err = NFE $\times$ Error.

Method	Steps	NFE	Error $\pm$ Std	Cost$\times$Err	Time (ms)
Euler	8	8	0.2359 ± 0.053	1.89	161
Euler	16	16	0.2475 ± 0.055	3.96	355
Euler	32	32	0.2541 ± 0.056	8.13	745
RK2	8	16	0.2603 ± 0.057	4.16	355
RK4	8	32	0.2621 ± 0.058	8.39	745
RK4	32	128	0.2616 ± 0.058	33.49	3083
Adaptive-EMA	10	10	0.2090 ± 0.041	2.09	448
Adaptive-EMA	13	13	**0.1762**	**2.29**	524

Across both datasets, RK4 at 32 NFE is strictly worse than Euler at 32 NFE. The adaptive sampler achieves the lowest absolute error at 10–13 NFE, well below the budget of any fixed-step baseline. This is because error

Table 10: ODE integrator comparison on **CloudShock2D** (OOD). Same metrics as Table 9.

Method	Steps	NFE	Error $\pm$ Std	Cost$\times$Err	Time (ms)
Euler	8	8	0.2211 ± 0.021	1.77	150
Euler	16	16	0.2261 ± 0.021	3.62	330
Euler	32	32	0.2289 ± 0.021	7.32	694
RK2	8	16	0.2319 ± 0.021	3.71	331
RK4	8	32	0.2323 ± 0.021	7.43	693
RK4	32	128	0.2322 ± 0.021	29.72	2873
Adaptive-EMA	11	11	0.2259 ± 0.017	2.48	440
Adaptive-EMA	13	13	$\mathbf{0.2121 \pm 0.016}$	**2.76**	486

saturates quickly with NFE once the velocity field is sufficiently straight; additional steps in high-straightness regions yield no further benefit.

M.5   Relation to ODE-Based Diffusion Samplers

A natural question is whether ReFlow's efficiency can be matched simply by applying a probability-flow ODE (PF-ODE) sampler — such as DPM-Solver or the Heun-based solver of Karras et al. — to the existing GenCFD score model. We address this directly.

PF-ODE methods accelerate sampling of a *fixed* learned score model; they do not change the learned dynamics. Our method trains a *different* conditional transport field v_θ, whose objective promotes straighter trajectories in rectified time, yielding a smoother, less stiff field that can be integrated accurately in very few steps. The efficiency gain comes from *learning a straighter field*, not from choosing an ODE solver.

To verify this, we re-evaluated GenCFD using the PF-ODE with a second-order Heun solver at $4, 8, 16, 32, 64$, and 128 NFE. On ShearLayer2D at 128 NFE, PF-ODE was worse than the standard SDE sampler on both e_μ and e_σ, confirming that the stiffness of the score field — not the choice of solver — is the bottleneck for GenCFD. The rectified-flow velocity field learned by ReFlow is intrinsically less stiff, which is why it integrates accurately in 8–10 steps regardless of solver choice.

M.6   Training Efficiency Observations

To assess training efficiency, we compare ReFlow with GenCFD using a matched parameter count ($\approx$5M) and three-level UViT architecture. Both models were trained for up to 160,000 iterations with a batch size of 16.

Figure 6 summarizes performance over the training trajectory. At approximately 100,000 steps, ReFlow consistently outperforms GenCFD across all key metrics: e_μ, e_σ, and $\overline{W}_1$ for both u_x and u_y. The y-axis uses a logarithmic scale to emphasize differences in error magnitude.

To further probe the long-term capabilities of GenCFD, we extended its training to 600,000 iterations. Table 11 summarizes the earliest step at which GenCFD overtakes ReFlow's performance at 150,000 steps. While GenCFD catches up in several cases, it never surpasses ReFlow on $\overline{W}_1$ for u_y within the training horizon considered.

Table 11: Number of training iterations at which GenCFD surpasses ReFlow's performance at 150,000 iterations. "—" indicates GenCFD never surpasses ReFlow within the training horizon.

Metric	GenCFD Iteration	GenCFD Value	ReFlow @ 150k
u_x Mean Error (e_μ)	280,000	3.33×10^{-2}	3.45×10^{-2}
u_y Mean Error (e_μ)	400,000	1.70×10^{-1}	1.88×10^{-1}
u_x Std Error (e_σ)	400,000	6.48×10^{-2}	7.24×10^{-2}
u_y Std Error (e_σ)	340,000	7.91×10^{-2}	7.97×10^{-2}
u_x Wasserstein-1 (W_1)	200,000	3.89×10^{-2}	3.95×10^{-2}
u_y Wasserstein-1 (W_1)	—	—	4.11×10^{-2}

Figure 6: **Training efficiency comparison.** Performance of ReFlow and GenCFD on the Macro-Micro SL ensemble dataset at multiple training checkpoints. Metrics: relative L^2 error of the mean (e_μ) and standard deviation (e_σ), and the average 1-point Wasserstein-1 distance ($\overline{W}_1$), for both velocity components (u_x, u_y). The y-axis is logarithmic; the x-axis (training iteration) is linear.

M.7 Experimental Advantages of Straightness

This subsection presents empirical evidence that the rectified trajectories generated by ReFlow enable faster convergence and higher-fidelity reconstructions compared to GenCFD.

Evaluation settings. We use the CloudShock dataset throughout; the same results hold across datasets. For each initial condition, both ReFlow and GenCFD are allotted $T = 10$ diffusion steps over normalized diffusion time $\tau \in [0, 1]$. We record outputs at five evenly spaced timesteps $\tau \in \{0.0, 0.25, 0.50, 0.75, 1.0\}$ and analyze: trajectory inpainting of the density field ρ; latent-space trajectory visualization via PCA; per-sample average MSE evolution; and evolution of the energy spectrum. All other components (backbone, noise schedule, batch size) are held equal.

Trajectory Inpainting

We compare ReFlow and GenCFD reconstructions of the density field ρ over five normalized diffusion timesteps $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. ReFlow inpaints fine-scale features in far fewer steps, while GenCFD remains overly diffusive. The leftmost panel corresponds to the initial condition u_0 upon which both models are conditioned; the following panels show the evolution of the model output as diffusion time progresses.

Figure 7: Density trajectories for Sample 1: ReFlow (top) vs. GenCFD (bottom). ReFlow recovers sharp shock fronts by diffusion time $\tau = 1.0$.

Figure 8: Density trajectories for Sample 2.

Figure 9: Density trajectories for Sample 3.

Latent-Space Trajectory Visualization via PCA

To quantify how directly each model moves through the data manifold, we flatten the $(H \times W \times C)$ field at each timestep into a single feature vector, stack all ReFlow and GenCFD vectors, fit a 3-component PCA, and project each timestep into PC1/PC2/PC3. A straighter path indicates fewer diffusive detours. Because the ReFlow trajectory is much shorter in the projected space, it may visually appear as a tight cluster near the endpoint; this compactness is itself evidence of rectification — the model reaches its target in very few, nearly-collinear steps.

(a) Sample 1   (b) Sample 2   (c) Sample 3

(d) Sample 4   (e) Sample 5   (f) Sample 6

Figure 10: **3D PCA latent-space trajectories (Samples 1–6).** Flattened snapshots at each of T timesteps projected into the top three PCA components. ReFlow (blue) consistently traces a straighter path than GenCFD (red). Circles mark $\tau = 0$, squares mark $\tau = 1$; intermediate timesteps are annotated.

To further illustrate generative dynamics, we visualize single-sample generation trajectories from both models in a 2D PCA space for the RM dataset (Figure 11). For each physical channel (ρ, m_x, m_y, p), we apply PCA to the full set of ground truth snapshots to define a common projection basis, then overlay the generative trajectory of a single sample. Kernel density estimates (KDEs) show the empirical data distribution in the same projected space. ReFlow (top) traces a straighter, more compact path over 10 rectified steps; GenCFD (bottom) uses 128 stochastic steps and produces a more diffuse, nonlinear trajectory.

Figure 11: **2D PCA latent-space trajectories.** Flattened velocity snapshots from the RM dataset projected into a 2D PCA space, computed independently per channel (ρ, m_x, m_y, p). KDE overlays show the distribution of target fields. ReFlow (top, 10 steps) evolves along straighter, more structured trajectories than GenCFD (bottom, 128 steps).

Per-Sample Average Error Evolution

We compute the mean-squared error at each timestep τ and average across all C channels:

$$\overline{\mathrm{MSE}}(\tau) = \frac{1}{C} \sum_{c=1}^{C} \mathrm{MSE}_c(\tau).$$

Figure 12 shows, for Samples 1–6, the log-scaled average MSE (left half of each subfigure) and the normalized error $\overline{\mathrm{MSE}}(\tau)/\overline{\mathrm{MSE}}(0)$ (right half). ReFlow (blue) consistently reduces error faster and to a lower residual than GenCFD (red).

(a) Sample 1

(b) Sample 2

(c) Sample 3

(d) Sample 4

(e) Sample 5

(f) Sample 6

Figure 12: **Per-sample average MSE evolution.** Left half: $\log_{10} \overline{\mathrm{MSE}}(\tau)$; right half: $\overline{\mathrm{MSE}}(\tau)/\overline{\mathrm{MSE}}(0)$. ReFlow (blue) rapidly drives error down and maintains it orders of magnitude below GenCFD (red) across all samples.

Evolution of the Energy Spectrum

We examine the 2D radial power spectrum of the energy field E at five normalized diffusion times $\tau \in \{0.00, 0.25, 0.50, 0.75, 1.00\}$. Each figure shows log–log power vs. wavenumber for ReFlow (blue), GenCFD (red), and the ground-truth target (black dashed), with inset log-MSE error annotations. The leftmost panel corresponds to the spectrum of the initial condition u_0; subsequent panels track spectral evolution as τ progresses.

Figure 13: Energy spectrum evolution for Sample 1. ReFlow (blue) outperforms GenCFD (red) in capturing high-wavenumber energy.

Figure 14: Energy spectrum evolution for Sample 2. ReFlow remains closer to the ground truth (dashed) than GenCFD throughout.

Figure 15: Energy spectrum evolution for Sample 3. Inset log-MSE annotations quantify ReFlow's advantage at each τ.

Figure 16: Energy spectrum evolution for Sample 4. ReFlow's spectrum approaches the target as $\tau \to 1.0$.

Figure 17: Energy spectrum evolution for Sample 5. ReFlow's superior high-k fidelity is evident throughout.

Figure 18: Energy spectrum evolution for Sample 6. ReFlow better captures the ground-truth spectrum's slope across all timesteps.

N Computational Considerations

All ReFlow models for 2D fluid-flow tasks use the network configuration in Table 5 and have approximately 5M trainable parameters with identical layer-wise dimensions. We ran each training job for 100,000 iterations on a single NVIDIA Quadro RTX 6000 (Driver 570.124.06, CUDA 12.8) in persistence mode. Resource utilization averaged over the full 100 h training window is reported in Table 12.

Table 12: Aggregate hardware utilization across all training runs.

Metric	Range	Typical
GPU power draw (W)	200–260	230
GPU utilization (%)	30–80	55
GPU memory allocated (GB)	12–17	15
GPU temperature (°C)	40–60	50
Process GPU memory usage (%)	60–80	70
Process GPU memory access time (%)	10–50	30
Process CPU threads in use	7	7
System CPU utilization (per core, %)	60–100	80
Process memory in use (GB)	up to 50	25
Disk I/O read (MB total)	up to 1.2×10^6	5×10^5
Disk utilization (%)	70–75	72
Network traffic (bytes total)	$\approx 3 \times 10^{13}$	3×10^{13}

Since all datasets are paired with models of identical size and the hardware envelope is effectively the same across runs, any observed performance differences are attributable to the sampling strategy (noise schedule, ODE steps) rather than to model-size or hardware variations. (Network traffic is due to Wandb logging.)

We explored architectures ranging from approximately 5M to 10M trainable parameters; across this range we observed no significant differences in final predictive performance or convergence behavior. All other hyperparameters were held fixed across comparisons, ensuring that differences in accuracy and runtime reflect only the conditioning and sampling strategies under study.

O Code and Data Availability

Prior to acceptance, we will make available all three datasets, the complete data-processing scripts, and a fully functional training and evaluation pipeline for ReFlow, including a model checkpoint that can be loaded and tested directly. A more comprehensive, user-friendly code release will follow shortly thereafter.

P Additional Visualizations

Test-time ensemble perturbation (evaluation only). Following the protocol of *GenCFD* [25], we construct small micro-ensembles around each test initial condition $\bar{u}$ by sampling M_{micro} perturbed fields uniformly in an ε-ball centered at $\bar{u}$. Each perturbed member is advanced to evaluation time t with a high-fidelity PDE solver to produce a reference ensemble $\{u_{\mathrm{ref}}^{(j)}(t)\}_{j=1}^{M_{\mathrm{micro}}}$. Our model generates a corresponding ensemble $\{u_{\mathrm{model}}^{(j)}(t)\}_{j=1}^{M_{\mathrm{micro}}}$ from the same perturbed inputs, but without ever observing ensembles during training. We compare these via e_μ, e_σ, and $\overline{W}_1$ (see §M).

Out-of-distribution testing (cloud-shock and shear-flow). Because the micro-perturbations render each initial field slightly OOD, this evaluation probes generalization under small chaotic perturbations. Our ReFlow ensemble closely tracks the reference uncertainty and multiscale statistics, whereas deterministic baselines collapse to a single trajectory and fail to capture the conditional variability.

In-distribution scaling (Richtmyer–Meshkov). For the RM dataset, we additionally study the effect of training set size on a held-out test set from the same distribution. Even deterministic approaches improve with more data, but still underperform on the micro-ensemble test, requiring significantly larger training sets to match ReFlow's accuracy and exhibiting poor calibration under small perturbations.

In this appendix we provide comprehensive qualitative comparisons between all baselines (GenCFD variants, UViT, FNO) and ReFlow across three 2D fluid-flow benchmarks. For each task we show:

- **Mean fields.** Ensemble averages reveal how deterministic models (UViT/FNO) diffuse fine-scale features versus preserving sharp interfaces (ReFlow, GenCFD variants).

- **Uncertainty maps.** Per-pixel standard deviations illustrate whether uncertainty localizes in physically meaningful regions (shocks, shear interfaces) or remains overly diffuse.

- **Random samples.** Representative samples from ReFlow alongside the deterministic FNO and the hybrid GenCFD ∘ FNO, highlighting ReFlow's ability to produce realistic, high-resolution flow fields that preserve physical coherence across scales.

- **Spectral and pointwise comparisons.** (Fig. 22: RM global $E(k)$, local spectra, and pointwise density histograms; Fig. 25: SL global u_x spectra and pointwise u_x distributions; Fig. 29: CS global m_y spectra and pointwise energy distributions.) Combined Fourier-space and histogram panels quantify multiscale fidelity and calibration.

Together, these visualizations underscore ReFlow's ability to maintain sharper physical structures, produce better-calibrated uncertainties, and faithfully reproduce multiscale spectral statistics.

Figure 21: **Richtmyer–Meshkov Individual Sample Comparison**: A representative random test sample from the Richtmyer–Meshkov dataset, visualized across all four physical channels (ρ, m_x, m_y, p). All models produce physically plausible results, with only little variation in fidelity to fine-scale structures. ReFlow offers the closest visual match to the ground truth, preserving coherent details and sharp interfaces. Notably, the GenCFD ∘ FNO hybrid enhances spectral richness by reconstructing high-frequency features based on a low-frequency FNO prior, illustrating its capacity to recover sharper modes even when starting from a coarse prediction.

(a) UVit global $E(k)$.

(b) RF global $E(k)$.

(c) UVit local at $(120, 44)$.

(d) RF local at $(120, 44)$.

(e) UVit ρ at $(60, 12)$, $W_1 = 0.0278$.

(f) RF ρ at $(60, 12)$, $W_1 = 0.0005$.

Figure 22: Richtmyer–Meshkov: spectral and pointwise distribution comparisons between UVit and Rectified Flow.

(a) **mean-field** μ (b) **standard-deviation** σ

Figure 23: **Shear-Layer Mean and Standard Deviation Comparison**: Visualization of mean-field (μ) and standard-deviation (σ) predictions for the Shear-Layer dataset across both velocity components (u_x, u_y). For each model, the left half shows the predicted mean fields and the right half shows per-pixel standard deviations. The top row contains the reference ground truth. Despite the reduced channel complexity of this

(a) FNO $E_{u_x}(r)$.

(b) RF $E_{u_x}(r)$.

(c) FNO u_x at $(36, 8)$.

(d) RF u_x at $(36, 8)$.

Figure 25: Shear-layer: global u_x spectra and pointwise u_x distributions.

Figure 28: **Cloud–Shock Individual Sample Comparison**: A representative random test sample from the Cloud–Shock dataset, displayed across all physical channels. While all models produce plausible results, ReFlow and the hybrid GenCFD ∘ FNO most closely align with the ground truth, particularly in preserving fine-scale detail. The spectral reconstruction effect of the hybrid model is especially evident, recovering high-frequency structures from the coarse FNO prediction and enhancing the overall visual fidelity.

(a) UVit m_y spectrum.

(b) RF m_y spectrum.

(c) UVit E at $(68, 28)$.

(d) RF E at $(68, 28)$.

Figure 29: Cloud-shock: spectral and pointwise energy comparisons.