Faster Reinforcement Learning with Value Target Lower Bounding

Abstract

We show that an arbitrary lower bound of the maximum achievable value can be used to improve the Bellman value target during value learning. In the tabular case, value learning using the lower bounded Bellman operator converges to the same optimal value as using the original Bellman operator, at a potentially faster speed. In practice, discounted episodic return in episodic tasks and n-step bootstrapped return in continuing tasks can serve as lower bounds to improve the value target. We experiment on Atari games, FetchEnv tasks and a challenging physically simulated car push and reach task. We see large gains in sample efficiency as well as converged performance over common baselines such as TD3, SAC and Hindsight Experience Replay (HER) in most tasks, and observe a reliable and competitive performance against the stronger n-step methods such as td-lambda, Retrace and optimality tightening. Prior works have already successfully applied a special case of lower bounding (using episodic return), but are limited to a small number of episodic tasks. To the best of our knowledge, we are the first to propose the general method of value target lower bounding (with possibly bootstrapped return), to demonstrate its optimality in theory, and effectiveness in a wide range of tasks over many strong baselines.

1 Introduction

The value function is a key concept in dynamic programming approaches to Reinforcement Learning (RL) (Bellman, 1957). It estimates the sum of all future rewards (usually time-discounted) of a given state. In temporal difference (TD) learning, the value function is adjusted toward its Bellman target which adds the reward of the current step with the (discounted) value of the next state (Sutton & Barto, 2018). This forms the basis of many state of the art RL algorithms such as DQN (Mnih et al., 2013), DDPG (Lillicrap et al., 2016), TD3 (Fujimoto et al., 2018), and SAC (Haarnoja et al., 2018).

The value of the next state is typically estimated using a "bootstrapped value" based on the value function itself, which is being actively learned during training. The bootstrapped values can be random and far from the optimal value, especially at the initial stage of training, or with sparse reward tasks where rewards can only be achieved through a long sequence of actions. Consequently, the Bellman value targets as well as the learned values are usually far away from the optimal value (the value of the optimal policy).

Naturally, this leads to the following idea: If we can make the value target closer to the optimal value, we may speedup TD learning. For example, we know that the optimal value is just the expected discounted return of the optimal policy, which always upper bounds the expected return of any policy. For episodic RL tasks, we could use the observed discounted return up to episode end from the training trajectories to lower bound the value target. This makes the new value target closer to the optimal value, when the empirical return is higher than the Bellman target.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Algorithm 1 Value iteration with value target lower bounding

Input: Finite MDP $p(s', r|s, a)$, convergence threshold θ, a lower bound $f(s)$ of the maximum achievable value $\bar{G}(s)$
Output: State value $v(s)$
$v(s) \leftarrow 0$
repeat
    $\Delta \leftarrow 0$
    $v_p(s) \leftarrow v(s)$
    for each state s **do**
        $\hat{v}(s) \leftarrow \max_a \sum_{s',r} p(s', r|s, a)[r + \gamma v_p(s')]$
        $\hat{v}_f(s) \leftarrow \max(f(s), \hat{v}(s))$
        $v(s) \leftarrow \hat{v}_f(s)$
        $\Delta \leftarrow \max(\Delta, |v(s) - v_p(s)|)$
    end for
until $\Delta < \theta$

The case for continuing or non-episodic tasks is less clear though. When a continuing task can return negative rewards, any safe lower bound of the optimal value can be too low to be useful. One could take the risk and use n-step bootstrapped return as a lower bound, which is unsafe because bootstrapped return can overestimate and be greater than the optimal value. Can we still use them as lower bounds to improve TD value targets?

2 Theoretical Results for the Tabular Case

Our results show that for the tabular case, arbitrary functions below a certain bootstrap bound can be used to lower bound the value target to still converge to the same optimal value.

2.1 Background

In finite MDPs with a limited number of states and actions, a table can keep track of the value of each state. Using dynamic programming algorithms such as value iteration, values are guaranteed to converge to the optimum through Bellman updates (Chapter 4.4 (Sutton & Barto, 2018)).

The core of the value iteration algorithm (Algorithm 1) is the Bellman update of the value function, $\mathcal{B}(v)$, where $v(s')$ is the bootstrapped value:

$$\mathcal{B}(v)(s) \coloneqq \max_a \sum_{s',r} p(s', r|s, a)[r + \gamma v(s')] \tag{1}$$

It is well known that the Bellman operator, $\mathcal{B}$, is a contraction mapping over value functions (Denardo, 1967). That is, for any two value functions v_1 and v_2, $||\mathcal{B}(v_1) - \mathcal{B}(v_2)||_\infty \leq \gamma ||v_1 - v_2||_\infty$ for the discount factor $\gamma \in [0, 1)$ and $||x||_\infty \coloneqq \max_i |x_i|$ (the L_∞ norm). This guarantees that any value function under the algorithm converges to the optimal value $\mathcal{B}^\infty(v) = v^*$.[1]

2.2 Convergence of value target lower bounding

Definition 2.1. The expected n-step bootstrapped return for a given policy π and value function $v(s)$ is defined as the expected bootstrapped return of taking n steps according to policy π:

$$G_n^\pi(s_0) \coloneqq \mathbb{E}^\pi\{r_1 + ... + \gamma^{n-1} r_n + \gamma^n v(s_n)\} \tag{2}$$

Here, the step rewards r_i and the resulting n-th step state s_n are random variables, with the expectation $\mathbb{E}^\pi$ taken over all possible n-step trajectories under the policy π and the given MDP.

---
[1]For the gist of the proof, see for example page 8 of `https://people.eecs.berkeley.edu/~pabbeel/cs287-fa09/lecture-notes/lecture5-2pp.pdf`

Definition 2.2. Given the current learned value function $v(s)$, policy class Π, the *maximum achievable value* of a state s is defined as:

$$\bar{G}(s) := \max_{\pi \in \Pi, n \in [1, +\infty)} G_n^\pi(s) \tag{3}$$

This is a more relaxed definition of maximum because for each state s, a different policy $\pi(s)$ and a different number of steps $n(s)$ can be used to achieve the maximum $\bar{G}(s)$. And the theorem below says any function not exceeding the maximum achievable value can be used to lower bound the value target, and still achieve the optimal value in convergence.

Theorem 2.3. *Under the same assumptions for Bellman value contraction, for any function f that lower bounds the maximum achievable value, i.e. $\forall s, f(s) \leq \bar{G}(s)$, if we define the lower bounded Bellman operator as $\mathcal{B}_f(v) := \max(\mathcal{B}(v), f)$, then $\mathcal{B}_f^\infty(v) = \mathcal{B}^\infty(v)$.*

Note, the value $v(s)$ and the bootstrapped value can be inaccurate, and even above the optimal value. As a consequence, when n is finite, the maximum achievable value $\bar{G}(s)$ (and f) can be above the maximum expected return (i.e. the optimal value). On the other hand, when n is sufficiently large, the effect of the bootstrap value $v(s_n)$ diminishes (see Equation 2), and the maximum achievable value becomes the maximum expected return (i.e. the optimal value). Therefore, $\forall s, \bar{G}(s)$ is no smaller than the optimal value $\mathcal{B}^\infty(v)(s)$. As a special case of the theorem, as long as f is below the optimal value, value target lower bounding converges correctly:

Corollary 2.4. *If function f lower bounds the optimal value, i.e. $\forall s, f(s) \leq \mathcal{B}^\infty(v)(s)$, then $\mathcal{B}_f^\infty(v) = \mathcal{B}^\infty(v)$.*

A few things to note about the proof of Theorem 2.3 (included in Appendix 1.1).

First, this only proves convergence, not contraction under the original $||v_1 - v_2||_\infty$ metric. In the case of the Bellman operator, contraction shows that $\forall v_1, v_2$ value functions, $||\mathcal{B}(v_1) - \mathcal{B}(v_2)||_\infty \leq \gamma ||v_1 - v_2||_\infty$. Here, for value target lower bounding, what's proved is convergence to v^* at a rate of γ, not contraction. There can be counter examples where the distance between v_1 and v_2 under one application of $\mathcal{B}_f$ can increase in the original L_∞ metric space, even though v_1 and v_2 are both getting closer to v^* at a rate of γ. One difficulty caused by convergence instead of contraction is that the stopping criterion in Algorithm 1 ($\Delta < \theta$) no longer works, due to the inaccessible v^* during learning. In practice, this may not be a serious concern, as people often train algorithms for a fixed number of iterations or time steps.

Second, based on the proof, the new algorithm is at least as fast as the original. When the lower bound actually improves the value target, i.e. $f(s) > \mathcal{B}(v_1)(s)$, there is a chance for the convergence to be faster. Convergence is strictly faster when the lower bound f has an impact on the L_∞ distance between the current value and the optimal value, i.e. it increases the value target for the states where the differences between the current value and the optimal value are the largest.

Third, the lower bound function doesn't have to be static during training. As long as there is a single f during each training update, convergence is preserved.

The following sections detail how to compute lower bounds of the maximum achievable value (Section 3), how to integrate the lower bounds into state of the art RL algorithms (Section 4), and provide an illustration of how this method may benefit value learning in practice (Section 4.3).

3 Example Lower Bound Functions

We show a few cases where lower bound functions can be readily obtained from the training experience. Future work may investigate alternatives.

3.1 Episodic tasks

In episodic tasks, discounted return is accumulated up to the last step of an episode. In this case, we can wait until an episode ends, and compute future discounted returns of all time steps up to the end of the episode. This episodic return is a lower bound of the optimal value when the environment is

deterministic, because the reward sequence can be repeated using the same sequence of actions[2]. To make training efficient, we can compute and store such discounted returns into the replay buffer for each time step, and simply read them out during training, which adds very little computation to the baseline one-step TD computation.

$$f(s_0) = \sum_{i=0,..,\infty} \gamma^i r(s_i, a_i) \tag{4}$$

We call this variant "lb-DR", short for lower bounding with discounted return.

3.1.1 Episodic with hindsight relabeled goals

In goal conditioned tasks, one helpful technique is hindsight goal relabeling (Andrychowicz et al., 2017). It takes a future state that is d time steps away from the current state as the hindsight / relabeled goal for the current state. When the goal is reached, a reward of 0 is given, otherwise a -1 reward is given for each time step.

In this case, we know it took d steps to reach the hindsight goal, so the discounted future return is:

$$\begin{aligned} f(s_0) &= \sum_{i=0,..,d-1} -1\gamma^i \\ &= -1(1-\gamma^d)/(1-\gamma) \end{aligned} \tag{5}$$

This calculation can be done on the fly as hindsight relabeling happens, requiring no extra space and very little computation.

We call this variant "lb-GD", short for lower bounding with goal distance based return.

Additionally, we can also apply lb-DR and lb-GD together, with discounted episodic return (lb-DR) on the original experience and goal distance based return (lb-GD) on the hindsight experience, giving the "lb-DR+GD" variant, which was used in Fujita et al. (2020).

3.2 In general (including non-episodic tasks)

If the task is continuing, without an episode end[3], discounted return needs to be accumulated all the way to infinity. When rewards are always non-negative, one can still use the accumulated discounted reward of the future n-steps to lower bound the value. But accumulated n-step discounted reward is no longer a lower bound when rewards can be negative, in which case, the more general lower bounding with bootstrapped value can be used: given a trajectory of training experience $\tau :=< s_0, ..., s_n >$:

$$G_n(\tau) := r_1 + \gamma r_2 + ... + \gamma^{n-1} r_n + \gamma^n v(s_n) \tag{6}$$

Assuming the rewards and the state s_n can be repeated with the same action sequence, $G_n(\tau)$ lower bounds the maximum achievable value $\bar{G}(s_0)$ (Equation 3).

Two variations are possible: Given a trajectory of length n,

1. compute $v(s_i)$ for all $i \in [1, n]$ and take the maximum of all $G_i(\tau)$ to obtain a tighter lower bound. We call this variant "lb-b-$n$step":

$$f(s_0) = \max_{i \in [1,n]} G_i(\tau) \tag{7}$$

2. only evaluate v on the last (nth) step and use the nth-step bootstrapped return as the lower bound, which involves less compute but results in a looser bound. (When n is large enough, this becomes the lb-DR variant.) We call this variant "lb-b-$n$step-only".

$$f(s_0) = G_n(\tau) \tag{8}$$

---

[2]Note that the behavior policy can be stochastic, as long as the policy class contains the optimal policy, value learning will converge to the optimal.

[3]Chapter 3.3 of Sutton & Barto (2018) has more details on episodic vs continuing tasks.

4 Integration into RL algorithms

4.1 Background

The value target lower bounds can be readily plugged into RL algorithms that regresses value to a target, e.g. DQN, DDPG or SAC.

In these algorithms, the action value $q(s, a)$ is learned through a squared loss with the target value y. In one step TD return, for a batch $\mathbf{B}$ of experience $\{s, a \to r, s'\}$, the loss is:

$$\mathcal{L}_q := \sum_{(s,a,r,s')\in\mathbf{B}} |q(s,a) - y|^2 \tag{9}$$

In one step TD return, y is the one step TD return $\hat{q}(s, a, r, s')$:

$$\hat{q}(s, a, r, s') := r(s, a) + \gamma q'(s', \mu'(s')) \tag{10}$$

Here, q' and μ' are the bootstrap value and policy functions, typically following the value and policy functions in a delayed schedule during training. (They are also called "target value" and "target policy", and are very different from the "value target" y in this paper.)

4.2 Value target lower bounding

With lower bounding, we replace the value target y with the lower bounded target:

$$y \leftarrow \max(f, \hat{q}(s, a, r, s')) = \max(f, r + \gamma q'(s', \mu'(s'))) \tag{11}$$

This is the same as was done by Fujita et al. (2020) (confirmed via personal communication), but is subtly and importantly different from lower bounding the q value directly (Oh et al., 2018; Tang, 2020): $q(s,a) \leftarrow \max(f, q(s,a))$, which stays overestimated if $q(s,a)$ initially overestimates.

To the best of our knowledge, this way of value target lower bounding with bootstrapped values is novel.

4.3 An Illustrative Example

Figure 1 includes a fairly general example showing how value target lower bounding would improve value learning. Suppose we enhance an off policy algorithm such as DDPG with value target lower bounding (lb-DR), when there is no training experience hitting the target state, no meaningful training happens for the baseline or lb-DR. However, when there is one trajectory hitting the target state, all states along the trajectory will soon be propagated with meaningful return, and nearby states will also enjoy faster learning. As the state space becomes larger and the time horizon longer, a successful trajectory will speed up learning quite a bit.

5 Experiments

The goal is to demonstrate the sample efficiency of lower bounding the value target over baseline such as DDPG, TD3, SAC and HER. Because the lower bounded value target can now look potentially many steps into the future, we suspect it to be best suited for long horizon, sparse reward tasks. Hence, we choose to experiment on a sampled subset of Atari games, the goal conditioned FetchEnv tasks and the harder goal conditioned Pioneer Push and Reach tasks. See details of the experiment setup in Appendix 1.2.

5.1 Baselines

Baselines include DDPG (Lillicrap et al., 2016), TD3 (Fujimoto et al., 2018), SAC (Haarnoja et al., 2018) and HER (Andrychowicz et al., 2017; Plappert et al., 2018). Implementations are based on open sourced repositories, and baseline performance is verified against published results under similar

| Baseline: 0 | Baseline: 1 | Baseline: 2 | (a) Baseline: 3 |
| Lowerbound 0 | Lowerbound 1 | Lowerbound 2 | Lowerbound 3 |

Figure 1: Illustration of value target lower bounding speeding up value learning as training progresses from stages 0 to 3. The task is to navigate in the state space from start state S to end state T, with sparse reward 1 at T and 0 elsewhere. The curve from S to T denotes a training experience that reaches the target. The shaded areas denote roughly states whose value has been significantly improved during training up to that stage.

settings. The Appendix 1.6 and 1.5 include results on more baselines such as DDQN (van Hasselt et al., 2015), td-labmda (Sutton & Barto, 2018) and Retrace (Munos et al., 2016).

5.2 Hyperparameters

Value target lower bounding does not introduce any additional hyperparameter. The only hyperparameters come from the baselines. These hyperparameters follow published work as much as possible. When tuning baseline hyperparameters, we searched for the best performance in total episode reward on one set of random seeds, then the optimal hyperparameters are fixed and evaluated on a separate set of random seeds never seen during development. Value target lower bounding simply used the the parameter values optimal for the baselines. Details are in Appendix 1.3.

5.3 Results

We report results on both episodic and continuing/non-episodic tasks. We report evaluation performance averaged across several runs of the algorithms (five for the less stable Atari games and three for the others). Each run uses a random seed never seen during development.

5.3.1 Lower bounding with episodic return

5.3.1.1 lb-DR (episodic return) vs baseline SAC/DDPG

Figure 2 in Appendix 1.4.1 compares lower bounding with discounted return (lb-DR) against SAC or DDPG baseline on 17 sampled Atari games and the episodic FetchEnv tasks.

For 16 out of the 17 Atari games, lower bounding with episodic discounted return (lb-DR) performs at least as well as the baseline, often much better. On more than half of the Atari games and on the Fetch PickAndPlace task, there are large gains in both sample efficiency and final performance. On FetchPush and a few of the Atari games (Alien, Bank Heist and Fishing Derby), there is about 70% sample efficiency gain with similar converged performance. Among all the 20 tasks, only 1 task (Atari Breakout) shows lb-DR underperforming the baseline.

The lb-DR method is mostly effective, but is it really due to improvements to the value targets? Figure 3 (Appendix 1.4.1.1) looks at the fraction of training experience where lower bounded value target is actually higher than the baseline Bellman value target over the course of training. For the episodic FetchEnv tasks, as training progresses, a meaningful fraction of experience start to benefit from better value targets, and the agent's performance in terms of average return starts to improve over the baseline. For most tasks and Atari games, improved value target does coincide with significant performance gains, the only exceptions being Breakout and FetchSlide, where value improvement does not lead to a clear win.

5.3.1.2   lb-GD (goal distance return) and lb-DR+GD vs HER

Figure 5 (Appendix 1.4.2) compares lower bounding with goal distance return (lb-GD) and lower bounding with both goal distance and discounted return combined (lb-DR+GD) against the much stronger HER baseline, on the goal conditioned episodic FetchEnv and Pioneer tasks.

On the easier FetchEnv tasks, lower bounding is similar as HER, but on the more challenging Pioneer Push and Reach tasks, lower bounding is able to achieve over 70% more sample efficiency. It seems the harder the task, the wider the margin of gain.

We also looked at the fraction of experience where the lower bounding goal return is higher than the Bellman target (see Figure 6 in Appendix 1.4.1.1). It quickly grows to 1-8% and then slowly drops, matching the region where the new method outperforms the baselines in average return.

5.3.2   Lower bounding with Bootstrapping

5.3.2.1   lb-b-$n$step (bootstrapping all n steps) vs baselines

Figure 7 (Appendix 1.4.3) shows performance of lb-b-$n$step methods on a subset of the Atari games (episodic) and the original (non-episodic) FetchEnv tasks. Besides SAC/DDPG, baselines also include n-step methods such as td-lambda, Retrace (Munos et al., 2016) and optimality tightening (He et al., 2017). lb-b-$n$step methods are at least as good as the best baseline method, and clearly outperforms the baselines in two of the six tasks.

Figure 8 (Appendix 1.4.3.1) has more details on the fractions of experience improved by the lower bounds. In general, there is still some correlation between value target improvement and agent performance. With bootstrapping, the fractions of experience with value being improved are between 40-70%, higher than those of lb-DR in Figure 3.

The following two sections include ablations which show the lower bounding methods to be robust to variations in the hyperparameters.

5.3.2.2   lb-b-$n$step with different n (number of steps)

Figure 9 (Appendix 1.4.4) shows the effect of how the number of steps n in n-step bootstrapped return impacts lower bounding performance. The lb-b-$n$step method is not very sensitive to the value n, typically, the higher the value n the better the performance, while n-step methods like td-lambda or Retrace would degrade a lot as n increases above 3 or 4. We also observe lower value overestimation as n increases (Figure 13 Appendix 1.4.3.1).

5.3.2.3   lb-b-$n$step vs lb-b-$n$step-only (only n-th step)

Figure 10 (Appendix 1.4.4) shows the effect of taking a maximum of all 2- to n-step bootstrapped returns versus only using the n-step bootstrapped return. It seems using the maximum bootstrapped return of all 2- to n-steps, hence a tighter lower bound, works better than only using the n-step return.

5.3.2.4   lb-b-$n$step (bootstrap) or lb-DR (episodic return)

In continuing tasks (with negative rewards), we have to use the bootstrapped lb-b-$n$step method. But for episodic tasks, should we use bootstrapped return or episodic return as value target lower bound? In theory, lb-b-$n$step-only becomes lb-DR when n is large enough. In practice, in terms of effectiveness, we can compare lb-b-$n$step with lb-DR on the Atari games (Appendix 1.4 Figure 7 and 2 respectively). lb-b-$n$step is better than lb-DR on Atari Breakout. On Seaquest, the two are similar. On the other two games: Frostbite and Q*bert, episodic return is better. It seems lb-DR is better on tasks where rewards are more sparse and longer term planning is needed. In terms of efficiency, as n becomes larger, the memory and compute efficient lb-DR method will become more attractive. Overall, both methods show a clear advantage over the baselines.

6   Related Work

Prior works (Fujita et al., 2020; Hoppe & Toussaint, 2020; He et al., 2017; Oh et al., 2018; Tang, 2020) employed several different ways of computing future returns and using that as a lower bound

to improve value learning. It is quite easy to introduce biases and inefficiencies into the process and end up with a suboptimal or inefficient algorithm. Our work is the first to propose the general form of value target lower bounding (possibly with bootstrapping), to show its convergence to the optimal value in the tabular case, and to demonstrate its effectiveness in illustrative examples and extensive experiments on a wide range of tasks.

Fujita et al. (2020)'s method is similar to a special case (the lb-DR+GD variant) of the general method. They used it as a part of a large system and showed that it improved sample efficiency for a robotic grasping task. Hoppe & Toussaint (2020) also bounded the value target. But instead of using empirical return, they used a simplified MDP with a subset of actions. Although without theoretical proof and only experimented on a limited set of robotic manipulation tasks, both works show that value target lower bounding increased sample efficiency. This work, in addition to the theory and the more general method, shows that lower bounding improves both sample efficiency and converged performance in a wide range of tasks.

He et al. (2017) used empirical return with bootstrap to improve value learning. They formulated value learning as a constrained optimization problem with the empirical bootstrapped value being the lower (and upper) constraints of the value function. In their experiments, the Lagrangian multiplier was fixed, which would likely lead to suboptimal solutions. Our lb-b-$n$step method also uses bootstrapped value. But we lower bound the value target directly, which is simpler, more efficient, and likely more optimal. Our work points out that for episodic tasks, even more efficient and effective methods like lb-DR exist. Appendix 1.5 offers more discussion and results related to this.

Our work is subtly but importantly different from the prior works on lower bound Q learning or Self Imitation Learning (SIL) (Oh et al., 2018; Tang, 2020). SIL uses empirical return R to lower bound the value function itself (instead of the *value target*). This is achieved by adding an off policy value loss during on-policy (AC or PPO) training ($L_{value}^{sil} = \frac{1}{2}|v(s) - \max(v(s), R)|^2$). When the value function overestimates, the SIL value loss becomes zero, and keeps overestimating. Mixing the SIL loss with the loss from the baseline algorithms probably helped to correct the overestimation, but no theoretical guarantee was given. In evaluation, SIL was often compared to on-policy Actor Critic or PPO baselines, so it was not clear how much of the gain was due to lower bounding and how much due to off-policy value learning. In this work, we bound the Bellman value target (Equation 11), so overestimates are automatically corrected via Bellman updates, and convergence is guaranteed in the tabular case. We also use off-policy algorithms as baselines for a cleaner comparison.

N-step return methods such as td-lambda (Sutton & Barto, 2018) and Retrace (Munos et al., 2016) also look a few steps ahead, but to obtain more accurate value of the behavior policy. Traditionally, this requires careful off-policy correction, and the value can still be far from the optimal value due to the often suboptimal behavior. This work shows that value target lower bounding efficiently and effectively looks ahead much further without the need for off-policy correction, due to aiming at the optimal value. Appendix 1.5 has more detailed observations and discussions.

Planning methods can look into the future to achieve higher value targets and better control. Examples include Monte Carlo Tree Search (MCTS) (Schrittwieser et al., 2019; Ye et al., 2021) and Model Predictive Control (MPC) or receding horizon planning with raw actions (Chua et al., 2018; Hafner et al., 2019; Zhang et al., 2022), options (Silver & Ciosek, 2012), or subgoals (Nasiriany et al., 2019; Nair & Finn, 2020; Chane-Sane et al., 2021). Planning methods use either a dynamics model together with the learned value or just the learned value (in the case of goal conditioned tasks) (Nasiriany et al., 2019) to improve policy or value estimates. Planning typically happens during roll out (Nasiriany et al., 2019), but can also be used to improve the value target, as in Reanalyze of MuZero (Schrittwieser et al., 2019; Ye et al., 2021). During value improvement, if planning takes the maximum over a set of possible future values (e.g. from different trajectories as in the case of MPC), and if this set includes the one step Bellman value target, then the planner is essentially using alternative trajectories and their values to lower bound the Bellman value target. In this sense, the theory developed here can potentially justify and improve Reanalyze. In general, planning is orthogonal to value target lower bounding, and typically requires additional components and a lot more compute than the basic TD learning does. Therefore, we leave it to future work to explore the synergy between the two.

Interestingly, it is common practice to lower and upper bound the returns to the possible region, e.g. Andrychowicz et al. (2017) bounds value between $[-\frac{1}{1-\gamma}, 0]$. Similar to lower bounding with episodic return (Section 3.1), such strict bounds of the actual value can be thought of as admissible

heuristics (bounds) used during search of the optimal solution (Russell & Norvig, 2020). What's new in this work is that lower bounding with bootstrapped values (which can overestimate the value) still converges to the optimal value.

Kumar et al. (2020) (DisCor) also recognized that bootstrapped value targets can be inaccurate. This bias impacts learning adversely under function approximation. DisCor uses distribution correction to sample experience with accurate bootstrap targets more frequently, while value target lower bounding aims to directly reduce the bias.

While in theory using empirical return to lower bound the value target is only correct for deterministic environments, in practice, it seems as long as the environment is not heavily impacted by random fluctuations, they still perform well. In fact, with function approximation, the agents cannot distinguish between two slightly different states, making the problem partially observable (Sutton & Barto, 2018) and appear slightly random. Prior methods such as SIL (Oh et al., 2018), Optimality Tightening (He et al., 2017) and MuZero (Schrittwieser et al., 2019) also require the environment to be deterministic. Despite this limitation, the lower bounding methods and the prior methods still outperform baselines, often by large margins.

7 Conclusions

We propose a general form of lower bounding the value target using possibly bootstrapped return. In theory, value target lower bounding converges to the same optimal solution as the original Bellman operator. In practice, several ways of finding value lower bounds are examined.

For episodic tasks, discounted episodic return is an efficient and effective method involving very little extra computation. Precomputing the episodic return and storing it into the replay buffer allows efficient lower bound computation. It achieves much higher sample efficiency and converged performance than one-step baselines such as SAC, DDPG or TD3 in most tasks, and is competitive among n-step baselines. Simple goal distance based return uses even less compute and achieves large gains in certain long horizon tasks over Hindsight relabeling (HER).

For non-episodic tasks or in general, lower bounding with n-step bootstrapped return outperforms one-step baselines and is a strong competitor to the n-step methods such as (truncated) td-lambda and Retrace.

7.1 Future Work

There are probably better ways of finding value lower bounds that improve training even more. One direction may be to use planning (e.g. Monte Carlo Tree Search, the Cross Entropy Method or using subgoals) to achieve tighter lower bounds given a model of the task.

Estimating value lower bound for stochastic tasks may be possible, e.g. by learning a reward function and a dynamics model and using imagined rollouts to obtain bootstrapped returns without overestimation.

Other ways of bounding the value target, e.g. upper bounding (He et al., 2017), may be worth investigating as well, e.g. to reduce overestimation in regions of poor reward.

References

Andrychowicz, M., Crow, D., Ray, A., Schneider, J., Fong, R., Welinder, P., McGrew, B., Tobin, J., Abbeel, P., and Zaremba, W. Hindsight experience replay. In Guyon, I., von Luxburg, U., Bengio, S., Wallach, H. M., Fergus, R., Vishwanathan, S. V. N., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pp. 5048–5058, 2017. URL https://proceedings.neurips.cc/paper/2017/hash/453fadbd8a1a3af50a9df4df899537b5-Abstract.html.

Bellman, R. *Dynamic Programming*. Princeton Univ. Press, Princeton, NJ, USA, 1957. ISBN 0-691-07951-X.

Chane-Sane, E., Schmid, C., and Laptev, I. Goal-conditioned reinforcement learning with imagined subgoals. In Meila, M. and Zhang, T. (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 1430–1440. PMLR, 18–24 Jul 2021. URL `https://proceedings.mlr.press/v139/chane-sane21a.html`.

Chua, K., Calandra, R., McAllister, R., and Levine, S. Deep reinforcement learning in a handful of trials using probabilistic dynamics models. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, NIPS'18, pp. 4759–4770, Red Hook, NY, USA, 2018. Curran Associates Inc.

Denardo, E. V. Contraction mappings in the theory underlying dynamic programming. *SIAM Review*, 9(2):165–177, 1967. ISSN 00361445. URL `http://www.jstor.org/stable/2027440`.

Fujimoto, S., van Hoof, H., and Meger, D. Addressing function approximation error in actor-critic methods. *CoRR*, 2018. URL `http://arxiv.org/abs/1802.09477`.

Fujita, Y., Uenishi, K., Ummadisingu, A., Nagarajan, P., Masuda, S., and Castro, M. Distributed reinforcement learning of targeted grasping with active vision for mobile manipulators. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 9712–9719, Oct 2020.

Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In Dy, J. and Krause, A. (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 1861–1870. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/haarnoja18b.html`.

Hafner, D., Lillicrap, T., Fischer, I., Villegas, R., Ha, D., Lee, H., and Davidson, J. Learning latent dynamics for planning from pixels. In Chaudhuri, K. and Salakhutdinov, R. (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2555–2565. PMLR, 09–15 Jun 2019. URL `https://proceedings.mlr.press/v97/hafner19a.html`.

He, F. S., Liu, Y., Schwing, A. G., and Peng, J. Learning to play in a day: Faster deep reinforcement learning by optimality tightening. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL `https://openreview.net/forum?id=rJ8Je4clg`.

Hoppe, S. and Toussaint, M. Qgraph-bounded q-learning: Stabilizing model-free off-policy deep reinforcement learning. *CoRR*, abs/2007.07582, 2020. URL `https://arxiv.org/abs/2007.07582`.

Kumar, A., Gupta, A., and Levine, S. Discor: Corrective feedback in reinforcement learning via distribution correction. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M. F., and Lin, H. (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 18560–18572. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/d7f426ccbc6db7e235c57958c21c5dfa-Paper.pdf`.

Lillicrap, T. P., Hunt, J. J., Pritzel, A., Heess, N., Erez, T., Tassa, Y., Silver, D., and Wierstra, D. Continuous control with deep reinforcement learning. In Bengio, Y. and LeCun, Y. (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016. URL `http://arxiv.org/abs/1509.02971`.

Mnih, V., Kavukcuoglu, K., Silver, D., Graves, A., Antonoglou, I., Wierstra, D., and Riedmiller, M. A. Playing atari with deep reinforcement learning. *CoRR*, abs/1312.5602, 2013. URL `http://arxiv.org/abs/1312.5602`.

Munos, R., Stepleton, T., Harutyunyan, A., and Bellemare, M. G. Safe and efficient off-policy reinforcement learning. In Lee, D. D., Sugiyama, M., von Luxburg, U., Guyon, I., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pp. 1046–1054, 2016. URL `https://proceedings.neurips.cc/paper/2016/hash/c3992e9a68c5ae12bd18488bc579b30d-Abstract.html`.

Nair, S. and Finn, C. Hierarchical foresight: Self-supervised learning of long-horizon tasks via visual subgoal generation. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=H1gzR2VKDH`.

Nasiriany, S., Pong, V., Lin, S., and Levine, S. Planning with goal-conditioned policies. *Advances in Neural Information Processing Systems*, 2019.

Oh, J., Guo, Y., Singh, S., and Lee, H. Self-imitation learning. *CoRR*, abs/1806.05635, 2018. URL `http://arxiv.org/abs/1806.05635`.

Plappert, M., Andrychowicz, M., Ray, A., McGrew, B., Baker, B., Powell, G., Schneider, J., Tobin, J., Chociej, M., Welinder, P., Kumar, V., and Zaremba, W. Multi-goal reinforcement learning: Challenging robotics environments and request for research. *CoRR*, abs/1802.09464, 2018. URL `http://arxiv.org/abs/1802.09464`.

Russell, S. J. and Norvig, P. *Artificial Intelligence: A Modern Approach (4th Edition)*. Pearson, 2020. ISBN 9780134610993. URL `http://aima.cs.berkeley.edu/`.

Schrittwieser, J., Antonoglou, I., Hubert, T., Simonyan, K., Sifre, L., Schmitt, S., Guez, A., Lockhart, E., Hassabis, D., Graepel, T., Lillicrap, T. P., and Silver, D. Mastering atari, go, chess and shogi by planning with a learned model. *CoRR*, abs/1911.08265, 2019. URL `http://arxiv.org/abs/1911.08265`.

Silver, D. and Ciosek, K. Compositional Planning Using Optimal Option Models. In *Proceedings of the 29th International Conference on Machine Learning*, pp. 165. icml.cc / Omnipress, 2012.

Sutton, R. S. and Barto, A. G. *Reinforcement Learning: An Introduction*. A Bradford Book, Cambridge, MA, USA, 2018. ISBN 0262039249.

Tang, Y. Self-imitation learning via generalized lower bound q-learning. *CoRR*, abs/2006.07442, 2020. URL `https://arxiv.org/abs/2006.07442`.

van Hasselt, H., Guez, A., and Silver, D. Deep reinforcement learning with double q-learning. *CoRR*, abs/1509.06461, 2015. URL `http://arxiv.org/abs/1509.06461`.

Ye, W., Liu, S., Kurutach, T., Abbeel, P., and Gao, Y. Mastering atari games with limited data. *CoRR*, abs/2111.00210, 2021. URL `https://arxiv.org/abs/2111.00210`.

Zhang, H., Xu, W., and Yu, H. Generative planning for temporally coordinated exploration in reinforcement learning. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=YZHES8wIdE`.