InComeS: Integrating Compression and Selection Mechanisms into LLMs for Efficient Model Editing

Abstract

Although existing model editing methods perform well in recalling exact edit facts, they often struggle in complex scenarios that require deeper semantic understanding rather than mere knowledge regurgitation. Leveraging the strong contextual reasoning abilities of large language models (LLMs), in-context learning (ICL) becomes a promising editing method by comprehending edit information through context encoding. However, this method is constrained by the limited context window of LLMs, leading to degraded performance and efficiency as the number of edits increases. To overcome this limitation, we propose InComeS, a flexible framework that enhances LLMs' ability to process editing contexts through explicit compression and selection mechanisms. Specifically, InComeS compresses each editing context into the key-value (KV) cache of a special token, enabling efficient handling of multiple edits without being restricted by the model's context window. Furthermore, specialized cross-attention modules are added to dynamically select the most relevant information from the pool of special tokens, enabling adaptive and effective utilization of edit information. We conduct experiments on diverse model editing benchmarks with various editing formats, and the results demonstrate the effectiveness and efficiency of our method.

1 Introduction

Model editing, also known as knowledge editing, has seen rapid progress in recent years (Fang et al., 2025; Li et al., 2024; Wang et al., 2024; Zhang et al., 2024a). Its primary goal is to precisely integrate updated knowledge into a model, enabling targeted behavioral modifications while maintaining performance on unrelated tasks. Existing techniques have demonstrated strong performance in accurately recalling edited facts (Yao et al., 2023; Zhang et al., 2024a, 2025). However, they often struggle in more complex editing scenarios, such as multi-hop editing composition (Zhong et al., 2023; Zhang et al., 2025), natural language editing (Akyürek et al., 2023), and editing tasks that require reasoning and generalization (Cohen et al., 2024; Zhang et al., 2024a). Moreover, recent studies (Zhang et al., 2025) show that previous editing methods are prone to overfitting: they may assign excessively high probabilities to edited targets, which can distort the model's responses to more complex or nuanced queries.

Leveraging the in-context learning (ICL) abilities of large language models (LLMs) provides a promising direction for addressing these problems. As LLMs continue to grow in size and capability, their ability to understand and utilize contextual information continues to improve. By incorporating all the editing information into the prefix contexts, ICL enables a simple, powerful, and flexible approach for employing updated knowledge in complex scenarios. However, this approach faces significant challenges as the number of edits increases. First, the finite context window restricts the maximum number of edits that can be included, and the computational cost of self-attention over long contexts leads to a sharp decline in *efficiency*. Moreover, the effectiveness of ICL is constrained by the model's ability to process extended contexts, and the retrieval *accuracy* of the most relevant editing information also tends to decrease as the editing context grows.

To address these challenges, we introduce *In-ComeS* (**In**tegrating **Com**pression and **S**election Mechanisms), a novel framework for efficient and scalable model editing. InComeS adopts context compression techniques to condense the representation of each edit into the KV cache of special gist tokens, which can be cached and reused for computational efficiency. While gisting (Mu et al., 2023) was originally developed to compress single-input prompts, we extend this approach to handle mul-

tiple edits by further introducing a specialized selection mechanism. We further augment the model with cross-attention modules that allow each input token to attend to the compressed gist representations of edits, enabling fine-grained and adaptive selection of the most relevant information. Since each edit is compressed in parallel, our framework overcomes the limitations imposed by the context window, and the specialized selection modules can be learned to enhance retrieval accuracy.

We conduct experiments across a range of complex model editing settings, including multi-hop editing, natural language editing, and tasks requiring complicated reasoning. Experimental results demonstrate that InComeS outperforms existing editing methods, effectively handling diverse editing scenarios while offering efficiency gains.

2 Preliminary

Model editing (Yao et al., 2023; Mitchell et al., 2022a) aims to adjust a base model ψ to a post-edited model ψ' according to a set of editing information $\mathcal{T} = \{t_1, \ldots, t_n\}$: $\psi' = \text{Edit}(\psi, \{t_1, \ldots, t_n\})$. Here, "Edit" indicates the model editing method, while $\{t_1, \ldots, t_n\}$ represents the knowledge pieces to be integrated. A typical example of editing information is query-label pair $t = (x, y)$, where the goal is for the edited model to produce y in response to input x, even if the original model does not: $\psi(x) \neq y, \psi'(x) = y$. When the editing set contains only a single piece of information ($|\mathcal{T}| = 1$), this is known as single-instance editing. In contrast, batch editing refers to the scenario where multiple pieces of knowledge are updated simultaneously ($|\mathcal{T}| > 1$). Batch editing is particularly practical in real-world applications, where simultaneously updating several edits is often required. In these scenarios, it will be more efficient to integrate them into the model in a single operation.

In practice, editing information can take various forms beyond simple query-label pairs. For instance, multiple related edits can be combined to enable multihop editing, or updated knowledge may be provided as a paragraph of natural language text. In such scenarios, many traditional editing methods may struggle to produce the desired outcomes, since they are not designed to handle these diverse types of editing information. In contrast, in-context learning (ICL) approaches, where editing information is simply concatenated

as contextual prefixes, offer a straightforward yet powerful solution: $\text{Edit}_{\text{ICL}}(\psi, \{t_1, \ldots, t_n\})(x) = \psi(t_1, \ldots, t_n, x)$. By leveraging the LLM's ability to understand and reason over context, ICL can naturally accommodate a wide range of editing scenarios. Nevertheless, ICL is constrained by the context window of LLMs, and its accuracy and efficiency tend to decline when processing larger batches of edits.

3 Method

In this work, we aim to enhance the ICL-based editing approach to better understand multiple edits and accurately extract relevant information from the edit batch. Given a batch of editing information set $\mathcal{T} = \{t_1, \ldots, t_n\}$, an input query x, and the subset of its related[1] edits $\{t_i | i \in \mathfrak{R}(x)\}$, we hope that our model can answer the query as effectively as a vanilla LM provided only with the relevant edits (ignoring the irrelevant editing information): $\psi' = \text{Edit}(\psi, \{t_1, \ldots, t_n\}) \approx \text{Edit}(\psi, \{t_i | i \in \mathfrak{R}(x)\})$.

To enable accurate and efficient batch editing, we propose ***InComeS*** an ICL-based approach that integrates both compression and selection mechanisms into the LMs. First, we adopt gist-based edit compression, condensing each editing information into the KV cache representations of one special (gist) token. Furthermore, we introduce parallel-context cross-attention modules that allow ordinary tokens to attend to these compressed gist representations. These modules serve as soft selectors to dynamically identify the most relevant information for the current input. This strategy can effectively mitigate the limitations imposed by context window sizes and enhance the model's ability to precisely capture editing information.

3.1 Edit Compression

We adopt the concept of gisting (Mu et al., 2023), which is originally developed to compress input prompts into the representations of an extra, specially inserted token (the gist token). The condensed gist activation serves the same function as the original prompt and can be cached for later reuse, thereby improving computational and memory efficiency. While the original work primarily focuses on instruction tuning, we extend this idea to edit compression.

---

[1]We define related edits as those editing pieces that the model should reference when answering the query.

Figure 1: An overview of *InComeS*. At the compression stage, each edit is individually condensed into KV cache representations of a gist token. These representations are integrated into the model via selection through the cross-attention modules. A special zero-gist token is included alongside the cached gists from actual edits, allowing the model to have the option to "select nothing." Note that the compression and integration steps are performed separately, but both use the same underlying model.

For each editing information piece t_i, represented as a sequence of tokens $t_i^0, t_i^1, \ldots, t_i^n$, we append a special gist token t_g to the end of the sequence and feed it into the LM. After encoding, we discard the original edit tokens and retain only the gist's representations (KV caches) for each edit. Notably, each edit context is encoded independently, allowing us to efficiently handle an arbitrary number of edits. This approach is highly flexible and accommodates edits of varying lengths and formats.

After edit compression, the edit information $t_1, t_2, \ldots, t_n$ is converted into their corresponding gist KV representations[2] $(gK_1, gV_1), (gK_2, gV_2), \ldots, (gK_n, gV_n)$. Importantly, we use the same LM targeted for editing to encode and compress the edit information, ensuring that the subsequent information selection process is seamless and well-aligned with the model's internal representations.

3.2 Edit Selection

After compressing the edit contexts, we obtain a pool of gist representations for the batch of edits. To integrate this information into the model, we introduce additional cross-attention modules that enable input tokens to attend to the edit representations. Since these representations are stored as KV caches, we leverage a similar attention mechanism to incorporate the edit information. Formally, given a token's query state q, the cross-attention is computed as: $o_{cross} = attention(q, \{gK_0, gK_1, gK_2, \ldots, gK_n\}, \{gV_0, gV_1, gV_2, \ldots, gV_n\})$. We finally add the

cross-attention outputs to the self-attention outputs for information aggregation.

Since tokens are not required to always attend to the edit information, we further introduce a zero-gist (g_0 in Figure 1) to allow the model to attend to "nothing" when appropriate. For the zero-gist, we use learnable parameters for the key vectors gK_0 and assign fixed zero vectors to the value gV_0. This design allows the model to flexibly select relevant information as needed during sequence prediction.

3.3 Meta Training

Since vanilla LMs lack explicit mechanisms for context compression and selection, we perform continued training (Figure 2) to enhance pre-trained LMs with these capabilities. Our main goal is to ensure that the compressed gist representations serve as effective substitutes for the original editing information. To achieve this, it is essential to distinguish between edit-sensitive tokens, whose losses change significantly when editing context is given, and edit-insensitive tokens, which can be predicted accurately from local context alone and do not depend on edit information. This distinction is captured by employing a customized token weighting scheme:

$$w_{x_i} = \max(0, \; CE(x_i|x_0, \ldots, x_{i-1}) - CE(x_i|\{t_i|i \in \Re(x)\}, x_0, \ldots, x_{i-1})) \quad (1)$$

where the CE is the cross entropy and $\Re(x)$ represents the subset of related edits. Here, the token weight is the difference between the edit-conditioned and edit-unconditioned losses. This scheme increases the weights of edit-sensitive tokens to encourage the model to learn to retrieve information from the compressed edits. The loss differences are calculated with a teacher model,

---

[2]For brevity, we present the representations and operations for a single layer.

Figure 2: An overview of the one-time meta training of *InComeS*. The teacher model performs two forward passes: one with edit-contextualized input (1) and one with uncontextualized input (2). The cross-entropy between the outputs of (1) and (2) is used to compute a customized weight (3). The student model then compresses the edit information into KV representations using gist tokens (4). These KV caches are used to supply edit-relevant information to the query tokens (5). The final loss is computed as the sum of weighted cross entropy and KL divergence (6).

which is the original, unedited version of the target LM.

In addition to token reweighting, we also adopt knowledge distillation (Hinton et al., 2015) to transfer the teacher model's knowledge about the edit information into the target model. Specifically, we apply the KL divergence to align the output distributions of the gist-contextualized student model with those of the edit-contextualized teacher model:

$$KL_{x_i} = D_{KL}(p_T(x_i|\{t_i|i \in \mathfrak{R}(x)\}, x_0, \ldots, x_{i-1}) \,||$$
$$p_S(x_i|\{g_1, \ldots, g_n\}, x_0, \ldots, x_{i-1})) \quad (2)$$

$$loss_{x_i} = w_{x_i} \cdot CE(x_i) + KL_{x_i} \quad (3)$$

Here, $g_1, \ldots, g_n$ denote the cached gists for all the edits. We apply the token reweighting only to the vanilla cross-entropy term in our final loss, since we found that it would degrade effective learning of "attend-to-nothing" behavior if combined with the KL part. The explicit training details are provided in Appendix A.

4 Experiments

4.1 Experiment setting

Datasets & Evaluation Metrics To verify the effectiveness of our method in complex editing scenarios, we conduct experiments on five popular datasets in model editing: the dataset for multi-hop editing MQuAKE (Zhong et al., 2023), the natural language editing dataset DUNE (Akyürek

et al., 2023), the extended version of ZsRE (Yao et al., 2023; Zhang et al., 2024a), which adds a portability test set to the original ZsRE (Levy et al., 2017), and the dataset containing ripple effect samples WikiData$_{counterfact}$ (Cohen et al., 2024; Zhang et al., 2024a). We report edit success rate and portability for the extend-ZsRE and WikiData$_{counterfact}$, the results for 2, 3, and 4 edits for MQuAKE (Zhong et al., 2023) and new information, scientific reasoning, and debiasing for DUNE (Akyürek et al., 2023). More details about the datasets and evaluation metrics can be found in the Appendix B.1 and Appendix B.2, respectively.

Baselines For baselines, we select representative methods demonstrated to be powerful in relevant surveys (Yao et al., 2023; Zhang et al., 2024a). For methods that directly edit the model weights, we include ROME (Meng et al., 2022), R-ROME (Gupta et al., 2024a), MEMIT (Meng et al., 2023), EMMET (Gupta et al., 2024b), AlphaEdit (Fang et al., 2025); for methods that adopt explicit external memory, we include SERAC (Mitchell et al., 2022b), IKE (Zheng et al., 2023), and DR-IKE (Nafee et al., 2025); for methods that requires meta-training (like InComeS) or use implicit external memory (stores activations or nerons, etc), we adopt MEND (Mitchell et al., 2022a), GRACE (Hartvigsen et al., 2022), KN (Dai et al., 2022), MELO (Yu et al., 2024) and RECIPE (Chen et al., 2024). We also include some ICL-related methods like ICE (Qi et al., 2025) and ATBIAS (Bi et al.,

Method	Single Edit	Batch Edit
Llama-3.2-1B		
Base	38.96	38.96
FT-M	54.71	48.71
LoRA (Hu et al., 2022)	65.56	48.44
ROME (Meng et al., 2022)	3.43	-
R-ROME (Gupta et al., 2024a)	5.18	-
MEMIT (Meng et al., 2023)	34.03	24.76
EMMET (Gupta et al., 2024b)	5.58	14.85
GRACE (Hartvigsen et al., 2022)	6.94	2.26
SERAC (Mitchell et al., 2022b)	38.97	39.01
MEND (Mitchell et al., 2022a)	36.41	31.91
RECIPE (Chen et al., 2024)	55.49	45.81
MeLLo (Zhong et al., 2023)	53.09	44.10
MELO (Yu et al., 2024)	40.33	41.47
ATBIAS (Bi et al., 2024)	60.31	50.68
DR-IKE (Nafee et al., 2025)	49.44	38.67
AlphaEdit (Fang et al., 2025)	51.93	41.98
ICE (Qi et al., 2025)	52.81	45.38
ICL	56.62	47.43
InComeS	**71.99**	**53.15**
Qwen2.5-7B		
Base	39.61	39.61
FT-M	73.24	49.91
LoRA (Hu et al., 2022)	33.42	21.25
ROME (Meng et al., 2022)	8.64	-
R-ROME (Gupta et al., 2024a)	7.01	-
MEMIT (Meng et al., 2023)	40.78	40.20
EMMET (Gupta et al., 2024b)	30.28	39.91
GRACE (Hartvigsen et al., 2022)	14.15	5.85
SERAC (Mitchell et al., 2022b)	56.15	40.69
MEND (Mitchell et al., 2022a)	36.61	36.51
RECIPE (Chen et al., 2024)	58.55	46.58
MeLLo (Zhong et al., 2023)	55.50	47.34
MELO (Yu et al., 2024)	40.49	42.20
ATBIAS (Bi et al., 2024)	51.17	45.00
DR-IKE (Nafee et al., 2025)	55.61	41.37
AlphaEdit (Fang et al., 2025)	53.71	50.36
ICE (Qi et al., 2025)	67.30	49.17
ICL	**73.74**	49.61
InComeS	71.41	**52.17**

Table 1: Results on MQuAKE (Zhong et al., 2023). The full version can be found in Table 9.

Method	Single Edit	Batch Edit
Llama-3.2-1B		
Base	48.48	48.48
FT-M	48.83	47.89
LoRA (Hu et al., 2022)	47.08	49.08
SERAC (Mitchell et al., 2022b)	49.45	44.87
ICE (Qi et al., 2025)	48.49	48.76
ICL	57.05	50.69
InComeS	**57.59**	**53.45**
Qwen2.5-7B		
Base	55.47	55.47
FT-M	60.44	56.78
LoRA (Hu et al., 2022)	55.54	57.21
SERAC (Mitchell et al., 2022b)	53.80	48.99
ICE (Qi et al., 2025)	55.30	46.66
ICL	55.47	57.75
InComeS	**65.81**	**63.37**

Table 2: Results on DUNE (Akyürek et al., 2023). Detailed version can be found in Table 10.

4.2 Main results

Multi-hop edits We test our method on MQuAKE for the multiple-hop edit scenario, where the models are required to check multiple edits to answer each query. Because of this requirement, we mainly compare with methods designed to support batch or sequential editing. Table 1 presents our main results, which demonstrate the effectiveness of InComeS in both single-editing and batch-editing scenarios. In addition, InComeS surpasses ICL in all metrics except the single editing setting for Qwen2.5-7B, which shows that our method can effectively select relevant information from the editing contexts. Interestingly, single-edit specialized methods (such as ROME) collapse even in the single multi-hop query setting, revealing their incapability to handle complex editing scenarios. To verify the effectiveness of our method on different model scales, we conduct further analysis on the performance gain of different model scales in Appendix C.9.

Natural language edits One of our method's advantages is its flexibility in handling a variety of editing contexts with different formats. Unlike many traditional editing methods like ROME (Meng et al., 2022) and MEMIT (Meng et al., 2023), which require the input to follow the triplet-like fact statement format, InComeS can take edits in free-text forms without explicitly labeled subjects and objects. To verify our method's capability for such scenarios, we adopt the DUNE dataset, which includes *natural-language form edits*, and the results are shown in Table 2. Following the

2024), and some traditional but powerful methods, like fine-tuning, LoRA (Hu et al., 2022), and ICL, which directly concatenates all the edits as the prefix context. While some similarities exist between our method and RAG, they vary considerably in problem setting and methodology. A detailed analysis is given in Appendix C.1. We choose two representative open-source models for evaluation: Llama-3.2-1B [3] and Qwen2.5-7B (Yang et al., 2024) (More results about Qwen3-8B-base is in Appendix C.14). Unless otherwise specified, we adopt an edit batch size of 100 for batch editing. More details on the baseline implementation can be found in the Appendix B.3.

[3]https://huggingface.co/meta-llama/Llama-3.2-1B

Method	WikiData$_{cf}$		ZsRE-extended	
	Single	Batch	Single	Batch
Llama-3.2-1B				
Base	19.73	19.73	40.17	40.17
FT-M	53.43	47.51	62.80	54.84
LoRA (Hu et al., 2022)	52.87	43.84	57.43	44.85
ROME (Meng et al., 2022)	40.44	-	46.04	-
MEMIT (Meng et al., 2023)	46.34	23.51	43.26	25.68
MEND (Mitchell et al., 2022a)	24.98	21.06	37.53	30.77
GRACE (Hartvigsen et al., 2022)	14.33	10.51	12.73	10.91
IKE (Zheng et al., 2023)	45.55	-	57.39	-
SERAC (Mitchell et al., 2022b)	60.56	40.45	66.59	51.61
ICL	**65.81**	44.75	62.19	51.58
InComeS	65.15	**45.66**	**70.70**	**52.23**
Qwen2.5-7B				
Base	21.46	21.46	43.86	43.86
FT-M	49.39	43.13	50.04	46.41
LoRA (Hu et al., 2022)	37.04	31.65	28.61	24.13
ROME (Meng et al., 2022)	40.25	-	50.43	-
MEMIT (Meng et al., 2023)	43.58	39.85	53.23	49.97
MEND (Mitchell et al., 2022a)	20.45	15.29	43.26	38.83
GRACE (Hartvigsen et al., 2022)	25.60	18.55	14.35	11.25
IKE (Zheng et al., 2023)	65.33	-	70.17	-
SERAC (Mitchell et al., 2022b)	51.12	41.26	62.41	52.63
ICL	**66.99**	**51.66**	66.10	60.57
InComeS	66.69	47.93	**75.63**	**61.22**

Table 3: Portability results on WikiData$_{counterfact}$ (Cohen et al., 2024; Zhang et al., 2024a) and ZsRE-extended (Zhang et al., 2024a; Yao et al., 2023). Full results can be found at Table 7.

350 original paper of DUNE (Akyürek et al., 2023),
351 we include fine-tuning, LoRA, SERAC (Mitchell
352 et al., 2022b), and ICL as our baselines. The result
353 confirms our method's capability to handle natural
354 language edits. Interestingly, the raw model itself
355 is a strong baseline in the batch editing scenario,
356 which may demonstrate the fast-evolving model
357 capabilities over the years.

358 **Evaluation on portability** We further evaluate
359 our method on two popular editing datasets that re-
360 quire reasoning abilities: $Wiki_{counterfact}$ (Cohen
361 et al., 2024; Zhang et al., 2024a) and the extended
362 ZsRE (Yao et al., 2023; Zhang et al., 2024a). Ta-
363 ble 3 shows the results. Our primary focus is on
364 portability, as it serves as the most representative
365 metric for assessing a model's comprehensive un-
366 derstanding of the editing information. Overall,
367 our method achieves performance comparable to
368 ICL and consistently outperforms other baselines.
369 More analysis about the detailed results is given in
370 Appendix C.8.

371 **Scaling up contexts** We further provide a scaling-
372 up analysis to illustrate our method's ability to gen-
373 eralize to larger numbers of edits, which is the
374 main motivation of our modification over the ICL
375 baseline. For this analysis, we use the COUNTER-

Figure 3: Scaling-up analysis. We compare InComeS and ICL by varying the number of edits, as indicated on the x-axis.

Llama-3.2-1B	
Method	Time (seconds)
InComeS-Compression	**0.0326**
ICL-Prefilling	0.8934
FT-M	3.4124
LoRA (Hu et al., 2022)	33.5412
MEMIT (Meng et al., 2023)	112.2238
EMMET (Gupta et al., 2024b)	158.6524
Qwen2.5-7B	
InComeS-Compression	**0.1071**
ICL-Prefilling	0.9082
FT-M	28.6132
LoRA (Hu et al., 2022)	122.1876
MEMIT (Meng et al., 2023)	423.4823
EMMET (Gupta et al., 2024b)	512.4235

Table 4: Measured time (seconds) for 100 edits.

376 FACT dataset (Meng et al., 2023), as it provides a
377 sufficient number of editing instances. We vary the
378 number of edits from 100 to 1000, resulting in total
379 token counts ranging from approximately $1.2K$ to
380 $12K$. The results are shown in Figure 3, which
381 shows that InComeS consistently outperforms ICL,
382 though the base models have already been pre-
383 trained over long contexts (Yang et al., 2024). This
384 finding suggests that the vanilla attention mecha-
385 nism alone is insufficient to effectively comprehend
386 and precisely select the required information from
387 the context in complex editing scenarios. In con-
388 trast, our method demonstrates greater potential for
389 handling large-scale edits through the unified com-
390 pression and selection mechanism. Further scaling
391 up experiments could be found in Appendix C.10.

4.3 Efficiency Analysis

393 Finally, we present the efficiency analysis for our
394 method. By default, the individual edit length is
395 around 10 to 11. We first compare the efficiency of
396 our method with the efficiency of other knowledge
397 editing methods. Table 4 reports the time required
398 to perform 100 edits for each method. Our method
399 has significantly better efficiency than the other pre-

Method	Time (seconds)
Encoding w/ $1k$	
InComeS-Compression	**0.2108**
ICL-Prefilling	1.0413
Decoding w/ $1k$	
InComeS-Selection	**0.0274**
ICL-Generation (with prefilled cache)	0.1555
Encoding w/ $2k$	
InComeS-Compression	**0.4051**
ICL-Prefilling	1.2165
Decoding w/ $2k$	
InComeS-Selection	**0.0297**
ICL-Generation (with prefilled cache)	0.3545

Table 5: Scaled efficiency comparison (seconds) between InComeS and ICL using Llama-3.2-1B.

Method	MQuAKE	
	Single editing	Batch editing
InComeS	71.99	**53.15**
- w/o zero-gist	58.98	40.59
- w/ full model	**72.40**	52.34
- w/o loss on query	59.86	44.78
- w/ golden loss	71.09	48.56
- w/o kl loss (Eq. 2)	55.10	51.71
- w/o token weighting (Eq. 1)	55.02	52.63

Table 6: Ablation and Analysis experiments, the edit batch size is 100 for all results. Detailed results can be found in Table 8.

sented editing methods. Additionally, compared to ICL, our approach only needs to maintain the KV cache of the gist representations from the deeper half layers, resulting in substantially lower memory cost. To verify our method's superiority in efficiency on long context, we further conduct experiments on scaled context length (Table 5). The result demonstrates the efficiency advantage of our method in both the encoding and decoding stages. More detailed analysis about the efficiency including time and memory can be found in Appendix C.3 and Appendix C.12.

4.4 Ablation study & Analysis

Full model vs. Half model We present the reason for our decision to use the KV cache from the second half of the model layers. To investigate this, we train a model using the KV cache from all layers and evaluate it on 1000 instances from ZsRE (Levy et al., 2017). We record the probabilities allocated to the zero-gist in the cross-attention modules, as shown in Fig. 4b. The result shows that the zero-gist probabilities in layers 7-15 are generally lower than those in layers 1-6, and there is a notable drop in the zero-gist probability at layer 7. This suggests that, even when trained to use the full-model KV cache, the model mainly relies on information from deeper layers, since higher probabilities of the zero-gists indicate lower utilization of the actual edit contexts. A possible explanation is that more information is accumulated in the deeper layers, which aids both compression and selection processes. To verify our analysis, we also test the full layer trained model (see the "w/ full model" line in Table 6). The results show nearly no increase compared to the half model case (InComeS). Additionally, restricting the KV cache to only the second half of the model could provide efficiency benefits with lower memory and computation costs.

Deciding inference temperature Applying a small temperature to the gist cross-attention sharpens the probability distribution over the gist KV caches, which facilitates the model's ability to retrieve the correct information. We determine the appropriate temperature based on entropy, which has been shown to be an important factor in attention mechanisms (Zhang et al., 2024b). Specifically, we aim to keep the cross-attention entropy close to its optimal value, which occurs when it only needs to attend to one edit. To achieve this, we select 1000 instances from ZsRE (Levy et al., 2017) and calculate the entropy of the edit batch size 1. We then calculate the entropy for larger edit batch sizes (10, 20, 40, 60, 80, 100, 200, 300) and find the temperatures that align their entropy with the optimal case via gradient descent [4]. We report the calculated temperature in Figure 4a. As expected, the temperature decreases as the edit batch size increases, but interestingly, it gradually converges to a specific value. Specifically, layers 9, 10, and 14 finally converge to around 0.5. To encourage more decisive selection, we slightly lower this value and set the temperature to $T = 0.45$.

Imposing golden loss on training As the golden gist representation is available for each training instance, it is natural to introduce an auxiliary loss to encourage correct selection in the cross-attention mechanism. We incorporate this additional loss in our experiments and report the result as "w/ golden loss" in Table 6. In the analysis in Figure 4, we use a suffix of "- t" to denote this setting. Incorporating the auxiliary loss leads the model to assign higher

---

[4]Note that all entropy is calculated in a way that the query and answer part are just a copy of the context

Figure 4: Ablation and Analysis. (a) Experiments to investigate the desired temperature for cross-attention. (b) Investigation on the informativeness of the layers. (c) and (d) Study to reveal the selection pattern of the query tokens.

probabilities to the golden gist compared to training without this loss. Interestingly, it also increases the cross-attention entropy, probably because the model is explicitly encouraged to make selections during training. However, despite the increase in golden-gist probabilities, this approach does not yield clear performance improvements and even results in declines in some cases. This suggests that the model may develop its own context selection strategies, which do not always align with focusing all attention on the golden edit information.

More analysis More analysis including side-effect analysis, etc. is provided in Appendix C.

5 Related Work

The area of knowledge editing (or model editing) has experienced a thriving development in recent years. Researchers have explored various directions in this area. One typical direction is to adopt external memory for the edits. The memory formats applied by different researchers are diverse. Methods like SERAC (Mitchell et al., 2022b), IKE (Zheng et al., 2023), DR-IKE (Nafee et al., 2025), MeLLo (Zhong et al., 2023) adopt *explicit non-parametric memory*, which stores specific edit instances, and a retriever that is responsible for recalling relevant edits from the memory. For example, IKE uses KNN, and SERAC applies a trained classifier. Another line of work, such as RECIPE (Chen et al., 2024), applies *implicit parametric memory* to store the edits. CaliNET (Dong et al., 2022), T-Patcher (Huang et al., 2023) embeds the knowledge into a fixed number of neurons and adds them to the model. GRACE (Hartvigsen et al., 2022) adopts

a discrete key-value codebook with the value optimized for the desired knowledge. MELO (Yu et al., 2024) applies dynamic LoRA blocks and indexes them via an internal vector database. KE (De Cao et al., 2021), MEND (Mitchell et al., 2022a) train a separate meta-model for editing. Another popular direction is to merge knowledge into the model directly. Methods like KN (Dai et al., 2022), ROME (Meng et al., 2022), R-ROME (Gupta et al., 2024a), MEMIT (Meng et al., 2023), PMET (Li et al., 2023), CoachHooK (Li et al., 2024), and AlphaEdit (Fang et al., 2025) perform editing by tweaking the located FFN part of the model directly. However, some studies reveal that these methods could potentially bring about side effects in the original model (Gu et al., 2024; Pinter and Elhadad, 2023), leaving the real effectiveness of these methods to be further investigated.

6 Conclusion

In this paper, we propose InComeS, a scalable model editing method that integrates compression and selection mechanisms directly into the LLMs. InComeS adopts a context compression technique to condense the editing context to KV representations on top of the introduced gist tokens and takes advantage of the compressed KVs to efficiently retrieve the relevant editing context information. Experiments on four different and complex editing settings demonstrate the superiority of our method for comprehensively editing. Further Analysis and ablations validate each component of InComeS and demonstrate the great efficiency and performance gain of our method.

Limitations

Model scale & Architecture   Due to the limited computational resources, we only extend the model size to 7B and leave the larger model size to future work. We are aware that the original gisting work (Mu et al., 2023) conducts experiments on three model architectures, i.e., encoder-decoder, encoder-only, and decoder-only. In this work, we determine to focus on the decoder-only autoregressive architecture as it is the structure used by most of the popular models nowadays (Yang et al., 2024; OpenAI, 2023; DeepSeek-AI et al., 2024).

Compression rate   In this work, we maintain the compression rate to roughly around 12:1 (one edit, which contains around 12 tokens for all testing datasets except DUNE (Akyürek et al., 2023), corresponds to one gist token), as one edit represents a fine-grained piece of information. However, we believe it is necessary to investigate the impact of lowering the compression rate, since it potentially helps extend the length of a single edit (Deng et al., 2024, 2025).

Task variety   InComeS can accept any input that follows natural language form. This flexibility gives it the potential to tackle many other tasks beyond knowledge editing. For example, long context language modeling, retrieval-augmented generation, etc. Due to the limited space of the main body of the paper, we first verify the effectiveness of our method on model editing and leave the investigation of other tasks to future work.

References

Afra Feyza Akyürek, Eric Pan, Garry Kuwanto, and Derry Wijaya. 2023. Dune: Dataset for unified editing. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 1847–1861. Association for Computational Linguistics.

Baolong Bi, Shenghua Liu, Yiwei Wang, Lingrui Mei, Hongcheng Gao, Yilong Xu, and Xueqi Cheng. 2024. Adaptive token biaser: Knowledge editing via biasing key entities. In *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024*, volume EMNLP 2024 of *Findings of ACL*, pages 11071–11083. Association for Computational Linguistics.

Qizhou Chen, Taolin Zhang, Xiaofeng He, Dongyang Li, Chengyu Wang, Longtao Huang, and Hui Xue'. 2024. Lifelong knowledge editing for llms with retrieval-augmented continuous prompt learning. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 13565–13580. Association for Computational Linguistics.

Roi Cohen, Eden Biran, Ori Yoran, Amir Globerson, and Mor Geva. 2024. Evaluating the ripple effects of knowledge editing in language models. *Trans. Assoc. Comput. Linguistics*, 12:283–298.

Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. 2022. Knowledge neurons in pretrained transformers. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pages 8493–8502. Association for Computational Linguistics.

Nicola De Cao, Wilker Aziz, and Ivan Titov. 2021. Editing factual knowledge in language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 6491–6506, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.

DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, and 81 others. 2024. Deepseek-v3 technical report. *CoRR*, abs/2412.19437.

Chenlong Deng, Zhisong Zhang, Kelong Mao, Shuaiyi Li, Tianqing Fang, Hongming Zhang, Haitao Mi, Dong Yu, and Zhicheng Dou. 2025. Unigist: Towards general and hardware-aligned sequence-level long context compression. *CoRR*, abs/2509.15763.

Chenlong Deng, Zhisong Zhang, Kelong Mao, Shuaiyi Li, Xinting Huang, Dong Yu, and Zhicheng Dou. 2024. A silver bullet or a compromise for full attention? A comprehensive study of gist token-based context compression. *CoRR*, abs/2412.17483.

Qingxiu Dong, Damai Dai, Yifan Song, Jingjing Xu, Zhifang Sui, and Lei Li. 2022. Calibrating factual knowledge in pretrained language models. In *Findings of the Association for Computational Linguistics: EMNLP 2022, Abu Dhabi, United Arab Emirates, December 7-11, 2022*, pages 5937–5947. Association for Computational Linguistics.

Junfeng Fang, Houcheng Jiang, Kun Wang, Yunshan Ma, Jie Shi, Xiang Wang, Xiangnan He, and Tat-Seng Chua. 2025. Alphaedit: Null-space constrained knowledge editing for language models. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Jia-Chen Gu, Hao-Xiang Xu, Jun-Yu Ma, Pan Lu, Zhen-Hua Ling, Kai-Wei Chang, and Nanyun Peng. 2024.

Model editing harms general abilities of large language models: Regularization to the rescue. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 16801–16819. Association for Computational Linguistics.

Akshat Gupta, Sidharth Baskaran, and Gopala Anumanchipalli. 2024a. Rebuilding ROME : Resolving model collapse during sequential model editing. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 21738–21744. Association for Computational Linguistics.

Akshat Gupta, Dev Sajnani, and Gopala Anumanchipalli. 2024b. A unified framework for model editing. In *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024*, pages 15403–15418. Association for Computational Linguistics.

Thomas Hartvigsen, Swami Sankaranarayanan, Hamid Palangi, Yoon Kim, and Marzyeh Ghassemi. 2022. Aging with GRACE: lifelong model editing with discrete key-value adaptors. *CoRR*, abs/2211.11031.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. Measuring massive multitask language understanding. In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Geoffrey E. Hinton, Oriol Vinyals, and Jeffrey Dean. 2015. Distilling the knowledge in a neural network. *CoRR*, abs/1503.02531.

Pin-Lun Hsu, Yun Dai, Vignesh Kothapalli, Qingquan Song, Shao Tang, Siyu Zhu, Steven Shimizu, Shivam Sahni, Haowen Ning, and Yanning Chen. 2024. Liger kernel: Efficient triton kernels for LLM training. *CoRR*, abs/2410.10989.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. Lora: Low-rank adaptation of large language models. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.

Zeyu Huang, Yikang Shen, Xiaofeng Zhang, Jie Zhou, Wenge Rong, and Zhang Xiong. 2023. Transformer-patcher: One mistake worth one neuron. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net.

Tushar Khot, Peter Clark, Michal Guerquin, Peter Jansen, and Ashish Sabharwal. 2020. QASC: A dataset for question answering via sentence composition. In *The Thirty-Fourth AAAI Conference on Artificial Intelligence, AAAI 2020, The Thirty-Second Innovative Applications of Artificial Intelligence Conference, IAAI 2020, The Tenth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2020, New York, NY, USA, February 7-12, 2020*, pages 8082–8090. AAAI Press.

Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur P. Parikh, Chris Alberti, Danielle Epstein, Illia Polosukhin, Jacob Devlin, Kenton Lee, Kristina Toutanova, Llion Jones, Matthew Kelcey, Ming-Wei Chang, Andrew M. Dai, Jakob Uszkoreit, Quoc Le, and Slav Petrov. 2019. Natural questions: a benchmark for question answering research. *Trans. Assoc. Comput. Linguistics*, 7:452–466.

Brian Lester, Rami Al-Rfou, and Noah Constant. 2021. The power of scale for parameter-efficient prompt tuning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, pages 3045–3059. Association for Computational Linguistics.

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. 2017. Zero-shot relation extraction via reading comprehension. In *Proceedings of the 21st Conference on Computational Natural Language Learning (CoNLL 2017)*, pages 333–342, Vancouver, Canada. Association for Computational Linguistics.

Shuaiyi Li, Yang Deng, Deng Cai, Hongyuan Lu, Liang Chen, and Wai Lam. 2024. Consecutive batch model editing with hook layers. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 13817–13833. Association for Computational Linguistics.

Xiang Lisa Li and Percy Liang. 2021. Prefix-tuning: Optimizing continuous prompts for generation. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 1: Long Papers), Virtual Event, August 1-6, 2021*, pages 4582–4597. Association for Computational Linguistics.

Xiaopeng Li, Shasha Li, Shezheng Song, Jing Yang, Jun Ma, and Jie Yu. 2023. PMET: precise model editing in a transformer. *CoRR*, abs/2308.08742.

Xiao Liu, Yanan Zheng, Zhengxiao Du, Ming Ding, Yujie Qian, Zhilin Yang, and Jie Tang. 2024. GPT understands, too. *AI Open*, 5:208–215.

Kyle Lo, Lucy Lu Wang, Mark Neumann, Rodney Kinney, and Daniel S. Weld. 2020. S2ORC: the semantic scholar open research corpus. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, ACL 2020, Online, July 5-10, 2020*, pages 4969–4983. Association for Computational Linguistics.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*.

Kevin Meng, Arnab Sen Sharma, Alex J. Andonian, Yonatan Belinkov, and David Bau. 2023. Mass-editing memory in a transformer. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net.

Yukai Miao, Yu Bai, Li Chen, Dan Li, Haifeng Sun, Xizheng Wang, Ziqiu Luo, Yanyu Ren, Dapeng Sun, Xiuting Xu, Qi Zhang, Chao Xiang, and Xinchi Li. 2023. An empirical study of netops capability of pre-trained large language models. *CoRR*, abs/2309.05557.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a suit of armor conduct electricity? A new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing, Brussels, Belgium, October 31 - November 4, 2018*, pages 2381–2391. Association for Computational Linguistics.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. 2022a. Fast model editing at scale. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.

Eric Mitchell, Charles Lin, Antoine Bosselut, Christopher D. Manning, and Chelsea Finn. 2022b. Memory-based model editing at scale. In *International Conference on Machine Learning, ICML 2022, 17-23 July 2022, Baltimore, Maryland, USA*, volume 162 of *Proceedings of Machine Learning Research*, pages 15817–15831. PMLR.

Jesse Mu, Xiang Li, and Noah D. Goodman. 2023. Learning to compress prompts with gist tokens. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Ananth Muppidi, Abhilash Nandy, and Sambaran Bandyopadhyay. 2025. Leveraging self-attention for input-dependent soft prompting in llms. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 960–969. Association for Computational Linguistics.

Mahmud Wasif Nafee, Maiqi Jiang, Haipeng Chen, and Yanfu Zhang. 2025. Dynamic retriever for in-context knowledge editing via policy optimization. *CoRR*, abs/2510.21059.

OpenAI. 2023. GPT-4 technical report. *CoRR*, abs/2303.08774.

Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. 2022. Medmcqa: A large-scale multi-subject multi-choice dataset for medical domain question answering. In *Conference on Health, Inference, and Learning, CHIL 2022, 7-8 April 2022, Virtual Event*, volume 174 of *Proceedings of Machine Learning Research*, pages 248–260. PMLR.

Yuval Pinter and Michael Elhadad. 2023. Emptying the ocean with a spoon: Should we edit models? In *Findings of the Association for Computational Linguistics: EMNLP 2023, Singapore, December 6-10, 2023*, pages 15164–15172. Association for Computational Linguistics.

Siyuan Qi, Bangcheng Yang, Kailin Jiang, Xiaobo Wang, Jiaqi Li, Yifan Zhong, Yaodong Yang, and Zilong Zheng. 2025. In-context editing: Learning knowledge from self-induced distributions. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Samyam Rajbhandari, Jeff Rasley, Olatunji Ruwase, and Yuxiong He. 2020. Zero: memory optimizations toward training trillion parameter models. In *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis, SC 2020, Virtual Event / Atlanta, Georgia, USA, November 9-19, 2020*, page 20. IEEE/ACM.

Samyam Rajbhandari, Olatunji Ruwase, Jeff Rasley, Shaden Smith, and Yuxiong He. 2021. Zero-infinity: breaking the GPU memory wall for extreme scale deep learning. In *International Conference for High Performance Computing, Networking, Storage and Analysis, SC 2021, St. Louis, Missouri, USA, November 14-19, 2021*, page 59. ACM.

Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. SQuAD: 100,000+ questions for machine comprehension of text. In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2383–2392, Austin, Texas. Association for Computational Linguistics.

Jie Ren, Samyam Rajbhandari, Reza Yazdani Aminabadi, Olatunji Ruwase, Shuangyan Yang, Minjia Zhang, Dong Li, and Yuxiong He. 2021. Zero-offload: Democratizing billion-scale model training. In *Proceedings of the 2021 USENIX Annual Technical Conference, USENIX ATC 2021, July 14-16, 2021*, pages 551–564. USENIX Association.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of BERT: smaller, faster, cheaper and lighter. *CoRR*, abs/1910.01108.

Pengwei Tang, Xiaolin Hu, and Yong Liu. 2025. Adept: Adaptive decomposed prompt tuning for parameter-efficient fine-tuning. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Peng Wang, Zexi Li, Ningyu Zhang, Ziwen Xu, Yunzhi Yao, Yong Jiang, Pengjun Xie, Fei Huang, and Huajun Chen. 2024. WISE: rethinking the knowledge memory for lifelong model editing of large language models. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024*.

Peng Wang, Ningyu Zhang, Bozhong Tian, Zekun Xi, Yunzhi Yao, Ziwen Xu, Mengru Wang, Shengyu Mao, Xiaohan Wang, Siyuan Cheng, Kangwei Liu, Yuansheng Ni, Guozhou Zheng, and Huajun Chen. 2023. Easyedit: An easy-to-use knowledge editing framework for large language models. *CoRR*, abs/2308.07269.

Shitao Xiao, Zheng Liu, Peitian Zhang, and Niklas Muennighoff. 2023. C-pack: Packaged resources to advance general chinese embedding. *CoRR*, abs/2309.07597.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, Guanting Dong, Haoran Wei, Huan Lin, Jialong Tang, Jialin Wang, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Ma, and 43 others. 2024. Qwen2 technical report. *CoRR*, abs/2407.10671.

Wanli Yang, Fei Sun, Jiajun Tan, Xinyu Ma, Qi Cao, Dawei Yin, Huawei Shen, and Xueqi Cheng. 2025a. The mirage of model editing: Revisiting evaluation in the wild. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2025, Vienna, Austria, July 27 - August 1, 2025*, pages 15336–15354. Association for Computational Linguistics.

Wujian Yang, Chunxu Jin, Guanlin Chen, and Haotian Jin. 2025b. Ce-prompt: enhance prompt expression stability by multiple understanding. *PeerJ Comput. Sci.*, 11:e3231.

Xianjun Yang, Wei Cheng, Xujiang Zhao, Wenchao Yu, Linda Ruth Petzold, and Haifeng Chen. 2025c. Position really matters: Towards a holistic approach for prompt tuning. In *Findings of the Association for Computational Linguistics: NAACL 2025, Albuquerque, New Mexico, USA, April 29 - May 4, 2025*, Findings of ACL, pages 8501–8523. Association for Computational Linguistics.

Yunzhi Yao, Peng Wang, Bozhong Tian, Siyuan Cheng, Zhoubo Li, Shumin Deng, Huajun Chen, and Ningyu Zhang. 2023. Editing large language models: Problems, methods, and opportunities. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 10222–10240. Association for Computational Linguistics.

Lang Yu, Qin Chen, Jie Zhou, and Liang He. 2024. MELO: enhancing model editing with neuron-indexed dynamic lora. In *Thirty-Eighth AAAI Conference on Artificial Intelligence, AAAI 2024, Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence, IAAI 2024, Fourteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2014, February 20-27, 2024, Vancouver, Canada*, pages 19449–19457. AAAI Press.

Mengqi Zhang, Xiaotian Ye, Qiang Liu, Shu Wu, Pengjie Ren, and Zhumin Chen. 2025. Uncovering overfitting in large language model editing. In *The Thirteenth International Conference on Learning Representations, ICLR 2025, Singapore, April 24-28, 2025*. OpenReview.net.

Ningyu Zhang, Yunzhi Yao, Bozhong Tian, Peng Wang, Shumin Deng, Mengru Wang, Zekun Xi, Shengyu Mao, Jintian Zhang, Yuansheng Ni, Siyuan Cheng, Ziwen Xu, Xin Xu, Jia-Chen Gu, Yong Jiang, Pengjun Xie, Fei Huang, Lei Liang, Zhiqiang Zhang, and 3 others. 2024a. A comprehensive study of knowledge editing for large language models. *CoRR*, abs/2401.01286.

Zhisong Zhang, Yan Wang, Xinting Huang, Tianqing Fang, Hongming Zhang, Chenlong Deng, Shuaiyi Li, and Dong Yu. 2024b. Attention entropy is a key factor: An analysis of parallel context encoding with full-attention-based pre-trained language models. *CoRR*, abs/2412.16545.

Ce Zheng, Lei Li, Qingxiu Dong, Yuxuan Fan, Zhiyong Wu, Jingjing Xu, and Baobao Chang. 2023. Can we edit factual knowledge by in-context learning? In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 4862–4876. Association for Computational Linguistics.

Zexuan Zhong, Zhengxuan Wu, Christopher D. Manning, Christopher Potts, and Danqi Chen. 2023. Mquake: Assessing knowledge editing in language models via multi-hop questions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 15686–15702. Association for Computational Linguistics.

A Training details

InComeS is trained on around 1.5 billion tokens, which mainly come from summarization and QA datasets. Specifically, for summerization datasets, we select $4.5e^6$ instances from S2ORC (Lo et al., 2020), $1.15e^6$ instances from AG News Corpus [5]; and for QA datasets, we use squad (Rajpurkar et al., 2016), a modified version [6] of the natural question dataset (Kwiatkowski et al., 2019), OpenBookQA (Mihaylov et al., 2018), QASC (Khot et al., 2020), MedMCQA (Pal et al., 2022), and NetEval (Miao

---

[5]https://huggingface.co/datasets/sentence-transformers/agnews

[6]https://huggingface.co/datasets/LLukas22/nq-simplified

et al., 2023). We also include the training split of ZsRE (Levy et al., 2017), COUNTERFACT (Meng et al., 2023), $Wiki_{counterfact}$ from EasyEdit framework (Wang et al., 2023).

We use a cosine linear-warmup scheduler for both models, with a maximum learning rate $1e^{-5}$ and a minimum learning rate $1e^{-6}$ for Llama-3.2-1B and a maximum $5e^{-6}$ and a minimum $1e^{-6}$ for Qwen2.5-7B. To improve the model's robustness and sample them at a predefined rate during training, the batch size is dynamically sampled from a predefined set rather than a fixed number. Specifically, the predefined set for batch size is 8, 16, 32, 64, and 128, and their corresponding sample rates are 0.05, 0.05, 0.05, 0.15, and 0.7. We adopt Deep-Speed (Rajbhandari et al., 2020, 2021; Ren et al., 2021) and Liger Kernel (Hsu et al., 2024) with 8 Nvidia GPUs for distributed training. Overall, the training takes around 11 hours for Llama-3.2-1B and 35 hours for Qwen2.5-7B.

B Experiment details

B.1 Datasets

MQuAKE The dataset MQuAKE (Zhong et al., 2023) (Multi-hop Question Answering for Knowledge Editing) is constructed based on Wikidata and contains question answering instances that require 2-hop, 3-hop, and 4-hop reasoning. In the experiment, we use the latest version of the dataset [7], which fixes the knowledge conflict problem for the old version multi-edit subset, and report the accuracy for each query.

DUNE DUNE (Akyürek et al., 2023) is a benchmark designed for edits in natural language form. It evaluates the model's capability of conducting natural language edits through four aspects: scientific reasoning, arithmetic reasoning, new information, and debiasing. As illustrated in Table 2 of (Akyürek et al., 2023), the arithmetic reasoning edits do not follow natural language form as other subsets do and cannot represent a complete piece of instruction, therefore, we do not include it in our experiment.

WikiData-counterfact The WikiData$_{counterfact}$ (Cohen et al., 2024; Zhang et al., 2024a) collects triplets from top-viewed pages from Wikipedia and contains portability (ripple-effect (Cohen et al.,

---

[7] "MQuAKE-CF-3k-v2.json" in https://github.com/princeton-nlp/MQuAKE

2024)) instances to test whether the output to the input relevant to the edits is changed as well. Specifically, the portability evaluates the post-edited model from three aspects, including logical generalization, subject aliasing, and reasoning.

ZsRE-extended The extended version of ZsRE (Zhang et al., 2024a; Yao et al., 2023) is constructed based on the original ZsRE (Levy et al., 2017), which is a dataset that focuses on the QA task. The extended version introduces a portability test (Yao et al., 2023), including inverse relation, one-hop reasoning, and subject aliasing.

COUNTERFACT COUNTERFACT (Meng et al., 2023) is a dataset that concentrates on counterfactual information, which typically receives a lower prediction score than accurate facts. It constructs out-of-scope data by substituting the subject entity with a comparable description that has the same predicate.

B.2 Evaluation metrics

This section explains the evaluation metrics used in the extended ZsRE(Yao et al., 2023; Zhang et al., 2024a) and Wiki$_{counterfact}$ (Cohen et al., 2024; Zhang et al., 2024a). Generally, they adopt four metrics: reliability, generality, portability, and locality. Given an initial base model f_θ, a post-edit model $f_{\theta'}$, and a set of edit instances $(x_t, y_t) \in \{(x_t, y_t)\}$, the reliability is computed as the average accuracy of the edit cases:

$$\mathbb{E}_{(x_t, y_t) \in \{(x_t, y_t)\}}\{\arg\max_y f_{\theta'}(y|x_t) = y_t\} . \quad (4)$$

The editing should also edit the equivalent neighbor of the instance $(x'_t, y'_t) \in N(x_t, y_t)$ (*e.g.* rephrased descriptions). This metric is named generality and is evaluated by the average accuracy on the neighbors of the edit cases:

$$\mathbb{E}_{(x'_t, y'_t) \in \{N(x_t, y_t)\}}\{\arg\max_y f_{\theta'}(y|x'_t) = y'_t\} . \quad (5)$$

Beyond simple rephrasing, the editing is also supposed to affect other sophisticatedly related instances $(x''_t, y''_t) \in P(x_t, y_t)$. For example, instances that require reasoning, logical generalization over the edits. This metric is defined as portability:

$$\mathbb{E}_{(x''_t, y''_t) \in \{P(x_t, y_t)\}}\{\arg\max_y f_{\theta'}(y|x''_t) = y''_t\} . \quad (6)$$

Despite the editing, those instances that are irrelevant to the edit cases $(\hat{x}_t, \hat{y}_t) \in$

Method	Model	WikiData$_{counterfact}$			ZsRE-extended		
		Edit Success	Portability	Locality	Edit Success	Portability	Locality
Base		21.28 / 21.28	19.73 / 19.73	-	30.06 / 30.06	40.17 / 40.17	-
FT-M		97.02 / 94.58	53.43 / 47.51	49.01 / 20.54	99.81 / 95.94	62.80 / 54.84	75.59 / 59.28
LoRA (Hu et al., 2022)		98.91 / 82.61	52.87 / 43.84	23.31 / 14.94	99.86 / 93.18	57.43 / 44.85	34.94 / 37.41
ROME (Meng et al., 2022)		94.33 / -	40.44 / -	26.13 / -	95.41 / -	46.04 / -	40.19 / -
R-ROME (Gupta et al., 2024a)		94.31 / -	40.65 / -	25.83 / -	95.29 / -	46.46 / -	39.95 / -
MEMIT (Meng et al., 2023)		77.87 / 66.94	46.34 / 23.51	33.45 / 11.12	79.43 / 58.79	43.26 / 25.68	40.33 / 30.10
EMMET (Gupta et al., 2024b)	Llama-3.2-1B	34.56 / 27.02	15.43 / 08.86	100.0 / 100.0	23.68 / 15.96	17.54 / 06.84	100.0 / 100.0
MEND (Mitchell et al., 2022a)		38.45 / 26.66	24.98 / 21.06	17.34 / 13.54	53.45 / 43.33	37.53 / 30.77	46.31 / 38.75
GRACE (Hartvigsen et al., 2022)		33.27 / 25.06	14.33 / 10.51	28.71 / 11.43	32.00 / 24.44	12.73 / 10.91	24.12 / 10.12
KN (Dai et al., 2022)		20.60 / -	17.16 / -	19.46 / -	16.01 / -	06.70 / -	21.23 / -
IKE (Zheng et al., 2023)		61.70 / -	45.55 / -	48.80 / -	59.15 / -	57.39 / -	40.21 / -
SERAC (Mitchell et al., 2022b)		89.56 / 78.32	60.56 / 46.45	45.67 / 39.36	92.69 / 89.61	66.59 / 63.60	48.96 / 41.32
ICL		93.31 / 82.95	65.81 / 44.75	52.70 / 45.59	68.86 / 60.84	62.19 / 51.58	62.78 / 59.43
InComeS		91.16 / 76.81	65.15 / 45.66	55.22 / 53.97	97.22 / 87.09	70.70 / 52.23	61.33 / 59.66
Base		22.35 / 22.35	21.46 / 21.46	-	36.21 / 36.21	43.86 / 43.86	-
FT-M		98.93 / 90.18	49.39 / 43.13	15.73 / 12.93	99.51 / 92.60	50.04 / 46.41	18.00 / 27.27
LoRA (Hu et al., 2022)		77.31 / 72.22	37.04 / 31.65	0.380 / 02.24	86.88 / 77.78	28.61 / 24.13	1.290 / 0.330
ROME (Meng et al., 2022)		92.69 / -	40.25 / -	38.76 / -	97.86 / -	50.43 / -	51.38 / -
R-ROME (Gupta et al., 2024a)		92.59 / -	40.15 / -	38.70 / -	97.89 / -	50.47 / -	51.31 / -
MEMIT (Meng et al., 2023)		93.43 / 91.16	43.58 / 39.85	33.79 / 25.85	95.23 / 93.28	53.23 / 49.97	54.23 / 51.85
EMMET (Gupta et al., 2024b)	Qwen2.5-7B	92.33 / 88.05	43.24 / 39.37	100.0 / 100.0	94.32 / 93.64	51.55 / 48.44	100.0 / 100.0
MEND (Mitchell et al., 2022a)		46.73 / 35.13	20.45 / 15.29	13.34 / 07.29	54.32 / 50.91	43.26 / 38.83	54.39 / 47.12
GRACE (Hartvigsen et al., 2022)		31.34 / 33.77	25.60 / 18.55	19.19 / 07.29	33.27 / 26.79	14.35 / 11.25	12.31 / 23.45
KN (Dai et al., 2022)		36.33 / -	29.60 / -	32.79 / -	14.49 / -	8.49 / -	33.21 / -
IKE (Zheng et al., 2023)		96.40 / -	65.33 / -	46.98 / -	99.75 / -	70.17 / -	43.19 / -
SERAC (Mitchell et al., 2022b)		91.79 / 80.68	51.12 / 41.26	37.84 / 35.10	91.12 / 82.56	62.41 / 52.63	40.56 / 42.46
ICL		90.24 / 85.28	66.99 / 51.66	52.63 / 40.97	71.75 / 71.57	66.10 / 60.57	51.43 / 47.12
InComeS		90.96 / 71.44	66.69 / 47.93	52.04 / 42.02	97.95 / 91.29	75.63 / 61.22	57.16 / 59.21

Table 7: More results for $WikiData_{counterfact}$ (Cohen et al., 2024; Zhang et al., 2024a) and ZsRE-extended (Yao et al., 2023; Zhang et al., 2024a). The data format of each cell is in "single-edit result / 100-edits result".

$\{O(x_t, y_t), f_\theta(x_t) = y_t\}$ should not be affected. This evaluation is called locality (also known as specificity) and is measured by the proportion of unchanged predictions between the initial model and the post-edit model:

$$\mathbb{E}_{(\hat{x_t}, \hat{y_t}) \in \{O(x_t, y_t)\}} \{f_{\theta'}(\hat{x}_t) = f_\theta(\hat{x}_t)\} . \quad (7)$$

For the extended ZsRE (Yao et al., 2023; Zhang et al., 2024a) and Wiki$_{counterfact}$ (Cohen et al., 2024; Zhang et al., 2024a), we follow the setting in the original paper and combine reliability and generality to the Edit Success rate.

B.3 Baseline implementation details

Unless otherwise specified, the baselines are implemented by using the EasyEdit framework (Wang et al., 2023).

Fine-tuning We follow the procedure implemented in previous work (Meng et al., 2022, 2023; Yao et al., 2023; Zhang et al., 2024a) to fine-tune a specific layer from the model. We select layer 13 for Llama-3.2-1B and layer 27 for Qwen2.5-7B. For both models, we adopt the learning rate of $5e^{-4}$ and the number of optimization steps 25.

LoRA For both models, we use LoRA (Hu et al., 2022) to update the query and key projection matrix of the models, with rank set to 8, α set to 32, the dropout rate 0.1, and the learning rate $5e^{-3}$. The number of updating steps is set to 70 for Llama-3.2-1B and 60 for Qwen2.5-7B.

ROME ROME (Meng et al., 2022) treats the FFN part of the LLMs as a key-value association and updates a pre-located layer by directly inserting an optimized key-value pair. We update the layer 5 for both Llama-3.2-1B and Qwen2.5-7B, and adopt 25 optimization steps for Llama-3.2-1B and 20 optimization steps for Qwen2.5-7B, with both learning rate $5e^{-5}$.

R-ROME R-ROME (Gupta et al., 2024a) is another version of ROME (Meng et al., 2022) with modified code implementation. We use the same hyperparameters as ROME.

KN KN (Dai et al., 2022) hypothesize that factual knowledge is stored in FFN memories and expressed by knowledge neurons. For both models, we use the threshold of 0.2 for knowledge attribution scores and 0.4 for the threshold of the prompts sharing percentage.

Method	MQuAKE							
	Single editing				Batch editing			
	2-edits	3-edits	4-edits	Avg	2-edits	3-edits	4-edits	Avg
Llama-3.2-1B								
InComeS	**71.19**	**72.17**	72.62	71.99	53.93	52.79	**52.73**	**53.15**
- w/o zero-gist	62.00	61.93	53.01	58.98	47.48	41.71	32.57	40.59
- w/ full model	69.74	70.02	**77.43**	**72.40**	51.91	52.59	52.53	52.34
- w/o loss on query	60.92	60.97	57.70	59.86	49.63	46.44	38.28	44.78
- w/ golden loss	69.91	69.98	73.37	71.09	**55.39**	50.24	40.06	48.56
- w/o kl loss (Eq. 2)	57.75	57.38	50.18	55.10	52.47	50.86	51.79	51.71
- w/o token weighting (Eq. 1)	57.45	57.84	49.76	55.02	53.49	**53.20**	51.91	52.63

Table 8: Full results of the ablation and analysis experiments.

GRACE GRACE (Hartvigsen et al., 2022) adopts a discrete codebook to memorize the edits as key-value pairs. We set the location of the codebook layer 13 and 18 for Llama-3.2-1B and Qwen2.5-7B, respectively. Surprisingly, the ϵ value used in the original paper (1-3) seems insufficient for the complex editing experiments in this paper. Therefore, we increase it to 50. The number of optimization steps for the value vector is set to 100.

IKE IKE (Zheng et al., 2023) maintains an explicit memory for edits and retrieves them via K-nearest neighbors. The retrieved edits are then used to construct demonstrations, which are then prefixed to the input to edit the behavior. In the experiments, we set $K = 16$.

MEND MEND (Mitchell et al., 2022a) trains an additional meta-network to predict a new rank-one update to the input gradient. In this paper, we train each model using ZsRE (Levy et al., 2017) and COUNTERFACT (Meng et al., 2023), and adopt the ZsRE-trained model to MQuAKE and the extended ZsRE and COUNTERFACT-trained model for Wiki$_{counterfact}$.

SERAC SERAC (Mitchell et al., 2022b) employs an explicit edit-instance memory, an additional trained scope classifier, and a trained counterfactual model. The scope classifier is responsible for determining whether an input is relevant to the edits in the memory. The input is fed to the counterfactual model once the input is deemed as relevant to memorized edits and the original model otherwise. We use the distilbert-base-cased (Sanh et al., 2019) model as the scope classifier, and train it using the training set of ZsRE (Levy et al., 2017) and COUNTERFACT (Meng et al., 2023) from EasyEdit (Wang et al., 2023). Following (Akyürek et al., 2023), we use instruction-tuned models (Llama-3.2-1B-Instruct[8] and Qwen2.5-0.5B[9]) for the counterfactual model.

MEMIT MEMIT (Meng et al., 2023) is the extension of ROME (Meng et al., 2022) that supports a batch of edits at a time. Unlike ROME, which only updates a single pre-located layer, MEMIT spreads the update to a set of identified layers. We apply changes to layers 4-8 for both models. Following the settings in the original paper, we set λ, the hyperparameter that balances the weighting of new and old associations, to 1.5×10^4.

EMMET EMMET (Gupta et al., 2024b) is an unification of ROME (Meng et al., 2022) and MEMIT (Meng et al., 2023). Similar to ROME, we edit the layer 5 for both models, and set $\lambda = 1e^5$.

RAG We adopt bge-base-en-v1.5 (Xiao et al., 2023) as our retriever. For batch editing, we treat the corresponding batch number of edits as our corpus, and retrieve the 10 most relevant edits for each testing query.

InComeS We apply cross-attention operations only for the second half of the model's layers since we found that the gist KV cache from the first half is not informative enough to allow effective edit selection. For the calculation of cross-attention during inference, we adopt a temperature of $T = 0.45$ to the logits before softmax, which is found to be helpful for effective editing.

C Further Analysis

C.1 RAG vs. InComeS

Problem settings InComeS and RAG target different problems. In RAG, the query is given and

---

[8]https://huggingface.co/meta-llama/Llama-3.2-1B-Instruct

[9]https://huggingface.co/Qwen/Qwen2.5-0.5B-Instruct

Method	Single Editing				Batch Editing			
	2-edits	3-edits	4-edits	Avg	2-edits	3-edits	4-edits	Avg
Llama-3.2-1B								
Base	41.79	43.51	31.58	38.96	41.79	43.51	31.58	38.96
FT-M	55.32	56.59	52.22	54.71	51.89	50.15	44.1	48.71
LoRA (Hu et al., 2022)	67.63	68.84	60.21	65.56	50.29	47.88	47.15	48.44
ROME (Meng et al., 2022)	1.97	7.77	0.55	3.43	-	-	-	-
R-ROME (Gupta et al., 2024a)	2.72	4.29	8.53	5.18	-	-	-	-
MEMIT (Meng et al., 2023)	40.21	39.54	22.34	34.03	29.71	28.87	15.7	24.76
EMMET (Gupta et al., 2024b)	5.4	6.61	4.74	5.58	11.49	17.16	15.89	14.85
GRACE (Hartvigsen et al., 2022)	8.45	7.13	5.24	6.94	2.03	2.68	2.06	2.26
SERAC (Mitchell et al., 2022b)	41.84	43.51	31.58	38.97	41.84	43.45	31.74	39.01
MEND (Mitchell et al., 2022a)	39.88	35.23	33.31	36.41	35.55	30.29	29.89	31.91
RECIPE (Chen et al., 2024)	58.44	54.69	53.33	55.49	50.71	47.34	39.39	45.81
MeLLo (Zhong et al., 2023)	55.21	54.19	49.87	53.09	43.33	47.22	41.76	44.10
MELO (Yu et al., 2024)	44.55	43.99	32.44	40.33	43.33	47.22	33.87	41.47
ATBIAS (Bi et al., 2024)	60.35	61.11	59.46	60.31	52.41	51.77	47.86	50.68
DR-IKE (Nafee et al., 2025)	52.95	48.26	47.12	49.44	42.45	41.33	32.22	38.67
AlphaEdit (Fang et al., 2025)	57.76	48.16	49.87	51.93	45.32	41.29	39.32	41.98
ICE (Qi et al., 2025)	55.34	53.23	49.86	52.81	46.56	45.26	44.33	45.38
ICL	59.23	59.00	51.63	56.62	50.06	49.86	42.37	47.43
InComeS	**71.19**	**72.17**	**72.62**	**71.99**	**53.93**	**52.79**	**52.73**	**53.15**
Qwen2.5-7B								
Base	44.08	44.14	30.62	39.61	44.08	44.14	30.62	39.61
FT-M	69.89	74.88	74.96	73.24	50.31	49.04	50.39	49.91
LoRA (Hu et al., 2022)	36.95	34.28	29.02	33.42	16.41	24.22	23.12	21.25
ROME (Meng et al., 2022)	9.67	7.33	8.93	8.64	-	-	-	-
R-ROME (Gupta et al., 2024a)	10.73	6.68	3.62	7.01	-	-	-	-
MEMIT (Meng et al., 2023)	44.14	46.05	32.15	40.78	43.94	46.10	30.55	40.20
EMMET (Gupta et al., 2024b)	26.10	38.38	26.36	30.28	40.83	45.02	33.89	39.91
GRACE (Hartvigsen et al., 2022)	15.78	13.45	13.23	14.15	5.43	7.88	4.23	5.85
SERAC (Mitchell et al., 2022b)	55.56	59.23	53.67	56.15	42.34	40.33	39.39	40.69
MEND (Mitchell et al., 2022a)	34.23	45.34	30.25	36.61	39.88	35.45	34.21	36.51
RECIPE (Chen et al., 2024)	57.54	59.69	58.43	58.55	49.24	49.78	40.71	46.58
MeLLo (Zhong et al., 2023)	59.34	56.41	50.74	55.50	50.85	47.32	43.85	47.34
MELO (Yu et al., 2024)	45.22	45.99	30.27	40.49	46.87	45.33	34.39	42.20
ATBIAS (Bi et al., 2024)	59.85	54.21	57.46	51.17	48.44	41.99	44.58	45.00
DR-IKE (Nafee et al., 2025)	60.95	54.66	51.22	55.61	44.35	39.99	39.77	41.37
AlphaEdit (Fang et al., 2025)	57.38	52.76	50.99	53.71	56.77	49.99	44.32	50.36
ICE (Qi et al., 2025)	63.23	67.76	70.91	67.30	51.33	47.86	48.33	49.17
ICL	**69.76**	**76.91**	74.54	**73.74**	53.53	50.54	44.77	49.61
InComeS	66.46	71.24	**76.54**	71.41	**55.13**	**53.48**	**47.91**	**52.17**

Table 9: Full results on MQuAKE (Zhong et al., 2023).

used to retrieve the relevant documents via a retrieval model before decoding. However, InComeS does not make such an assumption, and it "edits" the model with the provided knowledge before seeing any actual queries.

Methodology From the perspective of methodology, InComeS conducts selection mechanisms in a way that is better integrated into the LM and with a finer granularity compared to RAG methods. First, RAG inputs the full query for retrieval to select relevant documents, and this process needs an extra retrieval model; in contrast, our method requires no extra models or retrieval steps and directly integrates the selection mechanism into our base LM.

Moreover, our method dynamically performs selection for each token individually, which has a much finer granularity than the query-based selection in RAG. This supports a wider range of applications.

Experiments on Multi-hop edits Despite the differences between our method and RAG, we compare our method with RAG to demonstrate our method's superiority over the complex editing scenarios (Table 12). InComeS outperforms RAG in almost all cases for both single editing and batch editing. Note that the result of RAG is the same as the result of ICL in single editing, which does not need retrieval. We also conduct a scaling experiment to verify the effectiveness of InComeS over

Method	Single Editing				Batch Editing			
	New info	Scientific R.	Debiasing	Avg	New info	Scientific R.	Debiasing	Avg
Llama-3.2-1B								
Base	56.85	55.87	32.73	48.48	56.85	55.87	32.73	48.48
FT-M	57.43	53.34	35.73	48.83	57.07	53.45	33.43	47.89
LoRA (Hu et al., 2022)	53.65	50.87	36.73	47.08	56.77	54.66	35.83	49.08
SERAC (Mitchell et al., 2022b)	52.67	48.96	46.73	49.45	50.76	47.32	36.52	44.87
ICE (Qi et al., 2025)	54.52	51.32	39.64	48.49	56.32	53.44	36.52	48.76
ICL	58.67	55.84	**56.65**	57.05	56.94	55.68	39.46	50.69
InComeS	**60.00**	**58.17**	54.61	**57.59**	**57.76**	**56.46**	**46.14**	**53.45**
Qwen2.5-7B								
Base	63.44	66.03	36.95	55.47	63.44	66.03	36.95	55.47
FT-M	64.83	67.77	48.73	60.44	64.27	64.56	41.51	56.78
LoRA (Hu et al., 2022)	63.85	63.22	39.56	55.54	62.58	65.33	43.73	57.21
SERAC (Mitchell et al., 2022b)	64.45	63.57	33.38	53.80	56.78	58.97	31.24	48.99
ICE (Qi et al., 2025)	63.88	62.26	39.77	55.30	53.56	48.55	37.86	46.66
ICL	65.81	65.34	35.25	55.47	**66.29**	66.24	40.73	57.75
InComeS	**66.83**	**68.02**	**62.59**	**65.81**	65.61	**67.82**	**56.69**	**63.37**

Table 10: Full results on DUNE (Akyürek et al., 2023).

Method	MquAKE
Llama-3.2-1B	
InComeS - $12k$	**49.55**
RAG - $12k$	41.34
InComeS - $60k$	**45.63**
RAG - $60k$	39.29
InComeS - $120k$	**40.38**
RAG - $120k$	37.98
Qwen2.5-7B	
InComeS - $12k$	**49.37**
RAG - $12k$	43.27
InComeS - $60k$	**44.12**
RAG - $60k$	41.41
InComeS - $120k$	**42.29**
RAG - $120k$	39.86

Table 11: Scaling experiments for InComeS and RAG.

RAG in long context or massive edits scenario. The results (Table 11) show that the InComeS consistently outperforms RAG in different context lengths (number of edits).

Implicit retrieval vs. Explicit retrieval Some may claim that the explicitness of the retrieval process in RAG is an advantage over InComeS. We argue that it is not hard to transfer the implicit retrieval process of InComeS to an explicit one. As the setting of our method strictly follows one edit - one gist (Figure 1), the mapping between the text and its gist representations would not be hard to build.

C.2 Side effect

We present a side effect analysis of our method in this section (Table 13). We test the editing side effect under three different numbers of edits ($0k$, $0.1k$, $1k$) on MMLU (Hendrycks et al., 2021) benchmark, which consists of 57 tasks across 4 domains, namely Social science, Humanities, STEM, and others. The results indicate that increasing the number of edits does not significantly harm the model's general capability (lines 3 - 5 and 7 - 9 in Table 13), demonstrating the potential scalability of our method. The continuous pre-training brings an inevitable modest side effect to the model (lines 2 - 3 and 6- 7 in Table 13).

C.3 Efficiency analysis

Compared to many traditional editing methods that require model backward calculation, our method only requires one single forward pass for each editing context. In comparison to ICL, which needs to encode the entire concatenated edit context, our approach enables parallel encoding of multiple edits, leading to great efficiency gains for the encoding (prefilling) stage. In addition, the compressed context also accelerates the decoding phase compared to the ICL decoding with prefilled KV cache. Here, we provide an analysis of our method's efficiency advantage over traditional ICL for both the encoding and decoding stages.

Encoding Assume we have N edits and each edit has a Length of L. For ICL prefilling, it has to encode the whole sequence with length $N \times$

Method	Model	Single Editing				Batch Editing			
		2-edits	3-edits	4-edits	Avg	2-edits	3-edits	4-edits	Avg
Base	Llama-3.2-1B	41.79	43.51	31.58	38.96	41.79	43.51	31.58	38.96
RAG		59.23	59.00	51.63	56.62	40.65	46.78	43.58	43.67
ICL		59.23	59.00	51.63	56.62	50.06	49.86	42.37	47.43
InComeS		**71.19**	**72.17**	**72.62**	**71.99**	**53.93**	**52.79**	**52.73**	**53.15**
Base	Qwen2.5-7B	44.08	44.14	30.62	39.61	44.08	44.14	30.62	39.61
RAG		69.76	76.91	74.54	73.74	42.91	46.37	46.15	45.14
ICL		**69.76**	**76.91**	74.54	**73.74**	53.53	50.54	44.77	49.61
InComeS		66.46	71.24	**76.54**	71.41	**55.13**	**53.48**	**47.91**	**52.17**
Base	Qwen3-8B-base	43.49	41.01	26.32	36.94	43.49	41.01	26.32	36.94
RAG		55.82	54.13	47.06	52.34	45.98	46.52	46.67	46.39
ICL		55.82	54.13	47.06	52.34	50.78	48.84	45.28	48.30
InComeS		**56.36**	**58.71**	**59.93**	**58.33**	**53.42**	**50.90**	**50.36**	**51.56**

Table 12: Results for RAG on MQuAKE (Zhong et al., 2023).

Method	Model	Social Sciences	Humanities	STEM	Other	Average
Base	Llama-3.2-1B	25.09	27.31	25.87	27.49	26.44
InComeS - w/ no edits		23.18	25.91	22.66	26.06	24.45
InComeS - w/ $0.1k$ edits		22.45	25.01	22.66	24.62	23.68
InComeS - w/ $1k$ edits		22.91	25.30	22.73	24.11	23.76
Base	Qwen2.5-7B	72.72	69.19	63.42	69.72	68.76
InComeS - w/ no edits		68.06	65.68	59.58	66.39	64.93
InComeS - w/ $0.1k$ edits		64.64	60.65	56.84	63.39	61.38
InComeS - w/ $1k$ edits		63.86	62.08	57.58	62.88	61.60

Table 13: Side effect evaluation on MMLU (Hendrycks et al., 2021).

L. However, for InComeS, each edit is processed individually, and it encodes edits in parallel. In this case, it encodes a batch of N edits with length L. Thanks for the highly optimized GPU parallel computation, such a feature approximately reduces the time consumption by N times.

Decoding Suppose we have N compressed gists, which corresponds to N individual edits with length L and $N \times L$ tokens whose KV caches have been prefilled. For each decoding position, the ICL self-attention needs to compute a matrix with size $1 \times N \times L$. However, InComeS only needs to calculate the gist cross-attention matrix with size $1 \times N$. This roughly accelerates the decoding by L times.

C.4 Applying loss on queries

By convention, instruction tuning only takes into account the loss for labels, excluding queries (Fig. 2). In this section, we show that merely applying a loss on labels is not enough in our case. We train a model without the loss of queries and present its results in the Table 6 (the line of "w/o loss on query"). The absence of query loss results in a sharp decrease for multi-hop editing, suggesting that training on query tokens may improve the

model's capability of combining information retrieval and reasoning.

C.5 Inclusion of zero gist

The motivation for including the zero-gist mechanism is to ensure that context-independent tokens can bypass the influence of the edit contexts. To assess the impact of zero-gist, we train a model without this mechanism and evaluate it on MQuAKE (Zhong et al., 2023) (see the "w/o zero-gist" line in Table 6). The results show a notable performance drop, suggesting that the cross-attention calculations may sometimes interfere with ordinary generation and our zero-gist strategy can mitigate this issue by allowing tokens to "attend to nothing".

C.6 Information flow on tokens

We further investigate the cross-attention patterns to understand how the model performs context selection. We measure the zero-gist and golden-gist probability (Figure 4c), and cross-attention entropy (Figure 4d) of each token from two representative examples containing a correctly ("success") and a wrongly ("fail") predicted instance using Llama-3.2-1B. As expected, the golden gist probability

from the correctly predicted instance generally exceeds that of the failed one ("Golden prob - success" and "Golden prob - fail" line in Figure 4c). Notably, for all cases, the token at position zero allocates low probabilities to both golden and zero gists, while having high entropy, indicating that the model is "taking the average" of all gist representations at this beginning token. The dominance of zero-gist in later positions demonstrates that the model learns to "adaptively attend to edit information."

C.7 Necessity of distillation

We verify the importance of the distillation loss in this section. The result (see line "w/o kl loss" and "w/o token weighting" in Table 6) shows a significant decrease when excluding any of the distillation components, indicating that the distillation plays an important role.

C.8 Edit success & Locality

As expected, Table 7 shows traditional editing methods such as fine-tuning and ROME exhibit high edit success rates; however, their portability scores generally lag behind the top-performing methods, highlighting a common limitation of these approaches. In contrast, ICL-based approaches that leverage the in-context learning capabilities of LLMs demonstrate superior performance in complex editing scenarios that require reasoning, owing to the enhanced context understanding of LLMs. We argue that the edit success metric may not be a comprehensive metric to evaluate the real capability of the post-edited model, as it can be cheated by the overfitting problem (Zhang et al., 2025), i.e., the model can assign disproportionately high probabilities to the edit target to get a high edit success rate. This may explain why the simple fine-tuning method shows an extremely high edit success rate but fails to maintain it on the porability. Therefore, we focus on complex settings, including multi-hop editing, natural language editing, and portability that aligns more with the real application scenarios. Our method demonstrates excellent performance in these settings, which aligns with our motivations described in section 1.

Our method shows great locality gain compared to ICL, which aligns with the results in the side effect analysis (Appendix C.2). This results from the inclusion of the zero gist, which flexibly allows the token to ignore the gist information if none of them is deemed relevant.

Method	COUNTERFACT	
	Reliability	Generality
$1k$ (Length around $12k$)		
- ICL	42.38	11.83
- InComeS	**75.82**	**23.44**
$5k$ (Length around $60k$)		
- ICL	37.85	10.88
- InComeS	**69.96**	**20.98**
$10k$ (Length around $120k$)		
- ICL	35.55	09.76
- InComeS	**60.76**	**16.77**

Table 14: Further scales up contexts.

C.9 Effectiveness of the method over model scale

We observe that the performance gain in Table 1 appears to diminish as the model scale increases. In this section, we conduct further experiments to find out whether this is true. The results in Table 18 show that the performance gain does not decrease when the model scale increases.

C.10 Further scaling up contexts

Although the performance gap between ICL and InComeS is already noticeable under $1k$ edits (section 4.2), we conduct further experiments on Llama-3.2-1B to verify the effectiveness of InComeS under $10k$ edits, which is around $120k$ in context length. The results are shown in Table 14. InComeS shows consistent superiority over ICL.

C.11 Analysis on cross-attention layers

InComeS applies the cross attention only on the deeper half of the layers. Despite the relatively low zero-gist probability shown in Figure 4b theoretically proves the necessity of the deeper half layers, we still conduct further analysis to verify their effectiveness (Table 17). The results show that each increase in the number of layers generally leads to a growth in the performance. This demonstrates the necessity of applying the whole deeper half layers.

C.12 Memory bound quantification

During the inference stage, the additional memory introduced by InComeS is the storage of the KV cache of the gist representations. Take the Llama-3.2-1B as an example, if we have $1k$ edits, the memory required (in float16) for a single layer is $2 \times 2048 \times 1000 = 3.91MB$. Because the inference process is conducted sequentially, we can load

Method	Single Edit	Batch Edit
Llama-3.2-1B		
FT-M	45.22	38.96
LoRA (Hu et al., 2022)	54.23	40.84
ROME (Meng et al., 2022)	3.43	-
MEMIT (Meng et al., 2023)	28.23	20.84
MEND (Mitchell et al., 2022a)	27.95	23.99
RECIPE (Chen et al., 2024)	48.45	39.74
ATBIAS (Bi et al., 2024)	51.33	38.73
DR-IKE (Nafee et al., 2025)	35.49	31.73
AlphaEdit (Fang et al., 2025)	44.74	35.63
ICE (Qi et al., 2025)	40.74	31.23
ICL	48.22	42.38
InComeS	**62.74**	**47.98**
Qwen2.5-7B		
FT-M	**61.44**	37.88
LoRA (Hu et al., 2022)	28.22	18.77
ROME (Meng et al., 2022)	5.44	-
MEMIT (Meng et al., 2023)	30.99	27.12
MEND (Mitchell et al., 2022a)	29.86	24.77
RECIPE (Chen et al., 2024)	50.74	39.51
ATBIAS (Bi et al., 2024)	41.11	37.00
DR-IKE (Nafee et al., 2025)	44.14	33.13
AlphaEdit (Fang et al., 2025)	48.21	39.49
ICE (Qi et al., 2025)	55.97	38.11
ICL	60.78	37.63
InComeS	61.42	**42.29**

Table 15: Results on MQuAKE (Zhong et al., 2023) for wild evaluation framework (Yang et al., 2025a).

Method	ZsRE-extended	Wikidata$_{counterfact}$
Llama-3.2-1B		
FT-M	80.99 / 78.41	48.71
LoRA (Hu et al., 2022)	81.22 / 77.64	78.23 / 71.39
ROME (Meng et al., 2022)	72.97 / -	75.88 / -
MEMIT (Meng et al., 2023)	70.33 / 53.41	67.43 / 53.27
MEND (Mitchell et al., 2022a)	31.26 / 29.34	27.66 / 21.78
ICL	66.74 / 55.73	84.39 / 68.88
InComeS	**85.21 / 78.88**	**85.31 / 70.84**
Qwen2.5-7B		
FT-M	78.99 / 74.41	88.23 / 79.41
LoRA (Hu et al., 2022)	76.45 / 62.37	66.41 / 57.29
ROME (Meng et al., 2022)	78.37 / -	79.41 / -
MEMIT (Meng et al., 2023)	74.31 / 63.21	80.36 / 78.31
MEND (Mitchell et al., 2022a)	35.18 / 25.32	39.75 / 26.77
ICL	67.88 / 58.76	81.45 / 70.57
InComeS	88.34 / 80.41	**82.36 / 71.43**

Table 16: Results on ZsRE-extended and Wikidata$_{counterfact}$ for wild evaluation framework (Yang et al., 2025a).

one layer KV cache at a time. Therefore, 3.91MB is the extra memory required for inference. For the whole storage, since InComeS only use deeper half layers, the memory is $3.91 \times 8 = 31.28MB$. If the edit number goes considerably high, techniques like top-k can be easily applied to our method.

C.13 Meta training cost analysis

The meta-training cost is smaller than a simple SFT these days. Take Olmo-3-7B-Instruct-SFT as an example; the data[10] used for fine-tuning this model has at least 4B tokens, which is far larger than our meta-training cost (1.5B tokens). Given that the fine-tuning is a very common stage employed by almost all models nowadays, we believe such cost is not a considerable barrier for practical deployment.

Furthermore, compared to some tranditional light-weight editing method like MEMIT (Meng et al., 2023):

- InComeS has better performance in almost all scenarios reported in the paper.

- InComeS has better flexibility and supports the edits in any **natural language form**, while

MEMIT-like optimization requires the edits follow a **triplet-like structure**, which is unrealistic for deployment.

- InComeS requires meta-training for different base models, but MEMIT (Meng et al., 2023) also needs to compute the covariance matrix before editing for different models.

Compared to ICL:

- InComeS has better performance in almost all scenarios reported in the paper.

- InComeS requires an additional meta-training, but acquires a significant speedup for future inference (Table 5). We believe this is a great gain for future practical deployment.

C.14 More results

To further verify the effectiveness of our method over the recent model, we further test our method on Qwen3-8B-base. The results (Table 20 and Table 19) demonstrate that our method works well in recent models. We also perform an evaluation using the WILD framework (Yang et al., 2025a), the results are shown in Tables 15 and 16.

C.15 More related work

Unlike discrete prompts, soft prompts are learnable continuous vectors that are prepended to the input embedding sequence, enabling task-specific adaptation without modifying model weights. Prefix tuning (Li and Liang, 2021) and prompt tuning

---

[10]https://huggingface.co/datasets/allenai/Dolci-Instruct-SFT

Layers	Model	Single Editing				Batch Editing			
		2-edits	3-edits	4-edits	Avg	2-edits	3-edits	4-edits	Avg
Base		44.08	44.14	30.62	39.61	44.08	44.14	30.62	39.61
28		45.57	46.48	32.23	41.43	43.12	42.31	32.87	39.43
24-28	Qwen2.5-7B	55.12	62.74	61.13	59.66	49.45	44.32	39.86	44.54
20-28		55.96	61.95	63.23	60.38	50.35	45.63	40.33	45.46
17-28		62.87	68.95	69.64	67.15	53.26	51.38	45.77	50.14
14-28 (InComeS)		**66.46**	**71.24**	**76.54**	**71.41**	**55.13**	**53.48**	**47.91**	**52.17**

Table 17: Analysis on the effectiveness of the deeper half layers.

Method	Model	Single Editing				Batch Editing			
		2-edits	3-edits	4-edits	Avg	2-edits	3-edits	4-edits	Avg
Base		41.79	43.51	31.58	38.96	41.79	43.51	31.58	38.96
ICL	Llama-3.2-1B	59.23	59.00	51.63	56.62	50.06	49.86	42.37	47.73
InComeS		**71.19**	**72.17**	**72.62**	**71.99**	**53.93**	**52.79**	**52.73**	**53.15**
Base		45.29	45.69	31.66	40.88	45.29	45.69	31.66	40.88
ICL	Llama-3.1-8B	58.76	56.99	45.47	53.74	48.64	49.58	39.51	45.91
InComeS		**74.39**	**78.25**	**75.24**	**75.96**	**56.28**	**56.55**	**51.90**	**54.91**

Table 18: Results for different model scale (Zhong et al., 2023).

(Lester et al., 2021) insert trainable prefix activations or prompt embeddings into the input, achieving competitive performance with full fine-tuning while updating orders of magnitude fewer parameters. P-tuning (Liu et al., 2024) further incorporates prompt encoders to model interdependencies among prompt tokens. These foundational works have inspired a wide range of subsequent innovations.

Recent advances focus on improving the efficiency and expressiveness of soft prompting. ADePT (Tang et al., 2025) decomposes the soft prompt into a shorter prompt and a token-shared feed-forward network, enabling adaptive embedding offsets that vary according to model input, consistently outperforming prior methods across 23 NLP tasks. CE-Prompt (Yang et al., 2025b) introduces composite embeddings via multiple randomly initialized embedding layers, enhancing prompt expression stability and significantly reducing inference computational costs. Muppidi et al. (2025) propose Input-Dependent Soft Prompting with a self-Attention Mechanism (ID-SPAM), which generates soft prompts dynamically based on input tokens, demonstrating improved zero-shot domain transfer capability. Position also plays a critical role: Yang et al. (2025c) provides a theoretical analysis showing that optimizing the prompt's position to surround the input can capture additional semantic information beyond traditional prefix or postfix methods.

Method	Model	Single Editing				Batch Editing			
		2-edits	3-edits	4-edits	Avg	2-edits	3-edits	4-edits	Avg
Base		43.49	41.01	26.32	36.94	43.49	41.01	26.32	36.94
FT-M		51.32	50.39	45.22	48.98	48.11	44.24	41.39	44.58
LoRA (Hu et al., 2022)	Qwen3-8B-base	38.95	36.27	33.02	36.08	24.41	21.24	22.12	22.59
MEMIT (Meng et al., 2023)		49.14	46.05	41.15	45.45	42.34	40.10	33.45	38.63
ICL		55.82	54.13	47.06	52.34	50.78	48.84	45.28	48.30
InComeS		**56.36**	**58.71**	**59.93**	**58.33**	**53.42**	**50.90**	**50.36**	**51.56**

Table 19: More results on mquake (Zhong et al., 2023).

Method	Model	Single Editing				Batch Editing			
		new info	scientific	de-biasing	Avg	new info	scientific	de-biasing	Avg
Base		82.99	86.62	31.07	66.89	82.99	86.62	31.07	66.89
FT-M		78.23	75.44	56.38	70.02	76.33	72.34	54.28	67.65
LoRA (Hu et al., 2022)	Qwen3-8B-base	71.23	69.99	43.23	61.48	73.13	64.59	42.22	59.98
MEMIT (Meng et al., 2023)		81.29	80.45	49.65	70.46	80.99	78.53	45.66	68.39
ICL		83.06	81.12	45.45	69.88	83.35	82.76	30.34	65.48
InComeS		**83.17**	**85.36**	**63.96**	**77.41**	**84.17**	**87.57**	**65.96**	**79.23**

Table 20: More results on dune (Akyürek et al., 2023).