Learning from the Right Mistakes: When Do Low-Performing Data Help Offline Policy Gradients?

Jesse Silverberg [1 2]   **Marc G. Bellemare** [1 3 4]   **Glen Berseth** [1 2 4]

Abstract

Imitation learning approaches currently reign supreme for robotic manipulation, while value-based offline reinforcement learning (RL) approaches have not yet proven successful at scaling to state-of-the-art large models. As a result, most robotics training pipelines will filter out low-performing data or include them in supervised training objectives. Motivated by recent successes in post-training for large language models, we investigate the viability of policy gradient algorithms with importance sampling as a method of learning from subpar data. We find that critic-free policy gradient approaches can suffer from problematic gradient interference depending on the structure of the data. We isolate and demonstrate the harmful impacts of such interference, and connect this phenomenon to common dataset construction procedures for simulated and real-world robot learning. Our results point to the importance of considering the interplay between dataset composition and offline RL algorithm design.

1. Introduction

Robotics capabilities have improved massively in the last year due to advances from scaling up imitation learning (Fang et al., 2026; Team et al., 2025). The primary cost of such methods is that they require high-quality data that is scarcely available, often requiring expensive teleoperation setups, highly skilled operators, and significant human time investment. When collecting teleoperation data, human operators improve over time at consistently providing high-quality demonstrations. It is sensible that initial failures or mistakes made by the human operators could

be helpful to the agent, but current state-of-the-art training pipelines will simply filter out low-performing data (Chen et al., 2026) or incorporate it through "RL via Supervised Learning" approaches (Emmons et al., 2022; Intelligence et al., 2026).

Both aforementioned approaches are unsatisfying: discarding data is wasteful, and RL via Supervised Learning methods have known limitations, for example, learning in stochastic environments (Brandfonbrener et al., 2022). We study incorporating low-performing data with binary rewards, operating within the framework of offline RL (Lange et al., 2012; Levine et al., 2020), as online RL methods are sample-inefficient and costly to instrument in real-world settings (Chen et al., 2025; Li et al., 2026). Specifically, we choose to use policy gradient methods, both due to their stability and recent success when applied to large language models (Devvrit et al., 2026; MiniMax et al., 2025) and because learning accurate value functions is often difficult in practice (Li et al., 2023; Nauman et al., 2024; Kumar et al., 2020).

We find that depending on the shared structure between low-performing and high-performing demonstrations, such policy gradient methods can run into a problematic *interference* (McCloskey & Cohen, 1989) that can limit the benefits of using the additional subpar data, and, in some cases, can even hurt learning compared to just ignoring the subpar data altogether.

2. Preliminaries

We consider the standard offline RL setting (Levine et al., 2020) in which we have a Markov Decision Process (Puterman, 2014) with states $x \in \mathcal{X}$, actions $a \in \mathcal{A}$, and transition dynamics $\mathcal{P} : \mathcal{X} \times \mathcal{A} \to \Delta(\mathcal{X})$. For simplicity, we assume that each trajectory $\tau = (x_0, a_0, x_1, \ldots, x_T)$ is assigned a binary scalar reward $R(\tau) \in \{1, -1\}$ corresponding to success or failure. Given an offline dataset $\mathcal{D} = \{\tau_i\}_{i=1}^{N}$, the goal is to learn a policy $\pi : \mathcal{X} \to \Delta(\mathcal{A})$ that maximizes the expected reward: $J(\pi) = \mathbb{E}_{\tau \sim \pi}[R(\tau)]$.

We choose Tapered Off-Policy REINFORCE (TOPR; Le Roux et al. (2025)) as a prototypical policy gradient algorithm that can stably incorporate off-policy data. With

[1]Mila – Québec AI Institute [2]Université de Montréal [3]McGill University [4]CIFAR AI Chair. Correspondence to: Jesse Silverberg <jesse.silverberg@mila.quebec>.

Accepted at ICML 2026 Workshop on Decision-Making from Offline Datasets to Online Adaptation: Black-Box Optimization to Reinforcement Learning. Copyright 2026 by the authors.

Figure 1. Left: Illustration of the *shared prefix* structure in `can-paired`. All trajectories successfully grasp the can, after which half of the rollouts place the can in the proper bin (**successful** trajectories) while the other half drop the can off of the table (**failed** trajectories). **Right:** Cosine similarity of ∇J^+ and ∇J^- on `can-paired`. ∇J^+ and $\nabla J^-_{\mathcal{M}^{\text{pre}}}$ point in nearly opposite directions near the beginning of training, while $\nabla J^-_{\mathcal{M}^{\text{post}}}$ does not interfere much with ∇J^+.

binary rewards, TOPR uses the asymmetric policy gradient

$$\nabla J(\pi) = \underbrace{\mathbb{E}_{\tau \sim \mathcal{D}^+} \left[\nabla \log \pi(\tau) \right]}_{\nabla J^+}$$
$$\underbrace{- \mathbb{E}_{\tau \sim \mathcal{D}^-} \left[[\rho(\tau)]_0^1 \nabla \log \pi(\tau) \right]}_{\nabla J^-}, \quad (1)$$

where $\mathcal{D}^+ = \{\tau \in \mathcal{D} : R(\tau) = 1\}$ is the set of successful trajectories, $\mathcal{D}^-$ is symmetrically defined as the set of failed trajectories, and $[x]_0^1 := \max(0, \min(1, x))$ clips the trajectory-level importance ratios $\rho(\tau)$:

$$\rho(\tau) = \prod_{t=0}^{T-1} \frac{\pi(a_t \mid x_t)}{\pi_{\text{ref}}(a_t \mid x_t)}.$$

This clipping helps to avoid the high variance of the product of many per-timestep importance ratios (Precup et al., 2000). The reference policy is frozen and initialized at the beginning of training as $\pi_{\text{ref}} \leftarrow \pi$. Le Roux et al. (2025) construct $\mathcal{D}$ by collecting on-policy rollouts from π; in their case, the reference policy π_{ref} also functions as the data-generating policy. In general, these may not be the same, as it may not even be possible to access the data-generating policy beyond the collected trajectories (e.g., if $\mathcal{D}$ is human-generated). We make no assumptions about the data-generating policy, meaning that the importance ratios in (1) are no longer providing an exact off-policy correction, but still function to downweight off-policy negative trajectories in order to prevent divergence.

The decomposition of the TOPR objective (1) into ∇J^+ and ∇J^- is illustrative: ∇J^+ corresponds to performing behavior cloning (BC; Pomerleau (1988)) on the successful trajectories and ∇J^- corresponds to truncated importance

sampling (Munos et al., 2016; Espeholt et al., 2018) for the failed trajectories. A natural baseline approach is to only train with the term ∇J^+, which we will refer to as *filtered behavior cloning* (FBC; Chen et al. (2021)).

3. Can Failed Trajectories Interfere?

We seek to understand the conditions under which low-performing offline data can be helpful. To this end, we will highlight that the shared structure between the "positive" and "negative" data is of central importance, and in some cases can lead to harmful interference (McCloskey & Cohen, 1989) effects. To illustrate these phenomena, we study the `can-paired` environment from the `robomimic` task suite (Mandlekar et al., 2021). `can-paired` consists of paired human teleoperation demonstrations collected from the same initial state: for each initial state, one trajectory will successfully complete the task of picking up the can and placing it in the correct receptacle. The other trajectory from that initial state will pick up the can and drop it off of the edge of the table (Fig. 1, left). Importantly, the failed trajectories exhibit proper grasping behavior (i.e., the pre-grasp portions of all trajectories are approximately identically distributed). We will refer to this property as the data possessing a *shared prefix* structure; the failed trajectories begin with behavior resembling that of the successful demonstrations.

The potential trouble with such shared prefix structure is that there is a portion of the trajectories in $\mathcal{D}^+$ and $\mathcal{D}^-$ for which ∇J^+ is trying to maximize the likelihood while ∇J^- is trying to minimize the likelihood of data coming from that same distribution. To be more precise, consider binary masks of the form $\mathcal{M}^\tau \in [0, 1]^T$ to identify sub-

Figure 2. TOPR and FBC generally perform comparably, at least when comparing the best success rates achieved by each. However, TOPR is notably slower to learn than FBC on some datasets. Shaded areas represent standard error across 5 seeds; each evaluation records 100 episodes.

sets of timesteps, with $\mathcal{M}_i^{\mathrm{pre}} = \mathbb{1}_{\{i < T_g\}}$ indicating the timesteps before the grasp time T_g and $\mathcal{M}_i^{\mathrm{post}} = \mathbb{1}_{\{i \geq T_g\}}$ indicating the post-grasp timesteps. These masks let us reason about ∇J^- when restricted to specific subsegments:

$$\nabla J_{\mathcal{M}}^- = -\mathbb{E}_{\tau \sim \mathcal{D}^-}\left[[\rho(\tau)]_0^1 \sum_{t=0}^{T-1} \mathcal{M}_t \nabla \log \pi(a_t | x_t) \right],$$

with $\mathcal{M} \in \{\mathcal{M}^{\mathrm{pre}}, \mathcal{M}^{\mathrm{post}}\}$. In this notation, we can hypothesize that shared prefix structure will lead to gradient interference, manifested in the form of a large negative cosine similarity between the gradient terms: $\cos(\nabla J^+, \nabla J^-) = \frac{\langle \nabla J^+, \nabla J^- \rangle}{\|\nabla J^+\| \|\nabla J^-\|}$. Specifically, we expect $\cos(\nabla J^+, \nabla J_{\mathcal{M}^{\mathrm{pre}}}^-)$ to be smaller than $\cos(\nabla J^+, \nabla J_{\mathcal{M}^{\mathrm{post}}}^-)$, as ∇J^+ and $\nabla J_{\mathcal{M}^{\mathrm{pre}}}^-$ are opposing objectives on similar data. Such interference phenomena are commonplace in the multi-task learning literature (Yu et al., 2020; Liu et al., 2021).

4. Experiments

To illustrate gradient interference behavior and demonstrate the impact of the shared prefix structure, we conduct the following training-time intervention: train two policies on `can-paired` with TOPR, with one run using $\nabla J_{\mathcal{M}^{\mathrm{pre}}}^-$ to only include timesteps occurring *before* the grasp has been made ("TOPR (pre-grasp)") while the other uses $\nabla J_{\mathcal{M}^{\mathrm{post}}}^-$ for timesteps occurring *after* the grasp ("TOPR

(post-grasp)"). Both policies always use the full positive gradient term ∇J^+. Experimental details and extended results can be found in Appendix A and Appendix B. In Fig. 1 (right), we see that $\nabla J_{\mathcal{M}^{\mathrm{pre}}}^-$ interferes significantly with ∇J^+. Conversely, $\nabla J_{\mathcal{M}^{\mathrm{post}}}^-$ and ∇J^+ hardly interfere at all in comparison. The interference decreases over the course of training as π moves away from π_{ref} and the importance ratios in ∇J^- decrease (Fig. 1, right), and ultimately TOPR marginally outperforms FBC on this dataset (Fig. 2).

To expand on this self-correcting mechanism, recall that the importance ratios $\rho(\tau)$ are computed over the entire trajectory. While the conflicting signal on the shared prefix may prevent the policy from decreasing the likelihood of actions in that shared prefix, there is nothing preventing the policy from decreasing the likelihood of the later actions in the trajectory. Because those timesteps contribute to the trajectory-level ratios $\rho(\tau)$, the weight of ∇J^- is reduced. Even though `can-paired` is constructed with such a clear avenue for interference, the interference disappears quickly and doesn't hurt learning, while we counterintuitively find that datasets with rather unstructured failed trajectories can exhibit much more significant interference and degraded learning.

We further our analysis with two `robomimic` datasets containing highly unstructured failed trajectories: `can-mg` and `lift-mg`, which are comprised of rollouts collected by a

Soft Actor-Critic ([Haarnoja et al., 2018](#)) agent during its training process. The goal in `can-mg` is identical to that of `can-paired`, while the goal in `lift-mg` is to grasp and pick up a cube from a table. The distributions of trajectories in these datasets are thus similar to those of an agent's replay buffer, which is a popular dataset composition in the offline RL literature ([Fu et al., 2021](#)). These datasets do not possess the same qualitatively obvious shared prefix structure as `can-paired`; most of the failed trajectories consist of the robot arm flailing around, and do not resemble the successful behavior at all. While `robomimic` does not provide datasets with failed trajectories for its other domains (`square`, `tool-hang`, and `transport`), we construct our own in order to study a more diverse set of environments (see [Section A.1](#) for details).

Compared to `can-paired`, `can-mg` and `tool-hang` exhibit much greater interference sustained for a more significant fraction of the training process ([Fig. 3](#), top row); note the difference in x-axis. We see that this coincides with much slower learning progress ([Fig. 2](#)) for those environments. To understand how the negative term ∇J^- is gradually "tapered out," we also plot the ratio of the gradient norms $\|\nabla J^-\|/\|J^+\|$; this value approaches 0 when the importance ratios have vanished. The negative term ∇J^- continues to exercise some influence for a good portion of the training budget in `can-mg` and `tool-hang` ([Fig. 3](#), bottom row), but vanishes more quickly on other datasets ([Fig. 6](#)).

As ∇J^- vanishes quickly on some datasets, this raises the question: is TOPR learning something appreciably different than FBC in those cases? One such avenue is that an initial difference in objectives (however transient it may be) can significantly alter the course of the optimization trajectory ([Nikishin et al., 2022](#); [Nauman et al., 2024](#)). Of course, if the importance ratios ever exactly reach 0, [(1)](#) reduces to ∇J^+, the FBC objective. While this equivalence holds in expectation, it is worth noting that in a practical implementation of this algorithm, the resulting update is equivalent to FBC *with a reduced effective batch size*, which can also affect learning. Empirically, we find that across all datasets, TOPR learns a higher entropy policy than FBC ([Fig. 7](#)), which could be a result of this implicit small batch effect.

5. Discussion

We wish to contextualize our findings in the existing offline RL literature. Most prior works in value-based offline RL use methods based around the intuitive idea of "stitching together" good segments of low-performing trajectories ([Kostrikov et al., 2022](#)). While this is a sensible way to learn from subpar data, it contrasts with mechanisms demonstrated in this paper. To illustrate the difference, consider that value-based methods could recognize

Figure 3. Top: TOPR exhibits sizeable interference on `can-mg` and `tool-hang`. **Bottom:** The influence of ∇J^- is gradually tapered out over the course of training.

that the shared prefixes in `can-paired` consist of good actions, and can use those to improve the policy. In contrast, TOPR initially finds helpful learning signal not from the good pre-grasp data in failed trajectories, but from the bad post-grasp continuations ([Fig. 1](#), right). This points to a limitation of methods like TOPR that do not have any mechanisms for fine-grained credit assignment: potential benefits from cloning the high-quality prefixes of the failed trajectories are lost.

Our observations relating gradient interference and shared prefix structure are intriguing, considering that policy gradient algorithms with importance sampling are very effective for large language model post-training ([MiniMax et al., 2025](#)), a domain in which shared prefix structures are known to be abundant ([Wang et al., 2025](#)). As large models for robotic control continue to improve in base capabilities, we expect failures to look less like unstructured motion and more like failures in the reasoning chain of a language model, in which one or more mistakes is contained within a long sequence of subtasks. Some prior works explicitly encourage collecting demonstrations with intentional mistakes followed by corrective behavior ([Hu et al., 2025](#)); we note that this is just another example of specially structured offline data. We hope that our findings encourage careful consideration of the interaction between the structure of offline data and the algorithms we use for offline learning, and that new patterns of dataset composition may spark the design of new strains of offline RL algorithms suited to those patterns.

Acknowledgements

The authors would like to thank Nicolas Le Roux, Harley Wiltzer, and Dhruv Sreenivas for helpful discussions about this work. GB and MGB acknowledge funding support from the National Sciences and Engineering Research Council of Canada (NSERC) and the Canada CIFAR AI Chair program. This work used computational resources provided by Mila, Calcul Québec, and the Digital Research Alliance of Canada.

References

Ba, J. L., Kiros, J. R., and Hinton, G. E. Layer Normalization, July 2016. URL http://arxiv.org/abs/1607.06450. arXiv:1607.06450 [stat.ML].

Brandfonbrener, D., Bietti, A., Buckman, J., Laroche, R., and Bruna, J. When does return-conditioned supervised learning work for offline reinforcement learning? *Advances in Neural Information Processing Systems*, 35: 1542–1553, December 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/hash/0a2f65c9d2313b71005e600bd23393fe-Abstract-Conference.html.

Chen, K., Liu, Z., Zhang, T., Guo, Z., Xu, S., Lin, H., Zang, H., Li, X., Zhang, Q., Yu, Z., Fan, G., Huang, T., Wang, Y., and Yu, C. π_{rl}: Online RL Fine-tuning for Flow-based Vision-Language-Action Models, October 2025. URL http://arxiv.org/abs/2510.25889. arXiv:2510.25889 [cs].

Chen, L., Lu, K., Rajeswaran, A., Lee, K., Grover, A., Laskin, M., Abbeel, P., Srinivas, A., and Mordatch, I. Decision Transformer: Reinforcement Learning via Sequence Modeling. In *Advances in Neural Information Processing Systems*, volume 34, pp. 15084–15097. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/hash/7f489f642a0ddb10272b5c31057f0663-Abstract.html.

Chen, Q., Yu, J., Schwager, M., Abbeel, P., Shentu, F., and Wu, P. SARM: Stage-aware reward modeling for long horizon robot manipulation. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=aemqAxScl9.

Devvrit, F., Madaan, L., Tiwari, R., Bansal, R., Duvvuri, S. S., Zaheer, M., Dhillon, I. S., Brandfonbrener, D., and Agarwal, R. The art of scaling reinforcement learning compute for LLMs. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=FMjeC9Msws.

Emmons, S., Eysenbach, B., Kostrikov, I., and Levine, S. Rvs: What is essential for offline RL via supervised learning? In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=S874XAIpkR-.

Espeholt, L., Soyer, H., Munos, R., Simonyan, K., Mnih, V., Ward, T., Doron, Y., Firoiu, V., Harley, T., Dunning, I., Legg, S., and Kavukcuoglu, K. IMPALA: Scalable Distributed Deep-RL with Importance Weighted Actor-Learner Architectures. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1407–1416. PMLR, July 2018. URL https://proceedings.mlr.press/v80/espeholt18a.html.

Fang, H., Duan, J., Clay, D., Wang, S., Liu, S., Huang, W., Fan, X., Tsai, W.-C., Chen, S., Wang, Y. R., Xing, S., Cho, J., Park, J. S., Eftekhar, A., Sushko, P., Farley, K., Wadhwa, A., Harrison, C., Han, W., Lee, Y.-C., VanderBilt, E., Hendrix, R., Ellawela, S., Ngoo, L., Chai, J., Ren, Z., Farhadi, A., Fox, D., and Krishna, R. MolmoAct2: Action Reasoning Models for Real-world Deployment, May 2026. URL http://arxiv.org/abs/2605.02881. arXiv:2605.02881 [cs] version: 1.

Fu, J., Kumar, A., Nachum, O., Tucker, G., and Levine, S. D4RL: Datasets for Deep Data-Driven Reinforcement Learning, February 2021. URL http://arxiv.org/abs/2004.07219. arXiv:2004.07219 [cs].

Haarnoja, T., Zhou, A., Abbeel, P., and Levine, S. Soft Actor-Critic: Off-Policy Maximum Entropy Deep Reinforcement Learning with a Stochastic Actor. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1861–1870. PMLR, July 2018. URL https://proceedings.mlr.press/v80/haarnoja18b.html.

Hendrycks, D. and Gimpel, K. Gaussian Error Linear Units (GELUs), June 2016. URL http://arxiv.org/abs/1606.08415. arXiv:1606.08415 [cs.LG].

Hu, Z., Wu, R., Enock, N., Li, J., Kadakia, R., Erickson, Z., and Kumar, A. RaC: Robot Learning for Long-Horizon Tasks by Scaling Recovery and Correction, September 2025. URL http://arxiv.org/abs/2509.07953. arXiv:2509.07953 [cs].

Intelligence, P., Ai, B., Amin, A., Aniceto, R., Balakrishna, A., Balke, G., Black, K., Bokinsky, G., Cao, S., Charbonnier, T., Choudhary, V., Collins, F., Conley, K., Connors, G., Darpinian, J., Dhabalia, K., Dhaka, M., DiCarlo, J., Driess, D., Equi, M., Esmail, A., Fang, Y., Finn, C., Glossop, C., Godden, T., Goryachev, I., Groom, L., Habeeb, H., Hancock, H., Hausman, K., Hussein, G., Hwang, V., Ichter, B., Jacobsen, C., Jakubczak, S., Jen, R., Jones, T., Kammerer, G., Katz, B., Ke, L., Khadikov,

M., Kuchi, C., Lamb, M., LeBlanc, D., LeCount, B., Levine, S., Li, X., Li-Bell, A., Lialin, V., Liang, Z., Lim, W., Lu, Y., Luo, E., Mano, V., Marwaha, N., Mongush, A., Murphy, L., Nair, S., Patterson, T., Pertsch, K., Ren, A. Z., Schelske, G., Sharma, C., Shi, B., Shi, L. X., Smith, L., Springenberg, J. T., Stachowicz, K., Stoeckle, W., Tang, J., Tanner, J., Tekeste, S., Torne, M., Vedder, K., Vuong, Q., Walling, A., Wang, H., Wang, J., Wang, X., Whalen, C., Whitmore, S., Williams, B., Xu, C., Yoo, S., Yu, L., Zhang, W., Zhang, Z., and Zhilinsky, U. $\pi_{0.7}$: a Steerable Generalist Robotic Foundation Model with Emergent Capabilities, April 2026. URL http://arxiv.org/abs/2604.15483. arXiv:2604.15483 [cs].

Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In Bengio, Y. and LeCun, Y. (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Kostrikov, I., Nair, A., and Levine, S. Offline reinforcement learning with implicit q-learning. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=68n2s9ZJWF8.

Kumar, A., Zhou, A., Tucker, G., and Levine, S. Conservative Q-Learning for Offline Reinforcement Learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 1179–1191. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/hash/0d2b2061826a5df3221116a5085a6052-Abstract.html.

Lange, S., Gabel, T., and Riedmiller, M. Batch Reinforcement Learning. In Wiering, M. and van Otterlo, M. (eds.), *Reinforcement Learning: State-of-the-Art*, pp. 45–73. Springer, Berlin, Heidelberg, 2012. ISBN 978-3-642-27645-3. doi: 10.1007/978-3-642-27645-3_2. URL https://doi.org/10.1007/978-3-642-27645-3_2.

Le Roux, N., Bellemare, M., Lebensold, J., Bergeron, A., Greaves, J., Fréchette, A., Pelletier, C., Thibodeau-Laufer, E., Tóth, S., and Work, S. Tapered Off-Policy REINFORCE - Stable and efficient reinforcement learning for large language models. *Advances in Neural Information Processing Systems*, 38:68152–68180, 2025. URL https://papers.nips.cc/paper_files/paper/2025/hash/6274d57365d7a6be06e58cad30d1b9da-Abstract-Conference.html.

Levine, S., Kumar, A., Tucker, G., and Fu, J. Offline Reinforcement Learning: Tutorial, Review, and Perspectives on Open Problems, November 2020. URL http://arxiv.org/abs/2005.01643. arXiv:2005.01643 [cs].

Li, H., Zuo, Y., Yu, J., Zhang, Y., Zhaohui, Y., Zhang, K., Zhu, X., Zhang, Y., Chen, T., Cui, G., Wang, D., Luo, D., Fan, Y., Sun, Y., Zeng, J., Pang, J., Zhang, S., Wang, Y., Mu, Y., Zhou, B., and Ding, N. SimpleVLA-RL: Scaling VLA training via reinforcement learning. In *The Fourteenth International Conference on Learning Representations*, 2026. URL https://openreview.net/forum?id=TQhSodCM4r.

Li, Q., Kumar, A., Kostrikov, I., and Levine, S. Efficient deep reinforcement learning requires regulating overfitting. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=14-kr46GvP-.

Liu, B., Liu, X., Jin, X., Stone, P., and Liu, Q. Conflict-Averse Gradient Descent for Multi-task learning. In *Advances in Neural Information Processing Systems*, volume 34, pp. 18878–18890. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper/2021/hash/9d27fdf2477ffbff837d73ef7ae23db9-Abstract.html.

Mandlekar, A., Xu, D., Wong, J., Nasiriany, S., Wang, C., Kulkarni, R., Fei-Fei, L., Savarese, S., Zhu, Y., and Martín-Martín, R. What matters in learning from offline human demonstrations for robot manipulation. In *5th Annual Conference on Robot Learning*, 2021. URL https://openreview.net/forum?id=JrsfBJtDFdI.

McCloskey, M. and Cohen, N. J. Catastrophic Interference in Connectionist Networks: The Sequential Learning Problem. 24:109–165, 1989. doi: 10.1016/S0079-7421(08)60536-8. URL https://linkinghub.elsevier.com/retrieve/pii/S0079742108605368. Book Title: Psychology of Learning and Motivation ISBN: 9780125433242.

MiniMax, Chen, A., Li, A., Gong, B., Jiang, B., Fei, B., Yang, B., Shan, B., Yu, C., Wang, C., Zhu, C., Xiao, C., Du, C., Zhang, C., Qiao, C., Zhang, C., Du, C., Guo, C., Chen, D., Ding, D., Sun, D., Li, D., Jiao, E., Zhou, H., Zhang, H., Ding, H., Sun, H., Feng, H., Cai, H., Zhu, H., Sun, J., Zhuang, J., Cai, J., Song, J., Zhu, J., Li, J., Tian, J., Liu, J., Xu, J., Yan, J., Liu, J., He, J., Feng, K., Yang, K., Xiao, K., Han, L., Wang, L., Yu, L., Feng, L., Li, L., Zheng, L., Du, L., Yang, L., Zeng, L., Yu, M., Tao, M., Chi, M., Zhang, M., Lin, M., Hu, N., Di, N., Gao, P., Li, P., Zhao, P., Ren, Q., Xu, Q., Li, Q., Wang, Q., Tian, R., Leng, R., Chen, S., Chen, S., Shi, S., Weng, S., Guan, S., Yu, S., Li, S., Zhu, S., Li, T., Cai, T., Liang, T., Cheng, W., Kong, W., Li, W., Chen, X., Song, X., Luo, X., Su, X., Li, X., Han, X., Hou, X., Lu, X., Zou, X., Shen, X.,

Gong, Y., Ma, Y., Wang, Y., Shi, Y., Zhong, Y., Duan, Y., Fu, Y., Hu, Y., Gao, Y., Fan, Y., Yang, Y., Li, Y., Hu, Y., Huang, Y., Li, Y., Xu, Y., Mao, Y., Shi, Y., Wenren, Y., Li, Z., Li, Z., Tian, Z., Zhu, Z., Fan, Z., Wu, Z., Xu, Z., Yu, Z., Lyu, Z., Jiang, Z., Gao, Z., Wu, Z., Song, Z., and Sun, Z. MiniMax-M1: Scaling Test-Time Compute Efficiently with Lightning Attention, June 2025. URL https://arxiv.org/abs/2506.13585v1.

Munos, R., Stepleton, T., Harutyunyan, A., and Bellemare, M. Safe and Efficient Off-Policy Reinforcement Learning. In *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://papers.nips.cc/paper_files/paper/2016/hash/c3992e9a68c5ae12bd18488bc579b30d-Abstract.html.

Nauman, M., Bortkiewicz, M., Miłoś, P., Trzcinski, T., Ostaszewski, M., and Cygan, M. Overestimation, Overfitting, and Plasticity in Actor-Critic: the Bitter Lesson of Reinforcement Learning. In *Proceedings of the 41st International Conference on Machine Learning*, pp. 37342–37364. PMLR, July 2024. URL https://proceedings.mlr.press/v235/nauman24a.html.

Nikishin, E., Schwarzer, M., D'Oro, P., Bacon, P.-L., and Courville, A. The primacy bias in deep reinforcement learning. In Chaudhuri, K., Jegelka, S., Song, L., Szepesvari, C., Niu, G., and Sabato, S. (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 16828–16847. PMLR, 17–23 Jul 2022. URL https://proceedings.mlr.press/v162/nikishin22a.html.

Pomerleau, D. A. ALVINN: an autonomous land vehicle in a neural network. In *Proceedings of the 2nd International Conference on Neural Information Processing Systems*, NIPS'88, pp. 305–313, Cambridge, MA, USA, January 1988. MIT Press.

Precup, D., Sutton, R. S., and Singh, S. Eligibility Traces for Off-Policy Policy Evaluation. January 2000. URL https://hdl.handle.net/20.500.14394/10401.

Puterman, M. L. *Markov decision processes: discrete stochastic dynamic programming*. John Wiley & Sons, 2014.

Team, G. R., Abdolmaleki, A., Abeyruwan, S., Ainslie, J., Alayrac, J.-B., Arenas, M. G., Balakrishna, A., Batchelor, N., Bewley, A., Bingham, J., Bloesch, M., Bousmalis, K., Brakel, P., Brohan, A., Buschmann, T., Byravan, A., Cabi, S., Caluwaerts, K., Casarini, F., Chan, C., Chang, O., Chappellet-Volpini, L., Chen, J. E., Chen, X., Chiang, H.-T. L., Choromanski, K., Collister, A., D'Ambrosio, D. B., Dasari, S., Davchev, T., Dave, M. K., Devin, C., Palo, N. D., Ding, T., Doersch, C., Dostmohamed, A., Du, Y., Dwibedi, D., Egambaram, S. T., Elabd, M., Erez, T., Fang, X., Fantacci, C., Fong, C., Frey, E., Fu, C., Gao, R., Giustina, M., Gopalakrishnan, K., Graesser, L., Groth, O., Gupta, A., Hafner, R., Hansen, S., Hasenclever, L., Haves, S., Heess, N., Hernaez, B., Hofer, A., Hsu, J., Huang, L., Huang, S. H., Iscen, A., Jacob, M. G., Jain, D., Jesmonth, S., Jindal, A., Julian, R., Kalashnikov, D., Karagozler, M. E., Karp, S., Kecman, M., Kew, J. C., Kim, D., Kim, F., Kim, J., Kipf, T., Kirmani, S., Konyushkova, K., Ku, L. Y., Kuang, Y., Lampe, T., Laurens, A., Le, T. A., Leal, I., Lee, A. X., Lee, T.-W. E., Lever, G., Liang, J., Lin, L.-H., Liu, F., Long, S., Lu, C., Maddineni, S., Majumdar, A., Maninis, K.-K., Marmon, A., Martinez, S., Michaely, A. H., Milonopoulos, N., Moore, J., Moreno, R., Neunert, M., Nori, F., Ortiz, J., Oslund, K., Parada, C., Parisotto, E., Paryag, A., Pooley, A., Power, T., Quaglino, A., Qureshi, H., Raju, R. V., Ran, H., Rao, D., Rao, K., Reid, I., Rendleman, D., Reymann, K., Rivas, M., Romano, F., Rubanova, Y., Sampedro, P. P., Sanketi, P. R., Shah, D., Sharma, M., Shea, K., Shridhar, M., Shu, C., Sindhwani, V., Singh, S., Soricut, R., Sterneck, R., Storz, I., Surdulescu, R., Tan, J., Tompson, J., Tunyasuvunakool, S., Varley, J., Vesom, G., Vezzani, G., Villalonga, M. B., Vinyals, O., Wagner, R., Wahid, A., Welker, S., Wohlhart, P., Wu, C., Wulfmeier, M., Xia, F., Xiao, T., Xie, A., Xie, J., Xu, P., Xu, S., Xu, Y., Xu, Z., Yan, J., Yang, S., Yang, S., Yang, Y., Yu, H. H., Yu, W., Yuan, W., Yuan, Y., Zhang, J., Zhang, T., Zhang, Z., Zhou, A., Zhou, G., and Zhou, Y. Gemini Robotics 1.5: Pushing the Frontier of Generalist Robots with Advanced Embodied Reasoning, Thinking, and Motion Transfer, November 2025. URL http://arxiv.org/abs/2510.03342. arXiv:2510.03342 [cs].

Wang, S., Yu, L., Gao, C., Zheng, C., Liu, S., Lu, R., Dang, K., Chen, X.-H., Yang, J., Zhang, Z., Liu, Y., Yang, A., Zhao, A., Yue, Y., Song, S., Yu, B., Huang, G., and Lin, J. Beyond the 80/20 Rule: High-Entropy Minority Tokens Drive Effective Reinforcement Learning for LLM Reasoning. *Advances in Neural Information Processing Systems*, 38:115452–115486, 2025. URL https://papers.nips.cc/paper_files/paper/2025/hash/a797c2d2e0c1fdabf4d1ab8cd0b465c6-Abstract-Conference.html.

Yu, T., Kumar, S., Gupta, A., Levine, S., Hausman, K., and Finn, C. Gradient surgery for multi-task learning. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), *Advances in neural information processing systems*, volume 33, pp. 5824–5836. Curran Associates, Inc., 2020. URL https://proceedings.ne

urips.cc/paper_files/paper/2020/file/3fe78
a8acf5fda99de95303940a2420c-Paper.pdf.

A. Experimental Details

We used a network architecture comprised of four identical blocks, with residual connections between each block. Each block takes a 512-dimensional input (following an initial linear projection), and consists of LayerNorm (Ba et al., 2016), an up-projection to dimension 2048, GELU (Hendrycks & Gimpel, 2016) activation, and finally a down-projection back to dimension 512. Our networks were trained with Adam (Kingma & Ba, 2015) using learning rate 3×10^{-4} and gradient clipping. We used Gaussian policies with a state-independent learned variance. Policies were evaluated with 100 episodes per training seed, with results reported over 5 training seeds

A.1. Environments

We use the five environments from `robomimic` Fig. 4, using the standard low-dimensional state information provided by the environment as our observation space. We study the datasets they provide that contain negative demonstrations:

- `can-paired`: For each of 100 initial conditions, a human collected one successful trajectory (picking the can up and placing it in the correct bin) and one failed trajectory (picking the can up and dropping it off of the table).

- `can-mg` and `lift-mg`: These datasets follow the common replay buffer style of offline RL datasets; they are comprised of rollouts generated during the training run of a SAC (Haarnoja et al., 2018) agent. Specifically, `lift-mg` was produced from collecting 300 trajectories at 5 checkpoints throughout the training process, while `can-mg` used 13 checkpoints.

Figure 4. Environments from (Mandlekar et al., 2021). From left to right: `lift`, `can`, `square`, `tool-hang`, and `transport`.

Because `robomimic` doesn't provide datasets with failed trajectories for the other environments, we construct them ourselves. Our dataset generation process begins with training a BC policy on their provided datasets of proficient human-generated trajectories. We then rolled out this learned BC policy many times in the environment and filtered the resulting trajectories to yield balanced datasets (Table 1). We injected noise into some expert trajectories during the collection process.

Table 1. Dataset properties. Note that the trajectories for the datasets generated are all the same length, while `can-paired` consists of human demos that vary in length.

DATASET	TRAJECTORY LENGTH	SUCCESSFUL TRAJECTORIES	FAILED TRAJECTORIES
can-paired	99 (mean)	100	100
can-mg	150	718	3182
lift-mg	150	316	1184
square	400	4096	4096
tool-hang	700	2048	2048
transport	700	2048	2048

B. Additional Results

Figure 5. The different datasets yield different levels of gradient interference over the course of training. Training on certain datasets, like `can-paired` and `transport`, results in little interference, with effects disappearing quickly. On the other hand, `can-mg` and `tool-hang` exhibit more significant and persistent interference.

Figure 6. The influence of the negative term ∇J^- is eventually tapered out within the training budget for all datasets, though the length of training time to reach that point varies by dataset.

Figure 7. TOPR consistently learns a higher entropy policy than FBC.