VARIANCE BASED SAMPLE WEIGHTING FOR SUPERVISED LEARNING

ABSTRACT

In the context of supervised learning of a function by a Neural Network (NN), we claim and empirically justify that a NN yields better results when the distribution of the data set focuses on regions where the function to learn is steeper. We first traduce this assumption in a mathematically workable way using Taylor expansion. Then, theoretical derivations allow to construct a methodology that we call Variance Based Samples Weighting (VBSW). VBSW uses local variance of the labels to weight the training points. This methodology is general, scalable, cost effective, and significantly increases the performances of a large class of models for various classification and regression tasks on image, text and multivariate data. We highlight its benefits with experiments involving NNs from shallow linear NN to ResNet (He et al., 2015) or Bert (Devlin et al., 2019).

1 INTRODUCTION

When a Machine Learning (ML) model is used to learn from data, the distribution of the training data set can have a strong impact on its performances. More specifically, in the context of Deep Learning (DL), several works have hinted at the importance of the training set. In Bengio et al. (2009); Matiisen et al. (2017), the authors exploit the observation that a human will benefit more from easy examples than from harder ones at the beginning of a learning task. They construct a curriculum, inducing a change in the distribution of the training data set that will make a Neural Network (NN) achieve better results in an ML problem. With a different approach, Active Learning (Settles, 2012) modifies dynamically the distribution of the training data, by selecting the data points that will make the training more efficient. Finally, in Reinforcement Learning, the distribution of experiments is crucial for the agent to learn efficiently. Nonetheless, the challenge of finding a good distribution is not specific to ML. Indeed, in the context of Monte Carlo estimation of a quantity of interest based on a random variable $X \sim d\mathbb{P}_X$, Importance Sampling owes its efficiency to the construction of a second random variable, $\bar{X} \sim d\mathbb{P}_{\bar{X}}$ that will be used instead of X to improve the estimation of this quantity. Jie & Abbeel (2010) even make a connection between the success of likelihood ratio policy gradients and importance sampling, which shows that ML and Monte Carlo estimation, so distribution based methods, are closely linked.

In this paper, we leverage the importance of the training set distribution to improve performances of NNs in supervised ML. This task can be formalized as approximating a function f with a model f_θ parametrized by θ. We build a new distribution from the training points and their labels, based on the observation that a model f_θ needs more data points to approximate f on the regions where it is steep. We use Taylor expansion of a function f, which links the local behaviour of f to its derivatives, to build this distribution. We show that up to a certain order and locally, variance is an estimator of Taylor expansion. It allows constructing a methodology, Variance Based Sample Weighting (VBSW) that weights each training data points using the local variance of their neighbor labels, prior to the training and regardless of the model, to simulate the new distribution. Sample weighting has already been explored in many works and for various goals. Kumar et al. (2010); Jiang et al. (2015) use it to prioritize easier samples for the training, Shrivastava et al. (2016) for hard example mining, Cui et al. (2019) to avoid class imbalance, or (Liu & Tao, 2016) to solve noisy label problem. Here, the weights' construction relies on a more general claim that can be applied to any data set and whose goal is to boost the performances of the model.

VBSW is general, because it can be applied to any supervised ML problem that involves a loss function. It is made scalable and cost effective, specifically for DL, by applying it within the feature space of NNs. We validate VBSW on various tasks like classification or regression of text, from Glue benchmark (Wang et al., 2019), image, from MNIST (LeCun & Cortes, 2010) and Cifar10 (Krizhevsky et al.) and multivariate data, from UCI ML repository (Dua & Graff, 2017), for several models ranging from linear regression to Bert (Devlin et al., 2019) or ResNet20 (He et al., 2015). As a highlight, we obtain up to 1.65% classification improvement on Cifar10 with a ResNet.

Contributions: **(i)** We present and investigate a new approach of the learning problem, based the variations of the function f to learn. **(ii)** We construct a new simple, scalable and cost effective methodology, VBSW, that allows to exploit these findings in order to boost the performances of a NN. **(iii)** We validate VBSW on various ML tasks.

2 RELATED WORKS

Active Learning - Our methodology is based on the consideration that not every sample bring the same amount of information. Active learning (AL) exploits the same idea, in the sense that it adapts the training strategy to the problem by introducing a data point selection rule. In (Gal et al., 2017), the authors introduce a methodology based on Bayesian Neural Networks (BNN) to adapt the selection of points used for the training. Using the variational properties of BNN, they design a rule to focus the training on points that will reduce the prediction uncertainty of the NN. In (Konyushkova et al., 2017), the construction of the selection rule is taken as a ML problem itself. See (Settles, 2012) for a review of more classical AL methods. The similarity between AL and VBSW goes beyond adapting the training to the data. Indeed, AL selects the data points, so modifies the distribution of the initial training data set. The main difference is that VBSW is prior to the training, and therefore the distribution of the weights can not change throughout the training. Our methodology could even be applied before the training and AL used during the training.

Examples Weighting - VBSW can be categorized as an example weighting algorithm. The idea of weighting the data set has already been explored in different ways and for different purposes. While curriculum learning (Bengio et al., 2009; Matiisen et al., 2017) starts the training with easier examples, Self paced learning (Kumar et al., 2010; Jiang et al., 2015) downscales harder examples. However, some works have proven that focusing on harder examples from the beginning of the learning could lead to faster training. In (Shrivastava et al., 2016), hard example mining is performed to give more importance to harder examples by selecting them primarily. Example weighting is used in (Cui et al., 2019) to tackle the class imbalance problem by weighting rarer, and so harder examples. At the contrary, in (Liu & Tao, 2016) it is used to solve the noisy label problem by focusing on cleaner, so easier examples. All these ideas show that depending on the application, example weighting can be performed in an opposed manner. Some works aim at moving beyond this opposition by introducing more general methodologies. In (Chang et al., 2017), the authors use the variance of the prediction of each point throughout the training to decide whether it should be weighted or not. A meta learning approach is proposed in (Ren et al., 2018), where the authors choose the weights after an optimization nested in the training. VBSW stands out from the previously mentioned example weighting methods because it is built on a more general claim that a model will simply need more points to learn more complicated functions. Its effect is to boost the performances of a NN, whatever the application is.

Importance Sampling - Some of the previously mentioned methods use importance sampling to design the weights of the data set or to correct the bias induced by the sample selection (Katharopoulos & Fleuret, 2018). Here, we construct a new distribution that could be interpreted as an importance distribution. However, we weight the data points to simulate this distribution, not to correct a bias induced by this distribution.

Generalization Bound - Generalization bound for the learning theory of NN have motivated many works, most of which are reviewed in (Jakubovitz et al., 2018). In Bartlett et al. (1998), Bartlett et al. (2019), the authors focus on VC-dimension, a measure which depends on the number of parameters of NNs. Arora et al. (2018) introduces a compression approach that aims at reducing the number of model parameters to investigate its generalization capacities. PAC-Bayes analysis constructs generalization bounds using *a priori* and *a posteriori* distributions over the possible models. It is investigated for example in Neyshabur et al. (2018); Bartlett et al. (2017), and Neyshabur et al.

(2017); Xu & Mannor (2012) links PAC-Bayes theory to the notion of sharpness of a NN, i.e. its robustness to small perturbation. While sharpness of the model is often mentioned in the previous works, our bound includes the derivatives of f, the function to approximate, which can be seen as its sharpness. Even if it uses elements of previous works, like the Lipschitz constant of f_θ, our work does not pretend to tighten and improve the already existing generalization bounds, but only emphasizes the intuition that the NN will need more points to capture sharper functions. In a sense, it investigates the robustness to perturbations in the input space, not in the parameter space.

3 A NEW TRAINING DISTRIBUTION BASED ON TAYLOR EXPANSION

In this section, we first illustrate why a NN may need more points where f is steep by deriving a generalization bound that involves the derivatives of f. Then, using Taylor expansion, we build a new training distribution that improves the performances of a NN on simple functions.

3.1 PROBLEM FORMULATION

We formalize the supervised ML task as approximating a function $f : \mathbf{S} \subset \mathbb{R}^{n_i} \to \mathbb{R}^{n_o}$ with an ML model f_θ parametrized by θ, where $\mathbf{S}$ is a measured sub-space of $\mathbb{R}^{n_i}$ depending on the application. To this end, we are given a training data set of N points, $\{X_1, ..., X_N\} \in \mathbf{S}$, drawn from $X \sim d\mathbb{P}_X$ and their point-wise values, or labels $\{f(X_1), ..., f(X_N)\}$. Parameters θ have to be found in order to minimize an integrated loss function $J_X(\theta) = \mathbb{E}_X[L(f_\theta(X), f(X))]$, with L the loss function, $L : \mathbb{R}^{n_o} \times \mathbb{R}^{n_o} \to \mathbb{R}$. The data allow estimating $J_X(\theta)$ by $\widehat{J_X}(\theta) = \frac{1}{N} \sum_{i=1}^{N} L(f_\theta(X_i), f(X_i))$ and to use optimization algorithms to find a minimum of $\widehat{J_X}(\theta)$ w.r.t. θ.

3.2 INTUITION BEHIND TAYLOR EXPANSION

In the following, we illustrate the intuition with a Generalization Bound (GB) that include the derivatives of f, provided that these derivatives exist. The goal of the approximation problem is to be able to generalize to points not seen during the training. The generalization error $\mathcal{J}_X(\theta) = J_X(\theta) - \widehat{J_X}(\theta)$ thus needs to be as small as possible. Let S_i, $i \in \{1, ..., N\}$ be some sub-spaces of $\mathbf{S}$ such that $\mathbf{S} = \bigcup_{i=1}^{N} S_i$, $\bigcap_{i=1}^{N} S_i = \emptyset$, and $X_i \in S_i$. Suppose that L is the squared L_2 error, $n_i = 1$, f is differentiable and f_θ is K_θ-Lipschitz. Provided that $|S_i| < 1$, we show that

$$\mathcal{J}_X(\theta) \leq \sum_{i=1}^{N} (|f'(X_i)| + K_\theta)^2 \frac{|S_i|^3}{4} + O(|S_i|^4), \tag{1}$$

where $|S_i|$ is the volume of S_i. The proof can be found in **Appendix B**. We see that on the regions where $f'(X_i)$ is higher, quantity $|S_i|$ has a stronger impact on the GB. this idea is illustrated on Figure 1. Then, since $|S_i|$ can be seen as a metric for the local density of the data set (the smaller $|S_i|$ is, the denser the data set is), the GB can be reduced more efficiently by adding more points around X_i in these regions. This bound also involves K_θ, the Lipschitz constant of the NN, which

Figure 1: Illustration of the GB. The maximum error (the GB), at order $O(|S_i|^4)$, is obtained by comparing the maximum variations of f_θ, and the first order approximation of f, whose trends are given by K_θ and $f'(X_i)$. We understand visually that because $f'(X_1)$ and $f'(X_3)$ are higher than $f'(X_2)$, the GB is improved more efficiently by reducing S_1 and S_3 than S_2.

has the same impact than $f'(X_i)$. It also illustrates the link between the Lipschitz constant and the generalization error, which has been pointed out by several works like (Gouk et al., 2018), (Bartlett et al., 2017) and (Qian & Wegman, 2019). Note that equation 1 only gives indications about $n = 1$. Indeed, this GB only has illustration purposes, and motivates the metric described in the next section, which is based on Taylor expansion and therefore involves derivatives of order $n > 1$.

3.3 A Taylor expansion based metric

In this paragraph, we build a metric involving the derivatives of f. Using the Taylor expansion at order n on f and supposing that f is n times differentiable (multi index notation):

$$f(x+\epsilon) \underset{\|\epsilon\|\to 0}{=} \sum_{0\le|\boldsymbol{k}|\le n} \epsilon^{\boldsymbol{k}} \frac{\partial^{\boldsymbol{k}} f(x)}{\boldsymbol{k}!} + O(\epsilon^{\boldsymbol{n}}). \qquad Df_{\epsilon}^{n}(x) = \sum_{1\le|\boldsymbol{k}|\le n} \frac{\|\epsilon\|^{k} \cdot \|\operatorname{Vect}(\partial^{\boldsymbol{k}} f(x))\|}{\boldsymbol{k}!}. \quad (2)$$

Quantity $f(x + \epsilon) - f(x)$ gives an indication on how much f changes around x. By neglecting the orders above $\epsilon^{\boldsymbol{n}}$, it is then possible to find the regions of interest by focusing on Df_{ϵ}^{n}, given by equation 2, where $\operatorname{Vect}(\mathbf{X})$ denotes the vectorization of a tensor $\mathbf{X}$ and $\|.\|$ the squared L_2 norm. Note that Df_{ϵ}^{n} is evaluated using $\|\partial^{\boldsymbol{k}} f(x)\|$ instead of $\partial^{\boldsymbol{k}} f(x)$ for derivatives not to cancel each other. f will be steeper and more irregular in the regions where $x \to Df_{\epsilon}^{n}(x)$ is higher.

To focus the training set on these regions, one can use $\{Df_{\epsilon}^{n}(X_1), ..., Df_{\epsilon}^{n}(X_N)\}$ to construct a probability density function (pdf) and sample new data points from it. This sampling is evaluated and validated in **Appendix A** for conciseness. Based on these experiments, we choose $n = 2$, i.e. we use $\{Df_{\epsilon}^{2}(X_1), ..., Df_{\epsilon}^{2}(X_N)\}$. The good results obtained confirm our observation and motivate its application to more complex ML problems.

4 Variance Based Samples Weighting (VBSW)

4.1 Preliminaries

The new distribution cannot always be applied as is, because we do not have access to f. **Problem 1:** $\{Df_{\epsilon}^{2}(X_1), ..., Df_{\epsilon}^{2}(X_N)\}$ cannot be evaluated since it requires to compute the derivatives of f. Moreover, it assumes that f is differentiable, which is often not true. **Problem 2:** even if $\{Df_{\epsilon}^{2}(X_1), ..., Df_{\epsilon}^{2}(X_N)\}$ could be computed and new points sampled, we could not obtain their labels to complete the training data set.

Problem 1: Unavailability of derivatives To overcome **problem 1**, we construct a new metric based on statistical estimation. In this paragraph, $n_i > 1$ but $n_o = 1$. The following derivations can be extended to $n_o > 1$ by applying it to f element-wise and then taking the sum across the n_o dimensions. Let $\epsilon \sim \mathcal{N}(0, \epsilon\mathbb{I}_{n_i})$ with $\epsilon \in \mathbf{R}^{+}$ and $\mathbf{I}_{n_i}$ the identity matrix of dimension n_i. We claim that

$$Var(f(x + \epsilon)) = Df_{\epsilon}^{2}(x) + O(|\epsilon|_2^3).$$

The demonstration can be found in **Appendix B**. Using the unbiased estimator of variance, we define new indices $\widehat{Df_{\epsilon}^{2}}(x)$ by

$$\widehat{Df_{\epsilon}^{2}}(x) = \frac{1}{k-1} \sum_{i=1}^{k} \left(f(x + \epsilon_{\boldsymbol{i}}) - f(x)\right)^{2}, \qquad (3)$$

with $\{\epsilon_1, ..., \epsilon_k\}$ k samples of ϵ. Note that $\widehat{Df^2}_{\epsilon}(x) \underset{k\to\infty}{\to} Var(f(x + \epsilon))$. Since $Var(f(x + \epsilon)) = Df_{\epsilon}^{2}(x) + O(|\epsilon|_2^3)$, $\widehat{Df^2}_{\epsilon}(x)$ is a biased estimator of $Df_{\epsilon}^{2}(x)$, with bias $O(|\epsilon|_2^3)$. Hence, when $\epsilon \to 0$, $\widehat{Df^2}_{\epsilon}(x)$ becomes an unbiased estimator of $Df_{\epsilon}^{2}(x)$. It is possible to compute $\widehat{Df^2}(x)$ from any set of points centered around x. Therefore, we compute $\widehat{Df^2}(X_i)$ for each $i \in \{1, ..., N\}$ using the set $\mathcal{S}_k(X)$ of k-nearest neighbors of X_i. We obtain $\widehat{Df^2}(X_i)$ using

$$\widehat{Df^2}(X_i) = \frac{1}{k-1} \sum_{X_j \in \mathcal{S}_k(X_i)} \left(f(X_j) - \frac{1}{k} \sum_{l=1}^{k} f(X_l)\right)^{2}, \qquad (4)$$

The advantages of this formulation are twofold. First, $\widehat{Df^2}$ can even be applied to non-differentiable functions. Second, all we need is $\{f(X_1), ..., f(X_N)\}$. In other words, the points used by $\widehat{Df^2}(X_i)$ are those used for the training of the NN. Finally, while the definition of $Df_\epsilon^2(x)$ is local, the definition of $\widehat{Df^2}_\epsilon(x)$ holds for any ϵ. Note that equation 4 can even be applied when the data points are too sparse for the nearest neighbors of X_i to be considered as close to X_i. It can thus be seen as a generalization of $Df_\epsilon^2(x)$, which tends towards $Df_\epsilon^2(x)$ locally.

Problem 2: Unavailability of new labels To tackle **problem 2**, recall that the goal of the training is to find $\theta^* = \underset{\theta}{\operatorname{argmin}}\widehat{J_X}(\theta)$, with $\widehat{J_X}(\theta) = \frac{1}{N}\sum_i L(f(X_i), f_\theta(X_i))$. With the new distribution based on previous derivations, the procedure is different. Since the training points are sampled using $\widehat{Df^2}_\epsilon$, we no longer minimize $\widehat{J_X}(\theta)$, but $\widehat{J_{\bar{X}}}(\theta) = \frac{1}{N}\sum_i L(f(\bar{X}_i), f_\theta(\bar{X}_i))$, with $\bar{X} \sim d\mathbb{P}_{\bar{X}}$ the new distribution. However, $\widehat{J_{\bar{X}}}(\theta)$ estimates

$$J_{\bar{X}}(\theta) = \int_{\mathbf{S}} L(f(x), f_\theta(x))d\mathbb{P}_{\bar{X}}.$$

Let $p_X(x)dx = d\mathbb{P}_X$, $p_{\bar{X}}(x)dx = d\mathbb{P}_{\bar{X}}$ be the pdf of X and $\bar{X}$ (note that $Df_\epsilon^2 \propto p_{\bar{X}}$). Then,

$$J_{\bar{X}}(\theta) = \int_{\mathbf{S}} L(f(x), f_\theta(x))\frac{p_{\bar{X}}(x)}{p_X(x)}d\mathbb{P}_X.$$

The straightforward Monte Carlo estimator for this expression of $J_{\bar{X}}(\theta)$ is

$$\widehat{J_{\bar{X},2}}(\theta) = \frac{1}{N}\sum_i L(f(X_i), f_\theta(X_i))\frac{p_{\bar{X}}(X_i)}{p_X(X_i)} \propto \frac{1}{N}\sum_i L(f(X_i), f_\theta(X_i))\frac{\widehat{Df^2}(X_i)}{p_X(X_i)}. \quad (5)$$

It is therefore possible to estimate $J_{\bar{X}}(\theta)$ with the same points as $J_X(\theta)$. All we have to do is weighting these points by $w_i = \frac{\widehat{Df^2}(X_i)}{p_X(X_i)}$.

4.2 HYPERPARAMETERS OF VBSW

The expression of w_i involves $Df_\epsilon^2(X_i)$, whose estimation has been the goal of the previous sections. However, it also involves p_X, the distribution of the data. Just like for f, we do not have access to p_X. The estimation of p_X is a challenging task by itself, and standard density estimation techniques such as K-nearest neighbors or Gaussian Mixture density estimation led to extreme estimated values of $p_X(X_i)$ in our experiments. Therefore, we decided to only apply $\omega_i = \widehat{Df^2}(X_i)$ as a first order approximation. In practice, we re-scale the weighting points to be between 1 and m, a hyperparameter. As a result, VBSW has two hyperparameters: m and k. Their effects and interactions are studied in **Appendix C**.

4.3 VBSW FOR DEEP LEARNING

We specified that the local variance could be computed using already existing points. This statement implies to find the nearest neighbors of each point. In extremely high dimension spaces like image spaces the curse of dimensionality makes nearest neighbors spurious. In addition, the structure of the data may be highly irregular, and the concept of nearest neighbor misleading. Thus, it may be irrelevant to evaluate $\widehat{D^2 f_\epsilon}$ directly on this data.

One of the strength of DL is to construct good representations of the data, embedded in lower dimensional latent spaces. For instance, in Computer Vision, Convolutional Neural Networks (CNN)'s deeper layers represent more abstract features. We could leverage this representational power of NNs, and simply apply our methodology within this latent feature space.

Variance Based Samples Weighting (VBSW) for DL is recapitulated in Algorithm 1. Here, $\mathcal{M}$ is the initial NN whose latent space will be used to project the training data set and apply VBSW. **Line 1:** m and k are hyperparameters that can be chosen jointly with all other hyperparameters, e.g. using a random search. **Line 2:** The initial NN, $\mathcal{M}$, is trained as usual. Notations $\{(\frac{1}{N}, X_1), ..., (\frac{1}{N}, X_N)\}$ is equivalent to $\{X_1, ..., X_N\}$, because all the weights are the same ($\frac{1}{N}$). **Line 3:** The last fully

---

Algorithm 1 Variance Based Samples Weighting (VBSW) for Deep learning

1: **Inputs:** $k, m, \mathcal{M}$
2: Train $\mathcal{M}$ on the training set $\{(\frac{1}{N}, X_1), ..., (\frac{1}{N}, X_N)\}, \{(\frac{1}{N}, f(X_1)), ..., (\frac{1}{N}, f(X_N))\}$
3: Construct $\mathcal{M}^*$ by removing its last layer
4: Compute $\{\widehat{Df^2}(\mathcal{M}^*(X_1)), ..., \widehat{Df^2}(\mathcal{M}^*(X_N))\}$ using equation 4.
5: Construct a new training data set $\{(w_1, \mathcal{M}^*(X_1)), ..., (w_N, \mathcal{M}^*(X_N))\}$
6: Train f_θ on $\{(w_1, f(X_1)), ..., (w_N, f(X_N))\}$ and add it to $\mathcal{M}^*$. The final model is $\mathcal{M}_f = f_\theta \circ \mathcal{M}^*$

---

connected layer is discarded, resulting in a new model $\mathcal{M}^*$, and the training data set is projected in the feature space. **Line 4-5:** equation 4 is applied to compute the weights w_i that are used to weight the projected data set. To perform nearest neighbors search, we use KD-Tree (Bentley, 1975). **Line 6:** The last layer is re-trained (which is often equivalent to fitting a linear model) using the weighted data set and added to $\mathcal{M}^*$ to obtain the final model $\mathcal{M}_f$. As a result, $\mathcal{M}_f$ is a composition of the already trained model $\mathcal{M}^*$ and f_θ trained using the weighted data set.

5 EXPERIMENTS

We first test this methodology on toy datasets with linear models and small NNs. Then, to illustrate how general VBSW can be, we validate it for various tasks in image classification, text regression and classification, namely MNIST (LeCun & Cortes, 2010), Cifar10 (Krizhevsky et al.) and some of the glue benchmark data sets (Wang et al., 2019) (RTE, STS-B and MRPC). We use LeNet 5 (Lecun et al., 1998), ResNet20 (He et al., 2015), two CNNs and Bert (Devlin et al., 2019) a NN based on bi-directional Transformers (Vaswani et al., 2017).

5.1 TOY EXPERIMENTS

VBSW is studied on a Double Moon (DM) classification, in the Boston Housing (BH) regression and Breast Cancer (BC) classification data sets.

Figure 2: From left to right: **(a)** Double Moon (DM) data set. **(b)** Decision boundary with the baseline method. **(c)** Heat map of the value of w_i for each X_i (red is high and blue is low) and **(d)** Decision boundary with VBSW method

For DM, Figure 2 (c) shows that the points with highest w_i (in red) are close to the boundary between the two classes. Indeed, in classification, VBSW can be interpreted as local label agreement. We train a Multi Layer Perceptron of 1 layer of 4 units, using Stochastic Gradient Descent (SGD) and binary cross-entropy loss function, on a 300 points training data set for

	VBSW	baseline
DM	**99.4**, **94.44** ± 0.78	$99, 92.06 \pm 0.66$
BH	**13.31**, **13.38** ± 0.01	$14.05, 14.06 \pm 0.01$
BC	**99.12**, **97.6** ± 0.34	$98.25, 97.5 \pm 0.11$

Table 1: **best, mean + se** for each method. The metric used is accuracy for DM and BC and Mean Squared Error for BH.

50 random seeds. In this experiment, VBSW, i.e. weighting the data set with w_i is compared to baseline where no weights are applied. Figure 2 (b) and (d) displays the decision boundary of best fit for each method. VBSW provides a cleaner decision boundary than baseline. These pictures as well as the results of Table 1 show the improvement obtained with VBSW.

For BH data set, a linear model is trained and for BC data set, a MLP of 1 layer and 30 units, with a train-validation split of $80\% - 20\%$. Both models are trained with ADAM (Kingma & Ba, 2014).

Since these data sets are small and the models are light, we study the effects of the choice of m and k on the performances. Moreover, BH is a regression task and BC a classification task, so it allows studying the effect of hyperparameters more extensively. We train the models for a grid of 20×20 different values of m and k. These hyperparameters seem to have a different impact on performances for classification and regression. In both cases, low values for m yields better results, but in classification, low values of k are better, unlike in regression. Details and visualization of this experiment can be found in **Appendix C**. The best results obtained with this study are compared to the best result of the same models trained without VBSW in Table 1.

5.2 MNIST AND CIFAR10

For MNIST, we train 40 LeNet 5, i.e. with 40 different random seeds, and then apply VBSW for 10 different random seeds, with ADAM optimizer and categorical cross-entropy loss. Note that in the following, ADAM is used with the default parameters of its `keras` implementation. We record the best value obtained from the 10 VBSW training. The same procedure is followed for Cifar10, except that we train a ResNet20 for 50 random seeds and with data augmentation. The networks have been trained on 4 Nvidia K80 GPUs. The values of the hyperparameters used can be found in **Appendix C**. We compare the test accuracy between LeNet 5 + VBSW, ResNet20 + VBSW and the initial test accuracies of LeNet 5 and ResNet20 (baseline) for each of the initial networks.

	VBSW	baseline	gain per model
MNIST	**99.09**, **98.87** $\pm$ 0.01	98.99, 98.84 $\pm$ 0.01	**0.15**, **0.03** $\pm$ 0.01
Cifar10	**91.30**, **90.64** $\pm$ 0.07	91.01, 90.46 $\pm$ 0.10	**1.65**, **0.15** $\pm$ 0.04

Table 2: **best, mean + se** for each method. The metric used is accuracy. For a model $\mathcal{M}$, the gain g for this model is given by $g = \max_{1 \le i \le 10} (acc(\mathcal{M}_f^i) - acc(\mathcal{M}))$ with acc the accuracy and $\mathcal{M}_f^i$ the VBSW model trained at the i-th random seed.

The results statistics are gathered in Table 2, which also displays statistics about the gain due to VBSW for each model. The results on MNIST, for all statistics and for the gain are significantly better than baseline. For Cifar10, we get a 0.3% accuracy improvement for the best model and up to 1.65% accuracy gain, meaning that among the 50 ResNet20s, there is one whose accuracy has been improved by 1.65% by VBSW. Note that applying VBSW took less than 15 minutes on a laptop with an i7-7700HQ CPU. A visualization of the samples that were weighted by the highest w_i is given in Figure 3.

Figure 3: Samples from Cifar10 and MNIST with high w_i. Those pictures are either unusual or difficult to classify, even for a human (especially for MNIST).

5.3 RTE, STS-B AND MRPC

For this application, we did not train Bert NN, like in the previous experiments, since its purpose is to be used as is and then fine-tuned on any NLP data set. However, because of the small size of the dataset and the high number of model parameters we chose not to fine-tune the Bert model, and only to use the representations of the data sets in its latent space to apply a linear model. More specifically, we use tiny-bert (Turc et al., 2019), which is a lighter version of the initial Bert NN. We train the linear model with tensorflow, to be able to add the trained model on top of the Bert model and obtain a unified model. RTE and MRPC are classification tasks, so we use binary cross-entropy loss function to train our model. STS-B is a regression task so the model is trained with Mean Squared Error. All the models are trained with ADAM optimizer. For each task, we compare the training of the linear model with VBSW, and without VBSW (baseline). The results obtained with

VBSW are better overall, except for Pearson Correlation in STS-B, which is slightly worse than baseline (Table 3).

	VBSW		baseline	
	m1	m2	m1	m2
RTE	**61.73**, **58.46** ± 0.15	-	61.01, 58.09 ± 0.13	-
STS-B	**62.31**, **62.20** ± 0.01	**60.99**, 60.88 ± 0.01	61.88, 61.87 ± 0.01	60.98, **60.92** ± 0.01
MRPC	**72.30**, **71.71** ± 0.03	**82.64**, **80.72** ± 0.05	71.56, 70.92 ± 0.03	81.41, 80.02 ± 0.07

Table 3: **best, mean + se** for each method. For RTE the metric used is accuracy (m1). For MRPC, metric 1 (m1) is accuracy and metric 2 (m2) is F1 score. For STS-B, metric 1 (m1) is Spearman correlation and metric 2 (m2) is Pearson correlation.

6 DISCUSSION & FUTURE WORK

The previous experiments demonstrate the performance improvement that VBSW can bring in practice. In addition to these results, several advantages can be pointed out.

- VBSW is validated on several different tasks, which makes it quite versatile. Moreover, the problem of high dimensionality and irregularity of f, which often arises in DL problems, is alleviated by focusing on the latent space of NN. This makes VBSW scalable. As a result, VBSW can be applied from linear regression to complex models such as ResNet, a very deep and complex CNN or Bert, for various ML tasks.

- This validation supports an original view of the learning problem, that involves the local variations of f. Note that the study of **Appendix A** supports this approach as well.

- VBSW allows to extend this approach to problems where the derivatives of f are not accessible, and sometimes not defined. Indeed, VBSW comes from Taylor expansion, which is specific to derivable functions, but in the end can be applied regardless of the properties of f.

- Finally, this method is cost effective. In most cases, it allows to quickly improve the performances of a NN using a regular CPU. In terms of energy consumption, it is better than carrying on a whole new training with a wider and deeper NN.

We first approximated p_X to be uniform, because we could not approximate it correctly. This still led to a an efficient methodology, but VBSW may benefit from a finer approximation of p_X. Improving the approximation of p_X is among our perspectives. Finally, the KD-tree and even Approximate Nearest Neighbors algorithms struggle when the data set is too big. One possibility to overcome this problem would be to parallelize their execution.

We only considered the cases where we have not access to f. However, there are ML applications where we do. For instance, in numerical simulations, for physical sciences, economics or climatology, ML can be used for various reasons, e.g. sensitivity analysis, inverse problems or to speed up computer codes (Zhu et al., 2019), (Winovich et al., 2019) or (Feng et al., 2018). In this context the data comes from numerical models, so the derivatives of f are accessible and could be used to sample training points from the distribution obtained in Section 3.3.

7 CONCLUSION

Our work is based on the observation that, in supervised learning, a function f is more difficult to approximate by a ML model in the regions where it is steeper. We mathematically traduced this intuition and derived a generalization bound to illustrate it. Then, we constructed an original method, Variance Based Samples Weighting (VBSW), that uses the variance of the training samples to weight the training data set and boosts the model performances. VBSW is simple to use and to implement, because it only requires to compute statistics on the input space. In Deep Learning, applying VBSW on the data set projected in the feature space of an already trained NN allows to boost its performance by simply training its last layer. This method is applicable to any loss function based supervised learning problem, scalable, cost effective, and validated on several applications such as glue benchmark with Bert, for text classification and regression and Cifar10 with a ResNet20, for image classification.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL http://tensorflow.org/. Software available from tensorflow.org.

Sanjeev Arora, Rong Ge, Behnam Neyshabur, and Yi Zhang. Stronger generalization bounds for deep nets via a compression approach. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 254–263, Stockholmsmässan, Stockholm Sweden, 10–15 Jul 2018. PMLR.

Peter L. Bartlett, Vitaly Maiorov, and Ron Meir. Almost linear vc dimension bounds for piecewise polynomial networks. In *Proceedings of the 11th International Conference on Neural Information Processing Systems*, NIPS'98, pp. 190–196, Cambridge, MA, USA, 1998. MIT Press.

Peter L Bartlett, Dylan J Foster, and Matus J Telgarsky. Spectrally-normalized margin bounds for neural networks. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 6240–6249. Curran Associates, Inc., 2017.

Peter L. Bartlett, Nick Harvey, Christopher Liaw, and Abbas Mehrabian. Nearly-tight vc-dimension and pseudodimension bounds for piecewise linear neural networks. *Journal of Machine Learning Research*, 20(63):1–17, 2019.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, ICML '09, pp. 41–48, New York, NY, USA, 2009. ACM. ISBN 978-1-60558-516-1. doi: 10.1145/1553374. 1553380.

Jon Louis Bentley. Multidimensional binary search trees used for associative searching. *Commun. ACM*, 18(9):509–517, September 1975. ISSN 0001-0782. doi: 10.1145/361002.361007.

Haw-Shiuan Chang, Erik Learned-Miller, and Andrew McCallum. Active bias: Training more accurate neural networks by emphasizing high variance samples. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 1002–1012. Curran Associates, Inc., 2017.

Yin Cui, Menglin Jia, Tsung-Yi Lin, Yang Song, and Serge Belongie. Class-balanced loss based on effective number of samples. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423.

Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

J. Feng, Q. Teng, X. He, and X. Wu. Accelerating multi-point statistics reconstruction method for porous media via deep learning. *Acta Materialia*, 159:296–308, 2018.

Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep bayesian active learning with image data. In *Proceedings of the 34th International Conference on Machine Learning - Volume 70*, ICML'17, pp. 1183–1192. JMLR.org, 2017.

Henry Gouk, Eibe Frank, Bernhard Pfahringer, and Michael Cree. Regularisation of neural networks by enforcing lipschitz continuity. 04 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2015.

Kurt Hornik, Maxwell Stinchcombe, and Halbert White. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359 – 366, 1989. ISSN 0893-6080. doi: https://doi.org/10.1016/0893-6080(89)90020-8.

Daniel Jakubovitz, Raja Giryes, and Miguel R. D. Rodrigues. Generalization error in deep learning. *CoRR*, abs/1808.01174, 2018.

Lu Jiang, Deyu Meng, Qian Zhao, Shiguang Shan, and Alexander G. Hauptmann. Self-paced curriculum learning. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, AAAI'15, pp. 2694–2700. AAAI Press, 2015. ISBN 0262511290.

Tang Jie and Pieter Abbeel. On a connection between importance sampling and the likelihood ratio policy gradient. In J. D. Lafferty, C. K. I. Williams, J. Shawe-Taylor, R. S. Zemel, and A. Culotta (eds.), *Advances in Neural Information Processing Systems 23*, pp. 1000–1008. Curran Associates, Inc., 2010.

Angelos Katharopoulos and François Fleuret. Not all samples are created equal: Deep learning with importance sampling. In *ICML*, 2018.

Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *International Conference on Learning Representations*, 12 2014.

Ksenia Konyushkova, Raphael Sznitman, and Pascal Fua. Learning active learning from data. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 4225–4235. Curran Associates, Inc., 2017.

Alex Krizhevsky, Vinod Nair, and Geoffrey Hinton. Cifar-10 (canadian institute for advanced research).

M. P. Kumar, Benjamin Packer, and Daphne Koller. Self-paced learning for latent variable models. In J. D. Lafferty, C. K. I. Williams, J. Shawe-Taylor, R. S. Zemel, and A. Culotta (eds.), *Advances in Neural Information Processing Systems 23*, pp. 1189–1197. Curran Associates, Inc., 2010.

Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Yann LeCun and Corinna Cortes. MNIST handwritten digit database. 2010.

Tongliang Liu and Dacheng Tao. Classification with noisy labels by importance reweighting. *IEEE Trans. Pattern Anal. Mach. Intell.*, 38(3):447–461, March 2016. ISSN 0162-8828. doi: 10.1109/TPAMI.2015.2456899.

Tambet Matiisen, Avital Oliver, Taco Cohen, and John Schulman. Teacher-student curriculum learning, 2017.

Behnam Neyshabur, Srinadh Bhojanapalli, David Mcallester, and Nati Srebro. Exploring generalization in deep learning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5947–5956. Curran Associates, Inc., 2017.

Behnam Neyshabur, Srinadh Bhojanapalli, and Nathan Srebro. A PAC-bayesian approach to spectrally-normalized margin bounds for neural networks. In *International Conference on Learning Representations*, 2018.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Haifeng Qian and Mark N. Wegman. L2-nonexpansive neural networks. In *International Conference on Learning Representations*, 2019.

Mengye Ren, Wenyuan Zeng, Bin Yang, and Raquel Urtasun. Learning to reweight examples for robust deep learning. *CoRR*, abs/1803.09050, 2018.

Burr Settles. *Active Learning*. Synthesis Lectures on Artificial Intelligence and Machine Learning. Morgan & Claypool Publishers, 2012.

Abhinav Shrivastava, Abhinav Gupta, and Ross B. Girshick. Training region-based object detectors with online hard example mining. *CoRR*, abs/1604.03540, 2016.

Iulia Turc, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Well-read students learn better: On the importance of pre-training compact models. *arXiv preprint arXiv:1908.08962v2*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 5998–6008. Curran Associates, Inc., 2017.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *International Conference on Learning Representations*, 2019.

Nick Winovich, Karthik Ramani, and Guang Lin. Convpde-uq: Convolutional neural networks with quantified uncertainty for heterogeneous elliptic partial differential equations on varied domains. *Journal of Computational Physics*, 394:263 – 279, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.05.026.

Huan Xu and Shie Mannor. Robustness and generalization. *Machine Learning*, 86(3):391–423, Mar 2012. ISSN 1573-0565. doi: 10.1007/s10994-011-5268-1.

Yinhao Zhu, Nicholas Zabaras, Phaedon-Stelios Koutsourelakis, and Paris Perdikaris. Physics-constrained deep learning for high-dimensional surrogate modeling and uncertainty quantification without labeled data. *Journal of Computational Physics*, 394:56 – 81, 2019. ISSN 0021-9991. doi: https://doi.org/10.1016/j.jcp.2019.05.024.

Appendix A Taylor Based Sampling (TBS)

In this part, we empirically verify that using Taylor expansion to construct a new training distribution has a beneficial impact on the performances of a NN. To this end, we construct a methodology, Taylor Based Sampling (TBS), that generate a new training data set based on the metric introduced in Section **3.3**. First, we recall the formula for the $\{Df_{\epsilon}^n(X_1), ..., Df_{\epsilon}^n(X_N)\}$.

$$Df_{\epsilon}^n(x) = \sum_{1 \leq |\boldsymbol{k}| \leq n} \frac{\|\boldsymbol{\epsilon}\|^k \cdot \| \operatorname{Vect}(\partial^{\boldsymbol{k}} f(x))\|}{\boldsymbol{k}!}. \tag{6}$$

To focus the training set on the regions of interest, i.e. regions of high $\{Df_{\epsilon}^n(X_1), ..., Df_{\epsilon}^n(X_N)\}$, we use this metric to construct a probability density function (pdf). This is possible since $Df_{\epsilon}^n(x) \geq 0$ for all $x \in \mathbf{S}$. It remains to normalize it but in practice it is enough considering a distribution $d \propto Df_{\epsilon}^n$. Here, to approximate d we use a Gaussian Mixture Model (GMM) with pdf d_{GMM} that we fit to $\{Df_{\epsilon}^n(X_1), ..., Df_{\epsilon}^n(X_N)\}$ using the Expectation-Maximization (EM) algorithm. N' new data points $\{\bar{X}_1, ..., \bar{X}_{N'}\}$, can be sampled, with $\bar{X} \sim d_{\text{GMM}}$. Finally, we obtain $\{f(\bar{X}_1), ..., f(\bar{X}_{N'})\}$, add it to $\{f(X_1), ..., f(X_N)\}$ and train our NN on the whole data set.

Taylor Based Sampling (TBS)

Our methodology, which we call Taylor Based Sampling (TBS) is described in Algorithm 2. **Line 1:** The choice criterion of ϵ, the number of Gaussian distribution n_{GMM} and N' is to avoid sparsity of $\{\bar{X}_1, ..., \bar{X}_{N'}\}$ over $\mathbf{S}$. **Line 2:** Without *a priori* information on f, we sample the first points uniformly in a subspace $\mathbf{S}$. **Line 3-7:** We construct $\{Df_{\epsilon}^n(X_1), ..., Df_{\epsilon}^n(X_N)\}$, and then d to be able to sample points accordingly. **Line 8:** Because the support of a GMM is not bounded, some points can be sampled outside $\mathbf{S}$. We discard these points and sample until all points are inside $\mathbf{S}$. This rejection method is equivalent to sampling points from a truncated GMM. **Line 9-10:** We construct the labels and add the new points to the initial data set.

Algorithm 2 Taylor Based Sampling (TBS)

1: **Inputs:** ϵ, N, N', n_{GMM}, n
2: Sample $\{X_1, ..., X_N\}$, with $X \sim \mathcal{U}(\mathbf{S})$
3: **for** $0 \leq k \leq n$ **do**
4:    Compute $\{\partial^{\boldsymbol{k}} f(X_1), ..., \partial^{\boldsymbol{k}} f(X_N)\}$
5: Compute $\{Df_{\epsilon}^n(X_1), ..., Df_{\epsilon}^n(X_N)\}$ using equation 2
6: Approximate $d \sim D_{\epsilon}$ with a GMM using EM algorithm to obtain a density d_{GMM}
7: Sample $\{\bar{X}_1, ..., \bar{X}_{N'}\}$ using rejection method to sample inside $\mathbf{S}$
8: Compute $\{f(\bar{X}_1), ..., f(\bar{X}_{N'})\}$
9: Add $\{f(\bar{X}_1), ..., f(\bar{X}_{N'})\}$ to $\{f(X_1), ..., f(X_N)\}$

Application to simple functions

In order to illustrate the benefits of Taylor based sampling (TBS) compared to a uniform, basic sampling (BS), we apply it to two simple functions: hyperbolic tangent and Runge function. We chose these functions because they are differentiable and have a clear distinction between flat and steep regions. These functions are displayed in Figure 4, as well as the map $x \rightarrow Df_{\epsilon}^n(x)$.

All NN have been implemented in `Python`, with `Tensorflow` Abadi et al. (2015). We use the Python package `scikit-learn` Pedregosa et al. (2011), and more specifically the

Sampling	L_2 error	L_{∞}
	f: Runge ($\times 10^{-2}$)	
BS	1.45 ± 0.62	5.31 ± 0.86
TBS	$\mathbf{1.13 \pm 0.73}$	$\mathbf{3.87 \pm 0.48}$
	f: tanh ($\times 10^{-1}$)	
BS	1.39 ± 0.67	2.75 ± 0.78
TBS	$\mathbf{0.95 \pm 0.50}$	$\mathbf{2.25 \pm 0.61}$

Table 4: Comparison between BS and TBS. The metrics used are the L_2 and L_{∞} errors, displayed with a 95% confidence interval.

`GaussianMixture` class to construct d_{GMM}. The network chosen for this experiment is a Multi Layer Perceptron (MLP) with one layer of 8 neurons, with Relu activation function, that we trained

Figure 4: **Left:** (left axis) Runge function w.r.t x and (right axis) $x \rightarrow Df_\epsilon^2(x)$. Points sampled using TBS are plotted on the x-axis and projected on f. **Right:** Same as left, with hyperbolic tangent function.

alternatively with BS and TBS using Adam optimizer Kingma & Ba (2014) with the defaults tensorflow implementation hyperparameters, and Mean Squared Error loss function. We first sample $\{X_1, ..., X_N\}$ according to a regular grid. To compare the two methods, we add N' additional points sampled using BS to create the BS data set, and then N' other points sampled with TBS to construct the TBS data set. As a result, each data set have the same number of points $(N + N')$. We repeated the method for several values of n, n_{GMM} and ϵ, and finally selected $n = 2$, $n_{\text{GMM}} = 3$ and $\epsilon = 10^{-3}$.

Table 4 summarizes the L_2 and the L_∞ norm of the error of f_θ, obtained at the end of the training phase for $N + N' = 16$, with $N = 8$. Those norms are estimated using a same test data set of 1000 points. The values are the means of the 40 independent experiments displayed with a 95% confidence interval. These results illustrate the benefits of TBS over BS. Table 4 shows that TBS slightly degrades the L_2 error of the NN, but improves its L_∞ error. This may explain the good results of VBSW for classification. Indeed, for a classification task, the accuracy will not be very sensitive to small output variations, since the output is rounded to 0 or 1. However, a high error can induce a misclassification, and the reduction in L_∞ norm limits this risk.

APPLICATION TO AN ODE SYSTEM

We apply TBS to a more realistic case: the approximation of the resolution of the Bateman equations, which is an ODE system :

$$\begin{cases} \partial_t u(t) & = v\boldsymbol{\sigma_a} \cdot \boldsymbol{\eta}(t)u(t), \\ \partial_t \boldsymbol{\eta}(t) & = v\boldsymbol{\Sigma_r} \cdot \boldsymbol{\eta}(t)u(t), \end{cases}, \text{ with initial conditions } \begin{cases} u(0) = u_0, \\ \boldsymbol{\eta}(0) = \boldsymbol{\eta_0}. \end{cases},$$

with $u \in \mathbb{R}^+, \boldsymbol{\eta} \in (\mathbb{R}^+)^M, \boldsymbol{\sigma}_a^T \in \mathbb{R}^M, \boldsymbol{\Sigma}_r \in \mathbb{R}^{M \times M}$. Here, $f : (u_0, \boldsymbol{\eta_0}, t) \rightarrow (u(t), \boldsymbol{\eta}(t))$. For physical applications, M ranges from tens to thousands. We consider the particular case $M = 1$ so that $f : \mathbb{R}^3 \rightarrow \mathbb{R}^2$, with $f(u_0, \eta_0, t) = (u(t), \eta(t))$. The advantage of $M = 1$ is that we have access to an analytic, cheap to compute solution for f. Of course, this particular case can also be solved using a classical ODE solver, which allows us to test it end to end. It can thus be generalized to higher dimensions ($M > 1$).

All NN trainings have been performed in `Python`, with `Tensorflow` Abadi et al. (2015). We used a fully connected NN with hyperparameters chosen using a simple grid search. The final values are: 2 hidden layers, "ReLU" activation function, and 32 units for each layer, trained with the Mean Squared Error (MSE) loss function using Adam optimization algorithm with a batch size of 50000, for 40000 epochs and on $N + N' = 50000$ points, with $N = N'$. We first trained the model for $(u(t), \eta(t)) \in \mathbb{R}$, with an uniform sampling, that we call basic sampling (BS) ($N' = 0$), and then with TBS for several values of n, n_{GMM} and $\epsilon = \epsilon(1, 1, 1)$, to be able to find good values. We finally select $\epsilon = 5 \times 10^{-4}$, $n = 2$ and $n_{\text{GMM}} = 10$. The data points used in this case have

been sampled with an explicit Euler scheme. This experiment has been repeated 50 times to ensure statistical significance of the results.

Table 5 summarizes the MSE, i.e. the L_2 norm of the error of f_θ and L_∞ norm, with $L_\infty(\theta) = \max_{X \in \mathbf{S}}(|f(X) - f_\theta(X)|)$ obtained at the end of the training phase. This last metric is important because the goal in computational physics is not only to be averagely accurate, which is measured with MSE, but to be accurate over the whole input space $\mathbf{S}$. Those norms are estimated using a same test data set of $N_{test} = 50000$ points. The values are the means of the 50 independent experiments displayed with a 95% confidence interval. These results reflect an error reduction of 6.6% for L_2 and of 45.3% for L_∞, which means that TBS mostly improves the L_∞ error of f_θ. Moreover, the L_∞ error confidence intervals do not intersect so the gain is statistically significant for this norm.

Table 5: Comparison between BS and TBS

Sampling	L_2 error $(\times 10^{-4})$	L_∞ $(\times 10^{-1})$	AEG $(\times 10^{-2})$	AEL $(\times 10^{-2})$
BS	1.22 ± 0.13	5.28 ± 0.47	-	-
TBS	$\mathbf{1.14 \pm 0.15}$	$\mathbf{2.96 \pm 0.37}$	2.51 ± 0.07	0.42 ± 0.008

Figure 5: **1a:** $t \to f_\theta(u_0, \eta_0, t)$ for randomly chosen (u_0, η_0), for f_θ obtained with the two samplings. **1b:** $t \to f_\theta(u_0, \eta_0, t)$ for (u_0, η_0) resulting in the highest point-wise error with the two samplings. **2a:** $u_0, \eta_0 \to \max_{0 \le t \le 10} D^n_\epsilon(u_0, \eta_0, t)$ w.r.t. (u_0, η_0). **2b:** $u_0, \eta_0 \to g_{\theta_{BS}}(u_0, \eta_0) - g_{\theta_{TBS}}(u_0, \eta_0)$,

Figure 1a shows how the NN can perform for an average prediction. **Figure 1b** illustrates the benefits of TBS relative to BS on the L_∞ error (Figure 2b). These 2 figures confirm the previous observation about the gain in L_∞ error. Finally, **Figure 2a** displays $u_0, \eta_0 \to \max_{0 \le t \le 10} D^n_\epsilon(u_0, \eta_0, t)$ w.r.t. (u_0, η_0) and shows that D^n_ϵ increases when $U_0 \to 0$. TBS hence focuses on this region. Note that for the readability of this plots, the values are capped to 0.10. Otherwise only few points with high D^n_ϵ are visible. **Figure 2b** displays $u_0, \eta_0 \to g_{\theta_{BS}}(u_0, \eta_0) - g_{\theta_{TBS}}(u_0, \eta_0)$, with $g_\theta : u_0, \eta_0 \to \max_{0 \le t \le 10} \|f(u_0, \eta_0, t) - f_\theta(u_0, \eta_0, t)\|^2_2$ where θ_{BS} and θ_{TBS} denote the parameters obtained after a training with BS and TBS, respectively. It can be interpreted as the error reduction achieved with TBS.

The highest error reduction occurs in the expected region. Indeed, more points are sampled where D_ϵ^n is higher. The error is slightly increased in the rest of $\mathbf{S}$, which could be explained by a sparser sampling on this region. However, as summarized in **Table 1**, the average error loss (AEL) of TBS is around six times lower than the average error gain (AEG), with $AEG = \mathbb{E}_{u_0,\eta_0}(Z\mathbf{1}_{Z>0})$ and $AEL = \mathbb{E}_{u_0,\eta_0}(Z\mathbf{1}_{Z<0})$ where $Z(u_0,\eta_0) = g_{\theta_{BS}}(u_0,\eta_0) - g_{\theta_{TBS}}(u_0,\eta_0)$. In practice, AEG and AEL are estimated using uniform grid integration, and averaged on the 50 experiments.

APPENDIX B: DEMONSTRATIONS

INTUITION BEHIND TAYLOR EXPANSION (SECTION 3.2)

We want to approximate $f : x \to f(x)$, $x \in \mathbb{R}^{n_i}$, $f(x) \in \mathbb{R}^{n_o}$ with a NN f_θ. The goal of the approximation problem can be seen as being able to generalize to points not seen during the training. We thus want the generalization error $\mathcal{J}_X(\theta)$ to be as small as possible. Given an initial data set $\{X_1, ..., X_N\}$ drawn from $X \sim d\mathbb{P}_X$ and $\{f(X_1), ..., f(X_N)\}$, and the loss function L being the squared L_2 error, recall that the integrated error $J_X(\theta)$, its estimation $\widehat{J_X}(\theta)$ and the generalization error $\mathcal{J}_X(\theta)$ can be written:

$$J_X(\theta) = \int_{\mathbf{S}} \|f(x) - f_\theta(x)\| d\mathbb{P}_X,$$
$$\widehat{J_X}(\theta) = \frac{1}{N} \sum_{i=1}^{N} \left(f_\theta(X_i) - f(X_i)\right)^2, \tag{7}$$
$$\mathcal{J}_X(\theta) = J(\theta) - \widehat{J}(\theta),$$

where $\|.\|$ denotes the squared L_2 norm. In the following, we find an upper bound for $\mathcal{J}_X(\theta)$. We start by finding an upper bound for $J(\theta)$ and then for $\mathcal{J}_X(\theta)$ using equation 7.

Let S_i, $i \in \{1, ..., N\}$ be some sub-spaces of a bounded space $\mathbf{S}$ such that $\mathbf{S} = \bigcup_{i=1}^{N} S_i$, $\bigcap_{i=1}^{N} S_i = \emptyset$, and $X_i \in S_i$. Then,

$$J_X(\theta) = \sum_{i=1}^{N} \int_{S_i} \|f(x) - f_\theta(x)\| d\mathbb{P}_X,$$
$$J_X(\theta) = \sum_{i=1}^{N} \int_{S_i} \|f(X_i + x - X_i) - f_\theta(x)\| d\mathbb{P}_X.$$

Suppose that $n_i = n_o = 1$ and f twice differentiable. Let $|\mathbf{S}| = \int_{\mathbf{S}} d\mathbb{P}_X$. The volume $|\mathbf{S}| = 1$ since $d\mathbb{P}_X$ is a probability measure, and therefore $|S_i| < 1$ for all $i \in \{1, ..., N\}$. Using Taylor expansion at order 2, and since $|S_i| < 1$ for all $i \in \{1, ..., N\}$

$$J_X(\theta) = \sum_{i=1}^{N} \int_{S_i} \|f(X_i) + f'(X_i)(x - X_i) + \frac{1}{2}f''(X_i)(x - X_i)^2 - f_\theta(x) + O((x - X_i)^3)\| d\mathbb{P}_X.$$

To find an upper bound for $J(\theta)$, we can first find an upper bound for $|A_i(x)|$, with $A_i(x) = f(X_i) + f'(X_i)(x - X_i) + \frac{1}{2}f''(X_i)(x - X_i)^2 - f_\theta(x) + O((x - X_i)^3)$.

NN f_θ is $K_\theta-$Lipschitz, so since $\mathbf{S}$ is bounded (so are S_i), for all $x \in S_i$, $|f_\theta(x) - f_\theta(X_i)| \leq K_\theta|x - X_i|$. Hence,

$$f_\theta(X_i) - K_\theta|x - X_i| \leq f_\theta(x) \leq f_\theta(X_i) + K_\theta|x - X_i|,$$
$$- f_\theta(X_i) - K_\theta|x - X_i| \leq -f_\theta(x) \leq -f_\theta(X_i) + K_\theta|x - X_i|,$$

$$f(X_i) + f'(X_i)(x - X_i) + \frac{1}{2}f''(X_i(x - X_i)^2) - f_\theta(X_i) - K_\theta|x - X_i| + O((x - X_i)^3)$$

$$\leq A_i(x) \leq f(X_i) + f'(X_i)(x - X_i) + \frac{1}{2}f''(X_i)(x - X_i)^2 - f_\theta(X_i) + K_\theta|x - X_i| + O((x - X_i)^3),$$

$$A_i(x) \leq f(X_i) - f_\theta(X_i) + f'(X_i)(x - X_i) + \frac{1}{2}f''(X_i)(x - X_i)^2 + K_\theta|x - X_i| + O((x - X_i)^3).$$

And finally, using triangular inequality,

$$\boxed{A_i(x) \leq |f(X_i) - f_\theta(X_i)| + |f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i| + O(|x - X_i|^3).}$$

Now, suppose that $\|.\|$ is the squared L_2 norm. Then,

$$J_X(\theta) = \sum_{i=1}^N \int_{S_i} \|f(X_i) + f'(X_i)(x - X_i) + \frac{1}{2}f''(X_i)(x - X_i)^2 - f_\theta(x) + O(|x - X_i|^3)\| d\mathbb{P}_X,$$

$$J_X(\theta) \leq \sum_{i=1}^N \int_{S_i} \left[\left(|f(X_i) - f_\theta(X_i)|\right) + \left(|f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right) \right.$$
$$\left. + O(|x - X_i|^3) \right]^2 d\mathbb{P}_X,$$

$$J_X(\theta) \leq \sum_{i=1}^N \int_{S_i} \left[|f(X_i) - f_\theta(X_i)|^2 \right.$$
$$+ 2|f(X_i) - f_\theta(X_i)|\left(|f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right)$$
$$\left. + \left[\left(|f'(X_i)||x - X_i|\right) + \left(\frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right)\right]^2 + O(|x - X_i|^3) \right] d\mathbb{P}_X,$$

$$J_X(\theta) \leq \sum_{i=1}^N \int_{S_i} \left[|f(X_i) - f_\theta(X_i)|^2 \right.$$
$$+ 2|f(X_i) - f_\theta(X_i)|\left(|f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right)$$
$$+ \left[|f'(X_i)|^2|x - X_i|^2 \right.$$
$$+ 2|f'(X_i)||x - X_i|\left(\frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right)$$
$$\left. + \left(\frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right)^2\right]$$
$$\left. + O(|x - X_i|^3) \right] d\mathbb{P}_X,$$

$$J_X(\theta) \leq \sum_{i=1}^N \int_{S_i} \left[|f(X_i) - f_\theta(X_i)|^2 \right.$$
$$+ 2|f(X_i) - f_\theta(X_i)|\left(|f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i|\right)$$
$$\left. + \left[|f'(X_i)|^2|x - X_i|^2 + 2K_\theta|f'(X_i)||x - X_i|^2 + K_\theta^2|x - X_i|^2\right] + O(|x - X_i|^3) \right] d\mathbb{P}_X,$$

$$J_X(\theta) \leq \sum_{i=1}^{N} \int_{S_i} \left[|f(X_i) - f_\theta(X_i)|^2 \right.$$

$$+ 2|f(X_i) - f_\theta(X_i)| \left(|f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i| \right)$$

$$\left. + \left(|f'(X_i)| + K_\theta \right)^2 |x - X_i|^2 + O(|x - X_i|^3) \right] d\mathbb{P}_X.$$

Hornik's theorem Hornik et al. (1989) states that given a norm $\|.\|_{p,\mu} =$ such that $\|f\|_{p,\mu}^p = \int_{\mathbf{S}} |f(x)|^p d\mu(x)$, with $d\mu$ a probability measure, for all ϵ, there exists θ such that $\|f(x) - f_\theta(x)\|_{p,\mu}^p < \epsilon$.

Let $\epsilon_i = O(|S_i|^3)$ for all $i \in \{1, ..., N\}$, $p = 1$ and $d\mu = \frac{1}{N} \sum_{i=1}^{N} \delta(x - X_i)$. Then, $\widehat{J_X}(\theta) = O(|S_i|^4)$ for all $i \in \{1, ..., N\}$ and $J_X(\theta) = \mathcal{J}_X(\theta) + O(|S_i|^4)$. Hence,

$$\mathcal{J}_X(\theta) \leq \sum_{i=1}^{N} \int_{S_i} \left[(|f'(X_i)| + K_\theta)^2 |x - X_i|^2 d\mathbb{P}_X \right] + O(|S_i|^4),$$

because $\int_{S_i} \left[|f(X_i) - f_\theta(X_i)|^2 + 2|f(X_i) - f_\theta(X_i)| \left(|f'(X_i)||x - X_i| + \frac{1}{2}|f''(X_i)||x - X_i|^2 + K_\theta|x - X_i| \right) \right] d\mathbb{P}_X = O(|S_i|^4)$. Finally,

$$\mathcal{J}_X(\theta) \leq \sum_{i=1}^{N} (|f'(X_i)| + K_\theta)^2 \frac{|S_i|^3}{3} + O(|S_i|^4), \tag{8}$$

where $|S_i|$ is the volume of S_i. We see that on the regions where $f'(X_i) + K_\theta$ is higher, quantity $|S_i|$ has a stronger impact on the GB. Then, since $|S_i|$ can be seen as a metric for the local density of the data set (the smaller $|S_i|$ is, the denser the data set is), the Generalization Bound (GB) can be reduced more efficiently by adding more points around X_i in these regions. This bound also involves K_θ, the Lipschitz constant of the NN, which has the same impact as $f'(X_i)$. It also illustrates the link between the Lipschitz constant and the generalization error, which has been pointed out by several works like, for instance, Gouk et al. (2018), Bartlett et al. (2017) and Qian & Wegman (2019).

PROBLEM 1: UNAVAILABILITY OF DERIVATIVES (SECTION 4.1)

In this paragraph, we consider $n_i > 1$ but $n_o = 1$. The following derivations can be extended to $n_o > 1$ by applying it to f element-wise. Let $\boldsymbol{\epsilon} \sim \mathcal{N}(0, \epsilon \mathbf{1}_{n_i})$ with $\epsilon \in \mathbb{R}^+$ and $\boldsymbol{\epsilon} = (\epsilon_1, ..., \epsilon_{n_i})$, i.e. $\epsilon_i \sim \mathcal{N}(0, \epsilon)$. Using Taylor expansion on f at order 2 gives

$$f(x + \boldsymbol{\epsilon}) = f(x) + \nabla_x f(x) \cdot \boldsymbol{\epsilon} + \frac{1}{2} \boldsymbol{\epsilon}^T \cdot \mathbb{H}_x f(x) \cdot \boldsymbol{\epsilon} + O(\|\boldsymbol{\epsilon}\|_2^3).$$

With $\nabla_x f$ and $\mathbb{H}_x f(x)$ the gradient and the Hessian of f w.r.t. x. We now compute $Var(f(X + \boldsymbol{\epsilon}))$ and make $Df_\epsilon^2(x) = \epsilon \|\nabla_x f(x)\|_F^2 + \frac{1}{2} \epsilon^2 \|\mathbb{H}_x f(x)\|_F^2$ appear in its expression to establish a link between these two quantities.

$$Var(f(x + \boldsymbol{\epsilon})) = Var \left(f(x) + \nabla_x f(x) \cdot \boldsymbol{\epsilon} + \frac{1}{2} \boldsymbol{\epsilon}^T \cdot \mathbb{H}_x f(x) \cdot \boldsymbol{\epsilon} + O(\|\boldsymbol{\epsilon}\|_2^3) \right),$$

$$= Var \left(\nabla_x f(x) \cdot \boldsymbol{\epsilon} + \frac{1}{2} \boldsymbol{\epsilon}^T \cdot \mathbb{H}_x f(x) \cdot \boldsymbol{\epsilon} \right) + O(\|\boldsymbol{\epsilon}\|_2^3).$$

Since $\epsilon_i \sim \mathcal{N}(0, \epsilon)$, $x = (x_1, ..., x_{n_i})$ and $\frac{\partial^2 f}{\partial x_i x_j}(X)$ be the cross derivatives of f w.r.t. x_i and x_j.

$$\nabla_x f(x) \cdot \boldsymbol{\epsilon} + \frac{1}{2} \boldsymbol{\epsilon}^T \cdot \mathbb{H}_x f(x) \cdot \boldsymbol{\epsilon} = \sum_{i=1}^{n_i} \epsilon_i \frac{\partial f}{\partial x_i}(x) + \frac{1}{2} \sum_{j=1}^{n_i} \sum_{k=1}^{n_i} \epsilon_j \epsilon_k \frac{\partial^2 f}{\partial x_j x_k}(x),$$

$$Var\Big(\nabla_x f(x)\cdot\boldsymbol{\epsilon}+\frac{1}{2}\boldsymbol{\epsilon}^T\cdot\mathbb{H}_x f(x)\cdot\boldsymbol{\epsilon}\Big)=Var\Big(\sum_{i=1}^{n_i}\epsilon_i\frac{\partial f}{\partial x_i}(x)+\frac{1}{2}\sum_{j=1}^{n_i}\sum_{k=1}^{n_i}\epsilon_j\epsilon_k\frac{\partial^2 f}{\partial x_j x_k}(x)\Big),$$

$$=\sum_{i_1=1}^{n_i}\sum_{i_2=1}^{n_i}Cov\Big(\epsilon_{i_1}\frac{\partial f}{\partial x_{i_1}}(x),\epsilon_{i_2}\frac{\partial f}{\partial x_{i_2}}(x)\Big),$$

$$+\frac{1}{4}\sum_{j_1=1}^{n_i}\sum_{k_1=1}^{n_i}\sum_{j_2=1}^{n_i}\sum_{k_2=1}^{n_i}Cov\Big(\epsilon_{j_1}\epsilon_{k_1}\frac{\partial^2 f}{\partial x_{j_1} x_{k_1}}(x),\epsilon_{j_2}\epsilon_{k_2}\frac{\partial^2 f}{\partial x_{j_2} x_{k_2}}(x)\Big)$$

$$+\sum_{i=1}^{n_i}\sum_{j=1}^{n_i}\sum_{k=1}^{n_i}Cov\Big(\epsilon_i\frac{\partial f}{\partial x_i}(x),\epsilon_j\epsilon_k\frac{\partial^2 f}{\partial x_j x_k}(x)\Big),$$

$$=\sum_{i_1=1}^{n_i}\sum_{i_2=1}^{n_i}\frac{\partial f}{\partial x_{i_1}}(x)\frac{\partial f}{\partial x_{i_2}}(x)Cov\Big(\epsilon_{i_1},\epsilon_{i_2}\Big)$$

$$+\frac{1}{4}\sum_{j_1=1}^{n_i}\sum_{k_1=1}^{n_i}\sum_{j_2=1}^{n_i}\sum_{k_2=1}^{n_i}\frac{\partial^2 f}{\partial x_{j_1} x_{k_1}}(x)\frac{\partial^2 f}{\partial x_{j_2} x_{k_2}}(x)Cov\Big(\epsilon_{j_1}\epsilon_{k_1},\epsilon_{j_2}\epsilon_{k_2}\Big)$$

$$+\sum_{i=1}^{n_i}\sum_{j=1}^{n_i}\sum_{k=1}^{n_i}\frac{\partial f}{\partial x_i}(x)\frac{\partial^2 f}{\partial x_j x_k}(x)Cov\Big(\epsilon_i,\epsilon_j\epsilon_k\Big).$$

In this expression, we have to assess three quantities: $Cov(\epsilon_{i_1},\epsilon_{i_2})$, $Cov(\epsilon_i,\epsilon_j\epsilon_k)$ and $Cov(\epsilon_{j_1}\epsilon_{k_1},\epsilon_{j_2}\epsilon_{k_2})$.

First, since $(\epsilon_1,...,\epsilon_{n_i})$ are i.i.d.,

$$Cov\Big(\epsilon_{i_1},\epsilon_{i_2}\Big)=\begin{cases}Var(\epsilon_i)=\epsilon\text{ if }i_1=i_2=i,\\0\text{ otherwise.}\end{cases}.$$

To assess $Cov(\epsilon_i,\epsilon_j\epsilon_k)$, three cases have to be considered.

- If $i=j=k$, because $\mathbb{E}[\epsilon_i^3]=0$,
$$Cov(\epsilon_i,\epsilon_j\epsilon_k)=Cov(\epsilon_i,\epsilon_i^2),$$
$$=\mathbb{E}[\epsilon_i^3]-\mathbb{E}[\epsilon_i]\mathbb{E}[\epsilon_i^2],$$
$$=0.$$

- If $i=j$ or $i=k$ (we consider $i=k$, and the result holds for $i=j$ by commutativity),
$$Cov(\epsilon_i,\epsilon_j\epsilon_k)=Cov(\epsilon_i,\epsilon_i\epsilon_j),$$
$$=\mathbb{E}[\epsilon_i^2\epsilon_j]-\mathbb{E}[\epsilon_i]\mathbb{E}[\epsilon_i\epsilon_j],$$
$$=\mathbb{E}[\epsilon_i^2]\mathbb{E}[\epsilon_j],$$
$$=0.$$

- If $i\neq j$ and $i\neq k$, ϵ_i and $\epsilon_j\epsilon_k$ are independent and so $Cov(\epsilon_i,\epsilon_j\epsilon_k)=0$.

Finally, to assess $Cov(\epsilon_{j_1}\epsilon_{k_1},\epsilon_{j_2}\epsilon_{k_2})$, four cases have to be considered:

- If $j_1=j_2=k_1=k_2=i$,
$$Cov(\epsilon_{j_1}\epsilon_{k_1},\epsilon_{j_2}\epsilon_{k_2})=Var(\epsilon_i^2),$$
$$=2\epsilon^2.$$

- If $j_1=k_1=i$ and $j_2=k_2=j$, $Cov(\epsilon_{j_1}\epsilon_{k_1},\epsilon_{j_2}\epsilon_{k_2})=Cov(\epsilon_i^2,\epsilon_j^2)=0$ since ϵ_i^2 and ϵ_j^2 are independent.

- If $j_1 = j_2 = j$ and $k_1 = k_2 = k$,

$$Cov(\epsilon_{j_1}\epsilon_{k_1}, \epsilon_{j_2}\epsilon_{k_2}) = Var(\epsilon_j\epsilon_k),$$
$$= Var(\epsilon_j)Var(\epsilon_k),$$
$$= \epsilon^2.$$

- If $j_1 \neq k_1, j_2$ and k_2,

$$Cov(\epsilon_{j_1}\epsilon_{k_1}, \epsilon_{j_2}\epsilon_{k_2}) = \mathbb{E}[\epsilon_{j_1}\epsilon_{k_1}\epsilon_{j_2}\epsilon_{k_2}] - \mathbb{E}[\epsilon_{j_1}\epsilon_{k_1}]\mathbb{E}[\epsilon_{j_2}\epsilon_{k_2}],$$
$$= \mathbb{E}[\epsilon_{j_1}]\mathbb{E}[\epsilon_{k_1}\epsilon_{j_2}\epsilon_{k_2}] - \mathbb{E}[\epsilon_{j_1}]\mathbb{E}[\epsilon_{k_1}]\mathbb{E}[\epsilon_{j_2}\epsilon_{k_2}],$$
$$= 0.$$

All other possible cases can be assessed using the previous results, commutativity and symmetry of Cov operator. Hence,

$$Var\left(\nabla_x f(x) \cdot \boldsymbol{\epsilon} + \frac{1}{2}\boldsymbol{\epsilon}^T \cdot \mathbb{H}_x f(x) \cdot \boldsymbol{\epsilon}\right) = \sum_{i_1=1}^{n_i}\sum_{i_2=1}^{n_i} \frac{\partial f}{\partial x_{i_1}}(x)\frac{\partial f}{\partial x_{i_2}}(x)Cov\left(\epsilon_{i_1}, \epsilon_{i_2}\right)$$
$$+ \frac{1}{4}\sum_{j_1=1}^{n_i}\sum_{k_1=1}^{n_i}\sum_{j_2=1}^{n_i}\sum_{k_2=1}^{n_i} \frac{\partial^2 f}{\partial x_{j_1}x_{k_1}}(x)\frac{\partial^2 f}{\partial x_{j_2}x_{k_2}}(x)Cov\left(\epsilon_{j_1}\epsilon_{k_1}, \epsilon_{j_2}\epsilon_{k_2}\right),$$
$$= \sum_{i=1}^{n_i} \epsilon\frac{\partial f^2}{\partial x_i}(x) + \frac{1}{2}\sum_{j=1}^{n_i}\sum_{k=1}^{n_i} \epsilon^2\frac{\partial^2 f^2}{\partial x_j x_k}(x),$$
$$= \epsilon\|\nabla_x f(x)\|_F^2 + \frac{1}{2}\epsilon^2\|\mathbb{H}_x f(x)\|_F^2,$$
$$= Df_\epsilon^2(x).$$

And finally,

$$\boxed{Var(f(x + \epsilon)) = Df_\epsilon^2(x) + O(\|\epsilon\|_2^3)} \tag{9}$$

If we consider $\widehat{Df^2}_\epsilon(x)$ as defined in (4), on section 3.1 of the main document, $\widehat{Df^2}_\epsilon(x) \underset{k\to\infty}{\to} Var(f(x + \epsilon))$. Since $Var(f(x + \epsilon)) = Df_\epsilon^2(x) + O(|\epsilon|_2^3)$, $\widehat{Df^2}_\epsilon(x)$ is a biased estimator of $Df_\epsilon^2(x)$, with bias $O(|\epsilon|_2^3)$. Hence, when $\epsilon \to 0$, $\widehat{Df^2}_\epsilon(x)$ becomes an unbiased estimator of $Df_\epsilon^2(x)$.

APPENDIX C: HYPERPARAMETERS

This appendix is split into two parts. First, we describe the results of the experiments on the hyperparameters search of Boston Housing (BH) and Breast Cancer (BC) data sets (section 4.1.). The second part is a list of final hyperparameters values chosen for the experiments of the main paper.

EXPERIMENTS ON BOSTON HOUSING AND BREAST CANCER DATA SETS

For BH and BC experiments, we conduct a grid search for VBSW on the values of m and k. As a reminder, m is the ratio between the highest and the lowest weights, and k is the number of neighbor points used to compute the local variance. We train a linear model for BH and a MLP with 30 units for BC with VBSW on a grid of 20 values of m equally distributed between 2 and 100 and 20 values of k equally distributed between 10 and 50. As a result, we train the model on 400 pairs of (m, k) values, and with 10 different random seeds for each pair.

Figure 6: Color map of the error, with respect to m and k. **Left:** BH data set, for the mean of the MSE accross 10 different seeds and **right:** BC data set, for the mean of $1 - acc$ across these seeds. Blue is lower.

These experiments, illustrated in Figure 6 shows that the influence of m and k on the performances of the model can be different. For BH data set, low values of k clearly lead to poorer performances. Hyperparameter m seems to have less impact, although it should be chosen not too far from its lowest value, 2. For BC data set, at the contrary, the best performances are obtained for low values of k, while m could be chosen in high values. These experiments highlight that the impact of m and k can be different between classification and regression, but it could also be different depending on the data set. Hence, we recommend considering these hyperparameters like many other involved in DL, and to select their values using classical hyperparameters optimization techniques.

PAPER HYPERPARAMETERS VALUES

The values chosen for the hyperparameters of the paper experiments are gathered in Table 6. For ADAM optimizer hyperparameters, we kept the default values of Keras implementation. We chose these hyperparameters after simple grid searches.

Experiment	m	k	learning rate	batch size	epochs	optimizer	random seeds
double moon	100	20	1×10^{-3}	100	10000	SGD	50
Boston housing	8	35	5×10^{-4}	404	50000	ADAM	10
Breast Cancer	50	35	5×10^{-2}	455	250000	ADAM	10
MNIST	40	20	1×10^{-3}	25	25	ADAM	40
Cifar10	40	20	1×10^{-3}	25	25	ADAM	50
RTE	20	10	3×10^{-4}	8	10000	ADAM	50
STS-B	30	30	3×10^{-4}	8	10000	ADAM	50
MRPC	75	25	3×10^{-4}	16	10000	ADAM	50

Table 6: Paper experiments hyperparameters values