On the Role of Computation in Reinforcement Learning

Keywords: Reinforcement Learning, Recurrent Networks, Horizon generalization, Computation theory

Summary

How does the amount of compute available to a reinforcement learning (RL) policy affect its learning? Can policies using a fixed amount of parameters, still benefit from additional compute? The standard RL framework does not provide a language to answer these questions formally. Empirically, deep RL policies are often parameterized as neural networks with static architectures, conflating the amount of compute and the number of parameters. In this paper, we formalize compute bounded policies and prove that policies which use more compute can solve problems and generalize to longer-horizon tasks that are outside the scope of policies with less compute. Building on prior work in algorithmic learning and model-free planning, we propose a minimal architecture that can use a variable amount of compute. Our experiments complement our theory. On a set 31 different tasks spanning online and offline RL, we show that (1) this architecture achieves stronger performance simply by using more compute, and (2) stronger generalization on longer-horizon test tasks compared to standard feedforward networks or deep residual network using up to 5 times more parameters

Contribution(s)

1. In this work we advocate for a computational view of RL, where computation time and parameter count (memory) are distinct axes. The first primary contribution of our paper is to take a step towards formalizing this view. We formulate RL policies as bounded models of computation and prove that there exist MDPs where policies with more compute time are arbitrarily better than policies with less compute. We also prove that there exist MDPs where policies with less compute can overfit on the training tasks and fail to generalize, whereas policies with more compute can generalize to longer-horizon tasks during evaluatio
   Context: The idea of using

2. The second primary contribution of our work is to empirically show that RL policies which use more compute can achieve stronger performance as well as stronger generalization to longer-horizon unseen tasks.
   Context: None

On the Role of Computation in Reinforcement Learning

Anonymous authors

Abstract

How does the amount of compute available to a reinforcement learning (RL) policy affect its learning? Can policies using a fixed amount of parameters, still benefit from additional compute? The standard RL framework does not provide a language to answer these questions formally. Empirically, deep RL policies are often parameterized as neural networks with static architectures, conflating the amount of compute and the number of parameters. In this paper, we formalize compute bounded policies and prove that policies which use more compute can solve problems and generalize to longer-horizon tasks that are outside the scope of policies with less compute. Building on prior work in algorithmic learning and model-free planning, we propose a minimal architecture that can use a variable amount of compute. Our experiments complement our theory. On a set 31 different tasks spanning online and offline RL, we show that (1) this architecture achieves stronger performance simply by using more compute, and (2) stronger generalization on longer-horizon test tasks compared to standard feedforward networks or deep residual network using up to 5 times more parameters

1 Introduction

The standard view in reinforcement learning (RL) is to treat RL policies as static functions that map states to actions. Policies typically spend a fixed amount of compute, regardless of the complexity of making the correct decision in the underlying state. For example, for a humanoid robot, the action of where to move the right foot is easy, but figuring out how to efficiently pack furniture in a truck requires more deliberation.

In RL, this limitation is often solved by citing Moore's law (Moore, 1965) and simply scaling the number of policy parameters. But the compute required to make good decisions in different situations can span many orders of magnitude; using a static massive policy with a large number of parameters is wasteful. Additionally, as compute becomes cheap, the complexity of the world and sensory data also increase (Javed & Sutton, 2024).

In this work we advocate for a computational view of RL, where computation time and parameter count (memory) are distinct axes. The first primary contribution of our paper is to take a step towards formalizing this view. We formulate RL policies as bounded models of computation and prove that there exist MDPs where policies with more compute time are arbitrarily better than policies with less compute. Intuitively, policies with more compute time should learn more generalizing solutions, where static or computationally limited policies might instead learn heuristics which overfit their training (Zhou et al., 2023; 2024b). In this vein, we prove that there exist MDPs where policies with less compute can overfit on the training tasks and fail to generalize, whereas policies with more compute can generalize to longer-horizon tasks during evaluation (Myers et al., 2025).

The second primary contribution of our work is to empirically show that RL policies which use more compute can achieve stronger performance as well as stronger generalization to longer-horizon

37 *unseen tasks*. Indeed, prior empirical work has also recognized the importance of using more com-
38 putation to improve the performance of RL agents. Model-Based RL attempts this by learning a
39 transition model and performing search using a planning algorithm (Sutton, 1991). Prior work in
40 model-free planning uses various inductive biases like tree-search (Farquhar et al., 2018; Coulom,
41 2007) or latent space planning (Oh et al., 2017; Silver et al., 2017) to train policies which generate
42 solutions iteratively. Notably Guez et al. (2018); Tamar et al. (2016) have shown that using iterative
43 architectures for RL policies with purely model-free RL objectives can display planning-like behav-
44 ior (Bush et al., 2025). One limitation of these works is that the architectures proposed are restricted
45 to tasks with a complete top down view. In our work, we propose a minimal recurrent architecture
46 that can be trained on any task, to use a variable amount of compute with the same number of param-
47 eters (Figure 1). On over 30 tasks, we show that these recurrent policies improve significantly when
48 using more recurrent steps. When trained to reach only nearby goals, we show that these policies
49 outperform residual networks with 5 times more parameters when evaluated on unseen far-away
50 goals. We also propose a way to estimate a numerical measure of the *value of compute*, analogous
51 to the value of information studied in POMDPs. We provide a detailed comparison with prior work
52 in ()

2 Preliminaries

Goal-Conditioned Reinforcement Learning. The agent operates in a goal conditioned MDP
$\mathcal{M}$ (Kaelbling, 1993), where $s_t \in \mathcal{S}$ are states, $a_t \in \mathcal{A}$ are actions and $g \in \mathcal{G}$ are goals. Be-
fore every episode, a start state and a goal is sampled from a task distribution $p(s_0, g)$. At every
timestep, the agent samples an action using a goal-conditioned policy $\pi(a \mid s, g)$ and the next state
is sampled using the transition dynamics $p(s_{t+1} \mid s_t, a_t)$. At each timestep the agent receives a
reward $r_g(s, a)$ from the MDP. The objective of a GCRL algorithm is to maximize the discounted
sum of rewards:

$$J(\pi) = \mathbb{E}_{\substack{p(s_0,g),\pi(a_t,s_t,g), \\ p(s_{t+1}|s_t,a_t)}} \left[\sum_{t=0}^{H-1} \gamma^t r_g(s_t, a_t) \right] \tag{1}$$

Note that the task distribution could be different during evaluation $p_{\text{train}}(s_0, g) \neq p_{\text{test}}(s_0, g)$. The
value function of a policy $v_\pi(s)$ is defined as $\mathbb{E}_{\pi,p} \left[\sum_{t=0}^{H-1} \gamma^t r(s_t) \mid s_0 = s \right]$. When the reward is
sparse (of the form r_+ upon reaching the goal and r_- elsewhere) and the transitions are determinis-
tic, we will use the term horizon of a task (s, g) to mean the minimum number of timesteps that are
needed to reach the goal g from state s. Lastly, we also use deterministic policies which are special
policies which output an action instead of a distribution, i.e., $a = \pi(s, g)$.

Computational theory. For our theoretical results, we will represent an RL policy using a Turing
machine. A Turing machine M is defined by its set of states, input and tape alphabets, a transition
function, and an accept and reject state (Sipser, 2006). In our work, the input alphabet is always
$\{0, 1\}$ and the input is a binary string s. We denote the length of this string as $|s|$. We use w^K to
denote the string that repeats w, k times. w^* denotes the set $\{w^k \text{ for } k \in \mathbb{N}\}$, and ϵ to denote the
empty string. We only focus on single-tape deciding machines that take an input string $s \in \{0, 1\}^*$
and always transition to either the accept ($M(s) = 1$) or reject state ($M(s) = 0$) and only use
a single-tape for their computation. We also use $\mathcal{O}(\cdot)$ and $o(\cdot)$ for the big-o and little-o notation
respectively. Lastly, a function $t : \mathbb{N} \to \mathbb{N}$, where $t(n)$ is at least $\mathcal{O}(n \log n)$, is called time-
constructible if the function that maps the string 1^n to the binary representation of $t(n)$ is computable
in time $O(t(n))$ (Sipser, 2006). Time-constructibility is a technical property of time-functions, that
is required for the proofs, we do not refer to it in our experiments. Please refer Sipser (2006) for
additional details on computation theory, all of our proofs use the same terminology.

3 On the complexity of behaving optimally

In this section, we introduce a framework for thinking about the compute used by deterministic policies in the context of complexity theory (Sipser, 2006). For all the theoretical results, we assume that the MDP is deterministic and the action space is binary, noting that all discrete action MDPs can be reduced to another MDP with binary action spaces. We first introduce two definitions.

Definition 1 (Time bounded Turing machines). (Hartmanis & Stearns, 1965) Let M be a Turing machine that halts on all inputs $s \in \{0,1\}^*$ and $t : \mathbb{N} \to \mathbb{N}$ be function. We say that M is t-bounded if it decides all inputs s in at most $t(|s|)$ steps.

Definition 2 (Time bounded policies and policy classes). A deterministic policy $\pi(s)$ is said to be t-bounded if there exists a t-bounded Turing machine such that $\pi(s) = 1$ if $M(s)$ accepts and $\pi(s) = 0$ if $M(s)$ rejects, for all $s \in \{0,1\}^*$. Here s is the binary encoding of the state. We define a policy class Π_t, as the set of all deterministic policies that are t-bounded.

Assumption 1. For all policies we consider $\pi \in \Pi_t$, the description length of its corresponding Turing machine under a canonical representation scheme is always bounded by a constant, i.e., $|\langle M \rangle| < K_{max} \in \mathbb{N}$. K_{max} can be as large as possible, but our theoretical results do require it to be no smaller than the length of a particular universal Turing machine.

In the real world this assumption is always true, as any feasible set of policies must rely on a finite amount of memory to store its parameters and code. Our main theoretical result is that policy classes with greater computational budgets are capable of solving a broader range of problems:

Theorem 3.1 (Policy Hierarchy Theorem). *Let $g(n)$ and $t(n)$ be time-constructible functions such that $g(n) \in o(t(n)/\log t(n))$. Then there exists an MDP and a function $f(n) \in \mathcal{O}(t(n))$ such that:*

1. The optimal policy π^* belongs to the class Π_f.

2. For any policy $\pi \in \Pi_g$, $J(\pi)$ is arbitrarily lower than $J(\pi^*)$.

This theorem tells us that there exist tasks on which policy classes that have more compute perform arbitrarily better than policies with less compute. See Appendix A for the proof, which uses the time hierarchy theorems (Sipser, 2006) and Assumption 1 to construct the desired MDP. Our experiments will empirically show that policies with additional compute can achieve higher returns in practice (Section 5). This result is interesting because it suggests that, under computational constraints, standard results about MDPs may no longer hold. For example, computation constraints may be reflected as partial observability, potentially explaining why prior experimental work has used non-Markov policies for solving "fully observed" tasks (Kapturowski et al., 2019; OpenAI et al., 2019; Petrenko et al., 2023). While recent work has argued that additional computation ("thinking" or "reasoning") is primarily useful because it enables policies to leverage multi-task pre-training (Hanna & Corrado, 2025a), Theorem 3.1 shows that the value of additional computation does not depend on multitask learning nor on pre-training.

Importantly, additional computation need not translate to larger hypotheses classes with weaker generalization. Rather, policies that use additional compute can provably exhibit stronger generalization. The intuition, which we formalize below, is that a certain amount of compute capacity is required to represent the correct algorithm, and compute-constrained models will instead learn heuristics.

Theorem 3.2 (Long Horizon Generalization). *Let $g(n)$ and $t(n)$ be time-constructible functions such that $g(n) \in o(t(n)/\log t(n))$. Then there exists a goal conditioned MDP and a function $f(n) \in \mathcal{O}(t(n))$ such that:*

1. The optimal goal conditioned policy π^* belongs to the class Π_f.

2. For all training tasks $(s_{train}, g_{train} \sim p_{train}(s,g))$, the best g-bounded policy $\pi_g^* \in \Pi_g$ has the same value function as π^*. But for infinitely many longer-horizon test tasks, π_g^* is arbitrarily worse than π^*.

127 The proof can be found in Appendix A. This theorem implies that a policy class with less com-
128 pute can overfit on the training tasks of a more difficult problem and fail to generalize to longer-
129 horizon tasks during evaluation. A simple example of this is language models being unable to solve
130 GSM8K (Cobbe et al., 2021) problems in a single forward pass (constant compute), but solving
131 them when provided with more compute using chain of thought (Wei et al., 2022b). In our exper-
132 iments (Section 5.4), we show that RL policies using more compute generalize to longer-horizon
133 tasks during evaluation.

4 A Minimal recurrent architecture for studying the benefits of computation

135 The primary aim of this paper is to theoretically char-
136 acterize when and how recurrent computation can
137 aid reinforcement learning (Section 3). To comple-
138 ment our theory, we propose a simple recurrent ar-
139 chitecture that we will use for representing value
140 functions and policies (see Figure 1). The recur-
141 rent block we propose is called an interpolation re-
142 current unit (IRU). The IRU is heavily inspired by
143 components of the LSTM (Hochreiter & Schmidhu-
144 ber, 1997) and GRU (Cho et al., 2014) architectures,
145 though we have stripped away some components in
146 attempts to make it as simple as possible while reca-
147 pitulating the experimental phenomenon. The work-
148 ings of the IRU and the details of our architecture are
149 explained in detail in section B. This recurrent archi-
150 tecture allows us to train the same set of weights with

Figure 1: **Complete recurrent architec-
ture.** This figure demonstrates the archi-
tecture for training policies/value functions.
The recurrent block we use is an IRU sec-
tion 4.

151 different amount of computation steps in the forward pass of the network.

5 Experiments

153 The main goal of our experiments is to complement our theory and understand the impact of us-
154 ing additional recurrent steps on policy performance (Theorem 3.1) and generalization on longer-
155 horizon tasks (Theorem 3.2). We evaluate the IRU architecture presented in Section 4 in both con-
156 tinuous and discrete settings. We describe the tasks and baselines in Section 5.1 and Section 5.2,
157 and answer the following questions in the subsequent sections:

158 • Do more recurrent steps lead to better-performing policies? (Section 5.3)

159 • Does the recurrent architecture enable horizon generalization? (Section 5.4)

160 • How to measure the value of additional compute? (Section 5.5)

161 • Why does more compute improve performance? (Section 5.6)

162 • How do different recurrent blocks perform with additional compute? (Section 5.7)

5.1 Tasks

164 To evaluate the proposed architecture across a wide range of tasks — including discrete and
165 continuous — we conduct experiments in the following domains: boxpick stitching bench-
166 mark (Bortkiewicz et al., 2025), lightsout puzzle (Anderson & Feil, 1998) and OGBench (Park
167 et al., 2025). The details of these benchmarks are provided in Section D.

5.2 Baselines

169 In all three settings, we use the same algorithm for all baselines with the standard hyper-parameters.
170 The only change is the architecture used. We primarily compare with two baseline architectures – a

Figure 2: **Scaling recurrent steps in discrete environments.** Performance in most tasks improves as the number of recurrent steps increases, with performance often peaking at five recurrent steps.

Figure 3: **Scaling up recurrent steps in continuous environments improves performance in OGBench tasks (Park et al., 2025).** Interestingly, additional recurrent steps considerably improve performance mainly in tasks that involve long-horizon reasoning (scene, cube, and puzzle), while performance in stitching navigation tasks increases marginally with more steps.

standard feedforward network (**MLP**) and a residual network (**ResNet**). The MLP baseline contains a similar number of parameters to the IRU in all experiments. The ResNet baseline has the same effective depth as the IRU, i.e., it uses a similar amount of compute. But the number of parameters in ResNet scales with its depth. For instance, in the boxpick tasks the IRU contains 500K parameters, while the ResNet contains 3M parameters. These baselines help distinguish the effects of amount of compute and the number of parameters used by RL agents.

Results are reported using five random seeds for each experiment. For additional details about the environments and the algorithmic implementation, please refer to Section E.

5.3 The effect of recurrent steps on policy performance

In both the discrete tasks (Figure 2) and the continuous tasks (Figure 3), we see that performance increases significantly with more recurrent steps. In the challenging boxpick tasks, or the manipulation tasks in ogbench, performance increases up to 8 times after increasing the recurrent steps from one to ten.

In Table 1, we compare IRU-(5), with the MLP and the ResNet architecture after 2.5 (50%) and 5 (50%) million environment steps. On all tasks, IRU-(5) outperforms the MLP, which uses

Table 1: **Sample efficiency and final performance of IRU vs. feed-forward architectures.** IRU achieves higher final performance across all tasks and better sample efficiency in most cases.

Environment	Env Steps	IRU-(5)	ResNet	MLP
boxpick-exact-4	50%	**94.8 ± 2.3**	29 ± 15.2	25 ± 2.2
	100%	**97.4 ± 2.8**	58 ± 10.7	37 ± 5.8
boxpick-exact-3	50%	82.6 ± 5.9	**89.1 ± 3.1**	51.6 ± 5.8
	100%	**95.5 ± 2.4**	93.8 ± 4.4	67.0 ± 8.0
boxpick-gen-4-1	50%	**91.4 ± 2.0**	53.0 ± 8.6	64.4 ± 3.4
	100%	**93.3 ± 1.8**	57.7 ± 8.1	73.2 ± 0.7
boxpick-gen-4-2	50%	**84.8 ± 5.0**	31.3 ± 6.2	56.8 ± 1.8
	100%	**87.4 ± 4.9**	32.8 ± 5.4	64.3 ± 1.4
lightsout-4x5	50%	**54.2 ± 7.7**	1.0 ± 0.5	0.2 ± 0.2
	100%	**71.9 ± 8.9**	0.2 ± 0.2	0.5 ± 0.2
lightsout-3x3	50%	**100.0 ± 0.0**	30 ± 5.7	2.3 ± 1.6
	100%	**100.0 ± 0.0**	66 ± 13.6	1.5 ± 1.2

less compute but similar number of parameters. Notably, IRU-(5) is able to solve the most chal-

Figure 4: **Do recurrent steps improve generalization?** Throughout training, we track how policies learned by the IRU architecture and baselines perform on unseen tasks, including those that require more steps to solve. The IRU architecture learns faster (on $5/5$ tasks) and converges to higher asymptotic performance (on $4/5$ tasks) than MLPs and deep ResNets. The gains from IRU are most pronounced on `lightsout-4x4`, where all other architectures achieve only trivial performance.

lenging tasks like boxpick-exact-4, boxpick-gen-4-1 and lightsout-4x5, achieving a significant performance boost over the ResNet architecture. This is despite the ResNet using $\approx 2\times$ more compute and $\approx 5\times$ more parameters than IRU-(5). We hypothesize that this is due to the ResNet overfitting to seen tasks. This hypothesis is supported by the higher standard error values for the ResNet architecture in Table 1.

5.4 Generalization to longer-horizon tasks

We hypothesize that the solution learned by IRU policies will achieve better generalization to longer-horizon tasks during evaluation (Theorem 3.2). We also hypothesize that the recurrent inductive bias of IRUs will help them generalize better than ResNets, on tasks where the true solution requires iteratively applying some fixed computation (for e.g., lightsout). To empirically validate this hypothesis, we evaluate the performance of IRU, MLP and ResNet on a test distribution of unseen tasks that are strictly longer-horizon than the training tasks.

Figure 4 shows that IRU outperforms MLP on all tasks and ResNet on $4/6$ tasks, and the IRU is more sample efficient on all tasks. Importantly, IRU training is more stable than ResNet, which exhibits higher variance across seeds.

5.5 How to measure the value of compute?

Figure 5: **The Value of Compute.** We plot the value of compute of IRU-(1) over IRU-(5) for different number of steps. We see that VoC increases with number of MDP time-steps using less compute. VoC also peaks at the early half of the episode where choosing the correct action is both difficult and crucial.

Our theory proves that there are certain tasks which only policies with more compute can solve (Section 3) and previous experiments (Section 5.3 and Section 5.4) show that policies with more recurrent steps perform better. We now provide a method to estimate the **value of compute** for any given problem. Given two policies π_{t_1} and π_{t_2} which use t_1, t_2 recurrent steps respectively, the n-step

218 value of compute of π_{t_2} over of π_{t_1} is:[1]

$$\text{VoC}_n(s_0) = v_{\pi_{t_1}}(s_0) - \left(\Sigma_{k=1}^n \gamma^{k-1} r(s_k, \pi_{t_2}(s_k)) + \gamma^k v_{\pi_{t_1}}(s_n)\right), \tag{2}$$

219 where v_{π_t} is the value function of π_t. Intuitively, the value of compute measures how much value is
220 gained/lost by temporarily using t_2 recurrent steps (instead of t_1) for n time-steps in the MDP.

221 In Figure 5, we plot the value of compute for the boxpick-exact-4 with $t_1 = 5$ (IRU-(5)) and $t_2 = 1$
222 (IRU-(1)) over the course of several successful trajectories. We observe that value of compute
223 increases with n, in line with the intuition that an agent will lose more value if it continues to use
224 less compute for longer. For all values of n, the value of compute increases and peaks in the early
225 half of the episode and then decreases towards zero. This is also expected since during the early
226 half of an episode, selecting the correct action is both difficult and crucial. If the agent behaves
227 sub-optimally, due to less compute, for too long, it might enter a region of the state space where it
228 no longer knows how to recover. Towards the end of the episode when most blocks are already in
229 their place, the value of compute is low as it is easier to select the correct action. This experiment
230 highlights an opportunity for future work: compute-optimal agents should adaptively decide how
231 much compute to use based on the difficulty of the current state.

5.6 Why does more compute improve performance?

233 While experiments show that using more com-
234 pute markedly improves policy performance
235 and the theory provides expressivity results,
236 it remains unclear whether this improvement
237 stems from stronger exploration (i.e., better
238 data) or from applying a higher capacity model
239 to those data. It is important to dissect where
240 the primary benefits of additional compute
241 come from. We now propose an experiment
242 (similar to (Ostrovski et al., 2021)) which al-
243 lows us to do so.

244 Along the standard RL training loop, we train a
245 passive agent on the data collected by original
246 active agent. Both agents use the same objec-
247 tive and the architecture (but different weights),
248 but the amount of recurrent steps they use are
249 different. We perform this experiment on the
250 boxpick-exact-4 and boxpick-gen-4-1 tasks and
251 report the average success rates of the passive

Figure 6: **Yoked experiments (Ostrovski et al., 2021) to understand the performance benefits of using more compute.** These results show performance of a passive agent that is trained using the data collected by an active agent. We see that the highest jump in performance comes when the passive agent uses five recurrent step even though the data collecting agent only uses one.

252 agent on training and testing distribution in Figure 6. Note that all reported algorithms like
253 DQN (Mnih et al., 2013), CRL (Eysenbach et al., 2023b), and IQL (Kostrikov et al., 2021) achieved
254 zero success rates with standard architectures in the long horizon evaluation of the boxpick-exact-4
255 task (Bortkiewicz et al., 2025).

256 In Figure 6, we see that the highest jump in performance comes when the passive agent uses 5
257 recurrent steps. Remarkably, the data required to train the high-performing agent with 5 recurrent
258 steps are almost all contained in the data collected by an agent that used just 1 recurrent step, even
259 though that agent itself received low returns. We also run experiments where the active agent uses
260 five recurrent steps and the passive agent uses one. We observe that the performance of this passive
261 agent is worse than the performance of IRU-(1). This could be because the off-policy bias of training
262 passive agents or the inability of policies with less compute to learn good policies despite high
263 quality data. Increasing the compute used by the active agent improves the performance marginally

---

[1]For simplicity we assume deterministic transitions and policies. An expectation needs to be added to the second and
third term for the general case.

on the training tasks, but slightly reduces the performance on evaluation tasks. This suggests that most of the benefits of more compute comes from the additional expressivity of the agent. While we expect additional expressivity to indirectly improve exploration, using additional compute to explicitly improve exploration is an interesting direction for future work.

5.7 Ablation studies for architectural choices.

We perform an ablation experiment to compare the results when substituting three other choices of recurrent blocks in Figure 1, instead of the IRU. We use an LSTM network (Hochreiter & Schmidhuber, 1997), feedforward residual network (He et al., 2015), and the IRU with the deep recursion technique from Jolicoeur-Martineau (2025).

For deep recursion, the network maintains two latent variables and performs two hierarchies of recurrence (see Figure 3 of Jolicoeur-Martineau (2025) for more details). All the networks use the same number of recurrent steps. Figure 7 shows that the LSTM marginally outperforms the IRU. We prefer the IRU because it is twice as fast as an LSTM and contains half as many parameters at the same depth and hidden state dimensions. We see that the recurrent ResNet blocks do not achieve the same benefits of added compute. This suggests that a suitable architecture (some gating mechanisms in our case) are necessary to achieve the scaling

Figure 7: **Ablation experiments comparing several recurrent blocks in the complete architecture (Figure 1).**

benefits of additional compute. We also observe that the deep recursion technique works relatively worse. We believe that there is significant room for improving architectures as well as techniques that efficiently leverage the benefits that additional compute can provide in RL.

6 Conclusion

In this work, we challenge the standard view of RL policies as static functions that map states to actions. Instead we advocate for a computational view of RL policies where computation time can be independent from the number of policy parameters. We formulate RL policies as bounded models of computation and prove that policies which use more compute can perform and generalize to longer-horizon evaluation tasks better than policies which use less compute. For our experimental results, we propose a minimal architecture that is trainable at different levels of compute and show that using more compute can lead to significant gains in performance and longer-horizon generalization which was elusive for strong prior algorithms with standard architectures (Bortkiewicz et al., 2025). Finally, we also provide a computational method to estimate the value of compute in RL, akin to the value of information in partially observed tasks. These results help us measure, even in fully observed tasks, the value that additional compute provides.

One limitation of our work is that we use a fixed amount of recurrent computation steps for all states. We do not demonstrate how the same policy can use an adaptive amount of compute depending on the difficulty of the current state. Future work could explore such methods which might automatically learn inference-time compute scaling strategies or pre-fetch anticipated computation to store in memory. Additionally, our empirical evaluation focuses on a minimal recurrent architecture to isolate the effects of computation. We do not explore transformer-based architectures, and given their ubiquity in machine learning, an exploration of transformer-based recursive architectures in RL remains an interesting direction for future research. Lastly, our theoretical results use a single tape Turing machine as a computational model and only focus on time-complexity. Similar interesting results could be proven for space complexity or by using computational models like boolean circuits which better resemble modern neural networks.

A Proofs

Theorem A.1 (Policy Hierarchy Theorem). *Let $g(n)$ and $t(n)$ be time-constructible functions such that $g(n) \in o(t(n)/\log t(n))$. Then there exists an MDP and a function $f(n) \in \mathcal{O}(t(n))$ such that:*

1. The optimal policy π^* belongs to the class Π_f.

2. For any policy $\pi \in \Pi_g$, $J(\pi)$ is arbitrarily lower than $J(\pi^*)$.

Proof. Let U be a universal Turing machine that given an input of the form $(\langle M \rangle 10^*)$, simulates the computation of $M(\langle M \rangle 10^*)$ such that each step of the simulating M takes up some time $c(|\langle M \rangle|)$, depending only on the size of M and not on its input[2]. See Theorem 9.10 of Sipser (2006) for the description of this Turing machine U.

We will briefly re-describe how U works. U has two tracks (odd positions and even positions) in its single working tape. One of the tracks contains the information on M's tape, and the second contains M's current state and a copy of M's transition function. During the simulation, U always keeps the information on the second track near the current position of M's head on the first track. Every time M's head moves, U shifts all the information on the second track near the new head position. Because the information on the track depends only on $|M|$, shifting it and reading M's next action for every simulation step of M takes at most a constant amount of time depending on $|M|$.

We now define a language L that it is decidable in $\mathcal{O}(t(n))$, but cannot be decided in $o(t(n)/\log t(n))$.

$$L = \{(\langle M \rangle 10^*) : U \text{ rejects } (\langle M \rangle 10^*)$$
$$\text{in} \ \leq \frac{t(|\langle M \rangle 10^*|)}{\log t(|\langle M \rangle 10^*|)} \text{ steps}\} \tag{3}$$

The proof for this can be found in Theorem 9.10 of Sipser (2006) (see Theorem 3.1 of Arora & Barak (2006) for the proof of a simpler case). The proof constructs a Turing machine D that decides L in $f(n) \in \mathcal{O}(t(n))$. The proof then shows that for any $g(n) \in o(t(n)/\log t(n))$ bounded Turing machine M, there exists a constant $n_0 \in \mathbb{N}$ such that on all inputs of the form $\{(\langle M \rangle 10^*) \in \{0, 1\}^{n > n_0}\}$ it will output the opposite of D. That is if D accepts, M will reject and vice versa. Hence proving that any $g \in o(t(n)/\log t(n))$-bounded Turing machine cannot decide L. In Assumption 1, we need K_{max} to be larger than $|D|$. This is not a stringent requirement as D follows a relatively simple algorithm whose pseudo-code can be described in seven english statements in Theorem 9.10 of Sipser (2006).

Even though Theorem 9.10 of Sipser (2006) shows that the constant n_0 exists for any g-bounded Turing machine, it can be arbitrarily large. We will use Assumption 1 to bound this constant. The Turing machine U computes $M(\langle M \rangle 10^*)$ on inputs of the form $(\langle M \rangle 10^*)$. We know that each step of this simulation can be done in constant time $c(|\langle M \rangle|)$. If M is a $g(n)$-bounded Turing machine then U will simulate it in at most $c(|\langle M \rangle|)g(|(\langle M \rangle 10^*)|)$ steps. Because of Assumption 1, the maximum time that U will take to simulate any g-bounded Turing machine will be $c(K_{max})g(|(\langle M \rangle 10^*)|)$. Since $g(n) \in o(t(n)/\log t(n))$, there exists an n_{max} such that for all $n \geq n_{max}$, $g(n)c(K_{max}) < t(n)/\log t(n)$. Hence, the running time of any g-bounded Turing machine on inputs of the form $(\langle M \rangle 10^*)$ with length greater than n_{max} is going to be less than $\frac{t(|\langle M \rangle 10^*|)}{\log t(|\langle M \rangle 10^*|)}$. Such strings will be in L if M rejects and won't be in L if M accepts. Because D decides L, any g-bounded Turing machine M will output opposite to D on inputs of the form $(\langle M \rangle 10^*)$ with length greater than n_{max}.

---

[2]This does not mean that U runs in constant time; the total deciding time still depends on the length of w.

353 Using this language, we will define an MDP which satisfies both conditions of Theorem A.1. Each
354 episode in the MDP will end in a single time-step. The state space of this MDP is the following:

$$\mathcal{S} = \{(\langle M \rangle 10^*) : |\langle M \rangle| < K_{max}\} \tag{4}$$

355 The action space is binary and the reward function is:

$$R(s, a) = \begin{cases} 0 & \text{if } a = D(s) \\ -R & \text{otherwise} \end{cases} \tag{5}$$

356 The start state distribution $p(s_0)$ is:

$$\langle M \rangle \sim \mathcal{U}\big(\{0,1\}^{\leq K_{max}}\big) \text{ and } 10^q \sim p(10^{l > n_{max}}), \tag{6}$$

357 where p can be any distribution.

358 Condition 1 of Theorem A.1 is true because we know that D is a $f \in \mathcal{O}(t(n))$-time Turing machine.
359 Hence, π^* will just be the policy that is simulated by D.

360 Condition 2 of Theorem A.1 is true because for any $\pi \in \Pi_g$, there are infinitely many states of the
361 form $s = (\langle M_\pi \rangle 10^{l > n_{max}})$, where π will get arbitrarily low reward $(-R)$. Because such states occur
362 with probability $\frac{1}{2^{K_{max}+1}-2}$, the maximum returns that any g-bounded policy can get is $\frac{-R}{2^{K_{max}+1}-2}$.
363 This value can be reduced arbitrarily by reducing the value of $-R$. $\qquad \square$

364 **Theorem A.2** (Long Horizon Generalization). *Let $g(n)$ and $t(n)$ be time-constructible functions*
365 *such that $g(n) \in o(t(n)/\log t(n))$. Then there exists a goal conditioned MDP and a function*
366 *$f(n) \in \mathcal{O}(t(n))$ such that:*

367 *1. The optimal goal conditioned policy π^* belongs to the class Π_f.*

368 *2. For all training tasks $(s_{train}, g_{train} \sim p_{train}(s,g))$, the best g-bounded policy $\pi_g^* \in \Pi_g$ has the*
369 *same value function as π^*. But for infinitely many longer-horizon test tasks, π_g^* is arbitrarily*
370 *worse than π^*.*

371 *Proof.* We will use a lot of the components built in the policy hierarchy theorem (Theorem A.1) in
372 this proof.

373 We first define the MDP. The state and goal space of the MDP are:

$$\mathcal{S} = \{(\langle M \rangle 10^*) : |\langle M \rangle| < K_{max}\},$$
$$\mathcal{G} = \{10^*\} \cup \{\epsilon\}.$$

374 The action space is binary and the reward is:

$$R_g(s, a) = \begin{cases} +R & \text{if } s \text{ is of the form } (\langle M \rangle, g) \\ 0 & \text{otherwise.} \end{cases}$$

375 The transition dynamics of the MDP are the following:

$$T((\langle M \rangle, w), a) = \begin{cases} (\langle M \rangle, w_{1,\dots,|w|-1}) & \text{if } a = D(s) \text{ and } w \neq \epsilon \\ \text{Terminal State} & \text{otherwise.} \end{cases}$$

376 Hence, at every step, if the policy outputs the correct action, the last bit of the current state string w
377 is removed. If the policy outputs the wrong answer, then the episode will end with a return of 0.

378 The training task distribution is a uniform distribution over the following set:

$$\{(\langle M \rangle 10^*) : |(\langle M \rangle 10^*)| < K_{train} < n_{max}\} \times \{\epsilon\}.$$

So the agent has to provide the correct answer at all time steps, till the string w is reduced to an empty string. The agent will then receive a reward of $+R$. Note that the horizon of training tasks is always bounded by K_{train}.

Condition 1 of Theorem A.2 is true because, π^* will just be the policy that is simulated by D and we know that D is a $f \in \mathcal{O}(t(n))$-time Turing machine.

For Condition 2, we note that the set of training tasks $\mathcal{S}_{train}$ is a finite set. Hence it is a regular language that can always be decidable in $\mathcal{O}(1) \subset o(t(n)/\log t(n))$. One can run the policy corresponding to this g-bounded Turing machine (since it is constant time, it is also g-bounded) and achieve the optimal returns on all training tasks. Let this policy be π_g^* and let M_g^* be the corresponding Turing machine. From Theorem A.1, we know that the there are infinitely many longer-horizon test tasks of the form $s_{test} = (\langle M_{\pi_g^*}\rangle 10^*), g_{test} = \epsilon$, with $|\langle M_{\pi_g^*}\rangle 10^*| > n_{max}$, where π_g^* will take the suboptimal action and get zero returns. $\square$

B Recurrent Architecture

This section will explain the architecture we use in all our experiments (visualized in fig. 1).

A Recurrent Block. The key component of our architecture is a recurrent block which takes as input x and the current hidden state c_i and outputs the next hidden state, c_{i+1}. We will recursively apply this block N times, so we can think about this computation as mapping an input x to an output c_n. We initialize $c_0 = \vec{0}$. The recurrent block is composed of two linear layers, FORGET $: (x, c_i) \mapsto f_i$ and INPUT $: (x, c_i) \mapsto I_i$. The recurrent block uses these layers in the following computation:

$$f_i = \sigma(\text{FORGET}_\theta([x, \tanh(c_i)])) \tag{7}$$

$$I_i = \tanh(\text{INPUT}_\theta([x, \tanh(c_i)])) \tag{8}$$

$$c_{i+1} = f_i \odot c_i + (1 - f_i) \odot I_i. \tag{9}$$

Because the new cell state is calculated as an interpolation between the previous cell state and the latest local computation, we call this layer an interpolation recurrent unit (IRU).

The Complete Architecture. In our experiments, we will use this recurrent block as the core building block for our policy and value networks. These networks will take as input the observation and (for Q-functions) the action. After an initial Linear layer and Layer-normalization layer Ba et al. (2016), we apply the recurrent block layer N times. After each application of the recurrent block, the previous cell state is added to the output using a skip connection. The final cell state c_N, after a Tanh activation, is passed through a final linear layer to predict the actions and values. The entire architecture is referred to as IRU-(N). See Fig. 1 for a visualization.

C Related Work

Model-based RL and planning. There has been significant prior work in model-based RL on using additional compute to improve RL policies using planning (Coulom, 2007; Schrittwieser et al., 2020; Hafner et al., 2019; Janner et al., 2021; Hansen et al., 2022; Heess et al., 2015). The model of the world (Sutton, 1991) is typically learned independent of the primary learning process. Previous works have proposed model-learning objectives that support the primary RL objective (Farahmand et al., 2017; Grimm et al., 2020; Voelcker et al., 2023) or learning policies and models using a single objective (Eysenbach et al., 2023a; Ghugare et al., 2023). Our work is more closely related to approaches that propose architectures that can learn to plan, without explicitly learning a model of the world (Tamar et al., 2016; Farquhar et al., 2018; Guez et al., 2019b; Oh et al., 2017; Guez et al., 2018). Guez et al. (2019a) show that planning-like computations can be learned using a convolutional LSTM architecture (Shi et al., 2015) and a purely model-free RL objective.

Recurrent architectures for learning algorithmic solutions. In the supervised learning literature, prior works have shown that recurrent networks (Rumelhart et al., 1986; Hochreiter & Schmidhuber, 1997; Graves et al., 2014; He et al., 2015) trained on outputs of an algorithm can learn solutions that extrapolate to much longer inputs (Graves, 2017; Wang et al., 2025a; Jolicoeur-Martineau, 2025; Geiping et al., 2025; Schwarzschild et al., 2021; Bansal et al., 2022). In our experiments we also show that such an architecture learns policies that can solve more difficult tasks during evaluation. However, unlike the longer length evaluation in supervised learning, the horizon of evaluation tasks is longer in our RL setup. The architecture we use falls in the family of hybrid recurrent networks in which certain layers are repeated multiple times during the forward pass (Gers & Schmidhuber, 2001). Let n_i, n_o be the input network and the output head respectively and r be an intermediate network. Then the forward pass of a canonical recurrent architecture is of the form $n_o(r^k(n_i(x)))$. Many variants of such architectures have been proposed, mostly in the supervised learning literature, where r could be a recurrent network (Gers & Schmidhuber, 2001; Geiping et al., 2025; Dehghani et al., 2019; Yang et al., 2024; Guez et al., 2019a), a residual network (Bansal et al., 2022; Schwarzschild et al., 2021), or a diffusion model (Du et al., 2024). In Section 4, we propose a new minimal variant of a recurrent network that worked well in our experiments. Recently, Jolicoeur-Martineau (2025); Wang et al. (2025a) have proposed multiple techniques like deep supervision, truncated gradients and early stopping (Graves, 2017) for training recurrent architectures in supervised learning tasks. We perform ablations (Section 5.7) to determine the benefits of these techniques for our RL experiments.

Chain of thought reasoning in LLMs. The performance of pre-trained language models can be improved significantly using inference time strategies without changing the parameters of the model (Brown et al., 2020; Wei et al., 2022b;a). Such strategies include prompting the model to "think step by step" Wei et al. (2022b) or using self verification combined with a search algorithm to iteratively improve its output Yao et al. (2023); Zhou et al. (2024a); Weng et al. (2023); Muennighoff et al. (2025). Our paper also shows that policies using more compute and the same number of parameters can significantly improve performance. But unlike pretrained LLMs, our work is focused on training RL policies from scratch.

Length generalization in LLMs. Our work is also reminiscent of recent work on length generalization in language models (Zhou et al., 2023; 2024b) that make use of iterative computation to promote this sort of generalization. Our experiments complement these results by empirically demonstrating that iterative computation can unlock horizon generalization in RL, and can do so without a special training dataset or curriculum (Cho et al., 2024; Lee et al., 2025). While prior work often attributes the success of iterative reasoning to the tasks that a model has seen before Hanna & Corrado (2025b); Lester et al. (2021), both our experiments and theory highlight that increasing compute (including via iterative function application) can improve performance on RL tasks in settings without language, pre-training, or multi-task training.

D Benchmarks

Boxpick. The Boxpick benchmark consists of a discrete task on an $n \times n$ grid, where an agent navigates, picks up boxes, and places them on target locations. A rollout is successful if all boxes are placed on arbitrary targets, similar to Sokoban. We use two settings: *generalized stitching* (boxpick-gen-m−n) and *exact stitching* (boxpick-exact-m). In boxpick-gen-m−n, training tasks are sampled where only n boxes are not on target. During evaluation, longer-horizon tasks are sampled such that all the boxes are off the target. In the boxpick-exact-m, the agent is trained to move boxes between any two neighboring quadrants of the board, while evaluation is performed with boxes and targets on diagonally opposite quadrants to evaluate test-time generalization to longer-horizon tasks. These tasks are very difficult for RL algorithms, and many state of the art algorithms only achieve trivial performance on them (Bortkiewicz et al., 2025).

467 **Lightsout.** lightsout-m×n is a combinatorial puzzle where the state space is a m×n grid of black
468 or white switches ($\{0,1\}^{mn}$). The action space contains mn actions, each pushing a particular
469 switch on the grid. Upon pushing, the colors of adjacent switches flip their color. At the start of
470 every episode, a target grid configuration is sampled ($\{0,1\}^{mn}$). The agent receives a reward of -1
471 until it reaches this target. The space of possible inputs is very large (2^{21} for lightsout-4×5), hence
472 it is challenging to memorize all the optimal actions. During training, we sample shorter horizon
473 tasks and during evaluation we sample longer-horizon tasks.

E   Implementation details

475 We present the implementation details of all the results presented in our paper. Unless stated oth-
476 erwise, the algorithm specific hyper-parameters used for all architectures are the same as standard
477 hyper-parameters and hence are not tuned to favor any architecture. Only the architecture relevant
478 code is changed when comparing IRU, MLP or ResNets. The underlying algorithm for all the box-
479 pick tasks is goal conditioned DQN (He et al., 2015), for lightsout is PPO, and for OGBench tasks
480 is goal conditioned IQL (Kostrikov et al., 2021).

481 **Boxpick.** We use the standard hyper-parameters used by the DQN algorithm implemented
482 in Bortkiewicz et al. (2025) benchmark listed in Table 2. We use a single IRU layer to make the
483 recurrent block. All linear layers have a dimension of 256. The ResNets used in this task consist of
484 two residual blocks, each with four hidden layers, following the architecture of Wang et al. (2025b).
485 The dimensions of all layers in the residual blocks is 256. The MLPs used in this task contain 2
486 hidden linear layers of 256 dimensions.

Table 2: DQN hyperparameters in Boxpick benchmark.

Hyperparameter	Value
num env steps	500,000,000
num updates	1,000,000
max replay size (per env instance)	10,000
min replay size	1,000
episode length	100
discount	0.99
number of parallel envs	1024
batch size	256
learning rate	3e-4
target_entropy	1.1
layer_norm	True

487 **OGBench.** We use the standard hyper-parameters used by the IQL algorithm implemented in Park
488 et al. (2025) benchmark. We use a single IRU layer to make the recurrent block. All linear layers
489 have a dimension of 64. The baseline MLP results are directly taken from Park et al. (2025).

490 **Lightsout.** We implement the PPO algorithm and use standard hyper-parameters listed in Table 3.
491 We use stack two IRU layers to make the recurrent block. All linear layers have a dimension of
492 64. The ResNets used in this task contain 10 residual blocks with two hidden layers each. The
493 dimensions of all layers in the residuals blocks is 64. The MLPs used in this task contain 4 hidden
494 linear layers of 256 dimension.

495 **OGBench.** We use a total of five different environments consisting of a total of 25 tasks from
496 OGBench. All tasks are offline goal reaching RL tasks where agents are supposed to learn using
497 a fixed dataset. The success rate of agents is plotted throughout training. Antmaze-medium-stitch

Table 3: PPO Hyperparameters in lightsout benchmark.

Hyperparameter	Value
number of parallel envs	2048
discount factor	0.99
gae parameter	0.95
clipping parameter	0.3
entropy coefficient	0.01
learning rate	1×10^{-4}
rollout length	160
optimization epochs	8
mini-batches per rollout	32
advantage normalization	True

498 and pointmaze-large-stitch tasks test trajectory stitching, while scene-play, cube-double-play and
499 puzzle-4x4-play test long-horizon reasoning and combinatorial generalization abilities.

References

Marlow Anderson and Todd Feil. Turning lights out with linear algebra. *Mathematics magazine*, 71 (4):300–303, 1998.

S. Arora and B. Barak. *Computational Complexity: A Modern Approach.* Cambridge University Press, 2006. ISBN 978-0-521-42426-4. URL https://theory.cs.princeton.edu/complexity/book.pdf.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization, 2016. URL https://arxiv.org/abs/1607.06450.

Arpit Bansal, Avi Schwarzschild, Eitan Borgnia, Zeyad Emam, Furong Huang, Micah Goldblum, and Tom Goldstein. End-to-end algorithm synthesis with recurrent networks: Extrapolation without overthinking. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 20232–20242. Curran Associates, Inc., 2022. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/7f70331dbe58ad59d83941dfa7d975aa-Paper-Conference.pdf.

Michał Bortkiewicz, Władysław Pałucki, Mateusz Ostaszewski, and Benjamin Eysenbach. Is temporal difference learning the gold standard for stitching in rl?, 2025. URL https://arxiv.org/abs/2510.21995.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS '20, Red Hook, NY, USA, 2020. Curran Associates Inc. ISBN 9781713829546.

Thomas Bush, Stephen Chung, Usman Anwar, Adrià Garriga-Alonso, and David Krueger. Interpreting emergent planning in model-free reinforcement learning, 2025. URL https://arxiv.org/abs/2504.01871.

Hanseul Cho, Jaeyoung Cha, Pranjal Awasthi, Srinadh Bhojanapalli, Anupam Gupta, and Chulhee Yun. Position coupling: Improving length generalization of arithmetic transformers using task structure. *Advances in Neural Information Processing Systems 37*, 2024. URL https://api.semanticscholar.org/CorpusID:273695226.

Kyunghyun Cho, Bart van Merrienboer, Dzmitry Bahdanau, and Yoshua Bengio. On the properties of neural machine translation: Encoder-decoder approaches. In Dekai Wu, Marine Carpuat, Xavier Carreras, and Eva Maria Vecchi (eds.), *Proceedings of SSST@EMNLP 2014, Eighth Workshop on Syntax, Semantics and Structure in Statistical Translation, Doha, Qatar, 25 October 2014*, pp. 103–111. Association for Computational Linguistics, 2014. DOI: 10.3115/V1/W14-4012. URL https://aclanthology.org/W14-4012/.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems, 2021. URL https://arxiv.org/abs/2110.14168.

Rémi Coulom. Efficient selectivity and backup operators in monte-carlo tree search. In H. Jaap van den Herik, Paolo Ciancarini, and H. H. L. M. (Jeroen) Donkers (eds.), *Computers and Games*, pp. 72–83, Berlin, Heidelberg, 2007. Springer Berlin Heidelberg. ISBN 978-3-540-75538-8.

Mostafa Dehghani, Stephan Gouws, Oriol Vinyals, Jakob Uszkoreit, and Łukasz Kaiser. Universal transformers, 2019. URL https://arxiv.org/abs/1807.03819.

Yilun Du, Jiayuan Mao, and Joshua B. Tenenbaum. Learning iterative reasoning through energy diffusion, 2024. URL https://arxiv.org/abs/2406.11179.

Benjamin Eysenbach, Alexander Khazatsky, Sergey Levine, and Ruslan Salakhutdinov. Mismatched no more: Joint model-policy optimization for model-based rl, 2023a. URL https://arxiv.org/abs/2110.02758.

Benjamin Eysenbach, Tianjun Zhang, Ruslan Salakhutdinov, and Sergey Levine. Contrastive learning as goal-conditioned reinforcement learning, 2023b. URL https://arxiv.org/abs/2206.07568.

Amir-Massoud Farahmand, Andre Barreto, and Daniel Nikovski. Value-Aware Loss Function for Model-based Reinforcement Learning. In Aarti Singh and Jerry Zhu (eds.), *Proceedings of the 20th International Conference on Artificial Intelligence and Statistics*, volume 54 of *Proceedings of Machine Learning Research*, pp. 1486–1494. PMLR, 20–22 Apr 2017. URL https://proceedings.mlr.press/v54/farahmand17a.html.

Gregory Farquhar, Tim Rocktäschel, Maximilian Igl, and Shimon Whiteson. Treeqn and atreec: Differentiable tree-structured models for deep reinforcement learning, 2018. URL https://arxiv.org/abs/1710.11417.

Jonas Geiping, Sean Michael McLeish, Neel Jain, John Kirchenbauer, Siddharth Singh, Brian R. Bartoldson, Bhavya Kailkhura, Abhinav Bhatele, and Tom Goldstein. Scaling up test-time compute with latent reasoning: A recurrent depth approach. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025. URL https://openreview.net/forum?id=S3GhJooWIC.

F.A. Gers and E. Schmidhuber. Lstm recurrent networks learn simple context-free and context-sensitive languages. *IEEE Transactions on Neural Networks*, 12(6):1333–1340, 2001. DOI: 10.1109/72.963769.

Raj Ghugare, Homanga Bharadhwaj, Benjamin Eysenbach, Sergey Levine, and Russ Salakhutdinov. Simplifying model-based RL: Learning representations, latent-space models, and policies with one objective. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=MQcmfgRxf7a.

Alex Graves. Adaptive computation time for recurrent neural networks, 2017. URL https://arxiv.org/abs/1603.08983.

Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines, 2014. URL https://arxiv.org/abs/1410.5401.

Christopher Grimm, André Barreto, Satinder Singh, and David Silver. The value equivalence principle for model-based reinforcement learning, 2020. URL https://arxiv.org/abs/2011.03506.

Arthur Guez, Théophane Weber, Ioannis Antonoglou, Karen Simonyan, Oriol Vinyals, Daan Wierstra, Rémi Munos, and David Silver. Learning to search with mctsnets, 2018. URL https://arxiv.org/abs/1802.04697.

Arthur Guez, Mehdi Mirza, Karol Gregor, Rishabh Kabra, Sebastien Racaniere, Theophane Weber, David Raposo, Adam Santoro, Laurent Orseau, Tom Eccles, Greg Wayne, David Silver, and Timothy Lillicrap. An investigation of model-free planning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2464–2473. PMLR, 09–15 Jun 2019a. URL https://proceedings.mlr.press/v97/guez19a.html.

Arthur Guez, Mehdi Mirza, Karol Gregor, Rishabh Kabra, Sébastien Racanière, Théophane Weber, David Raposo, Adam Santoro, Laurent Orseau, Tom Eccles, Greg Wayne, David Silver, and Timothy Lillicrap. An investigation of model-free planning, 2019b. URL https://arxiv.org/abs/1901.03559.

Danijar Hafner, Timothy Lillicrap, Ian Fischer, Ruben Villegas, David Ha, Honglak Lee, and James Davidson. Learning latent dynamics for planning from pixels, 2019. URL https://arxiv.org/abs/1811.04551.

Josiah P Hanna and Nicholas E Corrado. When can model-free reinforcement learning be enough for thinking? *arXiv preprint arXiv:2506.17124*, 2025a.

Josiah P. Hanna and Nicholas E. Corrado. When can model-free reinforcement learning be enough for thinking?, 2025b. URL https://arxiv.org/abs/2506.17124.

Nicklas Hansen, Xiaolong Wang, and Hao Su. Temporal difference learning for model predictive control, 2022. URL https://arxiv.org/abs/2203.04955.

Juris Hartmanis and Richard Edwin Stearns. On the computational complexity of algorithms. *Transactions of the American Mathematical Society*, 117:285–306, 1965. URL https://api.semanticscholar.org/CorpusID:40185800.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition, 2015. URL https://arxiv.org/abs/1512.03385.

Nicolas Heess, Greg Wayne, David Silver, Timothy Lillicrap, Yuval Tassa, and Tom Erez. Learning continuous control policies by stochastic value gradients, 2015. URL https://arxiv.org/abs/1510.09142.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural Comput.*, 9(8): 1735–1780, November 1997. ISSN 0899-7667. DOI: 10.1162/neco.1997.9.8.1735. URL https://doi.org/10.1162/neco.1997.9.8.1735.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization, 2021. URL https://arxiv.org/abs/1906.08253.

Khurram Javed and Richard S. Sutton. The big world hypothesis and its ramifications for artificial intelligence. In *Finding the Frame: An RLC Workshop for Examining Conceptual Frameworks*, 2024. URL https://openreview.net/forum?id=Sv7DazuCn8.

Alexia Jolicoeur-Martineau. Less is more: Recursive reasoning with tiny networks, 2025. URL https://arxiv.org/abs/2510.04871.

Leslie Pack Kaelbling. Learning to achieve goals. In *International Joint Conference on Artificial Intelligence*, 1993. URL https://api.semanticscholar.org/CorpusID:5538688.

Steven Kapturowski, Georg Ostrovski, Will Dabney, John Quan, and Remi Munos. Recurrent experience replay in distributed reinforcement learning. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=r1lyTjAqYX.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning, 2021. URL https://arxiv.org/abs/2110.06169.

Nayoung Lee, Ziyang Cai, Avi Schwarzschild, Kangwook Lee, and Dimitris Papailiopoulos. Self-improving transformers overcome easy-to-hard and length generalization challenges, 2025. URL https://arxiv.org/abs/2502.01612.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning, 2021. URL https://arxiv.org/abs/2104.08691.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning, 2013. URL https://arxiv.org/abs/1312.5602.

Gordon E. Moore. Cramming more components onto integrated circuits. *Electronics*, 38(8):114–117, April 1965.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. s1: Simple test-time scaling, 2025. URL https://arxiv.org/abs/2501.19393.

Vivek Myers, Catherine Ji, and Benjamin Eysenbach. Horizon generalization in reinforcement learning. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=BH8Nrt2dPf.

Junhyuk Oh, Satinder Singh, and Honglak Lee. Value prediction network, 2017. URL https://arxiv.org/abs/1707.03497.

OpenAI, Ilge Akkaya, Marcin Andrychowicz, Maciek Chociej, Mateusz Litwin, Bob McGrew, Arthur Petron, Alex Paino, Matthias Plappert, Glenn Powell, Raphael Ribas, Jonas Schneider, Nikolas Tezak, Jerry Tworek, Peter Welinder, Lilian Weng, Qiming Yuan, Wojciech Zaremba, and Lei Zhang. Solving rubik's cube with a robot hand, 2019. URL https://arxiv.org/abs/1910.07113.

Georg Ostrovski, Pablo Samuel Castro, and Will Dabney. The difficulty of passive learning in deep reinforcement learning, 2021. URL https://arxiv.org/abs/2110.14020.

Seohong Park, Kevin Frans, Benjamin Eysenbach, and Sergey Levine. Ogbench: Benchmarking offline goal-conditioned rl. In *International Conference on Learning Representations (ICLR)*, 2025.

Aleksei Petrenko, Arthur Allshire, Gavriel State, Ankur Handa, and Viktor Makoviychuk. Dexpbt: Scaling up dexterous manipulation for hand-arm systems with population based training, 2023. URL https://arxiv.org/abs/2305.12127.

D. E. Rumelhart, G. E. Hinton, and R. J. Williams. *Learning internal representations by error propagation*, pp. 318–362. MIT Press, Cambridge, MA, USA, 1986. ISBN 026268053X.

Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, Timothy Lillicrap, and David Silver. Mastering atari, go, chess and shogi by planning with a learned model. *Nature*, 588 (7839):604–609, December 2020. ISSN 1476-4687. DOI: 10.1038/s41586-020-03051-4. URL http://dx.doi.org/10.1038/s41586-020-03051-4.

Avi Schwarzschild, Eitan Borgnia, Arjun Gupta, Furong Huang, Uzi Vishkin, Micah Goldblum, and Tom Goldstein. Can you learn an algorithm? generalizing from easy to hard problems with recurrent networks, 2021. URL https://arxiv.org/abs/2106.04537.

Xingjian Shi, Zhourong Chen, Hao Wang, Dit-Yan Yeung, Wai kin Wong, and Wang chun Woo. Convolutional lstm network: A machine learning approach for precipitation nowcasting, 2015. URL https://arxiv.org/abs/1506.04214.

David Silver, Hado van Hasselt, Matteo Hessel, Tom Schaul, Arthur Guez, Tim Harley, Gabriel Dulac-Arnold, David Reichert, Neil Rabinowitz, Andre Barreto, and Thomas Degris. The predictron: End-to-end learning and planning, 2017. URL https://arxiv.org/abs/1612.08810.

Michael Sipser. *Introduction to the Theory of Computation*. Course Technology, second edition, 2006. ISBN 7111173279 9787111173274.

Richard S. Sutton. Dyna, an integrated architecture for learning, planning, and reacting. *SIGART Bull.*, 2(4):160–163, July 1991. ISSN 0163-5719. DOI: 10.1145/122344.122377. URL https://doi.org/10.1145/122344.122377.

Aviv Tamar, Yi Wu, Garrett Thomas, Sergey Levine, and Pieter Abbeel. Value iteration networks. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, NIPS'16, pp. 2154–2162, Red Hook, NY, USA, 2016. Curran Associates Inc. ISBN 9781510838819.

Claas Voelcker, Victor Liao, Animesh Garg, and Amir massoud Farahmand. Value gradient weighted model-based reinforcement learning, 2023. URL https://arxiv.org/abs/2204.01464.

Guan Wang, Jin Li, Yuhao Sun, Xing Chen, Changling Liu, Yue Wu, Meng Lu, Sen Song, and Yasin Abbasi Yadkori. Hierarchical reasoning model, 2025a. URL https://arxiv.org/abs/2506.21734.

Kevin Wang, Ishaan Javali, Michał Bortkiewicz, Tomasz Trzcinski, and Benjamin Eysenbach. 1000 layer networks for self-supervised RL: Scaling depth can enable new goal-reaching capabilities. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2025b. URL https://openreview.net/forum?id=s0JVsx3bx1.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, Ed H. Chi, Tatsunori Hashimoto, Oriol Vinyals, Percy Liang, Jeff Dean, and William Fedus. Emergent abilities of large language models, 2022a. URL https://arxiv.org/abs/2206.07682.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, brian ichter, Fei Xia, Ed H. Chi, Quoc V Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022b. URL https://openreview.net/forum?id=_VjQlMeSB_J.

Yixuan Weng, Minjun Zhu, Fei Xia, Bin Li, Shizhu He, Shengping Liu, Bin Sun, Kang Liu, and Jun Zhao. Large language models are better reasoners with self-verification, 2023. URL https://arxiv.org/abs/2212.09561.

Liu Yang, Kangwook Lee, Robert Nowak, and Dimitris Papailiopoulos. Looped transformers are better at learning learning algorithms, 2024. URL https://arxiv.org/abs/2311.12424.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Thomas L. Griffiths, Yuan Cao, and Karthik Narasimhan. Tree of thoughts: Deliberate problem solving with large language models, 2023. URL https://arxiv.org/abs/2305.10601.

Andy Zhou, Kai Yan, Michal Shlapentokh-Rothman, Haohan Wang, and Yu-Xiong Wang. Language agent tree search unifies reasoning acting and planning in language models, 2024a. URL https://arxiv.org/abs/2310.04406.

Hattie Zhou, Arwen Bradley, Etai Littwin, Noam Razin, Omid Saremi, Josh Susskind, Samy Bengio, and Preetum Nakkiran. What algorithms can transformers learn? a study in length generalization, 2023. URL https://arxiv.org/abs/2310.16028.

Yongchao Zhou, Uri Alon, Xinyun Chen, Xuezhi Wang, Rishabh Agarwal, and Denny Zhou. Transformers can achieve length generalization but not robustly, 2024b. URL https://arxiv.org/abs/2402.09371.

Supplementary Materials

The following content was not necessarily subject to peer review.

Content that appears after the references are not part of the "main text," have no page limits, are not necessarily reviewed, and should not contain any claims or material central to the paper. If your paper includes supplementary materials, use the

\beginSupplementaryMaterials

command as in this example, which produces the title and disclaimer above. If your paper does not include supplementary materials, this command can be removed or commented out.