Neural Network Surgery: Combining Training with Topology Optimization

Abstract

With ever increasing computational capacities, neural networks become more and more proficient at solving complex tasks. However, picking a sufficiently good network topology usually relies on expert human knowledge. Neural architecture search aims to reduce the extent of expertise that is needed. Modern architecture search techniques often rely on immense computational power, or apply trained meta controllers for decision making. We develop a framework for a genetic algorithm that is both computationally cheap and makes decisions based on mathematical criteria rather than trained parameters. It is a hybrid approach that fuses training and topology optimization together into one process. Structural modifications that are performed include adding or removing layers of neurons, with some re-training applied to make up for incurred change in input-output behaviour. Our ansatz is tested on both the SVHN and (augmented) CIFAR-10 datasets with limited computational overhead compared to training only the baseline. This algorithm can achieve a significant increase in accuracy (as compared to a fully trained baseline), rescue insufficient topologies that in their current state are only able to learn to a limited extent, and dynamically reduce network size without loss in achieved accuracy.

1 Introduction

A common uncertainty for any given machine learning task based on artificial neural networks (ANNs) is how to choose a sufficiently good network topology. Picking one that is too small may not yield acceptable prediction accuracy. To improve results, one can keep adding structural elements to the network until the desired accuracy value has been reached. Depending on the problem at hand, this approach may require an immense number of trainable parameters for the network, causing an explosion in computational cost for both training and evaluation. Where the sweet spot in between lies is unclear, and heavily dependent on the given task. A priori optimization is not easily possible, since reliable estimates on network behaviour would already depend on training results, and also there exists no generalization for which topology will fit which problem. Researchers have applied a number of search strategies such as random search (Li & Talwalkar, 2019), Bayesian optimization (Kandasamy et al., 2018), reinforcement learning (Zoph & Le, 2017), and gradient-based methods (Dong & Yang, 2019). Another technique that has been applied since at least Miller et al. (1989) are so called (neuro-) evolutionary algorithms. These algorithms serve to evolve the network architecture, often also training network weights at the same time (Elsken et al., 2019).

Our goal is to develop a genetic algorithm that benefits from lower computational cost compared to other state of the art approaches (Dong & Yang, 2019; Li & Talwalkar, 2019) while still adhering to the genetic algorithm. We achieve this by re-using network weights for competing modification candidates instead of retraining each net from scratch, branching off modification candidates during training, and letting them compete against each other until a new main branch is selected. This better fuses the evolutionary optimization paradigm with the ANN training into an integrated framework that folds both processes into one training/topology optimization hybrid. As such, evolutionary steps are not carried out by a meta-controller or other black-box-like implementations. We make use of mathematical tools such as singular value decomposition (SVD) and Bayesian information criterion (BIC) (Schwarz, 1978) for network weight analysis, decision making, and structural modifications. Network modifications are performed by adapting existing weights in such a way as to incur minimal changes to input-output behaviour.

We develop a framework for a combined ANN training and neural architecture search that consists of three main components: a module that can perform a number of minimally invasive network operations ("surgeries"), a module that analyses network weights and can give recommendations which modifications are most likely to increase (validation) accuracy, and finally a module that serves as a genetic algorithm (the "Surgeon"), containing the former two while gradually evolving any given starting network. With the Surgeon, we are able to evolve and improve models for the SVHN (Netzer et al., 2011) and CIFAR-10 (Krizhevsky, 2009) datasets for varying starting topologies. We achieve particularly good results on starting topologies that would a posteriori have proven to be suboptimal. A great benefit of our approach is that it can add topology optimization to the ML training with limited computational resources. Convergence is reached for all test cases within a few CPU hours.

This paper contributes a computationally cheap ansatz for a genetic neural architecture search algorithm, that makes evolutionary decisions based on mathematical analysis.

2 RELATED WORK

Neural architecture search (NAS) has been an increasingly popular research topic for many years (Elsken et al., 2019), starting as early as Miller et al. (1989), who presented one of the earliest neuro-evolutionary algorithms to search for suitable network topologies. Recent approaches by Dong & Yang (2019); Li & Talwalkar (2019), and Zoph & Le (2017) reach competitive performance on benchmark datasets such as CIFAR-10. However, this often comes at the cost of vast computational resources, with Zoph & Le (2017) making use of up to 800 GPUs for several weeks.

Cai et al. (2018) attempt to reduce computational costs by re-using network weights, as well as training and applying a reinforcement meta controller for structural decisions. They make use of a number of function-preserving transformations introduced by Chen et al. (2016), and extend them to also allow non-sequential network structures, such as DenseNet (Huang et al., 2017). DiMattina & Zhang (2010) introduce and rigorously prove conditions, under which gradual changes to the parametrization of a neural network are possible, while keeping the input-output behaviour constant.

There are also a number of neural architecture search strategies that do not depend on manual network modifications. Dong & Yang (2019) represent the search space as a directed acyclic graph and propose an efficient search algorithm. İrsoy & Alpaydın (2020) learn the network structure via so-called "budding perceptrons", in which an extra parameter is learned for each layer, that indicates whether or not any given node needs to branch out again or be removed altogether. Their method focuses on growing the network to the required size from a minimal starting topology. Frankle & Carbin (2019) present a method to identify particularly good network initializations that can train sparse networks to competitive accuracy. Another approach in NAS is to prune down from a larger starting topology (Blalock et al., 2020). Popular pruning techniques include applying SVD to existing network weights (Girshick, 2015; Denton et al., 2014; Xue et al., 2013).

3 METHODS

This work introduces and utilizes three main components:

- "The modification module": A module which can perform network modifications ("surgeries") in such a way as to incur minimal changes to input-output behaviour.
- "The recommendation module": A module that analyzes network weights and can give recommendations on which operations are most likely to improve network accuracy.
- "The Surgeon": A genetic algorithm that links the two modules, and gradually evolves a given starting network.

The modification module. We need to be able to perform a number of different modifications that can restructure network architecture. Ideally, these operations should leave input-output behaviour completely intact. DiMattina & Zhang (2010) have shown that for generalized changes this is possible only when exponentials, logarithmic or power functions are used for hidden unit activations. Since we do not wish to restrict the Surgeon to such networks only, we aim to perform minimal impact changes instead.

Under piecewise linear activation functions such as ReLu, one can always add neurons to a hidden layer, or even add whole layers, without any change to the overall network behaviour. Adding a whole layer is done by using an identity matrix as a new weight matrix. We add a new neuron to any layer by dividing all weights for one existing neuron by two, and duplicating the respective connections in the next layer (cf. appendix A.1).

Removing neurons from a layer can rarely, and in typical use cases never, be done completely loss free, unless some of the units are degenerate to begin with, i.e. the weight matrix is of reduced rank. For a modification with minimal impact on input output behaviour we need the closest[1] possible projection onto a lower rank subspace. The Eckart-Young(-Mirsky) theorem states that this projection can be found by applying Singular Value Decomposition (SVD) to the weight matrix:

Let $\boldsymbol{A} \in \mathbb{R}^{m \times n}$ be a (weight) matrix, then there exists a representation

$$\boldsymbol{A} = \boldsymbol{U}\Sigma\boldsymbol{V}^T \tag{1}$$

with orthogonal $\boldsymbol{U} \in \mathbb{R}^{m \times m}, \boldsymbol{V} \in \mathbb{R}^{n \times n}$ and rectangular diagonal $\Sigma \in \mathbb{R}^{m \times n}$ with $k \leq \min(m, n)$ non-negative real entries σ_i along its diagonal, called singular values of $\boldsymbol{A}$ (cf. appendix A.2).

In order to reduce the rank of $\boldsymbol{A}$ to $r < k$, we set $\sigma_i = 0 \ \forall i > r$, and drop associated columns/rows of $\boldsymbol{U}$ and $\boldsymbol{V}$. We then project to a smaller matrix $\tilde{\boldsymbol{A}}$ by computing $\boldsymbol{U}\Sigma$. To project back to the original layer size, so that the layer weight shapes match again, we multiply the weights of the next layer with $\boldsymbol{V}^T$.

Projecting onto a lower rank subspace by setting singular values to zero is sometimes called truncated SVD, and is used in network pruning (Denton et al., 2014; Girshick, 2015; Xue et al., 2013). This technique adds an intermediate layer of (potentially much fewer) neurons, which in case of very large weight matrices can drastically reduce the overall connection count.

Note that this projection method is not concerned at all with a potential activation function after the network's modified layer, which is now of reduced size. In particular, changing a layer's activation function will never work without changes to input/output behaviour, since activation functions are usually non-linear. We therefore do not perform any additional modifications to counterbalance a change of activation.

As we have seen, network modifications will in general lead to a small disruption in input-output behaviour, most likely leading to a loss in prediction accuracy. In order to make up for this, all network modifications are given a small amount of recuperative training (several batches) before any comparison is made. The retraining amount was determined by trials and statistical analysis based on a dataset[2] which we do not otherwise use in our results. This is done to avoid overfitting the neural architecture search algorithm to a specific dataset.

The recommendation module. For the decision *when* to execute *which* network operation, we perform a two-fold analysis. As a first order criterion, we compute the amount of information carried by each neuron by looking at the layer's singular values. The number of neurons that may be removed from a layer depends on the count of singular values that are (close to) zero, or are several orders of magnitude smaller than the layer's largest singular value. This number in relation to the layer's total neuron count gives an indication whether to add or remove neurons or even whole layers.

The second order decision basis is the Bayesian information criterion (BIC). The BIC weighs the number of model parameters and training samples against the likelihood function of predicted vs. true target data. Since all operations are chosen to incur minimal changes to predicted values, the difference in the likelihood function becomes negligible compared to the number of parameters, which allows us to reduce the formula to the parameter count of the modified network (cf. appendix A.3).

3.1 A GENETIC ALGORITHM FOR NEURAL ARCHITECTURE SEARCH

The final module is the Surgeon, the genetic algorithm that searches for an optimized network architecture while training network weights at the same time. Currently we are restricted to perhaps

---

[1] under Frobenius norm $\| \cdot \|_F$
[2] MNIST, (Lecun et al., 1998)

the most ubiquitous type of architecture: sequential networks (i.e. without recurrent or skip connections) consisting only of fully connected layers. As Cai et al. (2018) have shown however, a number of the used tools already generalize well to non-sequential networks as well as convolutional layers.

Algorithm 1 The Surgeon

1: **function** PERFORMSURGERY($model$)
2:     train $model$ for initial number of epochs
3:     current branches = $[model]$
4:     **while** termination criteria not met **do**   ▷ e.g. max. number of epochs
5:         **for** all current branches **do**
6:             determine potential modification candidates $[m_{cand}]$
7:         **repeat**
8:             select $[m_{sel}]$ from $[m_{cand}]$ ▷ e.g. 7 competitors
9:             re-train $[m_{sel}]$ for small amount   ▷ e.g. 15 batches
10:            compare $[m_{sel}]$, keep n top scoring as new current branches ▷ e.g. 2 conc. branches
11:            train current branches to full epoch step   ▷ e.g. 10 epochs
12:         **until** improvement achieved or max re-tries reached
13:     select final best scoring branch
14:     **return** optimized network m_{opt}

The overall structure of the Surgeon can be seen in algorithm 1. First, the provided model is pre-trained for an initial number of epochs, so we do not start optimizing newly initiated weights, and then added to the list of current branches. The choice of how many branches at most are being kept concurrently is a hyperparameter setting, and has a great influence on the total computational cost of the Surgeon.

We then evolve and continuously update the list of concurrent branches until termination criteria, such as max. number of epochs (if limited by computational resources) or a minimum accuracy threshold (if the topology optimization is used without a computational resource bottleneck), are met. At each decision point, the recommendation module analyses all networks in the list of current branches, and ranks all potential modifications as stated above. From these, we select the most promising candidates, and perform the selected operations using the modification module.

The generated candidates are re-trained for several batches, to make up for lost performance, and then scored according to their validation accuracy, validation accuracy gain, and parameter count increase. This composite score serves to reduce greediness of the Surgeon, and is adapted from Cai et al. (2018). Our approach shares Cai et al. (2018)'s rationale that a 1% increase in accuracy should be of higher value if it happens from 90% to 91%, than from 70% to 71%. However, staying constant at 95% accuracy is indicative of a local optimum, whereas an increase from 90% to 94% may suggest a higher ceiling in accuracy. Lastly, a 1% accuracy gain should be worth less if it comes at the cost of a massive increase in network size. We therefore calculate the score as $accuracy + \exp{(accuracy\ gain)}/\exp{(size\ fraction)}$, where the size fraction is the modified network's trainable parameter count as a fraction of its parent's parameter count (cf. appendix A.4). The top scoring candidates are then kept as new concurrent branches, and trained up to the full epoch step.

Table 1: Scoring example. The layer number is given in reference to the hidden layers. Winning operations, that are kept as new concurrent branches, are indicated with an asterisk.

Operation	Position	Accuracy	Acc. gain	Param. frac.	Score
Remove layer *	layer 5	0.6023	0.0274	0.9977	0.9812
Identity *	-	0.6016	0.0268	1.0000	0.9795
Remove 1 Neuron	layer 5	0.5829	0.0081	0.9997	0.9539
Add layer	before layer 4	0.5773	0.0025	1.0030	0.9450
Add 20 Neurons	layer 2	0.5678	-0.0070	2.6544	0.6377

As an option to alleviate greediness, the Surgeon can keep a one cycle memory. In this case, the newly selected concurrent branches are compared to previously best scoring ones, and retained only if their achieved accuracy is at least as good as the previous value. Should this not be the case, they are discarded and we backtrack one step. New potential candidates are provided by the recommendation module, and we train and compare these.

Finally the best scoring branch is returned as the optimized network.

4 EXPERIMENTS

We evaluate the performance of the Surgeon on two standard benchmark datasets: CIFAR-10, and SVHN. We pick three starting topologies that are described in table 2, and perform several runs of the Surgeon on each one. The small one is consciously chosen to be insufficient, to simulate a case where a model is unknowingly trained with an inadequate network architecture. We average our results over several runs and several random seeds, and compare to results achieved by simply training the starting topology for the same number of epochs. Precise machine properties and hyperparameter settings are listed in appendix B.

Table 2: Starting topologies for the Surgeon, excluding input and output layers

Name	Hidden layer count	Hidden layer sizes
Small	1	10
Medium	3	10 - 10 - 10
Large	3	300 - 100 - 100

The CIFAR-10 dataset. The Canadian Institute For Advanced Research (CIFAR)-10 dataset was first published by Krizhevsky (2009). It contains 60,000 32×32 color images that are evenly divided into ten classes. 10,000 of the images are set aside for validation purposes.

Following related works (Cai et al., 2018; Huang et al., 2017), we perform data augmentation by flipping images horizontally, as well as translating by 4 pixels in either up, down, left or right direction. This yields a dataset of 360,000 images. We then normalize these images using channel means and standard deviation.

The SVHN dataset. The (Google) Street View House Number (SVHN) dataset was first published by Netzer et al. (2011). It contains 73,257 training, as well as 26,032 validation color images. We use the cropped version, where images are of size 32×32, and fall into 10 classes according to the numbers 0-9. An additional 531,131 extra images of lesser difficulty are available but currently not used.

We do not apply data augmentation, but divide by 255 in order to scale the data to the range 0-1.

4.1 RESULTS

For our experiments, we apply the Surgeon to each combination of dataset and starting topology (cf table 2). We perform each experiment a total of 15 times, picking a new random seed after every 3 runs, and report average statistics (cf table 3). As a baseline, we train the starting topology for the same number of epochs at each random seed. Note that throughout the entire section, unless otherwise stated, we report achieved validation accuracies rather than training accuracies.

To avoid overfitting on any specific dataset, we fix some hyperparameters for training (such as batch size, optimizer, and learning rate) before starting any runs with the Surgeon (cf. appendix B). No additional fine tuning is performed on any model.

Overall Surgeon performance. Table 3 and figure 1 both show an overview of average Surgeon performance for all starting topologies and datasets. We can see that in all cases, the Surgeon reaches or outperforms the result of the baseline. As expected, achieved accuracies for the SVHN dataset are higher than for the (almost 5 times larger) CIFAR-10 dataset.

Figure 1: Performance of the Surgeon on the SVHN (top row) and CIFAR-10 (bottom row) datasets for each starting topology, compared to training the starting topologies as a baseline. Left to right columns: small, medium and large starting topologies. Averages are calculated over all runs.

In case of the SVHN dataset (figure 1 top row), the baseline for the small starting topology is not able to learn at all, whereas the only slightly larger medium topology is just about sufficient for at least a little bit of learning. The Surgeon is able to improve training in both cases, reaching almost 60% accuracy in case of the medium topology. One first glance it may seem peculiar that the Surgeon on average is able to reach only around 28% accuracy for the small one, given how similar the two of them are. This is due to averaging over several unsuccessful runs as well as a number of successful ones, the latter of which produce results comparable to those achieved on the medium topology.

The large topology trained on SVHN yields similar accuracies with or without the aid of the Surgeon. What we can not see in figure 2 (top right) however, is that the Surgeon on average is able to reduce the total number of trainable parameters by around 7%, with an std of around 32% (cf. table 3 and figure 3 right).

For the CIFAR-10 set (figure 1 bottom row), both the small and medium starting topologies are too small for good results, even with the aid of the Surgeon, achieving an average of 34% and 36% accuracy respectively. On the large starting topology, the Surgeon is able to on average achieve at least a little improvement compared to the baseline. Parameter count is increasing in all three cases, which is indicative of the fact that neither of the chosen topologies is sufficient for a dataset of this size.

Overall it is noteworthy that when growing the network, operations are preferred that add whole layers instead of widening existing layers (data not shown). We will subsequently highlight a few interesting cases.

Table 3: Statistics over all baseline and Surgeon runs. We report means and standard deviations.

Topology	small	medium	large
		SVHN	
Baseline accuracy	0.20 ± 0.00	0.34 ± 0.12	0.78 ± 0.01
Surgeon accuracy	0.29 ± 0.16	0.58 ± 0.04	0.79 ± 0.01
Parameter fraction increase [%]	16.48 ± 52.0	1.97 ± 7.13	-7.23 ± 32.48
		CIFAR-10	
Baseline accuracy	0.28 ± 0.01	0.32 ± 0.01	0.49 ± 0.01
Surgeon accuracy	0.34 ± 0.01	0.36 ± 0.00	0.51 ± 0.00
Parameter fraction increase [%]	1.12 ± 2.85	2.23 ± 1.03	3.76 ± 4.08

Topology rescue. We recall that the small starting topology, consisting of only one hidden layer with 10 neurons, was purposefully chosen to be insufficient for convergence. In fact, as we can see in the left column of figure 1, the baseline learns for neither SVHN nor CIFAR-10. The Surgeon on average manages to improve the topology and learn at least a little, though the achieved validation accuracy of around 29% and 34% respectively seems not great. In the case of SVHN however, the global average over all runs contains several instances where even with the Surgeon, the model is not able to learn at all and stays stuck in the initial state, as well as a number of runs where the Surgeon is able to very quickly leave this local sink and then in fact provides a model that learns very well.

Figure 2: Left: Single run of the Surgeon on the SVHN dataset and small starting topology. Right top: Small starting topology. Right bottom: Topology after 100 epochs training with the Surgeon.

In figure 2 (left), we can see a single run of the Surgeon, where an early *Add Layer* operation allows the network to train properly. The total parameter increase in this case is less than 2%, with the Surgeon preferring to add several small layers rather than widening existing layers. Figure 2 (right) shows the starting topology (top) and the result after training with the Surgeon for 100 epochs (bottom). Note that up until epoch 50, only two layers have been added. In particular in this case, an earlier stopping point would have yielded similar performance with a lower parameter count.

Accuracy increase. The Surgeon is able to detect and improve sub-optimally sized network architectures. This works in cases such as above (figure 2 left), where it is very obvious that little to no learning happens, but also in less apparent ones, where the base topology does learn to a certain extent. In figure 3 (left) we can see a single run of the Surgeon trained on CIFAR-10 where both the large starting topology as well as the Surgeon start learning in a similar fashion and soon reach a plateau. After a while however, the Surgeon is able to perform an *Add Layer* operation that allows the topology to overcome the local optimum which had been reached.

Figure 3: Left: Single run of the CIFAR-10 dataset and large starting topology. The Surgeon manages to overcome the local optimum at around epoch 30. Right: Single run of the Surgeon on the SVHN dataset and large starting topology. The Surgeon is able to reduce the total parameter count by almost 2/3 while still reaching the same overall validation accuracy.

Parameter reduction. As mentioned above, using the large topology as a starting point for the Surgeon does not improve achieved accuracy by any large margin (figure 2, right column). The baseline in this case is already performing quite okay given that we are regarding a very basic

network architecture. In this case we can observe pruning behaviour exhibited by the Surgeon. The composite scoring function that is used to compare competing branches in sec. 3.1 prevents any big jumps in accuracy since they would most likely come at the cost of a (potentially rather large) increase in network size. The scoring function much rather prefers network operations that keep the accuracy more or less constant while also reducing network size. On average, for the SVHN dataset, we are able to reduce the network's parameter count by around 7%. In figure 3 (right) we see an example where with an early *Remove Layer* operation, the Surgeon is able to reduce the total parameter count by almost 66%. The resulting loss in validation accuracy is compensated within just a few epochs of training.

Computational costs. All of our experiments are performed on a standard office computer, without making use of any GPU acceleration (cf. appendix B for detailed specs). In our trials the Surgeon is configured to produce a resulting topology that has been trained for exactly 100 epochs, with decision points every 10 epochs. We allow for a maximum of two concurrent branches, as well as re-drawing from potential branches up to two times. On average, 0.63 re-draws are necessary per decision step, resulting in an average total training amount of around 300 epochs per run of the Surgeon.

We can see from figure 1 that 100 epochs seems to be longer than is necessary for the Surgeon to reach convergence. With appropriate early stopping techniques, and/or a more dynamic training schedule, the total training amount for the Surgeon could be considerably reduced, and the resulting model (including its trained weights) used either as is, or further fine tuned.

5 DISCUSSION AND OUTLOOK

In this paper we presented the Surgeon, a ANN/evolutionary algorithm hybrid optimization designed for neural architecture search. The algorithm utilizes a modification module, that is able to perform minimally invasive network surgeries, where the topology of the network is modified with as little change to overall input-output-behaviour as possible. Additionally, it uses a recommendation module, that analyses a given neural network and indicates which structural changes may be most beneficial. Those changes can be to either increase network width or depth in case of high information density, or a respective decrease, in case network size can be reduced without fear of too high an accuracy loss. Both modules do not utilize any black box behaviour but are based on mathematical tools, which we presented in section 3.

We put the Surgeon to the test on several combinations of starting topologies and the SVHN and CIFAR-10 datasets. We saw that the network generated by the Surgeon is able to outperform the baseline in case of suboptimal topologies, or reach comparable accuracies while pruning the underlying network structure to less resource intensive topologies.

A very important feature of the Surgeon is that it itself is computationally cheap, with little overhead compared to baseline training.

Via hyperparameter settings, it is possible to make use of larger computational power if required/available. For this proof of concept work, we limited ourselves to the most basic and ubiquitous of network structures - dense layers linked strictly in sequence.

For future work we wish to extend and improve both the Surgeon as well as the underlying modules. Currently, the Surgeon follows a static routine, with hyperparameters such as epochs steps, number of selected candidates, or number of concurrent branches staying constant throughout the whole process. This could be changed to a more dynamic approach, and could maybe integrate further features such as adaptive learning rates, or a more sophisticated memory, as well as early stopping mechanisms to improve performance gains compared to baseline training even further. The recommendation module can be improved by finding a closer approximation for the BIC.

Lastly we want to expand the modification module to allow more complex topologies as well, and include an option to cross architecture types. This would allow us to include e.g. convolutional or recurrent elements, change a network from one type to another, or even freely mix and match as required.

REFERENCES

Davis Blalock, Jose Javier Gonzalez Ortiz, Jonathan Frankle, and John Guttag. What is the state of neural network pruning? In I. Dhillon, D. Papailiopoulos, and V. Sze (eds.), *Proceedings of Machine Learning and Systems*, volume 2, pp. 129–146, 2020.

Han Cai, Tianyao Chen, Weinan Zhang, Yong Yu, and Jun Wang. Efficient architecture search by network transformation. In *32nd AAAI Conference on Artificial Intelligence, AAAI 2018*, pp. 2787–2794. AAAI press, jul 2018. ISBN 9781577358008.

Tianqi Chen, Ian J. Goodfellow, and Jonathon Shlens. Net2net: Accelerating learning via knowledge transfer. In Yoshua Bengio and Yann LeCun (eds.), *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, 2016.

Emily L Denton, Wojciech Zaremba, Joan Bruna, Yann LeCun, and Rob Fergus. Exploiting linear structure within convolutional networks for efficient evaluation. In Z. Ghahramani, M. Welling, C. Cortes, N. D. Lawrence, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 27*, pp. 1269–1277. Curran Associates, Inc., 2014.

Christopher DiMattina and Kechen Zhang. How to modify a neural network gradually without changing its input-output functionality. *Neural Computation*, 22(1):1–47, 2010. doi: 10.1162/neco.2009.05-08-781.

Xuanyi Dong and Yi Yang. Searching for a robust neural architecture in four gpu hours. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *Journal of Machine Learning Research*, 20(55):1–21, 2019.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *International Conference on Learning Representations*, 2019.

Ross Girshick. Fast R-CNN. In *2015 IEEE International Conference on Computer Vision (ICCV)*, pp. 1440–1448. IEEE Computer Society, dec 2015. doi: 10.1109/ICCV.2015.169.

Gao Huang, Zhuang Liu, Laurens van der Maaten, and Kilian Q. Weinberger. Densely connected convolutional networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017. doi: 10.1109/CVPR.2017.243.

O. İrsoy and E. Alpaydın. Continuously constructive deep neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 31(4):1124–1133, 2020. doi: 10.1109/TNNLS.2019.2918225.

Kirthevasan Kandasamy, Willie Neiswanger, Jeff Schneider, Barnabas Poczos, and Eric P Xing. Neural architecture search with bayesian optimisation and optimal transport. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 2016–2025. Curran Associates, Inc., 2018.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, University of Toronto, 2009.

Y. Lecun, L. Bottou, Y. Bengio, and P. Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Liam Li and Ameet Talwalkar. Random search and reproducibility for neural architecture search. In *Conference on Uncertainty in Artificial Intelligence (UAI)*, 2019.

Geoffrey F. Miller, Peter M. Todd, and Shailesh U. Hegde. Designing neural networks using genetic algorithms. In *Proceedings of the Third International Conference on Genetic Algorithms*, pp. 379–384. Morgan Kaufmann Publishers Inc., 1989.

Yuval Netzer, Tao Wang, Adam Coates, Alessandro Bissacco, Bo Wu, and Andrew Ng. Reading digits in natural images with unsupervised feature learning. *NIPS Workshop on Deep Learning and Unsupervised Feature Learning*, 2011.

Gideon Schwarz. Estimating the dimension of a model. *Ann. Statist.*, 6(2):461–464, 03 1978. doi: 10.1214/aos/1176344136.

Jian Xue, Jinyu Li, and Yifan Gong. Restructuring of deep neural network acoustic models with singular value decomposition. In *Proceedings of the Annual Conference of the International Speech Communication Association, INTERSPEECH*, pp. 2365–2369, 2013.

Barret Zoph and Quoc V. Le. Neural architecture search with reinforcement learning. In *5th International Conference on Learning Representations*, 2017.

A   APPENDIX A - MATHEMATICAL BACKGROUND

A.1   ADDING LAYERS AND NEURONS LOSS-FREE UNDER PIECEWISE LINEAR ACTIVATION FUNCTIONS

Let Φ denote the activation function of a dense layer, and $\boldsymbol{x}$ an arbitrary input, then

$$\Phi(\boldsymbol{x}) = \Phi(\boldsymbol{I}\Phi(\boldsymbol{x})) \tag{2}$$

if and only if Φ is at least piecewise linear (Chen et al., 2016). In particular, for ReLu activation, adding layers loss free is possible by setting the weight matrix of the new layer to the identity matrix.

$\square$

For adding neurons to a layer, consider the following example. Let $\boldsymbol{x} \in \mathbb{R}^n$ be the input to a layer with weights $\boldsymbol{A} \in \mathbb{R}^{m \times n}$, and $\boldsymbol{B} \in \mathbb{R}^{k \times m}$ the next layer's weights, then the output $\boldsymbol{y} \in \mathbb{R}^k$ is given by

$$\boldsymbol{y} = \boldsymbol{B} \cdot (\boldsymbol{A}\boldsymbol{x}) \tag{3}$$

Note that we have omitted the activation function between the two layers.

In particular, the j^{th} entry of $\boldsymbol{y}$ is given by

$$\boldsymbol{y}_j = (b_{j1}, b_{j2}, \ldots, b_{jm}) \cdot \begin{bmatrix} \sum_{i=1}^{n} x_i a_{1i} \\ \sum_{i=1}^{n} x_i a_{2i} \\ \vdots \\ \sum_{i=1}^{n} x_i a_{mi} \end{bmatrix} \tag{4}$$

$$= b_{j1} \sum_{i=1}^{n} x_i a_{1i} + \cdots + b_{jm} \sum_{i=1}^{n} x_i a_{1m} \tag{5}$$

We now arbitrarily pick unit m and duplicate its incoming and outgoing weights. Note that we also have to divide by 2 in order to keep the total sum constant.

$$= b_{j1} \sum_{i=1}^{n} x_i a_{1i} + \cdots + \frac{b_{jm}}{2} \sum_{i=1}^{n} x_i a_{1m} + \frac{b_{jm}}{2} \sum_{i=1}^{n} x_i a_{1m} \tag{6}$$

$$= (b_{j1}, b_{j2}, \ldots, \frac{b_{jm}}{2}, \frac{b_{jm}}{2}) \cdot \begin{bmatrix} \sum_{i=1}^{n} x_i a_{1i} \\ \sum_{i=1}^{n} x_i a_{2i} \\ \vdots \\ \sum_{i=1}^{n} x_i a_{mi} \\ \sum_{i=1}^{n} x_i a_{mi} \end{bmatrix} \tag{7}$$

This methods yields the exact same output $\boldsymbol{y} \in \mathbb{R}^k$ given input $\boldsymbol{x} \in \mathbb{R}^n$, but the weight matrices $\boldsymbol{A}$ and $\boldsymbol{B}$ are now of dimension $(m+1, n)$ and $(k, m+1)$ respectively.

Recall now that we did not add any activation function so far. Indeed, the equation between (5) and (6) holds true when adding an activation, if and only if this activation is at least piecewise linear.

$\square$

Chen et al. (2016) base their Net2WiderNet and Net2DeeperNet transformation on these steps.

A.2   SINGULAR VALUE DECOMPOSITION AND PROJECTION ON LOWER RANK SUBSPACES

Removing units from a neural network's dense layer can never be done completely loss free, unless the weight matrix is of reduced rank to begin with. Assuming that this is not the case, we need a method to generate the closest possible lower rank representation of our weight matrix, and find a projection onto it. Here we introduce said method and specify what we mean by closest possible.

Singular value decomposition. Let $\boldsymbol{A} \in \mathbb{R}^{m \times n}$ be an arbitrary, real-valued matrix of rank $k \leq \min(m, n)$. Then there exist *orthogonal*[3] matrices $\boldsymbol{U} \in \mathbb{R}^{m \times m}$, $\boldsymbol{V} \in \mathbb{R}^{n \times n}$, as well as a rectangular diagonal matrix $\Sigma \in \mathbb{R}^{m \times n}$ with k non-negative real entries along its diagonal, such that

$$\boldsymbol{A} = \boldsymbol{U} \Sigma \boldsymbol{V}^T. \tag{8}$$

This representation is called the *Singular Value Decomposition* of $\boldsymbol{A}$. The non-negative diagonal entries σ_i of Σ are called *singular values* of $\boldsymbol{A}$, and are usually given in descending order, i.e. $\sigma_1 \geq \sigma_2 \geq \cdots \geq \sigma_k > 0$.

For some applications, a slightly different notation is chosen by dropping any rows and columns of Σ that consist entirely of zeros. This yields a quadratic diagonal matrix $\Sigma \in \mathbb{R}^{k \times k}$ with k non-negative diagonal entries. $\boldsymbol{U} \in \mathbb{R}^{m \times k}$ and $\boldsymbol{V} \in \mathbb{R}^{n \times k}$ are cropped accordingly by dropping the respective columns.

A measure for closeness. Let further $|| \cdot ||_F$ denote the *Frobenius norm*, given by

$$||\boldsymbol{A}||_F^2 = \sum_{i=1}^{m} \sum_{j=1}^{n} |a_{ij}|^2 = \text{trace}(\boldsymbol{A}^T \boldsymbol{A}). \tag{9}$$

It can be shown that $||\boldsymbol{A}||_F^2 = \sum \sigma_i^2(\boldsymbol{A})$, since $\sigma_i(\boldsymbol{A})$ corresponds to the square root of the i^{th} non-zero eigenvalue of $\boldsymbol{A}^T \boldsymbol{A}$.

The closest lower rank representation. The matrices $\boldsymbol{U}$ and $\boldsymbol{V}$ act as projectors to and from a rank k subspace of $\boldsymbol{A}$, spanned by the k non-zero entries σ_i of Σ. If we now wish to find a projection from $\boldsymbol{A}$ to a matrix of rank $r < k$, all we need to do is set the singular values $\sigma_{r+1}, \ldots, \sigma_k$ to zero, yielding a matrix $\boldsymbol{A}_r$ of rank r. The Eckart-Young(-Mirsky) theorem states that this matrix is the closest rank r representation of $\boldsymbol{A}$ under the Frobenius norm, or

$$||\boldsymbol{A} - \boldsymbol{A}_r||_F \leq ||\boldsymbol{A} - \boldsymbol{B}||_F \ \forall \boldsymbol{B} \text{ of } \text{rank}(\boldsymbol{B}) = r. \tag{10}$$

This property is the core for a number of rank reduction techniques such as principal component analysis (PCA).

Application for network modifications. Think now of $\boldsymbol{A}$ as the weight matrix for a dense layer. As we already stated, the singular values σ_i are always non-negative and ordered by descending magnitude. In particular, the magnitudes and magnitude distribution of the singular values allows us to infer how many units are actually needed to carry all of this layer's information.

This number may be surprisingly small compared to the number of units present, since (given a large enough dense layer) normally the first few singular values make up for the majority of contained information, see for example Xue et al. (2013). A number of publications (Denton et al., 2014; Girshick, 2015) make use of this fact for various pruning techniques.

A.3 STATISTICAL CRITERIA FOR MODEL SELECTION

The Bayesian information criterion, also known as Schwarz information criterion (BIC), was derived by Schwarz (1978) to address the problem of selecting between (statistical) models of different dimension. It takes into account the number of parameters of the given model, the sample size of the input data, as well as the a-posteriori model error computed from a likelihood function of the model given its parameters and input data. Since methods from Bayesian statistics are applied, it is assumed that the underlying data is independent and identically distributed from a family of allowed distributions.

The Bayesian information criterion is given by

$$\text{BIC} = \ln n \cdot k - 2 \cdot \ln L, \tag{11}$$

where k is the number of model parameters, n the sample size, and L the likelihood function.

In our application, sample size is constant throughout the whole process. L needs to be estimated or calculated a-posteriori after a network operation has been performed. Our modifications are

---

[3] $\boldsymbol{U}^T \boldsymbol{U} = \boldsymbol{U} \boldsymbol{U}^T = \boldsymbol{I}$

intended to keep the change in input-output behaviour minimal, therefore the difference in L will be very similar between any two modifications. Eq. (11) thus becomes

$$\text{BIC} \approx c_1 \cdot k + c_1 + \Delta L \tag{12}$$

where c_1 and c_2 are constant and ΔL is the (small) change in error depending on the performed operation. Since the number of parameters k may be well above 10^6, we neglect ΔL and the constants, and directly use k as a second order constraint when deciding which modifications to apply.

A.4 EVALUATING COMPETING BRANCHES

Our main objective function is to maximize the accuracy achieved by any given neural network through continuous network surgery. It is therefore sensible to retain those network candidates in algorithm 1, line 10 that reach the highest validation accuracy score. Note that we are scoring accuracy instead of accuracy to avoid overfitting.

Focusing on accuracy alone is a greedy approach and carries the risk of getting stuck in local optima. We overcome this by additionally rewarding modification candidates that show a greater accuracy gain. But gain should not automatically equal gain. We share Cai et al. (2018)'s rationale, that an increase of 1% needs to be weighed higher in case it happens from 90 to 91% accuracy rather than 70 to 71%. At the same time, if an operation keeps the accuracy constant at e.g. 95% we can assume that a local optimum may have been reached. Therefore an operation that leads to an accuracy increase from 90% to 94%, showing potential for further improvement, should be regarded higher even though the reached accuracy is lower. Lastly we do not wish to neglect network size. A 1% accuracy increase might never be favourable at all, if the required increase in network size is "too big".

Note that it is hard to define when a network has indeed become "too big", a fact that is emphasized by the large number of publications dealing with pruning techniques (Blalock et al., 2020).

We need to find a way to balance these three components, and to create a composite score by which we can rank the performance of current branches. As an additional restriction, the composite score should not depend on any global candidate statistics, nor do we want to set a global limit for network size. Therefore we cannot in any meaningful way regard the total number of parameters of a modification candidate, since we lack overall comparison. Instead, for each candidate, we store the network size as a fraction of the candidate's parent's network size. Thus, a network size fraction greater 1 indicates growth, a fraction smaller 1 indicates shrinking, and the identity operation yields a size fraction of exactly 1.

We want the scoring function as well as its first order derivative to be strictly increasing in accuracy gain, but decreasing in size fraction. This behaviour needs to hold even when accuracy gain becomes 0 or network size fraction becomes 1. The following scoring function fulfills all specified requirements:

$$\text{score} = \text{acc} + \frac{\exp\left(\Delta \text{acc}\right)}{\exp\left(\Delta \text{size}\right)} \tag{13}$$

where acc is the current accuracy, Δacc the current accuracy gain, and Δsize the current network size fraction.

B APPENDIX B - HYPERPARAMETER SETTINGS AND MACHINE SPECIFICATIONS

All our simulations were performed on a Windows 10 machine with an Intel(R) Core(TM) i7-9700K CPU 3.6GHz processor and 64,0 GB RAM.

All our code was implemented in python 3.7.7 using tensorflow 2.1.0. We chose the following hyperparameters:

The modification module.

- Re-training multiplicator per modification type:
  - Identity: 1
  - Add Neuron: 1
  - Add Layer: 10
  - Remove Neuron: 10
  - Remove Layer: 10
  - Truncated SVD: 1

The recommendation module.

- Absolute singular value threshold: 0.3
- Relative singular value threshold: 0.005
- Recommendation style: best scoring per modification type
- Include additional random draw: True

The Surgeon.

- Training time for winning branch: 100 Epochs
- Initial pre-training: 10 Epochs
- Interval between decision points: 10 Epochs
- Concurrent branches: 2
- Maximum re-draws per decision step: 2
- Number of batches for re-training: 25

The testing setup.

- Random seeds: 6, 63, 72, 77, 97
- Loss function: Sparse categorical crossentropy
- Optimizer: SGD, learning rate = 0.005
- Metrics: accuracy
- Batch size: 16