DOMAIN-WISE ADVERSARIAL TRAINING FOR OUT-OF-DISTRIBUTION GENERALIZATION

ABSTRACT

Despite the impressive success on many tasks, deep learning models are shown to rely on spurious features, which will catastrophically fail when generalized to out-of-distribution (OOD) data. To alleviate this issue, Invariant Risk Minimization (IRM) is proposed to extract domain-invariant features for OOD generalization. Nevertheless, recent work shows that IRM is only effective for a certain type of distribution shift (*e.g.,* correlation shift) while fails for other cases (*e.g.,* diversity shift). Meanwhile, another thread of method, Adversarial Training (AT), has shown better domain transfer performance, suggesting that it is potential to be an effective candidate for extracting domain-invariant features. In this paper, we investigate this possibility by exploring the similarity between the IRM and AT objectives. Inspired by this connection, we propose Domain-wise Adversarial Training (DAT), an AT-inspired method for alleviating distribution shift by domain-specific perturbations. Extensive experiments show that our proposed DAT can effectively remove the domain-varying features and improve OOD generalization on both correlation shift and diversity shift tasks.

1 INTRODUCTION

Modern deep learning techniques have achieved remarkable success on many tasks (He et al., 2016; Brown et al., 2020). Yet, under some scenarios, deep models will suffer a catastrophic performance degradation since they tend to seize on spurious correlations in the training data (Beery et al., 2018). One of those representative scenarios is the Out-of-Distribution (OOD) generalization, where one expects the trained model to perform well at the test time even when the training and testing data come from different distributions[1]. Another representative scenario under which deep models are unstable is the adversarial example. Researchers have found that deep models are quite brittle since one can inject imperceptible perturbations into the input and cause the model to make wrong predictions with extremely high confidence (Szegedy et al., 2014).

These two issues have some similarities to each other. They both arise because deep networks do not learn the essential causal associations (or intrinsic features). Nevertheless, in their corresponding fields, different approaches are proposed. For OOD generalization, a large class of methods called Invariant Causal Prediction (ICP) (Peters et al., 2016) are proposed. Among them, Invariant Risk Minimization (IRM) (Arjovsky et al., 2019) attracts significant attention, which intends to extract features that are invariant across different data distributions and expects the model to ignore information related to the environment. While for adversarial robustness against adversarial examples, Adversarial Training (AT) (Madry et al., 2018) is the most effective approach at the current stage (Athalye et al., 2018). It trains a model on adversarial examples that are generated by injecting carefully designed perturbations into natural examples. These two fields seem to be independent, and their connections are rarely studied. That is exactly what we are exploring in this paper.

Although IRM and its variants have shown promising on certain tasks, *e.g.,* CMNIST (Arjovsky et al., 2019), recent studies (Gulrajani & Lopez-Paz, 2021) show that on a large-scale controlled experiment on OOD generalization, all these methods fail to exceed the simplest *i.i.d.* baseline, *i.e.,* Empirical Risk Minimization (ERM). Through a dissection of the benchmark datasets, Ye et al.

---

[1]In current literature, the terminologies of "domain", "environment" and "distribution" are often used interchangeably, so we do the same in the whole paper.

(2021) notice that there are actually two types of distribution shifts: correlation shift (same support, different correlation) and diversity shift (different support, same correlation). IRM variants can only perform well at (some) correlation shift tasks while performing poorly for the diversity shift tasks. Thus, we need to seek better alternatives for OOD generalization, while AT seems to be a promising candidate from both theoretical and empirical aspects. Theoretically, by learning invariance *w.r.t.* local input perturbations, AT can be regarded as Distributionally Robust Optimization (DRO) (Rahimian & Mehrotra, 2019; Duchi et al., 2021) over ℓ_p-bounded distributional shift. Thus, AT could reliably extract robust features, *e.g.,* the object shape, from the input. Empirically, several recent works show that AT has better domain transferability than ERM (Salman et al., 2020). These findings naturally leads to the questions:

Will AT perform better than IRM? Will AT be helpful for OOD generalization?

In this paper, we take a further step to answering these intriguing questions. We first reveal the connections between IRM and AT, and find that IRM can be regarded as an instance-reweighted version of Domain-wise Adversarial Training (DAT), a new version of adversarial training that we propose for generalizing Universal Adversarial Training (Moosavi-Dezfooli et al., 2017) to multiple domains. Inspired by this connection, we further explore how DAT performs for OOD data. We first notice that DAT is suitable for solving domain generalization problems as it can effectively remove the relatively static background information with domain-wise perturbations. We further verify this intuition on both synthetic tasks (Xiao et al., 2021) and real-world datasets, where we show clear advantages over ERM. At last, we conduct extensive experiments on benchmark datasets and show our DAT can outperform ERM consistently on both correlation-shift and diversity-shift tasks, and as a result, achieve state-of-the-art performance (in average) on these datasets.

We summarize our contributions as follows:

- We develop a new kind of adversarial training, Domain-wise Adversarial Training (DAT), for domain generalization, and we establish the intrinsic similarity between IRM and domain-wise AT objectives.

- We analyze how DAT will benefit learning invariant features and verify our hypothesis through both synthetic data and real-world datasets.

- Extensive experiments on benchmark datasets show that DAT does not only perform better than ERM at correlation shift tasks like IRM but also outperforms ERM at diversity shift tasks like (sample-wise) AT. Therefore, our methods achieve state-of-the-art results by surpassing ERM at both kinds of distribution shifts.

2 RELATED WORKS

IRM and Its Variants   Invariant Risk Minimization (IRM) (Arjovsky et al. (2019)) develops a paradigm to extract causal (invariant) features and find the optimal invariant classifier on top over several given training environments. The work of Kamath et al. (2021) reveals the gap between IRM and IRMv1, show that even in a simple model that echos the idea of the original IRM objective, IRMv1 can fail catastrophically. Rosenfeld et al. (2021) prove that when the number of training environments is not large enough, IRM can face the risk of using environmental features. There also exists a predictor feasible for IRMv1 that is very similar to the ERM solution.

AT and Its Variants   Szegedy et al. (2014) report one can inject imperceptible perturbations to make deep models be fooled. Athalye et al. (2018) reveal that among the proposed defenses, adversarial training was the only effective one. Adversarial Training (AT) (Madry et al., 2018) is the representative approach to train robust models. Recently, Kamath et al. (2021) show adversarially learned features can transfer better than standardly trained models, and Yi et al. (2021) adopt sample-wise adversarial training for improving OOD robustness. However, their discussion is limited to distributional robustness *w.r.t.* Wasserstein distance, making it less practical for accounting real-world OOD scenarios as discussed in this work.

Evaluating OOD Robustness   Gulrajani & Lopez-Paz (2021) recently noticed that the evaluation criteria are crucial for fair comparison of OOD robustness, where under fair settings, no algorithm

has performed consistently better than vanilla ERM. Ye et al. (2021) further identifies that there exists two kinds of distribution in current benchmark datasets: diversity shift and correlation shift. Diversity shifts refer to the shift of the distribution support, while correlation shifts refer to the change of density on the same support. In particular, they show that there seems to be a trade-off between the two tasks as an algorithm that performs well at one task tends to perform poorly on the other. Instead, in this work, we show that our DAT can achieve superior performance on both correlation-shift and diversity-shift tasks.

Universal Adversarial Training Universal adversarial perturbation proposed by Moosavi-Dezfooli et al. (2017) is a type of adversarial attack that adopts a universal perturbation for all images. Universal adversarial training (UAT) (Shafahi et al., 2020) is then proposed to defend against this attack by training against universally perturbed data. Instead, in our work, we firstly show that we can adapt UAT for solving domain generalization problems.

3 ON THE RELATIONSHIP BETWEEN IRM AND AT

3.1 PRELIMINARY

Notation Let $\Phi : \mathcal{X} \subset R^n \to R^d$ denotes the representation of a θ-parameterized piecewise linear classifier, *i.e.,* $\Phi(\cdot) = \phi^L(W^L\phi^{L-1}(\dots) + b^{L-1}) + b^L$, where ϕ^L is the activation function, and W^L, b^L denote the layer-wise weight matrix and bias vector, collectively denoted by θ. Additionally, let β be the linear classifier on top, and the output of the network is $\beta \cdot \Phi(x) = \beta^\top \Phi(x)$. Let $\ell(\hat{y}, y) = -\log \sigma(y\hat{y})$ be the sample logistic loss. We consider a two-class ($y = \pm 1$) classification setting with output dimension $d = 1$, and our discussion can be easily extended to the general cases.

ERM The traditional Empirical Risk Minimization (ERM) algorithm optimizes over the loss on i.i.d. data, *i.e.,*

$$\min_{\beta,\Phi} R(\beta \cdot \Phi), \text{ where } R(\beta \cdot \Phi) = \mathbb{E}_{(x,y)\sim D}\ell(\beta^\top \Phi(x), y). \tag{1}$$

In OOD generalization problem, one faces a set of (training) *environments* $\mathcal{E}$, where each environment $e \in \mathcal{E}$ corresponds to a unique data distribution D_e. When facing multiple environments, the ERM objective simply mixes the data together and takes the form

$$\text{(ERM)} \quad \min_{\beta,\Phi} \sum_e R^e(\beta \cdot \Phi), \text{ where } R^e(\beta \cdot \Phi) = \mathbb{E}_{(x,y)\sim D_e}\ell(\beta^\top \Phi(x), y). \tag{2}$$

IRM and IRMv1 Instead of simply mixing the data together, IRM seeks to learn an *invariant* representation Φ such that it can be minimizing with the same classifier β. Formally we have

$$\text{(IRM)} \quad \begin{aligned} &\min_{\beta,\Phi} \sum_{e\in\mathcal{E}} R^e(\beta \cdot \Phi) \\ &\text{s.t. } \beta \in \arg\min_{\bar{\beta}} R^e(\bar{\beta} \cdot \Phi), \forall e \in \mathcal{E}. \end{aligned} \tag{3}$$

Since this bi-level optimization problem is difficult to solve, the practical version IRMv1 as regularized ERM, where the gradient penalty is calculated *w.r.t.* a dummy variable w:

$$\text{(IRMv1)} \quad \min_{\beta,\Phi} \sum_{e\in\mathcal{E}} \Big[R^e(\beta \cdot \Phi) + \lambda \cdot \underbrace{||\nabla_{w|w=1.0} R^e(w \cdot (\beta \cdot \Phi))||^2}_{\text{Penalty}_{\text{IRM}}} \Big]. \tag{4}$$

AT Adversarial Training (Madry et al., 2018)) instead replaces ERM with a minimax objective,

$$\text{(AT)} \quad \min_{\beta,\Phi} R^{\text{AT}}(\beta \cdot \Phi) = \min_{\beta,\Phi} \mathbb{E}_{(x,y)\sim D} \max_{||\delta_x||_p \leq \varepsilon} \ell(\beta^\top \Phi(x + \delta_x), y), \tag{5}$$

where one maximizes the inner loss by injecting *sample-wise* perturbations δ_x and solve the outer minimization *w.r.t.* parameters β, Φ on the perturbed sample $(x + \delta_x, y)$. Typically, the perturbation is constrained within an ℓ_p ball with radius ε. In this way, AT can learn models that are robust to ℓ_p perturbations.

UAT Instead of injecting sample-wise perturbations, Moosavi-Dezfooli et al. (2017) notice that we can also adopt a *universal* perturbation δ for all samples, which results in the Unversarial Adversarial Training (UAT) objective as follows:

$$\text{(UAT)}\quad \min_{\beta,\Phi} R^{\text{UAT}}(\beta \cdot \Phi) = \min_{\beta,\Phi} \max_{||\delta||_p \leq \varepsilon} \mathbb{E}_{(x,y)\sim D_e} \ell(\beta^\top \Phi(x+\delta), y),\tag{6}$$

3.2 Relating Adversarial Training to IRM

Motivation As shown above, it seems that IRM and AT are two distinct learning paradigms, while in fact, we can show that IRM is closely related to a certain kind of adversarial training. To see this, we first notice that AT can be rephrased into a regularized ERM loss with a penalty on *sample-wise* robustness through linearization:

$$
\begin{aligned}
R^{\text{AT}}(\beta \cdot \Phi) &= \mathbb{E}_{(x,y)\sim D} \max_{||\delta_x||\leq \varepsilon} \ell(\beta^\top \Phi(x+\delta_x), y)\\
&= \mathbb{E}_{(x,y)\sim D}\Big[\ell(\beta^\top \Phi(x), y) + \max_{||\delta_x||\leq \varepsilon}\big(\ell(\beta^\top \Phi(x+\delta_x), y) - \ell(\beta^\top \Phi(x), y)\big)\Big]\\
&\approx R(\beta \cdot \Phi) + \varepsilon \underbrace{\mathbb{E}_{(x,y)\sim D}\left\|\nabla_x \ell(\beta^\top \Phi(x), y)\right\|}_{\text{Penalty}_{\text{AT}}},
\end{aligned}\tag{7}
$$

which resembles the gradient penalty adopted in IRMv1. One main difference is that AT's penalty is calculated *w.r.t.* sample-wise gradients, while IRM's penalty *w.r.t.* the population loss. This difference motivates us to adopt a population-level perturbation δ instead, which, in the literature of adversarial learning, corresponds to Universal AT (Eq. 6) that could be rephrased as follows:

$$
\begin{aligned}
R^{\text{UAT}}(\beta \cdot \Phi) &= \max_{\|\delta\|\leq \varepsilon} \mathbb{E}_{(x,y)\sim D} \ell(\beta^\top \Phi(x+\delta), y)\\
&= \mathbb{E}_{(x,y)\sim D}\ell(\beta^\top \Phi(x), y) + \max_{\|\delta\|\leq \varepsilon} \mathbb{E}_{(x,y)\sim D}\big(\ell(\beta^\top \Phi(x+\delta), y) - \ell(\beta^\top \Phi(x), y)\big)\\
&\approx R(\beta \cdot \Phi) + \varepsilon \underbrace{\left\|\nabla_x \mathbb{E}_{(x,y)\sim D}\ell(\beta^\top \Phi(x), y)\right\|}_{\text{Penalty}_{\text{UAT}}}.
\end{aligned}\tag{8}
$$

DAT Inspired by the connection above between UAT with IRM, we adapt UAT to the OOD setting with multiple domains and propose Domain-wise Adversarial Training (DAT), which adopts a *domain-wise* perturbation δ_e for each training domain $e \in \mathcal{E}$. Formally, we have

$$
\begin{aligned}
&\min_{\beta,\Phi} \sum_{e\in\mathcal{E}} \mathbb{E}_{(x,y)\sim D_e} \ell\left(\beta^\top \Phi(x+\delta_e)), y\right)\\
&\text{s.t. } \delta_e \in \arg\max_{\|\delta\|\leq\varepsilon} \mathbb{E}_{(x,y)\sim D_e} \ell(\beta^\top \Phi(x+\delta), y), \forall e \in \mathcal{E}.
\end{aligned}\tag{9}
$$

The objective could be interpreted as the loss function of universal training in a domain-wise fashion, which lead to solving for the perturbation vector individually for each domain. We name this method as Domain-wise Adversarial Training (DAT), a generalization of UAT for learning invariance from multiple domains. In practice, we solve the problem above with alternating update of model parameters β, Φ and perturbations δ_e. Specifically, for each mini-batch B_e sampled from domain $\mathcal{D}_e$, we update δ_e with B_e using gradient ascent to find the best adversarial perturbations. Then the adversarial samples are used to train the model. A detailed description is shown in Algorithm 1.

Algorithm 1 Domain-wise Adversarial Training

Input: Dataset of multiple environments $D_e, e \in \mathcal{E}$, desired l_p norm of the perturbation ε, perturbation step size α
Output: Model θ
   Randomly initiate θ, perturbation $\delta_e, \forall e \in \mathcal{E}$
   for iterations $= 1, 2, 3, \ldots$ **do**
      for each environment e **do**
         1. Sample batch B_e from environment e
         2. Update the perturbation δ_e using one-step gradient ascent with step size α
         3. Project the perturbation δ_e to the ℓ_p ball of radius ε
         4. Generate adversarial examples $x_{adv} \leftarrow x + \delta_e, \forall x \in B_i$
         5. Update θ with gradient descent (Adam) on x_{adv}
      end for
   end for

3.3 CONNECTION BETWEEN IRM AND DAT

Here, we establish a formal connection between IRM and DAT. To begin with, we note that DAT can also be reformulated as a regularized ERM in the multi-domain scenario.

$$
R^{\text{DAT}}(\beta \cdot \Phi) = \sum_{e \in \mathcal{E}} \max_{||\delta_e|| \le \varepsilon} \mathbb{E}_{(x,y) \sim D_e} \ell(\beta^\top \Phi(x + \delta_e), y)
$$

$$
= \sum_{e \in \mathcal{E}} \left[\mathbb{E}_{(x,y) \sim D_e} \ell(\beta^\top \Phi(x), y) + \max_{||\delta_e|| \le \varepsilon} \mathbb{E}_{(x,y) \sim D_e} \left(\ell(\beta^\top \Phi(x + \delta_e), y) - \ell(\beta^\top \Phi(x), y) \right) \right]
$$

$$
\approx \sum_{e \in \mathcal{E}} \left[R^e(\beta \cdot \Phi) + \varepsilon \underbrace{\left\| \nabla_x \mathbb{E}_{(x,y) \sim D_e} \ell(\beta^\top \Phi(x), y) \right\|}_{\text{Penalty}_{\text{DAT}}} \right].
$$

$$(10)$$

Based on this reformulation, we can show that there exists an intrinsic relationship between DAT and IRM as in the following proposition:

Proposition 1 *Consider each D_e as the corresponding distribution of a particular training domain e. For any $\beta \cdot \Phi$ as a deep network with any activation function, the penalty term of IRMv1,* $\text{Penalty}_{\text{IRM}}$ *(Eq. 4), could be expressed as the square of a reweighted version of the penalty term of the above approximate target,* $\text{Penalty}_{\text{DAT}}$ *(Eq. 10), on each environment e with coefficients related to the distribution D_e, which could be stated as follows:*

$$
\text{Penalty}_{\text{IRM}} = \left\| \mathbb{E}_{D_e}[L_x x] \right\|^2, \text{ and } \text{Penalty}_{\text{DAT}} = \left\| \mathbb{E}_{D_e} L_x \right\| \tag{11}
$$

where $L_x = (1 - \sigma(y\beta^\top \Phi_x x))y\beta^\top \Phi_x$.

The proposition above shows that IRM can be regarded as an instance-reweighted version of DAT, which indicates that DAT can also be applied to improve out-of-distribution generalization performance. We explore this possibility in the next section.

Besides, assume that each domain only contains one sample, we can further obtain a stronger result, that is, the equivalence between IRM and (linearized) DAT as follows.

Remark 1 (Equivalence under Single-sample Environments) *When the environments degenerate into a single data point, we have the following relationship: If ε is sufficiently small, then for $\beta \cdot \Phi$ as a deep network with any activation function, the penalty term of IRMv1 (Eq. 4) on each sample and the square of the maximization term of Linearized version of Eq. 9 (LDAT, obtained by first-order approximation of DAT)*

$$
\text{Penalty}_{\text{LDAT}} = \left\langle \nabla_x \ell \left(\beta^T \Phi(x), y \right), \pm \hat{\delta}_x \right\rangle \tag{12}
$$

on each sample with perturbation $\hat{\delta}_x = \pm \varepsilon x$ only differ by a fixed multiple ε^2. Which is formally stated as

$$
\text{Penalty}_{\text{LDAT}}^2 = \varepsilon^2 \cdot \text{Penalty}_{\text{IRM}}. \tag{13}
$$

cat on grass cat on snow dog on beach elephant in forest

Figure 1: Images in different domains from NICO dataset and corresponding attention heatmaps of a model trained by ERM. The model has a strong focus on background information.

Proofs of Proposition 1 and Remark 1 can be found in Appendix B.

4   UNDERSTANDING DOMAIN-WISE ADVERSARIAL TRAINING

The above connection between DAT and IRM highlights that our DAT is potentially helpful for addressing OOD problems. In this section, we further explore how domain-wise perturbations could help alleviate distribution shift in real-world scenarios. In particular, we notice that the domain-wise perturbations could successfully remove the domain-varying *background information*, which usually corresponds to the spurious features for image classification tasks. And we empirically verify this property by applying DAT to a well-designed OOD task based on background shift.

4.1   COMPARING ERM TO DAT FOR BACKGROUND REMOVAL

ERM Learns Spurious Background Features   Our understanding of DAT hinges on the insight that an image is composed of a foreground object and the corresponding background, and typically, the object is the invariant feature while the background is only spuriously correlated with the labels. However, models relying on the spurious background information will easily fail when encountering images from a different domain. This phenomenon is also empirically verified by Xiao et al. (2021), who find that models trained on an ImageNet-like dataset with ERM require image backgrounds for correctly classifying large portions of test sets. These findings point out the limitations of ERM and motivate us to find a solution that could effectively learn background-invariant classifier.

Removing Background Information with DAT   Comparing to the failure of ERM above, we notice that Domain-wise Adversarial Training (DAT) can be applied to eliminate the domain-wise background information with its domain-specific perturbations. Take the NICO images in Figure 1 for an example, where samples from the environment "on grass" have a common background dominated by the green grass with low frequency, while the foreground object (*e.g.,* the cats) has complex and instance-specific shape and texture with much higher frequency. In fact, Moosavi-Dezfooli et al. (2017) show that a universal perturbation vector lies in a low dimensional subspace, which fits the background statistics and could be used to eliminate the low-frequency background factor. Therefore, when applying our DAT to these samples, the domain-wise perturbation will capture the common domain-specific background. And consequently, the domain-wise AT will help remove the dependence on these spurious background features.

4.2   EMPIRICAL VERIFICATION WITH CONTROLLED EXPERIMENTS

To verify the above analysis, we construct a synthetic OOD task to evaluate a classifier's dependence on background information. It is based on two datasets introduced by Xiao et al. (2021), Mixed-Same and Mixed-Rand, which are constructed from a subset of ImageNet images with the background of each image replaced by another background that is either from the same class (Mixed-Same) or a random class (Mixed-Rand). As they are perfect candidates for evaluating a classifier

| | Mixed-Same | Mixed-Rand |

Figure 2: Images from Mixed-Same and Mixed-Rand and corresponding attention heatmaps of ERM and DAT, DAT effectively fixed the problem of excessive attention on uncorrelated background information.

in terms of its background dependence, we construct a new OOD task by using Mixed-Same as the training domain and evaluating the learned classifier on Mixed-Rand as the test domain. If the classifier relies too much on background information, it will perform poorly in the test domain where objects and backgrounds are disentangled.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETUP

For the experiments, we follow the setting in Ye et al. (2021) and evaluate OOD generalization on both the two types of distribution shift, diversity shift and correlation shift. In particular, we select four representative tasks. For correlation shift, we use CMNIST (Arjovsky et al., 2019), a synthetic dataset, and NICO He et al. (2020), a real-world dataset. As for diversity shift, we use PACS (Li et al., 2017) and Terra Incognita (Beery et al., 2018). To ensure fair evaluation, we conduct all our experiments following the evaluation pipeline of DomainBed (Gulrajani & Lopez-Paz, 2021). Specifically, we use the same strategy for dataset splitting, model selection, and network backbone as in Ye et al. (2021) for each of these tasks. Details of the experiment settings could be found in Appendix A.2.

5.2 EVALUATION ON BENCHMARK DATASETS

We compare our results with previous works. The results for the CMNIST dataset are adopted from Gulrajani & Lopez-Paz (2021), which is the average of three environments, while the results of the other datasets are adopted from Ye et al. (2021).

From Table 1, we observe that on a variety of OOD benchmark datasets, DAT has a performance consistently better than ERM. In particular, DAT achieves state-of-the-art performance on both diversity and correlation shift tasks. In comparison, IRM only outperforms DAT on CMNIST and sample-wise AT fails on three of the four datasets. We also note that DAT performs slightly worse than IRM on CMNIST, which could possibly be attributed to the data gener-

Table 2: Comparison of test accuracy of different perturbation radius ε and step size α of ℓ_2-norm bounded DAT on the NICO dataset.

Radius ε	Step Size α	Acc (%)
$[10^{-2}, 10^{-1}]$	$[10^{-4}, 10^{-3}]$	72.6 ± 1.7
	$[10^{-3}, 10^{-2}]$	72.0 ± 2.1
	$[10^{-2}, 10^{-1}]$	68.9 ± 1.5
$[10^{-1}, 10^{0}]$	$[10^{-3}, 10^{-2}]$	71.2 ± 0.4
	$[10^{-2}, 10^{-1}]$	66.6 ± 1.7
	$[10^{-1}, 10^{0}]$	69.4 ± 0.4
$[10^{0}, 10^{1}]$	$[10^{-3}, 10^{-2}]$	64.6 ± 0.3
	$[10^{-2}, 10^{-1}]$	67.9 ± 2.0
	$[10^{-1}, 10^{0}]$	67.4 ± 0.4

Table 1: Test accuracy (%) on four representative tasks for OOD Robustness. According to OOD-Bench (Ye et al., 2021), two are correlation-shift tasks, CMNIST and NICO, and two are diversity-shift tasks, PACS and TerraInc. We highlight the top two results on each task.

Algorithm	Correlation-shift Tasks		Diversity-shift Tasks		Avg
	CMNIST	NICO	PACS	TerraInc	
ERM (Baseline)	58.5 ± 0.3	71.4 ± 1.3	81.5 ± 0.0	42.6 ± 0.9	63.5
VREx (Krueger et al., 2021)	56.3 ± 1.9	71.0 ± 1.3	81.8 ± 0.1	40.7 ± 0.7	62.5
GroupDRO (Sagawa* et al., 2020)	61.2 ± 0.6	$\mathbf{71.8 \pm 0.8}$	80.4 ± 0.3	36.8 ± 1.1	62.6
IRM (Ahuja et al., 2020)	$\mathbf{70.2 \pm 0.2}$	67.6 ± 1.4	81.1 ± 0.3	42.0 ± 1.8	$\mathbf{65.2}$
ARM (Zhang et al., 2020)	63.2 ± 0.7	63.9 ± 1.8	81.0 ± 0.4	39.4 ± 0.7	61.9
RSC (Huang et al., 2020)	58.5 ± 0.5	69.7 ± 0.3	$\mathbf{82.8 \pm 0.4}$	$\mathbf{43.6 \pm 0.5}$	63.7
DANN (Ganin et al., 2016)	58.3 ± 0.2	68.6 ± 1.1	81.1 ± 0.4	39.5 ± 0.2	61.9
MMD (Li et al., 2018b)	63.4 ± 0.7	68.3 ± 1.0	81.7 ± 0.2	38.3 ± 0.4	62.9
MTL (Blanchard et al., 2021)	57.6 ± 0.3	70.2 ± 0.6	81.2 ± 0.4	38.9 ± 0.6	62.0
MLDG (Li et al., 2018a)	58.4 ± 0.2	51.6 ± 6.1	73.0 ± 0.4	27.3 ± 2.0	52.6
SagNet (Nam et al., 2021)	58.2 ± 0.3	69.3 ± 1.0	81.6 ± 0.4	42.3 ± 0.7	62.9
CORAL (Sun & Saenko, 2016)	57.6 ± 0.5	68.3 ± 1.4	81.6 ± 0.6	38.3 ± 0.7	61.5
Mixup (Yan et al., 2020)	58.4 ± 0.2	66.6 ± 0.9	79.8 ± 0.6	39.8 ± 0.3	61.2
AT (sample-wise)	57.9 ± 0.4	70.5 ± 0.7	80.9 ± 0.3	42.6 ± 0.3	63.0
DAT (our work)	$\mathbf{68.4 \pm 2.0}$	$\mathbf{72.6 \pm 1.7}$	$\mathbf{82.0 \pm 0.1}$	$\mathbf{42.7 \pm 0.7}$	$\mathbf{66.4}$

ation process of CMNIST. As a synthetic dataset, CMNIST uses colored digits instead of colored background as the spurious features. In contrast, in real-world datasets like NICO (Figure 1), the spurious features mainly lie in the background instead of the object. This suggests that our method is more suitable for alleviating real-world distribution shifts.

5.3 ANALYSIS

We conduct experiments to understand better what our algorithm learns and how the magnitude of hyperparameters affects its performance.

Qualitative Analysis through Semantic Graphs We use GradCam (Selvaraju et al., 2017; Gildenblat & contributors, 2021) to visualize the attention heatmaps of models trained by ERM, sample-wise AT, and DAT on the NICO dataset. The results are shown in Figure 3, where we can see that DAT puts more attention on the object itself instead of the strongly correlated background, while ERM and sample-wise AT tend to use environmental features instead.

Perturbation Radius and Step Size We investigate the effect of perturbation radius ε and perturbation step size α on the NICO dataset. The results are shown in Table 2. From the results, we find that the perturbation radius ε has a huge impact on the OOD accuracy. When ε is too large ($> 10^{-1}$), it begins to hurt the invariant feature and causes performance degradation (from 72.9% to 67.9%). The step size α has a smaller influence, and choosing a value about $1/100$ to $1/10$ times the size of ε would be appropriate.

Table 3: Test accuracy of ℓ_∞-norm bounded DAT on the NICO dataset.

Radius ε	Step Size α	Acc (%)
$[10^{-3}, 10^{-2}]$	$[10^{-4}, 10^{-3}]$	68.5 ± 0.2
$[10^{-2}, 10^{-1}]$	$[10^{-3}, 10^{-2}]$	67.9 ± 2.4
$[10^{-1}, 10^{0}]$	$[10^{-3}, 10^{-2}]$	72.5 ± 1.6

Norm of Perturbations We also investigate the effect of the norm used in DAT. We perform experiments on the NICO dataset using ℓ_∞-norm bounded DAT. The results are shown in Table 3. Although there are slight differences, DAT bounded by both $p = 2$ and $p = \infty$ can achieve state-of-the-art performance (72.6% and 72.5%) on the NICO dataset.

Figure 3: Attention heatmaps of ERM, (sample-wise) AT, and our DAT on the NICO dataset. Compared to ERM and AT, DAT has a more precise focus on the object itself.

6 DISCUSSIONS

Comparison with Sample-wise AT   Previous works (Yi et al., 2021; Hendrycks et al., 2021) try to exploit *sample-wise* AT as a data augmentation strategy to get higher OOD performance. However, the performance only improves when the distribution shift is dominated by diversity shift, *e.g.,* noise, and blurring. Otherwise, the performance might be degraded, as shown in Table 1. One possible explanation is that because sample-wise AT fails to capture the domain-level variations as DAT. As a result, it could possibly add perturbations to the invariant features and lead to inferior performance, especially on correlation-shift tasks.

Comparison with Invariant Causal Prediction   A thread of methods including ICP (Peters et al., 2016), IRM (Arjovsky et al., 2019), and IGA (Koyama & Yamaguchi, 2020) try to find the invariant data representations that could induce an invariant classifier. They have superior performance on synthetic datasets like CMNIST but fail to outperform ERM on real-world datasets (both correlation-shift and diversity-shift tasks). We believe their failures might be attributed to the lack of prior information in their invariant learning principles. While in our DAT, we effectively exploit the foreground-background difference in image classification tasks through domain-wise perturbations.

7 CONCLUSION

In this work, we carefully analyze the similarity between IRM and adversarial training in a domain-wise fashion and establish a formal connection between OOD and adversarial robustness. Based on this connection, we propose a new adversarial training method for domain generalization, namely Domain-wise Adversarial Training (DAT). We show that it could effectively remove the spurious background features in image classification and obtain superior performance on benchmark datasets. Notably, our DAT could outperform ERM consistently on both correlation-shift and diversity-shift tasks, while previous methods typically fail in one of the two cases.

REFERENCES

Kartik Ahuja, Karthikeyan Shanmugam, Kush Varshney, and Amit Dhurandhar. Invariant risk minimization games. In *ICML*, 2020.

Martin Arjovsky, Léon Bottou, Ishaan Gulrajani, and David Lopez-Paz. Invariant risk minimization. *arXiv preprint arXiv:1907.02893*, 2019.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *ICML*, 2018.

Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *ECCV*, 2018.

Gilles Blanchard, Aniket Anand Deshmukh, Ürün Dogan, Gyemin Lee, and Clayton D. Scott. Domain generalization by marginal transfer learning. *J. Mach. Learn. Res.*, 22:2:1–2:55, 2021.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *NeurIPS*, 2020.

John C Duchi, Peter W Glynn, and Hongseok Namkoong. Statistics of robust optimization: A generalized empirical likelihood approach. *Mathematics of Operations Research*, 2021.

Yaroslav Ganin, E. Ustinova, Hana Ajakan, Pascal Germain, H. Larochelle, François Laviolette, Mario Marchand, and Victor S. Lempitsky. Domain-adversarial training of neural networks. *J. Mach. Learn. Res.*, 17:59:1–59:35, 2016.

Jacob Gildenblat and contributors. Pytorch library for cam methods. `https://github.com/jacobgil/pytorch-grad-cam`, 2021.

Ishaan Gulrajani and David Lopez-Paz. In search of lost domain generalization. In *ICLR*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Yue He, Zheyan Shen, and Peng Cui. Towards non-iid image classification: A dataset and baselines. *Pattern Recognition*, pp. 107383, 2020.

Dan Hendrycks, Steven Basart, Norman Mu, Saurav Kadavath, Frank Wang, Evan Dorundo, Rahul Desai, Tyler Zhu, Samyak Parajuli, Mike Guo, Dawn Song, Jacob Steinhardt, and Justin Gilmer. The many faces of robustness: A critical analysis of out-of-distribution generalization. In *ICCV*, 2021.

Zeyi Huang, Haohan Wang, Eric P. Xing, and Dong Huang. Self-challenging improves cross-domain generalization. In *ECCV*, 2020.

Pritish Kamath, Akilesh Tangella, Danica J. Sutherland, and Nathan Srebro. Does invariant risk minimization capture invariance? In *AISTATS*, 2021.

Masanori Koyama and Shoichiro Yamaguchi. When is invariance useful in an out-of-distribution generalization problem? *arXiv preprint arXiv:2008.01883*, 2020.

David Krueger, Ethan Caballero, Jörn-Henrik Jacobsen, Amy Zhang, Jonathan Binas, Dinghuai Zhang, Rémi Le Priol, and Aaron C. Courville. Out-of-distribution generalization via risk extrapolation (rex). In *ICML*, 2021.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Deeper, broader and artier domain generalization. In *ICCV*, 2017.

Da Li, Yongxin Yang, Yi-Zhe Song, and Timothy M Hospedales. Learning to generalize: Meta-learning for domain generalization. In *AAAI*, 2018a.

Haoliang Li, Sinno Jialin Pan, Shiqi Wang, and Alex C Kot. Domain generalization with adversarial feature learning. In *CVPR*, 2018b.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *ICLR*, 2018.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. In *CVPR*, 2017.

Hyeonseob Nam, HyunJae Lee, Jongchan Park, Wonjun Yoon, and Donggeun Yoo. Reducing domain gap by reducing style bias. In *CVPR*, 2021.

Jonas Peters, Peter Bühlmann, and Nicolai Meinshausen. Causal inference by using invariant prediction: identification and confidence intervals. *Journal of the Royal Statistical Society. Series B (Statistical Methodology)*, 2016.

Hamed Rahimian and Sanjay Mehrotra. Distributionally robust optimization: A review. *arXiv preprint arXiv:1908.05659*, 2019.

Elan Rosenfeld, Pradeep Kumar Ravikumar, and Andrej Risteski. The risks of invariant risk minimization. In *ICLR*, 2021.

Shiori Sagawa*, Pang Wei Koh*, Tatsunori B. Hashimoto, and Percy Liang. Distributionally robust neural networks. In *ICLR*, 2020.

Hadi Salman, Andrew Ilyas, Logan Engstrom, Ashish Kapoor, and Aleksander Madry. Do adversarially robust imagenet models transfer better? In *NeurIPS*, 2020.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *ICCV*, 2017.

Ali Shafahi, Mahyar Najibi, Zheng Xu, John P. Dickerson, Larry S. Davis, and Tom Goldstein. Universal adversarial training. In *AAAI*, 2020.

Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *ECCV*, 2016.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, D. Erhan, Ian J. Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *CoRR*, abs/1312.6199, 2014.

Kai Yuanqing Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image backgrounds in object recognition. In *ICLR*, 2021.

Shen Yan, Huan Song, Nanxiang Li, Lincan Zou, and Liu Ren. Improve unsupervised domain adaptation with mixup training. *arXiv preprint arXiv:2001.00677*, 2020.

Nanyang Ye, Kaican Li, Lanqing Hong, Haoyue Bai, Yiting Chen, Fengwei Zhou, and Zhenguo Li. Ood-bench: Benchmarking and understanding out-of-distribution generalization datasets and algorithms. *arXiv preprint arXiv:2106.03721*, 2021.

Mingyang Yi, Lu Hou, Jiachen Sun, Lifeng Shang, Xin Jiang, Qun Liu, and Zhi-Ming Ma. Improved ood generalization via adversarial training and pre-training. In *ICML*, 2021.

Marvin Zhang, Henrik Marklund, Nikita Dhawan, Abhishek Gupta, Sergey Levine, and Chelsea Finn. Adaptive risk minimization: A meta-learning approach for tackling group distribution shift. *arXiv preprint arXiv:2007.02931*, 2020.

A EXPERIMENT SETTINGS AND MORE DETAILED RESULTS

We train all the models based on the DomainBed benchmark presented in Gulrajani & Lopez-Paz (2021).

A.1 MIXED-SAME AND MIXED-RAND

To construct the dataset, we use the validation set of Mixed-Same (4185 images) provided by Xiao et al. (2021) as the training environment and use the validation set of Mixed-Rand (4185 images) as the testing (OOD) environment.

For training, we use pretrained ResNet-18 as backbone and train it for 5000 iterations. The hyperparameters are same to those proposed in Gulrajani & Lopez-Paz (2021), except that the learning rate searching interval is altered to [1e-5.5, 1e-4.5], while we set hyperparameters search space of DAT as $\varepsilon \in$ [1e-0.5, 1e0], $\alpha \in$ [1e-1.5, 1e-1].

A.2 TYPICAL OOD DATASETS

We conduct experiments on four typical OOD datasets, including CMNIST, NICO, Terra Incognita, and PACS. We split the NICO dataset using the same strategy in Ye et al. (2021) for a fair comparison.

For network architecture, models trained on CMNIST adopt the four-layer convolution network MNIST-CNN crafted in DomainBed benchmark (Gulrajani & Lopez-Paz, 2021), while other datasets use ResNet-18 as the backbone. For Terra Incognita and PACS, pretrained ResNet-18 is used, while on NICO, we use unpretrained ResNet-18 as it contains photos that are largely overlapped with ImageNet classes.

For model selection, models trained on PACS and Terra Incognita are selected by training-domain validation. For NICO, the OOD validation method is adopted using an OOD validation set. CMNIST, due to the large correlation shift, uses test-domain validation as its model selection criteria.

DAT models are trained for an appropriate number of iterations to ensure convergence, that is, 5000 for Terra Incognita, 8000 for NICO, 10000 for CMNIST and PACS.

When training NICO, we clamp the single sample adversarial loss to $(0, 2)$ to obtain a better domain-wise perturbation as suggested in Shafahi et al. (2020).

We use the same hyperparameters as those proposed in Ye et al. (2021) whenever possible while setting the hyperparameters search space for DAT and sample-wise AT as in Table 4 and 5. We use DAT with perturbation bounded by ℓ_2-norm in our experiments. For sample-wise AT, we use a 10-step ℓ_2 PGD (Madry et al., 2018).

Table 4: Hyperparameter Search Space for DAT on Typical OOD Datasets

Dataset	Radius ε	Step Size α
CMNIST	$[10^{-1}, 10^2]$	$[10^{-2}, 10^1]$
NICO	$[10^{-2}, 10^{-1}]$	$[10^{-4}, 10^{-3}]$
PACS	$[10^{-1}, 10^2]$	$[10^{-2}, 10^1]$
TerraInc	$[10^{-0.5}, 10^{0.7}]$	$[10^{-2}, 10^{-1}]$

Table 5: Hyperparameter Search Space for (sample-wise) AT on Typical OOD Datasets

Dataset	Radius ε	Step Size α
CMNIST	$[10^{-1}, 10^1]$	$[10^{-2}, 10^0]$
NICO	$[10^{-1}, 10^0]$	$[10^{-2}, 10^{-1}]$
PACS	$[10^{-1}, 10^1]$	$[10^{-2}, 10^0]$
TerraInc	$[10^{-1}, 10^0]$	$[10^{-2}, 10^{-1}]$

The more detailed results for DAT are shown in Table 6, 7, and 8.

Table 6: Accuracy of DAT on CMNIST

Validation	0.1	0.2	0.9	Average
Training Domain	72.4 ± 0.2	73.7 ± 0.1	10.2 ± 0.2	52.1 ± 0.1
Test Domain (Oracle)	78.5 ± 4.8	79.3 ± 0.2	47.5 ± 2.6	68.4 ± 2.0

Table 7: Accuracy of DAT on PACS

Validation	A	C	P	S	Average
Training Domain	80.0 ± 0.3	77.6 ± 0.8	92.6 ± 0.9	77.6 ± 0.5	82.0 ± 0.1
Test Domain (Oracle)	79.7 ± 0.1	74.9 ± 0.7	93.9 ± 0.6	78.1 ± 0.4	81.7 ± 0.2

Table 8: Accuracy of DAT on Terra Incognita

Validation	L100	L38	L43	L46	Average
Training Domain	53.8 ± 1.6	35.1 ± 2.3	50.3 ± 0.3	31.7 ± 0.6	42.7 ± 0.7
Test Domain (Oracle)	54.1 ± 2.3	42.5 ± 2.1	52.7 ± 0.8	35.1 ± 1.0	46.1 ± 0.6

B PROOFS

We give a proof of Remark 1 first, then use a similar technique to prove Proposition 1.

Remark 1 (Equivalence under Single-sample Environments) *When the environments degenerate into a single data point, we have the following relationship: If ε is sufficiently small, then for $\beta \cdot \Phi$ as a deep network with any activation function, the penalty term of IRMv1 (Eq. 4) on each sample and the square of the maximization term of Linearized version of DAT (LDAT, obtained by first-order approximation of DAT)*

$$\text{Penalty}_{\text{LDAT}} = \left\langle \nabla_x \ell \left(\beta^T \Phi(x), y \right), \pm \hat{\delta}_x \right\rangle \tag{14}$$

on each sample with $\hat{\delta}_x = \pm \varepsilon x$ only differ by a fixed multiple ε^2. Which is formally stated as

$$\text{Penalty}^2_{\text{LDAT}} = \varepsilon^2 \cdot \text{Penalty}_{\text{IRM}}. \tag{15}$$

Proof of Remark 1 Note that we presume Φ is piece-wise linear. We represent the output logit of the given deep network as $\beta^\top \Phi(x) = \beta^\top \Phi_x x$ where Φ_x is the matrix related to sample x due to the fact of different activation patterns.

We first derive the form of $\text{Penalty}_{\text{LDAT}}$ by first-order approximation of Eq. 9.

$$\ell(\beta^\top \Phi(x + \delta_e), y) - \ell(\beta^\top \Phi(x), y) \approx \left\langle \nabla_x \ell(\beta^\top \Phi(x), y), \delta_e \right\rangle \tag{16}$$

Letting $\delta_e = \pm \varepsilon x$, we have that

$$\text{Penalty}_{\text{LDAT}} = \left\langle \nabla_x \ell \left(\beta^T \Phi(x), y \right), \pm \hat{\delta}_x \right\rangle \tag{17}$$

The penalty term of IRMv1 on each sample is as follows:

$$\begin{aligned}
&\left\| \nabla_{w|w=1.0} - \log(\sigma(w \cdot (y\beta^\top \Phi(x)))) \right\|^2 \\
&= \left\| -\frac{\sigma'(w \cdot (y\beta^\top \Phi(x)))}{\sigma(w \cdot (y\beta^\top \Phi(x)))} y\beta^\top \Phi(x) \right\|^2 \\
&= \left\| -(1 - \sigma(y\beta^\top \Phi(x)))y\beta^\top \Phi(x) \right\|^2 \\
&= (1 - \sigma(y\beta^\top \Phi(x)))^2 \left\| \beta^\top \Phi_x x \right\|^2
\end{aligned} \tag{18}$$

For LDAT, note that the gradient *w.r.t.* x is equal to

$$\nabla_x [-\log(\sigma(y\beta^\top \Phi(x)))] = -(1 - \sigma(y\beta^\top \Phi(x)))y\beta^\top \Phi_x$$

So the square of the penalty term of LDAT on each sample with perturbation $\pm \varepsilon x$ is:

$$[\langle \nabla_x - \log(\sigma(y\beta^\top \Phi(x))), \pm \varepsilon x \rangle]^2 = \varepsilon^2 (1 - \sigma(\beta^\top \Phi(x)))^2 \left\| \beta^\top \Phi_x x \right\|^2 \tag{19}$$

which is identical to Eq. 4 with a difference of multiple ε^2.

$\square$

Proposition 1 *Consider each D_e as the corresponding distribution of a particular training domain e. For any $\beta \cdot \Phi$ as a deep network with any activation function, the penalty term of IRMv1, $\text{Penalty}_{\text{IRM}}$ (Eq. 4), could be expressed as the square of a reweighted version of the penalty term of the above approximate target, $\text{Penalty}_{\text{DAT}}$(Eq. 10), on each environment e with coefficients related to the distribution D_e, which could be stated as follows:*

$$\text{Penalty}_{\text{IRM}} = \left\| \mathbb{E}_{D_e}[L_x x] \right\|^2, \ and \ \text{Penalty}_{\text{DAT}} = \left\| \mathbb{E}_{D_e} L_x \right\| \tag{20}$$

where $L_x = (1 - \sigma(y\beta^\top \Phi_x x))y\beta^\top \Phi_x$.

Proof of Proposition 1 For IRMv1, from the proof of Remark 1 we know

$$\nabla_{w|w=1.0}\ell(w \cdot (\beta \cdot \Phi), y) = -(1 - \sigma(y\beta^\top \Phi_x x))y\beta^\top \Phi_x x \tag{21}$$

So that $\text{Penalty}_{\text{IRM}}$ (suppose derivation and integration are commutable)

$$\left\| \nabla_{w|w=1.0} R^e(w \cdot (\beta \cdot \Phi)) \right\|^2 = \left\| \mathbb{E}_{D_e}(1 - \sigma(y\beta^\top \Phi_x x))y\beta^\top \Phi_x x \right\|^2 \tag{22}$$

For DAT, on each environment

$$
\begin{aligned}
&\max_{\|\delta_e\| \leq \varepsilon} \mathbb{E}_{D_e}\left[\ell(\beta^\top \Phi(x + \delta_e), y) - \ell(\beta^\top \Phi(x), y)) \right] \\
&\approx \max_{\|\delta_e\| \leq \varepsilon} \mathbb{E}_{D_e}\left[\left\langle \nabla_x \ell(\beta^\top \Phi(x), y), \delta_e \right\rangle \right] \\
&= \max_{\|\delta_e\| \leq \varepsilon} \left\langle \mathbb{E}_{D_e}\left[\nabla_x \ell(\beta^\top \Phi(x), y) \right], \delta_e \right\rangle \\
&= \varepsilon \left\| \mathbb{E}_{D_e}\left[\nabla_x \ell(\beta^\top \Phi(x), y) \right] \right\|
\end{aligned}
\tag{23}
$$

So $\text{Penalty}_{\text{DAT}}$ is

$$\left\| \mathbb{E}_{D_e}\left[\nabla_x \ell(\beta^\top \Phi(x), y) \right] \right\| = \left\| \mathbb{E}_{D_e}\left[-(1 - \sigma(y\beta^\top \Phi(x)))y\beta^\top \Phi_x \right] \right\| \tag{24}$$

So we know $\text{Penalty}_{\text{IRM}}$ can be regarded as the square of a *reweighted* version of $\text{Penalty}_{\text{DAT}}$ with coefficient on each sample inside the expectation x.

$\square$