ACT-in-LLM: Adaptively Compression Vision Tokens in LLM for High-Resolution Multimodal Large Language Models

Abstract

High-resolution inputs empower Multimodal Large Language Models (MLLMs) to capture intricate visual details, thereby enhancing comprehension. However, the self-attention mechanism's quadratic complexity poses significant computational and memory challenges as image resolution increases, particularly with long-vision tokens. Existing approaches generally alleviate these issues by reducing vision tokens before feeding them into LLMs. Although efficient, this Pre-LLM compression strategy fails to match the performance of models utilizing all tokens, particularly on high-resolution benchmarks. Our experiments reveal that the performance gap arises from this strategy's limitation in selecting important visual tokens in early LLM layers, leading to the irretrievable loss of critical information. To overcome these challenges, we propose a new strategy that **A**daptively **C**ompresses vision **T**okens with**in** different **LLM** layers, named ACT-in-LLM. Our innovative approach retains all tokens throughout the layers to ensure no vital information is lost while compressing key and value tokens in the self-attention mechanism, to reduce computational costs. The layer-wise compression of ACT-in-LLM is guided by the interaction information between vision and text tokens, leading to more accurate selections. Our theoretical analysis and extensive experiments demonstrate the effectiveness of ACT-in-LLM, showing a 6.3% improvement over existing token compression techniques. It also achieves the competitive performance with non-compression methods, while reducing training/inference time by $\sim 20\%$ and vision tokens by $\sim 60\%$.

1 Introduction

In recent years, large language models (LLMs) like GPT-4 (Achiam et al., 2023) and LLaMA (Dubey et al., 2024) have driven advancements in multimodal LLMs (MLLMs), which integrate visual and textual data for better cross-modal understanding (Li et al., 2023c; 2024a; Bai et al., 2023; Zhang et al., 2023; Cheng et al., 2024; Ding et al., 2024). However, MLLMs often process low-resolution visual inputs, limiting fine-grained scene comprehension. While efforts to support high-resolution inputs (Li et al., 2024d; Xu et al., 2024; Li et al., 2024a) exist, they face substantial computational and memory challenges due to the quadratic complexity of self-attention (Vaswani, 2017).

(a) Pre-LLM Compression   (b) Ours

Figure 1: **(a) Pre-LLM Compression Strategy** reduces the number of visual tokens before passing them into the LLM, inevitably leading to information loss. **(b) Our ACT-in-LLM** reserves full tokens for final auto-regressive prediction, while adaptively compressing vision tokens within the specific LLM layers.

To tackle these challenges, existing methods primarily rely on Pre-LLM (Xu et al., 2024; Chen et al., 2024a; Liu et al., 2024c; Huang et al., 2024; Cha et al., 2024) or Early-LLM (Chen et al., 2024a) compression, where the number of visual tokens is reduced before being fed into the LLM or in the early layers of the LLM. This strategy helps lower the computational load and offers competitive

(a)   (b)

Figure 2: **Drawbacks of the early compression. (a) Performance vs. Vision Token Dropping Layers.** The x-axis is the layer index dropping vision tokens, with 0 indicating before the LLM, and the y-axis is the average performance across benchmarks. We observe that *dropping tokens in earlier layers significantly reduces performance on high-resolution tasks by up to* 15%. **(b) Attention Scores Across Layers.** 'hr', 'lr' and 'txt' mean the high-resolution, low-resolution and text tokens respectively. We observe that *early-stage token selection is challenging as low-attention tokens in early layers may gain importance later (see red dotted boxes).*

performance in general MLLM tasks. However, as shown in Table. 2, there is a notable performance gap ($\sim 9\%$) on high-resolution benchmarks when compared to models that retain all visual tokens.

To investigate this performance gap, we conduct experiments to compare the average performance of compressing vision tokens at different LLM layers on high-resolution and general benchmarks respectively (see Section F.1 for details). We compare four methods: full (all tokens retained), average (dropped based on averaged attention scores), separate (current layer scores, *i.e.*, FastV (Chen et al., 2024a)), and last (final layer scores). In each method, once compression is applied in the specific layer, only 50% of the visual tokens are retained in subsequent layers. Fig.2 (a) shows that the performance gap widens when compression occurs in earlier layers. Additionally, the visualization of the average attention weights of LLaVA-1.5-HD (Fig.2 (b)) shows that vision tokens receiving low attention in early layers become critical in the latter, showing the risks of compressing tokens prematurely. In summary, *existing Pre-LLM approaches compress vision tokens too early, leading to irreversible performance degradation*, potentially due to: (1) early-layer's insufficient interaction between vision and text tokens, (2) varying token importance across layers, making it difficult to decide which tokens to drop, and (3) the inability to recover lost information in latter layers.

To address the above drawbacks, we propose a novel compression strategy, ACT-IN-LLM, which **A**daptively **C**ompresses vision **T**okens **within** different LLM layers. Unlike existing methods that discard tokens prematurely, ACT-IN-LLM retains all tokens across layers, ensuring an implicit error correction mechanism that mitigates the loss of critical information (see Fig. 1 (b)). To reduce computational and memory overhead, ACT-IN-LLM uniformly integrates an adaptive compression module (ACM) into various transformer decoder layers, selectively compressing only the key and value tokens within the self-attention mechanism. Specifically, ACM utilizes the final token in each layer's hidden states— which encodes the complete multimodal context— to guide visual token compression, ensuring more accurate token selection, compared with early-layer selection.

We theoretically demonstrate that this key-value compression used in ACT-IN-LLM provides a better low-rank approximation of the full-token self-attention mechanism compared to the query or all compression used in existing vision token compression techniques. Extensive experiments on high-resolution and general benchmarks, across LLMs of varying sizes (0.5B to 7B parameters), show that ACT-IN-LLM achieves a 6.2% improvement over existing token compression techniques, and competitive performance compared with non-compression models while reducing training/inference time by $\sim 20\%$ and vision tokens by $\sim 60\%$.

2 RELATED WORKS

Multimodal Large Language Models. Advanced Large Language Models (LLMs) like GPT-4 (OpenAI, 2023), Mistral (Jiang et al., 2023), and Gemini (Team et al., 2023) excel in reasoning, while Multimodal LLMs (MLLMs), such as LLaVA (Liu et al., 2023b), MiniGPT-4 (Zhu et al., 2023), and QwenVL (Bai et al., 2023), extend this to images, though limited resolution hampers fine-grained visual understanding. To address this, splitting images into patches (Bavishi et al.,

2023; Li et al., 2023a) and up-resizing methods (Bai et al., 2023) improve resolution, though they introduce issues like poor visual representation and positional encoding disruptions (Radford et al., 2021). Dual-branch methods add high-resolution branches but increase complexity and training data requirements (Hong et al., 2024; Ding et al., 2023). Cropping strategies offer a more efficient approach by dividing high-resolution images into patches without increasing model parameters (Li et al., 2024d; Xu et al., 2024; Huang et al., 2024). However, increasing image resolution leads to higher computational costs due to the quadratic complexity of self-attention (Vaswani, 2017). This paper is aimed at developing efficient high-resolution MLLMs.

Vision Token Compression in MLLMs. Vision Token Compression in MLLMs. Existing methods for vision token compression can be categorized into interaction-based and pre-LLM strategies. Interaction-based approaches (Hong et al., 2024; Li et al., 2024b; Tong et al., 2024) process low-resolution tokens in the LLM while using a high-resolution branch with lightweight cross-attention for feature interaction. However, these methods fail to fully align high-resolution visual inputs with the LLM's low-resolution and text representations, requiring additional parameters and training data (Huang et al., 2024; Yao et al., 2024). Pre-LLM approaches, on the other hand, reduce tokens before entering the LLM, employing either parameterized (Bai et al., 2023; Li et al., 2023c; Cha et al., 2024; Xu et al., 2024) or non-parameterized (Liu et al., 2024a; Yao et al., 2024; Shang et al., 2024) techniques. Recently, Early-LLM methods such as FastV (Chen et al., 2024a) discard tokens during early LLM layers at inference but risk losing critical information due to suboptimal token selection. In contrast, ACT-IN-LLM introduces adaptive token compression at multiple LLM layers, retaining all tokens for final predictions to minimize information loss. Theoretical analysis and experiments demonstrate that ACT-IN-LLM outperforms existing approaches in efficiency and effectiveness.

Efficient Attention in Transformer Models. To reduce the computation and memory costs associated with the self-attention mechanism in Transformers, various alternative attention mechanisms have been proposed (Child et al., 2019; Zaheer et al., 2020; Wang et al., 2020; Choromanski et al., 2020). For instance, Sparse Transformer (Child et al., 2019) employs fixed sparse attention patterns to reduce complexity. BIGBIRD (Zaheer et al., 2020) extends this approach by combining multiple attention patterns, including window, random, and global attention, for further efficiency. Reformer (Kitaev et al., 2020) replaces traditional self-attention with locality-sensitive hashing (LSH) to reduce computation costs. Similarly, Axial Transformer (Beltagy et al., 2020) applies attention along single axes of input tensors, significantly lowering the computational burden. PvT-V2 (Wang et al., 2022) leverages the average-pooling to reduce the tokens of the key and value. All of the above methods primarily target single-modal tasks. In contrast, our work focuses on reducing vision tokens based on the multi-modal information in MLLMs for high-resolution multimodal tasks.

3 METHOD

3.1 OVERALL FRAMEWORK

As illustrated in Fig. 3, ACT-IN-LLM comprises two components: (i) a vision/text tokenizer that processes an image and a question to generate concatenated vision-text embeddings, and (ii) a large language model (LLM) that utilizes these embeddings to predict responses.

Vision/Text Tokenizer. The input image is processed using a cropping strategy (Li et al., 2024a;d), producing multiple slices and a low-resolution slice. The original image is resized and padded into a low-resolution slice. To capture fine-grained details, the high-resolution image is dynamically split into slices, with a maximum slice count determined by the base resolution. This allows the image to automatically select an optimal bounding box by calculating the required rows and columns. These slices, along with the low-resolution slice, are then processed through a shared vision tokenizer like CLIP-ViT (Radford et al., 2021), to produce slice-wise vision embeddings. These embeddings are concatenated, with a connector such as a linear layer (Li et al., 2024a) generating the aligned vision representation $\mathbf{H}_0^{\text{vis}} \in \mathbb{R}^{N \times D}$, where N is the total number of vision tokens and D is the embedding dimension. Concurrently, we use the LLM's tokenizer to convert the question into text embeddings, denoted as $\mathbf{H}_0^{\text{txt}} \in \mathbb{R}^{L \times D}$, with L representing the number of text tokens. Finally, the visual and text embeddings are concatenated into $\mathbf{H}_0 = [\mathbf{H}_0^{\text{hr}}, \mathbf{H}_0^{\text{lr}}, \mathbf{H}_0^{\text{txt}}] \in \mathbb{R}^{(N+L) \times D}$ for the LLM.

Large Language Model (LLM). Existing LLMs, such as Qwen2 (Yang et al., 2024), LLaMA3 (Dubey et al., 2024) generally consist of several Transformer decoder layers, each of which consists of the multi-head self-attention layer (MSA) and feed-forward network (FFN). The MSA is the critical component of the decoder layer to learn the dense relation between tokens. For-

Figure 3: **Framework of ACT-IN-LLM.** Our ACT-IN-LLM framework follows the general slicing-based MLLMs (Liu et al., 2024b), while applying the adaptive compression module (ACM) at a series of decoder layers of the LLM for computation efficiency, dynamically reducing key/value tokens before the multi-head self-attention (MHA) block, while preserving all query tokens.

mally, given the hidden-states $\mathbf{H}_i \in \mathbb{R}^{(N+L) \times D}$ from the i-th layer of the LLM, the single attention head $h \in \{1, 2, ..., H\}$ can be defined as following:

$$\text{head}_{i,h} = \text{Attention}(\mathbf{Q}_{i,h}, \mathbf{K}_{i,h}, \mathbf{V}_{i,h}, \mathbf{M}_i) = \underbrace{\text{softmax}\left(\frac{\mathbf{Q}_{i,h}\mathbf{K}_{i,h}^{\top}}{\sqrt{D}} + \mathbf{M}_i\right)}_{\mathbf{A}_{i,h}} \mathbf{V}_{i,h}, \quad (1)$$

where $\mathbf{Q}_{i,h} = \mathbf{W}_{i,h}^Q \mathbf{H}_i$, $\mathbf{K}_{i,h} = \mathbf{W}_{i,h}^K \mathbf{H}_i$ and $\mathbf{V}_{i,h} = \mathbf{W}_{i,h}^V \mathbf{H}_i$ are the query, key and value matrices, $\mathbf{W}_{i,h}^Q / \mathbf{W}_{i,h}^K \in \mathbb{R}^{D_k \times D}$, $\mathbf{W}_{i,h}^V \in \mathbb{R}^{D_v \times D}$ are the learnable projection matrices, $\mathbf{M}_i$ is the casual mask for the i-th layer. $\mathbf{A}_{i,h}$ refers to the attention weight of the the h-th head in the i-th deocder layer. For clarity, we will not differentiate between D_k, D_v and D, and just use D in the following. Then the MSA can be represented as:

$$\text{MSA}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{Concat}(\text{head}_1, \text{head}_2, ..., \text{head}_{i,h})\mathbf{W}_i^O, \quad (2)$$

where $\mathbf{W}_i^O \in \mathbb{R}^{HD_v \times D}$ is the learnable projection matrix, Concat indicates the concatenation operation. The computational complexity for processing all tokens is $O((N + L)^2 \times D)$.

Previous Pre-LLM approaches (Liu et al., 2024b) generally reduce the vision tokens before the LLM (Fig. 1 (a)) leading to several drawbacks as shown in Fig. 2. Differently, our ACT-IN-LLM use the adaptive token compression (ACM) to reduce vision tokens of the key and value within the MSA layer of the LLM, shown as follows:

$$\text{head}_{i,h} = \text{Attention}(\mathbf{Q}_{i,h}, \overline{\mathbf{K}}_{i,h}, \{\overline{\mathbf{V}}_{i,h}), \quad \{\overline{\mathbf{K}}_{i,h}, \overline{\mathbf{V}}_{i,h}\} = \text{ACM}(\{\mathbf{K}_{i,h}, \mathbf{V}_{i,h}\}, \mathbf{A}_{i-1}), \quad (3)$$

where $\mathbf{A}_{i-1}$ is the averaged attention weight from the $i-1$-th layer, $\{\overline{\mathbf{K}}_{i,h}, \overline{\mathbf{V}}_{i,h}\} \in \mathbb{R}^{(M+L) \times D}$, where M is the number of compressed vision tokens, satisfying $M << N$. In this way, we can reduce the computational complexity of MSA from $O((N + L)^2 \times D)$ of the full tokens to $O((N + L) \times (M + L) \times D)$.

3.2 ADAPTIVE COMPRESSION MODULE

As shown in Fig. 2, reducing tokens before the LLM has significant drawbacks, including the absence of text-guided compression, challenges in selecting which tokens to reduce, and the risk of losing important information. To address these issues, our Adaptive Compression Mechanism (ACM) focuses on two key objectives: **(i)** preserving critical vision tokens to prevent information loss, and **(ii)** dynamically compressing tokens based on layer-wise vision-text relations. To achieve the first objective, we retain all query tokens $\mathbf{Q}_i$ across layers,

Figure 4: **(a) Adaptive compression module (ACM)** leverages three steps to compress vision tokens of the key and value at the i-th layer. **(b) Sampled Casual Mask** for the self-attention layer after ACM.

ensuring an inherent error correction mechanism that mitigates the permanent loss of valuable information. For the second objective, our ACM consists of three steps as shown in Fig. 4 (a).

Text-guided information extraction. We utilize attention weights from the previous layer to guide vision token compression, since higher attention weights typically indicate greater importance in the final output (Vaswani, 2017). To leverage the textual information to guide the compression, we focus on the last row of the attention weight, $\mathbf{A}_{i-1}[N+L,:]$, which captures the significance of all previous tokens in relation to the last token. We extract the relevant elements for high-resolution and low-resolution visual tokens as follows:

$$\mathbf{a}_{i-1}^{\text{hr}} = \mathbf{A}_{i-1}[N+L, 0:N^{\text{hr}}], \quad \mathbf{a}_{i-1}^{\text{lr}} = \mathbf{A}_{i-1}[N+L, N^{\text{hr}}:N^{\text{lr}}], \tag{4}$$

where N^{hr} and N^{lr} denote the counts of high-resolution and low-resolution tokens, satisfying $N^{\text{hr}} + N^{\text{lr}} = N$.

Top Selection. To retain critical vision tokens, we select the top $N^{\text{hr}}/r_i^{\text{hr}}$ and $N^{\text{lr}}/r_i^{\text{lr}}$ values from $\mathbf{a}_{i-1}^{\text{hr}}$ and $\mathbf{a}_{i-1}^{\text{lr}}$, respectively:

$$\mathbf{s}^{\text{hr}} = \text{Top}(\mathbf{a}_{i-1}^{\text{hr}}, r_i^{\text{hr}}), \quad \mathbf{s}^{\text{lr}} = \text{Top}(\mathbf{a}_{i-1}^{\text{lr}}, r_i^{\text{lr}}), \tag{5}$$

where $\mathbf{s}^{\text{hr}} = \{s_1, s_2, ..., s_{N^{\text{hr}}/r_i^{\text{hr}}}\}$ represents the indices of the top $N^{\text{hr}}/r_i^{\text{hr}}$ values.

Vision token Compression. After obtaining the indices, we sampling the $\mathbf{K}_i/\mathbf{V}_i$ and the casual mask $\mathbf{M}_i$ based on $\mathbf{s} = [\mathbf{s}^{\text{hr}}, \mathbf{s}^{\text{lr}}]$, which can be formulated as:

$$\overline{\mathbf{K}}_i = \mathbf{K}_i[\mathbf{s},:], \quad \overline{\mathbf{V}}_i = \mathbf{V}_i[\mathbf{s},:], \quad \overline{\mathbf{M}}_i = \mathbf{M}_i[:,\mathbf{s}], \tag{6}$$

where $\overline{\mathbf{K}}_i/\overline{\mathbf{V}}_i \in \mathbb{R}^{(M+L) \times D}$, $\overline{\mathbf{M}}_i \in \mathbb{R}^{(N+L) \times (M+L)}$ is the sampled casual mask (see the example in Fig. 4 (b)), $M = N^{\text{hr}}/r_i^{\text{hr}} + N^{\text{lr}}/r_i^{\text{lr}}$. Finally, the original self-attention in Eq. 1 can be performed as $\text{Attention}(\mathbf{Q}_{i,h}, \overline{\mathbf{K}}_{i,h}, \overline{\mathbf{V}}_{i,h}, \overline{\mathbf{M}}_i)$.

3.3 Architecture Configurations

We incorporate the ACM into the decoder layers of the LLM at three stages in a hierarchical way, *i.e.*, $r_i < r_j < r_p$, where r_i, r_j and r_p are the sampling ratios in the early, middle and latter layers, based on the observation that the attention weights in the early layers are much dense than the latter ones (see Fig. 2 (b)). Note that for efficiency, we keep the vision tokens index to be identical in each stage. The analysis of different configurations for $r_i/r_j/r_p$ is provided in Table 4a. We uniformly select the $\sim 70\%$ layers among the early, middle and latter layers within LLM decoder layers to apply ACM, for the best performance and efficiency trade-off; see Table 4c and Table 5.

4 Formulation and Analysis of Vision Token Compression

In this section, we will theoretically show the superiority of our proposed ACM. To this end, we first give a unified formulation of different vision token compression methods in the self-attention mechanism in Section 4.1. Then, we show that ACM is one low-rank approximation of the original self-attention with full tokens under the specific assumption in MLLMs in Section 4.2. Finally, we prove that our ACM provides a better low-rank approximation of the full self-attention mechanism compared to existing vision token compression techniques in Section 4.3.

4.1 Unified Formulation

For clarity, we omit the layer index i and head index h of Eq. 1 in this section. Formally, the hidden states can be denoted as $\mathbf{H} \in \mathbb{R}^{(N+L) \times D}$, where N and L are the number of the vision tokens (including high-resolution and low-resolution) and the text tokens; see detailed formulation in Section 3.1. Note we omit the system prompt for clarity in our paper. Then, we present a unified and simplified formulation of these different approaches, *i.e.*, presenting the vision compression process as a compression matrix:

$$\mathbf{C} \cdot \mathbf{H} = \mathbf{C} \cdot [\mathbf{V}; \ \mathbf{T}], \ \mathbf{C} \in \mathbb{R}^{(M+L) \times (N+L)}, \tag{7}$$

where $\cdot$ is the matrix multiplication, M is the number of the vision tokens after compression, $\mathbf{C}$ is the compression matrix, which is defined as:

$$\mathbf{C} = \begin{pmatrix} \mathbf{C}^{\text{vis}} & \mathbf{O}^1 \\ \mathbf{O}^2 & \mathbf{I} \end{pmatrix}, \tag{8}$$

(a)

(b)

Figure 5: **(a) Low-rank degree.** The x-axis represents the layer index in the LLM and the y-axis is the corresponding LDR (defined in Eq. 15). The high low-rank degree of vision tokens exists in both Vicuna-7b (left) and Qwen2-0.5B (right), and high-resolution tokens show more low-rank than low-resolution ones. **(b) Average attention score.** The x-axis represents the layer index in the LLM and the y-axis is the average attention score. Vision tokens receive small attention on average and high-resolution tokens present less attention than low-resolution ones.

where $\mathbf{C}^{\text{vis}} \in \mathbb{R}^{M \times N}$ is the compression operation for vision tokens, $\mathbf{I} \in \mathbb{R}^{N \times N}$ is the identity matrix, $\mathbf{O}^1 \in \mathbb{R}^{M \times L}$ and $\mathbf{O}^2 \in \mathbb{R}^{L \times N}$ are zero matrices.

Then, the vision token compression in self-attention can be represented as:

$$\text{Com}(\mathbf{C}^Q, \mathbf{C}^K, \mathbf{C}^V) = \text{softmax}\left(\frac{(\mathbf{C}^Q \mathbf{Q})(\mathbf{C}^K \mathbf{K})^\top}{\sqrt{D}}\right) \cdot \mathbf{C}^V \mathbf{V} = \text{softmax}\left(\mathbf{C}^Q \mathbf{A}(\mathbf{C}^K)^\top\right) \cdot \mathbf{C}^V \mathbf{V},$$
(9)

where $\mathbf{C}^Q$, $\mathbf{C}^K$ and $\mathbf{C}^V$ are the compression matrices with the form of Eq. 8 for the query, key and value respectively.

For simplicity, we omit the causal attention mask $\mathbf{M}$ as it does not affect the following analysis. A complete formulation can be found in Eq. 14 of the Appendix.

Using this formulation, *i.e.*, Eq. 9, our ACM can be expressed as $\text{Com}(\mathbf{I}, \mathbf{C}_i^K, \mathbf{C}_i^V)$, where i indicates that performing compression in the i-th decoder layer of the LLMs. Similarly, the Pre-LLM compression methods can be represented as $\text{Com}(\mathbf{C}_i^Q, \mathbf{C}_i^K, \mathbf{C}_i^V)$.

4.2 LOW-RANK APPROXIMATION

In this section, we would prove that ACM is the low-rank approximation of the self-attention with full tokens based on the formulation of Eq. 9. Note that all proofs of the theorems in this section can be referred to the Appendix.

We first demonstrate that the attention weight of vision tokens, *i.e.*, $\mathbf{A}^{\text{vis}}$, is low-rank:

Theorem 1. *For matrix $\mathbf{A}$, and any column vector $\mathbf{v}$ of matrix $\mathbf{V}$, there there exists a matrix $\tilde{\mathbf{A}}$, such that:*

$$\Pr\left(\left\|\tilde{\mathbf{A}}\mathbf{v} - \mathbf{A}\mathbf{v}\right\| \le \epsilon \left\|\mathbf{A}\mathbf{v}\right\|\right) > 1 - o(1) \text{ and } \text{rank}(\tilde{\mathbf{A}}) = \Theta(\log(N)),$$
(10)

where the sub-matrix $\tilde{\mathbf{A}}_{\text{vis}}$ of $\tilde{\mathbf{A}}$ is low-rank.

We also conduct experiments to demonstrate that $\mathbf{A}^{\text{vis}}$ show a higher degree of low-rankness than text tokens in Fig. 5 (a). For more details of this experiment and proof of Eq. 19, refer to the Appendix.

Assumption 1. *In the attention weight of MLLMs, vision tokens receive much less attention than text tokens.*

To validate this assumption, we compare the average attention scores of vision and text tokens (Fig. 5 (b)), which shows that text tokens receive significantly more attention ($\sim 13x$) than vision tokens.

Based on the above theorem and assumption, we show that ACM, *i.e.*, $\text{Com}(\mathbf{I}, \mathbf{C}^K, \mathbf{C}^V)$, can approximate the $\mathbf{A}\mathbf{v}$:

Theorem 2. *For the attention weight* $\mathbf{A}$ *and the value* $\mathbf{V}$, *there there exists matrices* $\mathbf{C}^K$ *and* $\mathbf{C}^V$ *in the formulation of Eq.* 8, *such that:*

$$\Pr\left(\left\|\text{softmax}\left(\mathbf{A}(\mathbf{C}^K)^\top\right)\mathbf{C}^V\mathbf{V} - \text{softmax}(\mathbf{A})\mathbf{V}\right\| \le \epsilon\left\|\text{softmax}(\mathbf{A})\mathbf{V}\right\|\right) > 1 - 2e^{-\left(\epsilon^2 - \epsilon^3\right)M/4}. \quad (11)$$

4.3 Comparison of different vision token strategies

In this section, we show that our vision token compression strategy *i.e.*, $\text{Com}(\mathbf{I}, \mathbf{C}^K, \mathbf{C}^V)$ is a better approximation of full-token self-attention $\text{Com}(\mathbf{I}, \mathbf{I}, \mathbf{I})$ than existing strategies, such as Pre-LLM or Early-LLM compression (Li et al., 2024a) $\text{Com}(\mathbf{C}^Q, \mathbf{C}^K, \mathbf{C}^V)$ and FlexAttention (Li et al., 2024b) $\text{Com}(\mathbf{C}^Q, \mathbf{I}, \mathbf{I})$:

Method	Formulation	Complexity per Layer
Full Token	$\text{Com}(\mathbf{I}, \mathbf{I}, \mathbf{I})$	O((N+L)²D)
Pre-LLM/Early-LLM	$\text{Com}(\mathbf{C}_i^Q, \mathbf{C}_i^K, \mathbf{C}_i^V)$	O((M+L)²D)
FlexAttention	$\text{Com}(\mathbf{C}^Q, \mathbf{I}, \mathbf{I})$	O((M+L)(N+L)D)
Ours	$\text{Com}(\mathbf{I}, \mathbf{C}_i^K, \mathbf{C}_i^V)$	O((N+L)(M+L)D)

Table 1: **Comparison of formulation and computation complexity of self-attention operation.** N, M, L are the number of the original vision tokens, vision tokens after compression and text tokens, respectively. See formulation definition in Eq. 9.

Theorem 3. *For any row vector* $\mathbf{a}$ *of* $\mathbf{A}$ *and any column vector* $\mathbf{v}$ *of matrix* $\mathbf{V}$, *any matrices* $\mathbf{C}^Q$, $\mathbf{C}^K$ *and* $\mathbf{C}^V$ *in the formulation of Eq.* 8, *if **Theorem 2** holds, then we have:*

$$\Pr(\|\underbrace{\text{Com}(\mathbf{I}, \mathbf{C}^K, \mathbf{C}^V)}_{\text{ACM}} - \underbrace{\text{Com}(\mathbf{I}, \mathbf{I}, \mathbf{I})}_{\text{Full}}\| < \|\underbrace{\text{Com}(\mathbf{C}^Q, \mathbf{C}^K, \mathbf{C}^V)}_{\text{Pre-LLM/Early-LLM}} - \underbrace{\text{Com}(\mathbf{I}, \mathbf{I}, \mathbf{I})}_{\text{Full}}\|) > 1 - o(1) \quad (12)$$

$$\Pr(\|\underbrace{\text{Com}(\mathbf{I}, \mathbf{C}^K, \mathbf{C}^V)}_{\text{ACM}} - \underbrace{\text{Com}(\mathbf{I}, \mathbf{I}, \mathbf{I})}_{\text{Full}}\| < \|\underbrace{\text{Com}(\mathbf{C}^Q, \mathbf{I}, \mathbf{I})}_{\text{FlexAttention}} - \underbrace{\text{Com}(\mathbf{I}, \mathbf{I}, \mathbf{I})}_{\text{Full}}\|) > 1 - o(1) \quad (13)$$

The detailed formulation and complexity comparison with different methods is shown in Table 1.

5 Experiments

In this section, we conduct extensive experiments to prove the effectiveness of our proposed ACT-IN-LLM. Specifically, we compare our methods with existing vision token approaches under the same setting in Section 5.1. Then, we show that ACT-IN-LLM can be a plug-and-play method to be applied to different LLMs with different scales in Section 5.2. After that, we demonstrate that our scaling-up ACT-IN-LLM can achieve competitive performance compared with the SOTA MLLMs in section 5.3. Finally, the ablation study of our proposed modules are presented in Section 5.4 for further in-depth analysis.

5.1 Comparison with Different Compression methods

Experiment setting. To ensure a fair comparison with existing vision token compression methods, we maintain all other settings (*e.g.*, epochs, training dataset, learning rate, cropping strategies, number of slices from high-resolution images, etc.) constant, varying only the method of vision token compression to compare their respective performances. Specifically, we utilize CLIP-ViT-L/14-224px as the vision encoder and Vicuna-7B-v1.5 as the LLM. We adopt a two-stage training approach comprising a pre-training stage and an instruction supervised (SFT) fine-tuning stage, following the training parameters outlined in (Liu et al., 2023a). The number of slices is set to four, consistent with LLaVA-1.5-HD (Liu et al., 2023a). All methods ultimately compress visual tokens of high-resolution slices to ~ 256 for fairness.

Figure 6: **Trade-off of different methods.** 'OOM' indicates the out-of-the-memory.

Training dataset. For pre-training, we follow (Liu et al., 2023b) and use a $558K$ subset of the LAION-CC-SBU dataset with BLIP captions (Li et al., 2023c). For supervised fine-tuning, in addition to the original $665K$ data from LLaVA, we gather additional public datasets from high-resolution benchmarks, including ChartQA (Masry et al., 2022), DocVQA (Mathew et al., 2021), and InfoVQA (Mathew et al., 2022), yielding a total of $774K$ data.

Model	Efficiency		General			High-Resolution				
	Times(ms)	Memory(GB)	SEED	POPE	MME	VQA-text	ChartQA	DocVQA	InfoVQA	Average
Full	621(**100.0%**)	19.9(**100.0%**)	64.2	85.3	1466.7	60.5	49.0	46.5	35.0	48.0
Q-former	507(81.6%)	18.6(93.0%)	61.4	84.2	1432.5	53.6	21.8	21.6	25.4	30.6
Avg-pooling	461(74.3%)	18.1(90.7%)	61.5	85.2	1402.7	56.5	37.8	34.9	27.4	39.1
FlexAttn	505(81.3%)	18.6(93.4%)	60.0	87.3	1442.9	53.6	27.3	24.3	24.6	32.5
LLaVA-UHD	470(75.7%)	18.3(91.9%)	60.5	85.8	1407.5	54.2	33.2	29.9	26.9	36.0
C-Abstractor	492(79.2%)	18.2(91.6%)	62.1	86.6	1448.1	56.7	36.4	31.3	26.2	37.6
FastV	499(80.3%)	18.3(94.0%)	61.9	86.7	1412.9	58.1	35.0	38.6	27.7	39.9 ⌐
Ours	515(83.0%)	18.8(94.0%)	**63.5**	**87.6**	**1480.3**	**58.5**	**46.1**	**45.2**	**31.6**	**45.4** +5.5
FastV w/o train	499(80.3%)	18.3(94.0%)	61.5	85.8	1412.9	57.8	33.5	37.3	26.2	38.7
Ours w/o train	515(83.0%)	18.8(94.0%)	63.2	87.1	1443.2	58.3	43.2	42.8	29.8	43.5

Table 2: **Comparison with SOTA vision token compression methods.** The ratios of time and memory cost for different methods relative to the full method are highlighted in **(green)**. All models are trained in the same setting. Gray means the model without vision token compression. 'w/o train' means the direct using our method without training. **Bold** means the best value and Underline mean the second-best value. The number in blue indicates the difference to the prior state of the art.

Evaluation dataset. We evaluate different methods on both high-resolution benchmarks including VQA-text(Singh et al., 2019), ChartQA val set (Masry et al., 2022), DocVQA val set (Mathew et al., 2021), InfoVQA val set (Mathew et al., 2022), and general multimodal benchmarks including SEED (Li et al., 2023b), POPE (Li et al., 2023d), MME (Fu et al., 2023).

Results. We compare our method with state-of-the-art pre-LLM approaches (e.g., Q-former (Li et al., 2023c), Avg-pooling (Li et al., 2024a), LLaVA-UHD (Xu et al., 2024), and C-Abstractor (Cha et al., 2024)) and interaction approaches (e.g., FlexAttention (Li et al., 2024b)), as well as FastV (Chen et al., 2024a). From Table 2, our method demonstrates a superior trade-off compared to existing approaches, *e.g.*, achieving 82.96% of the single-forward time of the full tokens while attaining 45.35% average performance on high-resolution benchmarks, outperforms 5.5% over the previous SOTA. Without training, our method can also outperform other vision token compression approaches even if they are trained.

Furthermore, we analyze the trade-offs of various vision token compression approaches by reporting average performance on high-resolution benchmarks alongside the single-example forward pass time at different input resolutions, executed on one V100 GPU. As shown in Fig. 6, our method demonstrates a superior trade-off, particularly as image resolution increases, indicating its effectiveness in balancing performance and efficiency, around 65% times compared with the full model while achieving the competitive performance.

5.2 SCALING UP ACT-IN-LLM

Experiment setting. This section investigates whether our ACT-IN-LLM performance improves with increasing model size and SFT dataset size. We employ the pretrained InternViT-300M (Chen et al., 2024b) as our vision encoder, evaluating various scale LLMs (Qwen2-0.5B (Yang et al., 2024), Phi3-3B (Abdin et al., 2024), and IntermLM2-7B (Cai et al., 2024)) alongside SFT data sizes of $0.5M$, $0.7M$, and $1.2M$. Average performance on high-resolution benchmarks is reported in Fig. 7.

Impact of LLM Scale. As illustrated in Fig.7, our ACT-IN-LLM shows consistent improvement with increasing model size across different SFT data scales. For example, with $0.7M$ SFT data, ACT-IN-LLM(0.5B) achieves an average

Figure 7: **Effect of different model and data sizes.**

score of 54.58%, while ACT-IN-LLM(3B) reaches 67.00%, resulting in a 6.23% gain when scaling from 3B to 7B.

Impact of SFT Data Size. Fig.7 also indicates that training with larger SFT datasets enhances ACT-IN-LLM performance across various LLM sizes. Specifically, increasing from $0.5M$ to $0.7M$ yields approximately 2% improvement, while moving to $1.2M$ data further boosts performance by around 6% relative to $0.7M$ data.

Model	Max Tokens^V	Data size	General				High-Resolution				
			SEED	GAQ	POPE	MME	VQA-text	ChartQA^{test}	DocVQA^{test}	InfoVQA^{test}	AVG
Without Vision Token Compression											
LLaVA-Next	2880	760K	72.7	**65.2**	-	1519	64.9	69.5	72.6	-	-
Mini-Gemini-HD	2880	1.5M	**73.2**	64.5*	86.0*	1546	**68.4**	53.5*	56.1*	39.5*	53.4*
LLaVA-Onevision	7290	4.8M	-	-	-	1580	-	80.0	90.2	70.7	-
InternVL2	3072	>5M	70.7	63.2	**86.9**	**1648**	**77.4**	**83.3**	**91.6**	**74.8**	**81.8**
With Vision Token Compression or $\leq$ 1k tokens											
LLaVA-FlexAttn	~576	665K	62.8*	62.2	85.9	1479	48.9	-	-	-	-
UReader	~841	-	-	-	-	-	57.6	59.3	65.4	42.2	56.1
TextMonkey	768	409K	-	-	-	-	65.9	65.5	71.5	28.2	57.8
DOCOWL2	324	6.4M	-	-	-	-	66.7	70.0	80.7	46.4	65.9
Cambrian-1	576	10M	-	-	-	-	**71.7**	73.3	77.8	-	-
ACT-IN-LLM (Ours)	~1K	1.2M	**71.3**	**64.4**	**86.1**	**1523**	71.4	**77.3**	**81.0**	**55.9**	**71.4**

Table 3: **Comparison with the stat-of-the-art MLLMs.** 'Tokens^V' means the vision token numbers. The LLM size of all models is around 7B. Within each group, the best and the second-best values are marked in **Bold** and Underline. * means the results reproduced by ours using official checkpoints.

In summary, as both model size and SFT data increase, our method consistently achieves significant gains, indicating its potential applicability for training larger-scale models and datasets.

5.3 STATE-OF-THE-ART COMPARISON

Our ACT-IN-LLM utilizes the 7B LLM trained on $1.2M$ SFT data, achieving the best performance as detailed in Section 5.2. We compare our model against state-of-the-art (SOTA) MLLMs, including: (i) MLLMs without vision token compression: LLaVA-NeXT (Liu et al., 2024b), Mini-Gemini-HD (Li et al., 2024c), LLaVA-Onevision (Li et al., 2024a), and InternVL2 (Chen et al., 2024b) and (ii) MLLMs with vision token compression or the vision tokens $\leq$ 1K: LLaVA-FlexAttn (Li et al., 2024b), UReader (Ye et al., 2023), Cambrian-1 (Tong et al., 2024), TextMonkey (Liu et al., 2024c) and DOCOWL2 (Hu et al., 2024).

Table 3 summarizes the performance of different methods alongside the maximum number of vision tokens and STF data sizes. From the table, we can observe that our ACT-IN-LLM obtains the SOTA performance on both general and high-resolution benchmarks among the MLLMs in the second group. Even compared with the MLLMs in the first group those using exceed 3K tokens, our ACT-IN-LLM achieves 87.2% of InternVL2's performance on high-resolution benchmarks while utilizing only 32.8% of the vision tokens and less than 24% of the SFT data, highlighting its efficiency.

5.4 ABLATION STUDY

In this section, we evaluate the effectiveness of the Adaptive Compression Module (ACM), a pivotal component of ACT-IN-LLM. Using the baseline configuration outlined in Section 5.1, our ablation study addresses three critical aspects: *(i) compression ratios—quantifying vision token reduction, (ii) compression implementation methods—strategies for token compression, and (iii) compression layers—optimal layers for token reduction.*

Compression Ratios. Compression ratios dictate the number of vision tokens reduced, specifically characterized by r_i^{hr} and r_i^{lr}, which represent the reduction ratios for high-resolution and low-resolution tokens at layer i. We categorize the LLM layers into three types: the early layers with compression ratio of r_i^{hr}/r_i^{hr}, the middle with compression ratio of r_j^{hr}/r_j^{hr} and the latter layers with compression ratio of r_k^{hr}/r_k^{hr}. To explore the best configuration of the compression ratios, our ablation study consists of two steps. First, we maintain equal compression ratios for he high-resolution and low-resolution vision tokens ($r^{hr} = r^{lr}$) and change r across different layer groups, *i.e.*, plain type ($r_i = r_j = r_p$) and hierarchical type ($r_i \neq r_j \neq r_p$). Results (rows (a) to (e) in Table 4a) indicate that a hierarchical approach ($r_i < r_j < r_p$) outperforms the plain type, aligning with the observed trend of sparser attention in deeper layers (Fig.2(b)). Subsequently, we investigate distinct ratios for high- and low-resolution tokens within each layer. The results from row (f) to row (i) in Table 4a demonstrate that $r^{hr} > r^{lr}$ performs better than $r^{hr} \leq r^{lr}$, likely due to the higher low-rank nature of high-resolution tokens (Fig. 5).

Compression Ways. In Section 3.2, we use the attention weight $\mathbf{A}_{i-1}$ from the $i-1$-th layer to guide the vision token compression in the i-th layer. We compare the attention weight with three

$\{r_l^{hr}/r_l^{lr}\}_{l=i,j,p}$	*time*	*general*	*hr*
plain: $r_i = r_j = r_p$ *identical*: $r^{hr} = r^{lr}$			
(a) $\{2/2, 2/2, 2/2\}$	563	74.25	**45.89**
(b) $\{4/4, 4/4, 4/4\}$	516	74.01	44.18
(c) $\{8/8, 8/8, 8/8\}$	**506**	74.12	43.25
hierarchical: $r_i \neq r_j \neq r_p$ *identical*: $r^{hr} = r^{lr}$			
(d) $\{2/2, 4/4, 8/8\}$	513	74.86	44.95
(e) $\{8/8, 4/4, 2/2\}$	513	74.42	43.35
hierarchical: $r_i \neq r_j \neq r_p$ *distinct*: $r^{hr} \neq r^{lr}$			
(f) $\{2/1, 4/1, 8/1\}$	531	75.02	45.11
(g) $\{2/2, 4/2, 8/2\}$	515	74.98	45.12
(h) $\{2/1, 4/2, 8/4\}$	515	**75.04**	45.35
(i) $\{2/4, 4/4, 8/4\}$	513	74.23	44.51

(a) **Compression ratios** r. The detailed definition of $\{r_i^{hr}/r_i^{lr}, r_j^{hr}/r_j^{lr}, r_p^{hr}/r_p^{lr}\}$ is presented in Section 3.2.

way	*general*	*hr*
Attention-weight	75.04	**45.35**
AvgPool-1D	**75.06**	45.08
AvgPool-2D	74.12	43.56
Learnable Projection	74.07	42.21
Pre-LLM	72.28	39.15

(b) **Compression ways**. 'Pre-LLM': the best Pre-LLM approaches in Table 2.

layer postions	*general*	*hr*
early	73.51	42.33
middle	74.68	44.08
latter	7430	44.29
uniform	**75.04**	**45.35**

(c) **Compression layer positions**. There are totally 20 layers to compress tokens for fair compression.

Table 4: **ACM module ablation experiments**. **time**: single-forward pass time (ms). **general**: the average performance on general benchmarks. **hr**: the average performance on high-resolution benchmarks. Best results and default settings are reported in **Bold** and gray.

alternative compression methods, including (i) average-pooling 1D: directly apply average-pooling 1D to the vision tokens of $\mathbf{K}_i/\mathbf{V}_i$. (ii) average-pooling 2D: reshape the vision-tokens in $\mathbf{K}_i/\mathbf{V}_i$ to be 2D, and then apply average-pooling 2D to the reshaped 2D hidden states. (iii) Learnable projection: use a learnable projection to reduce the length of $\mathbf{K}_i/\mathbf{V}_i$.

Table 4b reports the average performance[1] of general and high-resolution benchmarks of different implementations. Results show that all different ways of ACM can outperform Pre-LLM approaches, confirming the effectiveness of our method. Non-parameter ways consistently yield better performance than parameterized ones (*e.g.*, learnable projection), possibly due to the learnable methods requiring additional training complexity of learning effective mappings to compress vision tokens.

Compression Layers. We compress vision tokens in a uniform way as described in Section 3.3, *i.e.*, uniformly reducing tokens in early, middle and latter layers. To ablate where to reduce vision tokens, we further compare the other three types of compression layers: (i) the first 70% layers, (ii) the middle 70% layers and (iii) the last 70% layers. From Table 4c, we can find that selecting 70% layers uniformly across all layers of the LLM to apply ACM achieves the best performance. We also experiment with different proportions of ACM layers

num	times	general	high-resolution
50%	552	**75.25**	**46.12**
60%	538	75.02	45.68
70%	515	75.04	45.35
80%	512	74.19	44.61
90%	**502**	74.08	43.17

Table 5: **Effect of the ratio of ACM layers among all layers.** Best results and default settings are reported in **Bold** and gray.

applied across all LLM layers in Table 5, showing that using more ACM layers would improve the efficiency while degrading the performance. The detailed layer indexes of incorporating ACM can be found in the Appendix.

6 CONCLUSION

In this paper, we introduce ACT-IN-LLM, which enhances the efficiency of multimodal large language models (MLLMs) by adaptively compressing vision tokens across different LLM layers. Unlike prior methods that reduce vision tokens before LLM processing, our approach retains all tokens, providing an inherent error correction mechanism to prevent the loss of critical information. Additionally, the layer-wise compression is guided by interactions between vision and text tokens, ensuring precise token selection. Our theoretical analysis and extensive experiments demonstrate that ACT-IN-LLM outperforms existing vision token compression techniques. Moreover, we reveal the potential for scaling up ACT-IN-LLM to achieve competitive performance even with SOTA MLLMs without vision token compression.

---

[1]The MME Perception score is scaled down by 20 to align with other datasets, as (Tong et al., 2024).

REFERENCES

Marah Abdin, Sam Ade Jacobs, Ammar Ahmad Awan, Jyoti Aneja, Ahmed Awadallah, Hany Awadalla, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Harkirat Behl, et al. Phi-3 technical report: A highly capable language model locally on your phone. *arXiv preprint arXiv:2404.14219*, 2024.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Rosa I Arriaga and Santosh Vempala. An algorithmic theory of learning: Robust concepts and random projection. *Machine learning*, 63:161–182, 2006.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. Qwen-vl: A frontier large vision-language model with versatile abilities. *arXiv preprint arXiv:2308.12966*, 2023.

Rohan Bavishi, Erich Elsen, Curtis Hawthorne, Maxwell Nye, Augustus Odena, Arushi Somani, and Sağnak Taşırlar. Introducing our multimodal models, 2023. URL https://www.adept.ai/blog/fuyu-8b.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Zheng Cai, Maosong Cao, Haojiong Chen, Kai Chen, Keyu Chen, Xin Chen, Xun Chen, Zehui Chen, Zhi Chen, Pei Chu, et al. Internlm2 technical report. *arXiv preprint arXiv:2403.17297*, 2024.

Junbum Cha, Wooyoung Kang, Jonghwan Mun, and Byungseok Roh. Honeybee: Locality-enhanced projector for multimodal llm. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13817–13827, 2024.

Liang Chen, Haozhe Zhao, Tianyu Liu, Shuai Bai, Junyang Lin, Chang Zhou, and Baobao Chang. An image is worth 1/2 tokens after layer 2: Plug-and-play inference acceleration for large vision-language models. *arXiv preprint arXiv:2403.06764*, 2024a.

Lin Chen, Jisong Li, Xiaoyi Dong, Pan Zhang, Conghui He, Jiaqi Wang, Feng Zhao, and Dahua Lin. Sharegpt4v: Improving large multi-modal models with better captions. *arXiv preprint arXiv:2311.12793*, 2023.

Wenhu Chen, Hongmin Wang, Jianshu Chen, Yunkai Zhang, Hong Wang, Shiyang Li, Xiyou Zhou, and William Yang Wang. Tabfact: A large-scale dataset for table-based fact verification. *arXiv preprint arXiv:1909.02164*, 2019.

Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, et al. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 24185–24198, 2024b.

Zesen Cheng, Sicong Leng, Hang Zhang, Yifei Xin, Xin Li, Guanzheng Chen, Yongxin Zhu, Wenqi Zhang, Ziyang Luo, Deli Zhao, et al. Videollama 2: Advancing spatial-temporal modeling and audio understanding in video-llms. *arXiv preprint arXiv:2406.07476*, 2024.

Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*, 2019.

Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, et al. Rethinking attention with performers. *arXiv preprint arXiv:2009.14794*, 2020.

Xinpeng Ding, Jianhua Han, Hang Xu, Wei Zhang, and Xiaomeng Li. Hilm-d: Towards high-resolution understanding in multimodal large language models for autonomous driving. *arXiv preprint arXiv:2309.05186*, 2023.

Xinpeng Ding, Jinahua Han, Hang Xu, Xiaodan Liang, Wei Zhang, and Xiaomeng Li. Holistic autonomous driving understanding by bird's-eye-view injected multi-modal large models. *arXiv preprint arXiv:2401.00988*, 2024.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Jinrui Yang, Xiawu Zheng, Ke Li, Xing Sun, et al. Mme: A comprehensive evaluation benchmark for multimodal large language models. *arXiv preprint arXiv:2306.13394*, 2023.

Wenyi Hong, Weihan Wang, Qingsong Lv, Jiazheng Xu, Wenmeng Yu, Junhui Ji, Yan Wang, Zihan Wang, Yuxiao Dong, Ming Ding, et al. Cogagent: A visual language model for gui agents. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 14281–14290, 2024.

Anwen Hu, Haiyang Xu, Liang Zhang, Jiabo Ye, Ming Yan, Ji Zhang, Qin Jin, Fei Huang, and Jingren Zhou. mplug-docowl2: High-resolution compressing for ocr-free multi-page document understanding. *arXiv preprint arXiv:2409.03420*, 2024.

Runhui Huang, Xinpeng Ding, Chunwei Wang, Jianhua Han, Yulong Liu, Hengshuang Zhao, Hang Xu, Lu Hou, Wei Zhang, and Xiaodan Liang. Hires-llava: Restoring fragmentation input in high-resolution large vision-language models. *arXiv preprint arXiv:2407.08706*, 2024.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Kushal Kafle, Scott Cohen, Brian Price, and Christopher Kanan. Dvqa: Understanding data visualizations via question answering. In *CVPR*, 2018.

Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images, 2016.

Geewook Kim, Teakgyu Hong, Moonbin Yim, JeongYeon Nam, Jinyoung Park, Jinyeong Yim, Wonseok Hwang, Sangdoo Yun, Dongyoon Han, and Seunghyun Park. Ocr-free document understanding transformer. In *European Conference on Computer Vision*, pp. 498–517. Springer, 2022.

Nikita Kitaev, Łukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer. *arXiv preprint arXiv:2001.04451*, 2020.

Bo Li, Peiyuan Zhang, Jingkang Yang, Yuanhan Zhang, Fanyi Pu, and Ziwei Liu. Otterhd: A high-resolution multi-modality model. *arXiv preprint arXiv:2311.04219*, 2023a.

Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Yanwei Li, Ziwei Liu, and Chunyuan Li. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*, 2024a.

Bohao Li, Rui Wang, Guangzhi Wang, Yuying Ge, Yixiao Ge, and Ying Shan. Seed-bench: Benchmarking multimodal llms with generative comprehension. *arXiv preprint arXiv:2307.16125*, 2023b.

Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv preprint arXiv:2301.12597*, 2023c.

Junyan Li, Delin Chen, Tianle Cai, Peihao Chen, Yining Hong, Zhenfang Chen, Yikang Shen, and Chuang Gan. Flexattention for efficient high-resolution vision-language models. *arXiv preprint arXiv:2407.20228*, 2024b.

Yanwei Li, Yuechen Zhang, Chengyao Wang, Zhisheng Zhong, Yixin Chen, Ruihang Chu, Shaoteng Liu, and Jiaya Jia. Mini-gemini: Mining the potential of multi-modality vision language models. *arXiv preprint arXiv:2403.18814*, 2024c.

Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. *arXiv preprint arXiv:2305.10355*, 2023d.

Zhang Li, Biao Yang, Qiang Liu, Zhiyin Ma, Shuo Zhang, Jingxu Yang, Yabo Sun, Yuliang Liu, and Xiang Bai. Monkey: Image resolution and text label are important things for large multi-modal models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 26763–26773, 2024d.

W Johnson J Lindenstrauss and J Johnson. Extensions of lipschitz maps into a hilbert space. *Contemp. Math*, 26(189-206):2, 1984.

Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. *arXiv preprint arXiv:2310.03744*, 2023a.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *arXiv preprint arXiv:2304.08485*, 2023b.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, 2024a.

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, January 2024b. URL https://llava-vl.github.io/blog/2024-01-30-llava-next/.

Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an all-around player? *arXiv preprint arXiv:2307.06281*, 2023c.

Yuliang Liu, Biao Yang, Qiang Liu, Zhang Li, Zhiyin Ma, Shuo Zhang, and Xiang Bai. Textmonkey: An ocr-free large multimodal model for understanding document. *arXiv preprint arXiv:2403.04473*, 2024c.

Pan Lu, Swaroop Mishra, Tony Xia, Liang Qiu, Kai-Wei Chang, Song-Chun Zhu, Oyvind Tafjord, Peter Clark, and Ashwin Kalyan. Learn to explain: Multimodal reasoning via thought chains for science question answering. In *The 36th Conference on Neural Information Processing Systems (NeurIPS)*, 2022.

Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. *arXiv preprint arXiv:2203.10244*, 2022.

Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *Proceedings of the IEEE/CVF winter conference on applications of computer vision*, pp. 2200–2209, 2021.

Minesh Mathew, Viraj Bagal, Rubèn Tito, Dimosthenis Karatzas, Ernest Valveny, and CV Jawahar. Infographicvqa. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1697–1706, 2022.

Nitesh Methani, Pritha Ganguly, Mitesh M. Khapra, and Pratyush Kumar. Plotqa: Reasoning over scientific plots. In *The IEEE Winter Conference on Applications of Computer Vision (WACV)*, March 2020.

Anand Mishra, Shashank Shekhar, Ajeet Kumar Singh, and Anirban Chakraborty. Ocr-vqa: Visual question answering by reading text in images. In *ICDAR*, 2019.

OpenAI OpenAI. Gpt-4 technical report. Mar 2023.

Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pp. 8748–8763. PMLR, 2021.

Yuzhang Shang, Mu Cai, Bingxin Xu, Yong Jae Lee, and Yan Yan. Llava-prumerge: Adaptive token reduction for efficient large multimodal models. *arXiv preprint arXiv:2403.15388*, 2024.

Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 8317–8326, 2019.

Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

Shengbang Tong, Ellis Brown, Penghao Wu, Sanghyun Woo, Manoj Middepogu, Sai Charitha Akula, Jihan Yang, Shusheng Yang, Adithya Iyer, Xichen Pan, et al. Cambrian-1: A fully open, vision-centric exploration of multimodal llms. *arXiv preprint arXiv:2406.16860*, 2024.

A Vaswani. Attention is all you need. *Advances in Neural Information Processing Systems*, 2017.

Sinong Wang, Belinda Z Li, Madian Khabsa, Han Fang, and Hao Ma. Linformer: Self-attention with linear complexity. *arXiv preprint arXiv:2006.04768*, 2020.

Wenhai Wang, Enze Xie, Xiang Li, Deng-Ping Fan, Kaitao Song, Ding Liang, Tong Lu, Ping Luo, and Ling Shao. Pvt v2: Improved baselines with pyramid vision transformer. *Computational Visual Media*, 8(3):415–424, 2022.

Ruyi Xu, Yuan Yao, Zonghao Guo, Junbo Cui, Zanlin Ni, Chunjiang Ge, Tat-Seng Chua, Zhiyuan Liu, Maosong Sun, and Gao Huang. Llava-uhd: an lmm perceiving any aspect ratio and high-resolution images. *arXiv preprint arXiv:2403.11703*, 2024.

An Yang, Baosong Yang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Zhou, Chengpeng Li, Chengyuan Li, Dayiheng Liu, Fei Huang, et al. Qwen2 technical report. *arXiv preprint arXiv:2407.10671*, 2024.

Linli Yao, Lei Li, Shuhuai Ren, Lean Wang, Yuanxin Liu, Xu Sun, and Lu Hou. Deco: Decoupling token compression from semantic abstraction in multimodal large language models. *arXiv preprint arXiv:2405.20985*, 2024.

Jiabo Ye, Anwen Hu, Haiyang Xu, Qinghao Ye, Ming Yan, Guohai Xu, Chenliang Li, Junfeng Tian, Qi Qian, Ji Zhang, et al. Ureader: Universal ocr-free visually-situated language understanding with multimodal large language model. *arXiv preprint arXiv:2310.05126*, 2023.

Manzil Zaheer, Guru Guruganesh, Kumar Avinava Dubey, Joshua Ainslie, Chris Alberti, Santiago Ontanon, Philip Pham, Anirudh Ravula, Qifan Wang, Li Yang, et al. Big bird: Transformers for longer sequences. *Advances in neural information processing systems*, 33:17283–17297, 2020.

Hang Zhang, Xin Li, Lidong Bing, and at al. Video-llama: An instruction-tuned audio-visual language model for video understanding. *arXiv preprint arXiv:2306.02858*, 2023.

Deyao Zhu, Jun Chen, Xiaoqian Shen, Xiang Li, and Mohamed Elhoseiny. Minigpt-4: Enhancing vision-language understanding with advanced large language models. *arXiv preprint arXiv:2304.10592*, 2023.

A   FORMULATION OF SELF-ATTENTION

We can transfer Eq. 1 to the following formulation:

$$\text{Self-Attn}(\mathbf{Q}, \mathbf{K}, \mathbf{V}) = \text{softmax}\left(\frac{(\mathbf{Q} \odot \mathbf{M})(\mathbf{K}^{\mathbf{T}} \odot \mathbf{M})}{\sqrt{D}}\right) \mathbf{V},\tag{14}$$

where $\odot$ indicates the element-wise multiplication. Here we omit the layer and head indexes.

B   LOW-RANK ANALYSIS

Experiment Setting. We use a mainstream high-resolution MLLM, the LLaVA-1.6-7B with 2×2 high-resolution slices (), as our baseline model. Then, we randomly sample 50 samples from three common high-resolution benchmarks, *i.e.*, ChartQA, DocVQA and InfoVQA, as input, and obtain the average attention weight $\{\mathbf{A}_i\}_{i=1}^{32}$ across different samples, where $\mathbf{A}_i$ is the attention weight of the i-th LLM layer in LLaVA-1.6-7B. For better analysis of different types of tokens, we divide the attention weight $\mathbf{A}$ into three different sub-matrices : $\mathbf{A}^{\text{hr}} \in \mathbb{R}^{N^{\text{hr}} \times N^{\text{hr}}}$, $\mathbf{A}^{\text{lr}} \in \mathbb{R}^{N^{\text{lr}} \times N^{\text{lr}}}$ and $\mathbf{A}^{\text{txt}} \in \mathbb{R}^{N^{\text{txt}} \times N^{\text{txt}}}$.

Low-Rank Degree Measurement. In high-resolution MLLMs, the disparity in the number of different types of tokens is significant., *e.g.*, $N^{\text{hr}} >> N^{\text{lr}}/N^{\text{txt}}$. We introduce LRD to better measure the low-rank degrees for matrices with different sizes. Formally, we can conduct the singular value decomposition for one attention weight matrix $\mathbf{A}$, obtain its corresponding singular values R. Then, the low-rank degree can be computed as following:

$$\text{LRD} = \text{sum}(\text{Top}(r * N^{\text{sv}}, R))/\text{sum}(R),\tag{15}$$

where $\text{Top}(a, b)$ indicates selecting the top a singular values from b, $r \in (0, 1)$ is the ratio of sampling singular values and N^{sv} is the number of singular values in R. In this way, LDR reflects the proportion of the sum of the top $r\%$ singular values to the total sum of all singular values. A larger LDR indicates a higher degree of low-rankness in the matrix, and vice versa.

C   PROOF OF THEOREM 1

Proof. We first write $\mathbf{A}$ and $\mathbf{v}$ as:

$$\mathbf{A} = \begin{pmatrix} \mathbf{A}_{\text{vis}} & \mathbf{A}_1 \\ \mathbf{A}_2 & \mathbf{A}_3 \end{pmatrix}, \quad \mathbf{v} = \begin{pmatrix} \mathbf{v}_{\text{vis}} & \mathbf{v}_1 \end{pmatrix}\tag{16}$$

Then, $\mathbf{A}\mathbf{v}$ can be represented as:

$$\begin{pmatrix} \mathbf{A}_{\text{vis}}\mathbf{v}_{\text{vis}} + \mathbf{A}_1\mathbf{v}_1 \\ \mathbf{A}_2\mathbf{v}_{\text{vis}} + \mathbf{A}_3\mathbf{v}_1 \end{pmatrix}\tag{17}$$

Similarly, $\tilde{\mathbf{A}}$ can be formulated as:

$$\begin{pmatrix} \tilde{\mathbf{A}}_{\text{vis}}\mathbf{v}_{\text{vis}} + \tilde{\mathbf{A}}_1\mathbf{v}_1 \\ \tilde{\mathbf{A}}_2\tilde{\mathbf{v}}_{\text{vis}} + \tilde{\mathbf{A}}_3\mathbf{v}_1 \end{pmatrix}\tag{18}$$

We can let $\mathbf{A}_1\mathbf{v}_1 = \tilde{\mathbf{A}}_1\mathbf{v}_1$, $\mathbf{A}_2\mathbf{v}_{\text{vis}} = \tilde{\mathbf{A}}_2\tilde{\mathbf{v}}_{\text{vis}}$ and $\mathbf{A}_3\mathbf{v}_1 = \tilde{\mathbf{A}}_3\mathbf{v}_1$, then the proof of Eq. 10 can be equal to prove that there exists a low-rank matrix $\tilde{\mathbf{A}}_{\text{vis}}$ such that:

$$\Pr\left(\left\|\tilde{\mathbf{A}}_{\text{vis}}\mathbf{v}_{\text{vis}} - \mathbf{A}\mathbf{v}\right\| \leq \epsilon \|\mathbf{A}\mathbf{v}\|\right) > 1 - o(1) \text{ and } \text{rank}(\tilde{\mathbf{A}}) = \Theta(\log(N)).\tag{19}$$

The main idea of the proof follows (Lindenstrauss & Johnson, 1984; Arriaga & Vempala, 2006; Wang et al., 2020). Based on the distributional Johnson–Lindenstrauss lemma (Arriaga & Vempala, 2006), for any $\mathbf{x} \in \mathbb{R}^{1 \times N}, \mathbf{y} \in \mathbb{R}^{N \times 1}$, we have:

$$\Pr\left(\|\mathbf{x}\mathbf{R}^{\top}\mathbf{R}\mathbf{y} - \mathbf{x}\mathbf{y}\| \leq \epsilon \|\mathbf{x}\mathbf{y}\|\right) > 1 - 2e^{-\left(\epsilon^2 - \epsilon^3\right)M/4},\tag{20}$$

where $\mathbf{R} \in \mathbb{R}^{N \times M}$. After constructing a low-rank matrix $\tilde{\mathbf{A}}_{\text{vis}} = \mathbf{A}_{\text{vis}}\mathbf{R}^\top\mathbf{R}$, for any row vector $\mathbf{a} \in \mathbf{A}_{\text{vis}}$ and any column vector $\mathbf{v} \in \mathbf{V}$, we have:

$$\Pr\left(\|\mathbf{a}\mathbf{R}^\top\mathbf{R}\mathbf{v} - \mathbf{a}\mathbf{v}\| \leq \epsilon\|\mathbf{a}\mathbf{v}\|\right) > 1 - 2e^{-(\epsilon^2 - \epsilon^3)M/4}. \tag{21}$$

Therefore, we have:

$$\begin{aligned}
\Pr\left(\left\|\tilde{\mathbf{A}}_{\text{vis}}\mathbf{v}_{\text{vis}} - \mathbf{A}\mathbf{v}\right\| \leq \epsilon\|\mathbf{A}\mathbf{v}\|\right) &= \Pr\left(\left\|\mathbf{A}_{\text{vis}}\mathbf{R}^\top\mathbf{R}\mathbf{v}_{\text{vis}} - \mathbf{A}\mathbf{v}\right\| \leq \epsilon\|\mathbf{A}\mathbf{v}\|\right) \\
&\geq 1 - \sum_{\mathbf{a} \in P} \Pr\left(\left\|\mathbf{a}\mathbf{R}^\top\mathbf{R}\mathbf{v} - \mathbf{a}\mathbf{v}\right\| > \epsilon\|\mathbf{a}\mathbf{v}\|\right) \\
&> 1 - 2Ne^{-(\epsilon^2 - \epsilon^3)M/4} = 1 - o(1)
\end{aligned} \tag{22}$$

D PROOF OF THEOREM 2

Proof. Based on the definition of $(\mathbf{C}^K)^\top/\mathbf{C}^V$ (see Eq. 8), $\text{softmax}\left(\mathbf{a}((\mathbf{C}^K)^\top)\right)\mathbf{C}^V\mathbf{v}$ can be represented as:

$$\text{softmax}\left(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top, \quad \mathbf{a}_1\right)\begin{pmatrix}\mathbf{C}_{\text{vis}}^V\mathbf{v}_{\text{vis}} \\ \mathbf{v}_1\end{pmatrix}. \tag{23}$$

Similarly, $\text{softmax}(\mathbf{a})\mathbf{v}$ can be presented as:

$$\text{softmax}\left(\mathbf{a}_{\text{vis}}, \quad \mathbf{a}_1\right)\begin{pmatrix}\mathbf{v}_{\text{vis}} \\ \mathbf{v}_1\end{pmatrix}. \tag{24}$$

Let define:

$$D_1 = \text{sum}(\exp(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top) + \exp(\mathbf{a}_1)) \tag{25}$$

$$D_2 = \text{sum}(\exp(\mathbf{a}_{\text{vis}}) + \exp(\mathbf{a}_1)) \tag{26}$$

Then, Eq. 23 and Eq. 24 can be formulated as:

$$\exp(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top)\mathbf{C}_{\text{vis}}^V\mathbf{v}_{\text{vis}}/D_1 + \exp(\mathbf{a})\mathbf{v}_1/D_1. \tag{27}$$

$$\exp(\mathbf{a}_{\text{vis}})\mathbf{v}_{\text{vis}}/D_2 + \exp(\mathbf{a})\mathbf{v}_1/D_2. \tag{28}$$

Then, we have:

$$\begin{aligned}
\left\|\text{softmax}\left(\mathbf{a}(\mathbf{C}^K)^\top\right)\mathbf{C}^V\mathbf{v} - \text{softmax}(\mathbf{a})\mathbf{v}\right\| &= \|\exp(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top)\mathbf{C}_{\text{vis}}^V\mathbf{v}_{\text{vis}}/D_1 - \exp(\mathbf{a}_{\text{vis}})\mathbf{v}_{\text{vis}}/D_2 \\
&+ \exp(\mathbf{a})\mathbf{v}_1/D_1 - \exp(\mathbf{a})\mathbf{v}_1/D_2\| \overset{(a)}{\approx} \|\exp(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top)\mathbf{C}_{\text{vis}}^V\mathbf{v}_{\text{vis}} - \exp(\mathbf{a}_{\text{vis}})\mathbf{v}_{\text{vis}}\| \\
&\overset{(b)}{\leq} \|\exp(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top)\mathbf{C}_{\text{vis}}^V\mathbf{v}_{\text{vis}} - \exp(\mathbf{a}_{\text{vis}})\mathbf{R}^\top\mathbf{R}\mathbf{v}_{\text{vis}}\| + \|\exp(\mathbf{a}_{\text{vis}})\mathbf{R}^\top\mathbf{R}\mathbf{v}_{\text{vis}} - \exp(\mathbf{a}_{\text{vis}})\mathbf{v}_{\text{vis}}\| \\
&\overset{(c)}{\leq} (1+\epsilon)\|\mathbf{v}\|\left\|\exp\left(\mathbf{a}_{\text{vis}}\mathbf{C}_{\text{vis}}^K\right) - \exp(\mathbf{a}_{\text{vis}})\mathbf{R}^\top\right\| + \|\exp(\mathbf{a}_{\text{vis}})\mathbf{R}^\top\mathbf{R}\mathbf{v}_{\text{vis}} - \exp(\mathbf{a}_{\text{vis}})\mathbf{v}_{\text{vis}}\| \\
&\overset{(d)}{\leq} \|\exp(\mathbf{a}_{\text{vis}})\mathbf{R}^\top\mathbf{R}\mathbf{v}_{\text{vis}} - \exp(\mathbf{a}_{\text{vis}})\mathbf{v}_{\text{vis}}\| + o(\|\exp(\mathbf{a}_{\text{vis}})\|\|\mathbf{v}_{\text{vis}}\|) \\
&\overset{(e)}{\leq} \epsilon\|\exp(\mathbf{a}_{\text{vis}})\|\|\mathbf{v}_{\text{vis}}\| + o(\|\exp(\mathbf{a}_{\text{vis}})\|\|\mathbf{v}_{\text{vis}}\|)
\end{aligned} \tag{29}$$

The above, step (a) is based on the **Assumption 1**, *i.e.*, $\text{sum}(\exp(\mathbf{a}_1)) \gg \text{sum}(\exp(\mathbf{a}_{\text{vis}}))$ and $\text{sum}(\exp(\mathbf{a}_1)) \gg \text{sum}(\exp(\mathbf{a}_{\text{vis}}(\mathbf{C}_{\text{vis}}^K)^\top))$. The step (b) is based on the triangle inequality, and the step (c) leverages the Cauchy inequality and a version of JL Lemma from (Arriaga & Vempala, 2006). The step (d) utilizes the fact that exponential function is Lipschitz continuous in a compact region (Wang et al., 2020). The step (e) is based on Eq. 22. Applying the results in Eq. 29 to any row vector $\mathbf{a}$ of $\mathbf{A}$ and any column vector $\mathbf{v}$ of matrix $\mathbf{V}$, we can prove the Theorem 2.

E PROOF OF THEOREM 3

Proof. The main idea of the proof is based on the **Theorem 2** and the triangle inequality. Based on the definition of Eq. 9, the Pre-LLM compression strategy can be formulated as $\text{Com}(\mathbf{C}^Q, (\mathbf{C}^K), \mathbf{C}^V) = \text{softmax}\left(\mathbf{C}^Q \mathbf{A}(\mathbf{C}^K)^\top\right) \cdot \mathbf{C}^V \mathbf{V}$ and our ACM can be presented as $\text{Com}(\mathbf{I}, (\mathbf{C}^K)^\top, \mathbf{C}^V) = \text{softmax}\left(\mathbf{A}(\mathbf{C}^K)^\top\right) \cdot \mathbf{C}^V \mathbf{V}$. In the following, we use Pre-LLM and ACM to represent the detailed formulation for clarity. Then, for any $\mathbf{C}^Q$, $\mathbf{C}^K$, and $\mathbf{C}^V$, we have:

$$\|\text{ACM} - \text{softmax}(\mathbf{A})\mathbf{V}\|$$
$$\overset{(a)}{\leq} \|\text{ACM} - \text{Pre-LLM}\| + \|\text{Pre-LLM} - \text{softmax}(\mathbf{A})\mathbf{V}\| \qquad (30)$$
$$\overset{(b)}{<} \|\text{Pre-LLM} - \text{softmax}(\mathbf{A})\mathbf{V}\|$$

The step (a) is based on the the triangle inequality and the step (b) is based on the fact that $\|\text{softmax}\left(\mathbf{C}^Q \mathbf{A}(\mathbf{C}^K)^\top\right) \cdot \mathbf{C}^V \mathbf{V} - \text{softmax}\left(\mathbf{A}(\mathbf{C}^K)^\top\right) \cdot \mathbf{C}^V \mathbf{V}\| > 0$, since generally we have $\mathbf{C}^Q \mathbf{A}(\mathbf{C}^K)^\top \neq \mathbf{A}(\mathbf{C}^K)^\top$. The proof of Eq. 13 is similar to Eq. 30.

F MORE EXPERIMENTAL DETAILS AND RESULTS

F.1 DETAILS OF EARLY COMPRESSION LIMITATION EXPERIMENTS

Here, we give more details about the experiment settings for Fig. 2. Specifically, we utilize CLIP-ViT-L/14-224px as the vision encoder and Vicuna-7B-v1.5 as the LLM. We adopt a two-stage training approach comprising a pre-training stage and an instruction supervised (SFT) fine-tuning stage, following the training parameters outlined in (Liu et al., 2023a). The number of slices is set to four, consistent with LLaVA-1.5-HD (Liu et al., 2023a). We test the trained model on four high-resolution benchmarks, *i.e.*, VQA-text(Singh et al., 2019), ChartQA val set (Masry et al., 2022), DocVQA val set (Mathew et al., 2021), InfoVQA val set (Mathew et al., 2022), and three general multimodal benchmarks including SEED (Li et al., 2023b), MMBench (Liu et al., 2023c), POPE (Li et al., 2023d). To explore the impact of dropping vision tokens at different layers within the LLM, we select a specific layer from the pre-trained model, discard 50% of the original vision tokens at that layer, and retain only these 50% in all subsequent layers. We sample a total of four layers at intervals from early to latter across all 32 layers of the LLM, specifically the 5th, 15th, 25th, and 30th layers. Additionally, we also include the 0th layer, which performs token dropping before the vision tokens are input into the LLM. We select three types of token-dropping ways to compare with the non-compression model. (i) average: dropping vision tokens based on averaged attention scores from all of 32 layers of the Vicuna-7B-v1.5; (ii) separate: dropping vision tokens based on averaged attention scores from the previous layer, and (iii) last: dropping vision tokens based on averaged attention scores from the last layer.

F.2 STF DATASETS

Table 6 shows the detailed construction of the supervised instruction tuning dataset in Section 5.2. Our SFT data consists of four types: (i) caption data sampled from ShareGPT4V (Chen et al., 2023); (ii) Science data sampled from AI2D (Kembhavi et al., 2016) and ScienceQA (Lu et al., 2022); (iii) doc-related data sampled from ChartQA (Masry et al., 2022), DVQA (Kafle et al., 2018), PlotQA (Methani et al., 2020), OCRVQA (Mishra et al., 2019), DocVQA (Mathew et al., 2021), InfoVQA (Mathew et al., 2022), synthdog-en (Kim et al., 2022) and TableFact (Chen et al., 2019); (iv) general data sampled from LLaVA (Liu et al., 2023a) and sharegpt4v (Chen et al., 2023).

F.3 LAYER INDEX OF APPLYING ACM

In Section 5.4, we demonstrate that uniformly inserting ACM into different layers of the LLM yields the best performance. Here, we investigate the specific layer indexes of the early, middle, and latter layers within the LLM. We explore two different types: (i) continuous, *i.e.*, inserting ACMs into continuous layers of the LLM layers and (ii) interval, *i.e.*, inserting ACMs into the LLM layers with an interval. Results from Table 7 demonstrate that interval incorporation performs better in both 0.5B and 3B LLMs.

Task	Dataset	# Sample
Captioning	ShareGPT4V (Chen et al., 2023)	100K
Science	AI2D (Kembhavi et al., 2016)	12K
	ScienceQA (Lu et al., 2022)	12K
Doc QA	ChartQA (Masry et al., 2022)	28K
	DVQA (Kafle et al., 2018),	100K
	PlotQA (Methani et al., 2020)	10K
	OCRVQA (Mishra et al., 2019)	80K
	DocVQA (Mathew et al., 2021)	49K
	InfoVQA (Mathew et al., 2022)	14K
	synthdog-en (Kim et al., 2022)	29K
	TableFact (Chen et al., 2019)	14K
General QA	LLaVA (Liu et al., 2023a)	150k
	sharegpt4v (Chen et al., 2023)	665K
Total	-	**1.2M**

Table 6: Summary of datasets for SFT in Section 5.2.

LLM	early	middle	latter	average
Qwen2-0.5B	{ 3, 5, 7, 9}	{ 10-17 }	{ 18, 20, 22 }	61.08
Qwen2-0.5B	{ 3, 4, 8, 9}	{ 10-17 }	{ 20, 21, 22 }	64.32
Phi-3-3B	{ 3, 4, 5, 11, 12, 13}	{ 14-23 }	{ 27, 28, 29, 30 }	65.25
Phi-3-3B	{ 3, 5, 7, 9, 11, 13}	{ 14-23 }	{ 24, 26, 28, 30 }	69.12

Table 7: Layer index of incorporating ACM. **average** means the average performance on high-resolution benchmarks. The rows in `organe` and `blue` represents applying ACM in the continuous and interval layers of LLM respectively.

F.4 CASUAL MASK

In section 3.2, *i.e.*, Fig. 4 (b), we sampling the original casual mask based on the indexes of the selected vision tokens. Here, we also compare another implementation of the casual mask for the vision tokens, *i.e.*, setting high-resolution and low-resolution vision tokens to be non-causal, as shown in Fig. 8. Results from Table 8 show that using casual masks for both vision and text tokens can achieve better performance.

F.5 TOKEN SELECTION STRATEGIES FROM ATTENTION WEIGHT

To assess token importance, we use the average attention score across all heads, as it provides a stable and comprehensive view of token importance by integrating multiple perspectives. In this section, we conduct the ablation studies for more different token selection strategies.

F.5.1 MULTI-HEADS

In this section, we ablate the effect of attention scores from muli-heads: (i) **Specific heads**: Randomly selecting one head. (ii) **Separate**: Performing token selection independently within each head. As shown in Table 9, **Average (Ours)** achieves the highest and most consistent performance. Averaging

Figure 8: **Non-Casual for high-resolution and low-resolution vision tokens.**

Model	General			High-Resolution			
	SEED	POPE	MME	VQA-text	ChartQA	DocVQA	InfoVQA
Casual	**63.5**	**87.6**	**1480.3**	**58.5**	**46.1**	**45.2**	**31.6**
Non-Casual	62.7	86.5	1455.2	57.3	45.4	44.5	29.5

Table 8: Comparison with the casual or non-casual mask for vision tokens

way	general	high-resolution
Average (Ours)	**75.04**	**45.35**
Specific-1	69.53	34.29
Specific-2	71.43	38.21
Specific-3	70.21	37.55
Separate	73.51	44.05

Table 9: Comparison of token selection strategies across different attention aggregation methods. Specific-1', 'Specific-2', and 'Specific-3' represent three specific heads randomly selected in our experiments.

provides a comprehensive view, combining insights from multiple heads to capture both global and local token importance. **Specific** shows variable performance across different heads, as each head may focus on unique aspects of the data. Selecting heads suitable for all tasks proves challenging due to this variability. **Separate** performs better than Specific but still falls short of our method. Since each head typically captures local information, analyzing them separately limits the ability to assess global token importance.

Method	general	high-resolution
Vision-to-Text (Ours)	**75.04**	**45.35**
Vision-to-Vision	72.47	42.86
Text-to-Vision	Not Applied	

Table 10: Performance comparison between vision-to-text and vision-to-vision token selection strategies.

F.5.2 DIFFERENT TYPES OF TOKENS

In this section, we analyze the **attention weight distributions** across token types: **vision-to-vision**, **vision-to-text**, and **text-to-vision**, providing insights into the token compression mechanism. From Fig. 2 (b), we can have the follow observations: (i) **Vision-to-Vision**: Dense attention patterns focus on local visual relationships but lack the ability to capture multimodal dependencies. (ii) **Vision-to-Text (Ours)**: Selectively attends to text-relevant vision tokens, effectively integrating multimodal cues and enhancing task performance. (iii) **Text-to-Vision**: Current MLLMs concatenate vision and text tokens in a fixed order, making direct analysis of text-to-vision distributions challenging. As shown in Table 10, Vision-to-Text (Ours) Outperforms vision-to-vision attention weights, demonstrating superior performance on both general and high-resolution benchmarks. The reason may due to that Vision-to-Vision relies solely on single-modal visual information, which limits its effectiveness in capturing multimodal dependencies required for complex tasks.

F.6 TOKEN SELECTION WITH ENTROPY

To strengthen our analysis, we incorporated entropy measurements to quantitatively support our token selection strategy. **Entropy Computation:**

Entropy measures the uncertainty of attention weights and is calculated as:

$$H = -\sum_{i=1}^{n} a_i \log(a_i),$$

where a_i is the normalized attention weight for token i, and n is the total number of tokens. High-entropy tokens indicate diverse information, while low-entropy tokens reflect concentrated, less complex relationships.

Experiment Design: We tested two settings: (i) **High-entropy:** Selecting top-K tokens with the highest entropy values. (ii) **Low-entropy:** Selecting top-K tokens with the lowest entropy values. We also computed the **overlap percentage** between entropy-based selections and our method to evaluate alignment.

From Table 11, we can observe that: (i) **High-entropy tokens outperform low-entropy tokens**, showing they capture richer features. (ii) **Performance correlates with overlap**: High-entropy tokens (71.2% overlap) achieve comparable results to ours, while low-entropy tokens (40.1% overlap) significantly underperform. (iii) **Compared to Our Method**: Our method outperforms high-entropy selection, suggesting its token selection balances diversity (high entropy) and text-relevant information. These results confirm that our strategy inherently selects high-information-content tokens as well as the text-guided information.

way	overlap (%)	general	high-resolution
Ours	100.0	**75.04**	**45.35**
High-Entropy	71.2	73.06	42.33
Low-Entropy	40.1	71.12	38.21

Table 11: Performance comparison between our method and entropy-based token selection strategies. High-entropy tokens show closer alignment with our method and achieve superior results compared to low-entropy tokens.

F.7 COMPARISON RESULTS ON V* BENCH

To further validate the effectiveness of our method, we also report the comparison results in Table 12. **All results are tested based on the models used in Table 2.** Results demonstrate that our method still outperforms the existing approaches, indicating that our method can work for various domains.

Model	Attribute	Spatial	Overall
Full	46.8	63.2	53.1
FlexAttention	43.8	60.5	49.6
Avg-Pool	43.9	60.6	50.5
C-Abstractor	43.5	60.9	50.2
Ours	**45.7**	**62.8**	**52.2**

Table 12: Comparison with different methods on V* bench.

F.8 THE NUMBER OF COMPRESSION RATIOS

In this section, we analyze the number of compression ratios, *i.e.*, $\{r_i, r_j, r_p\}$, which determine how much vision tokens are dropped. Table 13 demonstrates the performance and efficiency trade-offs across different compression ratios. Excessive compression, such as $\{2, 8, 16\}$, significantly degrades

performance in high-resolution tasks despite marginally improving efficiency. Therefore, we selected $\{2, 4, 8\}$ as the optimal setting, providing a balance between efficiency and robust performance across general and high-resolution tasks.

$\{r_i, r_j, r_p\}$	Time (ms)	general	high-resolution
$\{1, 2, 4\}$	532	75.52	45.86
$\{2, 4, 8\}$	515	75.04	45.35
$\{2, 8, 16\}$	508	74.32	43.08

Table 13: Performance and efficiency with different compression ratios.

F.9   COMPARISON WITH PREVIOUS AND CURRENT LAYERS

In our approach, we use the attention map from the previous non-compression layer to guide vision token compression, primarily to reduce computational and memory overhead. Using the current layer's attention map would require performing full attention between the query and key tokens before compression, significantly increasing resource usage. As shown in Table 14, we compare the performance and time efficiency of using the previous layer's attention map (ours) versus the current layer's. Both methods achieve nearly identical performance, but the current layer incurs additional computation time.

Method	Time (ms)	general	high-resolution
Previous Layer (Ours)	515	75.04	45.35
Current Layer	524	75.05	45.39

Table 14: Performance and efficiency comparison between token selection using the previous layer's attention map (ours) and the current layer's attention map.

F.10   TRAINING TIME

In Table 2, we report the single-forward pass time as an indicator of both training and inference efficiency. In Table 15, we have now included total training time comparisons across models, demonstrating that our model achieves approximately 82.9% of the training time required by the full model.

Method	Training time	Inference time	Avg performance
Full	32.2 h	621 ms	48.0
Q-former	25.1 h	507 ms	30.6
Avg-pooling	24.7 h	461 ms	39.1
FlexAttn	25.4 h	505 ms	32.5
LLaVA-UHD	24.9 h	470 ms	36.0
C-Abstractor	25.0 h	492 ms	27.6
FastV	25.2 h	499 ms	39.9
Ours	26.7 h	512 ms	45.4

Table 15: Comparison with the efficiency and performance. All models are trained in one epoch on 16 V100 GPUs.

F.11   TOKEN SELECTION BASED ON VISUAL INFORMATION

We leverage the text-guided token selection for two reasons: (i) In the casual LLMs, the last text token receives holistic information from the whole previous tokens; (ii) Text-guided selection can efficiently filter the instruct-related tokens from noisy tokens.

In this section, to verify the potential benefits of incorporating visual information, we conducted additional experiments with ToMe [1] and Dynamic ViT [2], which explicitly consider visual complexity. Specifically:

- **ToMe[1]**: A similarity-based token merging method that preserves visual structure.

- **Dynamic ViT[2]**: A dynamic token pruning approach guided by visual importance.

- **ToMe+Ours**: We combined ToMe with our method by using our text-guided approach to select key tokens and ToMe to merge remaining tokens.

From Table 16, we have the following observations: (i) ToMe performs slightly better (+0.11%) on low-resolution tasks but is slower due to additional merging steps. (ii) Ours excels on high-resolution tasks (+1.42%) by efficiently filtering relevant tokens and reducing noise. (iii) Combining ToMe with our method improves performance slightly but adds significant computational cost.

In conclusion, while visual complexity-based methods like ToMe show certain advantages in specific settings, our approach strikes a better balance between performance and efficiency, particularly for high-resolution tasks. The additional experiments validate that text-guided selection remains an effective and practical choice for diverse tasks.

way	Times (ms)	general	high-resolution
Attention-weight (ours)	515	75.04	**45.35**
ToMe	564	**75.15**	43.93
Dynamic ViT	520	73.51	42.82
Ours + ToMe	571	75.21	45.44

Table 16: Comparison with different compression ways that use visual nuances in our ACT-In-MLLM.

F.12 COMPARISON WITH HIGHER COMPRESSION RATIO

Table 17 reports additional experiments with both FastV and our method to achieve approximately 60% compression, aiming for similar time efficiency. The results indicate that our method outperforms FastV by 3.43% under comparable efficiency conditions.

Model	Times (s)	Memory (GB)	high-resolution
Full	1.95 (100.0%)	26.8G (100.0%)	52.12
FastV [1]	1.21 (61.8%)	22.5G (83.9%)	44.82
Ours	1.27 (62.6%)	23.0G (86.0%)	48.25 (+3.43)

Table 17: Comparison of efficiency and performance between FastV and our method.

F.13 COMPARISON WITH FASTV AND OURS UNDER MORE VISION TOKENS

In Table 2, we deliberately used 512 tokens, as we believe thatretaining fewer vision tokens provides a better comparison of how well different compression methods preserve critical information. Additionally, as shown in Fig. 6, increasing the number of retained tokens improves performance consistently, further highlighting the effect of the number of reserved vision tokens for the performance, *i.e.*, retaining more vision tokens leads to higher performance.

We also conduct new experiments on LLaVA-NeXT-7B (Liu et al., 2024b) with both FastV and our method retaining 1440 tokens. The results show that our method outperforms FastV by 2.2%

Model	Efficiency		General			High-Resolution				
	Times(ms)	Memory(GB)	SEED	POPE	MME	VQA-text	ChartQA	DocVQA	InfoVQA	Average
LLava-Next	926(**100.0%**)	24.3(**100.0%**)	70.3	85.8	1533.5	67.1	64.2	70.0	34.5	58.9
FastV w/o train	579 (**62.5%**)	21.5(**88.4%**)	69.6	85.5	1502.0	67.0	60.5	62.1	33.1	55.7
Ours w/o train	592 (**63.9%**)	22.1(**90.9%**)	70.1	86.1	1532.2	67.3	63.1	66.9	33.4	57.9

Table 18: Comparison with applying Fastv and ours as the inference-only strategy based on LLaVA-Next.

on high-resolution tasks while maintaining comparable inference times. These results confirm our method's superior ability to preserve information under different vision token settings.

F.14 COMPARISON WITH FASTV AND OURS BASED ON LLAVA-1.5 TRAINING DATA

We conduct additional experiments using the original training data from LLaVA-1.5-7B (Liu et al., 2023a), applying both our method and FastV during training and inference. The results demonstrate that our method consistently outperforms FastV and achieves performance comparable to Full on both general and high-resolution benchmarks.

Notably, since LLaVA-1.5 lacks high-resolution training data, the performance gap between our method and FastV is smaller compared to experiments with augmented high-resolution data. For Open-LLaVA-NeXT[2] (since the training data from LLaVA-Next (Liu et al., 2024b) is not released), when trained on high-resolution data, our method exhibits a larger performance advantage over FastV, highlighting its superior ability to leverage additional information.

Model	Training/Inference Times	General			High-Resolution				
		SEED	POPE	MME	VQA-text	ChartQA	DocVQA	InfoVQA	Average
LLava-1.5	334ms/20.5h	66.1	85.9	1510.7	58.2	18.2	21.2	20.6	29.6
FastV	273ms/17.4h	65.2	85.2	1470.5	57.1	17.2	19.1	19.3	28.2
Ours	286ms/18.1h	66.3	85.8	1510.2	58.0	18.3	21.0	20.2	29.4
Open-LLava-Next	926ms/63.2h	70.9	86.2	1535.4	67.3	64.6	69.5	33.4	58.7
FastV	579ms/45.8h	69.8	86.3	1489.6	66.5	60.1	62.8	32.8	55.6
Ours	592ms/48.5h	70.2	86.5	1530.4	67.4	63.8	67.5	33.2	58.0

Table 19: Comparison between FastV and our method on LLaVA-1.5 and Open-LLaVA-Next during both training and inference.

F.15 VISUALIZATION

In Fig. 9, Fig. 10 and Fig. 11, we show visualization results to compare our method with existing vision compression approaches, *i.e.*, average-pooling from (Liu et al., 2024b) and FlexAttention (Li et al., 2024b).

---

[2]https://github.com/xiaoachen98/Open-LLaVA-NeXT

Figure 9: **Qualitative results from DocVQA (Mathew et al., 2021).** We compare ACT-IN-LLM with Average-pooling from (Liu et al., 2024b) and FlexAttn (Li et al., 2024b)

Figure 10: **Qualitative results from ChartQA (Masry et al., 2022).** We compare ACT-IN-LLMwith Average-pooling from (Liu et al., 2024b) and FlexAttn (Li et al., 2024b)

Figure 11: **Qualitative results from InfoVQA (Mathew et al., 2022).** We compare ACT-IN-LLM with Average-pooling from (Liu et al., 2024b) and FlexAttn (Li et al., 2024b)