Bi-parametric prostate MR image synthesis using pathology and sequence-conditioned stable diffusion

Abstract

We propose an image synthesis mechanism for multi-modality prostate MR images conditioned on text, to control lesion presence and modality, as well as to generate paired bi-parametric images conditioned on images e.g. for generating diffusion-weighted MR from T2-weighted MR for paired data, which are two challenging tasks in pathological image synthesis. Our proposed mechanism utilises and builds upon the recent stable diffusion model by proposing image-based conditioning for paired data generation. We validate our method using 2D image slices from real suspected prostate cancer patients. The realism of the synthesised images is validated by means of a blind expert evaluation for identifying real versus fake images, where a radiologist with 4 years experience reading urological MR only performs 9.4% better than chance, i.e. 59.4% accuracy, on all tested modalities. For the first time, we evaluate the realism of the generated pathology by blind expert identification of the presence of suspected lesions, where we find that the clinician performs similarly for both real and synthesised images, with a 2.9% difference in lesion identification accuracy between real and synthesised images, demonstrating the potentials in radiological training purposes. Furthermore, we also show that a machine learning model, trained for lesion identification, shows better performance (5.9% statistically significant improvement) when trained with real data augmented by synthesised data as opposed to training with only real images, demonstrating usefulness for model training.

Keywords: Stable Diffusion, Image Synthesis, MRI, Prostate.

1. Introduction

Image synthesis has been used to augment real training data, for domain adaptation, or to generate training data for applications with limited real labelled data (Kazeminia et al., 2020). Within these applications, it has also been demonstrated to be effective for improving task performance of automated task networks for tasks like organ segmentation, when synthetic data is used in conjunction with real (Chartsias et al., 2017; Frid-Adar et al., 2018). While these applications do benefit from realistic synthesised data, it is important for these synthesised images to be conditioned on features that need simulating within the context of the relevant clinical application (Kazeminia et al., 2020; Skandarani et al., 2021).

Before the advent of deep learning and even to this day, physics- or pre-operative-imaging-based simulators have been proposed for medical image synthesis, inspired by the physics of the underlying imaging processes. An example is generating intra-operative ultrasound data from larger and higher-resolution pre-operative images such as CT (Cong et al., 2013; Shams et al., 2008). Machine learning approaches for medical image synthesis have largely been focused on using generative adversarial networks (GANs) (Kazeminia

et al., 2020; Skandarani et al., 2021; Singh and Raza, 2021). Conditional GANs (cGAN) have been applied to a variety of problems, for both pre- and intra-operative image synthesis, without relying on patient anatomy being available for synthesis (Kazeminia et al., 2020; Skandarani et al., 2021; Singh and Raza, 2021). They have also been used for learning inter-modality correspondence e.g. for generating CT from MR or vice versa (Nie et al., 2017; Wolterink et al., 2017a,b; Chartsias et al., 2017), conditioned image synthesis for features of interest e.g. blood vessels (Costa et al., 2017a,b; Isola et al., 2017; Guibas et al., 2017; Zhao et al., 2017) or tumours (Mukherkjee et al., 2022; Li et al., 2020). While these GAN-based methods produce realistic images, they often suffer from problems such as under-represented features of interest (Kazeminia et al., 2020), poor performance on class-imbalanced data-sets (Kazeminia et al., 2020), especially for under-represented classes, or other common problems encountered during training, e.g. unstable training, mode collapse and diminishing gradients (Saxena and Cao, 2021), which prevent them from being widely usable (Li et al., 2021). Our preliminary experiments using cGANs or their variants were consistent with these identified limitations, with unconvincing results such as prostate gland broken, in-painted or lacking details, see illustrated examples (Fig. 1). The results may suggest lack of generative modelling ability or ineffective conditioning, for this challenging application with often subtle and sometimes radiologically undetermined pathology.

Recently, diffusion probabilistic models (DPM) have been proposed for image synthesis (Ho et al., 2020; Nichol and Dhariwal, 2021). These models have shown improved image synthesis capability for a wide array of problems and are capable of incorporating both image-based and text-based conditioning (Ho et al., 2020; Nichol and Dhariwal, 2021; Ramesh et al., 2022; Saharia et al., 2022; Rombach et al., 2022). While these models have been leveraged for medical image synthesis tasks (Kazerouni et al., 2022; Kim and Ye, 2022; Dorjsembe et al., 2022; Moghadam et al., 2023; Pinaya et al., 2022), studies so far have focused mostly on unconditional image synthesis or synthesis conditioned on text-based variables.

In many applications that estimate clinically important pathology, conditioning on often under-represented diverse pathology or less-specific, higher dimensional data, such as a specific image sequence in multi-parametric prostate MR, is beneficial or even inevitably required. The ability to generate pathological images potentially can provide useful data, for training junior clinicians as well as developing machine learning models, partly caused by the low sample availability to diversity ratio in specific disease conditions. In addition, in our application, prostate cancer is potentially sensitive to multiple sequences of MR images, reflected by modern uro-radiological guidelines such as PiRADS (pir). For example, peripheral zone lesions are primarily graded on DW images, while transition zone cancers are predominantly determined on T2 images but their risk may be upgraded with positive findings on DW images. The ability to model the conditional distribution of these paired image data and to synthesise diffusion images, given other complementary sequences are essential for the above-discussed data augmentation and clinician training applications.

In this work we present a conditional DPM for synthesis of prostate MR images, conditioned not only on text to control variables such as the presence of cancer and modality of MR acquisition, i.e. T2-weighted (T2W), apparent diffusion contrast (ADC), diffusion-weighted (DW), but on images to facilitate generation of corresponding image pairs by generating DW images conditioned on T2W images. We conduct evaluation by: 1) presenting images to a clinician to identify synthesised images, to test the efficacy of the image

synthesis, to demonstrate the realism of the synthesised images; 2) presenting corresponding T2-weighted and diffusion-weighted, generated and real, images to a clinician for a cancer detection task, to test the realism of the generated lesions; and 3) testing the segmentation accuracy for a neural network-based multi-parametric MR lesion identification task with real data versus with a dataset augmented using synthesised images.

The contributions of this work are summarised: 1) We propose a DPM for synthesis of prostate MR images with challenging pathology. 2) We propose conditioning the synthesis on text-based inputs to control presence of lesions and MR modality. 3) We propose conditional image synthesis to generate DW images from corresponding T2W images as a means of generating corresponding multi-modality images. 4) We conduct an evaluation to demonstrate the effectiveness of the synthesised images not only for clinical training use cases but also for machine learning model training for a task carried out with the MR images i.e. lesion identification.

2. Methods

2.1. Forward process

In our application, assume a forward process being the addition of noise in sequential steps to a given input image, $\mathbf{x}_0 \sim q(x|y)$ sampled from a data distribution of real samples $q(x)$, the distribution to be modelled. Here, y is a variable used to condition the data. At each time-step t, where $t \in \{1, T\}$, the added Gaussian noise follows a Markov chain with T steps, with variance β_t, and only depends on the sample from the previous step and the variable used for conditioning. The distribution can then be written as $q(\mathbf{x}_t|\mathbf{x}_{t-1}, y)$, with $\mathbf{x}_t$ as a latent variable. The diffusion forward process can, therefore, be formulated as:

$$q(\mathbf{x}_t|\mathbf{x}_{t-1}, y) = \mathcal{N}(\mathbf{x}_t; \mu_t = \sqrt{1 - \beta_t}\mathbf{x}_{t-1}, \sigma_t = \beta_t\mathbf{I}) \tag{1}$$

Going from the sample $\mathbf{x}_0$ to the sample $\mathbf{x}_T$ in a closed form thus looks like:

$$q(\mathbf{x}_{1:T}|\mathbf{x}_0, y) = \prod_{t=1}^{T} q(\mathbf{x}_t|\mathbf{x}_{t-1}, y) \tag{2}$$

Efficient re-parameterising allows to compute $\mathbf{x}_t$ without needing to compute all the samples at previous steps. As detailed in previous works (Ho et al., 2020; Nichol and Dhariwal, 2021; Rombach et al., 2022), it can be shown that by defining $\alpha_t = 1 - \beta_t$, $\bar{\alpha}_t = \prod_{s=0}^{t} \alpha_s$, a sample $\mathbf{x}_t$ may be sampled as follows:

$$\mathbf{x}_t \sim q(\mathbf{x}_t|\mathbf{x}_{t-1}, y) = \mathcal{N}(\mathbf{x}_t; \sqrt{\bar{\alpha}_t}\mathbf{x}_0, (1 - \bar{\alpha}_t)\mathbf{I} \tag{3}$$

Variance β may be fixed, whilst a cosine schedule (Nichol and Dhariwal, 2021) is adapted in this work, increasing β from 10^{-4} to 0.02 over T steps.

2.2. Additional input y for conditioning

As in Rombach et al. (2022), we use an encoder τ_γ, with weights γ, for our variables used to condition the synthesis y, which maps to an intermediate representation $\tau_\gamma(y) \in \mathbb{R}^{M \times d_\tau}$,

which is then mapped to the intermediate layers of the U-Net. For language prompts, the domain-specific encoder may be a transformer model as in Rombach et al. (2022). For higher-dimensional conditioning data, such as an image, we use a latent representation from a trained auto-encoder to generate the encoding. In this work the auto-encoder is implemented as a convolutional neural network with 3 down-sampling and 3 up-sampling layers with the latent representation being 128-dimensional; this is mapped to the intermediate layers of the U-Net, similar to Rombach et al. (2022). For sample $\mathbf{x}_t$, conditioned on y, consisting of the image encoding and text encoding, this gives us $\mathbf{x}_t \sim q(\mathbf{x}_t|\mathbf{x}_{t-1}, \tau_\gamma(y))$. For notational brevity, however, we use y, for both, in the remaining analysis.

2.3. Reverse process

With a sufficiently large T, the distribution approaches an isotropic Gaussian (Ho et al., 2020). Thus, the data distribution $q(x)$ can be modelled by reversing the noise adding process from unit Gaussian distribution $\mathcal{N}(0, \mathbf{I})$ samples. In practice, however, the reverse $q(\mathbf{x}_{t-1}|\mathbf{x}_t, y)$ is not known or can be statistically estimated since any statistical estimates would involve knowing the data distribution (Ho et al., 2020). We can, however, learn to approximate $q(\mathbf{x}_{t-1}|\mathbf{x}_t, y)$ using a parameterised function $\epsilon_\theta(\mathbf{x}_t, t, y)$ which can be interpreted as a sequence of de-noising auto-encoders with additional conditioning on the time-step t. It is easier to parameterise a Gaussian and then remove the predicted Gaussian noise manually. Thus for sample $\mathbf{x}_{t-1}$ we have:

$$p_\theta(\mathbf{x}_{t-1}|\mathbf{x}_t, t, y) = \mathcal{N}(\mathbf{x}_{t-1}; \mu_\theta(\mathbf{x}_t, t), \sigma_\theta(\mathbf{x}_t, t)) \tag{4}$$

Then applying the reverse process for all time-steps:

$$p_\theta(\mathbf{x}_{0:T}, 0:T, y) = p_\theta(\mathbf{x}_T, T, y) \prod_{t-1}^{T} p_\theta(\mathbf{x}_{t-1}|\mathbf{x}_t, t, y) \tag{5}$$

Here, we summarise the entire process as a de-noising function $\epsilon_\theta(\mathbf{x}_t, t, y)$ which is trained to predict a de-noised version of its input i.e. $\mathbf{x_0}$ from $\mathbf{x}_t$. To incorporate the encoder used to pre-process the conditioning variable we may re-write this as $\epsilon_\theta(\mathbf{x}_t, t, \tau_\gamma(y))$. As shown in previous works (Ho et al., 2020; Nichol and Dhariwal, 2021; Rombach et al., 2022), the objective for this can then be simplified to:

$$\mathcal{L} = \mathbb{E}_{x, \epsilon \sim \mathcal{N}(0,1), t, y} \left[||\epsilon - \epsilon_\theta(\mathbf{x}_t, t, y)||_1^1 \right] \tag{6}$$

In this work, we follow the implementation in Rombach et al. (2022) and use a U-Net as our de-noising function and feed latent representations to the function for training, as in Rombach et al. (2022), for computational efficiency.

2.4. Sampling from the trained diffusion model

To sample an image from the learnt data distribution with the given conditioning variables. We sample $\mathbf{x}_T \sim \mathcal{N}(0, \mathbf{I})$ and compute the sample using our reverse de-noising function $\mathbf{x}_0 = \epsilon_\theta(\mathbf{x}_t, t, \tau_\gamma(y))$. In practice, however, better performance is seen when noise is added back using the noise schedule until step $t - 1$, i.e. using Eq 2.1, and then the de-noising

function is applied again to generate another latent sample $\mathbf{x}_0$ to which noise is added back using the schedule until $t - 2$, repeated until $t - t$ (Rombach et al., 2022).

3. Experiments

3.1. Datasets

We used two datasets for training, a large open dataset to train and initialise the model for training with a smaller dataset, both of which are described below.

Open-source prostate MR data This dataset comes from Saha et al. (2022) with 1285 samples of 3D prostate MR images with T2W and ADC available. Approximately 190 samples were removed from the orignal set after a semi-manual process, due to their questionable quality and unclear conformity to radiological reporting standards or model training. Only 10 of the central slices were used for training from each of the 3D images since they contain the majority of the prostate volume. 200 patient cases were held out from training and these were used for the purpose of evaluation, see details in Sec. 3.3. For further details readers are referred to Saha et al. (2022). This dataset was used to generate ADC and T2W images used in Sec. 3.3.

Closed source multi-modal prostate MR data Multi-parametric 3D MR images were acquired from 850 patients undergoing prostate biopsy and therapy as part of the [Anonymised] trials. All patients gave written consent and ethics approval was obtained as part of the respective trial protocols. The lesions were manually contoured by a radiologist and these were used to generate binary labels of lesion presence on the slice-level. The image sequences included T2W and DW sequences with highest b-values = 1000 or 2000. For the purpose of this study, ten central slices were used for training from each of the 3D images since they contain the majority of the prostate volume. Slices with lesions visible, being PIRADS ≥ 3, are marked as containing a lesion. 200 samples were held out from training for purposes of evaluation, see details in Sec. 3.3. This dataset was used to generate paired T2W and DW images as described in Sec. 3.3. It should be noted that after training the model with the open-source dataset described above, the model was only fine-tuned with the paired closed source data.

3.2. Model implementation and training

In this work we closely follow the implementation used in Rombach et al. (2022). The hyperparameters are empirically configured, remaining the same as the ImageNet experiments using the latent diffusion model or LDM-1 from Rombach et al. (2022). The networks are trained by first setting to pre-trained weights and the BERT tokeniser is used together with the provided encoder for the conditioning text prompts Rombach et al. (2022). The encoder for the cross-modality translation, i.e. from T2W to DW, is trained as a convolutional autoencoder with latent representations used for conditioning, more details in Sec. 2.2. The models reported in this work were trained on slice-level 2D data, for computational and development efficiency, taking advantage of robust training strategies and hyperparameter values which may or may not to be readily generalised to 3D samples.

3.3. Usability study

Expert identification of synthesised ADC and T2W images   In this experiment, for independent 2D slices of T2W and ADC, which are not necessarily from the same patient, we ask the clinician, with 4 years experience reading urological MR, to identify synthesised images from a mixture of real and synthesised images, regardless of the images containing lesions. The data used consists of 32 2D ADC and 32 2D T2W image slices containing the prostate, with equal positive-to-negative ratio for lesions and real-to-synthesis ratio. The ratios are also blind to the observer. Comparisons and results reported in Sec. 4.

Expert identification of lesions on ADC and T2W images   Using the same data as in the above synthesised identification task, we now ask the clinician to identify 2D slices that contain a suspected lesion with PIRADS $\geq$ 3, regardless of the images being real or fake. Comparisons and results reported in Sec. 4.

Expert identification of lesions on paired T2W-DW images   Using the paired T2W-DW data, the clinician was asked to identify images with a suspected lesion, PIRADS $\geq$ 3, regardless of images being real or synthesised. The synthesised paired images were generated by conditioning DW generation on T2W images. The data used for this study are also sampled with equal ratios, between positive and negative and between real and synthesised, both blind prior to the observer, with results reported in Sec. 4.

Machine learning-automated lesion detection   An AlexNet (4 convolutional and 4 fully connected layers) was trained for the binary classification task of lesion identification, as performed by an expert in the previous paragraph, on each 2D slice pair of T2W and DW images, at the same depth from the same subject. We note that the performance reported in Sec. 4 is consistent with those reported in similar applications, e.g. (Kwon et al., 2018), therefore justifies the choice of the widely established baseline, which is also competitive in a wide variety of other tasks (Krizhevsky et al., 2012). Separate models were trained using only real images and a dataset augmented with the DPM synthesised images. For the real case, we use the closed-source dataset and split it into train, validation and holdout sets, with 510, 170 and 170 patients, respectively, resulting in a total of 5100, 1700 and 1700 2D slices in respective sets. For the augmented dataset, 1600 synthesised images with lesions and 1600 without, were split into train, validation sets, and added to the original sets, resulting in 7500, 2500 in each of the sets, respectively. The holdout set remains the same with 1700 images. The classification accuracy results are reported on 1700 real 2D slices from the holdout set for both trained models, to compare the difference between training with and without augmented synthesised images, in Sec. 4.

4. Results

Results comparing real images to synthesised ones are presented in Table 1 and Fig. 1. The stable diffusion model took approximately 8 days to train on a single Nvidia Tesla V100 GPU, with an average time for sample synthesis being 10 seconds on the same GPU.

Comparing real and synthesised images by expert observer   As in Table 1, an expert clinician was only able to identify synthesised images from real ones with an average

Task	Data	Accuracy
Clinician - synthesised identification	ADC (overall)	0.563
	ADC (w/ cancer)	0.625
	ADC (w/o cancer)	0.500
	T2W (overall)	0.625
	T2W (w/ cancer)	0.688
	T2W (w/o cancer)	0.563
Clinician - lesion identification	ADC (overall)	0.688
	ADC (real)	0.625
	ADC (synthesised)	0.750
	T2W (overall)	0.594
	T2W (real)	0.625
	T2W (synthesised)	0.563
Clinician - lesion identification	T2W-DW paired (overall)	0.563
	T2W-DW paired (real)	0.563
	T2W-DW paired (synthesised)	0.563
ML model - lesion identification	Trained with real	0.704 ± 0.035
	Trained with real + synthesised	0.762 ± 0.042

Table 1: Results summarised for both expert clinician and machine learning model experiments, with details described in Sec. 3

accuracy of 0.594 averaged over all ADC and T2W images, which is only 9.4% better than chance (i.e. 0.500).

Evaluating lesion realism by comparing expert lesion identification performance By comparing the lesion identification task performance accuracy for real and synthesised images, we observe only a small difference of 2.1% between the accuracy for real images versus for synthesised images, as in Sec. 3.3, averaged over ADC, T2W and paired T2W-DWI lesion identification as performed by the expert.

Evaluating usability of synthesised data for machine learning model training As in Table 1, we observe a 5.8% improvement in accuracy, with statistical significance (p-value=0.004), for the lesion identification task for the model trained with augmented data, compared to a model trained with only real images, as described in Sec. 3.3.

5. Discussion and Conclusion

Based on the results presented in Sec. 4, given that 1) the expert clinician only performed marginally better than chance in identifying synthesised images and 2) the expert lesion identification accuracy was similar between the real and generated data, we argue that this may enable a number of applications including flexible training tools for clinical trainees. Perhaps more interestingly, some of the most challenging radiologist tasks, such as the DW reading following a positive reading of T2W images for a transition zone lesion, could be simulated using the proposed sequence-conditioned models. Furthermore, performance

Figure 1: Examples of generated and real images, with keys as follows. Red: Synthesised using DPM, Blue: Real, Green: Synthesised using cGAN. Left: No Cancer, Right: Cancer (arrows indicating suspected lesions, w.r.t. PIRADS≥3). Top block: ADC, Middle block: T2W, Bottom block: Paired T2W-DW (left-right).

improvement in lesion identification experiments using machine learning models, with and without adding synthesised data for training, concludes that the data synthesis approach is promising for data augmentation. Future work will explore further specific use scenarios for conditional synthesis over other modalities, radiological or histo-pathological labels.

This work proposes a stable-diffusion-based image synthesis method together with a conditioning scheme to generate realistic prostate MR images where the modality of MR, presence of lesions and synthesis of paired data may be controlled. Our quantitative results demonstrate the usability of the generated images for use cases such as training trainee clinicians/ radiologists and for improving machine learning model task performance.

References

Pirads - prostate imaging – reporting and data system. https://www.acr.org/-/media/ACR/Files/RADS/Pi-RADS/PIRADS-v2-1.pdf. Accessed: Jan 2023.

Agisilaos Chartsias, Thomas Joyce, Rohan Dharmakumar, and Sotirios A Tsaftaris. Adversarial image synthesis for unpaired multi-modal cardiac data. In *International workshop on simulation and synthesis in medical imaging*, pages 3–13. Springer, 2017.

Weijian Cong, Jian Yang, Yue Liu, and Yongtian Wang. Fast and automatic ultrasound simulation from ct images. *Computational and mathematical methods in medicine*, 2013, 2013.

Pedro Costa, Adrian Galdran, Maria Inês Meyer, Michael David Abramoff, Meindert Niemeijer, Ana Maria Mendonça, and Aurélio Campilho. Towards adversarial retinal image synthesis. *arXiv preprint arXiv:1701.08974*, 2017a.

Pedro Costa, Adrian Galdran, Maria Ines Meyer, Meindert Niemeijer, Michael Abràmoff, Ana Maria Mendonça, and Aurélio Campilho. End-to-end adversarial retinal image synthesis. *IEEE transactions on medical imaging*, 37(3):781–791, 2017b.

Zolnamar Dorjsembe, Sodtavilan Odonchimed, and Furen Xiao. Three-dimensional medical image synthesis with denoising diffusion probabilistic models. In *Medical Imaging with Deep Learning*, 2022.

Maayan Frid-Adar, Eyal Klang, Michal Amitai, Jacob Goldberger, and Hayit Greenspan. Synthetic data augmentation using gan for improved liver lesion classification. In *2018 IEEE 15th international symposium on biomedical imaging (ISBI 2018)*, pages 289–293. IEEE, 2018.

John T Guibas, Tejpal S Virdi, and Peter S Li. Synthetic medical images from dual generative adversarial networks. *arXiv preprint arXiv:1709.01872*, 2017.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

Phillip Isola, Jun-Yan Zhu, Tinghui Zhou, and Alexei A Efros. Image-to-image translation with conditional adversarial networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1125–1134, 2017.

Salome Kazeminia, Christoph Baur, Arjan Kuijper, Bram van Ginneken, Nassir Navab, Shadi Albarqouni, and Anirban Mukhopadhyay. Gans for medical image analysis. *Artificial Intelligence in Medicine*, 109:101938, 2020. ISSN 0933-3657. doi: https://doi.org/10.1016/j.artmed.2020.101938. URL https://www.sciencedirect.com/science/article/pii/S0933365719311510.

Amirhossein Kazerouni, Ehsan Khodapanah Aghdam, Moein Heidari, Reza Azad, Mohsen Fayyaz, Ilker Hacihaliloglu, and Dorit Merhof. Diffusion models for medical image analysis: A comprehensive survey. *arXiv preprint arXiv:2211.07804*, 2022.

Boah Kim and Jong Chul Ye. Diffusion deformable model for 4d temporal medical image generation. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 539–548. Springer, 2022.

A. Krizhevsky, I. Sutskever, and G. Hinton. Imagenet classification with deep convolutional neural networks. *NeurIPS*, 2012.

Deukwoo Kwon, Isildinha Marques dos Reis, Adrian L Breto, Yohann Tschudi, Nicole Gautney, Olmo Zavala-Romero, Christopher Lopez, John Chetley Ford, Sanoj Punnen, Alan Pollack, and Radka Stoyanova. Classification of suspicious lesions on prostate multiparametric mri using machine learning. *Journal of Medical Imaging*, 5, 2018.

Qingyun Li, Zhibin Yu, Yubo Wang, and Haiyong Zheng. Tumorgan: A multi-modal data augmentation framework for brain tumor segmentation. *Sensors*, 20(15):4203, 2020.

Xiang Li, Yuchen Jiang, Juan Jose Rodríguez-Andina, Hao Luo, Shen Yin, and Okyay Kaynak. When medical images meet generative adversarial network: recent development and research opportunities. *Discover Artificial Intelligence*, 2021.

Puria Azadi Moghadam, Sanne Van Dalen, Karina C Martin, Jochen Lennerz, Stephen Yip, Hossein Farahani, and Ali Bashashati. A morphology focused diffusion probabilistic model for synthesis of histopathology images. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pages 2000–2009, 2023.

Debadyuti Mukherjee, Pritam Saha, Dmitry Kaplun, Aleksandr Sinitca, and Ram Sarkar. Brain tumor image generation using an aggregation of gan models with style transfer. *Scientific Reports*, 12(1):1–16, 2022.

Alexander Quinn Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. In *International Conference on Machine Learning*, pages 8162–8171. PMLR, 2021.

Dong Nie, Roger Trullo, Jun Lian, Caroline Petitjean, Su Ruan, Qian Wang, and Dinggang Shen. Medical image synthesis with context-aware generative adversarial networks. In *International conference on medical image computing and computer-assisted intervention*, pages 417–425. Springer, 2017.

Walter HL Pinaya, Petru-Daniel Tudosiu, Jessica Dafflon, Pedro F Da Costa, Virginia Fernandez, Parashkev Nachev, Sebastien Ourselin, and M Jorge Cardoso. Brain imaging generation with latent diffusion models. In *MICCAI Workshop on Deep Generative Models*, pages 117–126. Springer, 2022.

Aditya Ramesh, Prafulla Dhariwal, Alex Nichol, Casey Chu, and Mark Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

Robin Rombach, Andreas Blattmann, Dominik Lorenz, Patrick Esser, and Björn Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10684–10695, 2022.

Anindo Saha, Jasper J. Twilt, Joeran S. Bosma, Bram van Ginneken, Derya Yakar, Mattijs Elschot, Jeroen Veltman, Jurgen Fütterer, Maarten de Rooij, and Henkjan Huisman. Artificial Intelligence and Radiologists at Prostate Cancer Detection in MRI: The PI-CAI Challenge. 2022. doi: 10.5281/zenodo.6522364.

Chitwan Saharia, William Chan, Saurabh Saxena, Lala Li, Jay Whang, Emily Denton, Seyed Kamyar Seyed Ghasemipour, Burcu Karagol Ayan, S Sara Mahdavi, Rapha Gontijo Lopes, et al. Photorealistic text-to-image diffusion models with deep language understanding. *arXiv preprint arXiv:2205.11487*, 2022.

Divya Saxena and Jiannong Cao. Generative adversarial networks (gans) challenges, solutions, and future directions. *ACM Computing Surveys (CSUR)*, 54(3):1–42, 2021.

Ramtin Shams, Richard Hartley, and Nassir Navab. Real-time simulation of medical ultrasound from ct images. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pages 734–741. Springer, 2008.

Nripendra Kumar Singh and Khalid Raza. Medical image generation using generative adversarial networks: A review. *Health informatics: A computational perspective in healthcare*, pages 77–96, 2021.

Youssef Skandarani, Pierre-Marc Jodoin, and Alain Lalande. Gans for medical image synthesis: An empirical study. *ArXiv*, abs/2105.05318, 2021.

Jelmer M Wolterink, Anna M Dinkla, Mark HF Savenije, Peter R Seevinck, Cornelis AT van den Berg, and Ivana Išgum. Deep mr to ct synthesis using unpaired data. In *International workshop on simulation and synthesis in medical imaging*, pages 14–23. Springer, 2017a.

Jelmer M Wolterink, Tim Leiner, Max A Viergever, and Ivana Išgum. Generative adversarial networks for noise reduction in low-dose ct. *IEEE transactions on medical imaging*, 36 (12):2536–2545, 2017b.

He Zhao, Huiqi Li, and Li Cheng. Synthesizing filamentary structured images with gans. *arXiv preprint arXiv:1706.02185*, 2017.