SHOULD WE REPLACE CNNS WITH TRANSFORMERS FOR MEDICAL IMAGES?

ABSTRACT

Convolutional Neural Networks (CNNs) have reigned for a decade as the de facto approach to automated medical image diagnosis, pushing the state-of-the-art in classification, detection and segmentation tasks. Recently, vision transformers (ViTs) have appeared as a competitive alternative to CNNs, yielding impressive levels of performance in the natural image domain, while possessing several interesting properties that could prove beneficial for medical imaging tasks. In this work, we explore whether it is feasible to switch to transformer-based models in the medical imaging domain as well, or if we should keep working with CNNs – can we trivially replace CNNs with transformers? We consider this question in a series of experiments on several standard medical image benchmark datasets and tasks. Our findings show that, while CNNs perform better if trained from scratch, off-the-shelf vision transformers are on par with CNNs when pretrained on ImageNet in both classification and segmentation tasks. Further, ViTs often outperform their CNN counterparts when pretrained using self-supervision.

1 INTRODUCTION

Breakthroughs in medical image analysis over the past decade have been largely fuelled by convolutional neural networks (CNNs). CNN architectures have served as the workhorse for numerous medical image analysis tasks including breast cancer detection (Wu et al., 2019), ultrasound diagnosis (Christiansen et al., 2021), and diabetic retinopathy (De Fauw et al., 2018). Whether applied directly as a plug-and-play solution or used as the backbone for a bespoke model, CNNs such as ResNet (He et al., 2016) are the dominant model for medical image analysis. Recently, however, vision transformers have gained increased popularity for natural image recognition tasks, possibly signalling a transition from convolution-based feature extractors to attention-based models (ViTs). This raises the question: can ViTs also replace CNNs in the medical imaging domain?

In the natural image domain, transformers have been shown to outperform CNNs on standard vision tasks such as IMAGENET classification (Dosovitskiy et al., 2020), as well as in object detection (Carion et al., 2020) and semantic segmentation (Ranftl et al., 2021). Interestingly, transformers succeed despite their lack of inductive biases tied to the convolution operation – translation equivariance and locality – long thought to be essential for visual recognition. This may be explained, in part, by the attention mechanism central to transformers which offers several key advantages over convolutions: (1) it explicitly models and more efficiently captures long-range relationships (Raghu et al., 2021), (2) it has the capacity for adaptive modeling via dynamically computed self-attention weights that capture relationships between tokens. In addition, it provides a type of built-in saliency, providing insight as to what the model focused on (Caron et al., 2021).

Over the years, we have gained a solid understanding of how CNNs perform on medical images, and which techniques benefit them. For example, it is well-known that performance drops dramatically when training data is scarce (Cho et al., 2015). This problem is particularly acute in the medical imaging domain, where datasets are smaller and often accompanied by less reliable labels due to the inherent ambiguity of medical diagnosis. For CNNs, the standard solution is to employ transfer learning (Morid et al., 2020): typically, a model is pretrained on a larger dataset such as IMAGENET (Deng et al., 2009) and then fine-tuned for specific tasks using smaller, specialized datasets. In the medical imaging domain, CNNs pre-trained on IMAGENET typically outperform those trained from scratch, both in terms of final performance and reduced training time (Raghu et al., 2019), despite

the differences between the two domains. When training data is very scarce, pretrained networks are sometimes used directly to generate lower dimensional embeddings useful for downstream analysis.

Supervised transfer learning, while effective, requires many annotations to learn useful features. This can be problematic for medical tasks where annotations are costly and require specialized experts. Self-supervised approaches, on the other hand, can learn powerful representations by leveraging the intrinsic structure present in the image, rather than explicit labels (He et al., 2020; Chen et al., 2020). Although self-supervision performs best when large amounts of unlabelled data are available, it has been shown to be effective with CNNs for certain medical image analysis tasks, leading to increases in performance and faster convergence (Azizi et al., 2021; Sowrirajan et al., 2021).

In contrast to CNNs, we know relatively little about how vision transformers perform in the medical imaging domain. Are vanilla ViTs competitive with CNNs? Despite their success in the natural image domain, there are questions that cast doubt as to whether that success will translate to medical tasks. Evidence suggests that ViTs require very large datasets to outperform CNNs – in Dosovitskiy et al. (2020), the benefits of ViTs only became evident when Google's private 300 million image dataset, JFT-300M, was used for pretraining. Reliance on data of this scale may be a barrier to the widespread application of transformers for medical tasks. As outlined above, CNNs rely on techniques such as transfer learning and self-supervision to perform well on medical datasets. Are these techniques as effective for transformers as they are for CNNs? Finally, the variety and type of patterns and textures in medical images differ significantly from the natural domain. Can ViTs cope with this difference?

If the answers to these questions are affirmative, then there is little to prevent ViTs from becoming the dominant architecture for medical images. Therefore, in this work we explore whether it is feasible for ViTs to replace CNNs for medical imaging tasks, and if there is an advantage of doing so. Given the enormous computational cost of considering the countless variations in CNN and ViT architectures, we limit our study to prototypical CNN and ViT models over a representative set of well-known publicly available medical image benchmark datasets. Through these experiments we show that:

- ViTs pretrained on IMAGENET perform comparably to CNNs for classification tasks on medical images. While CNNs outperform ViTs when trained from scratch, ViTs receive a larger boost in performance from pretraining on IMAGENET.
- For medical image segmentation, directly replacing the CNN encoder of a standard segmentation model with a ViT increases its performance, despite the fact that the segmentation model was designed and optimized for CNNs.
- The best overall classification performance is achieved using self-supervised pre-training on domain-specific medical images, followed by supervised fine-tuning. Here ViTs perform on par with, or better than, CNNs.

These findings, along with additional ablation studies, suggest that medical image analysis can seamlessly transition from CNNs to ViTs, while at the same time potentially gaining from other properties of ViTs such as built-in explainability. The source code to reproduce our work is included in the supplementary material, and we will release it at the time of publication.

2 RELATED WORK

Transformers in vision problems. Following the success of transformers (Vaswani et al., 2017a) in natural language processing (NLP), attention-based models captured the interest of the vision community and inspired numerous improvements to CNNs (Hu et al., 2018; Zhang et al., 2020). The first work to show that vanilla transformers from NLP can be applied with minimal changes to large-scale computer vision tasks and compete with standard CNNs was from Dosovitskiy et al. (2020), which introduced the term *vision transformer*, or ViT[1]. Like their NLP counterparts, the original vision transformers required an enormous corpus of training data to perform well. To overcome this

---

[1]While Dosovitskiy's use of the term ViT referred to a direct adaptation of the original transformer model from NLP (Vaswani et al., 2017b), confusingly ViT has since been adopted as a term to refer to any transformer-based architecture for a vision task. We also use ViT in the latter sense, for brevity.

problem, Touvron et al. (2021) introduced DEITs, which proposed a distillation token in addition to the CLS token that allows transformers to learn more efficiently on smaller datasets. As the number of applications of vision transformers and architectural variations have exploded (Khan et al. (2021) provides a good review), DeiT and the original ViT (Dosovitskiy et al., 2020) have become the standard benchmark architectures for vision transformers.

Vision transformers in medical imaging.   Given the very recent appearance of vision transformers, their application in medical image analysis has been limited. Segmentation has seen the most applications of ViTs. Chen et al. (2021a), Chang et al. (2021) and Hatamizadeh et al. (2021) independently suggested different methods for replacing CNN encoders with transformers in U-Nets (Ronneberger et al., 2015), resulting in improved performance for several medical segmentation tasks. Vanilla transformers were not used in any of these works, however. In each, modifications to the standard vision transformer from Dosovitskiy et al. (2020) are proposed, either to adapt to the U-Net framework (Chen et al., 2021a) or to add components from CNNs (Chang et al., 2021). Other transformer-based adaptations of CNN based-architectures suggested for medical segmentation tasks include Zhang et al. (2021), who combined pyramid networks with transformers, and Lopez Pinaya et al. (2021) who used transformers in variational auto encoders (VAEs) for segmentation and anomaly detection in brain MR imaging.

Only a handful of studies have tackled tasks other than segmentation, such as 3-D image registration (Chen et al., 2021b) and detection (Duong et al., 2021). The only work so far, to our knowledge, applying transformers to medical image classification is a CNN/transformer hybrid model proposed by Dai et al. (2021) applied to a small (344 images) private MRI dataset. Notably, none of these works consider pure, off-the-shelf vision transformers – all propose custom architectures combining transformer/attention modules with components from convolutional feature extractors.

Improved initialization with transfer- and self-supervised learning.   Medical imaging datasets are typically orders of magnitude smaller than natural image datasets due to cost, privacy concerns, and the rarity of certain diseases. A common strategy to learn good representations for smaller datasets is transfer learning. For medical imaging, it is well-known that CNNs usually benefit from transfer learning with IMAGENET (Morid et al., 2020) despite the distinct differences between the domains. However, the question of whether ViTs benefit similarly from transfer learning to medical domains has yet to be explored.

While transfer learning is one option to initialize models with good features, another more recent approach is self-supervised pre-training. Recent advances in self-supervised learning have dramatically improved performance of label-free learning. State-of-the-art methods such as DINO (Caron et al., 2021) and BYOL (Grill et al., 2020) have reached performance on par with supervised learning on IMAGENET and other standard benchmarks. While these top-performing methods have not yet been proven for medical imaging, there has been some work using earlier self-supervision schemes on medical data. Azizi et al. (2021) adopted SimCLR (Chen et al., 2020), a self-supervised contrastive learning method, to pretrain CNNs. This yielded state-of-the-art results for predictions on chest X-rays and skin lesions. Similarly, Sowrirajan et al. (2021) employed MoCo (He et al., 2020) pre-training on a target chest X-ray dataset, demonstrating again the power of this approach. While these works exhibit promising improvements thanks to self-supervision, they have all employed CNN-based encoders. It has yet to be shown how self-supervised learning combined with ViTs performs in medical imaging, and how this combination compares to its CNN counterparts.

3   METHODS

The main question we investigate is whether prototypical vision transformers can be used as a drop-in alternative to CNNs for medical diagnostic tasks. More concretely, we consider how each model type performs on various tasks in different domains, with different types of initialization, and across a range of model capacities. To that end, we conducted a series of experiments to compare representative ViTs and CNNs for various medical image analysis tasks under the same conditions. Hyperparameters such as weight decay and augmentations were optimized for CNNs and used for both CNNs and ViTs – with the exception of the initial learning rate, which was determined individually for each model type using a grid search.

To keep our study tractable, we selected representative CNN and ViT model types as there are too many architecture variations to consider each and every one. For CNNs, an obvious choice is the RESNET family (He et al., 2016), as it is the most common and highly cited CNN backbone, and recent works have shown that RESNETs are competitive with more recent CNNs when modern training methods are applied (Bello et al., 2021). The choice for a representative vision transformer is less clear because the field is still developing. We considered several options including the original ViT (Dosovitskiy et al., 2020), SWIN transformers (Liu et al., 2021), CoaT (Xu et al., 2021), and focal transformers (Yang et al., 2021), but we selected the DEIT family (Touvron et al., 2021) for the following reasons: *(1)* it is one of the earliest and most established vision transformers, with the most citations aside from the original ViT, *(2)* it is similar in spirit to a pure transformer, *(3)* it was the first to show that vision transformers can compete on mid-sized datasets with short training times, *(4)* it retains the interpretability properties of the original transformer.

As mentioned above, CNNs rely on initialization strategies to improve performance for smaller datasets. Accordingly, we consider three common initialization strategies: randomly initialized weights, transfer learning from IMAGENET, and self-supervised pretraining on the target dataset. Using these models and initialization strategies, we consider the following datasets and tasks:

Medical image classification. Five standard medical image classification datasets were chosen to be representative of a diverse set of target domains. These cover different imaging modalities, color distributions, dataset sizes, and tasks, with expert labels.

- **APTOS 2019** – In this dataset, the task is classification of diabetic retinopathy images into 5 categories of disease severity (Kaggle, 2019). APTOS 2019 contains 3,662 high-resolution retinal images.
- **CBIS-DDSM** – A mammography dataset containing 10,239 images. The task is to detect the presence of masses in the mammograms (Sawyer-Lee et al., 2016; Lee et al., 2017; Clark et al., 2013).
- **ISIC 2019** – Here, the task is to classify 25,333 dermoscopic images among nine different diagnostic categories of skin lesions (Tschandl et al., 2018; Codella et al., 2018; Combalia et al., 2019).
- **CheXpert** – This dataset contains 224,316 chest X-rays with labels over 14 categories of diagnostic observations (Irvin et al., 2019).
- **PatchCamelyon** – Sourced from the Camelyon16 segmentation challenge (Bejnordi et al., 2017), this dataset contains 327,680 patches of H&E stained WSIs of sentinel lymph node sections. The task is to classify each patch as cancerous or normal (Veeling et al., 2018).

Medical image segmentation. Although there has been some recent work applying vision transformers to medical image segmentation, all works thus far have proposed hybrid architectures. Here, we evaluate the ability of vanilla ViTs to directly replace the encoder of a standard segmentation framework designed for CNNs. In particular, we use DEEPLAB3 (Chen et al., 2017) featuring a RESNET50 encoder. We merely replace the encoder of the segmentation model with DEIT-S and feed the outputs of the CLS token to the decoder of DEEPLAB3. As DEEPLAB3 was designed and optimized for RESNETs, CNNs have a clear advantage in this setup. Nevertheless, these experiments can shed some light into the quality and versatility of ViT representations for segmentation. Note that, unlike the classification experiments, all models were initialized with IMAGENET pretrained weights. We consider the following medical image segmentation datasets:

- **ISIC 2018** – This dataset consists of 2,694 dermoscopic images with their corresponding pixel-wise binary annotations. The task is to segment skin lesions (Codella et al., 2019; Tschandl et al., 2018).
- **CSAW-S** – This dataset contains 338 images of mammographic screenings. The task is pixel-wise segmentation of tumor masses (Matsoukas et al., 2020).

Experimental setup. We selected the RESNET family (He et al., 2016) as representative CNNs, and DEIT[2] (Touvron et al., 2021) as representative ViTs. Specifically, we test RESNET-18, RESNET-50, and RESNET-152 against DEIT-T, DEIT-S, and DEIT-B. These models were chosen because they are easily comparable in the number of parameters, memory requirements, and

---

[2]Note that we refer to the DEIT architecture pretrained *without* the distillation token (Touvron et al., 2021).

Initialization	Model	APTOS2019, κ ↑ $n = 3,662$	DDSM, ROC-AUC ↑ $n = 10,239$	ISIC2019, Recall ↑ $n = 25,333$	CheXpert, ROC-AUC ↑ $n = 224,316$	Camelyon, ROC-AUC ↑ $n = 327,6890$
Random	ResNet50	0.849 ± 0.022	0.916 ± 0.005	0.660 ± 0.016	0.796 ± 0.000	0.943 ± 0.008
	DeiT-S	0.687 ± 0.017	0.906 ± 0.005	0.579 ± 0.013	0.762 ± 0.002	0.921 ± 0.002
ImageNet (supervised)	ResNet50	0.893 ± 0.004	0.954 ± 0.005	0.810 ± 0.008	0.801 ± 0.001	0.960 ± 0.004
	DeiT-S	0.896 ± 0.005	0.949 ± 0.006	0.844 ± 0.021	0.794 ± 0.000	0.964 ± 0.008
ImageNet (supervised) + self-supervised with DINO	ResNet50	0.894 ± 0.008	0.955 ± 0.002	0.833 ± 0.007	0.801 ± 0.000	0.962 ± 0.004
	DeiT-S	0.896 ± 0.010	0.956 ± 0.002	0.853 ± 0.009	0.801 ± 0.001	0.976 ± 0.002

Table 1: *Comparison of vanilla CNNs vs. ViTs with different initialization strategies on medical image classification tasks.* For each task we report the median ($\pm$ standard deviation) over 5 repetitions using the metrics that are commonly used in the literature. For APTOS2019 we report quadratic Cohen Kappa, for ISIC2019 we report recall and for the rest we report ROC-AUC. The number of examples n in each dataset is also provided.

compute. They are also some of simplest, most commonly used, and versatile architectures of their respective type. Note that ViTs have an additional parameter, patch size, that directly influences the memory and computational requirement. We use the default 16×16 patches to keep the number of parameters comparable to the CNN models.

Using these models, we compare three commonly used initialization strategies:

1. Randomly initialized weights (Kaiming initialization from He et al. (2015)),
2. Transfer learning using supervised IMAGENET pretrained weights,
3. Self-supervised pretraining on the *target dataset*, following IMAGENET initialization.

After initialization using the strategies above, the models are fine-tuned on the target data using the procedure described below. Early experiments indicated that initialization using self-supervision on the target dataset consistently outperforms self-supervision on IMAGENET. We also determined that DINO performs better than other self-supervision strategies such as BYOL (Grill et al., 2020).

Training procedure. For supervised training, we use the ADAM optimizer (Kingma & Ba, 2014)[3]. We performed independent grid searches to find suitable learning rates, and found that 10^{-4} works best for both pretrained CNNs and ViTs, while 10^{-3} is best for random initialization. We used these as base learning rates for the optimizer along with default 1,000 warm-up iterations. When the validation metrics saturated, the learning rate was dropped by a factor of 10 until it reached its final value of 10^{-6}. For classification tasks, images were resized to 256×256 with the following augmentations applied: normalization; color jitter which consists of brightness, contrast, saturation, hue; horizontal flip; vertical flip; and random resized crops. For segmentation, all images were resized to 512×512 and we use the same augmentation methods as for classification except for CSAW-S, where elastic transforms are also employed. For each run, we select the checkpoint with highest validation performance. For self-supervision, pretraining starts with IMAGENET initialization, then applies DINO (Caron et al., 2021) on the target data following the default settings – except for three small changes determined to work better on medical data: *(1)* the base learning rate was set to 10^{-4}, *(2)* the initial weight decay is set at 10^{-5} and increased to 10^{-4} using a cosine schedule, and *(3)* we used an EMA of 0.99. The same settings were used for both CNNs and ViTs; both were pre-trained for 300 epochs using a batch size of 256, followed by fine-tuning as described above.

The classification datasets were divided into train/test/validation splits (80/10/10), with the exception of APTOS2019, which was divided 70/15/15 due to its small size. For the segmentation datasets, we split the training set into train/validation with a 90/10 ratio. For ISIC2018 and CSAW-S, we used the provided validation and test sets for model evaluation.

Evaluation. Unless otherwise specified, each experimental condition was repeated five times. We report the median and standard deviation of the appropriate metric for each dataset: Cohen Kappa, Recall, ROC-AUC, and IoU. For classification, we measure performance of the:

- initialized model representations, through a k-NN evaluation protocol (Caron et al., 2021)
- final model after *fine-tuning* on the target dataset.

The k-NN evaluation protocol is a technique to measure the usefulness of learned representations for some target task; it is typically applied before fine-tuning. For CNNs, it works by freezing the

---

[3] DEIT trained with random initialization used AdamW (Loshchilov & Hutter, 2017) instead of Adam.

Figure 1: Performance comparison of RESNET50 and DEIT-S, two commonly used CNN-based and ViT-based architectures. The comparison covers several standard medical image classification datasets and different types of initialization including random init, IMAGENET pretraining, and self-supervision using DINO (Caron et al., 2021). Performance is measured after fine-tuning on the dataset, as well as using k-NN evaluation without fine-tuning. We report the median over 5 repetitions, error bars represent standard deviation. Numeric values appear in Table 3 (Appendix A)

pretrained encoder, passing test examples through the network, and performing a k-NN classification using the cosine similarity between embeddings of the test images and the k nearest training images ($k = 200$ in our case). For ViTs, the principle is the same except the output of the CLS token is used instead of the CNN's penultimate layer.

4 EXPERIMENTAL RESULTS

Are randomly initialized vision transformers useful? Our first experiment compares the performance of ViTs against CNNs when initialized with random weights (He et al., 2015). The results in Table 1 and Figure 1 indicate that in this setting, CNNs outperform ViTs across the board. This is in line with previous observations in the natural image domain, where ViTs trained on smaller datasets are outperformed by similarly-sized CNNs, a trend that was attributed to the vision transformer's lack of inductive bias (Dosovitskiy et al., 2020). Note that the performance gap appears to shrink as the number of training examples n increases. However, since most medical imaging datasets are of modest size, the usefulness of randomly initialized ViTs appears to be limited.

Does pretraining transformers on IMAGENET work in the medical image domain? To deal with the smaller size of medical imaging datasets, CNNs are often initialized with IMAGENET pretrained weights. This typically results in better performance than random initialization (Morid et al., 2020). We investigate if this approach can be effectively applied to ViTs. To test this, we initialize all models with supervised IMAGENET-pretrained weights and then fine-tune on the target data using the procedure described in Section 3. The results in Table 1 and Figure 1 show that both CNNs and ViTs benefit significantly from IMAGENET initialization. In fact, ViTs appear to benefit more from transfer learning, as they make up for the gap observed using random initialization, performing on par with their CNN counterparts.

Do transformers benefit from self-supervision in the medical image domain? Recent self-supervised learning schemes such as DINO and BYOL achieve performance near that of supervised learning. When used for pretraining in combination with supervised fine-tuning, they can achieve a new state-of-the-art (Caron et al., 2021; Grill et al., 2020). While this phenomenon has been demonstrated for CNNs and ViTs on big data in the natural image domain, it is not clear whether self-supervised pretraining of ViTs helps for medical imaging tasks. To test if ViTs benefit from self-supervision, we adopt the learning scheme of DINO, which can be readily applied to both CNNs and ViTs (Caron et al., 2021). The results reported in Table 1 and Figure 1 show that both ViTs and CNNs perform better with self-supervised pretraining. ViTs appear to outperform CNNs in this setting, albeit by a small margin.

Are pretrained ViT features useful for medical imaging, even without fine-tuning? When data is particularly scarce, features from pre-trained networks can sometimes prove useful, even without fine-tuning on the target domain. The low dimensional embeddings from a good feature extractor can be used for tasks such as clustering or few-shot classification. We investigate whether different types of pretraining in ViTs yields useful representations. We measure this by applying the k-NN evaluation protocol described in Section 3. The embeddings from the penultimate layer

Model	ISIC2018, IoU ↑	CSAW-S, IoU ↑
DEEPLAB3-RESNET50	0.802 ± 0.012	0.320 ± 0.008
DEEPLAB3-DEIT-S	0.845 ± 0.014	0.322 ± 0.028

Table 2: *Medical image segmentation with* DEEPLAB3 *comparing CNN vs. ViT encoders.* For each segmentation task we report the median ($\pm$ standard deviation) over 5 repetitions using Intersection over Union (IoU) as the metric.

Figure 2: Medical image segmentation results comparing DEEPLAB3-RESNET50 (blue), DEEPLAB3-DEIT-S (red). Ground truth mask appears in yellow. Note that the ViT segmentations tend to do a better job of segmenting distant regions.

of the CNN and the CLS token of the ViT are used to perform k-NN classification of test images, assigning labels based on the most similar examples from the training set. We test whether out-of-domain IMAGENET pretraining or in-domain self-supervised DINO pretraining (Caron et al., 2021) yields useful representations when no supervised fine-tuning has been done. The results appear in Figure 1 and Table 3 of the Appendix A, where we compare embeddings for DEIT-S and RESNET50. Pretraining with IMAGENET yields surprisingly useful features for both CNNs and ViTs, considering that the embeddings were learned on out-of-domain data. We observe even more impressive results with in-domain self-supervised DINO pretraining. ViTs appear to benefit more from self-supervision than CNNs – in fact, ViTs trained without any labels using DINO perform similar or better than the same model trained from scratch with full supervision! The results indicate that representations from pretrained vision transformers, both in-domain and out-of domain, can serve as a solid starting point for transfer learning or k-shot methods.

Do transformers learn meaningful representations for segmentation tasks? Segmentation is an important medical image analysis task. For vision transformers to be a viable option to replace CNNs, a competitive level of performance is necessary for segmentation in addition to classification. While previous works have shown that custom attention-based segmentation models can outperform CNNs (see Section 2), here we ask: *can we achieve comparable performance to CNNs by merely replacing the encoder of a CNN-based segmentation model with a vision transformer?* We consider DEEPLAB3 (Chen et al., 2017), a mainstream segmentation model with a RESNET50 encoder. We simply replace the RESNET50 with DEIT-S, and train the model as prescribed in Section 3. Despite the model being designed for RESNET50 and DEIT-S having fewer parameters connected to the DEEPLAB3 head, we observe that ViTs outperform CNNs in our segmentation tasks. The results in Table 2 and Figure 2 clearly indicate that vision transformers are able to produce high quality embeddings for segmentation, even in this disadvantaged setting.

How does capacity of ViT models affect medical image classification? To understand the practical implications of ViT model size for medical image classification, we conducted an ablation study comparing different model capacities of CNNs and ViTs. All models were initialized with IMAGENET pretrained weights, and we followed the training settings outlined in Section 3. The results are presented in Figure 3 and Table 4 in Appendix B. Both CNNs and ViTs seem to benefit similarly from increased model capacity, within the margin of error. For most of the datasets, switching from a small ViT to a bigger model results in minor improvements, with the exception of ISIC 2019 where model size appears to be an important factor for optimal performance.

Other ablation studies. We also considered the effect of token size on ViT performance. Table 5 in Appendix C shows that reducing patch size results in a slight boost in performance, but at the cost of increasing the memory footprint. Finally, we investigate how ViTs attend to different regions of medical images. In Figure 5 of Appendix D we compute the *attention distance*, the average distance

Figure 3: Impact of model capacity on performance for the RESNET and DEIT families on standard medical image classification datasets. We report the median over 5 repetitions, error bars represent standard deviation. Both model types seem to perform better with increasing capacity, roughly scaling similarly. Numeric results appear in Table 4 of Appendix B.

in the image across which information is integrated in ViTs. We find that, in early layers, some heads attend to local regions and some to the entire image. Deeper into the network, attention becomes more global – though more quickly for some datasets than for others.

5 DISCUSSION

Our investigation of prototypical CNNs and ViTs *indicate that CNNs can readily be replaced with vision transformers in medical imaging tasks without sacrificing performance.* The caveat being that employing some form of transfer learning is necessary. Our experiments corroborate previous findings in the natural image domain and provide new insights, which we discuss below.

Discussion and implications of findings. Unsurprisingly, we found that CNNs outperform ViTs when trained from scratch on medical image datasets, which corroborates previous findings in the natural image domain (Dosovitskiy et al., 2020). This trend appears consistently and fits with the "insufficient data to overcome the lack of inductive bias" argument. Thus, the usefulness of randomly initialized ViTs appears to be limited in the medical imaging domain.

When initialized with supervised IMAGENET pretrained weights, the gap between CNN and ViT performance disappears on medical tasks. The benefits of supervised IMAGENET pretraining of CNNs for medical tasks is well-known, but it was unexpected that ViTs would benefit so strongly. To the best of our knowledge, we are the first to confirm that supervised IMAGENET pretraining is as effective for ViTs as it is for CNNs. This suggests that further improvements could be gained via transfer learning from other domains more closely related to the task, as is the case for CNNs (Azizpour et al., 2016). The benefits of IMAGENET pretraining was not only observed for the classification tasks, but also segmentation. There, we showed that vanilla ViTs can be used as a drop-in replacement for CNNs in segmentation frameworks and yield improved performance.

The best overall performance on medical images is obtained using ViTs with in-domain self-supervision, where small but consistent improvements over CNNs and other initialization methods were recorded. Our k-NN evaluation showed that ViT features learned this way are even strong enough to outperform supervised learning with random initialization. Interestingly, we did not observe as strong of an advantage for self-supervised ViTs over IMAGENET pretraining as was previously reported in the natural image domain, *e.g.* in Caron et al. (2021). We suspect this is due to the limited size of medical datasets, suggesting a tantalizing opportunity to apply self-supervision on larger and easier to obtain unlabeled medical image datasets, where greater benefits may appear.

Our other ablation studies showed that ViT performance scales with capacity in a similar manner to CNNs; that ViT performance can be improved by reducing the patch size; and that ViTs attend to information across the whole image even in the earliest layers. Although individually unsurprising, it is worthwhile to confirm these findings for medical images.

Interesting properties of ViTs. Our results indicate that switching from CNNs to ViTs can be done without compromising performance, but *are there any other advantages to switching to ViTs?* There are a number of important differences between CNNs and ViTs. We briefly discuss some of these differences and why they may be interesting for medical image analysis.

Lack of inductive bias – ViTs do away with convolutional layers. Our experiments indicate their implicit locality bias is only necessary when training from scratch on medical datasets. For larger datasets, evidence suggests removing this bias improves performance (Dosovitskiy et al., 2020).

| ISIC 2019 | APTOS 2019 | PatchCamelyon | CheXpert | CBIS-DDSM |

Figure 4: Comparing saliency for RESNET50 (2^{nd} row) and DEIT-S (3^{rd} row) on medical classification. Each column contains the original, a Grad-CAM visualization visualisation for ResNet50 (Selvaraju et al., 2017) and the top-50% attention map of the CLS token of DEIT-S.

Global + local features – ViTs, unlike CNNs, can combine information from distant and local regions of the image, even in early layers. This information can be propagated efficiently to later layers due to better utilization of residual connections that are unpolluted by pooling layers (Raghu et al., 2021). This may prove beneficial for certain medical modalities.

Interpretability – transformers' self-attention mechanism provides, for free, new insight into how the model makes decisions. CNNs do not naturally lend themselves well to visualizing saliency. Popular CNN explainability methods such as class activation maps (Zhou et al., 2016) and Grad-CAM (Selvaraju et al., 2017) provide coarse visualizations because of pooled layers. Transformer tokens give a finer picture of attention, and the self-attention maps explicitly model interactions between every region in the image. In Figure 4, we show examples from each dataset along with Grad-CAM visualizations of RESNET-50 and the top-50% self-attention of 16×16 DEIT-S CLS token heads. The ViTs provide a clear, localized picture of attention, *e.g.* attention at the boundary of the skin lesion in ISIC, on hemorrhages and exudates in APTOS, the membrane of the lymphatic nodule in PatchCamelyon, the opacity in the Chest X-ray, and a dense region in CBIS-DDSM.

6 CONCLUSION

To answer the question posed in the title: *vanilla transformers can reliably replace CNNs on medical image tasks with little effort.* More precisely, ViTs reach the same level of performance as CNNs in an array of medical classification and segmentation tasks, but they require transfer learning to do so. But since IMAGENET pretraining is the standard approach for CNNs, this does not incur any additional cost in practice. The best overall performance on medical imaging tasks is achieved using in-domain self-supervised pretraining, where ViTs show a small advantage over CNNs. As the data size grows, this advantage is expected to grow as well, as observed by Caron et al. (2021) and our own experiments. Additionally, ViTs have a number of properties that make them attractive: they scale similarly to CNNs (or better), their lack of inductive bias, global attention and skip connections may improve performance, and their self-attention mechanism provides a clearer picture of saliency. From a practitioner's point of view, these benefits are compelling enough to switch from convolutional models to vision transformers, especially considering that the switch can be made by simply swapping out a single encoder without an extensive hyper-parameter search. Finally, modern CNNs have been studied extensively for 15 years, while the first pure vision transformer appeared one year ago – the potential for ViTs to improve is considerable.

REFERENCES

Shekoofeh Azizi, Basil Mustafa, Fiona Ryan, Zachary Beaver, Jan Freyberg, Jonathan Deaton, Aaron Loh, Alan Karthikesalingam, Simon Kornblith, Ting Chen, et al. Big self-supervised models advance medical image classification. *arXiv preprint arXiv:2101.05224*, 2021.

Hossein Azizpour, Ali Sharif Razavian, Josephine Sullivan, Atsuto Maki, and Stefan Carlsson. Factors of transferability for a generic convnet representation. *IEEE transactions on pattern analysis and machine intelligence*, 38(9):1790–1802, 2016.

Babak Ehteshami Bejnordi, Mitko Veta, Paul Johannes Van Diest, Bram Van Ginneken, Nico Karssemeijer, Geert Litjens, Jeroen AWM Van Der Laak, Meyke Hermsen, Quirine F Manson, Maschenka Balkenhol, et al. Diagnostic assessment of deep learning algorithms for detection of lymph node metastases in women with breast cancer. *Jama*, 318(22):2199–2210, 2017.

Irwan Bello, William Fedus, Xianzhi Du, Ekin D Cubuk, Aravind Srinivas, Tsung-Yi Lin, Jonathon Shlens, and Barret Zoph. Revisiting resnets: Improved training and scaling strategies. *arXiv preprint arXiv:2103.07579*, 2021.

Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pp. 213–229. Springer, 2020.

Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. *arXiv preprint arXiv:2104.14294*, 2021.

Yao Chang, Hu Menghan, Zhai Guangtao, and Zhang Xiao-Ping. Transclaw u-net: Claw u-net with transformers for medical image segmentation. *arXiv preprint arXiv:2107.05188*, 2021.

Jieneng Chen, Yongyi Lu, Qihang Yu, Xiangde Luo, Ehsan Adeli, Yan Wang, Le Lu, Alan L Yuille, and Yuyin Zhou. Transunet: Transformers make strong encoders for medical image segmentation. *arXiv preprint arXiv:2102.04306*, 2021a.

Junyu Chen, Yufan He, Eric C Frey, Ye Li, and Yong Du. Vit-v-net: Vision transformer for unsupervised volumetric medical image registration. *arXiv preprint arXiv:2104.06468*, 2021b.

Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv preprint arXiv:1706.05587*, 2017.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Junghwan Cho, Kyewook Lee, Ellie Shin, Garry Choy, and Synho Do. How much data is needed to train a medical image deep learning system to achieve necessary high accuracy? *arXiv preprint arXiv:1511.06348*, 2015.

F Christiansen, EL Epstein, E Smedberg, M Åkerlund, Kevin Smith, and E Epstein. Ultrasound image analysis using deep neural networks for discriminating between benign and malignant ovarian tumors: comparison with expert subjective assessment. *Ultrasound in Obstetrics & Gynecology*, 57(1):155–163, 2021.

Kenneth Clark, Bruce Vendt, Kirk Smith, John Freymann, Justin Kirby, Paul Koppel, Stephen Moore, Stanley Phillips, David Maffitt, Michael Pringle, et al. The cancer imaging archive (tcia): maintaining and operating a public information repository. *Journal of digital imaging*, 26(6): 1045–1057, 2013.

Noel Codella, Veronica Rotemberg, Philipp Tschandl, M Emre Celebi, Stephen Dusza, David Gutman, Brian Helba, Aadi Kalloo, Konstantinos Liopyris, Michael Marchetti, et al. Skin lesion analysis toward melanoma detection 2018: A challenge hosted by the international skin imaging collaboration (isic). *arXiv preprint arXiv:1902.03368*, 2019.

Noel CF Codella, David Gutman, M Emre Celebi, Brian Helba, Michael A Marchetti, Stephen W Dusza, Aadi Kalloo, Konstantinos Liopyris, Nabin Mishra, Harald Kittler, et al. Skin lesion analysis toward melanoma detection: A challenge at the 2017 international symposium on biomedical imaging (isbi), hosted by the international skin imaging collaboration (isic). In *2018 IEEE 15th international symposium on biomedical imaging (ISBI 2018)*, pp. 168–172. IEEE, 2018.

Marc Combalia, Noel CF Codella, Veronica Rotemberg, Brian Helba, Veronica Vilaplana, Ofer Reiter, Cristina Carrera, Alicia Barreiro, Allan C Halpern, Susana Puig, et al. Bcn20000: Dermoscopic lesions in the wild. *arXiv preprint arXiv:1908.02288*, 2019.

Yin Dai, Yifan Gao, and Fayu Liu. Transmed: Transformers advance multi-modal medical image classification. *Diagnostics*, 11(8):1384, 2021.

Jeffrey De Fauw, Joseph R Ledsam, Bernardino Romera-Paredes, Stanislav Nikolov, Nenad Tomasev, Sam Blackwell, Harry Askham, Xavier Glorot, Brendan O'Donoghue, Daniel Visentin, et al. Clinically applicable deep learning for diagnosis and referral in retinal disease. *Nature medicine*, 24(9):1342–1350, 2018.

J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A Large-Scale Hierarchical Image Database. In *CVPR09*, 2009.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2020.

Linh T Duong, Nhi H Le, Toan B Tran, Vuong M Ngo, and Phuong T Nguyen. Detection of tuberculosis from chest x-ray images: Boosting the performance with vision transformer and transfer learning. *Expert Systems with Applications*, pp. 115519, 2021.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre H Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent: A new approach to self-supervised learning. *arXiv preprint arXiv:2006.07733*, 2020.

Ali Hatamizadeh, Dong Yang, Holger Roth, and Daguang Xu. Unetr: Transformers for 3d medical image segmentation. *arXiv preprint arXiv:2103.10504*, 2021.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. In *Proceedings of the IEEE international conference on computer vision*, pp. 1026–1034, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 7132–7141, 2018.

Jeremy Irvin, Pranav Rajpurkar, Michael Ko, Yifan Yu, Silviana Ciurea-Ilcus, Chris Chute, Henrik Marklund, Behzad Haghgoo, Robyn Ball, Katie Shpanskaya, et al. Chexpert: A large chest radiograph dataset with uncertainty labels and expert comparison. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 590–597, 2019.

Kaggle. Aptos 2019 blindness detection, 2019. URL https://www.kaggle.com/c/aptos2019-blindness-detection/data.

Salman Khan, Muzammal Naseer, Munawar Hayat, Syed Waqas Zamir, Fahad Shahbaz Khan, and Mubarak Shah. Transformers in vision: A survey. *arXiv preprint arXiv:2101.01169*, 2021.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Rebecca Sawyer Lee, Francisco Gimenez, Assaf Hoogi, Kanae Kawai Miyake, Mia Gorovoy, and Daniel L Rubin. A curated mammography data set for use in computer-aided detection and diagnosis research. *Scientific data*, 4:170177, 2017.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. *arXiv preprint arXiv:2103.14030*, 2021.

Walter Hugo Lopez Pinaya, Petru-Daniel Tudosiu, Robert Gray, Geraint Rees, Parashkev Nachev, Sebastien Ourselin, and M Jorge Cardoso. Unsupervised brain anomaly detection and segmentation with transformers. *arXiv e-prints*, pp. arXiv–2102, 2021.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Christos Matsoukas, Albert Bou Hernandez, Yue Liu, Karin Dembrower, Gisele Miranda, Emir Konuk, Johan Fredin Haslum, Athanasios Zouzos, Peter Lindholm, Fredrik Strand, et al. Adding seemingly uninformative labels helps in low data regimes. In *International Conference on Machine Learning*, pp. 6775–6784. PMLR, 2020.

Mohammad Amin Morid, Alireza Borjali, and Guilherme Del Fiol. A scoping review of transfer learning research on medical image analysis using imagenet. *Computers in biology and medicine*, pp. 104115, 2020.

Maithra Raghu, Chiyuan Zhang, Jon Kleinberg, and Samy Bengio. Transfusion: Understanding transfer learning for medical imaging. In *Advances in Neural Information Processing Systems*, pp. 3342–3352, 2019.

Maithra Raghu, Thomas Unterthiner, Simon Kornblith, Chiyuan Zhang, and Alexey Dosovitskiy. Do vision transformers see like convolutional neural networks? *arXiv preprint arXiv:2108.08810*, 2021.

René Ranftl, Alexey Bochkovskiy, and Vladlen Koltun. Vision transformers for dense prediction. *arXiv preprint arXiv:2103.13413*, 2021.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Rebecca Sawyer-Lee, Francisco Gimenez, Assaf Hoogi, and Daniel Rubin. Curated breast imaging subset of ddsm, 2016. URL `https://wiki.cancerimagingarchive.net/x/lZNXAQ`.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pp. 618–626, 2017.

Hari Sowrirajan, Jingbo Yang, Andrew Y. Ng, and Pranav Rajpurkar. Moco pretraining improves representation and transferability of chest x-ray models. In Mattias Heinrich, Qi Dou, Marleen de Bruijne, Jan Lellmann, Alexander Schläfer, and Floris Ernst (eds.), *Proceedings of the Fourth Conference on Medical Imaging with Deep Learning*, volume 143 of *Proceedings of Machine Learning Research*, pp. 728–744. PMLR, 07–09 Jul 2021. URL `https://proceedings.mlr.press/v143/sowrirajan21a.html`.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. In *International Conference on Machine Learning*, pp. 10347–10357. PMLR, 2021.

Philipp Tschandl, Cliff Rosendahl, and Harald Kittler. The ham10000 dataset, a large collection of multi-source dermatoscopic images of common pigmented skin lesions. *Scientific data*, 5(1):1–9, 2018.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017a. URL https://proceedings.neurips.cc/paper/2017/file/3f5ee243547dee91fbd053c1c4a845aa-Paper.pdf.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017b.

Bastiaan S Veeling, Jasper Linmans, Jim Winkens, Taco Cohen, and Max Welling. Rotation equivariant cnns for digital pathology. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 210–218. Springer, 2018.

Nan Wu, Jason Phang, Jungkyu Park, Yiqiu Shen, Zhe Huang, Masha Zorin, Stanislaw Jastrzebski, Thibault Fevry, Joe Katsnelson, Eric Kim, et al. Deep neural networks improve radiologists' performance in breast cancer screening. *IEEE transactions on medical imaging*, 39(4):1184–1194, 2019.

Weijian Xu, Yifan Xu, Tyler Chang, and Zhuowen Tu. Co-scale conv-attentional image transformers. *arXiv preprint arXiv:2104.06399*, 2021.

Jianwei Yang, Chunyuan Li, Pengchuan Zhang, Xiyang Dai, Bin Xiao, Lu Yuan, and Jianfeng Gao. Focal self-attention for local-global interactions in vision transformers. *arXiv preprint arXiv:2107.00641*, 2021.

Hang Zhang, Chongruo Wu, Zhongyue Zhang, Yi Zhu, Haibin Lin, Zhi Zhang, Yue Sun, Tong He, Jonas Mueller, R Manmatha, et al. Resnest: Split-attention networks. *arXiv preprint arXiv:2004.08955*, 2020.

Zhuangzhuang Zhang, Baozhou Sun, and Weixiong Zhang. Pyramid medical transformer for medical image segmentation. *arXiv preprint arXiv:2104.14702*, 2021.

Bolei Zhou, Aditya Khosla, Agata Lapedriza, Aude Oliva, and Antonio Torralba. Learning deep features for discriminative localization. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2921–2929, 2016.

APPENDIX

The Appendix contains several details and additional experimental results that did not fit within the page limit, organized by the order in which they are referenced in the main article.

A k-NN EVALUATION OF DEIT-S AND RESNET50

The k-NN evaluation protocol is a technique to measure the usefulness of learned representations for some target task; it is typically applied before fine-tuning. For CNNs, it works by freezing the pretrained encoder, passing test examples through the network, and performing a k-NN classification using the cosine similarity between embeddings of the test images and the k nearest training images ($k = 200$ in our case). For ViTs, the principle is the same except the output of the CLS token is used instead of the CNN's penultimate layer.

We applied the k-NN evaluation protocol to test whether out-of-domain IMAGENET pretraining or in-domain self-supervised DINO pretraining yields useful representations when no supervised fine-tuning has been done. The results appear in Table 3. Pretraining with IMAGENET yields surprisingly useful features for both CNNs and ViTs, considering that the embeddings were learned on out-of-domain data. We observe even more impressive results with in-domain self-supervised DINO pretraining. ViTs appear to benefit more from self-supervision than CNNs – in fact, ViTs trained with DINO perform similar or better than the same model trained from scratch with full supervision! The results indicate that representations from pretrained vision transformers, both in-domain and out-of domain, can serve as a solid starting point for transfer learning or k-shot methods.

Initialization	Model	APTOS2019, κ ↑	DDSM, ROC-AUC ↑	ISIC2019, Recall ↑	CheXpert, ROC-AUC ↑	Camelyon, ROC-AUC ↑
Random	ResNet50	0.000 ± 0.000	0.531 ± 0.063	0.125 ± 0.000	0.490 ± 0.029	0.396 ± 0.079
	DeiT-S	0.018 ± 0.086	0.596 ± 0.103	0.129 ± 0.026	0.501 ± 0.013	0.443 ± 0.073
ImageNet (supervised)	ResNet50	0.676 ± 0.000	0.874 ± 0.000	0.248 ± 0.000	0.682 ± 0.000	0.896 ± 0.000
	DeiT-S	0.687 ± 0.000	0.856 ± 0.000	0.242 ± 0.000	0.675 ± 0.000	0.892 ± 0.000
ImageNet (supervised) + self-supervised with DINO	ResNet50	0.786 ± 0.000	0.897 ± 0.000	0.338 ± 0.000	0.697 ± 0.000	0.907 ± 0.000
	DeiT-S	0.781 ± 0.000	0.898 ± 0.000	0.637 ± 0.000	0.739 ± 0.000	0.953 ± 0.000

Table 3: The k-NN evaluation of CNNs and ViTs with different initialization methods including random initialization, IMAGENET pretraining, and self-supervision using DINO (Caron et al., 2021) on the target medical dataset. For each task, we use the metrics that are commonly used in the literature, and for random initialization we report the median ($\pm$ standard deviation) over 5 repetitions. The numbers in this table correspond to Figure 1.

B DEIT AND RESNET WITH DIFFERENT CAPACITIES

To understand the practical implications of ViT model size for medical image classification, we compare different model capacities of CNNs and ViTs.

Specifically, we test RESNET-18, RESNET-50, and RESNET-152 against DEIT-T, DEIT-S, and DEIT-B. These models were chosen because they are easily comparable in the number of parameters, memory requirements, and compute. They are also some of simplest, most commonly used, and versatile architectures of their respective type. All models were initialized with IMAGENET pretrained weights, and trained following the settings outlined in Section 3. The results appear in Table 4.

Both CNNs and ViTs seem to benefit similarly from increased model capacity, within the margin of error. For most of the datasets, switching from a small ViT to a bigger model results in minor improvements, with the exception of ISIC 2019 where model size appears to be an important factor for optimal performance.

Model	APTOS2019, κ ↑	DDSM, ROC-AUC ↑	ISIC2019, Recall ↑	CheXpert, ROC-AUC ↑	Camelyon, ROC-AUC ↑
ResNet18	0.893 ± 0.003	0.950 ± 0.003	0.785 ± 0.015	0.793 ± 0.001	0.959 ± 0.012
ResNet50	0.893 ± 0.004	0.954 ± 0.005	0.810 ± 0.008	0.801 ± 0.001	0.960 ± 0.004
ResNet152	0.900 ± 0.004	0.960 ± 0.003	0.798 ± 0.012	0.801 ± 0.001	0.965 ± 0.003
DeiT-T	0.901 ± 0.005	0.946 ± 0.006	0.810 ± 0.013	0.789 ± 0.001	0.961 ± 0.003
DeiT-S	0.896 ± 0.005	0.949 ± 0.006	0.844 ± 0.021	0.794 ± 0.000	0.964 ± 0.008
DeiT-B	0.897 ± 0.004	0.953 ± 0.004	0.840 ± 0.013	0.795 ± 0.001	0.969 ± 0.002

Table 4: Effect of model capacity on the performance after fine-tuning, with three different RESNET variants (RESNET18, RESNET50 and RESNET152) and DEIT variants (DEIT-T, DEIT-S and DEIT-B) using IMAGENET pretraining. For each task, we report the median ($\pm$ standard deviation) over 5 repetitions using the metrics that are commonly used in the literature. We can see that both CNNs and ViTs mostly benefit from increased model capacity. Further, model types with similar capacity perform approximately on par in most of the datasets, indicating that ViTs scale similarly to CNNs. The numbers in this table correspond to Figure 3.

C EFFECT OF PATCH SIZE

ViTs have an additional parameter, patch size, that directly influences the memory and computational requirement. We compare the default 16×16 patches, used in this work, with 8×8 patches, as it has been noted in previous works that reducing the patch size leads to increased performance (Caron et al., 2021).

The results appear in Table 5. We observe that smaller patch sizes result in marginally better performance, though to a lesser degree than has been observed in the natural image domain.

Patch size	APTOS2019, κ ↑	DDSM, ROC-AUC ↑	ISIC2019, Recall ↑	CheXpert, ROC-AUC ↑	Camelyon, ROC-AUC ↑
16×16	0.896 ± 0.005	0.949 ± 0.006	0.844 ± 0.021	0.794 ± 0.000	0.964 ± 0.008
8×8	0.898 ± 0.006	0.947 ± 0.007	0.847 ± 0.015	0.800 ± 0.001	0.964 ± 0.002

Table 5: Comparison of performance of DEIT-S using 8×8 and 16×16 pixel input patches on standard medical image classification datasets. Performance is measured after fine-tuning on the dataset. For each task we report the median ($\pm$ standard deviation) over 5 repetitions using the metrics that are commonly used in the literature. Although, the model using 8×8 patch sizes median performance is slightly better in the majority of datasets, we see no significant improvements, aside from CheXpert.

D MEAN ATTENDED DISTANCE OF VITS

We compute the *attention distance*, the average distance in the image across which information is integrated in ViTs. As reported previously (e.g. Dosovitskiy et al. (2020)), in early layers, some heads attend to local regions and some to the entire image. Deeper into the network, attention becomes more global – though more quickly for some datasets than for others.

Figure 5: Mean attention distance with respect to the attention head and the network depth. Each point is calculated as the average over 512 test samples as the mean of the element-wise multiplication of each query token's attention and its distance from the other tokens