APPROXIMATE VANISHING IDEAL COMPUTATIONS AT SCALE

ABSTRACT

The *vanishing ideal* of a set of points $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$ is the set of polynomials that evaluate to 0 over all points $\mathbf{x} \in X$ and admits an efficient representation by a finite subset of generators. In practice, to accommodate noise in the data, algorithms that construct generators of the *approximate vanishing ideal* are widely studied but their computational complexities remain expensive. In this paper, we scale up the *Oracle Approximate Vanishing Ideal algorithm* (OAVI), the only generator-constructing algorithm with known learning guarantees. We prove that the computational complexity of OAVI is not superlinear, as previously claimed, but linear in the number of samples m. In addition, we propose two modifications that accelerate OAVI's training time: Our analysis reveals that replacing the *Pairwise Conditional Gradients algorithm*, one of the solvers used in OAVI, with the faster *Blended Pairwise Conditional Gradients algorithm* leads to an exponential speed-up in the number of features n. Finally, using a new *Inverse Hessian Boosting* approach, intermediate convex optimization problems can be solved almost instantly, improving OAVI's training time by multiple orders of magnitude in a variety of numerical experiments.

1 INTRODUCTION

High-quality features are essential for the success of machine learning algorithms (Guyon & Elisseff, 2003) and as a consequence, feature transformation and selection algorithms are an important area of research (Kusiak, 2001; Van Der Maaten et al., 2009; Abdi & Williams, 2010; Paul et al., 2021; Manikandan & Abirami, 2021; Carderera et al., 2021). A recently popularized technique for extracting nonlinear features from data is the concept of the vanishing ideal (Heldt et al., 2009; Livni et al., 2013), which lies at the intersection of machine learning and computer algebra. Unlike conventional machine learning, which relies on a manifold assumption, vanishing ideal computations are based on an algebraic set[1] assumption, for which powerful theoretical guarantees are known (Vidal et al., 2005; Livni et al., 2013; Globerson et al., 2017).

The core concept of vanishing ideal computations is that any dataset $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$ can be described by its *vanishing ideal*, $\mathcal{I}_X = \{g \in \mathcal{P} \mid g(\mathbf{x}) = 0 \text{ for all } \mathbf{x} \in X\}$, where $\mathcal{P}$ is the polynomial ring over $\mathbb{R}$ in n variables. Despite $\mathcal{I}_X$ containing infinitely many polynomials, there exists a finite number of *generators* of $\mathcal{I}_X$, $g_1, \ldots, g_k \in \mathcal{I}_X$ with $k \in \mathbb{N}$, such that any polynomial $h \in \mathcal{I}_X$ can be written as $h = \sum_{i=1}^{k} g_i h_i$, where $h_i \in \mathcal{P}$ for all $i \in \{1, \ldots, k\}$ (Cox et al., 2013). Thus, the generators share any sample $\mathbf{x} \in X$ as a common root, capture the nonlinear structure of the data, and succinctly represent the vanishing ideal $\mathcal{I}_X$. Due to noise in empirical data, we are interested in constructing generators of the *approximate vanishing ideal*, the ideal generated by the set of polynomials that approximately evaluate to 0 for all $\mathbf{x} \in X$ and whose leading term coefficient is 1, see Definition 2.2.

For classification tasks, constructed generators can, for example, be used to transform the features of the dataset $X \subseteq \mathbb{R}^n$ such that the data becomes linearly separable (Livni et al., 2013) and training a linear kernel *Support Vector Machine* (SVM) (Suykens & Vandewalle, 1999) on the feature-transformed data results in excellent classification accuracy.

---

[1] A set $X \subseteq \mathbb{R}^n$ is *algebraic* if it is the set of common roots of a finite set of polynomials.

Various algorithms for the construction of generators of the approximate vanishing ideal exist (Heldt et al., 2009; Fassino, 2010; Limbeck, 2013; Livni et al., 2013; Iraji & Chitsaz, 2017; Kera & Hasegawa, 2020; Kera, 2022), but among them, the *Oracle Approximate Vanishing Ideal algorithm* (OAVI) (Wirth & Pokutta, 2022) is the only one capable of constructing sparse generators and admitting learning guarantees. More specifically, CGAVI (OAVI with *Frank-Wolfe algorithms* (Frank & Wolfe, 1956), a.k.a. *Conditional Gradients algorithms* (CG) (Levitin & Polyak, 1966) as a solver) exploits the sparsity-inducing properties of CG to construct sparse generators and, thus, a robust and interpretable corresponding feature transformation. Furthermore, generators constructed with CGAVI vanish on out-sample data and the combined approach of transforming features with CGAVI for a subsequently applied linear kernel SVM inherits the margin bound of the SVM (Wirth & Pokutta, 2022). Despite OAVI's various appealing properties, the computational complexities of vanishing ideal algorithms for the construction of generators of the approximate vanishing ideal are superlinear in the number of samples m. With training times, in particular, that increase at least cubically with m, vanishing ideal algorithms have yet to be applied to large-scale machine learning problems.

1.1 CONTRIBUTIONS

In this paper, we improve and study the scalability of OAVI.

Linear computational complexity in m. Up until now, the analysis of computational complexities of approximate vanishing ideal algorithms assumed that generators need to vanish exactly, which gave an overly pessimistic estimation of the computational cost. For OAVI, we exploit that generators only have to vanish approximately and prove that the computational complexity of OAVI is not superlinear but linear in the number of samples m and polynomial in the number of features n.

Solver improvements. OAVI repeatedly calls a solver of quadratic convex optimization problems to construct generators. By replacing the *Pairwise Conditional Gradients algorithm* (PCG) (Lacoste-Julien & Jaggi, 2015) with the faster *Blended Pairwise Conditional Gradients algorithm* (BPCG) (Tsuji et al., 2021), we improve the dependence of the time complexity of OAVI on the number of features n in the dataset by an exponential factor.

Inverse Hessian Boosting (IHB**).** Throughout its execution, OAVI solves a series of quadratic convex optimization problems that differ only slightly and we can efficiently maintain and update the inverse of the corresponding Hessians. *Inverse Hessian Boosting* (IHB) then refers to the procedure of passing a starting vector, computed with inverse Hessian information, close to the optimal solution to the convex solver used in OAVI. Empirically, IHB speeds up the training time of OAVI by multiple orders of magnitude.

Large-scale numerical experiments. We perform numerical experiments on datasets of up to two million samples, highlighting that OAVI is an excellent large-scale feature transformation method.

1.2 RELATED WORK

The *Buchberger-Möller algorithm* was the first method for constructing generators of the vanishing ideal (Möller & Buchberger, 1982). Its high susceptibility to noise was addressed by Heldt et al. (2009) with the *Approximate Vanishing Ideal algorithm* (AVI), see also Fassino (2010); Limbeck (2013). The latter also introduced two algorithms that construct generators term by term instead of degree-wise such as AVI, the *Approximate Buchberger-Möller algorithm* (ABM) and the *Border Bases Approximate Buchberger-Möller algorithm*. All of the aforementioned algorithms are monomial-aware, that is, they require an explicit ordering of terms and construct generators as linear combinations of monomials. However, monomial-awareness is an unattractive property: changing the order of the features changes the outputs of the algorithms. Monomial-agnostic approaches such as *Vanishing Component Analysis* (VCA) (Livni et al., 2013) do not suffer from this shortcoming, as they construct generators as linear combinations of polynomials. VCA found success in hand posture recognition, solution selection using genetic programming, principal variety analysis for nonlinear data modeling, and independent signal estimation for blind source separation (Zhao & Song, 2014; Kera & Iba, 2016; Iraji & Chitsaz, 2017; Wang & Ohtsuki, 2018). The disadvantage of foregoing the term-ordering is that VCA sometimes constructs multiple orders of magnitudes more generators than monomial-aware algorithms (Wirth & Pokutta, 2022). Furthermore, VCA is susceptible to the *spurious vanishing problem*: polynomials that do not capture the nonlinear structure of the data but whose coefficient vector entries are small become generators, and, conversely, polynomials that capture the data well but whose coefficient vector entries are large get treated as non-vanishing. The

problem was partially addressed by Kera & Hasegawa (2019; 2020; 2021). Despite the attention vanishing ideal algorithms have received, we appear to be the first to focus on the scalability of generator-constructing algorithms.

2 PRELIMINARIES

Throughout, let $\ell, k, m, n \in \mathbb{N}$. We denote vectors in bold and let $\mathbf{0} \in \mathbb{R}^n$ denote the 0-vector. Sets of polynomials are denoted by capital calligraphic letters. We denote the set of terms (or monomials) and the polynomial ring over $\mathbb{R}$ in n variables by $\mathcal{T}$ and $\mathcal{P}$, respectively. For $\tau \geq 0$, a polynomial $g = \sum_{i=1}^{k} c_i t_i \in \mathcal{P}$ with $\mathbf{c} = (c_1, \ldots, c_k)^\intercal$ is said to be τ-*bounded* in the ℓ_1-norm if the ℓ_1-norm of its coefficient vector is bounded by τ, that is, if $\|g\|_1 := \|\mathbf{c}\|_1 \leq \tau$. Given a polynomial $g \in \mathcal{P}$, let $\deg(g)$ denote its *degree*. The sets of polynomials in n variables of and up to degree $d \in \mathbb{N}$ are denoted by $\mathcal{P}_d$ and $\mathcal{P}_{\leq d}$, respectively. Similarly, for a set of polynomials $\mathcal{G} \subseteq \mathcal{P}$, let $\mathcal{G}_d = \mathcal{G} \cap \mathcal{P}_d$ and $\mathcal{G}_{\leq d} = \mathcal{G} \cap \mathcal{P}_{\leq d}$. We often assume that $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq [0,1]^n$, a form that can be realized, for example, via *min-max feature scaling*. Given a polynomial $g \in \mathcal{P}$ and a set of polynomials $\mathcal{G} = \{g_1, \ldots, g_k\} \subseteq \mathcal{P}$, define the *evaluation vector* of g and *evaluation matrix* of $\mathcal{G}$ over X as $g(X) = (g(\mathbf{x}_1), \ldots, g(\mathbf{x}_m))^\intercal \in \mathbb{R}^m$ and $\mathcal{G}(X) = (g_1(X), \ldots, g_k(X)) \in \mathbb{R}^{m \times k}$, respectively. Further, define the *mean squared error* of g over X as $\mathrm{MSE}(g, X) = \frac{1}{|X|} \|g(X)\|_2^2 = \frac{1}{m} \|g(X)\|_2^2$.

OAVI sequentially processes terms according to a so-called *term ordering*. For ease of presentation, we only consider the *degree-lexicographical ordering of terms* (DegLex) (Cox et al., 2013), denoted by $<_\sigma$. For example, given the terms $t, u, v \in \mathcal{T}_1$, DegLex works as follows: $\mathbb{1} <_\sigma t <_\sigma u <_\sigma v <_\sigma t^2 <_\sigma t \cdot u <_\sigma t \cdot v <_\sigma u^2 <_\sigma u \cdot v <_\sigma v^2 <_\sigma t^3 <_\sigma \ldots$, where $\mathbb{1}$ denotes the constant-1 term. Given a set of terms $\mathcal{O} = \{t_1, \ldots, t_k\}_\sigma \subseteq \mathcal{T}$, the subscript σ indicates that $t_1 <_\sigma \ldots <_\sigma t_k$. With the notion of term ordering, we can define the leading term (coefficient) of a polynomial.

Definition 2.1 (Leading term (coefficient)). Let $g = \sum_{i=1}^{k} c_i t_i \in \mathcal{P}$ with $c_i \in \mathbb{R}$ and $t_i \in \mathcal{T}$ for all $i \in \{1, \ldots, k\}$ and let $j \in \{1, \ldots, k\}$ such that $t_j >_\sigma t_i$ for all $i \in \{1, \ldots, k\} \setminus \{j\}$. Then, t_j and c_j are called *leading term* and *leading term coefficient* of g, denoted by $\mathrm{LT}(g) = t_j$ and $\mathrm{LTC}(g) = c_j$, respectively.

We thus define approximately vanishing polynomials via the mean squared error as follows.

Definition 2.2 (Approximately vanishing polynomial). Let $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi \geq 0$, and $\tau \geq 2$. A polynomial $g \in \mathcal{P}$ is ψ-*approximately vanishing* (over X) if $\mathrm{MSE}(g, X) \leq \psi$. If also $\mathrm{LTC}(g) = 1$ and $\|g\|_1 \leq \tau$, then g is called $(\psi, 1, \tau)$-*approximately vanishing* (over X).

In the definition above, we fix the leading term coefficient of polynomials to address the spurious vanishing problem, and the requirement that polynomials are τ-bounded in the ℓ_1-norm is necessary for the learning guarantees of OAVI to hold.

Definition 2.3 (Approximate vanishing ideal). Let $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi \geq 0$, and $\tau \geq 2$. The (ψ, τ)-*approximate vanishing ideal* (over X), $\mathcal{I}_X^{\psi, \tau}$, is the ideal generated by all $(\psi, 1, \tau)$-approximately vanishing polynomials over X.

For $\psi = 0$ and $\tau = \infty$, it holds that $\mathcal{I}_X^{0, \infty} = \mathcal{I}_X$, that is, the approximate vanishing ideal becomes the vanishing ideal. Thus, Definition 2.3 subsumes the definition of the vanishing ideal. Finally, we introduce the generator-construction problem.

Problem 2.4 (Setting). *Let $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi \geq 0$, and $\tau \geq 2$. Construct a set of $(\psi, 1, \tau)$-approximately vanishing generators of $\mathcal{I}_X^{\psi, \tau}$.*

Recall that for terms $t, u \in \mathcal{T}$, t *divides (or is a divisor of)* u, denoted by $t \mid u$, if there exists $v \in \mathcal{T}$ such that $t \cdot v = u$. If t does not divide u, we write $t \nmid u$. We require the definition below.

Definition 2.5 (Border). Let $\mathcal{O} \subseteq \mathcal{T}$. The *(degree-d) border* of $\mathcal{O}$ is defined as
$$\partial_d \mathcal{O} = \{u \in \mathcal{T}_d : t \in \mathcal{O}_{\leq d-1} \text{ for all } t \in \mathcal{T}_{\leq d-1} \text{ such that } t \mid u\}.$$

3 THE ORACLE APPROXIMATE VANISHING IDEAL ALGORITHM (OAVI)

In this section, we recall the Oracle Approximate Vanishing Ideal algorithm (OAVI) (Wirth & Pokutta, 2022) in Algorithm 1, a method for solving Problem 2.4.

Algorithm 1: OAVI

Input : $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi \geq 0$, and $\tau \geq 2$.
Output: $\mathcal{G} \subseteq \mathcal{P}$ and $\mathcal{O} \subseteq \mathcal{T}$.

1 $d \leftarrow 1, \mathcal{O} = \{t_1\}_\sigma \leftarrow \{\mathbb{1}\}_\sigma, \mathcal{G} \leftarrow \emptyset$
2 **while** $\partial_d \mathcal{O} = \{u_1, \ldots, u_k\}_\sigma \neq \emptyset$ **do**
3   **for** $i = 1, \ldots, k$ **do**
4          $\ell \leftarrow |\mathcal{O}| \in \mathbb{N}, A \leftarrow \mathcal{O}(X) \in \mathbb{R}^{m \times \ell}, \mathbf{b} \leftarrow u_i(X) \in \mathbb{R}^m, P = \{\mathbf{y} \in \mathbb{R}^\ell \mid \|\mathbf{y}\|_1 \leq \tau - 1\}$
5          $\mathbf{c} \in \text{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ ▷ Convex optimization oracle call
6          $g \leftarrow \sum_{j=1}^\ell c_j t_j + u_i$
7   **if** $\text{MSE}(g, X) \leq \psi$ **then**   ▷ Check whether g vanishes
8              $\mathcal{G} \leftarrow \mathcal{G} \cup \{g\}$
9   **else**
10             $\mathcal{O} = \{t_1, \ldots, t_{\ell+1}\}_\sigma \leftarrow (\mathcal{O} \cup \{u_i\})_\sigma$
11   **end**
12   **end**
13     $d \leftarrow d + 1$
14 **end**

3.1 ALGORITHM OVERVIEW

OAVI takes as input a dataset set $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, a vanishing parameter $\psi \geq 0$, and a tolerance τ such that the constructed generators are τ-bounded in the ℓ_1-norm. From a high-level perspective, the algorithm constructs a finite set of $(\psi, 1, \tau)$-approximately vanishing generators of the (ψ, τ)-approximate vanishing ideal $\mathcal{I}_X^{\psi, \tau}$ by solving a series of constrained convex optimization problems. OAVI keeps track of two sets: a set of terms $\mathcal{O} \subseteq \mathcal{T}$ such that there does not exist a $(\psi, 1, \tau)$-approximately vanishing generator of $\mathcal{I}_X^{\psi, \tau}$ with terms only in $\mathcal{O}$ and a set of generators $\mathcal{G} \subseteq \mathcal{P}$ of $\mathcal{I}_X^{\psi, \tau}$. For every degree $d \geq 1$, the algorithm computes the set $\partial_d \mathcal{O}$ in Line 2. Then, in Lines 3–12, for every term $u \in \partial_d \mathcal{O}$, OAVI determines whether there exists a $(\psi, 1, \tau)$-approximately vanishing generator g of $\mathcal{I}_X^{\psi, \tau}$ with $\text{LT}(g) = u$ and other terms only in $\mathcal{O}$ via oracle access to a solver of the constrained convex optimization problem in Line 5. If a $(\psi, 1, \tau)$-approximately vanishing generator g exists, it gets appended to $\mathcal{G}$ in Line 8. Otherwise, the term u gets appended to $\mathcal{O}$ in Line 10. OAVI terminates when a degree $d \in \mathbb{N}$ is reached such that $\partial_d \mathcal{O} = \emptyset$. Then, $\mathcal{G}$ is a set of generators of the (ψ, τ)-approximate vanishing ideal of X, and there does not exist a $(\psi, 1, \tau)$-approximately vanishing polynomial with terms only in $\mathcal{O}$. For ease of exposition, unless noted otherwise, we ignore that the optimization problem in Line 5 of OAVI is addressed only up to a certain accuracy $\epsilon > 0$. Throughout, we denote the output of OAVI by $\mathcal{G}$ and $\mathcal{O}$, that is, $(\mathcal{G}, \mathcal{O}) = \text{OAVI}(X, \psi, \tau)$. We replace the first letter in OAVI with the abbreviation corresponding to the solver used to solve the optimization problem in Line 5. For example, OAVI with solver CG is referred to as CGAVI.

3.2 PREPROCESSING WITH OAVI IN A CLASSIFICATION PIPELINE

We present an overview of how OAVI can be used as a feature transformation method for a subsequently applied linear kernel Support Vector Machine (SVM). Let $\mathcal{X} \subseteq \mathbb{R}^n$ and $\mathcal{Y} = \{1, \ldots, k\}$ be an input and output space, respectively. We are given a training sample $S = \{(\mathbf{x}_1, y_1), \ldots, (\mathbf{x}_m, y_m)\} \in (\mathcal{X} \times \mathcal{Y})^m$ drawn $i.i.d.$ from some unknown distribution $\mathcal{D}$. Our task is to determine a *hypothesis* $h \colon \mathcal{X} \to \mathcal{Y}$ with small *generalization error* $\mathbb{P}_{(\mathbf{x}, y) \backsim \mathcal{D}}[h(\mathbf{x}) \neq y]$. For each class $i \in \{1, \ldots, k\}$, let $X^i = \{\mathbf{x}_j \in X \mid y_j = i\} \subseteq X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\}$ denote the subset of samples corresponding to class i and construct a set of $(\psi, 1, \tau)$-approximately vanishing generators $\mathcal{G}^i$ of the (ψ, τ)-approximate vanishing ideal $\mathcal{I}_{X^i}^{\psi, \tau}$ via OAVI, that is, $(\mathcal{G}^i, \mathcal{O}^i) = \text{OAVI}(X^i, \psi, \tau)$. Combine the sets of generators corresponding to the different classes to obtain $\mathcal{G} = \{g_1, \ldots, g_{|\mathcal{G}|}\} = \bigcup_{i=1}^k \mathcal{G}^i$, which encapsulates the feature transformation we are about to apply to dataset X. As proposed in Livni et al. (2013), we transform the training sample X via the feature transformation

$$\mathbf{x}_j \mapsto \tilde{\mathbf{x}}_j = \left(|g_1(\mathbf{x}_j)|, \ldots, |g_{|\mathcal{G}|}(\mathbf{x}_j)|\right)^\mathsf{T} \in \mathbb{R}^{|\mathcal{G}|} \tag{FT}$$

Figure 1: Training time comparisons with fixed $\psi = 0.005$, averaged over ten random runs with shaded standard deviations. On all datasets except skin, BPCGAVI is faster than PCGAVI.

for $j = 1, \ldots, m$. The motivation behind this feature transformation is that a polynomial $g \in \mathcal{G}^i$ vanishes approximately over all $\mathbf{x} \in X^i$ and (hopefully) attains values that are far from zero over points $\mathbf{x} \in X \setminus X^i$. We then train a linear kernel SVM on the feature-transformed data $\tilde{S} = \{(\tilde{\mathbf{x}}_1, y_1), \ldots, (\tilde{\mathbf{x}}_m, y_m)\}$ with ℓ_1-regularization to promote sparsity. If $\psi = 0$, $\tau = \infty$, and the underlying classes of S belong to disjoint algebraic sets, then the different classes become linearly separable in the feature space corresponding to transformation (FT) and perfect classification accuracy is achieved with the linear kernel SVM (Livni et al., 2013).

3.3 SOLVING THE OPTIMIZATION PROBLEM IN LINE 5 OF OAVI

Setting $\tau = \infty$, the optimization problem in Line 5 becomes unconstrained and can, e.g., be addressed with *Accelerated Gradient Descent* (AGD) (Nesterov, 1983). If, however, $\tau < \infty$, OAVI satisfies to generalization bounds. Indeed, assuming that the data is of the form $X \subseteq [0,1]^n$, the generators in $\mathcal{G}$ are guaranteed to also vanish on out-sample data. Furthermore, the combined approach of using generators obtained via OAVI to preprocess the data for a subsequently applied linear kernel SVM inherits the margin bound of the SVM (Wirth & Pokutta, 2022).

4 OAVI AT SCALE

Here, we address the main shortcoming of vanishing ideal algorithms, time, space, and evaluation complexities that depend superlinearly on m, where m is the number of samples in the dataset $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$. Recall the computational complexity of OAVI for $\tau = \infty$.

Theorem 4.1 (Computational complexity (Wirth & Pokutta, 2022)). *Let $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi \geq 0$, $\tau = \infty$, and $(\mathcal{G}, \mathcal{O}) = \text{OAVI}(X, \psi, \tau)$. Let T_{ORACLE} and S_{ORACLE} be the time and space complexities required to solve the convex optimization problem in Line 5 of OAVI, respectively. In the real number model, the time and space complexities of OAVI are $O((|\mathcal{G}| + |\mathcal{O}|)^2 + (|\mathcal{G}| + |\mathcal{O}|)T_{\text{ORACLE}})$ and $O((|\mathcal{G}|+|\mathcal{O}|)m+S_{\text{ORACLE}})$, respectively. The evaluation vectors of all polynomials in $\mathcal{G}$ over a set $Z = \{\mathbf{z}_1, \ldots, \mathbf{z}_q\} \subseteq \mathbb{R}^n$ can be computed in time $O((|\mathcal{G}| + |\mathcal{O}|)^2 q)$.*

Under mild assumptions, Wirth & Pokutta (2022) proved that $O(|\mathcal{G}| + |\mathcal{O}|) = O(mn)$, implying that OAVI's computational complexity is superlinear in m. Here, we improve OAVI's computational complexity both with a tighter theoretical analysis and algorithmic modifications.

4.1 NUMBER-OF-SAMPLES-AGNOSTIC BOUND ON $|\mathcal{G}| + |\mathcal{O}|$

For $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq [0,1]^n$, $\psi \geq 0$, $\tau = \infty$, and $(\mathcal{G}, \mathcal{O}) = \text{OAVI}(X, \psi, \tau)$, the bound $|\mathcal{G}| + |\mathcal{O}| = O(mn)$ implies that the number of constructed generators depends on the number of samples in X and is independent of the vanishing parameter ψ. Below, in contrast to most of the literature (Heldt et al., 2009; Fassino, 2010; Limbeck, 2013; Livni et al., 2013) where the analysis of generator-constructing algorithms assumes that $\psi = 0$, we exploit $\psi > 0$ to prove a number-of-samples-agnostic bound on $|\mathcal{G}| + |\mathcal{O}|$ that depends on ψ and the number of features n.

Figure 2: Training time comparisons with fixed $\psi = 0.005$, averaged over ten random runs with shaded standard deviations. `CGAVI-IHB` is faster than `BPCGAVI-WIHB`, which is faster than `BPCGAVI`.

Theorem 4.2 (Number-of-samples-agnostic bound on $|\mathcal{G}|+|\mathcal{O}|$). *Let* $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq [0,1]^n$, $\psi \in \,]0,1[$, $D = \lceil -\log(\psi)/\log(4) \rceil$, $\tau \geq (3/2)^D$, *and* $(\mathcal{G}, \mathcal{O}) = \mathtt{OAVI}(X, \psi, \tau)$. *Then,* `OAVI` *terminates after constructing generators of degree D and* $|\mathcal{G}| + |\mathcal{O}| \leq \binom{D+n}{D}$.

When T_{ORACLE} and S_{ORACLE} are linear in m and polynomial in $|\mathcal{G}| + |\mathcal{O}|$, the time and space complexities of `OAVI` are linear in m and polynomial in n. Furthermore, the evaluation complexity of `OAVI` does not depend on m and is polynomial in n.

4.2 Blended Pairwise Conditional Gradients algorithm (BPCG)

[Wirth & Pokutta](2022) solved the optimization problem in Line 5 of `OAVI` with the Pairwise Conditional Gradients algorithm (`PCG`). In this section, we replace `PCG` with the Blended Pairwise Conditional Gradients algorithm (`BPCG`) ([Tsuji et al., 2021](#)), yielding an exponential improvement in time complexity of `OAVI` in the number of features n in the dataset $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq [0,1]^n$.

Let $P \subseteq \mathbb{R}^\ell$, $\ell \in \mathbb{N}$, be a polytope of *diameter* $\delta > 0$ and *pyramidal width* $\omega > 0$, see Appendix D for details, and let $f \colon \mathbb{R}^\ell \to \mathbb{R}$ be a differentiable, μ-strongly convex, and L-smooth function. `PCG` and `BPCG` address constrained convex optimization problems of the form

$$\mathbf{y}^* \in \operatorname{argmin}_{\mathbf{y} \in P} f(\mathbf{y}). \tag{4.1}$$

With $\text{vert}(P)$ denoting the set of vertices of P, the convergence rate of `PCG` for solving (4.1) is $f(\mathbf{y}_T) - f(\mathbf{y}^*) \leq (f(\mathbf{y}_0) - f(\mathbf{y}^*))e^{-\rho_{\text{PCG}}T}$, where $\mathbf{y}_0 \in P$ is the starting point, $\mathbf{y}^*$ is the optimal solution to (4.1), and $\rho_{\text{PCG}} = \mu\omega^2/(4L\delta^2(3|\text{vert}(P)|! + 1))$ ([Lacoste-Julien & Jaggi, 2015](#)). The dependence of `PCG`'s time complexity on $|\text{vert}(P)|!$ is due to `PCG`'s tendency to perform a large number of so-called *swap steps*, which shift weight from the away vertex to the Frank-Wolfe vertex but do not lead to a lot of progress. For the optimization problem in Line 5 of `OAVI`, the dimension is $|\mathcal{O}|$, which can be of similar order of magnitude as $|\mathcal{G}| + |\mathcal{O}|$. Thus, to reach ϵ-accuracy, `PCG` can require a number of iterations that is exponential in $|\mathcal{G}| + |\mathcal{O}|$. Since `BPCG` does not perform swap steps, its convergence rate is $f(\mathbf{y}_T) - f(\mathbf{y}^*) \leq (f(\mathbf{y}_0) - f(\mathbf{y}^*))e^{-\rho_{\text{BPCG}}T}$, where $\rho_{\text{BPCG}} = 1/2 \min\{1/2, \mu\omega^2/(4L\delta^2)\}$ ([Tsuji et al., 2021](#)), which is polynomial in $|\mathcal{G}| + |\mathcal{O}|$: For the optimization problem in Line 5 of `OAVI`, $A = \mathcal{O}(X) \in \mathbb{R}^{m \times \ell}$ and μ and L are the smallest and largest eigenvalues of matrix $\frac{2}{m}A^\intercal A \in \mathbb{R}^{\ell \times \ell}$, respectively. Since the pyramidal width ω of the ℓ_1-ball of radius $\tau - 1$ is at least $(\tau - 1)/\sqrt{\ell}$ (Lemma D.1), ignoring dependencies on μ, L, ϵ, and τ and updating $A^\intercal A$ and $A^\intercal \mathbf{b}$ as explained in the proof of Theorem B.1, the computational complexity of `BPCGAVI` (`OAVI` with solver `BPCG`) is as summarized below.

Corollary 4.3 (Computational complexity of `BPCGAVI`). *Let* $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi > 0$, $\tau \geq 2$, *and* $(\mathcal{G}, \mathcal{O}) = \mathtt{BPCGAVI}(X, \psi, \tau)$. *In the real number model, the time and space complexities of* `BPCGAVI` *are* $O((|\mathcal{G}| + |\mathcal{O}|)^2 m + (|\mathcal{G}| + |\mathcal{O}|)^4)$ *and* $O((|\mathcal{G}| + |\mathcal{O}|)m + (|\mathcal{G}| + |\mathcal{O}|)^2)$, *respectively.*

The results in Figure 1, see Appendix F.1 for details, show that replacing `PCG` with `BPCG` in `OAVI` often speeds up the training time of `OAVI`. For the dataset skin in Figure 1c, see Table 1 for an overview on the datasets, it is not fully understood why `BPCGAVI` is slower than `PCGAVI`.

Figure 3: Training time comparisons, averaged over ten random runs with shaded standard deviations. For small datasets, `ABM` and `VCA` are faster than `OAVI`, but for synthetic, the training times of `ABM` and `VCA` scale worse than `OAVI`'s. See Appendix F.2 for details.

4.3 Inverse Hessian Boosting (IHB)

We introduce Inverse Hessian Boosting (`IHB`) to speed up the training time of `OAVI` by multiple orders of magnitudes by exploiting the structure of the optimization problems solved in `OAVI`.

For ease of exposition, assume for now that $\tau = \infty$, in which case we would use `AGD` to solve the problem in Line 5. Letting $\ell = |\mathcal{O}|$, $A = \mathcal{O}(X) \in \mathbb{R}^{m \times \ell}$, $\mathbf{b} = u_i(X) \in \mathbb{R}^m$, and $f(\mathbf{y}) = \frac{1}{m}\|A\mathbf{y} + \mathbf{b}\|_2^2$, the optimization problem in Line 5 of `OAVI` takes the form $\mathbf{c} \in \operatorname{argmin}_{\mathbf{y} \in \mathbb{R}^\ell} f(\mathbf{y})$. Then, the gradient and Hessian of f at $\mathbf{y} \in \mathbb{R}^\ell$ are $\nabla f(\mathbf{y}) = \frac{2}{m}A^\mathsf{T}(A\mathbf{y} + \mathbf{b}) \in \mathbb{R}^\ell$ and $\nabla^2 f(\mathbf{y}) = \frac{2}{m}A^\mathsf{T}A \in \mathbb{R}^{\ell \times \ell}$, respectively. By construction, the columns of $A = \mathcal{O}(X)$ are linearly independent. Hence, $A^\mathsf{T}A \in \mathbb{R}^{\ell \times \ell}$ is positive definite and invertible, f is strongly convex, and the optimal solution $\mathbf{c}$ to the optimization problem in Line 5 of `OAVI` is unique. Thus, for $\mathbf{y} \in \mathbb{R}^\ell$, we have $\nabla f(\mathbf{y}) = \mathbf{0}$ if and only if $\mathbf{y} = \mathbf{c}$. Instead of using `AGD` to construct an ϵ-accurate solution to the optimization problem in Line 5 of `OAVI`, we could compute the optimal solution $\mathbf{c} = (A^\mathsf{T}A)^{-1}A^\mathsf{T}\mathbf{b} \in \mathbb{R}^\ell$. Since matrix inversions are numerically unstable, relying on them directly would make `OAVI` less robust, and approximately vanishing polynomials might not be correctly detected. Instead, we capitalize on the fact that the number of iterations of `AGD` to reach an ϵ-accurate solution to the optimization problem in Line 5 of `OAVI` depends on the Euclidean distance between the starting vector and the optimal solution. Inverse Hessian Boosting (`IHB`) refers to the procedure of passing $\mathbf{y}_0 = (A^\mathsf{T}A)^{-1}A^\mathsf{T}\mathbf{b} \in \mathbb{R}^\ell$ to `AGD` as a starting vector. Then, `AGD` often reaches ϵ-accuracy in one iteration. In case $(A^\mathsf{T}A)^{-1}$ is not computed correctly due to floating point errors, `AGD` still guarantees an ϵ-accurate solution to the optimization problem. Thus, `IHB` can also be thought of as performing one iteration of *Newton's method* starting with iterate $\mathbf{0}$, see, e.g., Galántai (2000), and passing the resulting vector as a starting iterate to `AGD`. We stress that the dimension of $A^\mathsf{T}A \in \mathbb{R}^{\ell \times \ell}$ is number-of-samples-agnostic, see Theorem 4.2.

`IHB` also works for `OAVI` with $\tau < \infty$, in which we case we use `CG` variants to address the optimization problem in Line 5 of `OAVI`. Then, the optimization problem in Line 5 of `OAVI` is $\mathbf{c} \in \operatorname{argmin}_{\mathbf{y} \in P} f(\mathbf{y})$, where $P = \{\mathbf{y} \in \mathbb{R}^\ell \mid \|\mathbf{y}\|_1 \leq \tau - 1\}$. Consider the problematic case that

$$\|\mathbf{y}_0\|_1 = \|(A^\mathsf{T}A)^{-1}A^\mathsf{T}\mathbf{b}\|_1 > \tau - 1. \tag{INF}$$

If (INF) holds, it is possible that the polynomial $g = \sum_{j=1}^{\ell} c_j t_j + u_i$ constructed in Line 6 of `OAVI` does not vanish approximately even though there exists a polynomial $h \in \mathcal{P}$ with $\operatorname{LT}(h) = u_i$, $\operatorname{LTC}(h) = 1$, non-leading terms only in $\mathcal{O}$, and $\|h\|_1 > \tau$ that vanishes exactly over X. Thus, $\operatorname{MSE}(h, X) = 0 \leq \psi < \operatorname{MSE}(g, X)$. Since $\psi < \operatorname{MSE}(g, X)$, `OAVI` cannot append polynomial g to $\mathcal{G}$ and instead updates $\mathcal{O} \leftarrow (\mathcal{O} \cup \{u_i\})_\sigma$ and $A \leftarrow (A, \mathbf{b}) \in \mathbb{R}^{m \times (\ell+1)}$. However, since $\operatorname{MSE}(h, X) = 0$, we just appended a linearly dependent column to A, making the matrix A rank-deficient, and $(A^\mathsf{T}A)^{-1}$ is no longer defined. Thus, `IHB` is no longer applicable. To address this problem, we could select τ adaptively, but this would invalidate the learning guarantees of `OAVI` that rely on τ being a constant. In practice, we fix $\tau \geq 2$ and stop using `IHB` as soon as (INF) holds, preserving the generalization bounds of `OAVI`. Through careful updates of $(A^\mathsf{T}A)^{-1}$, the discussion in Appendix B.1 implies the following computational complexity of `CGAVI-IHB`.

Corollary 4.4 (Computational complexity of `CGAVI-IHB`). *Let* $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n$, $\psi \geq 0$, $\tau \geq 2$ *large enough such that* (INF) *never holds, and* $(\mathcal{G}, \mathcal{O}) = \texttt{CGAVI-IHB}(X, \psi, \tau)$. *Assuming*

Table 1: Overview of datasets. All datasets are binary classification datasets and are retrieved from the UCI Machine Learning Repository (Dua & Graff, 2017) and additional references are provided.

Dataset	Full name	# samples	# features
bank	banknote authentication	1,372	4
credit	default of credit cards (Yeh & Lien, 2009)	30,000	22
htru	HTRU2 (Lyon et al., 2016)	17,898	8
skin	skin (Bhatt & Dhall, 2010)	245,057	3
spam	spambase	4,601	57
synthetic	synthetic, see Appendix E	2,000,000	3

`CG` *terminates after a constant number of iterations due to* `IHB`*, the time and space complexities of* `CGAVI-IHB` *are* $O((|\mathcal{G}|+|\mathcal{O}|)^2 m + (|\mathcal{G}|+|\mathcal{O}|)^3)$ *and* $O((|\mathcal{G}|+|\mathcal{O}|)m + (|\mathcal{G}|+|\mathcal{O}|)^2)$*, respectively.*

Furthermore, in Appendix B.2, we introduce *Weak Inverse Hessian Boosting* (`WIHB`), a variant of `IHB` designed to speed up `CG` variants while preserving the sparsity-inducing properties of `CG` variants. In Figure 2, see Appendix F.1 for details, we observe that `CGAVI-IHB` is faster than `BPCGAVI-WIHB`, which is faster than `BPCGAVI`. In Figure 3, see Appendix F.2 for details, we compare the training times of `OAVI-IHB` to `ABM` and `VCA`. In Figure 3d, we observe that `OAVI-IHB`'s training time scales better than `ABM` and `VCA`'s.

5 NUMERICAL EXPERIMENTS

Unless noted otherwise, the setup for the numerical experiments applies to all experiments in the paper. The experiments are implemented in PYTHON and performed on an Nvidia GeForce RTX 3080 GPU with 10GB RAM and an Intel Core i7 11700K 8x CPU at 3.60GHz with 64 GB RAM.

We implement `OAVI` as presented in Algorithm 1 with convex solvers `CG`, `PCG`, `BPCG`, and `AGD`, and refer to the resulting algorithms as `CGAVI`, `PCGAVI`, `BPCGAVI`, and `AGDAVI`, respectively. Solvers are run for up to 10,000 iterations. For the `CG` variants, we set $\tau = 1,000$. The `CG` variants are run up to accuracy $\epsilon = 0.01 \cdot \psi$ and are terminated early when less than $0.0001 \cdot \psi$ progress is made in aboslute difference between function values, when the coefficient vector of a generator is constructed, or if we have a guarantee that no coefficient vector of a generator can be constructed. For `AGD`, we set $\tau = \infty$. `AGD` is terminated early if less than $0.0001 \cdot \psi$ progress is made in aboslute difference between function values for 20 iterations in a row or the coefficient vector of a generator is constructed. If `OAVI` is implemented with `WIHB` or `IHB`, we refer to the algorithm as `OAVI-WIHB` or `OAVI-IHB`, respectively. We implement `ABM` as presented in Limbeck (2013) with the modifications that instead of applying the *Singular Value Decomposition* (`SVD`) to the matrix corresponding to $A = \mathcal{O}(X)$ in `OAVI`, we apply the `SVD` to $A^\intercal A$ in case this leads to a faster training time and that we employ the border as in Definition 2.5. We implement `VCA` as presented in Livni et al. (2013) with the modification that instead of applying the `SVD` to the matrix corresponding to $A = \mathcal{O}(X)$ in `OAVI`, we apply the `SVD` to $A^\intercal A$ in case this leads to a faster training time. We implement a polynomial kernel `SVM` with one-versus-rest approach using the SCIKIT-LEARN software package (Pedregosa et al., 2011). We run the polynomial kernel `SVM` with ℓ_2-regularization up to tolerance 10^{-3} or for up to 10,000 iterations.

We use `OAVI`, `ABM`, and `VCA` as preprocessing techniques for a subsequently applied linear kernel `SVM` as in Section 3.2 and refer to the combined approaches as `OAVI*`, `ABM*`, and `VCA*`, respectively. The linear kernel `SVM` is implemented using the SCIKIT-LEARN software package and run with ℓ_1-penalized squared hinge loss up to tolerance 10^{-4} or for up to 10,000 iterations. For `OAVI*`, `ABM*`, and `VCA*`, the hyperparameters are the vanishing tolerance ψ and the ℓ_1-regularization coefficient of the linear kernel `SVM`. For the polynomial kernel `SVM`, the hyperparameters are the degree and the ℓ_2-regularization coefficient. Table 1 contains an overview of the datasets and Table 3 contains an overview of the hyperparameter values.

Table 2: Numerical results averaged over ten random $60\%/40\%$ train/test partitions with best results in bold. For approaches other than BPCGAVI-WIHB*, SPAR $(\mathcal{G}) < 0.01$ and we omit the results.

	Algorithms	Datasets			
		credit	htru	skin	spam
Error	CGAVI-IHB*	18.08	2.09	0.23	6.69
	AGDAVI-IHB*	18.08	2.09	0.23	6.69
	BPCGAVI-WIHB*	**17.98**	**2.05**	**0.22**	6.71
	ABM*	18.36	2.09	0.43	**6.67**
	VCA*	19.85	2.11	0.24	7.15
	SVM	18.34	2.08	2.25	7.13
Time	CGAVI-IHB*	1.3×10^2	2.3×10^1	1.0×10^2	8.3×10^1
	AGDAVI-IHB*	1.9×10^2	2.8×10^1	1.1×10^2	3.1×10^2
	BPCGAVI-WIHB*	3.7×10^3	8.0×10^2	5.6×10^2	4.2×10^2
	ABM*	1.2×10^2	2.4×10^1	$6. \times 10^1$	1.7×10^2
	VCA*	$\mathbf{2.4 \times 10^1}$	6.2×10^0	$\mathbf{1.4 \times 10^1}$	6.5×10^1
	SVM	8.9×10^1	$\mathbf{4.1 \times 10^0}$	7.1×10^2	$\mathbf{2.2 \times 10^0}$
$\|\mathcal{G}\| + \|\mathcal{O}\|$	CGAVI-IHB*	82.40	27.90	39.00	786.60
	AGDAVI-IHB*	82.40	27.90	39.00	786.60
	BPCGAVI-WIHB*	106.40	55.20	39.00	653.00
	ABM*	51.40	28.70	19.30	**261.00**
	VCA*	**49.80**	**19.00**	**12.40**	1766.40
(SPAR)	BPCGAVI-WIHB*	**0.67**	**0.52**	**0.03**	**0.71**

5.1 EXPERIMENT: PERFORMANCE

We compare the performance of CGAVI-IHB*, BPCGAVI-WIHB*, AGDAVI-IHB*, ABM*, and VCA* and polynomial kernel SVM on the datasets credit, htru, skin, and spam.

Setup. We tune the hyperparameters on the training data using threefold cross-validation. We retrain on the entire training dataset using the best combination of hyperparameters and evaluate the classification error on the test set and the hyperparameter optimization time. For the generator-constructing methods, we also compare $|\mathcal{G}| + |\mathcal{O}|$, where $|\mathcal{G}| = \sum_i |\mathcal{G}^i|$, $|\mathcal{O}| = \sum_i |\mathcal{O}|^i$, and $(\mathcal{G}^i, \mathcal{O}^i)$ is the output of applying a generator-constructing algorithm to samples belonging to class i and the *sparsity of the feature transformation* $\mathcal{G} = \bigcup_i \mathcal{G}^i$, which is defined as

$$\text{SPAR}(\mathcal{G}) = \Big(\sum_{g \in \mathcal{G}} g_z \Big) / \Big(\sum_{g \in \mathcal{G}} g_e \Big) \in [0, 1], \tag{SPAR}$$

where for a polynomial $g = \sum_{j=1}^k c_j t_j + t$ with $t >_\sigma t_j$ for all $j \in \{1, \ldots, k\}$, $g_e = k$ and $g_z = |\{c_j = 0 \mid j \in \{1, \ldots, k\}\}|$, that is, g_e and g_z are the number of non-leading and the number of zero coefficient vector entries of g, respectively. The sparser the feature transformation, the larger $\text{SPAR}(\mathcal{G})$. Results are averaged over ten random $60\%/40\%$ train/test partitions.

Results. The results are presented in Table 2. OAVI* admits excellent test set classification accuracy. BPCGAVI-WIHB*, in particular, admits the best test set classification error on all datasets but one. Hyperparameter tuning for OAVI* is often slightly slower than for ABM* and VCA*. Since BPCGAVI-WIHB* does not employ IHB, the approach is always slower than CGAVI-IHB* and AGDAVI-IHB*. For all datasets but credit and skin, the hyperparameter optimization time for the SVM is shorter than for the other approaches. However, on skin, since the training time of the polynomial kernel SVM is superlinear in m, the hyperparameter training for the polynomial kernel SVM is slower than for the other approaches. For datasets with few features n, the magnitude of $|\mathcal{G}| + |\mathcal{O}|$ is often the smallest for VCA*. However, for spam, a dataset with $n = 57$, as already pointed out by Kera & Hasegawa (2019) as the spurious vanishing problem, we observe VCA's tendency to create unnecessary generators. Finally, only BPCGAVI-WIHB* constructs sparse feature transformations, potentially explaining the excellent test set classification accuracy of the approach.

REFERENCES

Hervé Abdi and Lynne J Williams. Principal component analysis. *Wiley Interdisciplinary Reviews: Computational Statistics*, 2(4):433–459, 2010.

Maurice S Bartlett. An inverse matrix adjustment arising in discriminant analysis. *The Annals of Mathematical Statistics*, 22(1):107–111, 1951.

Rajen Bhatt and Abhinav Dhall. Skin segmentation dataset. *UCI Machine Learning Repository*, 2010.

Alejandro Carderera, Sebastian Pokutta, Christof Schütte, and Martin Weiser. CINDy: conditional gradient-based identification of non-linear dynamics – noise-robust recovery, 2021.

David Cox, John Little, and Donal O'Shea. *Ideals, varieties, and algorithms: an introduction to computational algebraic geometry and commutative algebra*. Springer Science & Business Media, 2013.

Dheeru Dua and Casey Graff. UCI machine learning repository. 2017.

Claudia Fassino. Almost vanishing polynomials for sets of limited precision points. *Journal of Symbolic Computation*, 45(1):19–37, 2010.

Marguerite Frank and Philip Wolfe. An algorithm for quadratic programming. *Naval Research Logistics Quarterly*, 3(1-2):95–110, 1956.

Aurel Galántai. The theory of newton's method. *Journal of Computational and Applied Mathematics*, 124(1-2):25–44, 2000.

Amir Globerson, Roi Livni, and Shai Shalev-Shwartz. Effective semisupervised learning on manifolds. In *Proceedings of the Conference on Learning Theory*, pp. 978–1003, 2017.

Isabelle Guyon and André Elisseeff. An introduction to variable and feature selection. *Journal of Machine Learning Research*, 3(Mar):1157–1182, 2003.

Elad Hazan, Amit Agarwal, and Satyen Kale. Logarithmic regret algorithms for online convex optimization. *Machine Learning*, 69(2):169–192, 2007.

Daniel Heldt, Martin Kreuzer, Sebastian Pokutta, and Hennie Poulisse. Approximate computation of zero-dimensional polynomial ideals. *Journal of Symbolic Computation*, 44(11):1566–1591, 2009.

Reza Iraji and Hamidreza Chitsaz. Principal variety analysis. In *Proceedings of the Conference on Robot Learning*, pp. 97–108, 2017.

Hiroshi Kera. Border basis computation with gradient-weighted normalization. In *Proceedings of the 2022 International Symposium on Symbolic and Algebraic Computation*, ISSAC'22, pp. 225–234, 2022.

Hiroshi Kera and Yoshihiko Hasegawa. Spurious vanishing problem in approximate vanishing ideal. *IEEE Access*, 7:178961–178976, 2019.

Hiroshi Kera and Yoshihiko Hasegawa. Gradient boosts the approximate vanishing ideal. In *Proceedings of the Conference on Artificial Intelligence*, number 04, pp. 4428–4435, 2020.

Hiroshi Kera and Yoshihiko Hasegawa. Monomial-agnostic computation of vanishing ideals. *arXiv preprint arXiv:2101.00243*, 2021.

Hiroshi Kera and Hitoshi Iba. Vanishing ideal genetic programming. In *2016 IEEE Congress on Evolutionary Computation (CEC)*, pp. 5018–5025, 2016.

Andrew Kusiak. Feature transformation methods in data mining. *IEEE Transactions on Electronics Packaging Manufacturing*, 24(3):214–221, 2001.

Simon Lacoste-Julien and Martin Jaggi. On the global linear convergence of Frank-Wolfe optimization variants. In *Proceedings of Advances in Neural Information Processing Systems*, pp. 496–504, 2015.

Evgeny S Levitin and Boris T Polyak. Constrained minimization methods. *USSR Computational Mathematics and Mathematical Physics*, 6(5):1–50, 1966.

Jan Limbeck. Computation of approximate border bases and applications. 2013.

Roi Livni, David Lehavi, Sagi Schein, Hila Nachliely, Shai Shalev-Shwartz, and Amir Globerson. Vanishing component analysis. In *Proceedings of the International Conference on Machine Learning*, pp. 597–605. PMLR, 2013.

Robert J Lyon, BW Stappers, Sally Cooper, John Martin Brooke, and Joshua D Knowles. Fifty years of pulsar candidate selection: from simple filters to a new principled real-time classification approach. *Monthly Notices of the Royal Astronomical Society*, 459(1):1104–1123, 2016.

G Manikandan and S Abirami. Feature selection is important: state-of-the-art methods and application domains of feature selection on high-dimensional data. In *Applications in Ubiquitous Computing*, pp. 177–196. Springer, 2021.

H Michael Möller and Bruno Buchberger. The construction of multivariate polynomials with preassigned zeros. In *European Computer Algebra Conference*, pp. 24–31. Springer, 1982.

Yurii Nesterov. A method for unconstrained convex minimization problem with the rate of convergence $O(1/k^2)$. In *Doklady an USSR*, volume 269, pp. 543–547, 1983.

Dipanjyoti Paul, Anushree Jain, Sriparna Saha, and Jimson Mathew. Multi-objective pso based online feature selection for multi-label classification. *Knowledge-Based Systems*, 222:106966, 2021.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, et al. Scikit-learn: Machine learning in python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Javier Pena and Daniel Rodriguez. Polytope conditioning and linear convergence of the frank–wolfe algorithm. *Mathematics of Operations Research*, 44(1):1–18, 2019.

Jack Sherman and Winifred J Morrison. Adjustment of an inverse matrix corresponding to a change in one element of a given matrix. *The Annals of Mathematical Statistics*, 21(1):124–127, 1950.

Johan AK Suykens and Joos Vandewalle. Least squares support vector machine classifiers. *Neural Processing Letters*, 9(3):293–300, 1999.

Kazuma Tsuji, Ken'ichiro Tanaka, and Sebastian Pokutta. Sparser kernel herding with pairwise conditional gradients without swap steps. *arXiv preprint arXiv:2110.12650*, 2021.

Laurens Van Der Maaten, Eric Postma, Jaap Van den Herik, et al. Dimensionality reduction: a comparative. *Journal of Machine Learning Research*, 10(66-71):13, 2009.

Rene Vidal, Yi Ma, and Shankar Sastry. Generalized principal component analysis (gpca). *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 27(12):1945–1959, 2005.

Lu Wang and Tomoaki Ohtsuki. Nonlinear blind source separation unifying vanishing component analysis and temporal structure. *IEEE Access*, 6:42837–42850, 2018.

E Wirth and S Pokutta. Conditional gradients for the approximately vanishing ideal. *arXiv preprint arXiv:2202.03349*, 2022.

I-Cheng Yeh and Che-Hui Lien. The comparisons of data mining techniques for the predictive accuracy of probability of default of credit card clients. *Expert Systems with Applications*, 36(2): 2473–2480, 2009.

Yan-Guo Zhao and Zhan Song. Hand posture recognition using approximate vanishing ideal generators. In *Proceedings of the International Conference on Image Processing*, pp. 1525–1529. IEEE, 2014.

Algorithm 2: BPCG

Input : A smooth and convex function f, a starting vertex $\mathbf{y}_0 \in \text{vert}(P)$.
Output: A point $\mathbf{y}_T \in P$.

---

1   $S^{(0)} \leftarrow \{\mathbf{y}_0\}$
2   $\lambda_{\boldsymbol{v}}^{(0)} \leftarrow 1$ for $\boldsymbol{v} = \mathbf{y}_0$ and 0 otherwise
3   **for** $t = 0, \ldots, T - 1$ **do**
4      $\mathbf{a}_t \in \text{argmax}_{\boldsymbol{v} \in S^{(t)}} \langle \nabla f(\mathbf{y}_t), \boldsymbol{v} \rangle$ $\triangleright$ Away vertex
5      $\mathbf{q}_t \in \text{argmin}_{\boldsymbol{v} \in S^{(t)}} \langle \nabla f(\mathbf{y}_t), \boldsymbol{v} \rangle$ $\triangleright$ Local FW vertex
6      $\mathbf{w}_t \in \text{argmin}_{\boldsymbol{v} \in \text{vert}(P)} \langle \nabla f(\mathbf{y}_t), \boldsymbol{v} \rangle$ $\triangleright$ FW vertex
7   **if** $\langle \nabla f(\mathbf{y}_t), \mathbf{w}_t - \mathbf{y}_t \rangle \geq \langle \nabla f(\mathbf{y}_t), \mathbf{q}_t - \mathbf{a}_t \rangle$ **then**
8          $\mathbf{d}_t \leftarrow \mathbf{q}_t - \mathbf{a}_t$
9          $\gamma_t \in \text{argmin}_{\gamma \in [0, \lambda_{\mathbf{a}_t}^{(t)}]} f(\mathbf{y}_t + \gamma \mathbf{d}_t)$
10        $\lambda_{\mathbf{q}_t}^{(t+1)} \leftarrow \lambda_{\mathbf{q}_t}^{(t)} + \gamma_t$
11        $\lambda_{\mathbf{a}_t}^{(t+1)} \leftarrow \lambda_{\mathbf{a}_t}^{(t)} - \gamma_t$
12   **else**
13          $\mathbf{d}_t \leftarrow \mathbf{w}_t - \mathbf{y}_t$
14          $\gamma_t \in \text{argmin}_{\gamma \in [0,1]} f(\mathbf{y}_t + \gamma \mathbf{d}_t)$
15          $\lambda_{\boldsymbol{v}}^{(t+1)} \leftarrow (1 - \gamma_t) \lambda_{\boldsymbol{v}}^{(t)}$ for $\boldsymbol{v} \in S^{(t)}$
16          $\lambda_{\mathbf{w}_t}^{(t+1)} \leftarrow \begin{cases} \gamma_t, & \mathbf{w}_t \notin S^{(t)} \\ \lambda_{\mathbf{w}_t}^{(t)} + \gamma_t, & \mathbf{w}_t \in S^{(t)} \end{cases}$
17   **end**
18      $S^{(t+1)} \leftarrow \{\boldsymbol{v} \in \text{vert}(P) \mid \lambda_{\boldsymbol{v}}^{(t+1)} > 0\}$
19      $\mathbf{y}_{t+1} \leftarrow \mathbf{y}_t + \gamma_t \mathbf{d}_t$
20   **end**

A   BLENDED PAIRWISE CONDITIONAL GRADIENTS ALGORITHM (BPCG)

The Blended Pairwise Conditional Gradients algorithm (BPCG) is presented in Algorithm 2.

B   ADDITIONAL INFORMATION ON IHB

We discuss the computational complexity of IHB in Appendix B.1 and WIHB in Appendix B.2.

B.1   COMPUTATIONAL COMPLEXITY OF IHB

The main cost of IHB is the inversion of the matrix $A^\intercal A \in \mathbb{R}^{\ell \times \ell}$, which generally requires $O(\ell^3)$ elementary operations. Since OAVI solves a series of quadratic convex optimization problems that differ from each other only slightly, we can maintain and update $(A^\intercal A)^{-1}$ using $O(\ell^2)$ instead of $O(\ell^3)$ elementary operations.

Theorem B.1 (IHB update costs). *Let $A \in \mathbb{R}^{m \times \ell}$, $A^\intercal A \in \mathbb{R}^{\ell \times \ell}$, $(A^\intercal A)^{-1}$, and $\mathbf{b} \in \mathbb{R}^\ell$ be given. In the real number model, in case $\|\mathbf{b}\|_2 > 0$ and $\mathbf{b}^\intercal A (A^\intercal A)^{-1} A^\intercal \mathbf{b} \neq \|\mathbf{b}\|_2^2$,*

$$\tilde{A} = (A, \mathbf{b}) \in \mathbb{R}^{m \times (\ell+1)}, \qquad \tilde{A}^\intercal \tilde{A} \in \mathbb{R}^{(\ell+1) \times (\ell+1)}, \qquad (\tilde{A}^\intercal \tilde{A})^{-1} \in \mathbb{R}^{(\ell+1) \times (\ell+1)} \qquad \text{(B.1)}$$

can be constructed in $O(\ell m + \ell^2)$ elementary operations.

Proof. Let $B = A^\intercal A \in \mathbb{R}^{\ell \times \ell}$, $\tilde{B} = \tilde{A}^\intercal \tilde{A} \in \mathbb{R}^{(\ell+1) \times (\ell+1)}$, $N = B^{-1} \in \mathbb{R}^{\ell \times \ell}$, and $\tilde{N} = \tilde{B}^{-1} = (\tilde{A}^\intercal \tilde{A})^{-1} \in \mathbb{R}^{(\ell+1) \times (\ell+1)}$. In $O(m\ell)$ operations, we construct $A^\intercal \mathbf{b} \in \mathbb{R}^\ell$, $\mathbf{b}^\intercal \mathbf{b} = \|\mathbf{b}\|_2^2 \in \mathbb{R}$, and $\tilde{A} = (A, \mathbf{b}) \in \mathbb{R}^{m \times (\ell+1)}$ and in additional $O(\ell^2)$ operations, we construct

$$\tilde{B} = \tilde{A}^\intercal \tilde{A} = \begin{pmatrix} B & A^\intercal \mathbf{b} \\ \mathbf{b}^\intercal A & \|\mathbf{b}\|_2^2 \end{pmatrix} \in \mathbb{R}^{(\ell+1) \times (\ell+1)}.$$

We next compute $\tilde{N} = \tilde{B}^{-1} = (\tilde{A}^\intercal \tilde{A})^{-1} \in \mathbb{R}^{(\ell+1)\times(\ell+1)}$ in additional $O(\ell^2)$ operations. We write

$$\tilde{N} = \begin{pmatrix} \tilde{N}_1 & \mathbf{\tilde{n}}_2 \\ \mathbf{\tilde{n}}_2^\intercal & \tilde{n}_3 \end{pmatrix} \in \mathbb{R}^{(\ell+1)\times(\ell+1)},$$

where $\tilde{N}_1 \in \mathbb{R}^{\ell \times \ell}$, $\mathbf{\tilde{n}}_2 \in \mathbb{R}^\ell$, and $\tilde{n}_3 \in \mathbb{R}$. Then, it has to hold that

$$\tilde{B}\tilde{N} = \begin{pmatrix} B & A^\intercal \mathbf{b} \\ \mathbf{b}^\intercal A & \|\mathbf{b}\|_2^2 \end{pmatrix} \begin{pmatrix} \tilde{N}_1 & \mathbf{\tilde{n}}_2 \\ \mathbf{\tilde{n}}_2^\intercal & \tilde{n}_3 \end{pmatrix} = I \in \mathbb{R}^{(\ell+1)\times(\ell+1)},$$

where I is the identity matrix. Note that $\mathbf{b}^\intercal A \mathbf{\tilde{n}}_2 + \|\mathbf{b}\|_2^2 \tilde{n}_3 = 1$. Thus,

$$\tilde{n}_3 = \frac{1 - \mathbf{b}^\intercal A \mathbf{\tilde{n}}_2}{\|\mathbf{b}\|_2^2} \in \mathbb{R}, \tag{B.2}$$

which is well-defined due to the assumption $\|\mathbf{b}\|_2 > 0$. Since $\mathbf{b}^\intercal A$ is already computed, once $\mathbf{\tilde{n}}_2$ is computed, the computation of $\tilde{n}_3$ requires only additional $O(\ell)$ operations. Similarly, we have that

$$B\mathbf{\tilde{n}}_2 + A^\intercal \mathbf{b}\tilde{n}_3 = \mathbf{0} \in \mathbb{R}^\ell. \tag{B.3}$$

Plugging (B.2) into (B.3), we obtain $\left(B - \frac{A^\intercal \mathbf{b}\mathbf{b}^\intercal A}{\|\mathbf{b}\|_2^2}\right)\mathbf{\tilde{n}}_2 = -\frac{A^\intercal \mathbf{b}}{\|\mathbf{b}\|_2^2}$. Thus,

$$\mathbf{\tilde{n}}_2 = -\left(B - \frac{A^\intercal \mathbf{b}\mathbf{b}^\intercal A}{\|\mathbf{b}\|_2^2}\right)^{-1} \frac{A^\intercal \mathbf{b}}{\|\mathbf{b}\|_2^2}.$$

The existence of $\left(B - \frac{A^\intercal \mathbf{b}\mathbf{b}^\intercal A}{\|\mathbf{b}\|_2^2}\right)^{-1}$ follows from the Sherman-Morrison formula (Sherman & Morrison, 1950; Bartlett, 1951) and the assumption that $\mathbf{b}^\intercal A(A^\intercal A)^{-1}A^\intercal \mathbf{b} \neq \|\mathbf{b}\|_2^2$. Then,

$$\mathbf{\tilde{n}}_2 = -\left(B^{-1} + \frac{B^{-1}A^\intercal \mathbf{b}\mathbf{b}^\intercal AB^{-1}}{\|\mathbf{b}\|_2^2 - \mathbf{b}^\intercal AB^{-1}A^\intercal \mathbf{b}}\right)\frac{A^\intercal \mathbf{b}}{\|\mathbf{b}\|_2^2},$$

which can be computed using additional $O(\ell^2)$ operations. Finally, we construct $\tilde{N}_1$, which is determined by $B\tilde{N}_1 + A^\intercal \mathbf{b}\mathbf{\tilde{n}}_2^\intercal = I \in \mathbb{R}^{\ell \times \ell}$. Thus, $\tilde{N}_1 = B^{-1} - B^{-1}A^\intercal \mathbf{b}\mathbf{\tilde{n}}_2^\intercal \in \mathbb{R}^{\ell \times \ell}$, which can be computed in additional $O(\ell^2)$ operations, since $B^{-1}A^\intercal \mathbf{b} \in \mathbb{R}^\ell$ is already computed. In summary, we require $O(\ell m + \ell^2)$ elementary operations. Note that even if we do not compute $(\tilde{A}^\intercal \tilde{A})^{-1}$, we still require $O(\ell m + \ell^2)$ elementary operations. $\qquad\square$

In the remark below, we discuss the literature related to IHB.

Remark B.2 (Work related to IHB)**.** The proof of Theorem B.1 is similar to the proof that the inverse of the Hessian can be updated efficiently in the *Online Newton algorithm* (Hazan et al., 2007): both rely on the Sherman-Morrison formula (Sherman & Morrison, 1950; Bartlett, 1951). However, in our setting, the updates occur column-wise instead of row-wise. Updating $(A^\intercal A)^{-1}$ column-wise for generator-constructing algorithms was already discussed in Limbeck (2013) using QR decompositions without addressing the numerical instability of inverse matrix updates.

Next, we prove that Theorem B.1 implies the improved computational complexity of CGAVI-IHB in Corollary 4.4.

Proof of Corollary 4.4. Suppose that CGAVI-IHB is currently executing Lines 5–11 of Algorithm 1 for a particular term $u_i \in \partial_d \mathcal{O}$ and recall the associated notations $\ell = |\mathcal{O}|$, $A = \mathcal{O}(X) \in \mathbb{R}^{m \times \ell}$, $\mathbf{b} = u_i(X)$, $f(\mathbf{y}) = \frac{1}{m}\|A\mathbf{y} + \mathbf{b}\|_2^2$, and $P = \{\mathbf{y} \in \mathbb{R}^\ell \mid \|\mathbf{y}\|_1 \leq \tau - 1\}$. Then, the optimization problem in Line 5 takes the form

$$\mathbf{c} \in \operatorname{argmin}_{\mathbf{y} \in P} f(\mathbf{y}).$$

We first prove that the violation of any of the two assumptions of Theorem B.1 implies the existence of a $(\psi, 1, \tau)$-approximately vanishing generator g. We prove this claim by treating the two assumptions separately:

1. If $\|\mathbf{b}\|_2 = 0$, it holds that $\mathrm{MSE}(u_i, X) = 0$. By the assumption that $\tau \geq 2$ is large enough to guarantee that (INF) never holds, CGAVI-IHB constructs a $(\psi, 1, \tau)$-approximately vanishing generator in Line 6.

Algorithm 3: `BPCGAVI-WIHB`

Input : $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq \mathbb{R}^n, \psi \geq 0, \tau \geq 2$, and $\epsilon \geq 0$.
Output: $\mathcal{G} \subseteq \mathcal{P}$ and $\mathcal{O} \subseteq \mathcal{T}$.

---

1   $d \leftarrow 1, \mathcal{O} = \{t_1\}_\sigma \leftarrow \{\mathbb{1}\}_\sigma, \mathcal{G} \leftarrow \emptyset$
2   **while** $\partial_d \mathcal{O} = \{u_1, \ldots, u_k\}_\sigma \neq \emptyset$ **do**
3   **for** $i = 1, \ldots, k$ **do**
4         $\ell \leftarrow |\mathcal{O}| \in \mathbb{N}, A \leftarrow \mathcal{O}(X) \in \mathbb{R}^{m \times \ell}, \mathbf{b} \leftarrow u_i(X) \in \mathbb{R}^m, P = \{\mathbf{y} \in \mathbb{R}^\ell \mid \|\mathbf{y}\|_1 \leq \tau - 1\}$
5         $\mathbf{y}_0 \leftarrow (A^\intercal A)^{-1} A^\intercal \mathbf{b} \in \mathbb{R}^\ell$
6   Solve $\mathbf{c} \in \operatorname{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ up to tolerance ϵ using `CG` with starting vector $\mathbf{y}_0$
7         $g \leftarrow \sum_{j=1}^\ell c_j t_j + u_i$ ▷ A non-sparse polynomial
8   **if** $\operatorname{MSE}(g, X) \leq \psi$ **then**   ▷ Check whether g vanishes
9   Solve $\mathbf{d} \in \operatorname{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ up to tolerance ϵ using `BPCG` and a vertex of
             P as starting vector
10            $h \leftarrow \sum_{j=1}^\ell d_j t_j + u_i$ ▷ A sparse polynomial
11   **if** $\operatorname{MSE}(h, X) \leq \psi$ **then**   ▷ Check whether h vanishes
12               $\mathcal{G} \leftarrow \mathcal{G} \cup \{h\}$
13   **else**
14               $\mathcal{G} \leftarrow \mathcal{G} \cup \{g\}$
15   **end**
16   **else**
17            $\mathcal{O} = \{t_1, \ldots, t_{\ell+1}\}_\sigma \leftarrow (\mathcal{O} \cup \{u_i\})_\sigma$
18   **end**
19   **end**
20      $d \leftarrow d + 1$
21 **end**

---

     2. If $\mathbf{b}^\intercal A (A^\intercal A)^{-1} A^\intercal \mathbf{b} = \|\mathbf{b}\|_2^2$, it holds that $f(-(A^\intercal A)^{-1} A^\intercal \mathbf{b}) = 0$. By the assumption that $\tau \geq 2$ is large enough to guarantee that (INF) never holds, `CGAVI-IHB` constructs a $(\psi, 1, \tau)$-approximately vanishing generator in Line 6.

Since an update of $(A^\intercal A)^{-1}$ is necessary only if Line 10 is executed, that is, when there does not exist a $(\psi, 1, \tau)$-approximately vanishing generator g, we never have to update $(A^\intercal A)^{-1}$ when the assumptions of Theorem B.1 are violated.

Thus, by Theorem B.1, we can always update A, $A^\intercal A$, or $(A^\intercal A)^{-1}$ in $O(\ell m + \ell^2) \leq O((|\mathcal{G}| + |\mathcal{O}|)m + (|\mathcal{G}| + |\mathcal{O}|)^2)$ elementary operations using space $O(\ell m + \ell^2) \leq O((|\mathcal{G}| + |\mathcal{O}|)m + (|\mathcal{G}| + |\mathcal{O}|)^2)$. Then, since we run `CG` for a constant number of iterations, the time and space complexities of Lines 5–11 are $T_{\text{ORACLE}} = O((|\mathcal{G}| + |\mathcal{O}|)m + (|\mathcal{G}| + |\mathcal{O}|)^2)$ and $S_{\text{ORACLE}} = O((|\mathcal{G}| + |\mathcal{O}|)m + (|\mathcal{G}| + |\mathcal{O}|)^2)$, respectively.   □

Note that the time and space complexities in Corollary 4.4 also hold for `AGDAVI-IHB` with $\tau = \infty$.

B.2   WEAK INVERSE HESSIAN BOOSTING (`WIHB`)

So far, we have introduced `IHB` to drastically speed-up training of `AGDAVI` and `CGAVI`. A drawback of using `CGAVI-IHB` is that the initialization of `CG` variants with a non-sparse initial vector such as $\mathbf{y}_0 = (A^\intercal A)^{-1} A^\intercal \mathbf{b}$ leads to the construction of generally non-sparse generators. In this section, we explain how to combine the speed-up of `IHB` with the sparsity-inducing properties of `CG` variants, referring to the resulting technique as Weak Inverse Hessian Boosting (`WIHB`). Specifically, we present `WIHB` with `BPCGAVI` (`OAVI` with solver `BPCG`), referred to as `BPCGAVI-WIHB` in Algorithm 3.

The high-level idea of `BPCGAVI-WIHB` is to use `IHB` and vanilla `CG` to quickly check whether a $(\psi, 1, \tau)$-approximately vanishing generator exists. If it does, we then use `BPCG` to try and construct a $(\psi, 1, \tau)$-approximately vanishing generator that is sparse.

We proceed by giving a detailed overview of `BPCGAVI-WIHB`. In Line 5 of `BPCGAVI-WIHB`, we construct $\mathbf{y}_0$. Then, in Line 6, we solve $\mathbf{c} \in \operatorname{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ up to tolerance ϵ using `CG` with starting vector $\mathbf{y}_0 = (A^\intercal A)^{-1} A^\intercal \mathbf{b}$. Since $\mathbf{y}_0$ is a well-educated guess for the solution to the constrained optimization problem $\operatorname{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ in Line 6, `CG` often runs for only very few iterations and the execution time of Line 6 is brief. The drawback of using the non-sparse $\mathbf{y}_0$ as a starting vector is that $\mathbf{c}$ constructed in Line 6 and g constructed in Line 7 are generally non-sparse. We alleviate the issue of non-sparsity of g in Lines 8–18. In Line 8, we first check whether g is a $(\psi, 1, \tau)$-approximately vanishing generator of X. If g does not vanish approximately, we know that there does not exist an approximately vanishing generator with leading term u_i and we append u_i to $\mathcal{O}$ in Line 17. If, however, $\operatorname{MSE}(g, X) \leq \psi$, we solve the constrained convex optimization problem in Line 6 again in Line 9. In Line 9, we solve the constrained convex optimization problem up to tolerance ϵ using `BPCG` and a vertex of the ℓ_1-ball P as starting vector. This has two consequences:

1. The vector $\mathbf{d}$ constructed in Line 9 tends to be sparse, as corroborated by the results in Table 2.

2. The execution of Line 9 tends to take longer than the execution of Line 6.

Then, in Line 10, we construct the polynomial h, which tends to be sparse. If h is a $(\psi, 1, \tau)$-approximately vanishing generator, we append the sparse h to $\mathcal{G}$ in Line 12. If it happens that $\operatorname{MSE}(g, X) \leq \psi < \operatorname{MSE}(h, X)$, we append the non-sparse g to $\mathcal{G}$ in Line 14. Following the discussion of Section 4.3, should (INF) ever hold, that is, $\|\mathbf{y}_0\|_1 > \tau - 1$, we can no longer proceed with `BPCGAVI-WIHB` as we can no longer guarantee that the inverse of $A^\intercal A$ exists. In that case, we proceed with vanilla `BPCGAVI` for all terms remaining in the current and upcoming borders.

The discussion above illustrates that `BPCGAVI-WIHB` solves $\operatorname{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ with `BPCG` $|\mathcal{G}|$ times as opposed to `BPCGAVI`, which solves $\operatorname{argmin}_{\mathbf{y} \in P} \frac{1}{m} \|A\mathbf{y} + \mathbf{b}\|_2^2$ with `BPCG` $|\mathcal{G}| + |\mathcal{O}| - 1$ times. Thus, `BPCGAVI-WIHB` combines the sparsity-inducing properties of `BPCG` with the speed-up of `IHB` without any drawbacks. The speed-up of `BPCGAVI-WIHB` compared to `BPCGAVI` is evident from the numerical experiments in Figure 2 and the results of Table 2 indicate that the sparsity-inducing properties of `BPCG` are successfully exploited.

C MISSING PROOFS

Proof of Theorem 4.2. Let $X = \{\mathbf{x}_1, \ldots, \mathbf{x}_m\} \subseteq [0, 1]^n$ and let $t_1, \ldots, t_n \in \mathcal{T}_1$ be the degree-1 monomials. Suppose that during `OAVI`'s execution, for some degree $d \in \mathbb{N}$, `OAVI` checks whether the term $u = \prod_{j=1}^n t_j^{\alpha_j} \in \partial_d \mathcal{O}$, where $\sum_{j=1}^n \alpha_j = d$ and $\alpha_j \in \mathbb{N}$ for all $j \in \{1, \ldots, n\}$, is the leading term of a $(\psi, 1, \tau)$-approximately vanishing generator with non-leading terms only in $\mathcal{O}$. Let

$$h = \prod_{j=1}^n \left(t_j - \frac{1}{2}\mathbb{1}\right)^{\alpha_j}, \tag{C.1}$$

where $\mathbb{1}$ denotes the constant-1 monomial, that is, $\mathbb{1}(\mathbf{x}) = 1$ for all $\mathbf{x} \in \mathbb{R}^n$. Note that $\|h\|_1 \leq \left(\frac{3}{2}\right)^d \leq \tau$, guaranteeing that h can be constructed in Lines 5–6 of `OAVI`. Since $u \in \partial_d \mathcal{O}$, for any term $t \in \mathcal{T}$ such that $t \mid u$ and $t \neq u$, it holds that $t \in \mathcal{O}$, and, thus, h is a polynomial with $\operatorname{LTC}(h) = 1$, $\operatorname{LT}(h) = u$, and other terms only in $\mathcal{O}$. Under the assumption that the convex optimization oracle in `OAVI` is accurate, $\operatorname{MSE}(h, X) \geq \operatorname{MSE}(g, X)$, where g is the polynomial constructed during Lines 5 and 6 of `OAVI`. Hence, proving that h vanishes approximately implies that g vanishes approximately. Note that for all $\mathbf{x} \in X$ and $t \in \mathcal{T}_1$, it holds that $t(\mathbf{x}) \in [0, 1]$, and,

thus, $\left| t(\mathbf{x}) - \frac{1}{2} \right| \leq \frac{1}{2}$. We obtain

$$
\begin{aligned}
\mathrm{MSE}(g, X) &\leq \mathrm{MSE}(h, X) \\
&= \frac{1}{m} \|h\|_2^2 \\
&= \frac{1}{m} \sum_{\mathbf{x} \in X} \left(\prod_{j=1}^n \left(t_j(\mathbf{x}) - \frac{1}{2}\mathbb{1}(\mathbf{x}) \right)^{\alpha_j} \right)^2 \\
&\leq \max_{\mathbf{x} \in X} \prod_{j=1}^n \left| t_j(\mathbf{x}) - \frac{1}{2} \right|^{2\alpha_j} \\
&\leq 4^{-d}.
\end{aligned}
$$

Since $\mathrm{MSE}(g, X) \leq 4^{-d} \leq \psi$ is satisfied for $d \geq D := \left\lceil -\frac{\log(\psi)}{\log(4)} \right\rceil$, OAVI terminates after reaching degree D. Thus, at the end of OAVI's execution, $|\mathcal{G}| + |\mathcal{O}| \leq \binom{D+n}{D} \leq (D+n)^D$. $\qquad \square$

D PYRAMIDAL WIDTH OF THE ℓ_1-BALL

Pena & Rodriguez (2019) showed that the pyramidal width ω of the ℓ_1-ball of radius τ, that is, $P = \{\mathbf{x} \in \mathbb{R}^\ell \mid \|\mathbf{x}\|_1 \leq \tau\} \subseteq \mathbb{R}^\ell$ is given by

$$
\omega = \min_{F \in \mathrm{faces}\,(P), \emptyset \subsetneq F \subsetneq P} \mathrm{dist}\,(F, \mathrm{conv}(P \setminus F)),
$$

where, for a polytope $P \subseteq \mathbb{R}^\ell$, faces (P) denotes the set of faces of P, for a set $F \subseteq \mathbb{R}^\ell$, $\mathrm{conv}(F)$ is the convex hull of F, and for two disjoint sets $F, G \subseteq \mathbb{R}^\ell$, $\mathrm{dist}\,(F, G)$ is the Euclidean distance between F and G.

Lemma D.1 (Pyramidal width of the ℓ_1-ball). *The pyramidal width of the ℓ_1-ball of radius τ, that is, $P = \{\mathbf{x} \in \mathbb{R}^\ell \mid \|\mathbf{x}\|_1 \leq \tau\} \subseteq \mathbb{R}^\ell$, is lower bounded by $\omega \geq \frac{\tau}{\sqrt{\ell}}$.*

Proof. Let $\mathbf{e}^{(i)} \in \mathbb{R}^\ell$ denote the i-th unit vector. Note that a face of $P = \mathrm{conv}\{\pm\tau\mathbf{e}^{(1)}, \ldots, \pm\tau\mathbf{e}^{(n)}\} \subseteq \mathbb{R}^\ell$ cannot contain both $\tau\mathbf{e}^{(i)}$ and $-\tau\mathbf{e}^{(i)}$ for any $i \in \{1, \ldots, \ell\}$. Thus, due to symmetry, we can assume that any non-trivial face of P that is not P itself is of the form $F = \mathrm{conv}(\{\tau\mathbf{e}^{(1)}, \ldots, \tau\mathbf{e}^{(k)}\})$ for some $k \in \{1, \ldots, \ell - 1\}$. Then,

$$
G := \mathrm{conv}(P \setminus F) = \mathrm{conv}(\{-\tau\mathbf{e}^{(1)}, \ldots, -\tau\mathbf{e}^{(k)}, \pm\tau\mathbf{e}^{(k+1)}, \ldots, \pm\tau\mathbf{e}^{(\ell)}\})
$$

and, using $v_j^2 \geq 0$ for all $j \in \{k+1, \ldots, \ell\}$ and $v_i \leq 0 \leq u_i$ for all $i \in \{1, \ldots, k\}$, we have that

$$
\begin{aligned}
\mathrm{dist}\,(F, G) &= \min_{\mathbf{u} \in F, \mathbf{v} \in G} \|u - v\|_2 \\
&= \min_{\mathbf{u} \in F, \mathbf{v} \in G} \sqrt{\sum_{i=1}^k (u_i - v_i)^2 + \sum_{j=k+1}^\ell v_j^2} \\
&\geq \min_{\mathbf{u} \in F, \mathbf{v} \in G} \sqrt{\sum_{i=1}^k (u_i - v_i)^2} \\
&\geq \min_{\mathbf{u} \in F} \sqrt{\sum_{i=1}^k u_i^2} \\
&= \sqrt{\frac{\tau^2}{k}}.
\end{aligned}
$$

Since $\sqrt{\frac{\tau^2}{k}}$ is minimized for k as large as possible, it follows that $\omega \geq \frac{\tau}{\sqrt{\ell-1}} \geq \frac{\tau}{\sqrt{\ell}}$. $\qquad \square$

Table 3: Hyperparameter ranges for numerical experiments.

Hyperparameters	Values
ψ	0.1, 0.05, 0.01, 0.005, 0.001, 0.0005, 0.0001
Regularization coefficient for `SVMs`	0.1, 1, 10
Degree for polynomial kernel `SVM`	1, 2, 3, 4

E THE SYNTHETIC DATASET

The synthetic dataset consists of three features and contains two different classes. The samples $\mathbf{x}$ that belong to the first class are generated such that they satisfy the equation

$$x_1^2 + 0.01x_2 + x_3^2 - 1 = 0$$

and samples that belong to the second class are generated such that they satisfy the equation

$$x_1^2 + x_3^2 - 1.3 = 0.$$

The samples are perturbed by additive Gaussian noise with mean 0 and standard deviation 0.05.

F ADDITIONAL NUMERICAL EXPERIMENTS

In this section, we provide details for the numerical experiments conducted in Figures 1, 2, and 3.

F.1 EXPERIMENT: SPEEDING UP `CGAVI`

We compare the training times of `PCGAVI`, `BPCGAVI`, `BPCGAVI-WIHB`, and `CGAVI-IHB` on the datasets bank, htru, skin, and synthetic.

Setup. For a single run, we randomly split the dataset into subsets of varying sizes. Then, for fixed $\psi = 0.005$, we run the generator-constructing algorithms on subsets of the full dataset of varying sizes and plot the training times, which are the times required to run `PCGAVI`, `BPCGAVI`, `BPCGAVI-WIHB`, and `CGAVI-IHB` once for each class. The results are averaged over ten random runs and standard deviations are shaded in Figures 1 and 2.

Results. The results are presented in Figures 1 and 2. In Figure 1, we observe that the training times for `BPCGAVI` are often shorter than for `PCGAVI`, except for the skin dataset. In Figure 2, we observe that `IHB` not only leads to theoretically better training times but also speeds up training in practice: `CGAVI-IHB` is always faster than `BPCGAVI`. Furthermore, `WIHB` is indeed the best of both worlds: `BPCGAVI-WIHB` is always faster than `BPCGAVI` but preserves the sparsity-inducing properties of `BPCG`. The latter can also be seen in Table 2, where `BPCGAVI-WIHB`* is the only algorithmic approach that constructs sparse generators.

F.2 EXPERIMENT: SCALABILITY COMPARISON

We compare the training times of `CGAVI-IHB`, `AGD-IHB`, `ABM`, and `VCA` on the datasets bank, htru, skin, and synthetic.

Setup. For a single run, on at most 10,000 samples of the dataset, we tune the hyperparameters of generator-constructing algorithms `OAVI`, `ABM`, and `VCA` and a subsequently applied linear kernel `SVM` using threefold cross-validation. Then, using the determined hyperparameters, we run only the generator-constructing algorithms on subsets of the full dataset of varying sizes and plot the training times, which are the times required to run `CGAVI-IHB`, `AGD-IHB`, `ABM`, and `VCA` once for each class. The results are averaged over ten random runs and standard deviations are shaded in Figure 3.

Results. The results are presented in Figure 3. For small datasets, we observe that `ABM` and `VCA` are faster than `OAVI`. However, when the number of samples in the dataset is large, as in the synthetic dataset, `OAVI` can be trained faster than `ABM` and `VCA`. `AGDAVI-IHB` is slower than `CGAVI-IHB` because `AGD` cannot use the Frank-Wolfe gap as an early termination criterion to quickly decide that a solution close enough to the optimum is reached.