A stricter constraint produces outstanding matching: Learning reliable image matching with improved networks

Anonymous Authors *

Author's Affiliation

ABSTRACT

Image matching is widely used in many applications, such as visual-based localization and 3D construction. Comparing with Traditional local features (e.g., SIFT) and outlier elimination method (e.g, RANSAC), learning-based image matching methods, e.g., HardNet and OANet, show promising performance under challenging environments and large-scale benchmarks. However, the existing learning-based methods suffer the noise in training data and the existing loss function, e.g., hinge loss, does not work well in image matching network. In this paper, we propose an end-to-end image matching method with less training dataset to obtain a more accurate and robust performance. First, a novel data cleaning strategy is proposed to remove the noise in the training dataset. Second, we strengthen the matching constraints by proposing a novel quadratic hinge triplet (QHT) loss function to improve the network. Finally, we apply stricter OANet in sample judgement to produce more outstanding matching. The proposed method shows the state-of-the-art performance on a large-scale and challenging Phototourism dataset, and also reported the 1st place in the CVPR 2020 Image Matching Challenges Workshop Track1 with the metric measure of reconstructed pose accuracy.
Keywords: Image matching, HardNet, OANet, SIFT, large scale, challenging environments, pose accuracy.

Keywords: Image matching, HardNet, OANet, SIFT, large scale, challenging environments, pose accuracy.

1 INTRODUCTION

Image matching is the foundation task of some high-level 3D computer vision tasks, such as 3D reconstruction, structure-from-motion, camera pose estimation, etc. The goal of the task is to solve the corresponding pixels relationship within a same physical region from two images which have a common vision area [1]. Nowadays, with the widespread development of deep learning technologies on many computer vision areas and the need for long-term large-scale environments tasks, the shortcomings of traditional keypoint-based image matching method gradually appear, the major difficulty lies in that usually local features are evaluated through the accuracy of descriptors on small datasets, which only illustrates the matching performance, and is not suitable for integrating and evaluating some downstream tasks.

The use of deep learning based solution for image matching task is hopeful to outperform the disadvantages of traditional keypoint-based methods, which demonstrated the ability to integrate multi-stage tasks in a lot of works [2][3] and could

Figure 1: Our matching method's correspondences in extreme illumination variation and viewpoint changes.

optimize and evaluate different evaluation metrics in large dataset. Although without complex hand-crafted efforts and show convenient pipeline in further tasks, the methods face with challenging conditions, such as illumination variation, viewpoint changes, repeated texture, which is apparent in outdoor datasets where scenes scales and conditions are highly variable. This leads to the poor performance result both in accuracy and robustness.

To solve this problem, further end-to-end solutions and modified descriptors have been proposed with the premise being that the descriptor or network could learn more reliable features across image pairs. A novel representation of features with log-polar sampling method [4] is proposed to achieve scale invariance. Some works [2-3] propose a jointly learning feature detection and description method separately to improve the image matching performance.

Inspired by the mentioned knowledge, in this work, we propose a three-stage pipeline, including feature extraction, feature matching and outlier pre-filtering steps, to compute the corresponding pixels from image pairs, as shown in Figure 1. For each step, we add some constraints to enforce the algorithm converge to better matching results. Unlike the previous methods, our proposed method only requires light-weight model and does not need to train on multi-branches separately.

We show that our method outperforms previous algorithms and achieves the state-of-the-art performance using the Phototourism benchmark with large-scale environments and challenging conditions. We provide a detailed insight into how improved data processing strategy, HardNet [8] loss function, modified OANet [9] combined with guided match algorithm [10] could help the

---

Figure 2: Image matching based pose estimation pipeline, with some popular traditional and learning-based methods. Our method is based on the pipeline with some improvement on the chosen methods (indicated by a green box with a red tick).

pipeline to achieve accurate and robust matching results and evaluate the method on pose estimation task.

The main contributions include:
- We construct a new patch dataset based on the given Phototourism images and sparse model, which is similar to the UBC Phtotour dataset [11], and pre-train our model on that dataset;
- We propose a novel quadratic hinge triplet (QHT) loss function for the feature descriptor network HardNet, and an improved OANet combined with a guided matching strategy to compute reliable feature matches;
- Through abundant experiments and the ablation study for each module, we show that our algorithm achieves state-of-the-art performance in the reconstructed poses, which ranks first on both tracks of stereo and multi-view matching on the public Phototourism Image Matching challenge 2020 [7].

2 RELATED WORK

Image matching plays an important role in many high-level tasks in computer vision area [14-15], which is to find the corresponding pixels from the image pairs in the same physical region in which the scene imaged with geometrical constraints [1]. Feature extraction, feature matching and outlier pre-filtering are the most vital components in image matching pipeline, in which traditional methods and deep learning based methods are implemented and completed in recent years. Figure 2 shows the main parts of image matching based pose estimation pipeline, including some common methods and our chosen target algorithm to further improve.

Feature Extraction. End-to-end feature extraction and matching methods are classified into detect-then-describe (e.g. SuperPoint [16]), detect-and-describe (e.g. R2D2 [3], D2-Net [2]), and describe-then-detect (e.g. DELF [19]) strategies according to the sequences for executing the detection and description processes, which are utilized in different needs. However, they either have poor performance on challenging conditions and lack of repeatability on keypoints or show low efficiency on matching and storage. Traditionally, detectors and descriptors are separately applied in the pipeline, SIFT [5] (and RootSIFT [26]) and SURF [21] are most popular detectors while some descriptors are followed, in which LogPolar [4] shows better performance than ContextDesc [24] from the relative pose error, while SOSNet [25] and HardNet [8] overpass GIFT [23] in the public validation set.

Outlier pre-filtering. There are a large number of incorrect matches in the matching pair, which will bring noise to the subsequent pose estimation. Traditional outlier removal methods include ratio-test [5], GMS [6], guided-match [10] methods, etc.

A method based on deep learning is to judge whether the match is an outlier through the pose relationship obtained by the regression of the convolutional network, but it is usually difficult for network training to converge. Another way is to convert the pose to the label of whether the match is correct through the epipolar constraint, and then the regression problem can be converted into a classification problem to determine whether the match is inlier or outlier. The standard binary cross-entropy loss can be used to learn model.

However, the input matching pairs are unordered, so the network needs to be permutation-invariant (insensitive) to match sequence transformations, so it is not applicable to convolutional networks or fully connected networks. CNe [12] draws on the idea of pointNet [13] and proposes a multi-layer weight-sharing perceptron to solve the irrelevant transformation problem. For each input matching pair, the same perceptron is used to process iterations, but this also leads that each matching pair is processed independently, lacks information circulation, and cannot integrate the predicted matching pair judgment results, and thus cannot learn the useful information in the entire image matching pair. Context normalization [17] is an instance normalization method that is often used widely in image migration [29] and GAN [27]. It normalizes the processing results of image matching pairs to exchange and circulate information. But this simple and violent use of mean variance ignores the complexity of global features, and at the same time cannot capture the correlation information between parts. OANet [9] proposed the use of DiffPool and DiffUnPool layers to promote the information flow and communication of internal neurons.

To estimate a more accurate pose of the given image pairs or 3D reconstruction through the matching process, we consider improving the pipeline with respect to the following aspects:
- Obtain stable and accurate keypoints. The keypoints should appear invariably, e.g., a certain point in the first image could also appear stably in the second image taken under a different viewpoint or illumination change.
- Provide reliable and distinguishable descriptors. Under different environmental conditions, the same keypoint should have similar descriptor, so that the same keypoint in different images can be paired using nearest neighbor matching.
- Hold powerful outlier pre-filtering ability. Filtering the wrong matches to get most of the correct matching pairs could help to get an accurate pose estimation result finally.

3 METHOD

In this paper, we aim to learn accurate and reliable image matching in large-scale challenging conditions. In contrast with previous works which use end-to-end solutions of insufficient accuracy at the feature extraction stage or traditional solvers through the image matching pipeline, we combined traditional detector solver with an improved HardNet and OANet to pretrain on a constructed dataset. In particular, we propose a dataset

Figure 3: The whole architecture with proposed methods. We use SIFT feature detector firstly, and then apply HardNet from the 32×32 patch input into the 128 dimensions descriptors, after the nearest neighbor match and outlier pre-filtering, we could get the final matches, which is further used to compute the pose estimation.

construction method to optimize hypermeters before training on large-scale dataset and propose a new loss function in the description stage based on HardNet network, during outlier pre-filtering stage, we combined guided match with proposed stricter OANet to learn more accurate matches.

The whole architecture of the proposed method is demonstrated in Figure 3. Firstly, 128 dimensions of features are extracted from a basic HardNet with the input 32×32 patch. Then, after the matching stage, with the proposed stricter OANet, the correspondences could be transferred into N binary classification (inlier / outlier), which is permutation-invariant and feasible with convolutional layers. Finally, the pre-filtered matches are used to compute pose estimation in stereo and multi-view tasks.

3.1 Dataset Construction

3.1.1 UBC Dataset Construction for Pretraining

In order to quickly train our lightweight method and search for some hyperparameters to further use into the pretrained model, thus we use the UBC Phototour dataset for the pretraining, which is patch data and suitable for HardNet training.

3.1.2 Phototourism Dataset Construction for Training

After pretraining on the constructed UBC Phototour dataset for fast parameter selection, for the training period, we construct a clean dataset with low noise and less redundancy from Phototourism training scenes. Removing the redundant data could largely shorten the training period, while noise label reducing could help the loss function gradient descent optimization to improve network performance.

To reduce the noise label in the dataset, we set the threshold of discard the images with low confidence, in which 25% with the least 3d points and 3d points whose tracks are less than 5. For the redundant data removing, we sample the 3d points that have been tracked more than 5 times, and only keep the 3d points which are tracked 5 times. The sampling is repeated 10 times, and the NCC value is calculated for each sampling (the lower of the NCC indicates the lower similarity of the two images and the larger difference of the matching), and the result with the lowest NCC is retained. In addition, we also applied data augmentation with random flip and random rotation strategies in both pretraining and training processes.

3.2 Feature Extraction with Improved HardNet

Feature extraction includes keypoint detection and feature description processes. SIFT detector [5] is used firstly to extract the position and scale information on the selected keypoint of the given input image. We adopted OpenCV implemented SIFT with a low detection threshold to generate up to 8000 points and a fixed orientation [1] . A single pixel on the image cannot describe the physical information of the current key point, so in order to describe the key point and the information around it, the key point is cropped with its scale size, called a patch, and then resized to 32×32 as the input of the HardNet network to extract the patch's descriptor.

After a relatively simple 7-layer HardNet, the input 32×32 patch is described as a 128-dimensional feature vector, which represents the description generated for each patch. We remain the network structure, and made improvements to its loss function to train the network stably and efficiently on the constructed dataset.

HardNet uses triplet loss embedded with difficult sample mining to optimize so that the distance of the sample descriptor within the class is small, and the distance of the sample description vector between the classes is large.

In order to further improve the effectiveness and stability of model learning, we apply a quadratic hinge triplet (QHT) loss based on the triplet loss, which is inspired from the first order similarity loss in SOSNet [25], by adding the square term of the triple, which shares the same mining strategy as in HardNet to find the "hardest-within-batch" negatives. The description loss function $\mathcal{L}_{des}$ is expressed as:

$$\mathcal{L}_{des} = \frac{1}{N}\sum_{i=1}^{N}\max\left(0, 1 + d_i^{pos} - d_i^{neg}\right)^2 \qquad (1)$$

$$d_i^{pos} = d(a_i, pos_i) \qquad (2)$$

$$d_i^{neg} = \min_{\forall j \neq i}(d(a_i, neg_j)) \qquad (3)$$

Where d_i^{pos} represents the L2 distance between anchor descriptor and positive descriptor, d_i^{neg} represents the minimum distance in all the distances between anchor descriptor and the negative descriptor. The positive sample represents the patch on different images corresponding to the same 3d point with the given anchor in the real world, on the contrary, the negative sample represents the patch obtained from different 3d points.

Quadratic triplet loss weights the gradients with respect to the parameters of the network by the magnitude of the loss. Compared with HardNet, the gradient of QHT loss is more sensitive to changes in loss. Larger $d_i^{pos} - d_i^{neg}$ results in smaller loss gradient, thus the model learning is more effective and stable.

In addition, the improved model would be sensitive to the noise in the data. Wrong positive and negative sample labels will degrade the performance of the model, this risk could be avoided through the data denoising work proposed before.

---

[1] https://github.com/vcg-uvic/image-matching-benchmark-baselines

3.3 Stricter OANet with Dynamic Guided Matching

OANet proposed to use Diffpool and DiffUnPool layers on the basis of CNe to promote the information circulation and communication of internal neurons. The two network's models can be abstracted as Figure 4, N matching pairs with D-dimensional are processed by the perceptron of the CNe network to obtain output results of the same dimension. The OANet network reduces the input dimension to an M×D matrix through the Diffpool layer, and then raises the dimension back to N×D output through DiffUnpool, and merges the information in the middle. Diffpool maps the input N matches to M by learning the weights of soft distribution to aggregate the information, and then DiffUnpool reorganizes the information back to N dimensions. The network is not sensitive to disordered disturbances of input matching pairs.

Figure 4: Our matching method's correspondences in extreme illumination variation and viewpoint changes.

We convert the accuracy of the pose to the accuracy of the matching to learn, so the accuracy of the matching will affect the learning ability of the model. We have made the following improvements to OANet to make it more rigorous to learn from positive samples, and to make matching judgments the label be more accurate, which effectively filters the exception points and improves the matching and pose estimation performance. We shortened the threshold condition of the geometric error constraint from 1e-4 to 1e-6. In addition, we also added a point-to-point constraint based on the OANet point-to-line constraint. A point is judged as a negative sample when the projection distance is greater than 10 pixels.

Generally, inadequate matches may lead to inaccurate pose estimation. Apart from OANet, for the image pairs with less than 100 matches, we also proposed dynamic guided matching (DGM) to increase matches. Different from traditional guided matching [10], the dynamic threshold is applied on the Sampson distance constraint according to the number of matches of an image pair. We argue that a smaller number of matches requires greater threshold. The dynamic threshold th is set by the formula as:

$$th = th_{init} - \frac{n}{15} \qquad (4)$$

where th_{init} is 6 and n is the number of original matches of an image pair. For the image pairs with more than 100 matches, we directly applied DEGENSAC [21] to obtain the inliers for submission.

3.4 Implementation Details

We train the proposed model integrated with improved SIFT, HardNet, OANet on Phototourism dataset [7], in which HardNet is pretrained on the constructed UBC Patch dataset [11]. The whole model is implemented with Pytorch [18] on a NVIDIA Titan X GPU. All models were trained from scratch and no pre-trained models were used. For stereo task, the co-visibility threshold is restricted to 0.1 while for multi-view task, the minimum 3D points to set to 100 with no more than 25 images are evaluated at a time.

In description stage, the input patch size is cropped to 32 × 32 with the random flip and random rotation. Optimization was done

by SGD solver [28] with learning rate of 10 and weight decay of 0.0001. Learning rate was linearly decayed to zero within 15 epochs.

In outlier pre-filtering stage, for training, we employed dynamic learning rate schedule where the learning rate was increased from zero to maximum linearly during the warm-up period (the first 10,000 steps), and decayed step-by-step after that. Typically, the maximum learning rate was 1e−5, and the decay rate was 1e−8. Besides, we trained the fundamental estimation model with setting the value of parameter *geo_loss_margin* to 0.1. The side information of ratio test [5] with threshold of 0.8 and mutual check was also added into the model input. In inference time, the output of the model will undergo a DEGENSAC to further eliminate unreliable matches. The DEGENSAC in dynamic guided match all shares the same configuration with the iteration number of 100000, error type of Sampson, inlier threshold of 0.5, confidence of 0.999999 and enabled degeneracy check.

4 EXPERIMENTS

In this section, we evaluate the proposed method on the public Phototourism benchmark with the features results, the final pose estimation results are computed online. We firstly conduct performance for several separate modules, then qualitatively and quantitively analysis the effectiveness of our method.

4.1 Experimental Settings

4.1.1 Datasets

UBC Phototour dataset [11] is a dataset which involves corresponding patches from 3D reconstruction of Liberty, Notre Dame and Yosemite. Every tour consists of several bitmap images at the resolution of 1024 × 1024 pixels, each image contains image patches as a 16 × 16 array, in which the patch is sampled as 64 × 64 grayscale. In addition, the matching information (sample 3D point index of each patch) and keypoint information (reference image index, orientation, scale, and position are supplied separately in the file.

Phototourism dataset [7] was collected from multi-sensors in 26 popular tourism landmarks. The 3D reconstruction ground truth is obtained with Structure from Motion (SfM) using Colmap, which includes poses, co-visibility estimates and depth maps. The dataset is divided into training set (16 scenes), validation set (3 scenes of training set) and test set (10 scenes). As a benchmark large-scale dataset, the scenes contained in the dataset includes various challenging conditions, e.g., occlusions, changing viewpoints, different time, repeated textures, etc.

4.1.2 Tasks and Evaluation metrics

We implement and compare our method with different **approaches** on two downstream tasks: stereo and multi-view reconstruction with SfM, they both evaluate the intermediate metrics for further comparisons. The two tasks evaluate different format of dataset which is subsampled into smaller random subsets from the Phototourism dataset, Stereo task evaluates image pairs while Multi-view task evaluates 5~25 images with SfM reconstruction. Stereo task uses the random sampling consensus method (RANSAC) [20] to estimate the matches between the two images that meets the motion consistency, thereby decomposing the pose rotation R and translation t. Multi-view task recovers the pose R and t of each image through 3D reconstruction. By calculating the cosine distance of the vector between the estimated pose and the ground-truth pose, the performance of image matching is measured by the size of the computed angle.

Given an image pair with co-visibility constraints in stereo task or the 3D reconstruction from multi-view images, we may compute the following metrics in different experiments, the final results are compared with the mAA metric.

- Mean average accuracy (%mAA) is computed by integrating the area under curve up to a maximum threshold, which indicate the angular angle between the ground-truth and estimated pose vector.
- Keypoint repeatability (%Rep.) measures the ratio of possible matches and the minimum number of key points in the co-visible view.
- Descriptor matching score(%M.S.) is the average ratio of correct matches and the minimum number of key points in the co-visible view.
- Mean absolute trajectory error (%mATE) measures the average deviation from ground truth trajectory per frame.
- False positive rate (%FPT) is the ratio between the number of negative events wrongly categorized as positive and the total number of actual negative events

4.2 Qualitative and Quantative Results

The data construction information on the Phototourism dataset is given in Table 1, it could be seen that the proposed dataset construction method could largely reduce the amount of dataset size thus further speed up the training process and help improve the model performance. The training loss and FRP95 metric trend is shown in Figure 5 and Figure 6 on UBC Phototour dataset, which indicates the loss stability and help us know about the data characteristics. The comparison of matching visualization performance on stereo task is shown in Figure 7, in which we could see our proposed method outperforms the traditional RootSIFT based method with more accurate matches. Figure 8 shows the visualization on Phototourism dataset on stereo task and multi-view task.

To validate the performance of loss of different scenes, Table 2 lists the evaluation of correspondence on UBC Phototour dataset, which indicates the effects and improvements of our proposed QHT loss compared to HT (hinge triplet) loss. Table 3 demonstrates our submitted final results on Phototourism challenge Track1, we rank 1st on both tasks.

Table 1: Dataset construction information comparison of two selected scenes and the average of Phototourism dataset

Scenes	Type	Images	3D Points	Patches
Buckingham _palace	original	1676	246035	4352977
	sampled	1257	72814	364070
Grand_place _Brussels	original	1080	209550	3206171
	sampled	810	78108	390540
All scenes (Average)	original	1183.9	165124.8	3567694.5
	sampled	887.6	63433.6	317168

Table 2: Patch correspondence evaluation performance with the metric of FPR95. We compare different loss functions on UBC Phototour dataset with HardNet as the description network (* means the network is trained by our implement). The best results are in **bold**.

Train	Liberty		NotreDame	
Test	Notre-Dame	Youse-mite	Liberty	Youse-mite
HartNet [8]	0.62	2.14	1.47	2.67
HardNet-HT [8]	0.53	1.96	1.49	1.84
HardNet-HT*	0.50	1.96	1.48	1.61
HardNet-QHT*	**0.45**	**1.83**	**1.228**	**1.52**

Figure 5: The loss of the training model in different scenes of the UBC Phototour dataset, the difference between different losses is not big, indicating that the improved loss is stable on the model training

Figure 6: FRP95 metric trend, using different scene combinations in the UBC phototour dataset as the training set and the validation set. The results show that on the same validation set, the FRP95 trained on the Yosemite scene is higher, indicating that there are false matches or difficult matches.

(a) RootSIFT method   (b) our proposed method

Figure 7: Visualization of correspondence on stereo task based on traditional RootSIFT based method and our proposed method (green represents correct match, yellow encodes match error within 5 pixels, red shows the wrong match)

Table 3: Phototourism challenge. Mean average accuracy in pose estimation with an error threshold of 10°. The results are submitted with online evaluation. (We only remain the result with the highest rank in the submitted results from each team)

Method	stereo-task		multi-view task		avg.
	mAA$^{@10°}$	rank†	mAA$^{@10°}$	rank†	rank†
Ours	0.61081	1	0.78288	2	1
Luca et al.	0.58300	12	0.77056	3	2
Jiahui et al.	0.57826	17	0.77056	5	3
Ximin et al.	0.5887	5	0.75127	14	4

4.3 Ablation Study

To fully understand each module in our proposed method, we evaluate different module above the Phototourism validation dataset. In Table 4, our method is compared with several versions to see how data construction and improved HardNet could help to improve the descriptor and further to enhance the performance on both multi-view and stereo tasks. We evaluate four variants as the feature descriptor while the other parts keep the same with results: 1) RootSIFT; 2) the original pret rained HardNet; 3) our proposed improved HardNet; 4) our proposed improved HardNet with a data construction technology. The comparison of different feature descriptors indicates that the model performance increases largely by adding the loss constraints on HardNet: it shows an 8% improvement in average mAA of both tasks; with data construction, improved HardNet yields the best performance, obtaining an average mAA of 0.7894.

Table 4: Ablation study of proposed HardNet and data construction method on Phototourism validation set

Method	mAA@10°		
	Stereo	Multi-view	Avg
RootSIFT	0.6698	0.7258	0.6978
Pretrained HardNet	0.7317	0.7924	0.7621
Improved HardNet	0.7285	0.8159	0.7722
Improved HardNet+CleanData	0.7537	0.8252	0.7894

To evaluate whether the proposed modified OANet could help improve the performance of outlier pre-filtering, Table 5 lists the performance comparison of four different outlier pre-filtering methods: 1) use of RootSIFT as feature descriptor while ratio test and cross check as the outlier filtering; 2) use of pretrained HardNet with ratio test and cross check; 3) use of proposed improved HardNet with ratio test and cross check; 4) use of proposed improved HardNet with modified OANet. The comparison of different outlier removals indicates that the performance of modified OANet overpasses the ratio test with cross check method by 4% in average mAA.

Table 5: Table 6: Ablation study of proposed OANet method on Phototourism validation set.

Method	mAA@10°		
	Stereo	Multi-view	Avg
RootSIFT+RT+CC	0.6698	0.7258	0.6978
Pretrained HardNet+RT+CC	0.7317	0.7924	0.7621
Improved HardNet+RT+CC	0.7537	0.8252	0.7894
Improved HardNet+OANet	0.7918	0.8658	0.8288

5 CONCLUSION

This paper presents a novel image matching approach, which integrates a data construction method to remove noise and to ensure more efficient training, an improved HardNet QHT loss function to make the network more sensitive to noise gradient descent, and stricter OANet combined with guided match algorithm to reduce the recall rate of outlier pre-filtering. By proposing QHT loss, which strengthened the distance constraints and the improved OANet with a stricter judgment on positive samples, the more outstanding matching is produced by these stricter constraints. The proposed method is crucial to obtain high-quality correspondences on a large-scale challenging dataset with illumination vibrances, viewpoint changes and repeated textures. Our experiments show that this method achieves state-of-the-art performance on the public Phototourism Image Matching challenge.

Figure 8: Visualization of correspondence on stereo task and reconstruction points in multi-view task. (green represents correct match, yellow encodes match error within 5 pixels, red shows the wrong match, blue shows the keypoints with correct 3D points)

REFERENCES

[1] X. L Dai, Lu J. An object-based approach to automated image matching[C]//IEEE 1999 International Geoscience and Remote Sensing Symposium. IGARSS'99 (Cat. No. 99CH36293). IEEE, 1999, 2: 1189-1191.

[2] M. Dusmanu, I. Rocco, T. Pajdla, et al. D2-net: A trainable cnn for joint description and detection of local features[C]//Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2019: 8092-8101.

[3] J. Revaud, P. Weinzaepfel, C. De Souza, et al. R2D2: repeatable and reliable detector and descriptor[J]. arXiv preprint arXiv:1906.06195, 2019.

[4] P. Ebel, A. Mishchuk, M. Yi K, et al. Beyond cartesian representations for local descriptors[C]//Proceedings of the IEEE/CVF International Conference on Computer Vision. 2019: 253-262.

[5] G. Lowe D. Distinctive image features from scale-invariant keypoints[J]. International journal of computer vision, 2004, 60(2): 91-110.

[6] W. Bian J, Y. Lin W, Y. Matsushita, et al. Gms: Grid-based motion statistics for fast, ultra-robust feature correspondence[C]//Proceedings of the IEEE conference on computer vision and pattern recognition. 2017: 4181-4190.

[7] Phototourism Challenge, CVPR 2020 Image Matching Workshop. https://www.cs.ubc.ca/research/image-matching-challenge/.

[8] A. Mishchuk, D. Mishkin, F. Radenovic, et al. Working hard to know your neighbor's margins: Local descriptor learning loss[J]. arXiv preprint arXiv:1705.10872, 2017.

[9] J. Zhang, D. Sun, Z. Luo, et al. Learning two-view correspondences and geometry using order-aware network[C]//Proceedings of the IEEE/CVF International Conference on Computer Vision. 2019: 5845-5854.

[10] M. Andrew A. Multiple view geometry in computer vision[J]. Kybernetes, 2001.

[11] M. Brown, G. Lowe D. Automatic panoramic image stitching using invariant features[J]. International journal of computer vision, 2007, 74(1): 59-73.

[12] M. Yi K, E. Trulls, Y. Ono, et al. Learning to find good correspondences[C]//Proceedings of the IEEE conference on computer vision and pattern recognition. 2018: 2666-2674.

[13] R. Qi C, H. Su, K. Mo, et al. Pointnet: Deep learning on point sets for 3d classification and segmentation[C]//Proceedings of the IEEE conference on computer vision and pattern recognition. 2017: 652-660.

[14] H. Mughal M, J. Khokhar M, M. Shahzad. Assisting UAV Localization Via Deep Contextual Image Matching[J]. IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing, 2021, 14: 2445-2457.

[15] T. Song, B. Cao L, F. Zhao M, et al. Image tracking and matching algorithm of semi-dense optical flow method[J]. International Journal of Wireless and Mobile Computing, 2021, 20(1): 93-98.

[16] D. DeTone, T. Malisiewicz, A. Rabinovich. Superpoint: Self-supervised interest point detection and description[C]//Proceedings of the IEEE conference on computer vision and pattern recognition workshops. 2018: 224-236.

[17] A. Ortiz, C. Robinson, D. Morris, et al. Local context normalization: Revisiting local normalization[C]//Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2020: 11276-11285.

[18] A. Paszke, S. Gross, S. Chintala, et al. Automatic differentiation in pytorch[J]. 2017.

[19] H. Noh, A. Araujo, J. Sim, et al. Large-scale image retrieval with attentive deep local features[C]//Proceedings of the IEEE international conference on computer vision. 2017: 3456-3465.

[20] A. Fischler M, C. Bolles R. Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography[J]. Communications of the ACM, 1981, 24(6): 381-395.

[21] H. Bay, T. Tuytelaars, L. Van Gool. Surf: Speeded up robust features[C]//European conference on computer vision. Springer, Berlin, Heidelberg, 2006: 404-417.

[22] O. Chum, T. Werner, J. Matas. Two-view geometry estimation unaffected by a dominant plane[C]//2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05). IEEE, 2005, 1: 772-779.

[23] Y. Liu, Z. Shen, Z. Lin, et al. Gift: Learning transformation-invariant dense visual descriptors via group cnns[J]. arXiv preprint arXiv:1911.05932, 2019.

[24] Z. Luo, T. Shen, L. Zhou, et al. Contextdesc: Local descriptor augmentation with cross-modality context[C]//Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2019: 2527-2536.

[25] Y. Tian, X. Yu, B. Fan, et al. Sosnet: Second order similarity regularization for local descriptor learning[C]//Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2019: 11016-11025.

[26] R. Arandjelović, A. Zisserman. Three things everyone should know to improve object retrieval[C]//2012 IEEE Conference on Computer Vision and Pattern Recognition. IEEE, 2012: 2911-2918.

[27] Y. Wang, C. Chen Y, X. Zhang, et al. Attentive normalization for conditional image generation[C]//Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition. 2020: 5094-5103.

[28] L. Bottou. Large-scale machine learning with stochastic gradient descent[M]//Proceedings of COMPSTAT'2010. Physica-Verlag HD, 2010: 177-186.

[29] X. Huang, S. Belongie. Arbitrary style transfer in real-time with adaptive instance normalization[C]//Proceedings of the IEEE International Conference on Computer Vision. 2017: 1501-1510.