MoTVLA: A Vision-Language-Action Model with Unified Fast-Slow Reasoning

Wenhui Huang [* 1]   **Changhe Chen** [* 2]   **Han Qi** [1]   **Chen Lv** [3]   **Yilun Du** [† 1]   **Heng Yang** [† 1]

MoTVLA Project Page

Abstract

Integrating visual-language instructions into visuomotor policies is gaining momentum in robot learning for enhancing open-world generalization. Despite promising advances, existing approaches face two challenges: limited language steerability when no generated reasoning is used as a condition, or significant inference latency when reasoning is incorporated. In this work, we introduce MoTVLA, a mixture-of-transformers (MoT)–based vision–language–action (VLA) model that integrates fast–slow unified reasoning with behavior policy learning. MoTVLA preserves the general intelligence of the VLM (serving as the generalist) for tasks such as perception, scene understanding, and semantic planning, while incorporating a domain expert, a second transformer that shares knowledge with the generalist, to generate fast domain-specific reasoning (e.g., robot motion decomposition), thereby improving policy execution efficiency. By conditioning the action expert on decomposed motion instructions, MoTVLA can learn diverse behaviors and substantially improve language steerability. Extensive evaluations across natural language processing benchmarks, robotic simulation environments, and real-world experiments confirm the superiority of MoTVLA in both language reasoning and manipulation task performance. We refer to Project Page for the demonstration videos and corresponding descriptions.

1. Introduction

Vision-Language-Action (VLA) models, as natural extensions of Vision-Language Models (VLMs), have recently attracted growing interest in robot learning by generating action trajectories through next-token prediction (Kim et al., 2025; Zawalski et al., 2025). While promising progress has been made in tasks such as manipulation (Zhao et al., 2025; Zitkovich et al., 2023) and mobile navigation (Cheng et al., 2025), this paradigm faces inherent limitations. Compared to natural language processing (NLP), robotics datasets are much smaller, and fine-tuning large VLAs on such limited data often degrades the general intelligence acquired during pre-training, reducing adaptability and generalization. Moreover, representing continuous actions with discretized tokens compromises precision and robustness (Driess et al., 2025).

To address these issues, diffusion policies (DPs) have emerged as a compelling alternative, better suited for modeling continuous action spaces. Leveraging their multimodal nature (Ho et al., 2020; Song et al., 2021), visuomotor DPs capture diverse behaviors via iterative noise–denoise processes (Chi et al., 2024). One paradigm integrates VLMs with DPs by conditioning the policies on separately encoded textual and visual features, enabling multitasking through multimodal inputs (Liu et al., 2025), though this design suffers from limited language steerability since reasoning is not explicitly generated and conditioned (Barreiros et al., 2025a). Another paradigm employs autoregressive VLMs to generate reasoning in the language domain, with DPs subsequently conditioned on this reasoning for action generation (Intelligence et al., 2025; Driess et al., 2025). While this approach improves behavioral generalization, inference remains constrained by the latency of next-token prediction, which hinders time-critical applications.

To bridge the aforementioned gap, we propose a mixture-of-transformers (MoT)–based (Liang et al., 2025) vision-language-action (VLA) model, termed MoTVLA (*pronounced "MotiLA"*), which integrates fast–slow unified reasoning with policy learning through diffusion policies (DPs). Unlike existing approaches, MoTVLA unifies fast-slow reasoning within a single architecture by decomposing the modalities at the input and the functionalities at the output, while maintaining a shared global knowledge base in between. The slow reasoning process follows the standard next-token prediction paradigm of the VLM (generalist), whereas the fast reasoning process is realized via token-wise prediction in a secondary transformer (domain expert)

[1]Harvard University, US [2]University of Michigan, US [3]Nanyang Technological University, Singapore. Correspondence to: Heng Yang <hankyang@seas.harvard.edu>, Yilun Du <ydu@seas.harvard.edu>.

that shares global self-attention with the generalist. For illustration, we refer to these as the first and second transformers; however, in MoTVLA they are integrated into one architecture through a shared global attention mechanism. This design enables MoTVLA to retain the general intelligence of pre-trained VLMs for tasks such as perception, scene understanding, and semantic planning, while efficiently acquiring domain-specific reasoning, such as robot motion decomposition, at a faster pace. Finally, the action expert, implemented as a diffusion transformer (DiT), is conditioned on the reasoning signals together with visual and physical states to generate language-steered action trajectories, thereby closing the loop from high-level reasoning to low-level control.

We conduct comprehensive evaluations of MoTVLA across natural language processing (NLP) benchmarks, robotic simulation environments (ManiSkill) (Gu et al., 2023), and real-world experiments. These validations cover a wide spectrum of tasks, ranging from visual reasoning on image-based vision–question–answering (VQA) for text and mathematics to robotic manipulation tasks such as stacking, tool usage, insertion, pick-and-place, and table bussing. The results consistently confirm the superiority of MoTVLA over state-of-the-art (SOTA) baselines in both reasoning and manipulation tasks. Finally, the ablation study confirms the significance of the proposed architecture for both language reasoning and policy learning.

We summarize our main contributions as follows: (*i*) We unify fast-slow reasoning within a single model based on the MoT architecture, enabling the preservation of general intelligence while efficiently learning domain-specific knowledge that benefits from it; (*ii*) We condition policy learning on decomposed motion reasoning, thereby facilitating faster task execution while maintaining interpretability of policy behaviors within a language context. (*iii*) MoTVLA achieves superior performance in inference latency, language reasoning, and manipulation tasks, providing a novel insight of integrating reasoning into downstream behavior policy.

In the following, after a review of related work on VLA and DP in Section 2, we detail the MoTVLA model and training recipe in Section 3. We present experimental results in Section 4 and conclude in Section 6. Additional details, including inference latency comparisons, pseudo-code of the inference pipeline, dataset descriptions, and further qualitative results, are provided in the Appendix.

2. Related Work

Vision-Language-Action Models. Vision-language-action (VLA) models, as an important branch of robotic foundation models, have emerged as one of the most prominent approaches for learning multitask policies in robot learning. Owing to their billion-scale parameterization, VLAs are capable of accommodating large-scale robotic datasets (Khazatsky et al., 2024; O'Neill et al., 2024; Walke et al., 2023; Ji et al., 2025; Chen et al., 2025a; Li et al., 2025b). The underlying rationale of this paradigm is to learn behavior policies through next-token prediction, analogous to language modeling, thereby transferring general intelligence into domain-specific knowledge for robotic tasks. Representative examples include RT-2 (Zitkovich et al., 2023) and OpenVLA (Kim et al., 2025), which pioneered the learning of visuomotor control policies by leveraging vision-language models (VLMs) and modeling continuous actions through discretized action tokens. Recognizing that purely end-to-end training can impair reasoning capabilities, subsequent work such as ECoT (Zawalski et al., 2025), Gemini Robotics (Team et al., 2025), and CoT-VLA (Zhao et al., 2025) proposed to jointly learn textual and visual reasoning alongside visuomotor policy learning. Despite their demonstrated success across diverse robotic tasks, VLAs face challenges that hinder their practical applications. In particular, control accuracy is often compromised by the information loss incurred when continuous actions are represented with discrete tokens (Driess et al., 2025).

Diffusion Policy. DPs (Chi et al., 2024; Xue et al., 2025) have been widely adopted for robot policy learning by leveraging the strong generative capabilities of diffusion models (Song et al., 2021; Ho et al., 2020) in visual generation. The central idea of DP is to model the multimodality of robot behaviors through the noise–denoise process, which is naturally suited for continuous action spaces. Recently, an emerging research direction has focused on advancing diffusion-based VLAs (Liu et al., 2025; Wen et al., 2025; Intelligence et al., 2025; Driess et al., 2025; Deng et al., 2025b; Chen et al., 2025b; Bjorck et al., 2025; Barreiros et al., 2025b) by integrating VLMs with DP, thereby combining the strengths of both paradigms. For example, RDT-1B (Liu et al., 2025) tokenizes textual and visual inputs, encodes them, and conditions the action diffusion process on this information, resulting in a multitask DP. However, as highlighted by LBM (Barreiros et al., 2025b), such lightweight integration faces limitations in language steerability because it only encodes input information, which inherently lacks reasoning content. In contrast, the $\pi 0.5$ family (Intelligence et al., 2025; Driess et al., 2025) first generates textual reasoning based on input images and prompts, and then conditions the DP on this reasoning through flow matching, thereby enabling instruction-following action policies. While these approaches achieve impressive generalization in real-world settings, their reliance on next-token prediction for reasoning introduces significant inference latency, which in turn limits task execution efficiency.

Figure 1. **The universal framework of MoTVLA.** MoTVLA adopts a Mixture-of-Transformers architecture comprising a generalist, a domain expert, and an action expert. Its reasoning backbone follows a decomposition–composition–decomposition pipeline: multimodal inputs are first processed independently, then integrated through a unified global self-attention mechanism, and finally decoupled at the output to perform slow and fast reasoning via the generalist and domain expert, respectively. The fast reasoning module decomposes robotic motions, and the resulting motion signals, together with visual and physical states, condition the action expert. This design ensures that the learned policy aligns with motion instructions and enhances language steerability, even under ambiguous prompts.

3. The MoTVLA Model and Training Recipe

3.1. Model Architecture

The overall architecture of MoTVLA is illustrated in Fig. 1. MoTVLA adopts a Mixture-of-Transformers (MoT) design and consists of three key components: a generalist, a domain expert, and an action expert. The generalist is dedicated to visual–textual multimodal understanding, the domain expert focuses on fast reasoning for robotic tasks, and the action expert is responsible for multitask policy learning.

Input Space Design. The input modalities of MoTVLA consist of three domains: (1) language, which provides either general or domain-specific prompts, (2) RGB images, and (3) a set of learnable queries conditioned for fast reasoning generation. To process these inputs, MoTVLA employs a text tokenizer and a visual encoder that jointly support both fast-slow reasoning, along with learnable embeddings specifically designed for fast reasoning. We adopt a Vision Transformer (ViT) as the visual encoder, initialized from SigLIP2-so400m/14 (Tschannen et al., 2025) with a fixed input resolution of 384. For the text tokenizer, we directly use the one from the pre-trained Qwen2.5 LLM (Hui et al., 2024).

Reasoning Backbone Design: Decomposition-Composition-Decomposition. To realize fast–slow unified reasoning, we follow the MoT design principle

(Liang et al., 2025). Specifically, we adopt Qwen2.5 LLM 7B (Hui et al., 2024) as the generalist backbone and mirror the same architecture for the domain expert, which includes RMSNorm (Zhang & Sennrich, 2019), RoPE (Su et al., 2024) for positional embedding, and an additional QK-Norm module. Task information is decomposed into the three modalities introduced above and tokenized separately to produce multimodal tokens and their corresponding QKVs. These QKVs are then aggregated into a unified set for joint global attention, with modality-specific masks regulating interaction and conditioning, formulated as:

$$\text{GA}(x, \{\theta_{\text{LA}}^m\}) = \left(\text{softmax}\left(\frac{QK^T}{\sqrt{d_k}}\right)V\right)W_{QKV}^{m_i}$$
$$\text{att} = \text{GA}(x, \{\theta_{\text{LA}}^m\}_{m\in\{\text{text, image, queries}\}}) \quad (1)$$
$$h = x + \text{LayerNorm}_{\text{LA}}^{m_i}(\text{att}_i) \,,$$

where GA and LA denote global and local attention, $x = x_1, x_2, ..., x_n$ is the input token sequence, m represents the modality, θ the trainable parameters, and W^{m_i} the modality-specific projection weights. In this formulation, QKVs of later modalities are allowed to attend to those of earlier ones. Within each modality, we apply two types of local attention for text and maintain bidirectional attention for vision. The global attention is then decomposed by modality indices, enabling distinct functions such as general and domain-specific reasoning. Following this decomposi-

tion–composition–decomposition paradigm, MoTVLA preserves the general intelligence inherited from pre-training by decoupling the associated parameters, while also facilitating domain-specific reasoning through effective knowledge sharing from the generalist to the domain expert. The importance of this design is validated by the ablation study in Section 5. All primary training and evaluation in this work are conducted with MoTVLA-14B, while the 1B variant is used only to illustrate potential inference speed gains when scaling down. Limitations are discussed in Section 6, and inference frequency comparisons are provided in appendix.

Reasoning Output Design. The reasoning output of MoTVLA is unified in the textual space but decoupled into two functionalities: slow and fast reasoning. Slow reasoning follows the standard next-token prediction paradigm with causal attention, leveraging the strengths of autoregressive LLMs but incurring high latency. Owing to large-scale pre-training on internet-scale datasets, the generalist demonstrates strong generalization across tasks such as perception, scene understanding, and semantic planning. In contrast, fast reasoning adopts a token-wise prediction paradigm with bidirectional attention, enabling substantially faster text generation. This design allows MoTVLA to pass hidden state inferences from the domain expert directly to the action expert without multiple forward passes. The key insight is that hidden states from a single forward process in token-wise prediction already encode the information required for reasoning generation, whereas those from next-token prediction reflect only the input information. Although token-wise prediction inevitably sacrifices some reasoning accuracy, it is sufficient for producing simple outputs such as decomposed manipulation motions in this work.

Action Expert Design. In our setting, to better accommodate the varying token lengths of hidden states and their associated masks, we adopt the Diffusion Transformer (DiT) as the action expert of MoTVLA, instead of a U-Net. Policy learning is performed within the framework of action diffusion (Chi et al., 2024), which captures the multimodal nature of robot behaviors. The state space of the action expert consists of four components: (1) visual observations $I_{t-H_I:t}$ with time horizon H_I, (2) semantic conditioning signals $h_{\ell_{DE}}$ generated by the domain expert, (3) the robot configuration $q_{t-H_I:t}$ (e.g., joint angles and gripper status), and (4) noisy action trajectories $A_{t:t+H_A}$, where H_A denotes the action horizon. The diffusion policy learned by the action expert can be formulated as:

$$\pi_{\theta_{AE}}(A_{t:t+H_A}, h_{\ell_{DE}} | I_{t-H_I:t}, \ell, q_{t-H_I:t})$$
$$= \pi_{\theta_{AE}}(A_{t:t+H_A} | \mathcal{I}_{t-H_I:t}, h_{\ell_{DE}}, q_{t-H_I:t}) \pi_{\theta_{RE}}(h_{\ell_{DE}} | I_t, \ell),$$
$$(2)$$

where $h_{\ell_{DE}}$ represents the hidden states of fast reasoning, ℓ denotes the input prompts, and $H_\mathcal{I}$ indicates the time hori-

zon of visual observations. The parameters θ_{AE}, θ_{DE}, and θ_{RE} correspond to the trainable weights of the action expert, domain expert, and the reasoning backbone (comprising both the generalist and domain expert), respectively.

The full pseudo-code of the forward inference pipeline is presented in Appendix.

3.2. Training Recipe

Following the abovementioned architecture, MoTVLA has three individual parts, the generalist, domain expert, and action expert, to train with. To leverage strong power of the general intelligence, in this work we adopt the pre-trained VLM from Bagel (Deng et al., 2025a), which achieves SOTA performance on visual understanding benchmarks, as the initialization of the generalist. Therefore, we dedicate our effort to train the rest of two stages in this work.

Domain Expert Supervised Fine-Tuning. In the domain expert SFT stage, we construct a high-quality manipulation motion VQA dataset by combining both simulated data and real-world demonstrations from human operators. For data construction, we adopt a question template of the form "Your meta task is: ..." and fill the subsequent part with a specific task description, e.g., "Sort the rubbish into the box and move the other into the basket." For the corresponding answer, we employ the generalist to generate decomposed motions in four steps, which are then used as the training labels for the action expert. To further improve generalization capability, we jointly train the action expert with two additional open-source datasets: LLaVA-OV VQA (Li et al., 2024), which contributes to language generalization, and Robo2VLM (Chen et al., 2025a), which enhances robotic reasoning. We manually filter and curate long-answer samples from LLaVA-OV to ensure their suitability for token-wise prediction learning, while converting the selection-style annotations in Robo2VLM into reasoning-based labels. In total, our action expert reasoning dataset consists of 1.27M QA pairs, including 154K samples from simulation and 125K from real-world demonstrations collected in-house, 678K from Robo2VLM, and 318K from LLaVA-OV. Further details are provided in Appendix. The learning objective is to minimize the negative log-likelihood of target tokens:

$$\mathcal{L}(\theta_{DE}) = \mathbb{E}_{(x,y) \sim D}[-\log p_\theta(y_{1:n} | x_{1:n})] \quad (3)$$

where D denotes dataset and y represents sequence of target reasoning tokens in this stage.

Action Expert Diffusion Policy. We collect 300 demonstrations in the ManiSkill (Gu et al., 2023) simulator for each of the three short-horizon tasks (Cube Stacking, Peg-in-Hole, and L-Tool Pull), with additional distractors intro-

Table 1. Fast reasoning evaluation on both robotics and LLaVA-OV VQA tasks. ($*$ refers to revision, † denotes the same task evaluated under an alternative instruction prompt.)

Task	Dataset	Metrics			
		BLEU (0-1)↑	CIDEr (0-10) ↑	METEOR (0-1)↑	Token Accuracy (%)↑
Robotics	Cube Stacking	0.8041	8.0574	0.6005	89.82
	Peg-in-Hole	0.8174	7.6805	0.5633	88.41
	L-tool Pull	0.6221	6.6255	0.4263	71.76
	Pick & Place: Eggplant	0.8680	8.3945	0.6136	88.99
	Pick & Place: Carrot	0.7816	7.1222	0.5395	80.83
	Pick & Place: Corn	0.8836	8.7838	0.6320	91.86
	Table Bussing	0.9086	8.9802	0.6794	95.59
	Table Bussing†	0.9168	9.0454	0.6712	93.41
	Robo2VLM*	0.3782	2.3601	0.3279	57.05
LLaVA-OV VQA	FigureQA (Kahou et al., 2017)	0.9940	2.4850	0.8105	99.40
	CLEVR (Johnson et al., 2017)	0.9790	2.3950	0.7004	95.80
	ScienceQA (Saikh et al., 2022)	0.9780	2.4450	0.9749	97.80
	ScienceQA(nona context) (Li et al., 2024)	0.8004	2.4282	0.5544	86.16
	Hateful-memes (Kiela et al., 2020)	0.9270	2.1350	0.5603	85.40
	Visual-7W (Zhu et al., 2016)	0.9459	2.3647	0.9510	94.59
	Visual Spatial Reasoning (Liu et al., 2023)	0.9430	2.2150	0.6022	88.60
	TallyQA (Acharya et al., 2019)	0.9160	2.0850	0.5498	83.20

duced into the scenes. For the long-horizon tasks, we collect 100 demonstrations for each (Tool Pull & Place, Table Bussing, and Table Bussing Reverse). In the real world, using the SpaceMouse, we collect 50 demonstrations for pick-and-place with various vegetables and 100 demonstrations for each of the long-horizon tasks. Notably, this dataset is substantially smaller than that used for training the other two experts, as publicly available datasets with decomposed motion annotations are hardly available, and the workload of collecting and annotating such data in-house is prohibitively large. Conditioning on the visual observations $I_{t-H_I:t}$ over $H_I = 5$ observation horizons, robot configuration $q_{t-H_I:t}$, and decomposed motion reasoning signal $h_{\ell_{DE}}$, we implement a visuomotor policy using a conditional denoising diffusion model (Chi et al., 2024). During testing, the policy denoises Gaussian noise into action trajectories $A^0_{t:t+H_A}$ consisting of H_A steps starting at time t. Specifically, beginning from Gaussian noise $A^K_{t:t+H_A}$, the denoising network ϵ_θ iteratively refines the actions over K denoising steps until producing the noise-free action $A^0_{t:t+H_A}$, computed as:

$$A^{k-1}_{t:t+H_A} = \bar{\alpha}_k\Big(A^k_{t:t+H_A} - \epsilon_\theta\big(A^k_{t:t+H_A},\ k,$$
$$I_{t-H_I:t},\ q_{t-H_I:t},\ h_{\ell_{DE}}\big)\Big) + \bar{\beta}_k\,\epsilon^k. \tag{4}$$

where $\epsilon^k \sim \mathcal{N}(0, \mathbf{I})$ and $\bar{\alpha}_k, \bar{\beta}_k$ are noise scheduler coefficients.

To train the denoising network ϵ_θ, we corrupt the ground-truth action $A^0_{t:t+Ha}$ with noise ϵ^k at the k-th step, and optimize the network to predict the injected noise (Chi et al.,

2024), expressed as:

$$\mathcal{L}(\theta_{AE}) = \text{MSE}\Big(\epsilon^k,\ \epsilon_\theta\big(\bar{\alpha}_k A^0_{t:t+H_A} + \bar{\beta}_k \epsilon^k,\ k,$$
$$I_{t-H_I:t},\ q_{t-H_I:t},\ h_{\ell_{DE}}\big)\Big). \tag{5}$$

Due to space constraints, details of the inference pipeline are provided in the Appendix.

4. Experiments

MoTVLA is a multitasking model capable of performing general slow reasoning, multimodal robot-specific fast reasoning, and action planning for manipulation tasks. We conduct extensive evaluations in both simulation and real-world experiments, covering semantic fast-slow reasoning as well as embodied action execution.

4.1. Metrics and Baselines.

In this work, we employ standard NLP metrics, including BLEU (Papineni et al., 2002), METEOR (Banerjee & Lavie, 2005), CIDEr (Vedantam et al., 2015), and token accuracy, to evaluate reasoning performance. For manipulation tasks, we report the average success rate using random seeds that were not observed during data collection or training.

We compare MoTVLA against several well-known and SOTA baselines, including transformer-based DP (Chi et al., 2024), GR-MG (Li et al., 2025a), π_0 (Black et al., 2024), and the recently released $\pi_{0.5}$ with knowledge insulation (Driess et al., 2025). For a fair comparison and to align the baselines' output space with our hardware setting, we fine-tuned them on our own dataset, which contains 1650 trajectories, on top of their respective pre-trained models.

Figure 2. **Fast reasoning instances and slow reasoning benchmark.** ∗ indicates that the generalist is fine-tuned on the data originally intended for training the domain expert.

4.2. Reasoning Tasks

The performance of fast reasoning is particularly critical in our work, since its outputs serve as conditioning signals for the action expert. A completely hallucinated reasoning would misguide the diffusion policy and lead to undesirable behaviors. As discussed in Section 3.2, we incorporate additional VQA datasets, namely LLaVA-OV (Li et al., 2024) and Robo2VLM (Chen et al., 2025a), in addition to our own robotic motion reasoning dataset, to enhance generalization capability. Distinct from existing VLA approaches, we not only qualitatively assess the quality of fast reasoning through VQA, but also quantitatively evaluate its performance on both robotic and general datasets.

The overall statistical results of fast reasoning are summarized in Table 1. The average BLEU score and token accuracy across robotics and LLaVA-OV VQA tasks highlight its superior precision in capturing both domain expertise and common knowledge. Meanwhile, the CIDEr and METEOR scores on robotics tasks exhibit strong alignment with human judgment in terms of expression diversity and semantic similarity, indicating that the motion decomposition generated through fast reasoning has been effectively learned. The

manually curated Robo2VLM reasoning dataset further underscores the difficulty of this evaluation, as we reformatted it from multiple-choice to reasoning-based VQA, encompassing diverse scenes, tasks, views, and reasoning domains (spatial, goal-oriented, and interaction-based). For LLaVA-OV VQA, although the CIDEr score is less prominent and below human-level quality, the relatively high METEOR score demonstrates sufficient generalization, justifying our motivation for joint training with both general and domain-specific datasets.

Qualitative evaluations on two randomly selected reasoning tasks (Fig.2a) further confirm strong zero-shot generalization. Surprisingly, MoTVLA is able to infer unseen objects and decompose motions never encountered during training, and can also extract key information from an information-dense poster. These results collectively demonstrate MoTVLA's strong domain knowledge and generalization capability to handle diverse scenarios. Detailed reasoning latency comparisons and more qualitative results are provided in Appendix due to limited space.

Furthermore, we conduct an ablation study on slow reasoning for general knowledge evaluation by comparing training

Figure 3. **Evaluation for manipulation tasks.** MoTVLA is rigorously evaluated in both simulation and real-world experiments. The testing suite encompasses diverse case types and variations, including ambiguous instruction prompts that require strong reasoning capability and language-steered behavioral policies.

versus freezing the generalist, demonstrating the necessity of the MoT architecture in our approach. To this end, we fine-tuned the generalist using the data originally intended for training the domain expert and compared it with the unfine-tuned version. We benchmark both versions on the Massive Multi-discipline Multimodal Understanding and Reasoning (MMMU) dataset (Yue et al., 2024), which is widely used for evaluating broad general intelligence across multiple disciplines. As shown in Fig. 2b, after fine-tuning, the performance of slow reasoning degrades across several subjects. For instance, while the tuned generalist maintains its performance in domains such as art, accounting, finance, and other science-related subjects, it exhibits knowledge forgetting in music, marketing, energy and power, and mechanical engineering. This degradation is even more pronounced in public health, where accuracy drops by 6.6% after fine-tuning. We also observe similar catastrophic forgetting in robotic VQA when providing a meta-task description followed by a general question, for example: "Your meta task is: Put the cucumber into the box. Before executing the task, tell me what is the color of the cucumber." The

fine-tuned generalist fails to respond to the question about color and instead outputs the decomposed motion. These results highlight the superiority of MoTVLA, which preserves slow reasoning capability even after robotic VQA learning, confirming the necessity of the MoT architecture for maintaining fast–slow reasoning performance. Due to the space limitation, we refer the motion decomposition evaluation between fast reasoning of the MoTVLA and the finetuned generalist (generalist*) to the Appendix.

Overall, the demonstrated superiority of fast reasoning performance establishes a solid foundation for MoTVLA to effectively learn robotic knowledge and corresponding behavior policies while maintaining its general intelligence. The policy learning aspect will be further analyzed, both qualitatively and quantitatively, in the following sections.

4.3. Robot Manipulation tasks

We investigate whether MoTVLA can transform language-described motion decompositions into reliable manipulation across both simulation and real-world settings. Our objec-

Table 2. Performance comparison across different models for manipulation tasks.

Short-horizon Tasks	MoTVLA	π0.5 KI	π0	GR-MG	DP
Cube Stacking (Sim)	**0.79**	0.30	0.02	0.14	0.58
Peg-in-Hole (Sim)	**0.40**	0.22	0.0	0.06	0.24
L-Tool Pull (Sim)	**0.62**	0.36	0.28	0.10	0.48
Pick & Place Eggplant	**1.0**	**1.0**	**1.0**	0.50	0.25
Pick & Place Corn	**1.0**	**1.0**	0.75	0.0	0.50
Pick & Place Carrot	**1.0**	**1.0**	**1.0**	0.0	0.50
Carrot w/ distractions	**1.0**	**1.0**	0.75	0.0	0.75
Eggplant w/ distractions	0.75	**1.0**	0.75	0.0	0.50
Corn w/ distractions	0.75	**1.0**	0.50	0.0	0.50
Mean $\pm$ Variance	**0.81** $\pm$ 0.04	0.76 $\pm$ 0.11	0.56 $\pm$ 0.11	0.09 $\pm$ 0.03	0.48 $\pm$ 0.02
Long-horizon Tasks					
Tool Pull & Place (Sim)	**0.72**	0.10	0.08	-	0.50
Table Bussing (Sim)	**1.0**	0.26	0.54	-	0.10
Table Bussing Reverse (Sim)	**0.98**	0.70	0.50	-	0.60
Tool Pull & Place	**0.70**	0.40	0.30	-	0.10
Table Bussing	**0.80**	**0.80**	0.50	-	0.50
Table Bussing Reverse	**0.80**	0.70	0.60	-	0.20
Mean $\pm$ Variance	**0.83** $\pm$ 0.01	0.49 $\pm$ 0.07	0.42 $\pm$ 0.03	-	0.33 $\pm$ 0.04
Action Training Recipe	**Dataset and Scale**				
Fine-tuning	1650 Collected Trajectories				
Pre-training on Robotic Dataset	None	400h + much larger number data + OXE (Intelligence et al., 2025)	$\simeq$ 10000h + OXE (Black et al., 2024)	Ego4d ($>$ 3500h) (Li et al., 2025a)	None

tives are threefold: (i) to assess whether motion-decomposed conditioning improves policy learning and robustness, particularly in contact-rich and long-horizon tasks, (ii) to examine whether decomposed motion snippets benefit language steerability of the policy behavior, and (iii) to thoroughly benchmark MoTVLA against four strong and SOTA baselines across an evaluation spectrum ranging from simulation to real-world experiments. To this end, we adopt three challenging tasks from the ManiSkill environment (Gu et al., 2023) and manually increase their difficulty, along with three customized long-horizon tasks that require multi-step internal reasoning. In addition, we conduct two types of real-world experiments for training MoTVLA, including three single-stage manipulation tasks with clear instructions and three multi-stage, long-horizon tasks with ambiguous instructions. During testing, these tasks are further diversified into additional cases by varying initial states, random seeds, and introducing unseen objects as distractions, as illustrated in Fig. 3. For example, MoTVLA must distinguish carrots, corn, and eggplants (targets) from potato (distractions) in a zero-shot manner and guide the policy to complete the task accordingly. Full implementation details are provided in Appendix. For fair comparison and to unify the baselines' output space to our hardware setting, we fine-tuned all baselines on our dataset.

The quantitative comparison with baseline methods is reported in Table 2. As shown, MoTVLA consistently outperforms most baselines on both in-domain and zero-shot short-horizon tasks (with distractions), demonstrating strong robustness and generalization capability. Although the suc-

cess rate on the challenging *Peg-in-Hole* task is relatively lower due to its stringent precision requirements and tight tolerances, MoTVLA still achieves the best performance among all methods. Moreover, models equipped with VLM backbones (MoTVLA, π0.5 KI, and π0) consistently outperform those without pre-training, highlighting the benefits of leveraging general-purpose visual–language representations for short-horizon robotic tasks. Beyond short-horizon settings, MoTVLA exhibits particularly strong advantages on long-horizon tasks, where only ambiguous instructions are provided and multiple steps of internal reasoning are required. While the π0.5 KI model achieves performance comparable to our approach on short-horizon tasks, MoTVLA consistently surpasses π0.5 on long-horizon tasks by up to 34%, validating the importance of motion decomposition and language steerability. Furthermore, we observe that, unlike pick-and-place tasks, the π-series models struggle with tool-using tasks even after fine-tuning, regardless of task horizon or whether evaluation is conducted in simulation or real-world settings.

Figure 3 presents qualitative results of MoTVLA across a variety of tasks, highlighting its language steerability compared to other baselines in real-world scenarios, particularly when only ambiguous prompts are provided. For example, in the *Tool Pull & Place* task, we provide only the instruction "Put the cube on the plate." without explicitly indicating that the cube lies beyond the reach of the manipulator. As a result, the agent must infer the need to utilize a tool to pull the cube into a reachable region. Similarly, for the *Table Bussing* task, we do not specify object categories in the

Table 3. **Ablation study of the architectural design.** MD: Motion Decomposition; GE: Generalist, DE: Domain Expert; AE: Action Expert; TA: Token Accuracy; SR: Success Rate.

		MoTVLA w/o DE	MoTVLA (scratch)	MoTVLA (ours)
Component	GE (Slow Reasoning)	Pre-trained	Scratch	Pre-trained
	DE (Fast Reasoning)	N/A	Fine-tuned	Fine-tuned
	AE (Diffusion Policy)	Fine-tuned	Fine-tuned	Fine-tuned
Slow Reasoning	ScienceQA (TA)	94.12	0.0	94.12
	MD (TA)	1.68	0.0	1.68
Fast Reasoning	ScienceQA (TA)	N/A	17.00	90.99
	MD (TA)	N/A	37.10	89.07
Diffusion Policy	Tool Pull & Place (SR)	0.0	0.62	0.72

prompt, requiring the model to autonomously distinguish between trash and vegetables based on semantic understanding. As shown, MoTVLA successfully decomposes each task into a sequence of reasonable motions and guides the policy to complete the given instructions. Moreover, when an alternative prompt with a reversed order is provided for the same *Table Bussing* scene, MoTVLA adapts its behavior accordingly. In contrast, $\pi 0.5$ KI fails to follow the correct sub-task order and incorrectly picks up the rubbish while sorting the vegetables. This behavior demonstrates strong alignment between language instructions and policy execution in MoTVLA, highlighting the effectiveness of its language steerability.

5. Ablation Study.

In this ablation study, we evaluate the impact of the pre-trained generalist and the necessity of the domain expert. We compare three variants: **MoTVLA w/o DE**, where only the generalist and action expert are retained, enabling slow reasoning and diffusion-based action generation but lacking fast reasoning; **MoTVLA (scratch)**, where the generalist is randomly initialized while the domain expert and action expert are fine-tuned, enabling both fast–slow reasoning and diffusion-based action generation but without inherited general intelligence; and **MoTVLA (ours)**, the full model proposed in this work. The purpose of these baselines is twofold: (i) to investigate the significance of general intelligence by comparing our method with MoTVLA (scratch), and (ii) to illustrate the importance of the domain expert by comparing against MoTVLA w/o DE, where fast reasoning of motion decomposition is absent. As shown in Table 3, MoTVLA (scratch) fails to learn across all tasks under both slow and fast reasoning, confirming that the general intelligence inherited from the pre-trained VLM is essential for effective multimodal reasoning. Meanwhile, MoTVLA w/o DE performs well on ScienceQA but achieves the lowest token accuracy in the slow reasoning of motion decomposition, indicating that the domain expert and its global attention mechanism are vital for aligning domain-specific knowledge and stabilizing motion generation. While it is

possible to fine-tune the slow reasoning of MoTVLA w/o DE on our motion decomposition dataset to improve accuracy, as discussed in Section 4.2, this approach would inevitably lead to catastrophic forgetting of general intelligence. Notably, MoTVLA significantly outperforms the other two baselines on the long-horizon manipulation task (Tool Pull & Place), as the unstable and hallucinated motion decompositions produced by these baselines introduce substantial variance and hinder policy learning. Furthermore, the quantitative results of the ablation study on language steerability can be found in the following section.

6. Conclusion

In this paper, we address the challenging gap between reasoning latency and language steerability by proposing MoTVLA, a Mixture-of-Transformers (MoT) architecture-based robotic foundation model that unifies fast-slow reasoning and enhances the language steerability of behavior policies. MoTVLA acquires domain expertise and action policies through a two-stage curriculum learning scheme while preserving the general intelligence inherited from a pretrained VLM throughout the entire training process. Comprehensive benchmarking across semantic reasoning, simulation, and real-world experiments confirms the feasibility and superiority of the proposed approach. We believe that this integration of high-level reasoning and low-level control policies within a unified VLA framework paves the way for advancing robotic learning toward open-ended, language-instructed tasks and language-steered behaviors in large-scale open-world environments.

Despite its superior performance on most evaluation tasks, the full potential of MoTVLA has not yet been fully explored. The relatively limited amount of data available for training the action expert sometimes leads to strong reasoning ability but insufficient execution capability, resulting in failures on complex, long-horizon tasks. Leveraging large-scale open-sourced robotics datasets, annotating motion decompositions, and jointly pre-training the action expert with the reasoning backbone will be important directions for future work.

Impact Statement

This paper presents work aimed at advancing open-world physical intelligence through the integration of fast–slow unified reasoning with visuomotor policy learning. By improving the ability of robotic systems to interpret ambiguous language instructions, decompose complex tasks, and execute reliable manipulation behaviors, MoTVLA has the potential to significantly enhance the applicability of intelligent robots in real-world environments such as household assistance and industrial automation.

References

Acharya, M., Kafle, K., and Kanan, C. Tallyqa: Answering complex counting questions. In *Proceedings of the AAAI conference on artificial intelligence*, volume 33, pp. 8076–8084, 2019. 5

Banerjee, S. and Lavie, A. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pp. 65–72, 2005. 5

Barreiros, J., Beaulieu, A., Bhat, A., Cory, R., Cousineau, E., Dai, H., Fang, C.-H., Hashimoto, K., Irshad, M. Z., Itkina, M., et al. A careful examination of large behavior models for multitask dexterous manipulation. *arXiv preprint arXiv:2507.05331*, 2025a. 1

Barreiros, J., Beaulieu, A., Bhat, A., Cory, R., Cousineau, E., Dai, H., Fang, C.-H., Hashimoto, K., Irshad, M. Z., Itkina, M., et al. A careful examination of large behavior models for multitask dexterous manipulation. *arXiv preprint arXiv:2507.05331*, 2025b. 2

Bjorck, J., Castañeda, F., Cherniadev, N., Da, X., Ding, R., Fan, L., Fang, Y., Fox, D., Hu, F., Huang, S., et al. Gr00t n1: An open foundation model for generalist humanoid robots. *arXiv preprint arXiv:2503.14734*, 2025. 2

Black, K., Brown, N., Driess, D., Esmail, A., Equi, M., Finn, C., Fusai, N., Groom, L., Hausman, K., Ichter, B., et al. pi_0: A vision-language-action flow model for general robot control. *arXiv preprint arXiv:2410.24164*, 2024. 5, 8

Chen, K., Xie, S., Ma, Z., Sanketi, P. R., and Goldberg, K. Robo2vlm: Visual question answering from large-scale in-the-wild robot manipulation datasets. *arXiv preprint arXiv:2505.15517*, 2025a. 2, 4, 6, 16

Chen, X., Wei, H., Zhang, P., Zhang, C., Wang, K., Guo, Y., Yang, R., Wang, Y., Xiao, X., Zhao, L., Chen, J., and Bian, J. villa-x: Enhancing latent action modeling in vision-language-action models. *arXiv preprint arXiv: 2507.23682*, 2025b. 2

Cheng, A.-C., Ji, Y., Yang, Z., Gongye, Z., Zou, X., Kautz, J., Bıyık, E., Yin, H., Liu, S., and Wang, X. Navila: Legged robot vision-language-action model for navigation. In *RSS*, 2025. 1

Chi, C., Xu, Z., Feng, S., Cousineau, E., Du, Y., Burchfiel, B., Tedrake, R., and Song, S. Diffusion policy: Visuomotor policy learning via action diffusion. *The International Journal of Robotics Research*, 2024. 1, 2, 4, 5

Deng, C., Zhu, D., Li, K., Gou, C., Li, F., Wang, Z., Zhong, S., Yu, W., Nie, X., Song, Z., et al. Emerging properties in unified multimodal pretraining. *arXiv preprint arXiv:2505.14683*, 2025a. 4

Deng, S., Yan, M., Wei, S., Ma, H., Yang, Y., Chen, J., Zhang, Z., Yang, T., Zhang, X., Cui, H., et al. Graspvla: a grasping foundation model pre-trained on billion-scale synthetic action data. *arXiv preprint arXiv:2505.03233*, 2025b. 2

Driess, D., Springenberg, J. T., Ichter, B., Yu, L., Li-Bell, A., Pertsch, K., Ren, A. Z., Walke, H., Vuong, Q., Shi, L. X., et al. Knowledge insulating vision-language-action models: Train fast, run fast, generalize better. *arXiv preprint arXiv:2505.23705*, 2025. 1, 2, 5

Gu, J., Xiang, F., Li, X., Ling, Z., Liu, X., Mu, T., Tang, Y., Tao, S., Wei, X., Yao, Y., Yuan, X., Xie, P., Huang, Z., Chen, R., and Su, H. Maniskill2: A unified benchmark for generalizable manipulation skills. In *International Conference on Learning Representations*, 2023. 2, 4, 8

Ho, J., Jain, A., and Abbeel, P. Denoising diffusion probabilistic models. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 6840–6851. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/4c5bcfec8584af0d967f1ab10179ca4b-Paper.pdf. 1, 2

Hui, B., Yang, J., Cui, Z., Yang, J., Liu, D., Zhang, L., Liu, T., Zhang, J., Yu, B., Lu, K., et al. Qwen2. 5-coder technical report. *arXiv preprint arXiv:2409.12186*, 2024. 3

Intelligence, P., Black, K., Brown, N., Darpinian, J., Dhabalia, K., Driess, D., Esmail, A., Equi, M., Finn, C., Fusai, N., et al. π 0.5: a vision-language-action model with open-world generalization. *arXiv preprint arXiv:2504.16054*, 2025. 1, 2, 8

Ji, Y., Tan, H., Shi, J., Hao, X., Zhang, Y., Zhang, H., Wang, P., Zhao, M., Mu, Y., An, P., et al. Robobrain: A unified brain model for robotic manipulation from abstract to

concrete. In *Proceedings of the Computer Vision and Pattern Recognition Conference*, pp. 1724–1734, 2025. 2

Johnson, J., Hariharan, B., Van Der Maaten, L., Fei-Fei, L., Lawrence Zitnick, C., and Girshick, R. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 2901–2910, 2017. 5

Kahou, S. E., Michalski, V., Atkinson, A., Kádár, Á., Trischler, A., and Bengio, Y. Figureqa: An annotated figure dataset for visual reasoning. *arXiv preprint arXiv:1710.07300*, 2017. 5

Khazatsky, A., Pertsch, K., Nair, S., Balakrishna, A., Dasari, S., Karamcheti, S., Nasiriany, S., Srirama, M. K., Chen, L. Y., Ellis, K., et al. Droid: A large-scale in-the-wild robot manipulation dataset. In *RSS 2024 Workshop: Data Generation for Robotics*, 2024. 2

Kiela, D., Firooz, H., Mohan, A., Goswami, V., Singh, A., Ringshia, P., and Testuggine, D. The hateful memes challenge: Detecting hate speech in multimodal memes. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 2611–2624. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper_files/paper/2020/file/1b84c4cee2b8b3d823b30e2d604b1878-Paper.pdf. 5

Kim, M. J., Pertsch, K., Karamcheti, S., Xiao, T., Balakrishna, A., Nair, S., Rafailov, R., Foster, E. P., Sanketi, P. R., Vuong, Q., et al. Openvla: An open-source vision-language-action model. In *Conference on Robot Learning*, pp. 2679–2713. PMLR, 2025. 1, 2

Li, B., Zhang, Y., Guo, D., Zhang, R., Li, F., Zhang, H., Zhang, K., Zhang, P., Li, Y., Liu, Z., et al. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv:2408.03326*, 2024. 4, 5, 6

Li, P., Wu, H., Huang, Y., Cheang, C., Wang, L., and Kong, T. Gr-mg: Leveraging partially-annotated data via multimodal goal-conditioned policy. *IEEE Robotics and Automation Letters*, 2025a. 5, 8

Li, X., Mata, C., Park, J., Kahatapitiya, K., Jang, Y. S., Shang, J., Ranasinghe, K., Burgert, R., Cai, M., Lee, Y. J., and Ryoo, M. S. Llara: Supercharging robot learning data for vision-language policy. In *International Conference on Learning Representations*, 2025b. 2

Liang, W., YU, L., Luo, L., Iyer, S., Dong, N., Zhou, C., Ghosh, G., Lewis, M., tau Yih, W., Zettlemoyer, L., and

Lin, X. V. Mixture-of-transformers: A sparse and scalable architecture for multi-modal foundation models. *Transactions on Machine Learning Research*, 2025. ISSN 2835-8856. URL https://openreview.net/forum?id=Nu6N69i8SB. 1, 3

Liu, F., Emerson, G., and Collier, N. Visual spatial reasoning. *Transactions of the Association for Computational Linguistics*, 11:635–651, 2023. 5

Liu, S., Wu, L., Li, B., Tan, H., Chen, H., Wang, Z., Xu, K., Su, H., and Zhu, J. RDT-1b: a diffusion foundation model for bimanual manipulation. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=yAzN4tz7oI. 1, 2

O'Neill, A., Rehman, A., Maddukuri, A., Gupta, A., Padalkar, A., Lee, A., Pooley, A., Gupta, A., Mandlekar, A., Jain, A., et al. Open x-embodiment: Robotic learning datasets and rt-x models: Open x-embodiment collaboration 0. In *2024 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 6892–6903. IEEE, 2024. 2

Papineni, K., Roukos, S., Ward, T., and Zhu, W.-J. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pp. 311–318, 2002. 5

Saikh, T., Ghosal, T., Mittal, A., Ekbal, A., and Bhattacharyya, P. Scienceqa: A novel resource for question answering on scholarly articles. *International Journal on Digital Libraries*, 23(3):289–301, 2022. 5

Song, J., Meng, C., and Ermon, S. Denoising diffusion implicit models. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=St1giarCHLP. 1, 2

Su, J., Ahmed, M., Lu, Y., Pan, S., Bo, W., and Liu, Y. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024. 3

Team, G. R., Abeyruwan, S., Ainslie, J., Alayrac, J.-B., Arenas, M. G., Armstrong, T., Balakrishna, A., Baruch, R., Bauza, M., Blokzijl, M., et al. Gemini robotics: Bringing ai into the physical world. *arXiv preprint arXiv:2503.20020*, 2025. 2

Tschannen, M., Gritsenko, A., Wang, X., Naeem, M. F., Alabdulmohsin, I., Parthasarathy, N., Evans, T., Beyer, L., Xia, Y., Mustafa, B., et al. Siglip 2: Multilingual vision-language encoders with improved semantic understanding, localization, and dense features. *arXiv preprint arXiv:2502.14786*, 2025. 3

Vedantam, R., Lawrence Zitnick, C., and Parikh, D. Cider: Consensus-based image description evaluation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4566–4575, 2015. 5

Walke, H. R., Black, K., Zhao, T. Z., Vuong, Q., Zheng, C., Hansen-Estruch, P., He, A. W., Myers, V., Kim, M. J., Du, M., et al. Bridgedata v2: A dataset for robot learning at scale. In *Conference on Robot Learning*, pp. 1723–1736. PMLR, 2023. 2

Wen, J., Zhu, Y., Li, J., Zhu, M., Tang, Z., Wu, K., Xu, Z., Liu, N., Cheng, R., Shen, C., et al. Tinyvla: Towards fast, data-efficient vision-language-action models for robotic manipulation. *IEEE Robotics and Automation Letters*, 2025. 2

Xue, H., Ren, J., Chen, W., Zhang, G., Fang, Y., Gu, G., Xu, H., and Lu, C. Reactive diffusion policy: Slow-fast visual-tactile policy learning for contact-rich manipulation. In *Proceedings of Robotics: Science and Systems (RSS)*, 2025. 2

Yue, X., Ni, Y., Zhang, K., Zheng, T., Liu, R., Zhang, G., Stevens, S., Jiang, D., Ren, W., Sun, Y., et al. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9556–9567, 2024. 7

Zawalski, M., Chen, W., Pertsch, K., Mees, O., Finn, C., and Levine, S. Robotic control via embodied chain-of-thought reasoning. In *Conference on Robot Learning*, pp. 3157–3181. PMLR, 2025. 1, 2

Zhang, B. and Sennrich, R. Root mean square layer normalization. *Advances in neural information processing systems*, 32, 2019. 3

Zhao, Q., Lu, Y., Kim, M. J., Fu, Z., Zhang, Z., Wu, Y., Li, Z., Ma, Q., Han, S., Finn, C., Handa, A., Lin, T.-Y., Wetzstein, G., Liu, M.-Y., and Xiang, D. Cot-vla: Visual chain-of-thought reasoning for vision-language-action models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1702–1713, June 2025. 1, 2

Zhu, Y., Groth, O., Bernstein, M., and Fei-Fei, L. Visual7w: Grounded question answering in images. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4995–5004, 2016. 5

Zitkovich, B., Yu, T., Xu, S., Xu, P., Xiao, T., Xia, F., Wu, J., Wohlhart, P., Welker, S., Wahid, A., Vuong, Q., Vanhoucke, V., Tran, H., Soricut, R., Singh, A., Singh, J., Sermanet, P., Sanketi, P. R., Salazar, G., Ryoo, M. S., Reymann, K., Rao, K., Pertsch, K., Mordatch, I., Michalewski, H., Lu, Y., Levine, S., Lee, L., Lee, T.-W. E., Leal, I., Kuang, Y., Kalashnikov, D., Julian, R., Joshi, N. J., Irpan, A., Ichter, B., Hsu, J., Herzog, A., Hausman, K., Gopalakrishnan, K., Fu, C., Florence, P., Finn, C., Dubey, K. A., Driess, D., Ding, T., Choromanski, K. M., Chen, X., Chebotar, Y., Carbajal, J., Brown, N., Brohan, A., Arenas, M. G., and Han, K. Rt-2: Vision-language-action models transfer web knowledge to robotic control. In Tan, J., Toussaint, M., and Darvish, K. (eds.), *Proceedings of The 7th Conference on Robot Learning*, volume 229 of *Proceedings of Machine Learning Research*, pp. 2165–2183. PMLR, 06–09 Nov 2023. 1, 2

Appendix

A. Reasoning Latency.

Low reasoning latency is one of the advantage of the MoTVLA as it is able to perform fast reasoning with domain expert. We have thoroughly benchmarked the reasoning frequency of MoTVLA with two different sizes comparing with the $\pi 0.5\_KI$, which has the similar motion reasoning capability but still within next token prediction paradigm, as well as several open-sourced VLMs. All models are evaluated with the same visual and textual inputs, with the maximum generation length restricted to 16 tokens and computations performed in bfloat16 precision. We measured the reasoning latency with 50 iterations for the same example to avoid the influence of cold start. As shown in Table 4, MoTVLA-14B significantly outperforms the 3B and 7B baselines on both H100 and A6000 GPUs. Moreover, when scaled down to 1B parameters, MoTVLA achieves a reasoning frequency nearly four times higher than that of LLaVA-OV-0.5B. It is important to note that MoTVLA-0.5B is used only to measure the inference latency of fast reasoning and has not yet been fully integrated into our framework, as pre-training a 0.5B generalist remains highly challenging and requires large-scale datasets. All quantitative and qualitative results reported in this paper are obtained with MoTVLA-14B.

Table 4. Comparison of reasoning latency.

Model	Size	H100	A6000
$\pi 0.5$ KI	3B	< 1Hz	< 1Hz
Bagel-VLM	7B	2 Hz	1 Hz
Qwen2.5-VL	7B	3 Hz	2 Hz
LLaVA-OV	7B	3 Hz	2 Hz
LLaVA-OV	0.5B	5 Hz	4 Hz
MoTVLA	14B	9 Hz	4 Hz
	1B	20 Hz	11 Hz

B. Inference pipeline

In this section, we describe the full inference pipeline of MoTVLA for both general reasoning and robotic manipulation tasks. MoTVLA adopts a fast–slow inference framework. At test time, the interaction proceeds in two modes: (i) the operator may engage in multi-turn dialogue with MoTVLA, posing questions or logical reasoning queries such as object descriptions or semantic planning for specific tasks, and (ii) the operator may instruct MoTVLA to execute manipulation tasks via task-specific prompts. This design not only ensures alignment between language and policy (e.g., when asked "What do you see in the image?" MoTVLA will answer the question without executing actions), but also enhances the interpretability of policy behaviors by generating intermediate motion decompositions during real-time inference. Figure 4 demonstrates a concrete instance of slow and fast reasoning during the inference time.

Figure 4. **A concrete example of fast and slow reasoning during inference.** When asked a general question, the generalist performs slow reasoning and provides a detailed verbal response. When a task-execution prompt is issued, the domain expert performs fast reasoning to generate decomposed intermediate motions for action execution.

During manipulation rollout, the system maintains sliding windows of the most recent H_I images and robot states for context (1, 1). At each step, the Domain Expert DE performs fast, step-wise motion reasoning on the current image I_t conditioned by the $task\_prompt$, producing the hidden state $h_{\ell_{DE}}$ (1). The Action Expert AE then samples an action chunk $A_{H_A}^0$ conditioned on the image window $I_{t-H_I:t}$, state window $q_{t-H_I:t}$, and the hidden state $h_{\ell_{DE}}$ (1). Then action chunk $A_{H_A}^0$ is then sent to the ROBOTCONTROLLER for execution (1).

Algorithm 1 MoTVLA Inference: Generalist $\rightarrow$ Domain Expert $\rightarrow$ Action Expert

---

Require: Models: RE (Generalist/Reasoning backbone), DE (Domain Expert), AE (Action Expert)
Require: $I_0 \triangleright$ initial image, $\ell \triangleright$ user prompt, $H_I \triangleright$ obs-horizons, $H_A \triangleright$ action-horizons
Ensure: Executed closed-loop action sequence
 1: IMGBUF $\leftarrow$ [ ]
 2: STATEBUF $\leftarrow$ [ ]
 3: $t \leftarrow 0$
 4: $general\_reasoning \leftarrow RE.$SLOWREASON$(I_0, \ell)$ {multi-turn dialogue}
 5: IMGBUF.PUSH(I_0)
 6: STATEBUF.PUSH(GETROBOTSTATE())
 7: **while** $t <$ MAX_STEPS **do**
 8:    $h_{\ell_{\mathrm{DE}}} \leftarrow DE.$FASTREASON$(I_t, task\_prompt)$ {fast, step-wise motion reasoning}
 9:    $I_{t-H_I:t} \leftarrow$ IMGBUF.LAST(H_I)
10:    $q_{t-H_I:t} \leftarrow$ STATEBUF.LAST(H_I)
11:    $A^0_{t:t+H_A} \leftarrow AE.$SAMPLEDENOISE$(I_{t-H_I:t}, q_{t-H_I:t}, h_t^{DE}; \text{horizon} = H_A)$
12:    ROBOTCONTROLLER.STEP$(A^0_{t:t+H_A})$
13:    $I_t \leftarrow$ GETCURRENTIMAGE()
14:    $q_t \leftarrow$ GETROBOTSTATE() {update observations}
15:    IMGBUF.PUSH(I_t)
16:    STATEBUF.PUSH(q_t) {update buffer}
17:    $t \leftarrow t + 1$
18: **end while**
19: STOPROBOT()

B.1. Dataset Composition.

Our SFT dataset for training the domain expert consists of 279.6K demonstrations collected in-house, 678K robotic data curated from Robo2VLM (Chen et al., 2025a), and 318K general knowledge samples open-sourced from the internet. The detailed composition of each dataset is summarized in Table 5.

Table 5. Composition of the dataset employed for supervised fine-tuning.

Domain	Dataset	Size
Robotics	Cube Stacking	32.2K
	Peg-in-Hole	45.3K
	L-tool Pull	76.9K
	Pick & Place: Eggplant	11.0K
	Pick & Place: Carrot	10.0K
	Pick & Place: Corn	9.8K
	Table Bussing	94.4K
	Robo2VLM*	678.0K
General VQA	FigureQA	100.0K
	CLEVR	70.0K
	ScienceQA	5.0K
	ScienceQA(nona context)	19.2K
	Hateful-memes	8.5K
	Visual-7W	14.4K
	Visual Spatial Reasoning	2.2K
	TallyQA	98.7K

B.2. Motion Decomposition Benchmark

In this section, we compare the reasoning performance of the domain expert in MoTVLA with that of the Bagel VLM 7B, which is fine-tuned on the same motion decomposition dataset as ours, as reported in Table 6.

Table 6. **Motion decomposition benchmark between domain expert of MoTVLA and finetuned Bagel VLM 7B.**

		BLEU	CIDEr	METEOR	Token Accuracy
Pick & Place: Eggplant	Finetuned Bagel VLM	0.9741	8.9250	0.6385	89.40
	Domain Expert of MoTVLA	0.8837	8.6153	0.6303	90.13
Pick & Place: Carrot	Finetuned Bagel VLM	0.8252	8.3441	0.5921	82.70
	Domain Expert of MoTVLA	0.8435	7.9218	0.5835	88.47
Pick & Place: Corn	Finetuned Bagel VLM	0.8940	9.2152	0.6787	91.58
	Domain Expert of MoTVLA	0.8081	7.8534	0.5785	82.53
Table Bussing	Finetuned Bagel VLM	0.9727	9.7389	0.7841	98.40
	Domain Expert of MoTVLA	0.9018	8.6035	0.6678	92.47
Table Bussing Reverse	Finetuned Bagel VLM	0.9334	9.3886	0.7383	94.35
	Domain Expert of MoTVLA	0.9086	8.9802	0.6794	95.59

From Table 6, it can be observed that the fine-tuned Bagel VLM 7B and the domain expert of MoTVLA each exhibit complementary strengths. However, we would like to mention that the performance of Bagel VLM is associated with the cost of suffering from catastrophic forgetting in terms of the general intelligence after the fine-tuning, as we discussed in Section 4.2.

B.3. Tasks and Motion Annotation.

In this section, we elaborate on the demonstration tasks and corresponding motion annotation.

Object relocation with stability (Cube Stacking).   The robot must pick up a red cube, stack it on a green cube, and release without the stack falling. *Motion decomposition:* (i) "Move toward the red cube." (ii) "Pick up the red cube." (iii) "Move it to green cube." (iv) "Stack the red cube on top of the green cube."

Tight-tolerance insertion (Peg–in–Hole).   The robot must pick up an orange–white peg and insert the orange end into a box with a hole. To increase the difficulty, we manually augment the scene with distractions (a blue solid marker and a red dot marker). to the default setting. *Motion decomposition:* (i) "Move to the location of the peg on the table." (ii) "Pick up the peg from the table." (iii) "Move to the box with the hole." (iv) "Insert the orange end of the peg into the box."

Tool-mediated manipulation beyond reach (L-tool Pull).   The robot must grasp an L-shaped tool and use it to pull a cube that lies beyond the arm's direct reach. To increase the difficulty, we manually augment the scene with distractions (a green sphere and a white socket). *Motion decomposition:* (i) "Move the robot's end effector to the position of the tool on the table." (ii) "Pick up the tool from the table." (iii) "Use the tool to pull the cube that is out of reach."

Tool-mediated pull and place beyond reach (Ambiguous Instruction).   The robot must grasp an L-shaped tool and use it to pull a cube located beyond the arm's direct reach. Afterward, it drops the tool to the side, picks up the cube, and places it at the designated destination. *Motion decomposition:* (i) "Move the robot's end effector to the position of the tool on the table." (ii) "Pick up the tool from the table." (iii) "Use the tool to pull the cube that is out of reach." (iv) "Move to the cube and pick it up." (v) "Place the cube into the bin."

Table Bussing (Ambiguous Instruction).   The scene contains one *rubbish* item (an empty soda can), two *fruit* items (an apple and a banana), and two markers (ellipse). Since the instruction prompt does not explicitly specify which objects are rubbish, the model must interpret the instruction, ground the object categories, and generate a correct motion decomposition and execution order. *Ambiguous instruction:* "Place the garbage on the red ellipse and put all the other objects on the blue ellipse." *Motion decomposition:* (i) "Move to the can." (ii) "Pick up the can and place it on the red ellipse." (iii) "Move to the yellow banana." (iv) "Pick up the banana and place it on the blue ellipse." (v) "Move to the red apple." (vi) "Pick up the apple and place it on the blue ellipse."

Table Bussing Reverse (Ambiguous Instruction).   The scene is the same as in the previous Table Bussing task; however, the execution order is reversed. *Ambiguous instruction:* "Place all the fruits on the blue ellipse and put the garbage on the red ellipse." *Motion decomposition:* (i) "Move to the red apple." (ii) "Pick up the apple and place it on the blue ellipse." (iii) "Move to the yellow banana." (iv) "Pick up the banana and place it on the blue ellipse." (v) "Move to the can. (vi) "Pick up the can and place it on the red ellipse."

Real World Single-stage Pick-and-Place (Vegetables → Basket).   The robot must pick up a vegetable and place it into the basket. *Motion decomposition:* (i) "Move toward the {place_holder}." (ii) "Grasp the {place_holder} (iii) Move it toward the basket." (iv) "Put the {place_holder} in the basket." *Note:* {place_holder} corresponds to one of {corn, eggplant, carrot}; During the evaluation phase, we introduce three additional tasks containing distractions (a potato and a random cube) in the scene and assess the zero-shot performance.

Real World Table Bussing (Ambiguous Instruction).   The scene contains two *rubbish* items (an empty soda can and a snack bag), one *other* item (a cucumber), a yellow box, and a basket. Since the instruction prompt does not explicitly specify which objects are rubbish, the model must interpret the instruction, ground the object categories, and generate a correct motion decomposition and execution order.

- *Ambiguous instruction:* "Sort the rubbish into the box." *Motion decomposition:* (i) "Move toward the empty soda can." (ii) "Pick up the empty soda can." (iii) "Place into the rubbish box." (iv) "Move toward the snack bag." (v) "Pick up the snack bag." (vi) "Place into the rubbish box."

- *Clear instruction:* "Put the green cucumber into the basket." *Motion decomposition:* (i) "Move toward the cucumber." (ii) "Pick up the cucumber (iii) "Place it into the basket."

We collect 300 and 100 expert demonstrations for each short- and long-horizon task in simulation, respectively, 50 demonstrations for each real-world vegetable pick-and-place task (150 in total), and 100 demonstrations for each real-world table-bussing task (200 in total). Each demonstration is segmented into *motion decompositions* with aligned textual descriptions. We illustrate two concrete instances in Fig.5 and Fig.6. All training samples were collected using seeds ranging from 0 to the total number of trajectories (e.g., seeds 0–300 for the Peg-in-Hole task). Each seed triggers randomization of the object positions on the table and initializes the Gaussian noise for the diffusion policy through the interface functions in our codebase. Furthermore, all baselines are trained on the identical datasets, with language input provided only to methods that initially support text conditioning. Notably, to ensure accurate and semantically consistent annotations while maintaining a relatively balanced number of samples for each motion type, we adopt the following motion merging strategy during the training. For pick and place tasks, we omit the "move toward" motion and merge "pick up" and "place into," since "place into" inherently contains the semantic meaning of "move toward." Otherwise, "place into" would represent only a very short motion segment with an extremely small number of data samples. In contrast, for tasks involving more distinct terminating motions, such as "insert a peg into a hole" or "pull a cube with a tool," we retain the "move toward" motion and merge it with pick up," as they are often performed simultaneously by the robotic arm, making it difficult to define a clear boundary between them, while keeping the final motion independent. This design helps mitigate potential overfitting to any dominant single motion pattern.

B.4. Language Steerability of MoTVLA.

To evaluate the language steerability of MoTVLA, we tested a checkpoint trained on scenes containing only a single object (either an apple or a banana). During inference, we placed both objects together and provided object-specific prompts to assess whether the model could correctly follow the instructions. For each test prompt, we conducted 20 trials using unseen seeds. The results are shown in Table 7.

Table 7. **Language steerability evaluation of MoTVLA.**

Metric	Prompt: Put the red apple on the white ellipse.	Prompt: Put the yellow banana on the white ellipse.
Success Rate	0.90	0.95

Although the visual zero-shot setup prevents MoTVLA from achieving perfect performance, the relatively high success rates demonstrate its strong language steerability, successfully picking and placing the instructed objects based on the given prompts. Additional qualitative results are provided on our website.

```
Human:<\General>
"Is the peg inserted into the yellow
box? Provide the conclusion with a
simple reason.""

MoTVLA(SLow): No, the peg is not
inserted into the yellow box. The peg
is positioned outside the box,
resting on the surface of the table.
```

```
Human:<\Domain>
"Your meta task is: Pick up a orange-white peg and
insert the orange end into the box with a hole in
it."

MoTVLA(Fast): Move to the location of the peg on
the table.

                    •  •  •

MoTVLA(Fast): Pick up the peg from the table.

                    •  •  •

MoTVLA(Fast): Move to the box with the hole.

                    •  •  •

MoTVLA(Fast): Insert the orange end of the peg into
the box.
```

Figure 5. **A slow and fast reasoning annotation example of MoTVLA in the simulative environment.**

```
Human:<\General>
"Please determine whether the
green cucumber in the image
should be classified as
rubbish."

MoTVLA(SLow): The green
cucumber in the image should
not be classified as rubbish.
It is a fresh vegetable and
can be used for cooking or
eating.
```

```
Human:<\Domain>
"Your meta task is: Sort the rubbish into the
box."

MoTVLA(Fast): Move toward the empty soda can.
```

```
                    • • •

MoTVLA(Fast): Pick up the empty soda can.
```

```
                    • • •

MoTVLA(Fast): Place into the rubbish box.
```

```
                    • • •

MoTVLA(Fast): Move toward the snack bag.
```

```
                    • • •

MoTVLA(Fast): Pick up the snack bag.
```

```
                    • • •

MoTVLA(Fast): Place into the rubbish box.
```

Figure 6. **A slow and fast reasoning annotation example of MoTVLA in the real-world environment.**