BENCHMARKING OFFLINE REINFORCEMENT LEARNING ON REAL-ROBOT HARDWARE

ABSTRACT

Learning policies from previously recorded data is a promising direction for real-world robotics tasks, as online learning is often infeasible. Dexterous manipulation in particular remains an open problem in its general form. The combination of offline reinforcement learning with large diverse datasets, however, has the potential to lead to a breakthrough in this challenging domain analogously to the rapid progress made in supervised learning in recent years. To coordinate the efforts of the research community toward tackling this problem, we propose a benchmark including: i) a large collection of data for offline learning from a dexterous manipulation platform on two tasks, obtained with capable RL agents trained in simulation; ii) the option to execute learned policies on a real-world robotic system and a simulation for efficient debugging. We evaluate prominent open-sourced offline reinforcement learning algorithms on the datasets and provide a reproducible experimental setup for offline reinforcement learning on real systems. Visit `https://sites.google.com/view/benchmarking-offline-rl-real` for more details.

1 INTRODUCTION

Reinforcement learning (RL) (Sutton et al., 1998) holds great potential for robotic manipulation and other real-world decision-making problems as it can solve tasks autonomously by learning from interactions with the environment. When data can be collected during learning, RL in combination with high-capacity function approximators can solve challenging high-dimensional problems (Mnih et al., 2015; Lillicrap et al., 2016; Silver et al., 2017; Berner et al., 2019). However, in many cases online learning is not feasible because collecting a large amount of experience with a partially trained policy is either prohibitively expensive or unsafe (Dulac-Arnold et al., 2020). Examples include autonomous driving, where suboptimal policies can lead to accidents, robotic applications where the hardware is likely to get damaged without additional safety mechanisms, and collaborative robotic scenarios where humans are at risk of being harmed.

Offline reinforcement learning (offline RL or batch RL) (Lange et al., 2012) tackles this problem by learning a policy from prerecorded data generated by experts or handcrafted controllers respecting the system's constraints. Independently of how the data is collected, it is essential to make the best possible use of it and to design algorithms that improve performance with the increase of available data. This property has led to unexpected generalization in computer vision (Krizhevsky et al., 2012; He et al., 2016; Redmon et al., 2016) and natural language tasks (Floridi & Chiriatti, 2020; Devlin et al., 2018) when massive datasets are employed. With the motivation to learn similarly capable decision-making systems from data, the field of offline RL has gained considerable attention. Progress is currently measured by benchmarking algorithms on simulated domains, both in terms of data collection and evaluation.

Yet, real-world data differs from simulated data qualitatively and quantitatively in several aspects (Dulac-Arnold et al., 2020). First, observations are noisy and sometimes faulty. Second, real-world systems introduce delays in the sensor readings and often have different sampling rates for different modalities. Third, the action execution can also be delayed and can get quantized by low-level hardware constraints. Fourth, real-world environments are rarely stationary. For instance, in autonomous robotics, battery voltages might drop, leading to reduced motor torques for the same control command. Similarly, thermal effects change sensor readings and motor responses. Abrasion

Figure 1: **The TriFinger manipulation platform (Wüthrich et al., 2021; Bauer et al., 2022).** Left: The robot has 3 arms with 3 DoF each. The cube object is constrained by a bowl-shaped arena, allowing for unattended data collection. Right: A cluster of these robots for parallel data collection and evaluation.

changes friction behavior and dust particles can change object appearances and sensing in general. Fifth, contacts are crucial for robotic manipulation but are only insufficiently modeled in current physics simulations, in particular for soft materials. Lastly, physical robots have individual variations.

Since real-world data is different from simulated data, it is important to put offline RL algorithms to the test on real systems. We propose challenging robotic manipulation datasets recorded on real robots for two tasks: object pushing and object lifting with reorientation on the TriFinger platform (Wüthrich et al., 2021). To study the differences between real and simulated environments, we also provide datasets collected in simulation. Our benchmark of state-of-the-art offline RL algorithms on these datasets reveals that they are able to solve the moderately difficult pushing task while their performance on the more challenging lifting task leaves room for improvement. In particular, there is a much larger gap between the performance of the expert policy and offline-learned policies on the real system compared to the simulated system. This underpins the importance of real-world benchmarks for offline RL. We furthermore study the impact of adding suboptimal trajectories to expert data and find that all algorithms are 'distracted' by them, i.e., their success rate drops significantly. This identifies an important open challenge for the offline RL community: robustness to suboptimal trajectories.

Importantly, a cluster of TriFinger robots is set up for evaluation of offline-learned policies for which remote access can be requested for research purposes. With our dataset and evaluation platform, we therefore aim to provide a breeding ground for future offline RL algorithms.

2 THE TRIFINGER PLATFORM

We use a robot cluster to collect the dataset and test the policies. The cluster was initially developed and build for the *Real Robot Challenge* in 2020 and 2021 (Bauer et al., 2022). The robots that constitute the cluster are an industrial-grade adaptation of a robotic platform called TriFinger, an open-source hardware and software design introduced in Wüthrich et al. (2021), see Fig. 1. The robots have three arms mounted at a 120 degrees radially symmetric arrangement with 3 degrees of freedom (DoF) each. The arms are actuated by outrunner brushless motors with a 1:9 belt-drive, yielding high agility, low friction, and good force feedback (details on the actuator modules can be found in Grimminger et al. (2020)). Pressure sensors inside the elastic fingertips provide basic tactile feedback. The working area, where objects can be manipulated, is encapsulated by a high barrier to ensure that the object stays inside the arena even during aggressive motions. This is essential for operation without human supervision. The robot is inside a closed housing that is well lit by top-mounted LED panels making the images taken by three high-speed global shutter cameras consistent. The cameras are distributed between the arms to ensure objects are always seen by any camera. We study dexterous manipulation of a cube whose pose is estimated by a visual tracking system with 10 Hz.

To abstract away the low-level details, we developed a software with a simple Gym (Brockman et al., 2016) interface in Python that can interact with the robots at a maximal rate of 1 kHz in position control or torque control mode (see (Wüthrich et al., 2021) for details). We use a control frequency of 50 Hz and torque control for this work. We have a custom object tracking tool to provide position and orientation of a single colored cube in the environment, allowing algorithms to work without visual input.

Figure 2: **Overview of our approach.** Policies are trained with domain randomization in a parallel simulation using Isaac Gym (Makoviychuk et al., 2021) and then deployed in the PyBullet (Coumans & Bai, 2016) simulation and on the real system without fine-tuning to collect the datasets. We train state-of-the-art offline RL algorithms on these datasets and evaluate them on the respective system, i.e, the simulator or the real-robot cluster.

On top of this interface, we have developed a submission system that allows users to submit *jobs* to a cluster of these robots for unattended remote execution. This setup was specifically adapted for ease of use in the offline RL setting and was extensively tested. We will provide researchers with access to the robot cluster, which will allow them to evaluate the policies they trained on the dataset proposed herein. To ease development and study the fundamental differences between simulated and real world data, we provide a corresponding simulated environment using PyBullet (Coumans & Bai, 2016).

To summarize, the hardware and software have the following three key properties: i) physically capable of dexterous manipulation; ii) robust enough for running and evaluating learning methods, and iii) easy to use (robot hardware and simulator) and integrated in existing code frameworks.

3   THE TRIFINGER DATASETS

We consider two tasks that involve a colored cube: pushing the cube to a target location and lifting the cube to a desired location and orientation. To create behavioral datasets for these tasks on the TriFinger platform, we need expert policies, which we obtain using reinforcement learning in a parallel simulation environment with domain randomization. Figure 2 visualizes the entire procedure – from training to data collection to offline learning. In this section, we describe the tasks and the data collection while Sec. 4 is dedicated to benchmarking offline RL algorithms on the collected data.

3.1   DEXTEROUS MANIPULATION TASKS

We consider two tasks on the TriFinger platform that require dexterous manipulation of a cube:

Push   The goal is to move the cube to a target location on the ground of the arena. This task does not require the agent to align the orientation of the cube; the reward is based only on the desired and the achieved position.

Lift   The cube has to be picked up and moved to a target pose in the air which includes position and orientation. This requires flipping the cube on the ground, obtaining a stable grasp, lifting it to a target location and rotating it to match the target orientation.

Following prior work (Hwangbo et al., 2019; Allshire et al., 2021) we define the reward by applying a logistic kernel $k(x) = (b + 2)\left(\exp(a\|x\|) + b + \exp(-a\|x\|)\right)^{-1}$ to the difference between desired and achieved position (for the Push task) or the desired and achieved corner points of the cube (for the Lift task). The parameters a and b control the length scale over which the reward decays and how sensitive it is for small distances x, respectively. This yields a smooth, dense and bounded reward, see Appendix B.3 for details. We define success in the pushing task as reaching the goal position with a tolerance of 2 cm. For the lifting task we additionally require to not deviate more than 22 degrees from the goal orientation.

We note that pushing is more challenging than it may appear due to inelastic collisions between the soft fingertips and the cube which are not modeled in rigid body physics simulators. Furthermore, the performance of policies can be quite sensitive to the value of sliding friction. Lifting is, however, even more challenging as flipping the cube based on a noisy object-pose with a low refresh rate is error-prone, learning the right sequence of behaviors requires long-term credit assignment and dropping the cube often results in loosing all progress in an episode.

3.2 TRAINING EXPERT POLICIES

We train expert policies with online RL in simulation which we then use for data collection on the real system (Fig. 2). We build on prior work which achieved sim-to-real transfer for a dexterous manipulation task on the TriFinger platform (Allshire et al., 2021). This approach replicates the real system in a fast, GPU-accelerated rigid body physics simulator (Makoviychuk et al., 2021) and trains with an optimized implementation (Makoviichuk & Makoviychuk, 2022) of Proximal Policy Optimization (Schulman et al., 2017) with a high number of parallel actors. We furthermore adopt their choice of a control frequency of 50 Hz and use torque control to enable direct control of the fingers. The sensor input is the proprioceptive sensor information and the object pose. In order to obtain policies that are robust enough to work on the real system, domain randomization (Tobin et al., 2017; Mandlekar et al., 2017; Peng et al., 2018) is applied: for each episode, physics parameters like friction coefficients are sampled from a distribution that is likely to contain the parameters of the real environment. Additionally, noise is added to the observations and actions to account for sensor noise and the stochasticity of the real robot. Furthermore, random forces are applied to the cube to obtain a policy that is robust against perturbations, as in (Andrychowicz et al., 2020). The object and goal poses are represented by keypoints, i.e., the Cartesian coordinates of the corners of the cube. This choice was empirically shown to accelerate training compared to separately encoding position and orientation in Cartesian coordinates and a quaternion (Allshire et al., 2021).

To improve the robustness of the trained policies across the different robot instances and against other real-world effects like tracking errors due to accumulating dust, we modified the implementation of Allshire et al. (2021) in several ways. While the original code correctly models the 10 Hz refresh rate of the object pose estimate, we found it beneficial to also simulate the delay between the time when the camera images are captured and when they are provided to the agent. This delay typically ranges between 100 ms and 200 ms. We furthermore fully randomize the initial orientation of the cube and use a hand-crafted convex decomposition of the barrier collision mesh to avoid artifacts of the automatic decomposition, to which the policy can overfit. For the pushing task we penalized rapid changes in the cube position and orientation as sliding and flipping the cube transfers less well to the real system than moving it in a slow and controlled manner. We observed that policies trained with RL in simulation tend to output oscillatory actions, which does not transfer well to the real system and causes stronger wear effects (Mysore et al., 2021). To avoid this, we penalized changing the action which led to smoother movements and better performance. For the Lift task we additionally consider a policy which was trained with an Exponential Moving Average on the actions as we observed that vibrations on the real robot can lead to slipping and dropping (see Fig. S10 (b)). These vibrations might be caused by elastic deformations of the robot hardware and the complex contact dynamics between the soft fingertips and the cube that are not modeled in simulation. As also observed in Wang et al. (2022), the performance on the real system varies significantly with training seeds. We evaluated 20 seeds on the real system and used the best one for data collection. More details on training in simulation can be found in the Appendix C.1.

3.3 DATA COLLECTION

We collected data for the pushing and lifting tasks both in a PyBullet (Coumans & Bai, 2016) simulation (Joshi et al., 2020) and on the real system, as shown in Fig. 2. To ensure that the data collection procedures are identical, we run the same code with the simulator backend and with the real-robot backend on six TriFinger platforms (Fig. 1). We observed that policies learned in simulation struggle with retrieving the cube from the barrier on the real robot[1]. To alleviate this problem, we employ a predefined procedure to push the cube away from the barrier between episodes.

---

[1]Possibly because the object tracking performance is slightly worse at the barrier or the dynamics of the outstretched fingers aligns less well between simulation and reality.

Figure 3: **An example behavior of our expert policy on the lifting task.** The robot is grasping and reorienting the object to reach the desired target location and orientation (transparent cube).

Figure 4: **Dataset visualization**. Initial cube positions (blue) and goals (red) in the real datasets for the Push task (left) and Lift task (right). Note that we avoid initial positions close to the barrier.

The resulting starting positions together with the target positions are visualized in Fig. 4. During data collection, self-tests are performed at regular intervals to ensure that all robots are fully functional. Before the recording of each dataset the platforms were cleaned from particle dust to ensure consistent object tracking performance.

For the dataset to be useful to the community, it should be possible to evaluate offline-learned policies on the real robots. As machine learning models can be computationally demanding, we wait for a fixed time interval between receiving a new observation and starting to apply the action based on this observation. This time budget is allocated for running the policy without deviating from the control frequency used for data collection. We choose 10 ms for the Push task and 2 ms for the Lift task as we found training with bigger delays difficult. Note that our expert policies run in less than 1 ms.

We provide as much information about the system as possible in the observations. The robot state is captured by joint angles, angular velocities, recorded torques, fingertip forces, fingertip positions, fingertip velocities (both obtained via forward kinematics), and the ID of the robot. The object pose is represented by a position, a quaternion encoding orientation, the keypoints, the delay of the camera images for tracking and the tracking confidence. The observation additionally contains the last action, which is applied during the fixed delay between observation and action. The desired and achieved goal are also included in the observation and contain either a position for the Push task or keypoints for the Lift task. Some observations provide redundant information; however, we believe this simplifies working with the datasets, as we provide user-friendly Python code that implements filtering as well as automatically converting observations to a flat array. Moreover, we additionally publish a version of each dataset with camera images from three viewpoints. We believe that directly learning from these image datasets is an exciting challenge for the community[2] and that they are moreover interesting in their own right as a large collection of robotic manipulation video footage.

For each task we consider pure expert data (Expert), mixed data recorded with a range of training checkpoints (Mixed), a combination of of 50% expert trajectories and 50% trajectories recorded with a weaker policy with additive Gaussian noise on the actions (Weak&Expert) and the 50% expert data in Weak&Expert (Half-Expert). We run the same policies in simulation and on the real system. An exemplary expert behavior for the Lift task is shown in Fig. 3. Episodes last for 15 s for the Push task and 30 s for the Lift task as reorienting, grasping and lifting the cube requires more time. For the Push task, we collect 16 h of interaction for each dataset, corresponding to 3840 episodes and 2.8 million transitions. For the more demanding Lift task, we collect 20 h of robot interactions corresponding to 2400 episodes and 3.6 million transitions. The Half-Expert datasets contain the expert data that is included in the corresponding Weak&Expert datasets to isolate the effects of reducing the amount

---

[2] At the time of writing we cannot benchmark on these datasets since the robot cluster does not provide GPU-access at the moment. This will likely change in the near future.

Table 1: **Pushing: Success rate on the TriFinger-Push Datasets.** 'data' denotes the mean over the dataset. Average and standard deviation over five training seeds. A star * indicates significance w.r.t. all other methods using Welch's t-test with $p < 0.05$.

Push-Datasets	data	BC	CRR	AWAC	CQL	IQL
Sim-Expert	0.95	0.90 ± 0.03	0.90 ± 0.06	$\mathbf{0.97 \pm 0.02}$	0.05 ± 0.04	0.87 ± 0.05
Sim-Half-Expert	0.95	0.75 ± 0.11	$\mathbf{0.83 \pm 0.08}$	$\mathbf{0.83 \pm 0.09}$	0.05 ± 0.06	0.66 ± 0.1
Sim-Weak&Expert	0.53	0.51 ± 0.06	$\mathbf{0.81 \pm 0.10}$	0.75 ± 0.11	0.16 ± 0.07	0.73 ± 0.05
Sim-Mixed	0.76	0.55 ± 0.07	0.13 ± 0.13	$\mathbf{0.85 \pm 0.11}^*$	0.02 ± 0.04	0.65 ± 0.04
Real-Expert	0.92	0.74 ± 0.05	$\mathbf{0.87 \pm 0.07}$	0.80 ± 0.03	0.54 ± 0.13	0.75 ± 0.08
Real-Half-Expert	0.92	0.66 ± 0.08	$\mathbf{0.78 \pm 0.04}$	0.76 ± 0.10	0.48 ± 0.08	0.70 ± 0.08
Real-Weak&Expert	0.51	0.48 ± 0.10	$\mathbf{0.84 \pm 0.06}^*$	0.69 ± 0.06	0.14 ± 0.04	0.68 ± 0.05
Real-Mixed	0.49	0.29 ± 0.06	0.30 ± 0.06	0.61 ± 0.09	0.02 ± 0.02	$\mathbf{0.66 \pm 0.08}$

of expert data and adding suboptimal trajectories. The average success rates are provided next to the offline learning results in Table 1 and 2 (see *data* column). In Appendix B, we give a detailed analysis along with a specification (Table S4) and statistics (Table S5) of the offline RL datasets.

4 BENCHMARKING OFFLINE REINFORCEMENT LEARNING ALGORITHMS

We benchmark offline RL algorithms on pairs of simulated and real datasets and study the impact of data quality on their performance. We limit our evaluation to the best algorithms provided in the open-source library d3rlpy (Seno & Imai, 2021) to keep the required robot time for the evaluation of the trained policies manageable. Namely, we benchmark the following algorithms: BC (Bain & Sammut, 1995; Pomerleau, 1991; Ross et al., 2011; Torabi et al., 2018), CRR (Wang et al., 2020), AWAC (Nair et al., 2020), CQL (Kumar et al., 2020), and IQL (Kostrikov et al., 2021b). We report results for two sets of hyperparameters: The default values (except for CQL for which we performed a grid search on Push-Sim-Expert as the default parameters did not learn) and the results of a grid search on Lift-Sim-Weak&Expert (marked by †). Details about the hyperparamters and their optimization are in Appendix C.3. We think that the performance at the default hyperparameters is highly relevant for offline RL on real data as optimizing the hyperparameters without a simulator is often infeasible.

4.1 RESULTS

We train with five different seeds for each algorithm and evaluate with a fixed set of randomly sampled goals. Details about the policy evaluation on the simulated and real set-up can be found in Appendix D. We report success rates in the main text and returns in Appendix A.

The benchmarking results for the Push task are summarized in Table 1. Most of the offline RL algorithms perform well but the performance on the real data is generally worse. An exception to this pattern is CQL which performs poorly on the simulated Push task and gains some performance on the real data, perhaps due to the broader data distribution of the stochastic real-world environment. As expected BC performs well on the expert datasets but cannot exceed the dataset success rate on the Weak&Expert data, unlike CRR, AWAC, and IQL. On the expert data, CRR and AWAC match the performance of the expert policy in simulation but fall slightly behind on the real data. Interestingly, the performance of CRR is not negatively impacted by weak trajectories (84% on Real-Weak&Expert compared to 78% on Real-Half-Expert, where the latter only contains the expert data portion). We provide insights into how the behavior policy compares to an offline-trained policy for the Push task in Fig. 6 (b) and (c).

The more challenging Lift task separates the algorithms more clearly as summarized in Table 2. CQL does not reach a non-zero success rate at all, despite our best efforts to optimize the hyperparameters (see Appendix C.3). This is in line with the results reported in Mandlekar et al. (2021) where CQL failed to learn on the datasets corresponding to more complex manipulation tasks. Kumar et al. (2021b) furthermore discusses the sensitivity of CQL to the choice of hyperparameters, especially on robotic data. While the best algorithms can match the performance of the expert on Lift-Sim-Expert, they fall short of reaching the dataset success rate on the real-robot data (Lift-Real-Expert). On the Real-Smooth-Expert dataset the success rates are, on average, slightly lower, probably due to the non-Markovian behavior policy. The returns are generally higher, however, likely due to the smoothed expert reaching higher returns (see Table S2).

Table 2: **Lifting: Success rate on the TriFinger-Lift Simulation Dataset.** 'data' denotes the mean over the dataset. Average and standard deviation over five training seeds. Experiments with hyperparameters optimized on Sim-Weak&Expert are marked with a †. Stars * and ** indicate significance w.r.t. second best Welch's t-test with $p < 0.05$ and $p < 0.01$, respectively.

Lift-Datasets	data	BC	CRR	AWAC	CQL	IQL
Sim-Expert	0.87	0.68 ± 0.12	0.79 ± 0.09	$\mathbf{0.81 \pm 0.02}$	0.00 ± 0.00	0.37 ± 0.10
Sim-Half-Expert	0.88	0.52 ± 0.05	$\mathbf{0.71 \pm 0.12}$	0.68 ± 0.05	0.00 ± 0.00	0.04 ± 0.06
Sim-Weak&Expert	0.50	0.19 ± 0.06	0.41 ± 0.34	$\mathbf{0.55 \pm 0.10}$	0.00 ± 0.00	0.23 ± 0.10
Sim-Mixed	0.68	0.03 ± 0.04	0.21 ± 0.11	$\mathbf{0.36 \pm 0.07}$	0.00 ± 0.00	0.00 ± 0.00
Sim-Expert†	0.87	0.79 ± 0.10	$\mathbf{0.85 \pm 0.05}$	0.82 ± 0.09	0.00 ± 0.00	$\mathbf{0.85 \pm 0.05}$
Sim-Half-Expert†	0.88	0.60 ± 0.03	0.70 ± 0.09	0.72 ± 0.10	0.00 ± 0.00	$\mathbf{0.75 \pm 0.11}$
Sim-Weak&Expert†	0.50	0.41 ± 0.06	$\mathbf{0.63 \pm 0.07}$	0.42 ± 0.13	0.00 ± 0.00	0.57 ± 0.04
Sim-Mixed†	0.68	0.01 ± 0.02	0.19 ± 0.10	$\mathbf{0.36 \pm 0.11}$	0.00 ± 0.00	0.00 ± 0.00
Real-Smooth-Expert	0.64	0.26 ± 0.09	$\mathbf{0.52 \pm 0.12}^*$	0.34 ± 0.04	0.00 ± 0.00	0.24 ± 0.03
Real-Expert	0.66	0.27 ± 0.09	$\mathbf{0.57 \pm 0.07}^{**}$	0.24 ± 0.04	0.00 ± 0.00	0.29 ± 0.09
Real-Half-Expert	0.68	0.15 ± 0.01	$\mathbf{0.38 \pm 0.08}^{**}$	0.12 ± 0.08	0.00 ± 0.00	0.12 ± 0.06
Real-Weak&Expert	0.40	0.02 ± 0.04	$\mathbf{0.17 \pm 0.09}$	0.03 ± 0.06	0.00 ± 0.00	0.11 ± 0.13
Real-Mixed	0.42	0.00 ± 0.01	$\mathbf{0.18 \pm 0.07}^{**}$	0.02 ± 0.01	0.00 ± 0.00	0.03 ± 0.02
Real-Expert†	0.66	0.28 ± 0.04	$\mathbf{0.54 \pm 0.09}$	0.31 ± 0.04	0.00 ± 0.00	0.48 ± 0.07
Real-Half-Expert†	0.68	0.25 ± 0.07	$\mathbf{0.37 \pm 0.09}$	0.36 ± 0.06	0.01 ± 0.01	0.30 ± 0.06
Real-Weak&Expert†	0.40	0.09 ± 0.04	$\mathbf{0.29 \pm 0.07}^*$	0.12 ± 0.06	0.00 ± 0.00	0.15 ± 0.03
Real-Mixed†	0.42	0.00 ± 0.00	$\mathbf{0.18 \pm 0.04}^{***}$	0.01 ± 0.01	0.00 ± 0.00	0.02 ± 0.01

Figure 5: **Success rates during offline RL training on the simulated Lift task.** The black dashed line indicates the performance of the expert dataset, and the red dashed line depicts average success rate of the Weak&Expert dataset. Shaded areas indicate the interval between the 0.25 and 0.75 quantiles. Learning curves for all experiments are shown in Appendix A.4.

On the Lift-Weak&Expert datasets all algorithms perform significantly worse than on the expert data. This effect is most pronounced on the real robot data and calls the ability of the algorithms to make good use of the 50% expert trajectories into question. To verify that the performance drop is not due to only half of the expert data being available, we also train solely on the expert trajectories contained in the Weak&Expert dataset. We refer to this dataset as Half-Expert. We find that the resulting policy performs significantly better, ruling out that the performance drop on the Lift-Weak&Expert dataset is exclusively caused by a lack of data. Fig. 5 shows that this is true for the simulated Lift datasets as well. We conclude that the benchmarked offline RL algorithms still exhibit BC-like behavior, i.e., they are distracted by suboptimal data. Their poor performance on the Mixed datasets further underpins their reliance on imitation of a consistent expert as all algorithms struggle to learn from the data collected by a range of training checkpoints (see tables 1 and 2 and learning curves in section A.4).

The Lift datasets, in particular those recorded on the real robots, generally contain more useful sub-trajectories than apparent from the success rate, which is defined as achieving the goal pose *at the end* of an episode. For example, during 87% of all episodes in the Lift-Real-Expert dataset the goal pose is achieved *at some point* but the best algorithm CRR achieves a success rate of only 57%. This suggests that these datasets have an untapped potential for trajectory stitching. As the observations are furthermore noisy and do not contain estimates of the velocity of the cube, training recurrent policies could potentially lead to an increase in performance.

Figure 6: **Analysis of policy behavior.** (a) Success rate for simulated lifting for varying relative environment noise scales (1.0 corresponds to the noise level of the real system) when the algorithms were trained on data recorded with that noise scale using the expert policy. The dashed lines indicate the performance on the real system. (b) Average speed of the cube over a pushing episode on the real system. Some offline RL algorithms learn to move the cube faster than the expert. (c) Momentary success during a pushing episode on the real system: the fraction of episodes during which the goal was achieved at a given point in time (trained on expert data).

To investigate the impact of noise on the performance of offline RL policies and the expert, we collected datasets in simulation for up to twice the noise amplitudes measured on the real system. Fig. 6 (a) shows that the performance of the expert and the offline RL policies degrades only slowly when increasing the noise scale, ruling out that noise is the sole explanation for the performance gap between simulated and real system. As delays in the observation and action execution are already implemented in the simulated environment, we conclude that other factors like more complex contact dynamics and elastic deformations of the fingertips and robot limbs are likely causing the larger performance gap between data and learned policies on the real robots.

To test how well the policies learned from the datasets generalize over instances of the robot hardware, we evaluated on a hold-out robot which was not used for data collection. We did not see a significant difference in performance (see Appendix A.3 for details on this experiment) suggesting that the datasets cover enough variations in the robot hardware to enable generalization to unseen robots.

In summary, CRR and AWAC generally perform best on the proposed datasets with IQL also being competitive after hyperparameter optimization. The performance gap between expert and offline RL is in general bigger on the real system, perhaps due to more challenging dynamics.

5 RELATED WORK

Offline RL: The goal of offline RL (Levine et al., 2020; Prudencio et al., 2022) is to learn effective policies without resorting to an online interaction by leveraging large and diverse datasets covering a sufficient amount of expert transitions. This approach is particularly interesting if interactions with the environment are either prohibitively costly or even dangerous.

Offline RL faces a fundamental challenge, known as the Distributional Shift (DS) problem, originating from two sources. There is a distribution mismatch in training, as we use the behavioral data for training, but the learned policy would create a different state-visitation distribution. The second problem is that during policy improvement, the learned policy requires an evaluation of the Q-function on unseen actions (out of distribution). An over-estimation of the Q-value on these out-of-distribution samples leads to learning of a suboptimal policy.

Several algorithmic schemes were proposed for addressing the DS problem: i) constraining the learned policy to be close to the behavior data (Fujimoto et al., 2019; Kumar et al., 2019b; Zhang et al., 2021; Kostrikov et al., 2021a); ii) enforcing conservative estimates of future rewards (Kumar et al., 2020; Yu et al., 2021; Cheng et al., 2022); and iii) model-based methods that estimate the uncertainty via ensembles (Janner et al., 2019; Kidambi et al., 2020).

Additionally, other approaches include: implicitly tackling the DS problem via (advantage-weighted) variants of behavioral cloning (Nair et al., 2020; Wang et al., 2020; Chen et al., 2020; Fujimoto & Gu, 2021) or even completely bypassing it either by removing the off-policy evaluation and performing a constrained policy improvement using an on-policy Q estimate of the behavior policy (Brandfonbrener et al., 2021), or by approximating the policy improvement step implicitly by learning on-data state

value function (Kostrikov et al., 2021b). An orthogonal research line considers combining importance sampling and off-policy techniques (Nachum et al., 2019b;a; Zhang et al., 2020; Xu et al., 2021), and recently (Chen et al., 2021; Janner et al., 2021) investigated learning an optimal trajectory distribution via transformer architectures.

The simplest strategy for learning from previously collected data is behavioral cloning (BC), which is fitting a policy to the data directly. Offline RL can outperform BC: i) on long-horizon tasks with mixed expert data, e.g., equal amount of trajectories collected via an expert and a noisy-expert; and ii) with expert or near expert data, when there is a mismatch between the initial and the deployment state distribution.

RL for dexterous manipulation: Reinforcement learning was recently successfully applied to dexterous manipulation on real hardware (OpenAI et al., 2018; 2019; Allshire et al., 2021; Wang et al., 2022). These results rely on training with online RL in simulation, however, and are consequently limited by the fidelity of the simulator. While domain randomization (Tobin et al., 2017; Mandlekar et al., 2017; Peng et al., 2018) can account for a mismatch between simulation and reality in terms of physics parameters, it cannot compensate oversimplified dynamics. The challenges of real-world environments have been recognized and partly modeled in simulated environments (Dulac-Arnold et al., 2020). To overcome the sim-to-real gap entirely, however, data from real-world interactions is still required, in particular for robotics problems involving contacts.

Offline RL datasets: While offline RL datasets with data from simulated environments, like D4RL (Fu et al., 2020) and RL Unplugged (Gulcehre et al., 2020), have propelled the field forward, the lack of real-world robotics data has been recognized (Behnke, 2006; Bonsignorio & del Pobil, 2015; Calli et al., 2015; Amigoni et al., 2015; Murali et al., 2019). Complex contact dynamics, soft deformable fingertips and vibrations are particularly relevant for robotic manipulation but are not modeled sufficiently well in simulators used by the RL community (Todorov et al., 2012; Makoviychuk et al., 2021; Freeman et al., 2021). Recently, three small real-world datasets with human demonstrations for a robot arm with a gripper (using operational space control) have been proposed (Mandlekar et al., 2021). Two of them require only basic lifting and dropping while the third, more challenging task could not be solved with the available amount of data. For more challenging low-level physical manipulation, a dataset suitable for offline RL is still missing. We therefore provide the first real-robot dataset for dexterous manipulation which is sufficiently large for offline RL (one order of magnitude more data on real robots than prior work (Mandlekar et al., 2021)) and for which learned policies can easily be evaluated remotely on a real-robot platform.

Affordable open-source platforms: Our hardware platform is open source. Other affordable robotic open-source platforms are, for instance, a manipulator (Yang et al., 2019), a simple robotic hand and quadruped (Ahn et al., 2019). Since it is hard to set up and maintain such platforms, we provide access to our real platform upon request, and hope that this will bring the field forward.

Remote benchmarks: For mobile robotics, Pickem et al. (2017) propose the Robotarium, a remotely accessible swarm robotics research platform, and Kumar et al. (2019a) offer OffWorld gym consisting of two navigation tasks with a wheeled robot. Similarly, Duckietown (Paull et al., 2017) hosts the AI Driving Olympics (AI-DO-team, 2022).

6 CONCLUSION

We present benchmark datasets for robotic manipulation that are intended to help improving the state-of-the-art in offline reinforcement learning. To record datasets, we trained capable policies using online learning in simulation with domain randomization. Our analysis and evaluation on two tasks, Push and Lift, show that offline RL algorithms still leave room for improvement on data from real robotic platforms. We identified two factors that could translate into increased performance on our datasets: trajectory stitching and robustness to non-expert trajectories. Further, our analysis indicates that noise and delay alone cannot explain the larger gap between dataset and offline RL performance on real systems, underpinning the importance of real-robot benchmarks.

We invite the offline RL community to train their algorithms with the new datasets and test the empirical performance of the latest offline RL algorithms, e.g. (Kostrikov et al., 2021a; Xu et al., 2021; Kumar et al., 2021b; Cheng et al., 2022), on real-robot hardware.

REPRODUCIBILITY STATEMENT

We publish the datasets we propose as benchmarks (Sections 3.3 and B) and provide access to the cluster of real TriFinger platforms (Section 2) we used for data collection. Submissions to the cluster do not require any robotics training and can be made in the form of a Python implementation of a RL policy (section B.5). A simulated version of the TriFinger platform (Joshi et al., 2020) and a low-cost hardware variant are furthermore publicly available as open source (Wüthrich et al., 2021). For offline RL training we moreover use open-source software (Seno & Imai, 2021). Finally, we describe our hyperparameter optimization in detail and provide the resulting hyperparameters in section C.3.

REFERENCES

Michael Ahn, Henry Zhu, Kristian Hartikainen, Hugo Ponte, Abhishek Gupta, Sergey Levine, and Vikash Kumar. Robel: Robotics benchmarks for learning with low-cost robots. *arXiv preprint arXiv:1909.11639*, 2019.

AI-DO-team. The ai driving olympics (ai-do). `https://www.duckietown.org/research/AI-Driving-olympics`, 2022.

Arthur Allshire, Mayank Mittal, Varun Lodaya, Viktor Makoviychuk, Denys Makoviichuk, Felix Widmaier, Manuel Wüthrich, Stefan Bauer, Ankur Handa, and Animesh Garg. Transferring dexterous manipulation from gpu simulation to a remote real-world trifinger. arXiv, 2021. URL `https://arxiv.org/abs/2108.09779`.

F Amigoni, E Bastianelli, J Berghofer, A Bonarini, G Fontana, N Hochgeschwender, L Iocchi, G Kraetzschmar, P Lima, M Matteucci, P Miraldo, D Nardi, and V Schiaffonati. Competitions for Benchmarking: Task and Functionality Scoring Complete Performance Assessment. *IEEE robotics & automation magazine / IEEE Robotics & Automation Society*, 22(3):53–61, September 2015.

OpenAI: Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Jozefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, et al. Learning dexterous in-hand manipulation. *The International Journal of Robotics Research*, 39(1):3–20, 2020.

Michael Bain and Claude Sammut. A framework for behavioural cloning. In Koichi Furukawa, Donald Michie, and Stephen H. Muggleton (eds.), *Machine Intelligence 15, Intelligent Agents [St. Catherine's College, Oxford, UK, July 1995]*, pp. 103–129. Oxford University Press, 1995.

Stefan Bauer, Manuel Wüthrich, Felix Widmaier, Annika Buchholz, Sebastian Stark, Anirudh Goyal, Thomas Steinbrenner, Joel Akpo, Shruti Joshi, Vincent Berenz, Vaibhav Agrawal, Bernhard Schölkopf, Niklas Funk, Julen Urain De Jesus, Jan Peters, Joe Watson, Claire Chen, Krishnan Srinivasan, Junwu Zhang, Jeffrey Zhang, Matthew R. Walter, Rishabh Madan, Charles Schaff, Takuma Yoneda, Denis Yarats, Arthur Allshire, Ethan K. Gordon, Tapomayukh Bhattacharjee, Siddhartha S. Srinivasa, Animesh Garg, Takahiro Maeda, Harshit Sikchi, Jilong Wang, Qingfeng Yao, Shuyu Yang, Robert McCarthy, Francisco Roldan Sanchez, Qiang Wang, David Cordova Bulens, Kevin McGuinness, Noel O'Connor, and Stephen J. Redmond. Real robot challenge: A robotics competition in the cloud. In Barbara Caputo Douwe Kiela, Marco Ciccone (ed.), *Proceedings of the NeurIPS 2021 Competition and Demonstration Track*, Proceedings of Machine Learning Research. PMLR, 2022. to appear.

Sven Behnke. Robot competitions-ideal benchmarks for robotics research. In *Proc. of IROS-2006 Workshop on Benchmarks in Robotics Research*. Institute of Electrical and Electronics Engineers (IEEE), 2006.

Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. Dota 2 with large scale deep reinforcement learning. *arXiv preprint arXiv:1912.06680*, 2019.

F Bonsignorio and A P del Pobil. Toward Replicable and Measurable Robotics Research [From the Guest Editors]. *IEEE robotics & automation magazine / IEEE Robotics & Automation Society*, 22 (3):32–35, September 2015.

David Brandfonbrener, Will Whitney, Rajesh Ranganath, and Joan Bruna. Offline RL without off-policy evaluation. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 4933–4946, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/274a10ffa06e434f2a94df765cac6bf4-Abstract.html`.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Berk Calli, Aaron Walsman, Arjun Singh, Siddhartha Srinivasa, Pieter Abbeel, and Aaron M Dollar. Benchmarking in Manipulation Research: The YCB Object and Model Set and Benchmarking Protocols. arXiv:1502.03143, February 2015.

Lili Chen, Kevin Lu, Aravind Rajeswaran, Kimin Lee, Aditya Grover, Michael Laskin, Pieter Abbeel, Aravind Srinivas, and Igor Mordatch. Decision transformer: Reinforcement learning via sequence modeling. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 15084–15097, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/7f489f642a0ddb10272b5c31057f0663-Abstract.html`.

Xinyue Chen, Zijian Zhou, Zheng Wang, Che Wang, Yanqiu Wu, and Keith W. Ross. BAIL: best-action imitation learning for batch deep reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/d55cbf210f175f4a37916eafe6c04f0d-Abstract.html`.

Ching-An Cheng, Tengyang Xie, Nan Jiang, and Alekh Agarwal. Adversarially trained actor critic for offline reinforcement learning. *CoRR*, abs/2202.02446, 2022. URL `https://arxiv.org/abs/2202.02446`.

Erwin Coumans and Yunfei Bai. Pybullet, a python module for physics simulation for games, robotics and machine learning. *GitHub repository*, 2016.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Gabriel Dulac-Arnold, Nir Levine, Daniel J. Mankowitz, Jerry Li, Cosmin Paduraru, Sven Gowal, and Todd Hester. An empirical investigation of the challenges of real-world reinforcement learning. *CoRR*, abs/2003.11881, 2020. URL `https://arxiv.org/abs/2003.11881`.

Luciano Floridi and Massimo Chiriatti. Gpt-3: Its nature, scope, limits, and consequences. *Minds and Machines*, 30(4):681–694, 2020.

C. Daniel Freeman, Erik Frey, Anton Raichuk, Sertan Girgin, Igor Mordatch, and Olivier Bachem. Brax - a differentiable physics engine for large scale rigid body simulation, 2021. URL `http://github.com/google/brax`.

Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4RL: datasets for deep data-driven reinforcement learning. *CoRR*, abs/2004.07219, 2020. URL `https://arxiv.org/abs/2004.07219`.

Scott Fujimoto and Shixiang Shane Gu. A minimalist approach to offline reinforcement learning. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 20132–20145, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/a8166da05c5a094f7dc03724b41886e5-Abstract.html`.

Scott Fujimoto, David Meger, and Doina Precup. Off-policy deep reinforcement learning without exploration. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, volume 97 of *Proceedings of Machine Learning Research*, pp. 2052–2062. PMLR, 2019. URL `http://proceedings.mlr.press/v97/fujimoto19a.html`.

Felix Grimminger, Avadesh Meduri, Majid Khadiv, Julian Viereck, Manuel Wüthrich, Maximilien Naveau, Vincent Berenz, Steve Heim, Felix Widmaier, Jonathan Fiene, Alexander Badri-Spröwitz, and Ludovic Righetti. An Open Torque-Controlled Modular Robot Architecture for Legged Locomotion Research. In *International Conference on Robotics and Automation (ICRA)*, 2020.

Caglar Gulcehre, Ziyu Wang, Alexander Novikov, Thomas Paine, Sergio Gómez, Konrad Zolna, Rishabh Agarwal, Josh S Merel, Daniel J Mankowitz, Cosmin Paduraru, et al. Rl unplugged: A suite of benchmarks for offline reinforcement learning. *Advances in Neural Information Processing Systems*, 33:7248–7259, 2020.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 770–778, 2016.

Jemin Hwangbo, Joonho Lee, Alexey Dosovitskiy, Dario Bellicoso, Vassilios Tsounis, Vladlen Koltun, and Marco Hutter. Learning agile and dynamic motor skills for legged robots. *Science Robotics*, 4 (26):eaau5872, 2019. doi: 10.1126/scirobotics.aau5872. URL `https://www.science.org/doi/abs/10.1126/scirobotics.aau5872`.

Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 12498–12509, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/5faf461eff3099671ad63c6f3f094f7f-Abstract.html`.

Michael Janner, Qiyang Li, and Sergey Levine. Offline reinforcement learning as one big sequence modeling problem. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 1273–1286, 2021. URL `https://proceedings.neurips.cc/paper/2021/hash/099fe6b0b444c23836c4a5d07346082b-Abstract.html`.

Shruti Joshi, Felix Widmaier, Vaibhav Agrawal, and Manuel Wüthrich. `https://github.com/open-dynamic-robot-initiative/trifinger_simulation`, 2020.

Rahul Kidambi, Aravind Rajeswaran, Praneeth Netrapalli, and Thorsten Joachims. Morel: Model-based offline reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/f7efa4f864ae9b88d43527f4b14f750f-Abstract.html`.

Ilya Kostrikov, Rob Fergus, Jonathan Tompson, and Ofir Nachum. Offline reinforcement learning with fisher divergence critic regularization. In Marina Meila and Tong Zhang (eds.), *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pp. 5774–5783. PMLR, 2021a. URL `http://proceedings.mlr.press/v139/kostrikov21a.html`.

Ilya Kostrikov, Ashvin Nair, and Sergey Levine. Offline reinforcement learning with implicit q-learning. *CoRR*, abs/2110.06169, 2021b. URL `https://arxiv.org/abs/2110.06169`.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. ImageNet Classification with Deep Convolutional Neural Networks. In F Pereira, C J C Burges, L Bottou, and K Q Weinberger (eds.), *Advances in Neural Information Processing Systems 25*, pp. 1097–1105. Curran Associates, Inc., 2012.

Ashish Kumar, Toby Buckley, John B Lanier, Qiaozhi Wang, Alicia Kavelaars, and Ilya Kuzovkin. Offworld gym: open-access physical robotics environment for real-world reinforcement learning benchmark and research. *arXiv preprint arXiv:1910.08639*, 2019a.

Aviral Kumar, Justin Fu, Matthew Soh, George Tucker, and Sergey Levine. Stabilizing off-policy q-learning via bootstrapping error reduction. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 11761–11771, 2019b. URL `https://proceedings.neurips.cc/paper/2019/hash/c2073ffa77b5357a498057413bb09d3a-Abstract.html`.

Aviral Kumar, Aurick Zhou, George Tucker, and Sergey Levine. Conservative q-learning for offline reinforcement learning. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL `https://proceedings.neurips.cc/paper/2020/hash/0d2b2061826a5df3221116a5085a6052-Abstract.html`.

Aviral Kumar, Anikait Singh, Stephen Tian, Chelsea Finn, and Sergey Levine. A workflow for offline model-free robotic reinforcement learning. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Conference on Robot Learning, 8-11 November 2021, London, UK*, volume 164 of *Proceedings of Machine Learning Research*, pp. 417–428. PMLR, 2021a. URL `https://proceedings.mlr.press/v164/kumar22a.html`.

Aviral Kumar, Anikait Singh, Stephen Tian, Chelsea Finn, and Sergey Levine. A workflow for offline model-free robotic reinforcement learning. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Conference on Robot Learning, 8-11 November 2021, London, UK*, volume 164 of *Proceedings of Machine Learning Research*, pp. 417–428. PMLR, 2021b. URL `https://proceedings.mlr.press/v164/kumar22a.html`.

Sascha Lange, Thomas Gabel, and Martin Riedmiller. Batch reinforcement learning. In *Reinforcement learning*, pp. 45–73. Springer, 2012.

Sergey Levine, Aviral Kumar, George Tucker, and Justin Fu. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *CoRR*, abs/2005.01643, 2020. URL `https://arxiv.org/abs/2005.01643`.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations (ICLR)*, 2016. URL `http://arxiv.org/abs/1509.02971`.

Denys Makoviichuk and Viktor Makoviychuk. rl-games: A high-performance framework for reinforcement learning. `https://github.com/Denys88/rl_games`, May 2022.

Viktor Makoviychuk, Lukasz Wawrzyniak, Yunrong Guo, Michelle Lu, Kier Storey, Miles Macklin, David Hoeller, Nikita Rudin, Arthur Allshire, Ankur Handa, and Gavriel State. Isaac gym: High performance gpu-based physics simulation for robot learning, 2021.

Ajay Mandlekar, Yuke Zhu, Animesh Garg, Li Fei-Fei, and Silvio Savarese. Adversarially robust policy learning through active construction of physically-plausible perturbations. In *IEEE Int'l Conf. on Intelligent Robots and Systems (IROS)*, volume 16, 2017.

Ajay Mandlekar, Danfei Xu, Josiah Wong, Soroush Nasiriany, Chen Wang, Rohun Kulkarni, Li Fei-Fei, Silvio Savarese, Yuke Zhu, and Roberto Martín-Martín. What matters in learning from offline human demonstrations for robot manipulation. In Aleksandra Faust, David Hsu, and Gerhard Neumann (eds.), *Conference on Robot Learning, 8-11 November 2021, London, UK*, volume 164 of *Proceedings of Machine Learning Research*, pp. 1678–1690. PMLR, 2021. URL `https://proceedings.mlr.press/v164/mandlekar22a.html`.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, Stig Petersen, Charles Beattie, Amir Sadik, Ioannis Antonoglou, Helen King, Dharshan Kumaran, Daan Wierstra, Shane Legg, and Demis Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, February 2015.

Adithyavairavan Murali, Tao Chen, Kalyan Vasudev Alwala, Dhiraj Gandhi, Lerrel Pinto, Saurabh Gupta, and Abhinav Gupta. PyRobot: An Open-source Robotics Framework for Research and Benchmarking. arXiv: 1906.08236, June 2019.

Siddharth Mysore, Bassel Mabsout, Renato Mancuso, and Kate Saenko. Regularizing action policies for smooth control with reinforcement learning. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1810–1816. IEEE, 2021.

Ofir Nachum, Yinlam Chow, Bo Dai, and Lihong Li. Dualdice: Behavior-agnostic estimation of discounted stationary distribution corrections. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pp. 2315–2325, 2019a. URL https://proceedings.neurips.cc/paper/2019/hash/cf9a242b70f45317ffd281241fa66502-Abstract.html.

Ofir Nachum, Bo Dai, Ilya Kostrikov, Yinlam Chow, Lihong Li, and Dale Schuurmans. Algaedice: Policy gradient from arbitrary experience. *CoRR*, abs/1912.02074, 2019b. URL http://arxiv.org/abs/1912.02074.

Ashvin Nair, Murtaza Dalal, Abhishek Gupta, and Sergey Levine. Accelerating online reinforcement learning with offline datasets. *CoRR*, abs/2006.09359, 2020. URL https://arxiv.org/abs/2006.09359.

OpenAI, Marcin Andrychowicz, Bowen Baker, Maciek Chociej, Rafal Jozefowicz, Bob McGrew, Jakub Pachocki, Arthur Petron, Matthias Plappert, Glenn Powell, Alex Ray, Jonas Schneider, Szymon Sidor, Josh Tobin, Peter Welinder, Lilian Weng, and Wojciech Zaremba. Learning Dexterous In-Hand Manipulation. arXiv:1808.00177, August 2018.

OpenAI, Ilge Akkaya, Marcin Andrychowicz, Maciek Chociej, Mateusz Litwin, Bob McGrew, Arthur Petron, Alex Paino, Matthias Plappert, Glenn Powell, Raphael Ribas, Jonas Schneider, Nikolas Tezak, Jerry Tworek, Peter Welinder, Lilian Weng, Qiming Yuan, Wojciech Zaremba, and Lei Zhang. Solving Rubik's Cube with a Robot Hand. arXiv:1910.07113, October 2019.

Fabio Pardo, Arash Tavakoli, Vitaly Levdik, and Petar Kormushev. Time limits in reinforcement learning. In *International Conference on Machine Learning*, pp. 4045–4054. PMLR, 2018.

Liam Paull, Jacopo Tani, Heejin Ahn, Javier Alonso-Mora, Luca Carlone, Michal Cap, Yu Fan Chen, Changhyun Choi, Jeff Dusek, Yajun Fang, et al. Duckietown: an open, inexpensive and flexible platform for autonomy education and research. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1497–1504. IEEE, 2017.

Xue Bin Peng, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Sim-to-real transfer of robotic control with dynamics randomization. In *2018 IEEE international conference on robotics and automation (ICRA)*, pp. 3803–3810. IEEE, 2018.

Daniel Pickem, Paul Glotfelter, Li Wang, Mark Mote, Aaron Ames, Eric Feron, and Magnus Egerstedt. The robotarium: A remotely accessible swarm robotics research testbed. In *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 1699–1706. IEEE, 2017.

Dean A Pomerleau. Efficient training of artificial neural networks for autonomous navigation. *Neural computation*, 3(1):88–97, 1991.

Rafael Figueiredo Prudencio, Marcos R. O. A. Maximo, and Esther Luna Colombini. A survey on offline reinforcement learning: Taxonomy, review, and open problems. *CoRR*, abs/2203.01387, 2022. doi: 10.48550/arXiv.2203.01387. URL https://doi.org/10.48550/arXiv.2203.01387.

Joseph Redmon, Santosh Divvala, Ross Girshick, and Ali Farhadi. You only look once: Unified, real-time object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 779–788, 2016.

Stéphane Ross, Geoffrey J. Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In Geoffrey J. Gordon, David B. Dunson, and Miroslav Dudík (eds.), *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2011, Fort Lauderdale, USA, April 11-13, 2011*, volume 15 of *JMLR Proceedings*, pp. 627–635. JMLR.org, 2011. URL http://proceedings.mlr.press/v15/ross11a/ross11a.pdf.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

Takuma Seno and Michita Imai. d3rlpy: An offline deep reinforcement learning library. *CoRR*, abs/2111.03788, 2021. URL https://arxiv.org/abs/2111.03788.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *Nature*, 550(7676):354–359, 2017.

Richard S Sutton, Andrew G Barto, and Co-Director Autonomous Learning Laboratory Andrew G Barto. *Reinforcement Learning: An Introduction*. MIT Press, 1998.

Josh Tobin, Rachel Fong, Alex Ray, Jonas Schneider, Wojciech Zaremba, and Pieter Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pp. 23–30. IEEE, 2017. doi: 10.1109/IROS.2017.8202133.

Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 5026–5033. IEEE, 2012.

Faraz Torabi, Garrett Warnell, and Peter Stone. Behavioral cloning from observation. In Jérôme Lang (ed.), *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence, IJCAI 2018, July 13-19, 2018, Stockholm, Sweden*, pp. 4950–4957. ijcai.org, 2018. doi: 10.24963/ijcai.2018/687. URL https://doi.org/10.24963/ijcai.2018/687.

Qiang Wang, Francisco Roldan Sanchez, Robert McCarthy, David Cordova Bulens, Kevin McGuinness, Noel O'Connor, Manuel Wüthrich, Felix Widmaier, Stefan Bauer, and Stephen J Redmond. Dexterous robotic manipulation using deep reinforcement learning and knowledge transfer for complex sparse reward-based tasks. *arXiv preprint arXiv:2205.09683*, 2022.

Ziyu Wang, Alexander Novikov, Konrad Zolna, Josh Merel, Jost Tobias Springenberg, Scott E. Reed, Bobak Shahriari, Noah Y. Siegel, Çaglar Gülçehre, Nicolas Heess, and Nando de Freitas. Critic regularized regression. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020. URL https://proceedings.neurips.cc/paper/2020/hash/588cb956d6bbe67078f29f8de420a13d-Abstract.html.

Manuel Wüthrich, Felix Widmaier, Felix Grimminger, Shruti Joshi, Vaibhav Agrawal, Bilal Hammoud, Majid Khadiv, Miroslav Bogdanovic, Vincent Berenz, Julian Viereck, Maximilien Naveau, Ludovic Righetti, Bernhard Schölkopf, and Stefan Bauer. Trifinger: An open-source robot for learning dexterity. In *Proceedings of the 2020 Conference on Robot Learning (CoRL)*, volume 155, pp. 1871–1882. PMLR, 2021. URL https://proceedings.mlr.press/v155/wuthrich21a.html.

Haoran Xu, Xianyuan Zhan, Jianxiong Li, and Honglei Yin. Offline reinforcement learning with soft behavior regularization. *CoRR*, abs/2110.07395, 2021. URL https://arxiv.org/abs/2110.07395.

Brian Yang, Jesse Zhang, Vitchyr Pong, Sergey Levine, and Dinesh Jayaraman. Replab: A reproducible low-cost arm benchmark platform for robotic learning. *arXiv preprint arXiv:1905.07447*, 2019.

Tianhe Yu, Aviral Kumar, Rafael Rafailov, Aravind Rajeswaran, Sergey Levine, and Chelsea Finn. COMBO: conservative offline model-based policy optimization. In Marc'Aurelio Ranzato, Alina Beygelzimer, Yann N. Dauphin, Percy Liang, and Jennifer Wortman Vaughan (eds.), *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pp. 28954–28967, 2021. URL https://proceedings.neurips.cc/paper/2021/hash/f29a179746902e331572c483c45e5086-Abstract.html.

Chi Zhang, Sanmukh R. Kuppannagari, and Viktor K. Prasanna. BRAC+: improved behavior regularized actor critic for offline reinforcement learning. In Vineeth N. Balasubramanian and Ivor W. Tsang (eds.), *Asian Conference on Machine Learning, ACML 2021, 17-19 November 2021, Virtual Event*, volume 157 of *Proceedings of Machine Learning Research*, pp. 204–219. PMLR, 2021. URL https://proceedings.mlr.press/v157/zhang21a.html.

Ruiyi Zhang, Bo Dai, Lihong Li, and Dale Schuurmans. Gendice: Generalized offline estimation of stationary values. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL https://openreview.net/forum?id=HkxlcnVFwB.

A ADDITIONAL RESULTS

This section contains additional experimental results. To quantify how well the policies obtained with offline RL generalize to unseen hardware, we evaluate them on a holdout robot which was not used for data collection.

A.1 RETURNS FOR THE PUSH TASK

We report the returns achieved on the Push task in Table S1. Note that for the simulated datasets the best performing algorithm in terms of return is not necessarily the same as the best performing one in terms of success rates (see Table 1). For instance, BC has the highest average return on Sim-Expert while AWAC achieves a higher success rate. For Sim-Weak&Expert CRR has the best success rates and AWAC reacher higher returns. This has two reasons. First, the success is measured only at the final step of the episode, while the return is computed as the cumulative reward over time. Second, the return is dense as it is computed from the distance between cube and target, while the success rate is a sparse signal. With the optimized hyperparamters CRR and IQL have slightly higher success rates whereas AWAC reaches higher returns.

Table S1: **Push: Returns on the TriFinger-Push Datasets.** 'data' denotes the mean over the dataset. Average and standard deviation over five training seeds.

Push-Datasets	data	BC	CRR	AWAC	CQL	IQL
Sim-Expert	674	$\mathbf{668 \pm 19}$	648 ± 29	630 ± 35	226 ± 31	637 ± 46
Sim-Half-Expert	674	600 ± 30	607 ± 26	$\mathbf{638 \pm 43}$	224 ± 37	559 ± 37
Sim-Weak&Expert	512	499 ± 43	582 ± 37	$\mathbf{611 \pm 25}$	287 ± 38	587 ± 45
Sim-Mixed	583	406 ± 36	228 ± 85	$\mathbf{625 \pm 19}$	132 ± 38	570 ± 77
Real-Expert	660	563 ± 34	$\mathbf{638 \pm 16}$	624 ± 17	514 ± 37	592 ± 29
Real-Half-Expert	660	546 ± 29	$\mathbf{627 \pm 21}$	587 ± 46	471 ± 26	573 ± 23
Real-Weak&Expert	429	387 ± 45	$\mathbf{622 \pm 41}$	568 ± 29	346 ± 68	555 ± 16
Real-Mixed	419	335 ± 23	373 ± 41	569 ± 24	206 ± 18	$\mathbf{600 \pm 30}$

A.2 RETURNS FOR THE LIFT TASK

In this section, we report the returns achieved on the Lift task (Table S2). Interestingly, although IQL achieves a significantly higher return on the Real-Weak&Expert dataset than CRR, its final success rate is lower. There are two possible explanations for this mismatch: (i) IQL might be faster at reaching the target but the grasp might be more brittle than that of CRR. (ii) IQL might move the cube close enough to the target pose to get high rewards but not close enough to achieve the goal.

A.3 EVALUATION ON THE HOLD-OUT ROBOT

We check the performance of the offline RL agents on a hold-out robot from which no data entered the datasets. Table S3 shows the results for TriFinger-Push-Real-Expert and TriFinger-Lift-Real-Expert. The performance of the algorithms on the hold-out robot is within the performance margin of the other robots, suggesting that there is no significant difference between the different robots.

Table S2: **Lift: Returns on the TriFinger-Lift Datasets.** 'data' denotes the mean over the dataset. Average and standard deviation over five training seeds.

Lift-Datasets	data	BC	CRR	AWAC	CQL	IQL
Sim-Expert	1334	1090 ± 85	1239 ± 32	$\mathbf{1270 \pm 60}$	186 ± 36	1030 ± 79
Sim-Half-Expert	1337	1107 ± 62	$\mathbf{1209 \pm 60}$	1188 ± 20	146 ± 29	708 ± 34
Sim-Weak&Expert	1133	832 ± 116	717 ± 461	$\mathbf{1122 \pm 48}$	267 ± 0	961 ± 30
Sim-Mixed	1173	395 ± 31	640 ± 46	$\mathbf{896 \pm 162}$	179 ± 17	582 ± 52
Sim-Expert†	1334	1262 ± 53	1228 ± 32	$\mathbf{1283 \pm 26}$	476 ± 54	1211 ± 76
Sim-Half-Expert†	1337	1153 ± 55	1144 ± 35	$\mathbf{1263 \pm 59}$	402 ± 68	1192 ± 66
Sim-Weak&Expert†	1133	992 ± 24	1068 ± 42	$\mathbf{1107 \pm 27}$	485 ± 47	1075 ± 85
Sim-Mixed†	1173	430 ± 53	652 ± 36	$\mathbf{938 \pm 103}$	149 ± 40	550 ± 34
Real-Smooth-Expert	1206	915 ± 36	$\mathbf{1059 \pm 54}$	1031 ± 42	143 ± 33	1002 ± 19
Real-Expert	1064	711 ± 92	$\mathbf{1014 \pm 62}$	820 ± 50	283 ± 38	901 ± 43
Real-Half-Expert	1064	553 ± 77	$\mathbf{837 \pm 58}$	613 ± 107	200 ± 7	759 ± 101
Real-Weak&Expert	851	346 ± 21	633 ± 59	397 ± 71	298 ± 16	$\mathbf{827 \pm 105}$
Real-Mixed	862	272 ± 56	$\mathbf{631 \pm 62}$	346 ± 64	207 ± 5	608 ± 30
Real-Expert†	1064	676 ± 47	$\mathbf{889 \pm 39}$	747 ± 44	289 ± 33	899 ± 40
Real-Half-Expert†	1064	702 ± 83	$\mathbf{813 \pm 57}$	797 ± 54	312 ± 65	855 ± 51
Real-Weak&Expert†	851	437 ± 47	$\mathbf{707 \pm 20}$	481 ± 54	269 ± 33	574 ± 67
Real-Mixed†	862	288 ± 73	$\mathbf{634 \pm 36}$	361 ± 81	192 ± 28	596 ± 33

Table S3: **Evaluation on hold-out robot.** Success rate on the Real-Expert datasets.

Dataset	BC	CRR	AWAC	CQL	IQL
Push-Real-Expert	0.80 ± 0.04	0.91 ± 0.08	0.84 ± 0.06	0.61 ± 0.05	0.83 ± 0.09
Lift-Real-Expert	0.29 ± 0.04	0.64 ± 0.05	0.31 ± 0.08	0.00 ± 0.00	0.24 ± 0.07

A.4 LEARNING CURVES

In this section, we provide learning curves for the offline RL algorithms on all datasets. Since the evaluation of all training checkpoints on the real robots is prohibitively expensive and time-consuming, we evaluate the checkpoints learned on the **real data** in the **simulated environment**. This gives an over-optimistic estimate of the learning performance on the real robots.

For the challenging Lift-Real-Weak&Expert task we performed a grid search for each algorithm (BC, CRR, AWAC, CQL, IQL) and selected the best hyperparameters. We present the grid search in Table S7, the corresponding optimal hyperparameters in Table S8, and the default hyperparameters in Table S9. We note that due to the poor performance of CQL, we expanded our grid search specifically for this algorithm (on the Push-Sim-Expert data) and selected the corresponding optimal hyperparameters as its default parameters (see Figure S12). Our newly performed gridsearch, as mentioned above, was unfortunately not leading to improvements for CQL. Similar difficulties are reported in Kumar et al. (2021a) and are tackled via case distinction and appropriate regularization techniques. It would be interesting to test the preceding two algorithmic techniques on our datasets, once their implementation is integrated in the D3RLPY library (Seno & Imai, 2021).

We proceed by presenting the learning curves for the offline RL algorithms on the datasets: for the Lift task in Section A.4.1 and for the Push task in Section A.4.2. Shaded areas indicate the interval between the 0.25 and 0.75 quantiles.

A.4.1 LIFT DATASETS

Figure S1: **Training curves for the Lift-Real datasets:** Offline RL algorithms are trained on the **real** datasets and are evaluated in the **simulated** environment. Success rates and returns for the optimized hyperparameters (in Table S8) and the default hyperparameters (in Table S9). *The selected hyperparameters, by the grid-search procedure (in Table S7), optimize the algorithm's **final average return** on Sim-Weak&Expert.* The black dashed line shows the dataset performance of Real-Expert and the red dashed line the performance of the Real-Weak&Expert (first 3 columns) and Real-Mixed (last column).

Figure S2: **Training curves for the Lift-Sim datasets:** Offline RL algorithms are trained on a **simulated** dataset and are evaluated in the **simulated** environment. Success rates and returns for the optimized hyperparameters (in Table S8) and the default hyperparameters (in Table S9). *The selected hyperparameters, by the grid-search procedure (in Table S7), optimize the algorithm's **final average return** on Sim-Weak&Expert*. The black dashed line shows the dataset performance of Sim-Expert and the red dashed line the performance of the Sim-Weak&Expert (first 3 columns) and Sim-Mixed (last column).

A.4.2 PUSH DATASETS

Here, we use the **default** hyperparameters in Table S9, where for the CQL algorithm we selected hyperparameters optimized by a grid search (see Figure S12 for histograms). The *success rates* and *returns* are evaluated in the simulated environment.

Figure S3: **Training curves for the Push-Real datasets:** Offline RL algorithms are trained on the **real** datasets and are evaluated in the **simulated** environment. The black dashed line shows the dataset performance of Real-Expert and the red dashed line the performance of the Real-Weak&Expert (first 3 columns) and Real-Mixed (last column).

Figure S4: **Training curves for the Push-Sim datasets:** Offline RL algorithms are trained on a **simulated** dataset and are evaluated in the **simulated** environment. The black dashed line shows the dataset performance of Sim-Expert and the red the performance of the Sim-Weak&Expert (first 3 columns) and Sim-Mixed (last column).

B   DATASETS

In this section we provide additional details on the datasets we collected. Section B.1 summarizes the data collection process, section B.2 contains a discussion of the different notions of success we report, section B.3 is dedicated to the reward and the terminals, and section B.4 provides a detailed analysis of the statistics of the datasets.

B.1   DATA COLLECTION

Data is collected by running jobs on a cluster of TriFinger platforms without human intervention. Each job consists of the following steps:

1. Move fingers to initial state and sample new goal.

2. Run one episode/rollout with the selected policy and store transitions.

3. Move the cube away from the barrier with a pre-recorded trajectory of the fingers.

4. Repeat from 1. unless the desired number of episodes per job is reached.

5. Do a self-check including cameras, pose estimation and joints.

6. Approximately reset the cube to the center of the arena.

The number of episodes collected per job is eight for the Push task ($15\,\mathrm{s}$ per episode) and six for the Lift task ($30\,\mathrm{s}$ per episode). If a self-check fails, the corresponding robot is deactivated and the maintainers are alerted via mail. Finally, the data from all episodes is combined in a single HDF5 file following the conventions of D4RL (Fu et al., 2020).

The expert policies are obtained after the training in Isaac Gym (see section 3.2 and section C.1). The weak policies are training checkpoints at $210 \cdot 10^6$ training steps for pushing and $288 \cdot 10^6$ training steps for lifting. Gaussian noise is added to the actions with an amplitude of $0.2\,\mathrm{Nm}$ and an update frequency of 8 for pushing and $0.04\,\mathrm{Nm}$ with an update frequency of 4 for lifting.

The Mixed datasets are collected with policies from a range of training checkpoints where the total number of jobs was distributed as uniformly as possible over all training checkpoints. For pushing 22 checkpoints up to $668 \cdot 10^6$ training steps were used while for lifting 59 training checkpoints up to $1721 \cdot 10^6$ training steps were considered. Fig. S5 shows the return and success rate of these checkpoints on the real TriFinger cluster.

B.2   THREE NOTIONS OF SUCCESS

We consider dexterous manipulation tasks which require the agent to match a goal position (for the Push task) or a goal pose (for the Lift task) with a tracked cube. The tolerance for goal achievement is $2\,\mathrm{cm}$ for the position and 22 degrees for the orientation. We define *momentary success* as achieving the goal at a single point in time, i.e., in an individual time step. This notion of success is rather weak, however, as achieving the goal pose for a short amount of time is significantly easier than maintaining it. For the pushing task in particular, it is much more likely to move through the goal by accident than to stabilize the cube after having reached it. When lifting the cube, it is quite challenging to maintain a stable grasp due to the variance of the object pose estimate which introduces a considerable amount of noise to the observations. We therefore define *success* as achieving the goal at the end of the episode which is only likely to happen when maintaining the goal pose for an extended period of time.

From the perspective of offline RL, however, it is highly relevant whether parts of the trajectories in the datasets lead to success, even if it is short-lived. As offline RL algorithms can, in principle, combine information from several trajectories, even trajectories that do not end with goal achievement may contain enough information to learn a successful policy. We therefore also report *transient success* which indicates whether the goal has been achieved at any time during the episode and *mean momentary success* which corresponds to the fraction of time steps during which the goal has been achieved.

Figure S5: Return and success rates of the checkpoints used for collecting the Real-Mixed datasets. Note that the checkpoints were obtained by training in Isaac Gym (see section 3.2 and section C.1) and were evaluated on the **real** system. The shaded areas indicate the interval between the 0.25 and 0.75 quantiles of the return whereas the error bars represent the standard error of the mean of the success rate.

B.3 REWARD AND TERMINALS

As already mentioned in section 3 of the main text, we use a logistic kernel Hwangbo et al. (2019); Allshire et al. (2021)

$$k(x) = \frac{b + 2}{\exp(a\|x\|) + b + \exp(-a\|x\|)} \tag{S1}$$

to define the reward where $\|\cdot\|$ denotes the Euclidean norm. For the Push task, we apply it to the difference between the achieved and the desired cube position. Since we also want to take the orientation of the cube into account for the Lift task, we apply k separately to the differences between the desired and achieved corner points (or keypoints) of the cube and average over the results Allshire et al. (2021). We use $a = 30$ and $b = 2$. See Fig. S6 for a visualization of the reward function.

By default, the terminals in the dataset (a Boolean indicating whether a terminal state has been reached) are never set. We chose this default setting to avoid problems due to state aliasing: Episodes

Figure S6: Reward as a function of the Euclidean distance between the desired and achieved position (for the Push task) or keypoint (for the Lift task). The shaded grey area corresponds to a cube centered at the goal and the green area corresponds to the goal achievement threshold (2 cm).

Table S4: Overview of the TriFinger offline RL datasets.

task	dataset	overall duration [h]	#episodes	#transitions [10^6]	episode length [s]
Push-	Sim-Expert	16	3840	2.8	15
	Sim-Half-Expert	8	1920	1.4	15
	Sim-Weak&Expert	16	3840	2.8	15
	Sim-Mixed	16	3840	2.8	15
	Real-Expert	16	3840	2.8	15
	Real-Half-Expert	8	1920	1.4	15
	Real-Weak&Expert	16	3840	2.8	15
	Real-Mixed	16	3840	2.8	15
Lift-	Sim-Expert	20	2400	3.6	30
	Sim-Half-Expert	10	1200	1.8	30
	Sim-Weak&Expert	20	2400	3.6	30
	Sim-Mixed	20	2400	3.6	30
	Real-Smooth-Expert	20	2400	3.6	30
	Real-Expert	20	2400	3.6	30
	Real-Half-Expert	10	1200	1.8	30
	Real-Weak&Expert	20	2400	3.6	30
	Real-Mixed	20	2400	3.6	30

last for a finite number of time steps H, and the RL objective is to maximize the discounted return (or cumulative reward)

$$J = \sum_{t=0}^{H-1} \gamma^t r_t \,, \tag{S2}$$

where γ denotes the discounting factor and r_t the reward in step t. A Markov state therefore has to keep track of how much time remains until the episode ends. The observation, on the other hand, does not contain this information. This omission is a deliberate choice as we want to obtain a policy which is independent of the time step. This makes it impossible, however, to accurately estimate the value based on the observation if γ is too large. Intuitively, without access to the time step t, the agent cannot know whether a cube far away from the goal corresponds to a large expected return to go because it is the beginning of an episode or a small expected return to go because there is no time left to move the cube and accumulate reward. See Pardo et al. (2018) for a more detailed discussion of issues arising from training with a finite horizon.

A practical solution to this problem is to not set the terminals and choose a gamma which is appropriate for the time scale of the task (for offline learning we chose $\gamma = 0.99$). This choice hides the episodic nature of the task from the agent which results in good performance while avoiding a dependence of the policy on time. It may, however, sacrifice optimality in some corner cases like dropping the cube close to the end of the episode when there is not enough time to flip the cube over before lifting it again. Nevertheless, as we provide a flag to set the terminals at the episode ends and as it is straight forward to augment the observation with the intra-episode time step, the datasets are also suitable for experiments with time-dependent policies.

B.4 DATASET ANALYSIS

Overview: We provide an overview of the various dataset types and their properties in Table S4.

Statistics: Table S5 summarizes the statistics of the TriFinger datasets. While the success rate and the mean return constitute a limit to what can be achieved with pure imitation learning, the high numbers for the transient success rate (fraction of episodes in which the goal was achieved at least in one time step but not necessarily at the end of the episode) indicate that offline RL can potentially outperform the behavior policy significantly on these datasets.

Impact of variations between robots: Fig. S7 compares the success rates of the expert policies on the individual robots used for data collection. While the performance differences between the robot instances are significant, the expert policies perform reasonably well on all of them, achieving at least 80% success rate on the Push task and 60% on the Lift task on all robots.

Table S5: Statistics of the proposed TriFinger offline RL datasets: TriFinger-Push and TriFinger-Lift. Definitions of the success rates and the reward can be found in section B.2 and section B.3, respectively.

TriFinger-Push	success rate	mean momentary success rate	transient success rate	mean return
Sim-Expert	95%	87%	95%	674
Sim-Half-Expert	94%	86%	94%	667
Sim-Weak&Expert	53%	48%	86%	512
Sim-Mixed	76%	68%	77%	583
Real-Expert	92%	78%	98%	660
Real-Half-Expert	92%	78%	98%	660
Real-Weak&Expert	51%	43%	72%	429
Real-Mixed	49%	40%	63%	419

TriFinger-Lift	success rate	mean momentary success rate	transient success rate	mean return
Sim-Expert	87%	77%	97%	1334
Sim-Half-Expert	88%	78%	98%	1337
Sim-Weak&Expert	50%	44%	93%	1133
Sim-Mixed	68%	60%	84%	1173
Real-Smooth-Expert	64%	53%	82%	1206
Real-Expert	67%	52%	87%	1064
Real-Half-Expert	68%	52%	86%	1064
Real-Weak&Expert	40%	30%	66%	851
Real-Mixed	42%	32%	65%	862

(a) TriFinger-Push-Real-Expert   (b) TriFinger-Lift-Real-Expert

Figure S7: Success rates on the individual robots. The transitions were recorded with policies trained with PPO in simulation. While there are significant differences between the success rates, the expert policies achieve at least 80% and 60% on every robot for TriFinger-Push-Real-Expert and TriFinger-Lift-Real-Expert, respectively.

Distribution of returns: Fig. S8 shows the distribution of the episode returns for the datasets collected on the real system. It reveals that the expert policy on the Push task performed more consistently on the real robot than its counterpart for the Lift task. Qualitatively, this can be attributed to either (i) not being able to flip the cube to the approximately correct orientation, (ii) failing to establish a stable grasp on the cube, or (iii) dropping it after already having lifted it. Flipping the cube on the ground might fail due to incomplete modeling of interactions between the fingertips and the cube in the rigid body physics simulator or because it is sensitive to the value of sliding friction, the noise on the object pose estimate makes it difficult to maintain a stable grasp after having lifted the object.

Figure S8: Distribution of the episode returns in the datasets recorded on the real system.

Action statistics: Fig. S9 shows the distribution of actions of the expert policy that recorded TriFinger-Push-Real-Expert and of a policy learned from this data by AWAC.

Reset procedure: As mentioned in section 3.3 of the main text, we removed the cube from the barrier between episodes because we observed that the expert policies we trained in simulation struggled with retrieving the cube from the barrier. Fig. S10a shows a histogram of the distance between the center of the cube and the arena center. While the reset procedure is sufficiently stochastic to randomize the initial cube position (see Fig. 4 in the main text), it clearly removes the cube from the barrier in the majority of all resets. More precisely, only in 3% of all resets the cube center was within 6 cm of the boundary (the cube has a width of 6.5 cm).

Dropping frequency – pure feedforward vs. smoothed: One reason for the lower success rate on the Lift task as compared to the Push task is frequent dropping of the cube. This can be the result of vibrations of the fingers which can occur when applying policies trained in simulation on the real robots or of shaking caused by the noisy pose estimate for the cube. We found that applying a low-pass filter, more precisely an Exponential Moving Average, helps with both problems. Fig. S10b shows the frequency at which the cube is dropped over the course of a lifting episode. Dropping the cube is defined as reaching the height of the goal pose up to a tolerance of $2\,\text{cm}$ at some point during the episode and then dropping the cube flat on the ground (up to a tolerance of $1\,\text{cm}$). Smoothing the actions before applying them clearly helps with avoiding dropping, in particular later in the episode. Note, however, that the smoothing has to be applied already during training in simulation for the policy to adapt to it. Despite the action smoothing the dropping rate does not reach zero. This can be partly attributed to unstable grasps that lead to slipping on the real robot.

Figure S9: Distribution of action components, i.e., desired torques, for the expert policy that recorded the TriFinger-Push-Real-Expert dataset and for a policy learned with AWAC from this dataset. Averaged over five offline RL seeds.

B.5 Using the Datasets

We provide an easy-to-use Python package that is compatible with a popular collection of offline RL datasets Fu et al. (2020). To use the datasets, it is sufficient to clone the repository, instantiate the desired environment and call a method that returns the dataset. The correct dataset is then downloaded automatically. We also provide options for filtering the observations and for converting them to flat arrays.

C Training

C.1 Training Expert Policies in Simulation

In addition to the modifications mentioned in section 3.2, we also ported training from Isaac Gym 2 to the current version Isaac Gym 3 Makoviychuk et al. (2021). We furthermore increased the torque range from $[-0.36\,\mathrm{Nm}, 0.36\,\mathrm{Nm}]$ to $[-0.397\,\mathrm{Nm}, 0.397\,\mathrm{Nm}]$ to make sure the fingers are strong enough to lift the cube when supporting it from below. To make the training environment resemble the data collection setting on the real robots, we furthermore implemented an adjustable delay between when an observation is received and when the action based on this observation is applied for the first time. The success rates and returns reached after training are shown in Table S6.

Note that the success rates we give for the lifting task on the real robot are not directly comparable to the ones reported in Allshire et al. (2021) as our lifting task is more challenging. While Allshire et al. (2021) evaluate success after $60\,\mathrm{s}$[3], we evaluate after $30\,\mathrm{s}$. As policies usually need several attempts to flip the cube to roughly the correct orientation and for picking it up, the success rate after $30\,\mathrm{s}$ is lower in general. We chose the shorter episode length because it is, in principle, sufficient to solve the task and because we wanted to avoid episodes which consist, to a large part, of the cube being

---

[3]Personal communication

(a) Cube distribution after reset   (b) Dropping frequency   (c) Momentary success

Figure S10: (a) Histogram of the distance between the center of the cube and the arena center after the reset for the Lift-Real-Expert dataset. In the shaded gray area the cube can potentially touch the barrier which begins at the vertical black line. (b) Dropping frequency over a real lift episode. 'Pure feedforward' refers to directly applying the output of an MLP policy whereas 'smoothed' denotes a policy with an Exponential Moving Average applied. (c) Comparison of the momentary success rate of a policy learned from Push-Real-Expert (AWAC in green) with the expert policy (PPO-Expert in blue) that recorded the data. The momentary success rate captures how often the policy achieved the goal at a time step averaged over all episodes. The momentary success rate of the weak policy used in Push-Real-Weak&Expert is shown in orange.

Table S6: Performance of the expert policies in the Isaac Gym environment. The numbers for the success rate and return are not directly comparable to those in the PyBullet simulator and on the real robot for two reasons: (i) In Isaac Gym Lift episodes last for $15\,\mathrm{s}$ instead of $30\,\mathrm{s}$, and (ii) the return in the Isaac Gym environment is contains auxiliary reward terms as described in Allshire et al. (2021) and section 3.2.

	success rate	return	#training steps
Push	0.99	629	$0.83 \cdot 10^9$
Lift	0.87	589	$1.72 \cdot 10^9$

held in place. Moreover, unlike Allshire et al. (2021), we do not push the cube to the center of the arena before each episode but only remove it from the barrier.

C.2   TRAINING WITH OFFLINE RL ON THE DATASETS

We use the implementations of BC, CRR, AWAC, CQL and IQL provided by the open-source library D3RLPY (Seno & Imai, 2021). The code is available at `https://github.com/takuseno/d3rlpy` and the documentation can be found at `https://d3rlpy.readthedocs.io/`. For our experiments we used versions 1.1.0 and 1.1.1 of D3RLPY. The used hyperparameters and the performed optimization are discussed in the next section.

C.3 HYPERPARAMETERS

We performed a grid search over hyperparameters for all algorithms as documented in Table S7. The hyperparameter setting with the highest performance in terms of final average return on Lift-Sim-Weak&Expert was selected, as listed in Table S8. In the paper, the results with optimized parameters are marked with a †. Otherwise, the default parameters were used, as listed in Table S9.

The rest of the section contains a detailed analysis of the grid search.

Table S7: **Hyperparameter grid search (on dataset Lift-Sim-Weak&Expert)**. Each algorithm is trained with the same two seeds (sampled uniformly at random).

Algorithms	Parameters
AWAC	{(actor_learning_rate=R, critic_learning_rate=R) : R∈{1.5E-4, 3.0E-4, 6.0E-4}}; batch_size∈ {256, 512}; lam∈ {0.3, 1.0, 3.0}
BC	learning_rate={1.5E-4; 3.0E-4; 6.0E-4}; batch_size∈ {256, 512}
CRR	{(actor_learning_rate=R, critic_learning_rate=R) : R∈{1.5E-4, 3.0E-4, 6.0E-4}}; batch_size∈ {256, 512}; beta∈ {0.25, 1.0, 4.0}
CQL	{(actor_learning_rate=R, critic_learning_rate=3.0*R, initial_alpha=T[1], alpha_learning_rate={R if T[0] else 0}, temp_learning_rate=R, alpha_threshold=T[2]) : R∈{5.0E-5, 1.0E-4}, T∈{[true, 1.0, 1.0], [true, 1.0, 5.0], [true, 1.0, 10.0], [false, 0.3, 10.0], [false, 1.0, 10.0], [false, 3.0, 10.0]} }; conservative_weight∈{2.5, 5.0, 10.0, 20.0}
IQL	{(actor_learning_rate=R, critic_learning_rate=R) : R∈{1.5E-4, 3.0E-4, 6.0E-4}}; batch_size∈ {256, 512}; expectile∈ {0.7, 0.8, 0.9}; weight_temp∈ {3.0, 10.0}

Table S8: **Optimized Hyperparameters using grid search** Table S7.

Algorithms	Parameters
AWAC	actor_learning = critic_learning_rate = 0.00015; batch_size=256; lam=3.0
BC	learning_rate=0.00015; batch_size=512
CRR	actor_learning = critic_learning_rate = 0.00015; batch_size=256; beta=1.0
CQL	actor_learning_rate=0.0001; critic_learning_rate=0.0003; initial_alpha=1.0; conservative_weight=20.0; alpha_learning_rate=0.0; action_scaler: minmax
IQL	actor_learning_rate = critic_learning_rate= 0.00015; batch_size=256; expectile=0.9; weight_temp=3.0

Table S9: **Default hyperparameters**. All algorithms except BC (with batch_size=100 and without a critic) have batch_size=256 and n_critics=2. Note that due to bad performance we optimized CQL's parameters on Push-Sim-Expert with an extensive grid search as shown in Fig. S12. For all other algorithms, we used the default values of the implementation.

Algorithms	Parameters
AWAC	actor_learning = critic_learning_rate = 0.0003; batch_size=1024; lam=1.0
BC	learning_rate=0.001; batch_size=100
CRR	actor_learning = critic_learning_rate = 0.0003; batch_size=256; beta=1.0
CQL	actor_learning_rate=0.0001; critic_learning_rate=0.0003; initial_alpha=1.0; conservative_weight=20.0; alpha_learning_rate=0.0; action_scaler: minmax
IQL	actor_learning_rate = critic_learning_rate= 0.0003; batch_size=256; expectile=0.7; weight_temp=3.0

In Fig. S11 we present the returns and success rates for each of the hyperparameter settings for the Lift task in simulation. We see that the different algorithms have very different sensitivity to their hyperparameters. For CRR a large fraction of parameters leads to good results. For AWAC the sensitivity is a bit higher. IQL seems to degrade more gracefully with changed parameters. For CQL we were unable to find good hyperparameters, despite running 48 configurations. The performance of the individual runs over training time are shown in Fig. S13.

Figure S11: Hyperparameter grid search: Histogram of **returns** and **success rates** for the Lift-Sim-Weak&Expert task.

On the Push task, we ran an even larger hyperparameter scan with 405 configurations for CQL, as presented in Fig. S12. Even for this much simpler task, we see that the majority of parameters yield low success rates. In addition, we note that the training became quite unstable for alpha_lr > 0.0 and due to this, we conducted our main grid-search with alpha_lr = 0.0. Then, we chose the best hyperparameter configuration as the default setting for CQL.

Figure S12: Hyperparameter grid search on the Push-Sim-Expert task for **CQL**. Shown is the histogram of returns and success rates for the 405 hyperparameter settings, as defined on the right.

Figure S13: **Lift-Sim-Weak&Expert**. Hyperparameter grid search. **Returns** (top row) and **success rate** (bottom row). Every curve corresponds to one parameter configuration (averaged over 2 seeds). The black dashed line shows the dataset performance of Sim-Expert and the red dashed line the performance of the Sim-Weak&Expert.

D POLICY EVALUATION

D.1 EVALUATION ON THE REAL SYSTEM

On the real platforms, we report numbers for 48 trials for the Push task and 36 trials for the Lift task, each for 5 training seeds. Each algorithm and seed is evaluated on 5 to 6 robots with the same set of 6 (for the Lift task) to 8 (for the Push task) goals per robot (computed from the robot ID). The success rate and return of each algorithm and seed is computed from the resulting trials. The mean and standard deviations of the success rates and returns of each algorithm is computed across seeds.

D.2 EVALUATION ON THE SIMULATOR

In the simulated environment, we perform 20 testing episodes per policy with a fixed set of randomly sampled goals, for 5 independent training runs.