LATENT TASK-SPECIFIC GRAPH NETWORK SIMULATORS

ABSTRACT

Simulating object deformations is a critical challenge in many scientific domains, with applications ranging from robotics to materials science. Learned Graph Network Simulators (GNSs) are an efficient alternative to traditional mesh-based physics simulators. Their speed and inherent differentiability make them particularly well-suited for inverse design problems such as process optimization. However, these applications typically offer limited available data, making GNSs difficult to use in real-world scenarios. We frame mesh-based simulation as a meta-learning problem and apply conditional Neural Processes to adapt to new simulation scenarios with little data. In addition, we address the problem of error accumulation common in previous step-based methods by combining this approach with movement primitives, allowing efficient predictions of full trajectories. We validate the effectiveness of our approach, called Movement-primitive Meta-MeshGraphNet (M3GN), through a variety of experiments, outperforming state-of-the-art step-based baseline GNSs and step-based meta-learning methods.

1 INTRODUCTION

The simulation of complex physical systems is of paramount importance in a wide variety of engineering disciplines, including structural mechanics (Yazid et al., 2009; Zienkiewicz & Taylor, 2005; Stanova et al., 2015), fluid dynamics (Chung, 1978; Zienkiewicz et al., 2013; Connor & Brebbia, 2013), and electromagnetism (Jin, 2015; Polycarpou, 2022; Reddy, 1994). In particular, the simulation of object deformations under external forces is crucial for, e.g., robotic applications (Scheikl et al., 2022; Wang & Zhu, 2023; Linkerhägner et al., 2023). Mesh-based simulations are appealing for such problems due to the computational efficiency and accuracy of the underlying finite element method (Brenner & Scott, 2008; Reddy, 2019). However, the diversity of the problems to be modeled usually necessitates the development of task-specific simulators to accurately capture the relevant physical quantities (Reddy & Gartling, 2010). Such specialized simulators can be slow and cumbersome to use, especially for large-scale simulations (Paszynski, 2016; Hughes et al., 2005).

Thus, data-driven models trained on reference simulations have gained attention as an appealing alternative (Guo et al., 2016; Da Wang et al., 2021; Li et al., 2022). Among them, general-purpose Graph Network Simulators (GNSs) have recently become increasingly popular (Battaglia et al., 2018; Pfaff et al., 2021; Allen et al., 2022b; 2023; Linkerhägner et al., 2023). GNSs encode the simulated system as a graph of interacting entities whose dynamics are predicted using Graph Neural Networks (GNNs) (Bronstein et al., 2021). These models are one to two orders of magnitude faster than classical simulators (Pfaff et al., 2021) while being fully differentiable, which makes them highly effective for, e.g., inverse design problems (Allen et al., 2022b; Xu et al., 2021).

GNSs are typically trained through simple next-step supervision (Battaglia et al., 2018; Pfaff et al., 2021; Allen et al., 2023). During inference, entire trajectories are simulated by iteratively predicting per-node dynamics from an initial system state in an autoregressive manner. This approach is prone to error accumulation over time, especially as the input distribution diverges from the training set (Brandstetter et al., 2022; Han et al., 2022). To mitigate this issue, existing approaches add noise to the input during training and predict the dynamics based on the original inputs, thus following an implicit de-noising objective (Pfaff et al., 2021; Brandstetter et al., 2022). While this significantly improves simulation stability over longer rollouts, the auto-regressive inference of next-step GNSs still propagates and accumulates errors made in earlier prediction steps. These methods also struggle

Planar Bending   Deformable Plate   Tissue Manipulation   Teddy Bear Falling

Figure 1: Final M3GN (Movement-Primitive Meta-MeshGraphNet) simulation steps for different evaluation tasks. From left to right: a planar sheet bending under two orthogonal forces, a falling collider deforming a 2D plate, a surgical tool dragging tissue, and a falling teddy bear. All visualizations present the **predicted mesh** alongside a reference **wireframe** of the ground-truth simulation. M3GN takes the deformable object positions from a few initial time steps and applies meta-learning techniques to infer physical properties, such as Poisson's ratio or Young's modulus. With this latent task description, it predicts the remaining simulation steps using per-node movement primitives.

with partially known initial system states (Linkerhägner et al., 2023), which are common in, e.g., robotic planning (Antonova et al., 2022). Extensions that address this uncertainty (Linkerhägner et al., 2023) require a consistent stream of auxiliary information, such as point cloud observations, throughout the simulation. Furthermore, GNSs typically require large amounts of training data, which prevents their application in real-world scenarios where data is scarce, highlighting the need for efficient adaptation techniques to novel tasks.

To address these limitations, we reformulate learned mesh-based simulation as a trajectory-level meta-learning problem. Here, the initial mesh states of a trajectory serve as a context set on which to condition future predictions. We employ Conditional Neural Processs (CNPs) (Garnelo et al., 2018a) to aggregate these context sets and the dynamics inferred from them into a latent descriptor, which is then used to predict the rest of the trajectory. This method enables efficient training and rapid adaptation to trajectory-specific simulation parameters, such as unknown object material properties, during inference. In addition, we mitigate the problem of error accumulation by directly predicting full simulation trajectories of the mesh nodes instead of iteratively predicting their next-step dynamics. To this end, we represent the simulation using node-level Probabilistic Dynamic Movement Primitives (ProDMPs) (Schaal, 2006; Paraschos et al., 2013; Li et al., 2023), which allows for an efficient encoding of higher-order dynamics at arbitrary temporal resolution. The resulting method, called Movement-Primitive Meta-MeshGraphNet (M3GN), allows efficient generation of context-dependent simulation trajectories that accurately infer and integrate unknown system properties. Figure 1 shows examples for different tasks, while Figure 2 provides an overview of our approach.

To validate the effectiveness of M3GN, we introduce three novel tasks based on challenging deformable object simulations with varying object materials. These include a planar plate bending under stress, and a variety of falling objects that collide with the ground. In addition to these new tasks, we evaluate M3GN on an existing suite of experiments (Linkerhägner et al., 2023).Our results show that our method provides superior simulation accuracy compared to several variants of MeshGraphNet (MGN) Pfaff et al. (2021), the state-of-the-art GNS.[1] Further, the ProDMPs trajectory representation of M3GN reduces the number of required model calls, improving inference runtime by up to 32 times compared to MGN.

In summary, we (i) propose M3GN, a novel GNS that combines meta-learning and movement primitives to predict node-level simulation trajectories based on initial system state contexts; (ii) introduce two challenging deformation prediction tasks involving varying object materials; (iii) evaluate and compare our method to state-of-the-art GNSs, demonstrating superior prediction performance.

---

[1]Code is provided in the supplement. Here, the reviewers can also find a video showing the main results including HD renders of M3GN predictions and comparisons to existing baselines.

Figure 2: M3GN architecture schematic. Given a context set of initial system states, we calculate node-level latent features for every pair of states using a shared GNN encoder. These feature sets are then aggregated, yielding a node-level latent task description z_v. We concatenate this description with the last system state to predict ProDMP weights that are used to compute per-node trajectories.

2 RELATED WORK

Graph Network Simulators. Deep neural networks for physical simulations can provide significant speedups over traditional simulators while being fully differentiable (Pfaff et al., 2021; Allen et al., 2022a), making them a natural choice for applications like model-based Reinforcement Learning (Mora et al., 2021) and Inverse Design problems (Baqué et al., 2018; Durasov et al., 2021; Allen et al., 2022a). A popular class of learned neural simulators are Graph Network Simulators (GNSs) (Battaglia et al., 2016; Sanchez-Gonzalez et al., 2020). GNSs utilize Message Passing Networks (MPNs), a special type of GNN (Scarselli et al., 2009; Bronstein et al., 2021) that representationally encompasses the function class of many classical solvers (Brandstetter et al., 2022). GNS handle physical data by modeling arbitrary entities and their relations as a graph. Applications of GNSs include particle-based simulations (Li et al., 2019; Sanchez-Gonzalez et al., 2020; Whitney et al., 2023), atomic force prediction (Hu et al., 2021), and fluid dynamic problems (Brandstetter et al., 2022). These models have additionally been applied to the mesh-based prediction of deformable objects (Pfaff et al., 2021; Weng et al., 2021; Han et al., 2022; Fortunato et al., 2022; Linkerhägner et al., 2023). Recent extensions handle rigid objects (Allen et al., 2022b; 2023; Lopez-Guevara et al., 2024) and integrate learned adaptive mesh refinement strategies (Plewa et al., 2005; Freymuth et al., 2023) into the simulator (Wu et al., 2023). Existing work that considers unknown material properties in simulations of deformable objects combines the GNS prediction with point cloud information to improve long-term predictions Linkerhägner et al. (2023). This method requires a constant stream of point clouds to ground the simulation in, but can not aggregate this information into a description of the material properties. Additionally, the DEL method (Wang et al., 2024) integrates physical priors from the Discrete Element Analysis (DEA) framework with learnable graph kernels, addressing the challenges of simulating 3D particle dynamics from 2D images. In the context of larger-scale simulations, foundation models are gaining traction in neural simulation tasks, as exemplified by Aurora (Bodnar et al., 2024), a large-scale model trained on extensive climate data. While Aurora demonstrates impressive performance on atmospheric predictions, including global air pollution and weather forecasts, it requires significantly more data for fine-tuning compared to our approach, which focuses on efficient adaptation with fewer data points. Notably, all previously mentioned GNSs predict system dynamics iteratively from a given state, whereas we directly estimate entire trajectories, improving rollout stability and reducing function calls. Related to our approach is the Equivariant Graph Neural Operator (EGNO) (Xu et al., 2024), which also predicts full trajectories using SE(3) equivariance to model 3D dynamics and capture spatial and temporal correlations. In contrast to the related work, which rely on supervised learning or fine-tuning a foundation model, we employ meta-learning for efficient adaptation to new trajectories.

Meta-Learning. Meta-learning (Schmidhuber, 1992; Thrun & Pratt, 1998; Vilalta & Drissi, 2005; Hospedales et al., 2022) extracts inductive biases from a training set of related tasks in order to increase data efficiency on unseen tasks drawn from the same task distribution. In contrast to other

multi-task learning methods, such as transfer learning (Krizhevsky et al., 2012; Golovin et al., 2017; Zhuang et al., 2020), which merely fine-tune or combine standard single-task models, meta-learning makes the multi-task setting explicit in the model architecture (Bengio et al., 1991; Ravi & Larochelle, 2017; Andrychowicz et al., 2016; Volpp et al., 2019; Santoro et al., 2016; Snell et al., 2017). This explicit architecture allows the resulting meta-models to learn *how* to learn new tasks from a small number of example contexts. A popular variant is Model-Agnostic Meta-Learning (MAML) (Finn et al., 2017; Grant et al., 2018; Finn et al., 2018; Kim et al., 2018), which employs standard single-task models and formulates a multi-task optimization procedure. Neural Processes (NPs) (Garnelo et al., 2018a;b; Kim et al., 2019; Gordon et al., 2019; Louizos et al., 2019; Volpp et al., 2021; 2023) instead build on a multi-task model architecture (Heskes, 2000; Bakker & Heskes, 2003) but employ standard gradient based optimization algorithms (Kingma & Ba, 2015; Kingma & Welling, 2014; Rezende et al., 2014; Zaheer et al., 2017). Here, we use Conditional Neural Processes (CNPs) (Garnelo et al., 2018a), which aggregate learned features over a variable-sized context set to yield a latent task description that our downstream GNS is conditioned on. Compared to regular NPs, CNPs assume a deterministic task description, eliminating the need for a distribution over latent variables. This assumption simplifies and accelerates the training process, as our objective is to predict a single precise simulation trajectory from the context set.

3 Movement-Primitive Meta-MeshGraphNets

In this section, we present the theoretical foundation of the M3GN method, detailing the algorithmic design choices that guided its development. **Graph Network Simulators.** Consider a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E}, \mathbf{X}_\mathcal{V}, \mathbf{X}_\mathcal{E})$ with nodes $\mathcal{V}$, edges $\mathcal{E}$, and associated vector-valued node and edge features $\mathbf{X}_\mathcal{V}$ and $\mathbf{X}_\mathcal{E}$. An MPN (Sanchez-Gonzalez et al., 2020; Pfaff et al., 2021) consists of M message passing steps, which iteratively update the node and edge features based on the graph topology. Each such step is given as

$$\mathbf{h}_e^{m+1} = f_\mathcal{E}^m(\mathbf{h}_v^m, \mathbf{h}_e^m),$$
$$\mathbf{h}_v^{m+1} = f_\mathcal{V}^m(\mathbf{h}_v^m, \bigoplus_{e \in \mathcal{E}_v} \mathbf{h}_e^{m+1}),$$

where $\mathbf{h}_v^m$ and $\mathbf{h}_e^m$ denote embeddings of the system state per node and edge at message passing iteration m, respectively. $\mathcal{E}_v \subset \mathcal{E}$ are the edges connected to v. Further, $\bigoplus$ denotes a permutation-invariant aggregation operation such as the sum, the max, or the mean. The functions $f_\mathcal{V}^m$ and $f_\mathcal{E}^m$ are learned Multilayer Perceptrons (MLPs). The network's final output are the node-wise learned representations $\mathbf{h}_v := \mathbf{h}_v^M$ that encode local information of the initial node and edge features.

Conventional GNSs encode the state of the simulated system as a graph, feed it through the MPN, and interpret the per-node outputs as velocities or accelerations (Pfaff et al., 2021). These dynamics are used to forward the simulation in time using, e.g., a forward-Euler integrator (Sanchez-Gonzalez et al., 2020). The graph encodes relative distances and velocities between entities instead of absolute ones, as the resulting equivariance to translation improves generalization (Sanchez-Gonzalez et al., 2020). GNSs usually minimize a next-step Mean Squared Error (MSE) per node during training, adding carefully tuned implicit denoising strategies (Pfaff et al., 2021; Brandstetter et al., 2022) to stabilize long-term predictions. During inference, they compute trajectories by iteratively predicting and integrating their output in an autoregressive fashion. If some simulated objects, like the collider, are known, only the remaining nodes are predicted. Our method instead uses a ProDMP to predict a compact representation of a whole trajectory per system node, reducing the effect of error accumulation, similar to temporal bundling (Brandstetter et al., 2022).

Probabilistic Dynamic Movement Primitives. Movement Primitives (MPs) (Schaal, 2006; Paraschos et al., 2013) allow for compact and smooth trajectory representations y via a set of basis functions parameterized by a set of weights $\boldsymbol{w}$. This temporal smoothness is highly beneficial for, e.g., robotic applications (Li et al., 2024; Otto et al., 2022). Recent methods integrate MPs with neural networks to enhance their expressive capabilities (Seker et al., 2019; Bahl et al., 2020; Li et al., 2023). Dynamic Movement Primitives (DMPs) (Schaal, 2006) use a spring-damper dynamical system governed by parameters α and β. To manipulate the trajectory, an external forcing term f is added, before the system converges to a predefined goal g:

$$\tau^2 \ddot{y} = \alpha \left(\beta(g - y) - \tau \dot{y}\right) + f(x), \quad f(x) = x \boldsymbol{\varphi}^\mathsf{T} \boldsymbol{w}. \tag{1}$$

Figure 3: **Left:** M3GN and MGN task setup. Both methods predict mesh positions based on the initial mesh at the anchor time step. M3GN utilizes previous mesh positions and the last step of the collider trajectory for its latent task description, whereas MGN disregards past information and integrates the ground truth collider trajectory into its step-based model. **Right:** Exemplary final simulation steps on the Planar Bending task of M3GN given different context set sizes. A larger context size results in a more accurate **prediction** of the **ground truth** simulation.

Here, τ influences execution speed, while f depends on the basis functions $\boldsymbol{\varphi}$ in force-space, the weights $\boldsymbol{w}$ and the exponential decaying phase x. Solving this equation typically is computationally intensive, particularly when the gradient $dy/d\boldsymbol{w}$ is required (Bahl et al., 2020). ProDMPs (Li et al., 2023) instead solve Equation equation 7 with pre-computed basis functions $\boldsymbol{\Phi}$ in position-space as

$$y(t) = c_1 y_1(t) + c_2 y_2(t) + \boldsymbol{\Phi}(t)^\top \boldsymbol{w}.$$

The term $c_1 y_1(t) + c_2 y_2(t)$ only depends on the initial conditions $[y(t_0), \dot{y}(t_0)]$. ProDMPs thus generate smooth trajectories at an arbitrary temporal resolution from low-dimensional weights $\boldsymbol{w}$. They crucially allow for efficient gradient computation, and can respect different initial conditions such as positions or velocities. We provide an extensive mathematical background of ProDMPs in Appendix A.

Meta-Learning and Graph Network Simulators. To enable generalization across tasks with varying properties, we frame GNS as a meta-learning problem. In this setup, each task corresponds to a simulation of a deformable object with unknown material properties. The goal is to learn a simulator that can adapt quickly to a specific scenario using a limited amount of context data. Following the notation of Volpp et al. (2021), the meta-dataset $\mathcal{D} = \mathcal{D}_{1:L}$ consists of simulation trajectories $\mathcal{D}_l = \{\mathcal{G}_{l,1} \dots \mathcal{G}_{l,T}\}$ of length T, where T is the trajectory length. Each simulation step $\mathcal{G}_{l,t} = (\boldsymbol{m}_{l,t}, \boldsymbol{u}_{l,t})$ represents a graph capturing both the deformable object mesh $\boldsymbol{m}_{l,t}$ (describing its position and topology) and an optional rigid collider $\boldsymbol{u}_{l,t}$. Physical proximity is used to define graph edges that model interactions between the deformable object and the collider. At test time, the first $T^c \ll T$ simulation frames, $\mathcal{G}_{l,1:T^c}$, are observed as a context set to predict the remaining trajectory. Following prior work (Pfaff et al., 2021), we assume access to the full collider trajectory during prediction, resulting in the complete *context set*:

$$\mathcal{D}_l^c = \{\mathcal{G}_{l,1}, \dots \mathcal{G}_{l,T^c}\} \cup \{\boldsymbol{u}_{l,T^c+1}, \dots, \boldsymbol{u}_{l,T}\}. \tag{2}$$

To provide a clear reference point for discussion, we define the *anchor time step* as the final time step T^c of the context set. The corresponding *anchor graph*, $\mathcal{G}_{l,T^c}$, represents the system's state at this point and serves as the starting state for trajectory prediction by the GNSs. Notably, the anchor graph $\mathcal{G}_{l,T^c}$ alone does not capture the complete system state, as the material properties of the deformable object remain unknown. These properties must be inferred from the prior simulation steps, $\mathcal{G}_{l,1:T^c}$, to enable accurate trajectory predictions. Figure 3 illustrates this setup.

Model Architecture. Our model architecture, M3GN, is designed to learn from context data and predict future simulation steps by leveraging a combination of graph network simulation and meta-learning techniques. The architecture consists of two parts: the computation of the latent task description from the context data and the actual graph network simulation of future simulation steps. We base our context processing on the Conditional Neural Process (CNP) (Garnelo et al., 2018a), as it efficiently encodes a latent description over tasks given a set of context observations. Omitting the task index l to avoid clutter, CNPs expect a context set $\{(\boldsymbol{x}_1, \boldsymbol{y}_1), \dots, (\boldsymbol{x}_{N^c}, \boldsymbol{y}_{N^c})\}$ consisting of inputs $\boldsymbol{x}_i$ and corresponding targets $\boldsymbol{y}_i$. We translate our context set $\mathcal{D}^c$ from Equation 2 to this format by using each graph as an input, and setting its labels as the node-wise velocities. This approach allows the model to focus on dynamics rather than absolute positions, which are more task-specific. Assuming a forward-Euler integration scheme with a time step of 1, we numerically approximate the

velocities as the difference between consecutive simulation steps. The input graph $\boldsymbol{x}_i$ represents the simulation state at time step i, including mesh and collider, while $\boldsymbol{y}_i$ encodes the change in positions between consecutive time steps.

$$\boldsymbol{x}_i = \mathcal{G}_i, \qquad \boldsymbol{y}_i = \text{pos}(\mathcal{G}_{i+1}) - \text{pos}(\mathcal{G}_i).$$

To account for the known collider trajectory, we add its relative position as an additional node feature. Specifically, we include the position of the collider at time step T, $\text{pos}(\boldsymbol{u}_T)$, relative to its current position, $\text{pos}(\boldsymbol{u}_i)$. Preliminary testing indicated that incorporating the complete future collider trajectory $\text{pos}(\boldsymbol{u}_{T^c}), ...\text{pos}(\boldsymbol{u}_T)$ did not improve the results on our task suite. Given a context set $\mathcal{D}^c$ with anchor time step T^c, this results in $T^c - 1$ tuples $(\boldsymbol{x}_i, \boldsymbol{y}_i)$. A shared GNN encoder $h_{\boldsymbol{\theta}}$ computes node-level latent features

$$\boldsymbol{z}_{i,v} = h_{\boldsymbol{\theta}}(\boldsymbol{x}_i, \boldsymbol{y}_i) \in \mathbb{R}^{T^c \times |\mathcal{V}| \times d_z} \tag{3}$$

for each context time step with feature dimension d_z. We then aggregate over the context set to obtain $\boldsymbol{z}_v = \bigoplus \boldsymbol{z}_{i,v} \in \mathbb{R}^{|\mathcal{V}| \times d_z}$, using $\bigoplus = \max$ as the aggregation operator. Intuitively, $\boldsymbol{z}_v$ is a representation of the task inferred from the context data $\mathcal{D}^c$, and encodes material properties, future collider movements, and high-level deformations of the simulation. While we use node-level latent features for M3GN, one could additionally aggregate over the nodes to obtain a graph-global task descriptor $\boldsymbol{z} = \bigotimes \boldsymbol{z}_v \in \mathbb{R}^{d_z}$. We explore this choice and different aggregation functions $\bigoplus, \bigotimes$ in Section 4.

Once the task descriptor has been computed, it serves as the input to the predictive stage, enabling simulation of future trajectories. We concatenate the latent description $\boldsymbol{z}_v$ with the node features of the anchor graph $\mathcal{G}_{T^c}$ and subsequently use a GNN $g_{\boldsymbol{\theta}}$ to predict per-node ProDMP weights

$$\boldsymbol{w}_v = g_{\boldsymbol{\theta}}(\mathcal{G}_{T^c}, \boldsymbol{z}_v) \in \mathbb{R}^{|\mathcal{V}| \times d_w}. \tag{4}$$

The ProDMP trajectory generator $f(\boldsymbol{w}_v) \in \mathbb{R}^{T \times |\mathcal{V}| \times d_{\text{world}}}$ transforms these weights into per-node object trajectories over the entire simulation horizon. This approach can be seen as a form of temporal bundling (Brandstetter et al., 2022), requiring a single function call. In comparison, existing GNS train on next-step dynamics and require one call per step during their auto-regressive inference scheme (Pfaff et al., 2021; Allen et al., 2023). The trajectory-level view further allows us to omit noise injection during training, which MGN requires to generalize from learned next-step predictions to multi-step rollouts during inference. We provide a visualization of our model architecture in Figure 2 and refer to Appendix B for further details.

Meta Training. The goal of meta-learning is to automatically encode inductive biases towards the task distribution extracted from the meta-dataset $\mathcal{D}$ into the task-global parameter $\boldsymbol{\theta}$. To this end, we minimize the negative conditional log probability (Garnelo et al., 2018a)

$$\mathcal{L}(\boldsymbol{\theta}) = -\mathbb{E}_{l \sim 1:L} \Big[\mathbb{E}_{T^c \sim T_{\min}:T_{\max}} \big[\log p_{\boldsymbol{\theta}}(\text{pos}(\boldsymbol{m}_{l,1:T}) \mid \mathcal{D}_l^c) \big] \Big]. \tag{5}$$

Each training batch consists of a task $\mathcal{D}_l$ for which we sample a context size T^c uniformly between $T_{\min}$ and $T_{\max}$ to ensure that the model learns to handle different context set sizes. We then compute the latent task descriptor $\boldsymbol{z}_v$ and subsequently the predicted node trajectories $f(g_{\boldsymbol{\theta}}(\mathcal{G}_{l,T^c}, \boldsymbol{z}_v))$ as described in Equation 3 and Equation 4. The likelihood $p_{\boldsymbol{\theta}}$ is defined to be the Gaussian

$$p_{\boldsymbol{\theta}}(\text{pos}(\boldsymbol{m}_{l,1:T}) \mid \mathcal{D}_l^c) = \mathcal{N}(\text{pos}(\boldsymbol{m}_{l,1:T}) \mid f(g_{\boldsymbol{\theta}}(\mathcal{G}_{l,T^c}, \boldsymbol{z}_v)), \boldsymbol{\sigma}_o). \tag{6}$$

Since the training simulations are not affected by noise, we are not modeling the output variance and set it to $\boldsymbol{\sigma}_0 = 1$. Together with taking the mean over the nodes and time steps to stabilize training, optimizing the Gaussian log likelihood from Equation 6 is equivalent to minimizing the MSE

$$\log p_{\boldsymbol{\theta}}(\text{pos}(\boldsymbol{m}_{l,1:T}) \mid \mathcal{D}_l^c) \simeq \frac{1}{T |\mathcal{V}| d_{\text{world}}} \sum_{t,v,i} \Big(\text{pos}(\boldsymbol{m}_{l,t})_{v,i} - f(g_{\boldsymbol{\theta}}(\mathcal{G}_{l,T^c}, \boldsymbol{z}_v))_{t,v,i} \Big)^2.$$

The whole architecture is trained end-to-end using the loss $\mathcal{L}(\boldsymbol{\theta})$ from Equation 5. After the meta-training, we fix $\boldsymbol{\theta}$, which now encodes inductive biases towards the meta-data $\mathcal{D}$.

Figure 4: Comparison of the final simulation step between **M3GN** and **MGN** on all datasets. From (**Left**) to (**Right**): (**Top**) *Planar Bending* and *Deformable Plate* with an anchor time step of 2. (**Bottom**) *Tissue Manipulation* with a context size of 6, and *Falling Teddy Bear* and *Mixed Objects Falling* with an anchor time step of 20. M3GN provides much better alignment to the **ground truth** simulation on all tasks, except for *Tissue Manipulation*, where MGN also solves the task well.

4 EXPERIMENTS

Setup. Our experimental setup largely follows previous work (Linkerhägner et al., 2023). The graph representation views the mesh vertices as nodes and adds edges according to the mesh topology within an object, and based on Euclidean distance between different objects. We employ one-hot encoding to differentiate between deformable objects and colliders, omitting explicit world edges (Pfaff et al., 2021). The edges additionally contain the relative distances between their nodes.

For both the context MPN as well as the simulator MPN, we use 15 message passing steps. Each message passing step uses separate 1-layer MLPs with a latent dimension of 128 and LeakyReLU activations for its node and edge updates. We evaluate the *Full Rollout MSE*, which is calculated as the average of all simulation MSEs following the anchor time step, and the 10-*step MSE*, which is the average performance for the next 10 simulation steps following the anchor time step. Both metrics are averaged over all test set trajectories. We report the interquartile mean and bootstrapped confidence intervals (Agarwal et al., 2021) over 8 random seeds for each experiment. We evaluate the metrics for various context sizes ranging from 2 to 30 steps, always setting the anchor time step to the last context mesh position. Appendix C provides additional details on our experimental setup.

Datasets. We validate our method on five different simulation datasets based on three different mesh-based physics simulators. All task spaces are normalized to $[-1, 1]^3$. These include a 2D *Deformable Plate (DP)* task and a 3D *Tissue Manipulation (TM)* task (Linkerhägner et al., 2023) In both datasets, the material property, Poisson's ratio (Lim, 2015) was randomized. *Deformable Plate* simulates different trapezoids that are deformed by a circular collider with constant velocity and varying size and starting position. Each trajectory consists of a mesh with 81 nodes that is deformed over 39 time steps. *Tissue Manipulation* considers a surgical robotics scenario where a piece of tissue is deformed by a gripper. The gripper is attached to a fixed object position and moves in a random direction with constant velocity. The mesh comprises 361 nodes and the simulation has 100 steps.

We further propose three additional 3D datasets. *Planar Bending (PB)* simulates the bending of a 2D plane when two constant forces perpendicular to the plane are applied at different positions. As the Young's modulus is varied between sheets, this dataset constitutes a simplified stamp forming process, as common in material engineering (Zimmerling et al., 2022). The simulations are generated with Abaqus (Smith, 2009), comprising 50 time steps and a plate with 225 nodes. We test two different data splits: The in-distribution (ID) split uses material properties in the test set that the model has seen during training, while the out-of-distribution (OOD) split uses Young's modulus values outside the training domain for the test dataset.

The other two tasks place a randomly rotated deformable object at a specific height and let it fall to and collide with the ground. *Falling Teddy Bear (FTB)* considers the titular teddy bear as its only object, whereas six different objects are considered for *Mixed Objects Falling (MOF)*. Each trajectory assigns a random Poisson's ratio and random Young's modulus to the falling object, thus influencing its deformation upon contact with the floor. Each trajectory consists of 200 time steps. The object

Figure 5: Log-scale MSE over full rollouts for different methods under all tasks, including an additional figure for Planar Bending task using an out-of-distribution (OOD) test dataset of material properties. Overall, M3GN steadily improves its performance when provided with additional context information and a later anchor time step. Our method generally improves over MGN, likely due to the MP trajectory representation, and outperforms MGN (Oracle) when provided with sufficient context information.

meshes have up to 350 nodes and are shown in Figure 10 in the appendix. For simplicity, we only consider the triangular surface meshes for the experimental setup. Further information about the graph encoding are given in Appendix B.1, while we provide detailed information of the dataset sizes and preprocessing steps in Appendix D.

Baselines and Ablations. We compare our method to MGN (Pfaff et al., 2021) both with and without additional material property information as a node feature. When provided, this *oracle* information renders the simulation deterministic with respect to the initial system state. We never provide this node feature to M3GN. MGN iteratively predicts the velocities of the current simulation step to generate the next mesh state. It is trained to minimize the 1-step MSE over node velocities and employs Gaussian input noise (Brandstetter et al., 2022) during training to prevent error accumulation and stabilize auto-regressive rollouts during inference. We use the same hyperparameters as our method and tune the input noise level for each task to ensure strong performance.

Additionally, we ablate different design choices of M3GN on *Planar Bending* and *Deformable Plate*. To investigate the effect of the meta-learning approach, we train an MGN (MP) variant that uses ProDMPs predictions, but omits a context aggregation and thus has no latent task description z_v. Similarly, we compare to M3GN (Step-based), which performs a next-step prediction of the dynamics instead of predicting ProDMP parameters, but otherwise follows the CNP training scheme to learn a latent task description. Finally, we compare the deterministic CNP approach to both MP and step-based probabilistic Neural Process (NP) approaches. Here, we get diagonal Gaussian distributions as the outputs of the context MPN, which we aggregate using Bayesian context aggregation (Volpp et al., 2021). We further investigate if node aggregation of the latent task description is beneficial by applying a maximum aggregation of the node features before the context aggregation. While standard CNPs require a permutation-invariant context aggregation, our context has a temporal structure. We thus experiment with a small transformer model with 4 transformer blocks, 4 attention heads, temporal encoding and a latent dimension of 32 as an aggregator. The transformer takes the sequence of outputs of the context MPN and predicts the aggregated node-level task description z_v.

Results. Figure 4 visualizes exemplary final simulation steps for M3GN and MGN for all tasks. M3GN aggregates context information that it uses to condition node-level ProDMP representations of the simulated trajectory. This approach leads to accurate simulations, providing much better

Figure 6: Log-scale MSE over full rollouts for the *Planar Bending* (**Left**) and *Deformable Plate* (**Right**) tasks for different meta-learning and MP variants. Using a ProDMP representation for MGN improves performance. CNPs and NPs with a next-step prediction do not improve over standard MGN. A NP instead of an CNP architecture for M3GN slightly reduces performance.

Figure 7: Log-scale MSE over full rollouts for the *Planar Bending* (**Left**) and *Deformable Plate* (**Right**) tasks for different context and node aggregation methods. The node-level maximum context aggregation of M3GN performs best for *Planar Bending*, while all methods work roughly equally well on the *Deformable Plate* task.

alignment to the ground truth simulation than the step-based MGN on all tasks. Appendix E.2 shows visualizations of full simulation rollouts for all tasks and methods.[2]

Figure 5 shows the full rollout MSE for M3GN, MGN and MGN (Oracle) on all tasks. In general, the additional material information improves performance of MGN (Oracle) on both datasets compared to MGN. A later anchor time step improves performance for all methods, presumably because the remaining simulation is shorter. On *Deformable Plate*, M3GN surpasses MGN (Oracle) for a context size of 10, likely because the additional context improves the latent task description. For the *Planar Bending* task, M3GN significantly outperforms the step-based baselines across context sizes, likely because the temporal smoothness of the ProDMP trajectory is a strong inductive bias for the gradual bending of the simulated plane. Furthermore, M3GN generalizes well to the OOD task, while the MGN methods fail to extrapolate to unseen material properties.

Next, in a more difficult task, such as *Tissue Manipulation*, increasing the context size greatly improves performance for M3GN, whereas the step-based methods only slightly benefit from a later anchor time step. On the last two tasks, i.e. *Falling Teddy Bear* and *Mixed Objects Falling*, the step-based MGN methods fail to provide accurate long-term simulations. Here, the predicted trajectories usually qualitatively deviate from the ground truth, either causing an object drift or a misalignment of, e.g., teddy limbs, to the point that providing additional material information only yields marginal improvements. For M3GN, the ProDMP's temporally consistent movements combined with context aggregation to provide consistent simulations alleviates these issues, significantly improving over the baselines. The bottom of Figure 4 provides examples. Interestingly, providing more context information does not improve performance for either of these two tasks. A likely reason for this behavior is that most early context steps consist of a falling object, resulting in similar graph representations, which may cause the GNN context encoders to overfit.

---

[2]Videos of these simulations are in the supplementary material.

Figure 6 provides evaluations for various ablations, further supporting these results. Equipping MGN with a ProDMP representation improves performance, especially for *Planar Bending*. Combining NPs and ProDMPs uniquely leads to the strong performance of M3GN, suggesting that the latent task description extracted from the context set is particularly well-suited for trajectory-level representations of the simulations. Performance decreases slightly when using an NP instead of a CNP, indicating that the latent distribution in NPs is not beneficial for our GNS setup. Additional ablations in Figure 7 show similar performance for different aggregation schemes. Our node-level maximum context aggregation is the simplest and works slightly better than the alternatives for *Planar Bending*.

To provide a more detailed understanding of our model's performance, we include additional plots in the appendix showing the Mean Squared Error (MSE) over time for the trajectory, rather than just the final averaged MSE. These plots demonstrate the temporal progression of errors, offering insights into the model's behavior throughout the simulation. We additionally report the 10-step MSE in Appendix E.1, finding that the relative improvement of M3GN compared to the baselines matches or exceeds that on the full rollout MSE for all tasks. Furthermore, we present a visualization of the latent space for M3GN in the Appendix, Figure 15, which reveals that simulations with similar material properties are clustered together. This structure in the latent space highlights the model's ability to effectively differentiate between different material behaviors while preserving the relationships between similar properties. Finally, we compare the inference speed between M3GN and MGN in Figure 8. The ProDMPs trajectory representation of M3GN decreases the amount of required model calls, resulting in an inference-time speedup of up to 32 times compared to MGN, and up to 400 times compared to the ground truth simulators (Gth Simulators). We encode the context set for M3GN in parallel, resulting in a relatively minor cost for the context computation and aggregation for all tasks. In addition, our M3GN requires only one GNN forward pass via ProDMP to compute the full trajectory, enabling much faster inference. While MGN does not perform any context processing, its iterative rollout is inherently sequential and requires multiple forward passes.

Figure 8: Runtime comparison on four tasks between the learned methods and the different ground truth simulators. Note the log scale on the y-axis.

5 CONCLUSION

We introduce Movement-Primitive Meta-MeshGraphNet (M3GN), a novel Graph Network Simulator that combines movement primitives and trajectory-level meta-learning for efficient and accurate long-term predictions in physical simulations. Our method dynamically adapts to provided context information during inference, allowing for an accurate prediction of deformations under unknown object properties. Additionally, it effectively addresses the issue of error accumulation while reducing the number of required simulator function calls. To validate the effectiveness of M3GN, we propose three novel deformation prediction tasks with uncertain material properties. Results on these tasks and existing datasets show that our method consistently outperforms a strong Graph Network Simulators baseline, even when providing the baseline with oracle information about the material property.

Limitations and Future Work. We currently consider each trajectory as a task, and require initial states of this trajectory as a context set during inference. As generating such data is often impractical, we plan to group simulations with the same system properties into the same task. This adaptation will enable data-efficient generalization to unseen properties regardless of the underlying simulated objects. We also plan to integrate online re-planning of trajectories, predicting trajectory segments with every model forward pass. This process may increase coordination between simulated nodes across segments, while maintaining the benefits of a compact multi-step trajectory representation.

Broader Impact Statement Our proposed Graph Network Simulator can positively impact various fields relying on computational modeling and simulation by significantly reducing computational cost compared to traditional simulators while providing accurate simulations. However, efficient and accurate simulation of physical systems also comes with potential negative impacts, such as, e.g., the development of advanced weapon models.

REFERENCES

Agarwal, R., Schwarzer, M., Castro, P. S., Courville, A. C., and Bellemare, M. Deep reinforcement learning at the edge of the statistical precipice. In Ranzato, M., Beygelzimer, A., Dauphin, Y., Liang, P., and Vaughan, J. W. (eds.), *Advances in Neural Information Processing Systems*, volume 34, pp. 29304–29320. Curran Associates, Inc., 2021. URL https://proceedings.neurips.cc/paper_files/paper/2021/file/f514cec81cb148559cf475e7426eed5e-Paper.pdf.

Allen, K., Lopez-Guevara, T., Stachenfeld, K. L., Sanchez Gonzalez, A., Battaglia, P., Hamrick, J. B., and Pfaff, T. Inverse design for fluid-structure interactions using graph network simulators. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A. (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 13759–13774. Curran Associates, Inc., 2022a. URL https://proceedings.neurips.cc/paper_files/paper/2022/file/59593615e358d52295578e0d8e94ec4a-Paper-Conference.pdf.

Allen, K. R., Guevara, T. L., Rubanova, Y., Stachenfeld, K., Sanchez-Gonzalez, A., Battaglia, P., and Pfaff, T. Graph network simulators can learn discontinuous, rigid contact dynamics. *Conference on Robot Learning (CoRL).*, 2022b.

Allen, K. R., Rubanova, Y., Lopez-Guevara, T., Whitney, W. F., Sanchez-Gonzalez, A., Battaglia, P., and Pfaff, T. Learning rigid dynamics with face interaction graph networks. In *The Eleventh International Conference on Learning Representations*, 2023.

Andrychowicz, M., Denil, M., Colmenarejo, S. G., Hoffman, M. W., Pfau, D., Schaul, T., and de Freitas, N. Learning to Learn by Gradient Descent by Gradient Descent. *Advances in Neural Information Processing Systems*, 2016.

Antonova, R., Yang, J., Sundaresan, P., Fox, D., Ramos, F., and Bohg, J. A bayesian treatment of real-to-sim for deformable object manipulation. *IEEE Robotics and Automation Letters*, 7(3): 5819–5826, 2022.

Bahl, S., Mukadam, M., Gupta, A., and Pathak, D. Neural dynamic policies for end-to-end sensorimotor learning. *Advances in Neural Information Processing Systems*, 33:5058–5069, 2020.

Bakker, B. and Heskes, T. Task clustering and gating for Bayesian multitask learning. *Journal of Machine Learning Research*, 2003.

Baqué, P., Remelli, E., Fleuret, F., and Fua, P. Geodesic convolutional shape optimization. In Dy, J. G. and Krause, A. (eds.), *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*, volume 80 of *Proceedings of Machine Learning Research*, pp. 481–490. PMLR, 2018. URL http://proceedings.mlr.press/v80/baque18a.html.

Battaglia, P., Pascanu, R., Lai, M., Jimenez Rezende, D., and kavukcuoglu, k. Interaction networks for learning about objects, relations and physics. In Lee, D., Sugiyama, M., Luxburg, U., Guyon, I., and Garnett, R. (eds.), *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL https://proceedings.neurips.cc/paper/2016/file/3147da8ab4a0437c15ef51a5cc7f2dc4-Paper.pdf.

Battaglia, P. W., Hamrick, J. B., Bapst, V., Sanchez-Gonzalez, A., Zambaldi, V. F., Malinowski, M., Tacchetti, A., Raposo, D., Santoro, A., Faulkner, R., Gülçehre, Ç., Song, H. F., Ballard, A. J., Gilmer, J., Dahl, G. E., Vaswani, A., Allen, K. R., Nash, C., Langston, V., Dyer, C., Heess, N., Wierstra, D., Kohli, P., Botvinick, M., Vinyals, O., Li, Y., and Pascanu, R. Relational inductive biases, deep learning, and graph networks. *CoRR*, abs/1806.01261, 2018. URL http://arxiv.org/abs/1806.01261.

Bengio, Y., Bengio, S., and Cloutier, J. Learning a synaptic learning rule. *International Joint Conference on Neural Networks*, 1991.

Bodnar, C., Bruinsma, W. P., Lucic, A., Stanley, M., Brandstetter, J., Garvan, P., Riechert, M., Weyn, J. A., Dong, H., Vaughan, A., Gupta, J. K., Thambiratnam, K., Archibald, A., Heider, E., Welling, M., Turner, R. E., and Perdikaris, P. Aurora: A foundation model of the atmosphere. *CoRR*,

abs/2405.13063, 2024. doi: 10.48550/ARXIV.2405.13063. URL https://doi.org/10.48550/arXiv.2405.13063.

Brandstetter, J., Worrall, D. E., and Welling, M. Message passing neural pde solvers. In *International Conference on Learning Representations*, 2022.

Brenner, S. C. and Scott, L. R. *The mathematical theory of finite element methods*, volume 3. Springer, 2008.

Bronstein, M. M., Bruna, J., Cohen, T., and Velickovic, P. Geometric deep learning: Grids, groups, graphs, geodesics, and gauges. *CoRR*, abs/2104.13478, 2021. URL https://arxiv.org/abs/2104.13478.

Chung, T. Finite element analysis in fluid dynamics. *NASA STI/Recon Technical Report A*, 78:44102, 1978.

Connor, J. J. and Brebbia, C. A. *Finite element techniques for fluid flow*. Newnes, 2013.

Da Wang, Y., Blunt, M. J., Armstrong, R. T., and Mostaghimi, P. Deep learning in pore scale imaging and modeling. *Earth-Science Reviews*, 215:103555, 2021.

Durasov, N., Lukoyanov, A., Donier, J., and Fua, P. Debosh: Deep bayesian shape optimization. *arXiv preprint arXiv:2109.13337*, 2021.

Faure, F., Duriez, C., Delingette, H., Allard, J., Gilles, B., Marchesseau, S., Talbot, H., Courtecuisse, H., Bousquet, G., Peterlik, I., and Cotin, S. SOFA: A Multi-Model Framework for Interactive Physical Simulation. In Payan, Y. (ed.), *Soft Tissue Biomechanical Modeling for Computer Assisted Surgery*, volume 11 of *Studies in Mechanobiology, Tissue Engineering and Biomaterials*, pp. 283–321. Springer, June 2012. doi: 10.1007/8415_2012_125. URL https://hal.inria.fr/hal-00681539.

Finn, C., Abbeel, P., and Levine, S. Model-agnostic meta-learning for fast adaptation of deep networks. *International Conference on Machine Learning*, 2017.

Finn, C., Xu, K., and Levine, S. Probabilistic Model-Agnostic Meta-Learning. *Advances in Neural Information Processing Systems*, 2018.

Fortunato, M., Pfaff, T., Wirnsberger, P., Pritzel, A., and Battaglia, P. Multiscale meshgraphnets. In *ICML 2022 2nd AI for Science Workshop*, 2022. URL https://openreview.net/forum?id=G3TRIsmMhhf.

Freymuth, N., Dahlinger, P., Würth, T., Kärger, L., and Neumann, G. Swarm reinforcement learning for adaptive mesh refinement. *Neural Information Processing Systems*, 37, 2023.

Garnelo, M., Rosenbaum, D., Maddison, C., Ramalho, T., Saxton, D., Shanahan, M., Teh, Y. W., Rezende, D., and Eslami, S. M. A. Conditional neural processes. *International Conference on Machine Learning*, 2018a.

Garnelo, M., Schwarz, J., Rosenbaum, D., Viola, F., Rezende, D. J., Eslami, S. M. A., and Teh, Y. W. Neural processes. *ICML Workshop on Theoretical Foundations and Applications of Deep Generative Models*, 2018b.

Golovin, D., Solnik, B., Moitra, S., Kochanski, G., Karro, J., and Sculley, D. Google vizier: a service for black-box optimization. *International Conference on Knowledge Discovery and Data Mining*, 2017.

Gordon, J., Bronskill, J., Bauer, M., Nowozin, S., and Turner, R. E. Meta-Learning Probabilistic Inference for Prediction. *International Conference on Learning Representations*, 2019.

Grant, E., Finn, C., Levine, S., Darrell, T., and Griffiths, T. L. Recasting Gradient-Based Meta-Learning as Hierarchical Bayes. *International Conference on Learning Representations*, 2018.

Guo, X., Li, W., and Iorio, F. Convolutional neural networks for steady flow approximation. In *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '16, pp. 481–490, New York, NY, USA, 2016. Association for Computing Machinery. ISBN 9781450342322. doi: 10.1145/2939672.2939738. URL https://doi.org/10.1145/2939672.2939738.

Han, X., Gao, H., Pfaff, T., Wang, J., and Liu, L. Predicting physics in mesh-reduced space with temporal attention. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net, 2022. URL https://openreview.net/forum?id=XctLdNfCmP.

Heskes, T. Empirical Bayes for learning to learn. *International Conference on Machine Learning*, 2000.

Hospedales, T., Antoniou, A., Micaelli, P., and Storkey, A. Meta-learning in neural networks: a survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2022.

Hu, W., Shuaibi, M., Das, A., Goyal, S., Sriram, A., Leskovec, J., Parikh, D., and Zitnick, C. L. Forcenet: A graph neural network for large-scale quantum calculations. In *ICLR 2021 SimDL Workshop*, volume 20, 2021.

Hughes, T. J., Cottrell, J. A., and Bazilevs, Y. Isogeometric analysis: Cad, finite elements, nurbs, exact geometry and mesh refinement. *Computer methods in applied mechanics and engineering*, 194(39-41):4135–4195, 2005.

Jin, J.-M. *The finite element method in electromagnetics*. John Wiley & Sons, 2015.

Kim, H., Mnih, A., Schwarz, J., Garnelo, M., Eslami, A., Rosenbaum, D., Vinyals, O., and Teh, Y. W. Attentive neural processes. *International Conference on Learning Representations*, 2019.

Kim, T., Yoon, J., Dia, O., Kim, S., Bengio, Y., and Ahn, S. Bayesian Model-Agnostic Meta-Learning. *Advances in Neural Information Processing Systems*, 2018.

Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In Bengio, Y. and LeCun, Y. (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Kingma, D. P. and Welling, M. Auto-encoding variational bayes. *International Conference on Learning Representations*, 2014.

Krizhevsky, A., Sutskever, I., and Hinton, G. E. Imagenet classification with deep convolutional neural networks. In Pereira, F., Burges, C. J. C., Bottou, L., and Weinberger, K. Q. (eds.), *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012.

Li, G., Jin, Z., Volpp, M., Otto, F., Lioutikov, R., and Neumann, G. Prodmp: A unified perspective on dynamic and probabilistic movement primitives. *IEEE Robotics and Automation Letters*, 8(4): 2325–2332, 2023.

Li, G., Zhou, H., Roth, D., Thilges, S., Otto, F., Lioutikov, R., and Neumann, G. Open the black box: Step-based policy updates for temporally-correlated episodic reinforcement learning, 2024.

Li, J., Du, X., and Martins, J. R. Machine learning in aerodynamic shape optimization. *Progress in Aerospace Sciences*, 134:100849, 2022.

Li, Y., Wu, J., Tedrake, R., Tenenbaum, J. B., and Torralba, A. Learning particle dynamics for manipulating rigid bodies, deformable objects, and fluids. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=rJgbSn09Ym.

Lim, T.-C. *Auxetic Materials and Structures*. Springer Singapore, 01 2015. ISBN 978-981-287-274-6. doi: 10.1007/978-981-287-275-3. URL https://doi.org/10.1007/978-981-287-275-3.

Linkerhägner, J., Freymuth, N., Scheikl, P. M., Mathis-Ullrich, F., and Neumann, G. Grounding graph network simulators using physical sensor observations. In *The Eleventh International Conference on Learning Representations*, 2023.

Lopez-Guevara, T., Rubanova, Y., Whitney, W. F., Pfaff, T., Stachenfeld, K., and Allen, K. R. Scaling face interaction graph networks to real world scenes. *arXiv preprint arXiv:2401.11985*, 2024.

Louizos, C., Shi, X., Schutte, K., and Welling, M. The functional neural process. *Advances in Neural Information Processing Systems*, 2019.

Mora, M. A. Z., Peychev, M., Ha, S., Vechev, M., and Coros, S. Pods: Policy optimization via differentiable simulation. In Meila, M. and Zhang, T. (eds.), *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pp. 7805–7817. PMLR, 18–24 Jul 2021. URL `http://proceedings.mlr.press/v139/mora21a.html`.

NVIDIA. Isaac sim, 2022a. URL `https://developer.nvidia.com/isaac-sim`.

NVIDIA. Nvidia physx sdk, 2022b. URL `https://developer.nvidia.com/physx-sdk`.

Otto, F., Celik, O., Zhou, H., Ziesche, H., Vien, N. A., and Neumann, G. Deep black-box reinforcement learning with movement primitives. In Liu, K., Kulic, D., and Ichnowski, J. (eds.), *Conference on Robot Learning, CoRL 2022, 14-18 December 2022, Auckland, New Zealand*, volume 205 of *Proceedings of Machine Learning Research*, pp. 1244–1265. PMLR, 2022. URL `https://proceedings.mlr.press/v205/otto23a.html`.

Paraschos, A., Daniel, C., Peters, J. R., and Neumann, G. Probabilistic movement primitives. *Advances in neural information processing systems*, 26, 2013.

Paszynski, M. *Fast solvers for mesh-based computations*. CRC Press, 2016.

Pfaff, T., Fortunato, M., Sanchez-Gonzalez, A., and Battaglia, P. W. Learning mesh-based simulation with graph networks. In *International Conference on Learning Representations*, 2021. URL `https://arxiv.org/abs/2010.03409`.

Plewa, T., Linde, T., Weirs, V. G., et al. *Adaptive mesh refinement-theory and applications*. Springer, 2005.

Polycarpou, A. C. *Introduction to the finite element method in electromagnetics*. Springer Nature, 2022.

Ravi, S. and Larochelle, H. Optimization as a model for few-shot learning. *International Conference on Learning Representations*, 2017.

Reddy, C. *Finite element method for eigenvalue problems in electromagnetics*, volume 3485. NASA, Langley Research Center, 1994.

Reddy, J. N. *Introduction to the finite element method*. McGraw-Hill Education, 2019.

Reddy, J. N. and Gartling, D. K. *The finite element method in heat transfer and fluid dynamics*. CRC press, 2010.

Rezende, D. J., Mohamed, S., and Wierstra, D. Stochastic backpropagation and approximate inference in deep generative models. *International Conference on Machine Learning*, 2014.

Sanchez-Gonzalez, A., Heess, N., Springenberg, J. T., Merel, J., Riedmiller, M., Hadsell, R., and Battaglia, P. Graph networks as learnable physics engines for inference and control. In Dy, J. and Krause, A. (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 4470–4479. PMLR, 10–15 Jul 2018. URL `https://proceedings.mlr.press/v80/sanchez-gonzalez18a.html`.

Sanchez-Gonzalez, A., Godwin, J., Pfaff, T., Ying, R., Leskovec, J., and Battaglia, P. Learning to simulate complex physics with graph networks. In *Proceedings of the 37th International Conference on Machine Learning*, pp. 8459–8468. PMLR, 2020.

Santoro, A., Bartunov, S., Botvinick, M. M., Wierstra, D., and Lillicrap, T. P. Meta-learning with memory-augmented neural networks. *International Conference on Machine Learning*, 2016.

Scarselli, F., Gori, M., Tsoi, A. C., Hagenbuchner, M., and Monfardini, G. The graph neural network model. *IEEE Transactions on Neural Networks*, 20(1):61–80, 2009. doi: 10.1109/TNN.2008. 2005605.

Schaal, S. Dynamic movement primitives-a framework for motor control in humans and humanoid robotics. In *Adaptive motion of animals and machines*, pp. 261–280. Springer, 2006.

Scheikl, P. M., Tagliabue, E., Gyenes, B., Wagner, M., Dall'Alba, D., Fiorini, P., and Mathis-Ullrich, F. Sim-to-real transfer for visual reinforcement learning of deformable object manipulation for robot-assisted surgery. *IEEE Robotics and Automation Letters*, 8(2):560–567, 2022.

Schmidhuber, J. Learning to control fast-weight memories: an alternative to dynamic recurrent networks. *Neural Computation*, 1992.

Seker, M. Y., Imre, M., Piater, J. H., and Ugur, E. Conditional neural movement primitives. In *Robotics: Science and Systems*, volume 10, 2019.

Smith, M. *ABAQUS/Standard User's Manual, Version 6.9.* Dassault Systèmes Simulia Corp, United States, 2009.

Snell, J., Swersky, K., and Zemel, R. S. Prototypical networks for few-shot learning. *Advances in Neural Information Processing Systems*, 2017.

Stanova, E., Fedorko, G., Kmet, S., Molnar, V., and Fabian, M. Finite element analysis of spiral strands with different shapes subjected to axial loads. *Advances in engineering software*, 83:45–58, 2015.

Thrun, S. and Pratt, L. *Learning to Learn*. Kluwer Academic Publishers, 1998.

van der Maaten, L. and Hinton, G. Visualizing data using t-sne. *Journal of Machine Learning Research*, 9(86):2579–2605, 2008. URL http://jmlr.org/papers/v9/vandermaaten08a.html.

Vilalta, R. and Drissi, Y. A Perspective View and Survey of Meta-Learning. *Artificial Intelligence Review*, 2005.

Volpp, M., Fröhlich, L. P., Fischer, K., Doerr, A., Falkner, S., Hutter, F., and Daniel, C. Meta-learning acquisition functions for transfer learning in Bayesian optimization. *International Conference on Learning Representations*, 2019.

Volpp, M., Flürenbrock, F., Großberger, L., Daniel, C., and Neumann, G. Bayesian context aggregation for neural processes. *International Conference on Learning Representations*, 2021.

Volpp, M., Dahlinger, P., Becker, P., Daniel, C., and Neumann, G. Accurate bayesian meta-learning by accurate task posterior inference. In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net, 2023. URL https://openreview.net/pdf?id=sb-IkS8DQw2.

Wang, J., SUN, J., Zhang, Z., He, J., Zhang, Q., Sun, M., and Xu, R. DEL: Discrete element learner for learning 3d particle dynamics with neural rendering. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=2nvkD0sPOk.

Wang, L. and Zhu, J. Deformable object manipulation in caregiving scenarios: A review. *Machines*, 11(11):1013, 2023.

Weng, Z., Paus, F., Varava, A., Yin, H., Asfour, T., and Kragic, D. Graph-based task-specific prediction models for interactions between deformable and rigid objects. In *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5741–5748, 2021. doi: 10.1109/IROS51168.2021.9636660. URL https://arxiv.org/abs/2103.02932.

Whitney, W. F., Lopez-Guevara, T., Pfaff, T., Rubanova, Y., Kipf, T., Stachenfeld, K., and Allen, K. R. Learning 3d particle-based simulators from rgb-d videos. *arXiv preprint arXiv:2312.05359*, 2023.

Wu, T., Maruyama, T., Zhao, Q., Wetzstein, G., and Leskovec, J. Learning controllable adaptive simulation for multi-resolution physics. In *The Eleventh International Conference on Learning Representations*, 2023.

Xu, J., Chen, T., Zlokapa, L., Foshey, M., Matusik, W., Sueda, S., and Agrawal, P. An end-to-end differentiable framework for contact-aware robot design. In *Robotics: Science & Systems*, 2021.

Xu, M., Han, J., Lou, A., Kossaifi, J., Ramanathan, A., Azizzadenesheli, K., Leskovec, J., Ermon, S., and Anandkumar, A. Equivariant graph neural operator for modeling 3d dynamics. In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net, 2024. URL `https://openreview.net/forum?id=dccRCYmL5x`.

Yazid, A., Abdelkader, N., and Abdelmadjid, H. A state-of-the-art review of the x-fem for computational fracture mechanics. *Applied Mathematical Modelling*, 33(12):4269–4282, 2009.

Zaheer, M., Kottur, S., Ravanbakhsh, S., Póczos, B., Salakhutdinov, R., and Smola, A. J. Deep sets. *Advances in Neural Information Processing Systems*, 2017.

Zhuang, F., Qi, Z., Duan, K., Xi, D., Zhu, Y., Zhu, H., Xiong, H., and He, Q. A comprehensive survey on transfer learning. *Proceedings of the IEEE*, 2020.

Zienkiewicz, O. C. and Taylor, R. L. *The finite element method for solid and structural mechanics*. Elsevier, 2005.

Zienkiewicz, O. C., Taylor, R. L., and Nithiarasu, P. *The finite element method for fluid dynamics*. Butterworth-Heinemann, 2013.

Zimmerling, C., Poppe, C., Stein, O., and Kärger, L. Optimisation of manufacturing process parameters for variable component geometries using reinforcement learning. *Materials and Design*, 214:Art.–Nr.: 110423, 2022. ISSN 0264-1275, 0141-5530, 0261-3069, 1873-4197, 1878-2876. doi: 10.1016/j.matdes.2022.110423.

A MATHEMATICAL FORMULATIONS OF MOVEMENT PRIMITIVES

We provide an overview of the probabilistic dynamic movement primitives (ProDMP) formulations utilized in this paper, starting with the foundational methods: Dynamic Movement Primitives (DMPs) and Probabilistic Movement Primitives (ProMPs).

A.1 DMPs

Schaal (2006) introduced Dynamic Movement Primitives (DMPs), which integrate a forcing term into a dynamical system to generate smooth trajectories from given initial conditions[3], such as a robot's position and velocity at a particular time. A DMP trajectory is governed by a second-order linear ordinary differential equation (ODE) as follows:

$$\tau^2 \ddot{y} = \alpha(\beta(g - y) - \tau\dot{y}) + f(x), \quad f(x) = x\frac{\sum \varphi_i(x)w_i}{\sum \varphi_i(x)} = x\boldsymbol{\varphi}_x^\mathsf{T}\boldsymbol{w}, \tag{7}$$

where $y = y(t)$, $\dot{y} = \mathrm{d}y/\mathrm{d}t$, and $\ddot{y} = \mathrm{d}^2y/\mathrm{d}t^2$ denote the position, velocity, and acceleration of the system at a specific time t, respectively. Constants α and β are spring-damper parameters, g is the goal attractor, and τ is a time constant modulating the speed of trajectory execution.

The functions $\varphi_i(x)$ represent the basis functions for the forcing term, as shown in Fig. 9a, while the phase variable $x = x(t) \in [0, 1]$ captures the execution progress. The trajectory's shape is determined by the weight parameters $w_i \in \boldsymbol{w}$ for $i = 1, \dots, N$ and the goal term g. The trajectory $[y_t]_{t=0:T}$ is typically computed by numerically integrating the dynamical system from the start to the endpoint. However, this numerical process is computationally expensive (Bahl et al., 2020; Li et al., 2023), as its cost scales with the trajectory length and the resolution of the numerical integration.

A.2 PROMPS

Paraschos et al. (2013) introduced the Probabilistic Movement Primitives (ProMPs) framework for modeling trajectory distributions, effectively capturing both temporal and inter-dimensional correlations. Unlike DMPs, which rely on a forcing term, ProMPs directly model the desired trajectory and its distribution using a linear basis function representation. Given a weight vector $\boldsymbol{w}$ or a weight vector distribution $p(\boldsymbol{w}) \sim \mathcal{N}(\boldsymbol{w}|\boldsymbol{\mu_w}, \boldsymbol{\Sigma_w})$, the corresponding trajectory or trajectory distribution is computed as follows:

$$\text{Compute Trajectory:} \quad [y_t]_{t=0:T} = \boldsymbol{\Phi}^\mathsf{T}\boldsymbol{w}, \tag{8}$$

$$\text{Compute Distribution:} \quad p([y_t]_{t=0:T}; \boldsymbol{\mu_y}, \boldsymbol{\Sigma_y}) = \mathcal{N}(\boldsymbol{\Phi}^\mathsf{T}\boldsymbol{\mu_w}, \boldsymbol{\Phi}^\mathsf{T}\boldsymbol{\Sigma_w}\boldsymbol{\Phi}). \tag{9}$$

Here, the matrix $\boldsymbol{\Phi}$ contains the basis functions for each time step $t \in [0, T]$, shown in Fig. 9a. The trajectory shape is determined by the weight parameters $w_i \in \boldsymbol{w}$ through matrix-vector multiplication. Despite their simplicity and computational efficiency, ProMPs lack an intrinsic dynamic system, limiting their ability to specify a given initial condition for a trajectory or predict smooth transitions between two ProMP trajectories with differing parameter vectors.

A.3 PRODMPS

Solving the ODE underlying DMPs   Li et al. (2023) observed that the governing equation of DMPs, as described in Eq. (7), admits an analytical solution. We re-express the original ODE from Eq. (7) and its homogeneous counterpart in standard ODE forms as follows:

$$\text{Non-homo. ODE:} \quad \ddot{y} + \frac{\alpha}{\tau}\dot{y} + \frac{\alpha\beta}{\tau^2}y = \frac{f(x)}{\tau^2} + \frac{\alpha\beta}{\tau^2}g \equiv F(x, g), \tag{10}$$

$$\text{Homo. ODE:} \quad \ddot{y} + \frac{\alpha}{\tau}\dot{y} + \frac{\alpha\beta}{\tau^2}y = 0. \tag{11}$$

---

[3]In mathematics, an initial condition refers to the value of a function or its derivatives at a starting point, which can be specified at any time, not necessarily at $t = 0$.

(a) Basis functions of
DMPs / ProMPs

(b) Positional basis functions
of ProDMPs' weights

(c) Positional basis function
of ProDMPs' goal

Figure 9: Illustration of basis functions used in MP methods. (a) Normalized radial basis functions used in DMPs in Eq.(7) and ProMPs in Eq.(8), respectively. (b) Positional basis functions of ProDMPs' weights $\boldsymbol{w}$ and (c) ProDMPs' goal g in Eq.(17). In ProDMPs, g is concatenated with the weights vector $\boldsymbol{w}$ and treated as one dimension of the resulting vector $\boldsymbol{w}_g$. Both weights and goal basis functions are computed from solving the DMPs' underlying ODE, following the procedure from Eq.(12) to Eq.(16)

The solution to this ODE is essentially the position trajectory, and its time derivative yields the velocity trajectory. They are formulated through several time-dependent function as:

$$y = \begin{bmatrix} y_2\boldsymbol{p_2} - y_1\boldsymbol{p_1} & y_2q_2 - y_1q_1 \end{bmatrix} \begin{bmatrix} \boldsymbol{w} \\ g \end{bmatrix} + c_1y_1 + c_2y_2 \tag{12}$$

$$\dot{y} = \begin{bmatrix} \dot{y}_2\boldsymbol{p_2} - \dot{y}_1\boldsymbol{p_1} & \dot{y}_2q_2 - \dot{y}_1q_1 \end{bmatrix} \begin{bmatrix} \boldsymbol{w} \\ g \end{bmatrix} + c_1\dot{y}_1 + c_2\dot{y}_2. \tag{13}$$

Here, the learnable parameters $[\boldsymbol{w}, g]^T$ which control the shape of the trajectory, are separable from the remaining time-dependent functions $y_1, y_2, \boldsymbol{p}_1, \boldsymbol{p}_2, q_1, q_2$. These functions are computed by solving the ODE in Eq. (10), (11):

$$y_1(t) = \exp\left(-\frac{\alpha}{2\tau}t\right), \qquad y_2(t) = t\exp\left(-\frac{\alpha}{2\tau}t\right), \tag{14}$$

$$\boldsymbol{p}_1(t) = \frac{1}{\tau^2}\int_0^t t'\exp\left(\frac{\alpha}{2\tau}t'\right)x(t')\boldsymbol{\varphi}_x^{\mathsf{T}}\mathrm{d}t', \qquad \boldsymbol{p}_2(t) = \frac{1}{\tau^2}\int_0^t \exp\left(\frac{\alpha}{2\tau}t'\right)x(t')\boldsymbol{\varphi}_x^{\mathsf{T}}\mathrm{d}t', \tag{15}$$

$$q_1(t) = \left(\frac{\alpha}{2\tau}t - 1\right)\exp\left(\frac{\alpha}{2\tau}t\right) + 1, \qquad q_2(t) = \frac{\alpha}{2\tau}\left[\exp\left(\frac{\alpha}{2\tau}t\right) - 1\right]. \tag{16}$$

Here, the function y_1, y_2 are the complementary solutions to the homogeneous ODE presented in Eq.(11), with $\dot{y}_1, \dot{y}_2$ their time derivatives respectively.

It's worth noting that $\boldsymbol{p}_1$ and $\boldsymbol{p}_2$ cannot be derived analytically due to the complexity of the forcing basis terms $\boldsymbol{\varphi}_x$. Consequently, these terms must be computed numerically. However, isolating the learnable parameters, namely $\boldsymbol{w}$ and g, enables the reuse of other time-dependent functions across all generated trajectories.

ProDMPs identify these reusable terms as the position and velocity basis functions, denoted by $\boldsymbol{\Phi}(t)$ and $\dot{\boldsymbol{\Phi}}(t)$, respectively. Fig. 9b and Fig. 9c illustrate the resulting position basis functions for the weights $\boldsymbol{w}$ and the goal g, respectively. These functions are pre-computed offline and treated as constants during online learning. When $\boldsymbol{w}$ and g are combined into a concatenated vector, represented as $\boldsymbol{w}_g$, the position and velocity trajectories can be expressed in a manner similar to that used by ProMPs:

$$\textbf{Position:} \quad y(t) = \boldsymbol{\Phi}(t)^{\mathsf{T}}\boldsymbol{w}_g + c_1y_1(t) + c_2y_2(t), \tag{17}$$

$$\textbf{Velocity:} \quad \dot{y}(t) = \dot{\boldsymbol{\Phi}}(t)^{\mathsf{T}}\boldsymbol{w}_g + c_1\dot{y}_1(t) + c_2\dot{y}_2(t). \tag{18}$$

In the main paper, for simplicity and notation convenience, we use $\boldsymbol{w}$ instead of $\boldsymbol{w}_g$ to describe the parameters and goal of ProDMPs.

Trajectory's Initial Condition   The coefficients c_1 and c_2 are solutions to the initial value problem defined by Eqs.(17)(18). Assuming the trajectory starts at time t_b with position y_b and velocity $\dot{y}_b$, we denote the values of the complementary functions and their derivatives at the condition time t_b as $y_{1_b}, y_{2_b}, \dot{y}_{1_b}$ and $\dot{y}_{2_b}$. Similarly, the values of the position and velocity basis functions at t_b are denoted as $\mathbf{\Phi}_b$ and $\dot{\mathbf{\Phi}}_b$ respectively. Using these notations, c_1 and c_2 are computed as:

$$
\begin{bmatrix} c_1 \\ c_2 \end{bmatrix} = \begin{bmatrix} \frac{\dot{y}_{2_b} y_b - y_{2_b} \dot{y}_b}{y_{1_b} \dot{y}_{2_b} - y_{2_b} \dot{y}_{1_b}} + \frac{y_{2_b} \dot{\mathbf{\Phi}}_b^\intercal - \dot{y}_{2_b} \mathbf{\Phi}_b^\intercal}{y_{1_b} \dot{y}_{2_b} - y_{2_b} \dot{y}_{1_b}} \boldsymbol{w}_g \\ \frac{y_{1_b} \dot{y}_b - \dot{y}_{1_b} y_b}{y_{1_b} \dot{y}_{2_b} - y_{2_b} \dot{y}_{1_b}} + \frac{\dot{y}_{1_b} \mathbf{\Phi}_b^\intercal - y_{1_b} \dot{\mathbf{\Phi}}_b^\intercal}{y_{1_b} \dot{y}_{2_b} - y_{2_b} \dot{y}_{1_b}} \boldsymbol{w}_g \end{bmatrix}.
\tag{19}
$$

Set Goal Convergence Relative to Initial Condition   The goal attractor g in the ProDMPs framework represents an asymptotic convergence point for the dynamical system as $t \to \infty$, typically defined as an absolute coordinate. However, the goal term can also be modeled relative to the initial position y_b. In this approach, the relative goal g_{rel} is predicted, and its absolute counterpart is computed as $g_{\text{abs}} = g_{\text{rel}} + y_b$. This approach is particularly useful for predicting the goal in the coordinate system relative to a node's starting position. Since we aim to achieve a translation-equivariant approach (where absolute node positions are encoded as relative edge features between nodes), predicting relative goal positions aligns well with this design principle.

B   ARCHITECTURE AND METHOD DETAILS

This section offers detailed insights into our methodology and the architectural decisions guiding our approach.

B.1   GRAPH ENCODINGS

In processing the initial graph $\mathcal{G}_{*,T^c}$, we create edges between the mesh and the collider based on a radius graph. Specifically, we connect mesh and collider nodes for *Deformable Plate* and *Tissue Manipulation* if their euclidean distance is smaller than 0.3. In the *Tissue Manipulation* task, the collider is given as a single node which is connected to the tip of the tissue. It marks the grasping point of a gripper. In the *Planar Bending* task, we add an additional node feature to the nodes which get directly influenced by the external force. Therefore, no collider is used in this task. For the *Falling Teddy Bear* and the *Mixed Objects Falling* task, we implicitly model the ground as a collider by adding the current z position of every node to its node features (Sanchez-Gonzalez et al., 2018). This quantity gets updated for the step-based methods.

B.2   PRODMP DETAILS

Initialization of ProDMPs necessitates node velocities for the anchor time step T^c. We employ a linear approximation, leveraging data from the previous time step $T^c - 1$.

Similar to the relative encoding of node positions in the MPN, we employ a technique in ProDMP to derive relative trajectories. Initially, we integrate a relative goal position as part of the node weights $\boldsymbol{w}_v$. Utilizing this approach, trajectories commence from the origin and traverse towards their respective relative goals. Subsequently, we adjust all positions by the initial position. This strategy fosters model generalization across various nodes.

The parameter τ, as described in Equation 7, is learned globally across all tasks using a compact MLP. The model's final layer employs a scaled sigmoid function for parameter estimation.

C   EXPERIMENTAL PROTOCOL

In order to promote reproducibility, we provide details of our experimental methodology. Table 1 presents the hyperparameters used in our experiments. For a comprehensive description of the creation of all datasets, please refer to Appendix D.

The training took place on an NVIDIA A100 GPU, with each method given the same computation budget of 48 hours, except for the *Planar Bending* task, where the computation budget was set to 24

hours. Consequently, the number of epochs varied, as the batching differed significantly between the trajectory-based method M3GN and the step-based MGN. We adapted the batchsize of the step-based methods in order to use the GPU memory efficiently. M3GN is always trained on one full trajectory per batch. Here, the whole context is processed in parallel and the remaining trajectory is predicted and compared to the ground truth.

We conducted a multi-staged grid-based hyperparameter search for the learning rate, input noise, and other hyperparameters as the latent task description dimension. In general, we optimized all methods on all tasks separately, however, we noticed that over different tasks and methods some parameters had the same best configuration. We did not use the test data for this, but tuned all hyperparameters on a separate validation split. This split was also used to determine the best epoch checkpoint to mitigate any overfitting effects.

In the end, all methods worked well with a learning rate of 5.0×10^{-4} except in the *Planar Bending* task. Here, our hyperparameter optimization indicated that the trajectory based methods benefit from a smaller learning rate of 1.0×10^{-5}. For MGN, we experimented with different input noise scales. Notably, for the *Deformable Plate* and the *Planar Bending* task, a smaller noise scale improved performance significantly. In the falling objects tasks, we also explored second-order predictions, such as node accelerations, instead of velocity predictions. Following the approach in Pfaff et al. (2021), we adjusted the labels accordingly and conducted preliminary evaluations. However, since direct velocity predictions yielded superior results, we opted for them as our final approach, as presented in the main paper.

Table 1: Table listing the hyperparameters and configurations of the experiments

Parameter	Value
Node feature dimension	128
Latent task description dimension	64
Decoder hidden dimension	128
Message passing blocks	15
GNN Aggregation function	Mean
GNN Activation function	Leaky ReLU
M3GN Context Aggregation method	Max Aggr.
M3GN Latent Node Aggregation method	No Aggr.
Learning rate	5.0×10^{-4}
Learning rate (*Plan. Bend.* MP-based methods)	1.0×10^{-5}
Number of ProDMP basis functions	30
ProDMP τ	learned (min: 0.3, max: 3.0)
ProDMP Relative start position	True
MGN input mesh noise	0.01
MGN input mesh noise (*Def. Plate*)	0.001
MGN input mesh noise (*Plan. Bend.*)	0.0001
Minimum/Maximum Train Context Size (*Plan. Bend.*)	2 / 15
Minimum/Maximum Train Context Size (*Deformable Plate*)	2 / 15
Minimum/Maximum Train Context Size (*Tissue Manipulation*)	2 / 40
Minimum/Maximum Train Context Size (*Falling Teddy Bear*)	10 / 50
Minimum/Maximum Train Context Size (*Mixed Objects Fall*)	10 / 50
Threshold to create collider-mesh edge	0.3

D DATASETS AND PREPROCESSING INFORMATION

In this section, we give detailed information about the datasets we used. We report a general overview of all datasets in Table 2. Here each dataset is abbreviated for brevity as the following:

Table 2 lists in detail the datasets used in the paper. Each dataset is abbreviated for brevity and explained as follows:

- **PB.**: *Planar Bending*
- **DP.**: *Deformable Plate*

- **TM.**: *Tissue Manipulation*
- **FTB.**: *Falling Teddy Bear*
- **MOF.**: *Mixed Objects Falling*

Table 2: Table listing the datasets and their configurations

Name	Train/Val/Test Splits	Number of steps	Number of Nodes	Collider interaction
PB.	630/135/135	50	225	External Force
DP.	675/135/135	39	81	Rigid Collider
TM.	600/120/120	100	361	Grasping point
FTB.	700/150/150	200	304	Boundary Condition
MOF.	1800/360/360	200	up to 350	Boundary Condition

D.1 PLANAR BENDING

We select 9 different Young's modulus ranging between 10 and 1000 from a very deformable to an almost stiff sheet. Then, per material, we compute 100 simulations using Abaqus where the positions of the two acting forces are randomized. The boundary nodes of the sheet are kept in place. From every material configuration, we take 70 simulations for training and 15 simulations for validation and testing respectively. For the out-of-distribution task, we only trained on Young's modulus ranging between 60 and 500, while testing on Young's modulus values 10, 30, 750, and 1000.

D.2 DEFORMABLE PLATE

The original task was introduced in Linkerhägner et al. (2023), generated using Simulation Open Framework Architecture (SOFA) (Faure et al., 2012). It uses 3 different Poisson's ratios and 9 different trapezoidal meshes. We increase the difficulty of this dataset by introducing more complex initial starting conditions. This is done by selecting a random Poisson's ratio, simulating for 11 steps, and then switching to another Poisson's ratio. Then, the simulation continues for 39 steps. The first 11 steps are then discarded and step 12 is then the initial step for the dataset (and is referred to step 0 throughout the paper).

D.3 TISSUE MANIPULATION

We use the original task introduced in Linkerhägner et al. (2023) without alterations. This dataset was also generated using SOFA (Faure et al., 2012).

D.4 FALLING TEDDY BEAR

Each trajectory of the dataset was created by choosing an angle from $[0°, 360°]$ for the first time step. To vary the material properties, we randomly select one possible combination of the Young's modulus and Poisson's ratio from the sets generated by `np.linspace(1 × 10^5, 1 × 10^6, 1000)` and `np.linspace(0.0, 0.499, 100)`, respectively. This dataset is generated using NVIDIA Isaac Sim (NVIDIA, 2022a), which utilizes PhysX 5.0 (NVIDIA, 2022b) to simulate tetrahedral meshes based on initial CAD models.

D.5 MIXED OBJECTS FALLING

The simulation uses the setup from *Falling Teddy Bear*. In addition to the Teddy, we include other objects to encourage diversity. In total, there are six different objects presented in the dataset. We report an image of their high-resolution meshes in Figure 10. From every object, we use 300 simulations for the training split and 60 simulations for the test and validation split respectively.

Figure 10: Six objects used in the *Mixed Objects Falling* task. From left to right: Teddy Bear, Bunny, Gummy Bear, Gummy Worm 1, Gummy Worm 2, and Traffic Cone.

Figure 11: Log-scale MSE over the first 10 steps after the anchor time step for the *Deformable Plate* (**Left**) task, the *Planar Bending* (**Center**) task, and the *Planar Bending* task with out-of-distribution material properties for the test trajectories. M3GN steadily improves its performance when provided with additional context information and a later anchor time step. When evaluating this metric, we also outperform MGN Oracle on the *Deformable plate* task.

Figure 12: Log-scale MSE over the first 10 steps after the anchor time step for the *Tissue Manipulation* (**Left**), *Falling Teddy Bear* (**Middle**) and *Mixed Objects Falling* (**Right**) tasks for different methods. M3GN significantly outperforms all baselines on *Tissue Manipulation* when provided with a context size larger than 3. For the other tasks, M3GN significantly improves over both MGN variants, but does not benefit much from additional context information.

E   ADDITIONAL RESULTS

E.1   EVALUATIONS.

Figure 11 and Figure 12 show the performance of M3GN compared to the baselines evaluated on the 10 steps MSE. Here, instead of the whole trajectory, only the first 10 steps after the anchor time step are used to evalute the MSE.

To gain better insights into the rollout stability of the model predictions, we report the Mean Squared Error (MSE) over timesteps in Figure 13 and Figure 14. Overall, autoregressive-based methods, such as MGN and MGN (Oracle), exhibit significantly higher errors over time due to accumulated prediction errors. In contrast, our M3GN demonstrates greater robustness against error accumulation, benefiting from the inherent trajectory representation provided by the ProDMP method.

E.2   VISUALIZATIONS.

In Figure 15, we include a latent space visualization of the Planar Bending task, where simulations with 9 different Young's Modulus values are clustered according to their material properties. The t-SNE projection of the 64-dimensional latent node vectors demonstrates clear clustering, indicating that the model effectively captures and differentiates material characteristics based on learned task representations.

(a) Context Size 3   (b) Context Size 10   (c) Context Size 20

Figure 13: MSE over timesteps for the *Tissue Manipulation* task. Bigger context sizes help to improve the early error accumulation for M3GN.

(a) Deformable Plate - Context Size 5   (b) Planar Bending - Context Size 2

(c) Falling Teddy Bear - Context Size 20   (d) Multi Objects Fall - Context Size 20

Figure 14: MSE over timesteps for varied tasks. Overall, autoregressive methods suffer from accumulated errors, while using ProDMP as a trajectory representation, M3GN results in lower MSE across timesteps.

We further provide additional visualizations for M3GN, MGN and MGN (Oracle) for exemplary simulations of all tasks. Each visualization shows the same simulated trajectory for different time steps (columns) and different methods (rows).

- Figure 16 shows a simulation of the *Planar Bending* task for a context set size of 5.
- Figure 17 visualizes the *Deformable Plate* task for a context set size of 6.
- Figure 18 shows a *Tissue Manipulation* visualization for a context set size of 6.
- Figure 19 provides an examplary *Teddy Bear Falling* for a context set size of 20.
- Figure 20 and Figure 21 show two different simulated *Mixed Objects Falling* for a context set size of 20.

Across tasks, M3GN provides accurate simulations, whereas MGN, especially when not provided the additional material information as oracle knowledge, sometimes fails to respect the material properties or predicts a drift in the solution for later time steps.

Figure 15: This figure shows a latent space visualization of the Planar Bending task for trajectories with 9 different Young's Modulus values, using a context size of 10. Each dot represents a 64-dimensional latent node vector projected to 2D using the t-SNE algorithm (van der Maaten & Hinton, 2008). Dots of the same color correspond to latent node descriptions for the same task, each simulated with a unique Young's Modulus. The visualization reveals distinct clustering in the latent space, with similar material properties grouped closer together, highlighting the relationship between material characteristics and the learned task representations. To improve clarity, points corresponding to nodes on the plate's edge were excluded, as their constant boundary condition resulted in unvarying latent descriptions.

Figure 16: Simulation over time of an exemplary test trajectory from the **Planar Bending** task by M3GN, MGN, and MGN with oracle information. The **context set size** is set to 5. All visualizations show the colored **predicted mesh**, a **collider or floor**, and a **wireframe** of the ground-truth simulation. M3GN can accurately predict the correct material properties, resulting in a highly accurate simulation.

Figure 17: Simulation over time of an exemplary test trajectory from the **Deformable Plate** task by M3GN, MGN, and MGN with oracle information. The **context set size** is set to 6. All visualizations show the colored **predicted mesh**, a **collider or floor**, and a **wireframe** of the ground-truth simulation. M3GN can accurately predict the correct material properties, resulting in a highly accurate simulation.

Figure 18: Simulation over time of an exemplary test trajectory from the **Tissue Manipulation** task by M3GN, MGN, and MGN with oracle information. The **context set size** is set to 6. All visualizations show the colored **predicted mesh**, a **collider or floor**, and a **wireframe** of the ground-truth simulation. All methods can solve the task, however MGN is drifting a tiny bit to the left over time.

Figure 19: Simulation over time of an exemplary test trajectory from the **Falling Teddy Bear** task by M3GN, MGN, and MGN with oracle information. The **context set size** is set to 20. All visualizations show the colored **predicted mesh**, a **collider or floor**, and a **wireframe** of the ground-truth simulation. M3GN significantly outperforms both step-based baselines.

$t = 21$ $\quad$ $t = 41$ $\quad$ $t = 61$ $\quad$ $t = 81$ $\quad$ $t = 101$ $\quad$ $t = 121$ $\quad$ $t = 141$ $\quad$ $t = 181$

$t = 21$ $\quad$ $t = 41$ $\quad$ $t = 61$ $\quad$ $t = 81$ $\quad$ $t = 101$ $\quad$ $t = 121$ $\quad$ $t = 141$ $\quad$ $t = 181$

$t = 21$ $\quad$ $t = 41$ $\quad$ $t = 61$ $\quad$ $t = 81$ $\quad$ $t = 101$ $\quad$ $t = 121$ $\quad$ $t = 141$ $\quad$ $t = 181$

Figure 20: Simulation over time of a bunny from the **Mixed Objects Fall** task by M3GN, MGN, and MGN with oracle information. The **context set size** is set to 20. All visualizations show the colored **predicted mesh**, a **collider or floor**, and a **wireframe** of the ground-truth simulation. M3GN significantly outperforms both step-based baselines.

$t = 21$ $\quad$ $t = 41$ $\quad$ $t = 61$ $\quad$ $t = 81$ $\quad$ $t = 101$ $\quad$ $t = 121$ $\quad$ $t = 141$ $\quad$ $t = 181$

$t = 21$ $\quad$ $t = 41$ $\quad$ $t = 61$ $\quad$ $t = 81$ $\quad$ $t = 101$ $\quad$ $t = 121$ $\quad$ $t = 141$ $\quad$ $t = 181$

$t = 21$ $\quad$ $t = 41$ $\quad$ $t = 61$ $\quad$ $t = 81$ $\quad$ $t = 101$ $\quad$ $t = 121$ $\quad$ $t = 141$ $\quad$ $t = 181$

Figure 21: Simulation over time of a pylon from the **Mixed Objects Fall** task by M3GN, MGN, and MGN with oracle information. The **context set size** is set to 20. All visualizations show the colored **predicted mesh**, a **collider or floor**, and a **wireframe** of the ground-truth simulation. M3GN significantly outperforms both step-based baselines. The simulation generated by MGN is severly affected by drift.