DEEP REINFORCEMENT LEARNING BASED INSIGHT SELECTION POLICY

ABSTRACT

We live in the era of ubiquitous sensing and computing. More and more data is being collected and processed from devices, sensors and systems. This opens up opportunities to discover patterns from these data that could help in gaining better understanding into the source that produces them. This is useful in a wide range of domains, especially in the area of personal health, in which such knowledge could help in allowing users to comprehend their behavior and indirectly improve their lifestyle. Insight generators are systems that identify such patterns and verbalise them in a readable text format, referred to as insights. The selection of insights is done using a scoring algorithm which aims at optimizing this process based on multiple objectives, e.g., factual correctness, usefulness and interestingness of insights. In this paper, we propose a novel Reinforcement Learning (RL) framework for insight selection where the scoring model is trained by user feedback on interestingness and their lifestyle quality estimates. With the use of highly reusable and simple principles of automatic user simulation based on real data, we demonstrate in this preliminary study that the RL solution may improve the selection of insights towards multiple pre-defined objectives.

1 INTRODUCTION

The latest developments in big data, internet of things and personal health monitoring have lead to the massive increase in the ease and scale at which data has been collected and processed. Learning from the information present in the data has shown to help to gain wisdom to better run businesses, manage health care services and even maintain a healthier lifestyle. Such understanding are mostly in the form of identifying significant rise or fall of a certain measurement given a context of interest. Lets say that the sleep data logs of a user of a health monitoring service shows that the time at which they went to sleep was later during the weekends in comparison to weekdays. This can be informed to the user as a statement such as, "You went to sleep later during the weekends than the weekdays". Here, the time at which they went to sleep is the measurement and the fact of the day being a weekday or a weekend is the context of interest. We call such statements as 'insights'. Providing such insights that accurately describe the scenarios during which certain health parameter improved or deteriorated could enable the user to make better lifestyle choices.

The insight generation task can be seen as a natural language generation task where a generator model creates appropriate insight statements. A generalised framework for such a insight generator (Genf) was proposed in which components to analyse the data and generate the statements played an important role (Susaiyah et al., 2020). More importantly, the framework has a provision to capture user feedback mechanism that understands what type of insights they are interested in. Implementations of this framework have shown to incorporate the "overgenerate and rank" approach in which all possible candidates as per definition are generated and later filtered using a calculated rank or a score (Gatt & Krahmer, 2018; Varges & Mellish, 2010).

The selection of the most relevant insight via ranking or scoring from a list of multiple insights is an ongoing research topic. Earlier works have utilised purely statistical insight selection mechanisms where the top ranking insights based on a statistical algorithm are selected (Härmä & Helaoui, 2016) often combined with machine-readable knowledge (Musto et al., 2017). Other approaches combined neural networks with the knowledge of statistical algorithms with simulated user feedback (Susaiyah

et al., 2021). All the above techniques have limitations with respect to over-simplification of user-preference or need of a huge amount of data.

On the other hand, as noted in Afsar et al. (2021), the very nature of a recommendation is a sequential decision problem thus that could be modelled as a Markov Decision Process (MDP). Reinforcement Learning (RL) can therefore be used to solve this problem taking into account the dynamics of the user's interactions with the system, its long-term engagement to specific topics and more complex feedbacks than binary ratings.

In this paper we introduce a straightforward and reusable Deep Reinforcement Learning (DRL) based framework that can learn the user's preferences and deliver insights that are more relevant to them. Furthermore, the presented system is at the same time able to deliver insights aiming to improve the user's healthcare. To the best of our knowledge, there is no other existing system capable of reaching both of those objectives. We evaluate it in this preliminary study in terms of significance of life quality improvements, speed and accuracy of adaptation to the dynamics of user preferences and deploy-ability in a real life scenario.

2 RELATED WORK

Traditionally, insights were generated using associate rule mining techniques (Agrawal & Shafer, 1996), where associations between different contexts in a dataset are discovered. However, they do not work for continuous variables. This led to the work of Härmä & Helaoui (2016) where both continuous and categorical variables were considered. However, it lacked the ability to adapt to specific users, which is very important as what we consider as an insight is highly subjective. Later, a generalised insight-generation framework (Genf) was introduced in Susaiyah et al. (2020) to incorporate the users as part of the insight generation system. This framework requires highly dynamic mechanisms to rank and recommend the insights based on the dynamics of user interests.

To have a clear understanding of the main goals of this task, the survey Pramod & Bafna (2022) summarises and presents ten challenges to overcome for conversational recommender systems. As one of them, our approach was designed to respond to nine out of the ten, the latest being only related to dialogue management, which is not part of the scope of the present study. The proposed answers to those aims are synthesised hereafter:

- Keep reliability in ratings given by the user (e.g. bias in ratings, rating quality, noise in rating) by avoiding overfitting. One of the main advantages of our approach is that the policy network (i.e. the scoring algorithm) is not trained to learn by heart the interests of the user. Instead, it is taught how to discover them by testing different potential candidates.

- Minimise the time spent for rating and number of questions asked by providing one selected insight per day and only requiring a discrete rating as disliked, neutral or liked.

- Allow cold start recommendations by pretraining our policy network on a uniform interest over the possible topics. The policy network can also be pretrained on specific interests by using previously acquired knowledge from pre-existing users of the system.

- Balance cognitive load against user control, i.e. user effort in selecting the item against extend to which user can change recommendation list/give feedback. To keep interactions as simple as possible, as previously mentioned, only discrete feedback is given by the user. Nevertheless, this information is enough to dynamically and immediately adapt the selected insight.

- Remove user's need to tell the technical requirement by providing insights directly from the data, therefore not requiring any information from the user to specify.

- Allow a fallback recommendation when no items found satisfy the user. When an insight of a specific topic is not available from the data (i.e. when it is not statistically significant), the system can always provide to the user another insight by choosing the one with the highest p_{value}.

- Limit item presentation complexity leading to cognitive load by using comparison based generated sentences in natural language.

- Develop a system able to give domain-dependent recommendation using a Genf. This generator allows a high flexibility and reusability for any domain by extracting statistically significant differences between any kind of data.

- Convince users about the recommendation and its usefulness by formulating facts coming from the data rather than directives. Instead, the optimal behavior is intended, implied in the sentence, creating a better acceptance from the users.

The neural insight selection model presented in Susaiyah et al. (2021) was agnostic to the overall objective of the user to use the insights: to improve a behavior/performance. Indeed, the approach presented in Susaiyah et al. (2021) only focused on insight selection for user preferences and used supervised learning from binary feedback. Therefore, it could neither consider the long term nor short term impact a given insight will produce for a given user. Nowadays, the problem of long time interaction, understand daily recommendation over multiple months, can be solved using DRL. However, DRL is known to be a very consuming approach in terms of sample efficiency whether being model-free as policy-gradient, value-based, actor critic or model-based. All DRL algorithms as SAC (Haarnoja et al., 2018), A3C (Mnih et al., 2016), DDPG (Lillicrap et al., 2015), DQN (Mnih et al., 2013) or PPO (Schulman et al., 2017) suffer from this problem and require, on average, several millions of interactions with their environment to solve complex problems as demonstrated in their paper. This is even more problematic as the continuous supervised learning in Susaiyah et al. (2021) already required on average 15.6 labelled insights with the user feedback every day.

To implement such a DRL approach in the healthcare domain, several challenges need to be solved as described in Riachi et al. (2021). Usually data needs to be obtained through time-consuming, and not necessarily realistic, studies requiring the patient to wear electronic devices. Therefore, this leads to the usage of limited observational data, which denies the freedom to explore different interaction strategies during the training process. As a solution to solve this issue in DRL, dialogue (Zhao et al., 2021) or video game (Young et al., 2018; Yang et al., 2020) approaches, rely on episodic memory to exploit the observations in order to optimise both the training and decision processes. Researchers also worked on other strategies such as designing simulations from the data itself and plenty of examples can be found in the literature as HeartPole and GraphSim (Liventsev et al., 2021), or the dozens of RL applications presented in Yu et al. (2019). Another major challenge, as detailed in Riachi et al. (2021), is the design of the most appropriate reward function. To this end, RL solutions often exploit counterfactuals available in their own collected data, or datasets such as MIMIC-III (Johnson et al., 2016), to design their environment. Indeed, knowing what would have happened taking another decision allows for a more efficient reward function and training, but requires a careful and manual design. This conception, then, makes it difficult to reuse the ideas from one specific problem to another.

In an objective of simplifying the reusability of a such DRL approach, the authors focused on developing an environment in which the selection process is given an unlimited amount of data to learn. To leverage the limitations about the data, this work presents a generic replication procedure for individuals' behaviors from existing data, requiring only start and stop times of activities. This procedure is used to automatically create a simulation system as a probabilistic state machine. From the use of this state machine, the policy network can learn by itself how its actions impact the simulation, based on very simple assumptions, without the need of counterfactuals in the original dataset. Moreover, the probabilistic nature of the simulation generates an infinite, yet realistic, amount of data therefore not requiring manually designed reward functions to guide the policy during its training.

The approach detailed in Susaiyah et al. (2021) proposed to use an insight generator with a neural network to select insights to be given to the user. Depending on the simulated feedback, the system was able to change the selected insights and was therefore demonstrated to be robust to the user interests when tested with preferences variations. The role of this preliminary study is to show the interest of using DRL instead of supervised learning, requiring a continuous training on the current preferences of the user. Moreover, the reward system of RL allows taking into account more complex metrics of performance than just binary preferences (e.g. life quality improvements such as sleep quality). The experiments presented here show the robustness of this approach, considering the variability and complexity of the simulated user's behavior and associated preferences. In order to give to the reader the easiest explanation of our approach, we use the same sleeping simulation example throughout this paper.

3 METHODOLOGY

3.1 GENERAL FRAMEWORK

We designed a complete training pipeline, presented on figure 1, composed of 3 stages that are repeated every day: (1) insight generation, (2) insight selection, (3) user lifestyle simulation. The pipeline was designed to simulate the interaction between the policy network and a user, aiming at two distinct objectives being to select insights that are appreciated by the user and beneficial to their life quality. Insight generation is performed using the insight generator described in Susaiyah et al. (2021). The proper generation of insights is based on predefined schemas of comparison such as

$$sleep\_period : 1 \quad measurement \quad sleep\_period : 2 \quad mean : 2$$
$$short\_period : 1 \quad measurement \quad measurement\_benchmark : 2$$

with :1 and :2 respectively referring to subset 1 and 2 that are compared. This approach allows for a very precise control over the generation process, encoding all the possible comparisons between two subsets of the data that satisfy the constrains set by the schema. For each of the measurements, a benchmark value can be predefined such as 8 hours of sleep per night or sleeping time around 22:00 (i.e. 22 hours:00 minutes). Given the two examples above, it can therefore generate comparisons between two sleep periods or between the actual and the desired value of a measurement. From those comparisons, a Kolmogorov-Smirnov test is computed on the two subsets of all insights to score their individual statistical significance. The non-significant insights, with a $p_{value} < 0.05$, are filtered and removed. Subsequently, a score for relevance is calculated, determined by both the completeness of the data and the tolerance level as shown in Equation 1. The completeness score $Score_C$, is calculated using the expected rate of sampling of the data F_{exp} that is preset manually depending upon the data source, the time period of the queried data T, and the number of data samples available N_{rec}. The significance score $Score_S$, is calculated using γ, a weighting factor that determines the slope of the sigmoid function and δ, the difference in the means of the measurements across the two contexts. The final relevance score $Score_F$ is then calculated as a product of the completeness and significance scores.

$$Score_C = \frac{N_{rec}}{F_{exp} * T}$$
$$Score_S = \frac{1}{1 + \exp(-\frac{\gamma\delta}{\tau})} \qquad (1)$$
$$Score_F = Score_C * Score_S$$

Each insight is assigned a feature vector of size N_T based on the bag of words (BoW) embedding. This encodes into a vector format, the number of occurrences of each word of a predefined dictionary of words present in the insight. Finally, K-means clustering is performed on the feature vectors using Eucledian distances. Only the insights having the highest relevance scores are chosen forward from each of the K clusters.

Figure 1: **Representation of the daily insight selection pipeline.** The insight generator uses the generated data in order to produce new available insights from which one is selected by the policy network. The simulation is run for one day, and provides a reward based on life quality or satisfaction of the user.

From the feature vectors of the available insights after generation, the policy network was trained to directly select one of the N_C insights that are composed of the K-clustered insights and $N_C - K$ benchmark insights, ensuring the policy network to always have comparison with benchmark values for each measurement.

Finally, to simulate the everyday lifestyle of a user, we opted for a state machine with probabilistic and time dependant transitions. Depending on the insight that is selected by the

policy network, the behavior of the user is assumed to tend towards the optimal behavior implied by the insight. For example, an insight as 'You sleep around 3 hours later than 21:00 on weekdays' implies to the user to sleep earlier. A new day of simulation is then computed and new data about the user (e.g. sleep duration, exercise duration, etc) is generated. If the policy is trained on user satisfaction, it will be rewarded by a discrete feedback whether the topics from the selected insight meets the interests of the user or not. Otherwise, the policy network is rewarded using metrics evaluating the life quality of the user.

3.2 SIMULATION ENVIRONMENT

In an effort to be able to model any kind of time dependant behavior, our system relies only on three types of input data for each activity the user might be doing i.e. the day, the start time and the stop time on which it happened. From this information, a state machine is automatically constructed with one state representing each activity. Additionally, one other state, named Idle, is created to play the role of link between all the others. In this state machine, each transition between two states is modelled as a Bayesian Gaussian Mixture Model (GMM) (Roberts et al., 1998; Blei & Jordan, 2006; Attias, 2000) in order to preserve the random nature of human behavior depending on the current time and day in the simulation. An example of state machine with seven activities is presented on figure 2. As the reader can note, all the possible activities are linked to the state Idle by one transition in each direction.

(a) State machine with seven states representing the seven possible activities plus the Idle state

(b) Associated probabilities to Sleeping state transitions for Wednesday and Saturday in function of the time of the day

Figure 2: Example of state machine and associated probabilities

3.2.1 DATA EXTRACTION

In order to construct this state machine, the process is composed of three steps: (1) data filtering that depends on the activities considered and extraction of features such as start and stop time or duration, (2) Gaussian estimation with optional iterative component reduction and (3) creation of a new state in the state machine. As presented in the algorithm 1, two Bayesian GMMs are computed for every day of the week and every activity to simulate. First, the start times, stop times and durations related to a specific day and activity is filtered. Then, a Bayesian GMM is computed, using the library Scikit-Learn (Pedregosa et al., 2011), from the filtered start times, and an other one from the filtered stop times of the activity. An example of probabilities associated with the activation of the state Sleeping is given on figure 2 for two different days of the week after the Bayesian GMM estimations. In this example, we can observe that the wake time is on average later and more scattered for Saturday than for Wednesday. The initial number of component for the GMM was set to 24 and is decreased until a mixture model can be computed from the data. This value has been empirically selected and is suited for the later experiments presented in this paper, but may need to be modified. In the case where one considered activity would be happening consistently more than 24 times a day, a higher number of Gaussians would be needed to simulate it accurately. Finally, the Bayesian GMM corresponding to the start times of the activity is added to the transition from the state Idle of the state machine and the other GMM added to the transition to the state Idle.

Additionally, two other constraints are added to the transitions: the horizon and the proportion of the activity during the day. The horizon constraint is a mechanism of attention that is used here to

filter the sampled points from the GMM and ensures that (1) transition from Idle to any other state is selected within a range of 3.5 hours and (2) transition from a given state back to Idle happens within the maximum duration of the activity observed in the data. The proportion constraint is used to balance the activation likelihood of all states by normalising them by their number of occurrences in a given day. Indeed, the GMM only provides a time-dependant activation probability, independent of other states. Thus, in our example, proportion of Working is needed as it will be much greater than Shopping on the weekdays contrary to the weekend, encoding a different likelihood of activation.

3.2.2 RUN TIME EXECUTION

On run time, the simulation starts on Monday at 00:00 and is incremented by one minute at each new step. The first state to be activated is Idle and the following process, represented on figure 3, is repeated for each new active state. To illustrate how a transition is selected, we will consider the state machine on figure 2, the current active state Idle and the current time 12:00. For all the possible transition from Idle (i.e. to Sleeping, Working, Shopping, Eating, Exercising, Relaxing or Travelling), the transition processing on figure 3 is repeated. The first step is to sample 100 transition candidates, randomly generated from the GMM associated to the transition, as 12:20, 4:30 or 21:45 in this example. Then, the candidates referring to transitions in the past are removed, such as 4:30. The third step is to remove candidate times further than the horizon constraint associated to the transition, here it corresponds to 3.5 hours, filtering 21:45.

Finally, the transition with the highest probability is selected from the remaining candidates. Once this process has been repeated for every possible transition, the one wielding the highest $likelihood = probability * proportion$ is selected. The simulation then advances until the transition time is reached. The new state is activated, and the loop starts again. In case no activation is found, which happens by the end of the day as there are fewer candidates, the simulation goes to the next time step.

Figure 3: **Representation of the state machine run time process.** From a pool of candidates, the transition with the highest likelihood is selected, the simulation continues until the selected time, changes the current active state and the process is repeated.

3.3 REINFORCEMENT LEARNING

3.3.1 OBSERVATIONS

To take its decisions, the policy network is able to see both the history of selected insights for the last T days, with their impact on the user and the currently available insights as presented is figure 4. As each day, the policy network selects one new insight, one day is represented by a matrix with as many rows as the features dimension and 2 columns. The feature vector of the selected insight is represented vertically while the second column contains information about the metrics to be optimised, for a given day. In our example, these values are related to exercise duration, feedback about the selected insight or sleep quality measures. When a new day of data is

Figure 4: Observation matrix

available, the oldest day matrix is removed, the T days matrices are rolled to the left, the new day matrix is added to the right, and the N_C available insights are updated.

3.3.2   ACTIONS

Depending on the simulation itself and desired impact one insight can have, the implementation can greatly differ from one problem to the other. We will note r_{value} the implicitly recommended value by the insight and its impact. Considering the previous state machine represented on figure 2, we applied the following lifestyle improvement factors:

- If the insight is about sleep time, the means of the Gaussians corresponding to the transition from Idle to Sleeping are slided by $0.1 * r_{value}$ towards 22:00. In order to keep consistency with the other activities, the means of the Gaussians from Idle to Relaxing and Relaxing to Idle are modified by the same value towards 21:00.

- If the insight is about wake time, the means of the Gaussians corresponding to the transition from Sleeping to Idle are slided by $0.1 * r_{value}$ towards 10:00 with an additonnal clustering of the Gaussians around their common mean by 0.3.

- If the insight is about sleep duration, it produces the same effect as sleep time and wake time, except that no clustering is done around their common mean.

- If the insight is about exercise duration, the means of the Gaussians corresponding to the transition from Idle to Exercising are slided by $0.1 * r_{value}$ towards 16:00 with an additonnal clustering of the Gaussians around their common mean by 0.4. The same is applied to the transition from Exercising to Idle towards 17:00.

Depending on the selected insight, this modification can be applied on any specific day of the week (e.g. on the weekend, the weekdays, on the Monday, on the Wednesday-Thursday, etc). However, whether the policy network selects an appropriate insight or not, a real user will usually tend to get back to their original behavior. The simulation therefore mimicked this by coming back to its original GMM parameters in order to force the policy network to be efficient in its selection. Therefore, the transition from Idle to Sleeping is automatically slided by 0.1 towards 23:30, Sleeping to Idle towards 05:00 and, Idle to Relaxing and Relaxing to Idle towards 22:00. Idle to Exercise is slided towards 10:00 and Exercise to Idle towards 11:00, both means of transitions scattered by 0.03 around their common mean. These are called the lifestyle fallback factors.

3.3.3   REWARDS

For this study, we decided that the reward should translate (1) the improvements of the sleep quality, (2) the exercise duration and (3) satisfaction of the user's interests by giving them the insights they want to see. In order to give a realistic sense of the user's sleep quality, we decided to use the Pittsburg Sleep Quality Index or PSQI (Buysse et al., 1989). The PSQI is composed of 19 questions grouped into seven components respectively related to subjective sleep quality, sleep latency, sleep duration, habitual sleep efficiency, sleep disturbances, use of sleeping medications and daytime dysfunction. Each of these components are equally rated from 0 to 3 and summed to create a global PSQI score, therefore ranging from 0 to 21. In this study, the simulation being rather simple on purpose, only sleep duration and habitual sleep efficiency have been computed from the simulation and the other components were assigned a constant value. This results in a global PSQI score ranging from 4 to 10, the lower being the better.

The exercise duration of the user is computed as the exercise done in one week. Given our study example presented in figures 2, exercise can only happen on the Tuesday, Saturday and Sunday, raising the optimal value to 180 minutes of exercise per week.

Finally, to incite the policy network to give insights that the user appreciates, we decided of four different topics that could be selected as of interest for the user: sleep time, wake time, sleep duration or exercise. At each epoch of training, a new order of those four topics is randomly generated. Every three weeks, the topic of interest is modified following the previously generated order. If the selected insight contains the current topic of interest, the reward can very simply be 1 and otherwise 0.

4 EXPERIMENTS

In order to create a digital twin of a real user, we used the American Time Use Survey 2003-2020 dataset. This dataset contains information about how people spend their time in a day of 24 hours, each household being interviewed only once. From the 219,368 individuals interviewed, we focused on the working population (21 to 50 years old) which represents 68 percent of the respondents. Among the hundred of available activities, we only considered seven of them: sleeping, working, eating, exercising, relaxing, shopping and travelling. We intentionally created a user with a difficult sleep, as he/she is waking up in the middle of the night and also very early in the morning by taking into account thousands of persons with very different lifestyles as it is the perfect example for the policy network to work on. Indeed, the resulting simulated user has a great potential for improvements, generating a lot of very relevant recommendation insights.

For the following experiments, the features encode 15 possible topics that can be given by the insights: measurement benchmark, exercise duration, sleep duration, weekday, wake time, sleep time, weekend, Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, or Sunday. Those subjects have been selected in order to tell to the policy network about what measurement is the insight, if it compares it to the benchmark value and to which day of the week it refers to. Whether the policy network is doing a topic selection or an insight selection, we decided to give it the same number of options, which means $N_T = N_C = 15$. In the case of insight selection, 4 out of the 15 insights are reserved for benchmark insights, which ensure that the policy network has enough choices at all times. For the training of the policy network, the impact an insight can have on the simulation was entirely described in the previous sections. For the test part presented in the next sections, we set an even more difficult problem by dividing by two the lifestyle improvement factors and by ten the lifestyle fallback factors. The values of interest available to the policy network every day were the PSQI with its seven components, the exercise duration and the feedback from the user. The policy network had access to the history of the past 7 days, which means $T = 7$.

4.1 INSIGHT SELECTION FOR HEALTHCARE

For the first experiment, the reward was based on the PSQI and the exercise duration per week. In order to evaluate the capacity of the policy to learn relevant selection behaviors, the training was repeated with each of the following reward functions:

$$r_{PSQI} = \frac{-PSQI + 10}{6} \tag{2}$$

$$r_{EXE} = sigmoid(\frac{T_{EXE}}{180}) \tag{3}$$

$$r_{FULL} = \frac{-PSQI + 10}{6} + sigmoid(\frac{T_{EXE}}{180}) \tag{4}$$

$$r_{FULL\_LIN} = \frac{-PSQI + 10}{6} + \frac{T_{EXE}}{180} \tag{5}$$

Moreover, to have a point of comparison, we performed two other tests by randomly selecting an insight every day (i.e. RANDOM) and not selecting any insights at all (i.e. BASELINE). Each epoch of RL was composed of 3 weeks of only simulation plus 21 weeks of interaction, which means 147 actions required. As the process is time-consuming and this study is a preliminary study, the policy network was trained only for 500,000 steps and required an accelerated training process to be executed in a reasonable amount of time. For this reason, during the training, insights were only computed once every week instead of every day.

In the figure 5 is presented how the life quality of the simulated user evolve over time with the different selection policies. On the upper plot, three policies are able to increase the PSQI value within 35 days up to 4: the PSQI, FULL and FULL_LIN policies. The other policies, EXE and RANDOM, are then able to reach the same value within 120 days, while the BASELINE stays around 7. On the lower plot, the EXE policy is able to make the user perform almost 4000 hours of exercise over the simulation, BASELINE is almost reaching 3000 hours as exercise can happen without any intervention from the policy while FULL, RANDOM and PSQI are not getting more than 500 hours of exercise. Additional results can be found in the Appendix.

Figure 5: User's life quality over one test simulation with different insights selection policies.

All policies using the PSQI in their reward: the PSQI, FULL and FULL_LIN policies, were the fastest to improve the sleep quality of the user compared to EXE, RANDOM or BASELINE. This highlights the capacity of the policy network to learn the optimal behavior in order to improve sleep quality by different strategies. The EXE policy was the one pushing the user to do the most exercise, thus that learned how to maximise this behavior, while also selecting other types of insights as the PSQI can be seen improving. However, the policies that were trained to optimise both PSQI and exercise duration failed on the later objective. This could be due to an improper weightage of the two components of the reward, or a lack of training time.

4.2 INSIGHT SELECTION WITH FEEDBACK

For the second experiment, focusing on the adequation of the selected insights and the current interest of the user to a particular subject. As the reward is solely composed of the feedback of the user, that is generated at the start of the epoch, it does not require the state machine to run at every step from then. Therefore, each epoch of RL was composed of 6 weeks of simulation only, in order to generate enough insight candidates for every topic, and 60 weeks of interaction. This process allowed to greatly decrease the computing time, dividing it by a tenth.

On figure 6 is presented the behavior of the policy network after 12.000.000 steps of training. The policy network learned (1) that only 4 topics were of interest for this user and (2) to keep proposing the same type of insights while the feedback of the user is positive.

Figure 6: Comparison of user's topic of interest and the presence of it in the selected insight by the policy over time.

It is perfectly able to select the right insight when the topic of interest is either sleep time, exercise duration or wake time. When the topic of interest is sleep duration, the policy does not know which insight to select, and it results in choosing insights on other topics. This probably results from a lack of training time.

5 CONCLUSION

In this paper, we demonstrated the capabilities of our RL system to recommend insights with the objective of (1) improving the user's life quality and (2) satisfying their interest. From the same observation matrix encoding the history of the selected insights, the policy network is able to reach completely different objectives by a simple modification of the reward function. From an abstract representation of the insights, it is able to understand the impact of the recommendation encoded in the insights' features and efficiently select the most relevant. Furthermore, the random nature of the simulation ensures the robustness of the selection policy, using generic and reusable principles based on very simple assumptions. This framework allows our recommender system to generate and select domain-dependent insights limiting item presentation complexity and time spend for rating while keeping reliability in ratings.

REFERENCES

M. Mehdi Afsar, Trafford Crump, and Behrouz Far. Reinforcement learning based recommender systems: A survey, 2021. URL https://arxiv.org/abs/2101.06286.

Rakesh Agrawal and John C Shafer. Parallel mining of association rules. *IEEE Transactions on knowledge and Data Engineering*, 8(6):962–969, 1996.

Hagai Attias. A variational bayesian framework for graphical models. *Adv. Neural Inf. Process. Syst*, 12, 09 2000.

David Blei and Michael Jordan. Variational inference for dirichlet process mixtures. *Bayesian Analysis*, 1, 03 2006. doi: 10.1214/06-BA104.

Daniel J. Buysse, Charles F. Reynolds, Timothy H. Monk, Susan R. Berman, and David J. Kupfer. The pittsburgh sleep quality index: A new instrument for psychiatric practice and research. *Psychiatry Research*, 28(2):193–213, 1989. ISSN 0165-1781. doi: https://doi.org/10.1016/0165-1781(89)90047-4. URL https://www.sciencedirect.com/science/article/pii/0165178189900474.

Albert Gatt and Emiel Krahmer. Survey of the state of the art in natural language generation: Core tasks, applications and evaluation. *Journal of Artificial Intelligence Research*, 61:65–170, 2018.

Tuomas Haarnoja, Aurick Zhou, Kristian Hartikainen, George Tucker, Sehoon Ha, Jie Tan, Vikash Kumar, Henry Zhu, Abhishek Gupta, Pieter Abbeel, and Sergey Levine. Soft actor-critic algorithms and applications, 2018. URL https://arxiv.org/abs/1812.05905.

Aki Härmä and Rim Helaoui. Probabilistic scoring of validated insights for personal health services. *2016 IEEE Symposium Series on Computational Intelligence (SSCI)*, pp. 1–6, 2016.

A. Johnson, T. Pollard, and R. Mark. Mimic-iii clinical database (version 1.4), 2016. URL https://doi.org/10.13026/C2XW26.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning, 2015. URL https://arxiv.org/abs/1509.02971.

Vadim Liventsev, Aki Härmä, and Milan Petković. Towards effective patient simulators. *Frontiers in Artificial Intelligence*, 4, 2021. ISSN 2624-8212. doi: 10.3389/frai.2021.798659. URL https://www.frontiersin.org/articles/10.3389/frai.2021.798659.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Alex Graves, Ioannis Antonoglou, Daan Wierstra, and Martin Riedmiller. Playing atari with deep reinforcement learning, 2013. URL https://arxiv.org/abs/1312.5602.

Volodymyr Mnih, Adrià Puigdomènech Badia, Mehdi Mirza, Alex Graves, Timothy P. Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. 2016. doi: 10.48550/ARXIV.1602.01783. URL https://arxiv.org/abs/1602.01783.

Cataldo Musto, Pierpaolo Basile, Pasquale Lops, Marco de Gemmis, and Giovanni Semeraro. Introducing linked open data in graph-based recommender systems. *Information Processing & Management*, 53(2):405–435, 2017. ISSN 0306-4573. doi: https://doi.org/10.1016/j.ipm.2016.12.003. URL https://www.sciencedirect.com/science/article/pii/S0306457316306847.

F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and E. Duchesnay. Scikit-learn: Machine learning in Python. *Journal of Machine Learning Research*, 12:2825–2830, 2011.

Dhanya Pramod and Prafulla Bafna. Conversational recommender systems techniques, tools, acceptance, and adoption: A state of the art review. *Expert Systems with Applications*, 203:117539, 2022. ISSN 0957-4174. doi: https://doi.org/10.1016/j.eswa.2022.117539. URL https://www.sciencedirect.com/science/article/pii/S0957417422008612.

Antonin Raffin, Ashley Hill, Adam Gleave, Anssi Kanervisto, Maximilian Ernestus, and Noah Dormann. Stable-baselines3: Reliable reinforcement learning implementations. *Journal of Machine Learning Research*, 22(268):1–8, 2021. URL http://jmlr.org/papers/v22/20-1364.html.

Elsa Riachi, Muhammad Mamdani, Michael Fralick, and Frank Rudzicz. Challenges for reinforcement learning in healthcare, 2021. URL https://arxiv.org/abs/2103.05612.

S.J. Roberts, D. Husmeier, I. Rezek, and W. Penny. Bayesian approaches to gaussian mixture modeling. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 20(11):1133–1142, 1998. doi: 10.1109/34.730550.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017. URL https://arxiv.org/abs/1707.06347.

Allmin Susaiyah, Aki Härmä, Ehud Reiter, Rim Helaoui, Milan Petkoviĉ, et al. Towards a generalised framework for behaviour insight mining. In *SmartPHIL: 1st Workshop on Smart Personal Health Interfaces*. ACM, 2020.

Allmin Pradhap Singh Susaiyah, Aki Härmä, Ehud Reiter, and Milan Petkovic. Neural scoring of logical inferences from data using feedback. *Int. J. Interact. Multim. Artif. Intell.*, 6:90–99, 2021.

Sebastian Varges and Chris Mellish. Instance-based natural language generation. *Natural Language Engineering*, 16(3):309–346, 2010.

Dujia Yang, Xiaowei Qin, Xiaodong Xu, Chensheng Li, and Guo Wei. Sample efficient reinforcement learning method via high efficient episodic memory. *IEEE Access*, 8:129274–129284, 2020. doi: 10.1109/ACCESS.2020.3009329.

Kenny J. Young, Richard S. Sutton, and Shuo Yang. Integrating episodic memory into a reinforcement learning agent using reservoir sampling. *ArXiv*, abs/1806.00540, 2018.

Chao Yu, Jiming Liu, and Shamim Nemati. Reinforcement learning in healthcare: A survey, 2019. URL https://arxiv.org/abs/1908.08796.

Yangyang Zhao, Zhenyu Wang, Changxi Zhu, and Shihan Wang. Efficient dialogue complementary policy learning via deep Q-network policy and episodic memory policy. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 4311–4323, Online and Punta Cana, Dominican Republic, November 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.emnlp-main.354. URL https://aclanthology.org/2021.emnlp-main.354.

A APPENDIX

A.1 EXTRACTION ALGORITHM

Algorithm 1 Extraction algorithm

1: **procedure** EXTRACT_AND_BUILD($states$)
2:    **for** day in $week$ **do**
3:       **for** s in $states$ **do**
4:          $start, stop, duration \leftarrow$ FILTER_DATA(day, s)   ▷ All activation times of s on day
5:          $start\_gaussians, stop\_gaussians \leftarrow$ COMPUTE_GAUSSIANS($start, stop$)
6:          ADD_TO_TRANSITION($Idle, s, day, start\_gaussians, 3.5,$ SIZE($duration$))
7:          ADD_TO_TRANSITION($s, Idle, day, stop\_gaussians,$ MAX($duration$), 1)

   procedure COMPUTE_GAUSSIANS($start, stop$)
2:    $n\_components \leftarrow 24$
     $start\_gaussians \leftarrow$ FIT_BGMM($start, n\_components$)
4:    $stop\_gaussians \leftarrow$ FIT_BGMM($stop, n\_components$)
     return $start\_gaussians, stop\_gaussians$

   procedure ADD_TO_TRANSITION($start\_state, end\_state, day, gaussians, horizon, duration$)
     $state\_machine[start\_state][end\_state][day].start\_gaussians \leftarrow gaussians$
3:    $state\_machine[start\_state][end\_state][day].horizon \leftarrow horizon$
     $state\_machine[start\_state][end\_state][day].proportion \leftarrow proportion$

A.2 POLICY NETWORK

As for the user simulation, lots of efforts were put on the environment to keep it as reusable as possible to follow the general framework presented on figure 1. To code this framework, we developed our solution using the library Stable Baselines 3 (Raffin et al., 2021), again simplifying the reusability of our concepts. However, the main drawback of our standard DRL approach is still the need of a lot of training. For this reason, we decided to use the policy network PPO, described in Schulman et al. (2017), as it was demonstrated to be scalable to large models, allow parallel implementation for training and is more efficient than A2C in terms of sample complexity. The clipped surrogate objective of PPO in equation 6 makes it a perfect fit to avoid instability that could be caused by the sparse reward function we are using for user feedback.

$$L^{CLIP}(\theta) = \mathbf{E}_t[min(r_t(\theta)A_t(\theta),\ clip(r_t(\theta, 1 - \epsilon, 1 + \epsilon)A_t(\theta)))] \tag{6}$$

with θ the weights of the neural network, t the current time step, A the advantage function and ϵ a hyperparameter.

A.3 ADDITIONAL RESULTS

Figure 7: Resulting user's behavior with different insights selection policies during one test simulation.

In the figure 7 is presented how behavior of the user, sleep time and wake time, evolves over the simulation time. On the upper plot we can see that the PSQI, EXE, FULL_LIN and RANDOM policies are selecting enough insights recommending to sleep early in order to keep a reasonable sleep time between 22:00 and 22:30. On the other end, without recommendations about sleep time as for the BASELINE or for FULL, the user is sleeping on average after 23:00. by the end of the simulation. On the lower plot we can see that the PSQI, FULL and FULL_LIN policies are the ones recommending the most insights about wake time as the user is waking up after 06:00 as early as March, when it is only in June for EXE and RANDOM.

A.4 FUTURE WORK

We will be deploying this system in patient monitoring and personal health monitoring applications to study and explore insights from patient and personal health. Further work is needed on how to automatically encode the relative impact of each insight on the behavior of the user. Experiments will be conducted both on the relevance of the user simulation system and capabilities of the policy network to adapt to different user behaviors and reward functions. In this study, the same simulation was used during all the training, it would require to train the policy with different users to make it learn how to give good recommendations for different types of lifestyle.

For a matter of simplicity for this preliminary study, only four interests were possible for the user. As the policy was almost perfectly suited for these four interests, we can extrapolate that it would also work if there were more topics of interest with enough training time. Nevertheless, a real user might only be interested in five to ten of those subjects. We believe it would be possible to take this into account by using a weighted random sampling of interests during the training of the policy network, suited to the likelihood of interest of the specific user, instead of a uniform random sampling.