Beyond Scalar Scores: Exploring LLM-based Metrics for Clinical Significance Evaluation in Radiology Reports

Abstract

Automated evaluation of radiology reports is essential for clinical trust, yet clinically significant errors (e.g., missed findings or incorrect descriptions) can critically mislead diagnosis. Traditional metrics fail to distinguish between clinically meaningful and harmless textual variations, collapsing report quality into a single scalar score. Although Large Language Models (LLMs) embody richer medical knowledge, such metrics still lack an explicit boundary of clinical significance. To bridge this gap, we adopt the **ReEvalMed** benchmark as testbed and evaluate metric-level clinical significance from detecting true clinical errors ("*Discrimination*") and tolerating insignificant variations ("*Robustness*"). We design an evaluation framework with one-pass and two-pass settings, and compare 8 LLM evaluators against score-based baselines. Results reveal a *discrimination bias*: LLMs readily detect true clinical errors but struggle to tolerate harmless variations. To mitigate this, we synthesize 4k report pairs and train lightweight interpretable metrics on Qwen3-8B and MedGemma-4B. Our trained metric sharpens the clinical significance boundary, surpassing 32B-scale medical LLMs and remaining competitive with proprietary models. Notably, two-pass inference does not eliminate errors, but redistributes them between discrimination and robustness. We will release the dataset and metric to advance future research.

1 Introduction

Radiology reports document imaging findings (e.g., lesion characteristics, anatomical abnormalities, and diagnostic impressions) that directly guide clinical decisions on diagnosis and treatment (Tanno et al., 2025). Vision-language models can generate such reports automatically from medical images (Bannur et al., 2024; Chen et al., 2024), yet reliable and clinically-aligned evaluation remains an open challenge. A clinician-trusted evaluation

Figure 1: Score-based metrics (e.g. BERTScore) assign comparable scores to clinically significant errors and harmless rephrasings. Our LLM-as-evaluator outputs structured severity judgments, better distinguishing significant errors from insignificant variations.

metric must both identify errors that could significantly affect clinical decisions and remain robust to stylistic variation and clinically insignificant differences. However, as recent study Li et al. (2025) demonstrate, both traditional lexical metrics and LLM-based medical report metrics that correlate strongly with human judgement (e.g. GREEN (Ostmeier et al., 2024) and RaTEScore (Zhao et al., 2024)) lack the sensitivity to differentiate significant clinical errors from minor ones; such boundary blurring calls their validity as reliable indicators of clinical acceptability into question.

LLMs offer a path toward the interpretable evalu-

Figure 2: Discrimination–Robustness accuracy of 8 LLM-as-evaluators, 2 medical metrics, and our post-trained models on ReEvalMed. *Discrimination bias*: most LLMs fall below the diagonal ("D > R").

ation that previous metrics lack: rather than a scalar, an LLM can identify error spans, classify clinical error aspects, and assess clinical significance, thus providing fine-grained feedback. However, empirical validation of LLMs as evaluators for radiology reports remains limited, and it is unclear whether this interpretive capability translates into reliable clinical judgment. To this end, this work investigates the potential of current LLMs as report evaluation metrics from two angles: the zero-shot behaviour of existing open-source and proprietary LLMs, and whether targeted data augmentation and fine-tuning can bridge the performance gap.

Motivated by recent LLM-based evaluators for generated texts (Lu et al., 2024; Kocmi and Federmann, 2023), we design one-pass and two-pass prompts for radiology evaluation (Figure 1), where the former directly outputs structured error annotations and the latter separates ① error span detection from ② clinical significance judgment. As shown in Figure 2, we observe a consistent ***discrimination bias***: *current LLM evaluators struggle to distinguish clinically significant discrepancies from harmless report variations*, resulting in high discrimination but low robustness accuracy.

To mitigate such discrimination bias and better delineate the boundary of clinical significance, we synthesize a balanced dataset containing 2k discrimination and 2k robustness reports across 20 error types using Claude Sonnet, with clinician verification to ensure data quality. To further validate the effectiveness of our synthesized dataset, we train a radiology report evaluation metric based on

Qwen3-8B and MedGemma-4B. Our trained metric significantly improve the clinical significance boundary, outperforming 32B-scale medical LLMs and remaining competitive with proprietary LLMs. Another interesting finding is that two-pass inference settings does not eliminate errors, but redistributes them between discrimination and robustness. Our contributions are three-fold:

- **Analysis of LLM-based Evaluators.** We systematically evaluate 8 score-based metrics and 8 LLM-based metrics on ReEvalMed using one-pass and two-pass LLM prompting strategies, analyze the error pattern and revealing a consistent discrimination bias among most LLM metrics.

- **Clinically grounded data synthesis.** We synthesise a balanced dataset of 4k radiology report pairs covering all 20 error categories mentioned in ReEvalMed, annotated at the span level and verified for clinical validity.

- **Lightweight interpretable metric.** Building on the synthesised data, we train Qwen3-8B via supervised fine-tuning (SFT) and reinforcement learning (RL) techniques using both one-pass and two-pass prompting format, achieving 78.5% discrimination and 70.5% robustness accuracy, surpassing medical LLMs at the 32B scale (such as Lingshu-32B (Xu et al., 2025) and HuluMed-32B (Jiang et al., 2025)).

2 Preliminary

Task formulation A radiology report evaluation metric takes as input a reference report ("**REF**") and a generated candidate ("**TGT**"), and outputs a quality judgment. Traditional metrics, including lexical metrics (BLEU (Papineni et al., 2002), ROUGE-L (Lin, 2004)), embedding-based metrics (BERTScore (Zhang et al., 2019)), and clinical NLP metrics (RadGraph (Jain et al., 2021), CheXbert (Smit et al., 2020)), all reduce this judgment to a single **continuous score**. However, a scalar score cannot distinguish clinically significant errors from insignificant ones, as both may incur the same penalty under any scalar metric. In this work, we instead adopt a **structured textual output** that explicitly labels each discrepancy as *significant* or *insignificant*, and identifies its error span and clinical aspect, providing fine-grained attribution beyond what a scalar can express.

ReEvalMed benchmark To assess how well a metric aligns with clinical judgment,

Criteria	Error Type	Error Aspect	#
Discrimination	Omission, Fabrication, Inaccuracy	Location, Severity, Description, Comparison/Progression	120
	Inaccuracy Only	Negation, Modality, Size/Distance, Contradiction, Uncertainty, Terminology, Noise, Stylistic Variation	80
Robustness	Omission, Fabrication, Inaccuracy	Location, Severity, Description, Comparison/Progression	120
	Inaccuracy Only	Negation, Modality, Size/Distance, Contradiction, Uncertainty, Terminology, Noise, Stylistic Variation	80

Table 1: ReEvalMed error taxonomy and test set composition. The benchmark defines 20 error categories across two evaluation dimensions, *Discrimination* (detecting clinically significant errors) and *Robustness* (tolerating clinically insignificant variations), each with 200 samples (400 total).

ReEvalMed (Li et al., 2025) provides a meta-evaluation benchmark: given report pairs with known clinical labels, it measures whether a metric can correctly identify clinically meaningful discrepancies. Its evaluation criteria are co-developed with clinicians to capture what clinicians actually consider significant in a radiology report. ReEvalMed organises its 20 error categories along two axes, *Error Type* (Omission, Fabrication, Inaccuracy) and *Error Aspect* (e.g., Location, Severity, Negation), as summarised in Table 1. The test set contains 400 report pairs drawn from MIMIC-CXR (Johnson et al., 2019).

Discrimination and Robustness ReEvalMed introduce two metrics along two complementary dimensions to measure the quality of evaluation:

- **Discrimination** (200 test samples): the ability to detect errors that could materially affect diagnosis or treatment (e.g., incorrect severity grade, missed finding).
- **Robustness** (200 test samples): the ability to remain unpenalised by clinically harmless variations (e.g., synonym substitution, phrasing paraphrase).

A clinically significance-sensitive metric should achieve high accuracy on both dimensions simultaneously, i.e., correctly flagging clinically significant errors while tolerating harmless variations.

3 Analysis on LLM-based Metrics

3.1 LLM-as-Evaluator Methodology

Motivated by recent LLM-based evaluators for generated texts (Lu et al., 2024; Kocmi and Federmann, 2023), we design structured prompts that instruct an LLM to compare a REF and TGT pair and output fine-grained error annotations rather than a scalar score. Specifically, the evaluator identifies error spans and assigns each a severity level from three classes: `Critical` (internal contradictions that severely undermine report trust), `Significant` (errors that meaningfully alter clinical decision-making), and `Insignificant` (stylistic variations or clinically harmless deviations). We explore two inference paradigms for this task.

One-pass The LLM receives REF and TGT in a single prompt and directly outputs a JSON object containing three severity buckets (`critical`, `significant`, and `insignificant`), each mapping error spans to their error aspects, together with a free-text explanation.

Two-pass One-pass inference couples span detection and severity judgment into a single output, which may cause compounding errors. To address this, we decouple inference into two passes:

- **Pass 1 (Span Detection)**: the LLM identifies all discrepancies between REF and TGT, outputting a JSON array of error spans with their aspects (e.g., `Location - Omission`, `Negation`).
- **Pass 2 (Severity Judgment)**: for each detected span, a second call outputs exactly one word (`Critical`, `Significant`, or `Insignificant`), conditioned on aspect-specific criteria.

D/R classification rule Note that the three severity levels are *error-level* labels assigned to individual spans, whereas D and R are *metric-level* scores

Type	Metric	Maximin Threshold			
		D (↑)	R (↑)	Avg (↑)	Gap (↓)
NLP	BLEU	19.0	19.0	19.0	0.0
	BERTScore	24.0	24.0	24.0	0.0
	AlignScore	51.0	51.0	51.0	0.0
Med.	RadGraph	28.5	28.5	28.5	0.0
	RaTEScore	35.5	35.5	35.5	0.0
	CheXbert	47.0	49.0	48.0	2.0
LLM	GREEN	53.5	41.5	47.5	12.0
	CRIMSON	**75.0**	**80.5**	**77.8**	5.5

Table 2: Comparison of score-based metrics on ReEvalMed. D and R scores are in accuracy (%). Maximin threshold is applied to obtain balanced results. Best results are in **bold**.

that measure how well a metric's predictions align with clinical ground truth. To bridge the two levels, we aggregate span-level severities into a binary report-level prediction. Denoting a TGT–REF pair as (t, r), let n_{cri}, n_{sig}, n_{insig} be the number of Critical, Significant, and Insignificant spans identified:

$$\text{CLS}(t,r) = \begin{cases} sig. & n_{cri} + n_{sig} > 0 \,, \\ insig. & n_{cri} = n_{sig} = 0, \ n_{insig} \geq 0 \,. \end{cases} \quad (1)$$

The **Discrimination score** (D) is the accuracy of predicting *sig.* on the Discrimination subset, where all pairs contain clinically significant errors; the **Robustness score** (R) is the accuracy of predicting *insig.* on the Robustness subset, where all pairs contain only clinically insignificant variations.

3.2 Experimental Setup

Baselines We evaluate 8 score-based metrics that output continuous scores: 3 NLP metrics (BLEU (Papineni et al., 2002), BERTScore (Zhang et al., 2019), and AlignScore (Zha et al., 2023)); 3 medical metrics (RadGraph (Jain et al., 2021), RaTEScore (Zhao et al., 2024), and CheXbert (Smit et al., 2020)); and 2 LLM-based metrics (GREEN (Ostmeier et al., 2024), which prompts GPT-4 for finding-level error annotations, and CRIMSON (Baharoon et al., 2026), which fine-tunes MedGemma on 140K report pairs with GPT-5-generated severity labels via LoRA.

LLM-as-evaluators We evaluate 3 proprietary LLMs (GPT-5.1, Claude Sonnet 4.5, Gemini 3 Pro)

and 5 open-source LLMs (Qwen3-Max (Yang et al., 2025), LingShu-32B (Xu et al., 2025), HuluMed-32B (Jiang et al., 2025), Qwen3-8B (Yang et al., 2025), and MedGemma-4B (Sellergren et al., 2025)) using our one-pass and two-pass prompts.

Prompt Prompt templates for both one-pass and two-pass paradigms are provided in Appendix G.

Hyperparameters All LLM model inferences use greedy decoding (temperature = 0.0) with a maximum of 1024 output tokens.

Device and platform Proprietary models are accessed via their official APIs. Open-source models (≤32B) are served with vLLM (Kwon et al., 2023) on a single NVIDIA A800 GPU. The same device is used for all training experiments in Section 5.

3.3 Meta-Evaluation

Score-based metrics To align the accuracy scale with LLM-based metrics, score-based metrics require a decision threshold to convert continuous values into binary D/R predictions. We sweep all thresholds and apply the **maximin criterion** $\max_\theta \min(D_\theta, R_\theta)$, selecting the operating point that maximises the worse of the two dimensions.

Average and Gap We report **Avg** = (D + R)/2 for overall accuracy and **Gap** = |D − R| for D–R imbalance. An ideal evaluator achieves high Avg with low Gap.

3.4 Results

Score-based metrics fail to distinguish significance Score-based metrics require a decision threshold to convert continuous scores into binary significant/insignificant predictions. We select the maximin threshold $\max_\theta \min(D_\theta, R_\theta)$ that maximises the worse of the two dimensions, balancing D and R accuracy (see Appendix E, Figure 6 for full trade-off curves). As shown in Table 2 (left), most non-LLM metrics remain below 55% on both D and R (e.g. BLEU 19.0/19.0, CheXbert 47.0/49.0), indicating they cannot reliably separate significant errors from harmless variations. LLM-based score metrics perform notably better: CRIMSON achieves the best maximin point (75.0/80.5), substantially outperforming GREEN (53.5/41.5) and all non-LLM baselines.

LLM-as-Evaluators are sensitive but poorly calibrated Compared with score-based metrics, LLM-as-Evaluators achieve substantially higher

Type	Model	1-Pass				2-Pass			
		D (↑)	R (↑)	Avg (↑)	Gap (↓)	D (↑)	R (↑)	Avg (↑)	Gap (↓)
Proprietary	GPT-5.1	98.5	42.5	70.5	56.0	95.0	69.5	**82.3**	25.5
	Claude Sonnet 4.5	91.5	**84.0**	**87.8**	**7.5**	**98.0**	51.0	74.5	47.0
	Gemini 3 Pro	94.0	57.5	75.8	36.5	65.0	**79.5**	72.3	14.5
Open-source	Qwen3-Max	97.0	53.5	75.3	43.5	96.5	45.0	70.8	51.5
	LingShu-32B	99.5	64.0	81.8	35.5	97.5	5.5	51.5	92.0
	HuluMed-32B	**100.0**	23.0	61.5	77.0	96.0	52.5	74.3	43.5
	Qwen3-8B	96.5	8.0	52.3	88.5	95.5	9.0	52.3	86.5
	MedGemma-4B	49.0	9.0	29.0	40.0	67.0	67.5	67.3	**0.5**

Table 3: Comparison of LLM-as-evaluator on ReEvalMed benchmark. D and R scores are in accuracy (%). Best results are in **bold**.

Figure 3: Demonstration of error aspects from ground truth classifications to prediction of Claude Sonnet 4.5.

Discrimination: as shown in Table 3, most LLMs reach D ≥ 94% under 1-Pass, far exceeding the best score-based result (CRIMSON, 75.0%). However, Robustness varies drastically: R ranges from 8.0% (Qwen3-8B) to 84.0% (Claude Sonnet 4.5), with most models below 60%. Claude Sonnet 4.5 is the only model to achieve strong performance on both dimensions simultaneously (D=91.5%, R=84.0%), suggesting an internal calibration absent from all other tested LLM-based metrics.

1-Pass vs. 2-Pass Switching from 1-Pass to 2-Pass does not uniformly improve calibration; instead, it shifts the bias pattern in model-dependent ways. Some models see their Gap *reduce*: GPT-5.1 narrows from 56.0 to 25.5, and HuluMed-32B from 77.0 to 43.5. Others see Gap *amplify*: Claude Sonnet 4.5 increases from 7.5 to 47.0, LingShu-32B from 35.5 to 92.0, and Gemini 3 Pro from 36.5 to 14.5. These results suggest that decoupling span detection from severity judgment redistributes errors between the two passes rather than eliminating them, and the net effect depends on the model's internal calibration.

Discrimination bias Another consistent pattern emerges across both paradigms: nearly all models exhibit large Gap driven by D scores substantially exceeding R, indicating a systematic tendency to classify clinically harmless variations as significant errors. We term this discrimination bias. Without explicit supervision on the significance boundary, models lack a clear understanding of what constitutes a clinically meaningful error and tend to err on the side of caution by flagging variations as significant. Decoupling span detection from severity judgment (2-Pass) partially redistributes this bias, motivating further exploration through data augmentation and fine-tuning in Sections 4–5.

Error aspect confusion Beyond the overall D–R gap, we examine *which* error aspects are most confused by the best-performing LLM (Claude Sonnet 4.5). Figure 3 visualises the flow from ground-truth aspects to model-predicted aspects. Two systematic biases emerge: (1) over-prediction of Contradiction (20→39) and Negation (20→33), suggesting the model defaults to these labels when uncertain; (2) under-recognition of Modality (20→4) and Noise (20→10), indicating difficulty distinguishing subtle imaging-specific variations from true errors. These aspect-level confusions further motivate targeted training data.

Figure 4: Overview of our data synthesis and training pipeline. **Left:** Reference reports are stratified-sampled from MIMIC-CXR and paired with error specifications for controlled error injection. **Right:** Base models are fine-tuned through SFT and RL under both One-Pass and Two-Pass evaluation paradigms.

4 Report Synthesis via Clinical Error Injection

The analysis in Section 3 reveals that discrimination bias is pervasive across LLM evaluators, yet no large-scale training resource exists that explicitly supervises the boundary between clinically significant errors and harmless variations. To bridge this gap, we construct 4,000 REF–TGT medical report pairs with specific error annotations covering all 20 error categories with balanced D/R supervision, designed both to mitigate the bias when training lightweight metrics and to serve as a reusable resource, as shown in Figure 4 (left).

4.1 Stratified Sampling

Different error categories naturally occur in reports of varying lengths, e.g. *Stylistic Variation* errors require longer, multi-sentence reports, while *Severity Omission* errors can appear even in short single-finding reports. Inspired by stratified sampling practices in machine translation evaluation (Fuentes et al., 2022), we sample 2,000 reference reports from the approximately 227K reports in MIMIC-CXR (Johnson et al., 2019) across four character-length buckets (0–200, 200–350, 350–500, >500 characters), combined with category-specific keyword filters derived from the error specifications to guarantee lexical relevance. The resulting length distribution across all 20 error categories is visualised in Appendix C.

4.2 Error Specifications

A key challenge is defining when a textual difference is clinically significant versus harmless. We address this by prompting Claude Sonnet 4.5 to analyse the 20 ReEvalMed test samples per category and distil structured *error specifications*, each containing: (1) a precise clinical error definition, (2) common medical manifestation patterns in CXR reports, (3) discrimination text patterns showing changes that alter clinical meaning (e.g. "left upper lobe nodule" → "pulmonary nodule"), and (4) robustness text patterns showing clinically harmless reformulations (e.g. "hepatic lesion in segment 7" → "right hepatic lobe lesion"). To avoid potential test-set leakage, we deliberately prevent the model from directly reusing ReEvalMed samples during generation; instead, the specifications extract category-level patterns and encourage diverse, novel realisations beyond the original examples. We present the error injection prompt (Appendix G) and representative examples in Appendix F.

4.3 Error Injection and Report Synthesis

Each reference is assigned exactly one Discrimination injection (clinically significant error) and one Robustness injection (clinically harmless variation).[1] Across 20 categories with 100 D + 100 R

---

[1]We deliberately limit each reference to a single D and R pair rather than generating multiple variants from the same source, ensuring distributional diversity and preventing the model from overfitting to repeated reference patterns.

samples each, the corpus contains **4,000 (REF, TGT) pairs** in total. Claude Sonnet 4.5 generates each TGT conditioned on the error specification and sampled REF; each sample is further annotated with span-level labels (error spans, type, severity) for use in two-pass training.

4.4 Quality Control via Human Evaluation

To guarantee quality, we add automatic sanity checks (e.g. non-empty output, reasonable length ratio) to detect obviously invalid generations and trigger immediate re-generation.

Although **93%** of the samples passed clinician verification, the reviewer flagged 7 out of 100 sampled pairs. After careful inspection, we find the improper generations can be generally summarised into three error patterns: severity mislabelling (the assigned severity disagrees with clinical judgement), injection failure (error injection produces no meaningful change), and aspect mismatch (the injected change is purely stylistic, deviating from the assigned error type). Detailed cases of all 7 flagged samples are shown in Appendix D, which we hope will serve as a practical reference when constructing clinically grounded evaluation datasets.

5 Lightweight Metric Training

5.1 Training Stages

To validate the effectiveness of our synthesised 4K corpus in improving evaluation accuracy and reducing discrimination bias, we train a lightweight radiology report metric and evaluate it on ReEvalMed. The 4,000-sample corpus is 1:1 D:R balanced, which prevents model collapse into degenerate always-positive or always-negative prediction. As shown in Figure 4 (right), we adopt a two-stage training pipeline applied to both one-pass and two-pass paradigms: supervised fine-tuning (SFT) to teach the target output format, followed by an RL algorithm to calibrate the significance boundary.

Base models We select two lightweight LLMs of different scales: **Qwen3-8B** (Yang et al., 2025), a general-purpose 8B instruction-tuned LLM, and **MedGemma-4B** (Sellergren et al., 2025), a 4B model pre-trained on biomedical corpora. This allows us to examine whether domain-specific pre-training complements our clinically grounded data.

SFT The SFT stage trains the model to produce the target output format and acquire basic error detection ability. For one-pass, the model learns to

Model	Setting	D (↑)	R (↑)	Avg (↑)	Gap (↓)
One-Pass					
Qwen3	Base	96.5	8.0	52.3	88.5
	+ SFT	90.0	19.0	54.5	71.0
	+ SFT + RL	86.0	39.5	62.8	46.5
MedGemma	Base	49.0	9.0	29.0	40.0
	+ SFT	60.5	93.0	76.8	32.5
	+ SFT + RL	75.5	80.0	**77.8**	4.5
Two-Pass					
Qwen3	Base	95.5	9.0	52.3	86.5
	+ SFT	84.0	52.0	68.0	32.0
	+ SFT + RL	78.5	70.5	74.5	8.0
MedGemma	Base	67.0	67.5	67.3	**0.5**
	+ SFT	67.0	84.0	75.5	17.0
	+ SFT + RL	66.5	90.5	**78.5**	24.0

Table 4: Training results on ReEvalMed based on Qwen3-8B (Yang et al., 2025) and MedGemma-4B (Sellergren et al., 2025). D and R scores are in accuracy (%). Best results are in **bold**.

produce a structured JSON object containing severity buckets and error spans from a single REF+TGT input. For two-pass, we construct separate training samples for Pass 1 and Pass 2, then fine-tune the same base model on both parts so that it masters error span extraction (Pass 1: a JSON array of error spans with clinical aspects) and severity classification (Pass 2: labelling each span as Critical, Significant, or Insignificant).

RL SFT learns the output format and may improve performance, but does not calibrate the significance boundary. We apply DPO (Rafailov et al., 2023) to address this: preference pairs are constructed from the same 4K corpus by swapping the ground-truth severity label (e.g., Significant → Insignificant) to create *rejected* responses, while the original label serves as the *chosen* response. Note that for two-pass, since the model already captures error spans well after SFT, we only apply DPO to the Pass 2 severity classification.

Training framework All models are trained using LoRA (Hu et al., 2022) via LLaMA-Factory (Zheng et al., 2024). Detailed hyperparameters are provided in Appendix A.

5.2 Results

Table 4 summarises the training results.

Best results After post-training, MedGemma-4B under 1-Pass achieves the best D–R alignment

(D=75.5%, R=80.0%, Gap=4.5), while Qwen3-8B under 2-Pass reaches D=78.5%, R=70.5% (Gap=8.0). Both surpass 32B-scale medical LLMs such as LingShu-32B and HuluMed-32B (Table 3), and approach Claude Sonnet 4.5 (D=91.5%, R=84.0%) at a fraction of the inference cost.

SFT and RL serve complementary roles   SFT teaches models to produce structured outputs but does not calibrate the significance boundary: Qwen3-8B remains heavily D-biased after SFT (1-Pass Gap: 88.5→71.0; 2-Pass Gap: 86.5→32.0), while MedGemma-4B overcorrects toward R-bias under 1-Pass (D=60.5%, R=93.0%). RL then narrows the Gap from both directions: for Qwen3-8B it boosts R while preserving D (2-Pass Gap: 32.0→8.0); for MedGemma-4B it recovers D from 60.5% to 75.5% while maintaining high R (Gap: 32.5→4.5). The two stages are thus complementary—SFT establishes the output format and RL refines the D–R boundary.

1-Pass vs. 2-Pass depends on the model   For Qwen3-8B, 2-Pass substantially outperforms 1-Pass (Gap 8.0 vs. 46.5), as decoupling span detection from severity judgment helps the model avoid conflating *where* an error is with *how serious* it is. For MedGemma-4B, however, 1-Pass yields better alignment (Gap 4.5 vs. 24.0): under 2-Pass, R continues to rise (84.0→90.5%) but D stagnates at 66.5%, amplifying R-bias with each training stage. This suggests the optimal pipeline depends on the base model's inherent calibration characteristics.

Effectiveness of data and training   Across both models and paradigms, training on our synthesised data consistently reduces the Gap, demonstrating the effectiveness of targeted data augmentation for D–R alignment. Even with lightweight LoRA training on models as small as 4B, the resulting metrics achieve competitive performance with proprietary LLMs, validating both the quality of our synthesised dataset and the training framework.

6   Related Work

Radiology report evaluation   Standard lexical metrics (Papineni et al., 2002; Lin, 2004; Banerjee and Lavie, 2005) remain widely used despite well-documented limitations for clinical text. CREPE (Cho et al., 2025), CheXbert (Smit et al., 2020) and RadGraph (Jain et al., 2021) offer error counts or structured representations but reduce evaluation to a scalar. GREEN (Ostmeier et al., 2024)

and RGRG (Tanida et al., 2023) leverage LLMs as judges, but do not decompose error types or jointly evaluate D and R. RaTEScore (Zhao et al., 2024) and MAIRA (Hyland et al., 2023) target factual grounding but treat evaluation as scalar regression. None produce interpretable, span-level error attribution. ReEvalMed (Li et al., 2025) introduces the D–R framework and demonstrates the systematic failure of existing metrics on both dimensions; our work builds on this benchmark with targeted data construction and post-training.

LLM-as-judge   Zheng et al. (2023) established the LLM-as-judge paradigm for general NLP tasks. In the medical domain, Singhal et al. (2023) demonstrated expert-level performance on clinical QA. However, LLMs used as report evaluators tend to over-penalise stylistic variations (Liu et al., 2023), a failure mode our Robustness dimension systematically quantifies.

LLM post-training   Reinforcement learning from human feedback (Ouyang et al., 2022) and its offline variant DPO (Rafailov et al., 2023) have become standard techniques for aligning LLMs with human preferences. Parameter-efficient methods such as LoRA (Hu et al., 2022) make post-training accessible on consumer hardware, and unified frameworks like LLaMA-Factory (Zheng et al., 2024) streamline the SFT–RL pipeline. Recent work further simplifies preference optimisation by removing the reference model entirely (Hong et al., 2024). We leverage this post-training stack (SFT followed by iterative RL with LoRA) to build a lightweight clinical report evaluator calibrated on the D–R distinction, a clinically motivated supervision signal not previously explored in this domain.

7   Conclusion

We systematically evaluate LLM-based metrics for clinical significance in radiology reports, revealing a consistent *discrimination bias*: LLMs readily detect true clinical errors but struggle to tolerate harmless variations. To mitigate this, we synthesize 4k balanced report pairs and train lightweight metrics via SFT and RL, sharpening the significance boundary to surpass 32B-scale medical LLMs while remaining competitive with proprietary models. We also find that two-pass inference redistributes rather than eliminates errors between discrimination and robustness. We will release the dataset and metric to advance future research.

Limitations

The limitations of this study can be summarised as follows:

- **Quality control cost.** The most rigorous validation of synthesised report pairs would require expert clinician annotation, which is prohibitively expensive at scale. As a practical compromise, we randomly sampled 100 generated pairs for manual verification (Section 4), leaving full-scale clinician review for future work.

- **Training algorithm.** The primary goal of this paper is to explore the proposed LLM-based evaluation framework and demonstrate the effectiveness of our synthesised data; metric training serves as a validation vehicle rather than the core contribution. We therefore adopt DPO as a straightforward offline preference optimisation method. Modern reinforcement learning algorithms (e.g. PPO, GRPO) typically require large-scale rollouts that exceed our current data budget; exploring these and other advanced training pipelines is a promising direction for future work.

- **Domain coverage.** Our models are trained and evaluated on MIMIC-CXR (English, US clinical setting); out-of-distribution generalisation to other languages, imaging modalities, or clinical environments remains to be studied.

- **Inference cost.** The two-pass approach doubles inference cost compared to one-pass; in high-throughput settings, one-pass DPO may provide a better efficiency–calibration trade-off.

Ethics Statement

We take ethical considerations seriously and strictly adhere to the ACL Code of Ethics. All data used in this study are derived from publicly available datasets; no protected patient information is collected or used. A clinician co-author participated in the human verification of synthesized data (Section 4) to ensure clinical validity. Our proposed approaches and metrics do not include statements that induce the model to generate harmful information; the evaluation framework focuses solely on assessing clinical significance of textual differences in radiology reports. We ensure that the findings and conclusions of this paper are reported accurately and objectively.

References

Mohammed Baharoon, Thibault Heintz, Siavash Raissi, Mahmoud Alabbad, Mona Alhammad, Hassan AlOmaish, Sung Eun Kim, Oishi Banerjee, and Pranav Rajpurkar. 2026. Crimson: A clinically-grounded llm-based metric for generative radiology report evaluation. *arXiv preprint arXiv:2603.06183*.

Satanjeev Banerjee and Alon Lavie. 2005. Meteor: An automatic metric for mt evaluation with improved correlation with human judgments. In *Proceedings of the acl workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pages 65–72.

Shruthi Bannur, Kenza Bouzid, Daniel C Castro, Anton Schwaighofer, Anja Thieme, Sam Bond-Taylor, Maximilian Ilse, Fernando Pérez-García, Valentina Salvatelli, Harshita Sharma, and 1 others. 2024. Maira-2: Grounded radiology report generation. *arXiv preprint arXiv:2406.04449*.

Zhihong Chen, Maya Varma, Jean-Benoit Delbrouck, Magdalini Paschali, Louis Blankemeier, Dave Van Veen, Jeya Maria Jose Valanarasu, Alaa Youssef, Joseph Paul Cohen, Eduardo Pontes Reis, and 1 others. 2024. Chexagent: Towards a foundation model for chest x-ray interpretation. In *AAAI 2024 Spring Symposium on Clinical Foundation Models*.

Gihun Cho, Seunghyun Jang, Hanbin Ko, Inhyeok Baek, and Chang Min Park. 2025. Crepe: Rapid chest x-ray report evaluation by predicting multi-category error counts. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 21749–21766.

Belén Saldías Fuentes, George Foster, Markus Freitag, and Qijun Tan. 2022. Toward more effective human evaluation for machine translation. In *Proceedings of the 2nd Workshop on Human Evaluation of NLP Systems (HumEval)*, pages 76–89.

Jiwoo Hong, Noah Lee, and James Thorne. 2024. Orpo: Monolithic preference optimization without reference model. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11170–11189.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, and 1 others. 2022. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3.

Stephanie L Hyland, Shruthi Bannur, Kenza Bouzid, Daniel C Castro, Mercy Ranjit, Anton Schwaighofer, Fernando Pérez-García, Valentina Salvatelli, Shaury Srivastav, Anja Thieme, and 1 others. 2023. Maira-1: A specialised large multimodal model for radiology report generation. *arXiv preprint arXiv:2311.13668*.

Saahil Jain, Ashwin Agrawal, Adriel Saporta, Steven QH Truong, Du Nguyen Duong, Tan Bui, Pierre Chambon, Yuhao Zhang, Matthew P Lungren,

Andrew Y Ng, and 1 others. 2021. Radgraph: Extracting clinical entities and relations from radiology reports. *arXiv preprint arXiv:2106.14463*.

Songtao Jiang, Yuan Wang, Sibo Song, Tianxiang Hu, Chenyi Zhou, Bin Pu, Yan Zhang, Zhibo Yang, Yang Feng, Joey Tianyi Zhou, and 1 others. 2025. Hulu-med: A transparent generalist model towards holistic medical vision-language understanding. *arXiv preprint arXiv:2510.08668*.

Alistair EW Johnson, Tom J Pollard, Nathaniel R Greenbaum, Matthew P Lungren, Chih-ying Deng, Yifan Peng, Zhiyong Lu, Roger G Mark, Seth J Berkowitz, and Steven Horng. 2019. Mimic-cxr-jpg, a large publicly available database of labeled chest radiographs. *arXiv preprint arXiv:1901.07042*.

Tom Kocmi and Christian Federmann. 2023. Gemba-mqm: Detecting translation quality error spans with gpt-4. In *Proceedings of the Eighth Conference on Machine Translation*, pages 768–775.

Woosuk Kwon, Zhuohan Li, Siyuan Zhuang, Ying Sheng, Lianmin Zheng, Cody Hao Yu, Joseph Gonzalez, Hao Zhang, and Ion Stoica. 2023. Efficient memory management for large language model serving with pagedattention. In *Proceedings of the 29th symposium on operating systems principles*, pages 611–626.

Ruochen Li, Jun Li, Bailiang Jian, Kun Yuan, and Youxiang Zhu. 2025. Reevalmed: Rethinking medical report evaluation by aligning metrics with real-world clinical judgment. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 11823–11837.

Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*, pages 74–81.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: Nlg evaluation using gpt-4 with better human alignment. In *Proceedings of the 2023 conference on empirical methods in natural language processing*, pages 2511–2522.

Qingyu Lu, Baopu Qiu, Liang Ding, Kanjian Zhang, Tom Kocmi, and Dacheng Tao. 2024. Error analysis prompting enables human-like translation evaluation in large language models. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 8801–8816.

Sophie Ostmeier, Justin Xu, Zhihong Chen, Maya Varma, Louis Blankemeier, Christian Bluethgen, Arne Edward Michalson Md, Michael Moseley, Curtis Langlotz, Akshay S Chaudhari, and 1 others. 2024. Green: Generative radiology report evaluation and error notation. In *Findings of the association for computational linguistics: EMNLP 2024*, pages 374–390.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, and 1 others. 2022. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*, pages 311–318.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. *Advances in neural information processing systems*, 36:53728–53741.

Andrew Sellergren, Sahar Kazemzadeh, Tiam Jaroensri, Atilla Kiraly, Madeleine Traverse, Timo Kohlberger, Shawn Xu, Fayaz Jamil, Cían Hughes, Charles Lau, and 1 others. 2025. Medgemma technical report. *arXiv preprint arXiv:2507.05201*.

Karan Singhal, Shekoofeh Azizi, Tao Tu, S Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, and 1 others. 2023. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180.

Akshay Smit, Saahil Jain, Pranav Rajpurkar, Anuj Pareek, Andrew Y Ng, and Matthew Lungren. 2020. Combining automatic labelers and expert annotations for accurate radiology report labeling using bert. In *Proceedings of the 2020 conference on empirical methods in natural language processing (EMNLP)*, pages 1500–1519.

Tim Tanida, Philip Müller, Georgios Kaissis, and Daniel Rueckert. 2023. Interactive and explainable region-guided radiology report generation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 7433–7442.

Ryutaro Tanno, David GT Barrett, Andrew Sellergren, Sumedh Ghaisas, Sumanth Dathathri, Abigail See, Johannes Welbl, Charles Lau, Tao Tu, Shekoofeh Azizi, and 1 others. 2025. Collaboration between clinicians and vision–language models in radiology report generation. *Nature Medicine*, 31(2):599–608.

Weiwen Xu, Hou Pong Chan, Long Li, Mahani Aljunied, Ruifeng Yuan, Jianyu Wang, Chenghao Xiao, Guizhen Chen, Chaoqun Liu, Zhaodonghui Li, and 1 others. 2025. Lingshu: A generalist foundation model for unified multimodal medical understanding and reasoning. *arXiv preprint arXiv:2506.07044*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, and 1 others. 2025. Qwen3 technical report. *arXiv preprint arXiv:2505.09388*.

Yuheng Zha, Yichi Yang, Ruichen Li, and Zhiting Hu. 2023. Alignscore: Evaluating factual consistency with a unified alignment function. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 11328–11348.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q Weinberger, and Yoav Artzi. 2019. Bertscore: Evaluating text generation with bert. *arXiv preprint arXiv:1904.09675*.

Weike Zhao, Chaoyi Wu, Xiaoman Zhang, Ya Zhang, Yanfeng Wang, and Weidi Xie. 2024. Ratescore: A metric for radiology report generation. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 15004–15019.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, and 1 others. 2023. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in neural information processing systems*, 36:46595–46623.

Yaowei Zheng, Richong Zhang, Junhao Zhang, Yanhan Ye, and Zheyan Luo. 2024. Llamafactory: Unified efficient fine-tuning of 100+ language models. In *Proceedings of the 62nd annual meeting of the association for computational linguistics (volume 3: system demonstrations)*, pages 400–410.

A Model and Training Hyperparameters

Table 5 lists the model configuration and training hyperparameters used in all experiments. We fine-tune two base models (Qwen3-8B and MedGemma-4B) using LoRA (Hu et al., 2022) via LLaMA-Factory (Zheng et al., 2024). SFT and DPO share the same LoRA and optimiser settings; DPO-specific parameters (preference construction) are listed separately.

B Error Category Descriptions

Table 6 provides detailed descriptions of each of the 20 error categories in ReEvalMed, organised by Error Type and Error Aspect.

C Length Distribution of Synthesised Data

Figure 5 shows the length distribution of our synthesised data compared to the ReEvalMed test set, broken down by error category and stratified across four length buckets. The generated corpus covers all buckets in every category, confirming that stratified sampling produces diverse report lengths.

Hyperparameter	Value
Model	
Base model 1	Qwen/Qwen3-8B (8B)
Base model 2	google/medgemma-4b-it (4B)
LoRA	
LoRA rank	8
LoRA alpha	16
Training	
Learning rate	1e-4
Epochs	3
Scheduler	cosine
Precision	bfloat16
Gradient accumulation	8
Max sequence length	2048
DPO	
β	0.1
Sampling temperature	1.0
Samples per input	2

Table 5: Model and training hyperparameters for all SFT and DPO experiments. LoRA and optimiser settings are shared across stages; DPO-specific parameters govern preference pair construction via rejection sampling.

D Human Validation on Report Synthesis

To verify the clinical fidelity of our synthesised data, we randomly sample 100 pairs (50 D + 50 R) covering all 20 error categories and have a clinician manually review each pair. For each sample, the clinician assesses whether: (1) the injected error is clinically plausible and correctly categorised, (2) the severity label (significant vs. insignificant) is appropriate, and (3) the generated report reads naturally without obvious artefacts.

Case studies Table 7 presents representative examples from the human validation, illustrating both successful and problematic generations.

E Score-based Metric Results

Unlike LLM-based metrics that output binary significant/insignificant predictions, score-based metrics produce continuous scores requiring a decision threshold to convert to D/R accuracy. In the main paper (Table 3), we report results at the **maximin threshold** $\max_\theta \min(D_\theta, R_\theta)$, which selects the operating point that maximises the worse of the two dimensions.

Figure 6 shows the full D–R trade-off curves for all 8 score-based metrics. Each curve traces the (D, R) accuracy pair as the decision threshold

Figure 5: Length distribution comparison between the ReEvalMed test set (top axis) and our generated training corpus (bottom axis), stacked by length bucket across all 20 error categories.

varies; the filled circle marks the maximin operating point reported in Table 3. CRIMSON achieves the best maximin point (75.0, 80.5), substantially outperforming all other score-based metrics. NLP metrics (BLEU, BERTScore, AlignScore) cluster in the low-accuracy region, while medical metrics (RadGraph, RaTEScore, CheXbert) offer moderate improvements.

Figure 6: D–R trade-off curves for all score-based metrics. Each curve traces (D, R) accuracy across decision thresholds; filled circles mark the maximin operating point $\max_\theta \min(D_\theta, R_\theta)$ reported in Table 3.

F Error Specification Examples

We provide two representative error specifications generated by Claude Sonnet 4.5 (Section 4). Each specification contains a clinical definition, medical patterns, and contrastive text patterns that distinguish significant errors from harmless variations.

Error Specification: Location – Omission

Definition: Omission of anatomical location information present in the reference report, including missing specific anatomical sites, laterality (left/right), spatial relationships, or regional descriptors.

Medical Patterns:

- Missing laterality specification (left/right, bilateral)

- Missing specific anatomical region or lobe identification

- Missing spatial descriptors (upper/lower, anterior/posterior)

Discrimination Text Patterns (significant):

- "left upper lobe nodule" → "pulmonary nodule" (missing critical laterality and

---

lobe)

- "bilateral pleural effusions" → "pleural effusion" (missing bilateral nature)

- "fracture of L3 vertebral body" → "lumbar fracture" (missing specific vertebral level)

Robustness Text Patterns (insignificant):

- "hepatic lesion in segment 7" → "right hepatic lobe lesion" (alternative valid descriptor)

- "distal esophagus" → "lower esophagus" (synonymous location terms)

- "left lung base" → "left lower lung" (equivalent regional description)

Error Specification: Description – Fabrication

Definition: Adding findings, observations, or anatomical descriptions in TGT that do not exist in REF, including introducing new pathological findings, normal structures not mentioned, or additional descriptive details.

Medical Patterns:

- Adding new pathological findings not present in REF (e.g. pleural effusion, nodules)

- Adding quantitative details or measurements that do not exist in REF

- Introducing temporal or comparative information not in REF

Discrimination Text Patterns (significant):

- REF: "clear lungs" → TGT adds "bilateral pleural effusions"

- REF: "normal heart" → TGT adds "cardiomegaly"

- REF: "opacity present" → TGT adds "large 5cm mass"

Robustness Text Patterns (insignificant):

- REF: "no acute findings" → TGT: "heart, lungs, and mediastinum show no acute findings"

- REF: "unremarkable" → TGT lists "bones intact, soft tissues normal"

- REF gives findings → TGT adds "adequate inspiration" as contextual information

---

G Prompt Templates

We provide the full prompt templates used for inference (Section 3) and data synthesis (Section 4). In all templates, {REF} and {TGT} are replaced with the ground-truth and target reports, respectively.

One-Pass Evaluation Prompt

SYSTEM:
You are a clinical evaluation agent for chest X-ray reports. You will be given: 1) a ground-truth report written by professional radiologists, and 2) a target report to be evaluated.
Your task is to:

- Identify all clinically significant and insignificant errors in the target report.

- Classify each error into one of the predefined error categories.

- Determine the error type (Omission / Fabrication / Inaccuracy) when applicable.

- Provide a concise explanation of the errors and their classifications.

Follow all definitions and constraints provided in subsequent instructions.

USER:
You must evaluate the target report against the ground-truth report and produce a structured JSON output.
Your output must be a JSON object with the following structure:

- "critical": a dictionary mapping error spans to error aspects for critical errors

- "significant": a dictionary mapping error spans to error aspects for significant errors

- "insignificant": a dictionary mapping error spans to error aspects for insignificant errors

- "explanation": a concise explanation of the errors identified and the rationale for the categorization

Definition of significance:

- **Critical**: Refer to internal inconsistencies or logical contradictions, such as describing the presence of a structure previously stated to be absent, that can severely undermine clinician trust in the report and are considered critical failures.

- **Significant**: Errors that meaningfully alter, mislead, or distort clinical decision-making.

- **Insignificant**: Errors that represent stylistic variation, minor wording changes, or clinically harmless deviations.

Error Aspects:
Below are the 12 error categories and their descriptions:
{error_aspect_info}
Every error must be assigned exactly one of these aspects.
Error Types:
For the "Comparison/Progression", "Description", "Location", "Severity" aspects, you must further specify the error type using one of:
{error_type_info}
For all other error aspects, you must NOT include an error type; only the aspect label should be provided.
Example:

- "rib fractures": "Location - Omission"

- "no pneumothorax": "Negation" (no error type needed)

If no errors are identified, the "significant" and "insignificant" fields should be empty dictionaries.

Reports to evaluate:
Ground-Truth Report: {REF}
Target Report: {TGT}

Please output only a single valid JSON object.
IMPORTANT:

- Do NOT wrap the JSON in Markdown code fences.

- Do NOT include any language labels such as "json" before the JSON.

- The output must start directly with {{ and end with }}.

- Do NOT include any extra text, comments, or explanations outside the JSON.

Two-Pass: Pass 1 (Span Detection)

SYSTEM:
You are a clinical evaluator for chest X-ray reports. Given a ground-truth report (REF) and a target report (TGT), identify all differences.
For each difference, output a JSON object with:

- "span": the exact text span that changed (from TGT for Fabrication/Inaccuracy/Style; from REF for Omission)

- "aspect": one of the 20 error aspect codes

Valid aspect codes: Location - Omission, Location - Fabrication, Location - Inaccuracy, Severity - Omission, Severity - Fabrication, Severity - Inaccuracy, Description - Omission, Description - Fabrication, Description - Inaccuracy, Comparison/Progression - Omission, Comparison/Progression - Fabrication, Comparison/Progression - Inaccuracy, Negation, Modality, Size/Distance, Contradiction, Uncertainty, Terminology, Noise, Stylistic Variation
Output a JSON array. If no differences, output []. Do NOT wrap in markdown. Start directly with [and end with].

USER:
Ground-Truth Report:
{REF}
Target Report:
{TGT}
Identify all differences and output the JSON array of {span, aspect} objects.

Two-Pass: Pass 2 (Severity Judgment)

SYSTEM:
You are a clinical evaluator for chest X-ray reports. You will be given a REF/TGT report pair, a specific error span, its aspect, and judgment criteria. Determine whether the error is SIGNIFICANT or INSIGNIFICANT.

Output a single JSON object: {"severity":
"significant"/"insignificant"/"critical", "ex-
planation": "..."}
Do NOT wrap in markdown. Start with {
and end with }.

USER:
Ground-Truth Report:
{REF}
Target Report:
{TGT}

Identified Error Span: "{span}"
Error Aspect: {aspect}
Error Type: {etype_label}

Judgment Criteria for [{aspect}]:
{criteria}

Is this error SIGNIFICANT or INSIGNIFI-
CANT? Output only the JSON.

- Keep the rest of the report unchanged

- Maintain medical plausibility and report
  structure

- Preserve the overall report length (±20%)

- Ensure the severity matches the specified
  level

Output ONLY the modified target report
text, without any explanations or format-
ting.

Error Injection Prompt (Data Synthesis)

SYSTEM:
You are a medical imaging report error gen-
eration system specialized in radiology re-
ports.

USER:
Error Type Definition:
Error Category: {error_type} ({er-
ror_category_name})
Error Aspect: {error_aspect}
{error_definition}

Reference Medical Context:
The following patterns show how this error
type manifests in real medical reports:
{medical_patterns}

Severity Level: {severity_description}
Example Text Patterns:
{selected_text_patterns}

Task:
{severity_instruction}
Reference Report: {REF}
Instructions:
- Introduce the specified error type into the
  reference report

- Follow the text patterns shown above as
  guidance

Type	Aspect	Description	Significant Example	Insignificant Example
O / F / E	Location	Errors in the precise anatomical site of a finding (e.g., laterality, lobe, region).	**REF**: *left-sided rib fractures* **TGT**: *right rib fractures*	**REF**: *left retrocardiac opacity* **TGT**: *opacity behind the heart on the left side*
O / F / E	Severity	Errors in describing the extent or clinical seriousness of a finding.	**REF**: *Heart is mildly enlarged* **TGT**: *Severely enlarged heart*	**REF**: *Severe cardiomegaly* **TGT**: *Moderate-to-severe cardiomegaly*
O / F / E	Description	Errors in morphological characteristics such as shape, margins, or appearance.	**REF**: *irregular mass with spiculated margins* **TGT**: *round, smooth mass*	**REF**: *patchy ill-defined opacities* **TGT**: *faint and poorly marginated opacities*
O / F / E	Comp./Prog.	Errors in describing interval changes compared to prior imaging.	**REF**: *Pulmonary edema has improved* **TGT**: *Pulmonary edema has worsened*	**REF**: *No interval change in pleural effusion* **TGT**: *Pleural effusion is essentially unchanged*
S	Negation	Incorrect presence or absence of a finding.	**REF**: *No evidence of pneumothorax* **TGT**: *Pneumothorax is present*	**REF**: *No pleural effusion is seen* **TGT**: *There is no definite pleural effusion*
S	Modality	Conflicts with the imaging modality.	**REF**: *Refer to prior CT torso for details* **TGT**: *Refer to prior abdominal ultrasound*	**REF**: *Consider chest CT for further evaluation* **TGT**: *CT can be considered for further assessment*
S	Size/Distance	Errors in quantitative measurements.	**REF**: *3-cm mass in the lingula* **TGT**: *8-cm mass in the lingula*	**REF**: *ET tube within 1 cm of the carina* **TGT**: *ET tube within 0.9 cm of the carina*
S	Contradiction	Internal logical inconsistencies within the same report.	**REF**: *The lungs are clear.* **TGT**: *The lungs are clear. There is consolidation in the right base*	**REF**: *No evidence of larger pleural effusions* **TGT**: *No evidence of larger pleural effusions. Minimal effusions may exist*
S	Uncertainty	Incorrect use of hedging terms conveying diagnostic uncertainty.	**REF**: *Whether this is pneumonia is radiographically indeterminate* **TGT**: *Pneumonia exists*	**REF**: *A possible infiltrate is suggested* **TGT**: *An infiltrate is likely present*
S	Terminology	Inaccurate or unclear medical terminology.	**REF**: *A cavitary lesion, suggesting tuberculosis* **TGT**: *A hole, suggesting infection*	**REF**: *A 3-cm mass* **TGT**: *A 3-cm lesion*
S	Noise	Grammatical mistakes, typographical errors, or other linguistic noise.	**REF**: *3-cm mass in the lingula has grown* **TGT**: *3-cm lingula margins has been growing irregularly*	**REF**: *subtle opacity may represent atelectasis* **TGT**: *subtble opaciti may represent atelectasi*
S	Stylistic Var.	Variations in phrasing that do not alter clinical meaning.	**REF**: *Bilateral left greater than right pleural effusion* **TGT**: *Fluid accumulation on both sides of the chest, more on the right*	**REF**: *lung... pulmonary edema... pleural effusions* **TGT**: *pleural effusions... lung... pulmonary edema*

Table 6: Descriptions and examples of the 20 error categories in ReEvalMed (Li et al., 2025). The first four aspects combine with three error types (Omission (O), Fabrication (F), and Inaccuracy (E)), yielding $4 \times 3 = 12$ categories. The remaining eight aspects apply to Inaccuracy Only (S), yielding 8 categories. Each category appears in both the Discrimination and Robustness test sets. Examples are shown as REF–TGT pairs; significant examples represent clinically meaningful errors, while insignificant examples represent harmless variations.

Case 1	Severity Mislabel		*Significant / Noise*

REF: ... There is no intraperitoneal free air. The lungs are clear without effusion or pneumothorax. ... IMPRESSION: Normal chest.

TGT: ... Severe motion artifact and noise significantly limit evaluation; intraperitoneal free air cannot be excluded. ... Recommend repeat imaging to exclude free air.

Error Span: "no intraperitoneal free air" → "cannot be excluded"

Clinician: Retake imaging only; no serious clinical consequence. Label should be *insignificant*.

Case 2	Severity Mislabel		*Significant / Noise*

REF: ... Frontal and lateral radiographs of the chest demonstrate normal heart size, mediastinal and hilar contours. Clear lungs. No pneumothorax or pleural effusion. IMPRESSION: Normal chest radiograph.

TGT: ... Severe motion artifact and excessive noise degrade image quality, limiting diagnostic evaluation. ... Pneumothorax or pleural effusion cannot be excluded. IMPRESSION: Nondiagnostic chest radiograph ... Recommend repeat imaging ...

Error Span: "normal heart size ... Clear lungs" → "Severe motion artifact ... cannot be reliably assessed"

Clinician: Same pattern as Case 1; normal study changed to nondiagnostic with repeat imaging recommendation. No actual pathology introduced. Label should be *insignificant*.

Case 3	Injection Failure		*Significant / Location-Omission*

REF: CHEST ON __ HISTORY: Pneumonitis. REFERENCE EXAM: __. Compared to the prior exam, there is no significant interval change.

TGT: CHEST ON __ HISTORY: Pneumonitis. REFERENCE EXAM: __. Compared to the prior exam, there is no significant interval change in the pneumonitis.

Error Span: *null* → "in the pneumonitis"

Clinician: Appears to critique the REF rather than inject an error into the TGT; the added location specificity is arguably an improvement rather than an omission.

Case 4	Injection Failure		*Significant / Location-Omission*

REF: HISTORY: Hickman catheter placement. FINDINGS: The catheter tip lies at the level of the mid portion of the SVC. No evidence of acute pneumonia or vascular congestion.

TGT: *(identical to REF)*

Error Span: *null* → *null*

Clinician: Error injection failed entirely; REF and TGT are identical. The model's explanation reveals an aborted attempt: "*This is actually appropriate positioning. Let me generate a proper SEVERE omission error.*"

Case 5	Aspect Mismatch		*Insignificant / Negation*

REF: ... IMPRESSION: In comparison with the study of __

TGT: ... IMPRESSION: Compared with the study of __

Error Span: "In comparison with" → "Compared with"

Clinician: Purely stylistic; the model failed to inject the assigned *Negation* error.

Case 6	Aspect Mismatch		*Insignificant / Contradiction*

REF: ... There is no large pleural effusion or pneumothorax. ...

TGT: ... No large pleural effusion or pneumothorax is identified. ...

Error Span: "There is no large pleural effusion or pneumothorax." → "No large pleural effusion or pneumothorax is identified."

Clinician: Purely stylistic; the model failed to inject the assigned *Contradiction* error.

Case 7	Aspect Mismatch		*Insignificant / Size-Distance*

REF: ... IMPRESSION: AP and lateral chest compared to __: Normal heart, lungs, hila, mediastinum, and pleural surfaces.

TGT: ... IMPRESSION: AP and lateral chest compared to __: Normal heart size, lungs, hila, mediastinum, and pleural surfaces.

Error Span: "Normal heart" → "Normal heart size"

Clinician: Purely stylistic; the model failed to inject the assigned *Size/Distance* error.

Table 7: Representative cases from human validation of synthesised data. Cases are categorised by failure type: Severity Mislabel (severity label disagrees with clinical judgement), Injection Failure (error injection produces no meaningful change), and Aspect Mismatch (injected change is purely stylistic, deviating from the assigned error type).